

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: McGRAW-EDISON

Report Number: P227548

Luminaire Tested: **ISS-AF-350-LED-E1-T2-8030-ULG**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P227548  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29758)-DOWNLIGHT AND  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: MCGRAW-EDISON  
Catalog Number: ISS-AF-350-LED-E1-T2-8030-ULG  
Description: IMPACT ELITE LED QUATER SPHERE LUMINAIRE WITH UPLIGHT  
LIGHT SQUARE WITH ACCULED OPTICS-TYPE II, WITH UPLIGHT GLOW  
Light Source: (16) 3000K CCT, 80 CRI LEDs and (1) UPLIGHT LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 3333.2 lumens  
Efficiency: N/A  
Efficacy: 90.6 lumens/watt  
Luminous Opening: Rectangular w/ Sides (W: 0.5' x L: 0.5' x H: 0.54')  
IES Classification: Type II - Medium - Non-Cutoff  
BUG Rating: B0 - U5 - G1  
  
Input Watts (W): 36.79  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



REPORT NUMBER: P227548  
 CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 10 foot mounting height. Maximum calculated value = 3.1 fc  
 Type II - Medium - Non-Cutoff

REPORT NUMBER: P227548  
CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

### Luminous Intensity Polar Plot



— Vertical Plane Through 77.5-Deg Lateral    - - - Horizontal Cone Through 72.5-Deg Vertical

REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	316.0	713.1	1029.1
	% Fixture	9.5	21.4	30.9
<b>Street Side</b>	Lumens	1591.0	713.1	2304.1
	% Fixture	47.7	21.4	69.1
<b>Total</b>	Lumens	1907.0	1426.2	3333.2
	% Fixture	57.2	42.8	100.0

**Coefficient of Utilization**

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	23.6	0.7
10°-20°	72.5	2.2
20°-30°	128.7	3.9
30°-40°	204.0	6.1
40°-50°	306.0	9.2
50°-60°	396.5	11.9
60°-70°	450.5	13.5
70°-80°	299.0	9.0
80°-90°	26.1	0.8
90°-100°	4.7	0.1
100°-110°	69.0	2.1
110°-120°	153.0	4.6
120°-130°	223.9	6.7
130°-140°	265.6	8.0
140°-150°	269.3	8.1
150°-160°	231.1	6.9
160°-170°	155.1	4.7
170°-180°	54.3	1.6
0°-90°	1907.0	57.2
0°-180°	3333.2	100.0



REPORT NUMBER: P227548


CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	150.0	4.5			
FM (30°-60°)	771.5	23.1			
FH (60°-80°)	651.2	19.5			G0/660
FVH (80°-90°)	18.3	0.5			G1/100
BL (0°-30°)	74.9	2.2	B0/110		
BM (30°-60°)	135.0	4.0	B0/220		
BH (60°-80°)	98.3	2.9	B0/110		G0/110
BVH (80°-90°)	7.9	0.2			G0/10
UL (90°-100°)	4.7	0.1		U1/10	
UH (100°-180°)	713.1	21.4		U4/1000	

**BUG Rating: B0-U5-G1**

Type II Medium





REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	37.5°	40°	42.5°	45°	47.5°	50°
0°	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6
2.5°	275.8	274.6	273.9	272.6	271.3	270.7	268.8	267.5	269.4	268.8	268.8
5°	296.4	295.1	293.2	291.3	288.7	286.8	284.8	282.9	284.2	282.9	281.6
7.5°	313.1	311.8	309.3	307.3	304.8	302.2	299.6	299.0	297.7	295.8	295.1
10°	322.8	321.5	320.2	318.9	315.1	313.1	309.9	308.0	308.6	306.1	306.1
12.5°	331.8	330.5	329.8	329.8	326.6	324.7	323.4	321.5	322.8	318.9	317.6
15°	340.1	338.8	336.9	338.8	338.2	337.6	336.9	336.3	338.2	334.3	335.0
17.5°	353.6	353.0	349.1	346.6	347.2	349.1	350.4	349.8	349.8	347.8	348.5
20°	374.9	374.9	369.7	365.2	358.1	358.1	358.8	358.1	359.4	360.7	362.6
22.5°	390.9	389.6	387.7	383.9	376.1	369.7	369.7	367.1	369.1	369.7	373.6
25°	411.5	410.2	405.7	405.7	398.0	389.6	388.4	384.5	389.0	380.6	387.1
27.5°	436.6	435.3	429.5	426.9	423.1	412.8	410.2	410.9	415.4	403.1	409.6
30°	468.1	466.8	459.7	452.7	446.2	435.3	434.0	433.4	443.7	429.5	437.9
32.5°	508.0	508.0	500.2	490.6	477.7	462.9	457.8	458.4	472.6	457.2	471.3
35°	568.4	560.7	546.5	531.7	518.2	500.9	493.8	492.5	505.4	489.9	506.0
37.5°	607.0	601.8	589.0	578.0	563.2	546.5	541.4	543.3	554.2	531.7	554.9
40°	641.7	641.0	632.7	625.6	610.8	594.1	600.5	626.3	655.2	611.5	612.1
42.5°	664.8	666.1	665.5	666.1	657.8	640.4	651.3	687.3	736.8	711.1	687.3
45°	668.7	673.2	675.1	688.0	696.3	686.1	691.8	729.8	828.8	868.7	761.3
47.5°	678.3	682.8	679.0	694.4	733.0	732.3	755.5	769.6	783.1	789.6	870.6
50°	691.2	699.6	695.7	708.6	740.1	758.1	778.0	796.0	785.1	744.6	766.4
52.5°	691.8	701.5	722.7	735.6	766.4	762.6	776.1	766.4	783.1	741.4	762.6
55°	635.3	637.2	698.9	763.9	817.9	806.9	798.6	776.7	797.9	745.9	772.9
57.5°	545.9	552.3	616.6	725.9	841.7	851.3	848.7	846.8	863.5	794.1	823.7
60°	447.5	455.2	516.3	644.9	792.1	817.2	851.9	873.2	916.2	888.6	937.5
62.5°	279.1	284.8	352.4	513.1	698.9	748.4	799.2	824.3	886.7	899.5	982.5
65°	133.1	135.0	161.4	279.1	508.0	601.2	676.4	729.8	806.3	864.2	976.0
67.5°	103.5	104.2	113.8	148.5	260.4	322.8	408.3	479.0	560.7	718.8	857.7
70°	82.9	82.9	90.7	109.3	161.4	169.7	191.6	215.4	250.1	377.4	489.9
72.5°	69.4	69.4	74.6	86.2	119.6	121.5	120.2	118.3	118.3	149.2	190.3
75°	58.5	57.9	61.1	68.8	88.7	91.3	90.0	85.5	80.4	80.4	90.7
77.5°	47.6	47.6	50.2	54.0	64.3	65.6	65.6	61.7	57.2	57.9	62.4
80°	37.3	37.3	39.2	41.8	45.0	44.4	44.4	40.5	37.3	36.6	39.2
82.5°	27.0	27.6	32.1	30.2	28.9	27.0	27.0	26.4	23.8	21.9	23.1
85°	8.4	9.0	15.4	18.0	14.8	12.2	11.6	9.6	10.3	8.4	9.6
87.5°	0.0	0.0	0.0	0.0	0.6	0.0	0.0	0.0	0.6	0.0	0.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
97.5°	2.0	2.0	2.0	3.0	4.0	5.2	6.5	7.8	9.0	10.0	11.0
100°	8.0	8.0	10.0	14.0	22.0	24.0	26.0	28.0	30.0	30.5	31.0
102.5°	28.0	28.0	32.0	38.0	45.0	46.2	47.5	48.8	50.0	50.2	50.5
105°	54.0	54.0	56.0	61.0	66.0	67.0	68.0	69.0	70.0	70.2	70.5
107.5°	78.0	77.0	80.0	84.0	88.0	88.8	89.5	90.2	91.0	91.5	92.0
110°	101.0	102.0	103.0	106.0	110.0	110.5	111.0	111.5	112.0	112.5	113.0



REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**CANDELA DISTRIBUTION (continued):**

	0°	5°	15°	25°	35°	37.5°	40°	42.5°	45°	47.5°	50°
112.5°	124.0	124.0	126.0	129.0	132.0	132.5	133.0	133.5	134.0	134.5	135.0
115°	146.0	147.0	149.0	151.0	154.0	154.5	155.0	155.5	156.0	156.5	157.0
117.5°	169.0	170.0	172.0	174.0	177.0	177.5	178.0	178.5	179.0	179.2	179.5
120°	193.0	195.0	196.0	198.0	201.0	201.2	201.5	201.8	202.0	202.5	203.0
122.5°	219.0	220.0	221.0	223.0	226.0	226.2	226.5	226.8	227.0	227.2	227.5
125°	244.0	246.0	247.0	248.0	251.0	251.2	251.5	251.8	252.0	252.2	252.5
127.5°	267.0	269.0	270.0	272.0	274.0	274.5	275.0	275.5	276.0	276.5	277.0
130°	290.0	292.0	293.0	294.0	298.0	298.2	298.5	298.8	299.0	299.5	300.0
132.5°	313.0	314.0	317.0	318.0	321.0	321.2	321.5	321.8	322.0	322.8	323.5
135°	336.0	337.0	339.0	341.0	345.0	345.0	345.0	345.0	345.0	345.8	346.5
137.5°	359.0	360.0	363.0	364.0	367.0	367.0	367.0	367.0	367.0	367.5	368.0
140°	382.0	383.0	385.0	386.0	388.0	388.2	388.5	388.8	389.0	389.2	389.5
142.5°	404.0	406.0	408.0	407.0	410.0	410.0	410.0	410.0	410.0	410.5	411.0
145°	425.0	426.0	428.0	428.0	431.0	431.2	431.5	431.8	432.0	432.5	433.0
147.5°	444.0	444.0	447.0	448.0	452.0	452.2	452.5	452.8	453.0	453.2	453.5
150°	461.0	462.0	464.0	465.0	469.0	469.2	469.5	469.8	470.0	470.2	470.5
152.5°	479.0	480.0	483.0	482.0	485.0	485.2	485.5	485.8	486.0	486.2	486.5
155°	499.0	500.0	502.0	501.0	503.0	503.0	503.0	503.0	503.0	503.2	503.5
157.5°	513.0	515.0	517.0	516.0	519.0	519.0	519.0	519.0	519.0	519.0	519.0
160°	525.0	527.0	529.0	529.0	532.0	532.0	532.0	532.0	532.0	532.0	532.0
162.5°	535.0	536.0	539.0	538.0	541.0	541.0	541.0	541.0	541.0	541.2	541.5
165°	546.0	547.0	549.0	548.0	552.0	552.0	552.0	552.0	552.0	552.2	552.5
167.5°	555.0	556.0	559.0	558.0	561.0	560.8	560.5	560.2	560.0	560.0	560.0
170°	562.0	563.0	566.0	565.0	567.0	566.8	566.5	566.2	566.0	565.8	565.5
172.5°	565.0	566.0	569.0	567.0	569.0	568.8	568.5	568.2	568.0	568.2	568.5
175°	567.0	569.0	570.0	569.0	572.0	572.0	572.0	572.0	572.0	572.2	572.5
177.5°	572.0	573.0	575.0	574.0	578.0	577.8	577.5	577.2	577.0	577.0	577.0
180°	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0





REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**CANDELA DISTRIBUTION (continued):**

	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77°
0°	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6
2.5°	265.5	266.8	264.3	264.3	261.0	263.0	259.8	260.4	257.2	258.5	258.5
5°	278.4	279.1	275.8	274.6	271.3	271.3	268.1	268.1	263.6	264.9	263.6
7.5°	290.6	290.6	287.4	284.8	281.6	280.3	276.5	274.6	270.7	270.0	268.1
10°	300.9	300.9	296.4	293.8	290.0	288.1	282.9	281.0	276.5	273.3	271.3
12.5°	313.8	312.5	307.3	304.8	298.3	297.7	290.0	288.7	282.3	280.3	277.1
15°	329.2	330.5	322.1	321.5	312.5	311.8	301.6	300.9	291.3	290.6	286.1
17.5°	345.9	348.5	341.4	340.8	329.8	329.8	317.6	317.0	304.1	303.5	297.7
20°	360.7	363.9	359.4	360.7	351.1	351.7	338.2	338.2	320.2	318.9	313.8
22.5°	374.2	380.6	376.8	383.9	374.2	378.7	360.7	363.9	342.7	340.1	332.4
25°	387.7	396.1	394.8	406.4	399.3	407.0	388.4	394.8	367.1	369.1	358.8
27.5°	401.2	412.1	410.9	427.6	425.0	440.4	424.4	431.4	401.2	403.1	391.6
30°	423.7	435.9	431.4	448.8	448.8	473.9	461.7	472.6	439.2	443.0	429.5
32.5°	453.9	468.1	454.6	477.1	475.8	508.6	498.9	517.6	484.8	489.9	473.2
35°	486.7	509.2	487.4	512.5	508.6	542.7	536.2	566.5	531.7	537.5	520.8
37.5°	529.8	556.8	527.9	549.7	532.4	571.6	567.7	608.9	573.5	588.3	568.4
40°	580.6	601.8	565.8	584.5	555.5	596.0	589.6	646.2	613.4	637.2	619.2
42.5°	627.5	642.3	594.8	617.9	583.2	624.3	612.8	680.9	652.6	689.3	669.3
45°	670.0	686.7	623.7	649.4	610.8	655.8	635.9	714.3	695.1	750.4	730.4
47.5°	730.4	706.0	650.0	683.5	640.4	689.9	663.6	753.6	746.5	824.9	801.8
50°	710.5	726.6	671.9	706.6	667.4	727.8	698.9	800.5	802.4	906.0	892.4
52.5°	712.4	739.4	688.6	736.8	698.9	780.6	750.4	857.1	866.1	984.4	965.7
55°	724.0	763.9	713.7	778.6	743.3	839.1	817.9	918.2	933.6	1058.3	1047.4
57.5°	752.9	808.2	756.8	841.7	805.0	906.0	886.7	981.2	1002.4	1132.3	1129.1
60°	864.2	929.7	839.7	933.6	884.7	981.8	956.1	1047.4	1068.6	1203.0	1211.4
62.5°	988.3	1102.1	1048.7	1146.4	1017.2	1115.6	1039.7	1129.1	1130.3	1278.9	1305.2
65°	1020.4	1195.3	1240.9	1422.9	1355.4	1456.3	1253.8	1313.6	1236.4	1417.1	1455.1
67.5°	1008.2	1222.3	1349.0	1554.1	1630.6	1806.8	1772.7	1752.1	1573.4	1703.2	1748.9
70°	740.1	967.0	1276.9	1485.3	1705.8	1821.5	2004.8	2023.4	2015.7	1997.7	2027.9
72.5°	336.9	528.5	864.2	1102.1	1466.0	1543.8	1809.3	1804.2	2076.8	2009.3	2056.9
75°	132.5	203.8	411.5	615.3	1014.0	1109.8	1410.7	1336.1	1676.2	1577.2	1678.8
77.5°	72.7	91.3	154.3	264.3	553.6	604.4	863.5	738.8	1039.7	868.0	902.1
80°	43.7	54.7	70.7	100.3	235.3	248.8	368.4	297.1	425.0	322.8	313.1
82.5°	23.8	29.6	35.4	49.5	87.4	97.1	127.3	114.4	136.3	116.4	113.8
85°	9.6	12.9	13.5	19.9	28.9	33.4	40.5	43.7	53.4	48.9	47.6
87.5°	0.0	0.6	0.0	1.3	0.0	1.3	0.0	1.9	1.9	3.2	3.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
97.5°	12.0	13.0	11.5	10.0	8.5	7.0	6.5	6.0	5.5	5.0	4.8
100°	31.5	32.0	31.5	31.0	30.5	30.0	29.2	28.5	27.8	27.0	26.8
102.5°	50.8	51.0	50.8	50.5	50.2	50.0	49.5	49.0	48.5	48.0	48.2
105°	70.8	71.0	71.0	71.0	71.0	71.0	70.5	70.0	69.5	69.0	69.4
107.5°	92.5	93.0	92.8	92.5	92.2	92.0	91.8	91.5	91.2	91.0	91.2
110°	113.5	114.0	114.0	114.0	114.0	114.0	113.8	113.5	113.2	113.0	113.2



REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**CANDELA DISTRIBUTION (continued):**

	52.5°	55°	57.5°	60°	62.5°	65°	67.5°	70°	72.5°	75°	77°
112.5°	135.5	136.0	136.0	136.0	136.0	136.0	135.8	135.5	135.2	135.0	135.4
115°	157.5	158.0	158.0	158.0	158.0	158.0	158.0	158.0	158.0	158.0	158.4
117.5°	179.8	180.0	180.2	180.5	180.8	181.0	180.8	180.5	180.2	180.0	180.4
120°	203.5	204.0	204.0	204.0	204.0	204.0	204.0	204.0	204.0	204.0	204.4
122.5°	227.8	228.0	228.0	228.0	228.0	228.0	228.2	228.5	228.8	229.0	229.8
125°	252.8	253.0	253.2	253.5	253.8	254.0	254.0	254.0	254.0	254.0	254.6
127.5°	277.5	278.0	277.8	277.5	277.2	277.0	277.2	277.5	277.8	278.0	278.6
130°	300.5	301.0	301.0	301.0	301.0	301.0	301.2	301.5	301.8	302.0	302.6
132.5°	324.2	325.0	325.0	325.0	325.0	325.0	325.2	325.5	325.8	326.0	326.6
135°	347.2	348.0	348.0	348.0	348.0	348.0	348.2	348.5	348.8	349.0	349.4
137.5°	368.5	369.0	369.0	369.0	369.0	369.0	369.2	369.5	369.8	370.0	370.8
140°	389.8	390.0	390.0	390.0	390.0	390.0	390.5	391.0	391.5	392.0	392.8
142.5°	411.5	412.0	412.0	412.0	412.0	412.0	412.2	412.5	412.8	413.0	413.6
145°	433.5	434.0	433.8	433.5	433.2	433.0	433.2	433.5	433.8	434.0	434.6
147.5°	453.8	454.0	453.5	453.0	452.5	452.0	452.2	452.5	452.8	453.0	453.6
150°	470.8	471.0	470.5	470.0	469.5	469.0	469.0	469.0	469.0	469.0	469.8
152.5°	486.8	487.0	486.8	486.5	486.2	486.0	486.0	486.0	486.0	486.0	486.6
155°	503.8	504.0	503.8	503.5	503.2	503.0	503.2	503.5	503.8	504.0	504.6
157.5°	519.0	519.0	518.5	518.0	517.5	517.0	517.2	517.5	517.8	518.0	519.0
160°	532.0	532.0	531.5	531.0	530.5	530.0	530.0	530.0	530.0	530.0	530.6
162.5°	541.8	542.0	541.5	541.0	540.5	540.0	539.5	539.0	538.5	538.0	538.4
165°	552.8	553.0	552.2	551.5	550.8	550.0	549.5	549.0	548.5	548.0	548.4
167.5°	560.0	560.0	559.5	559.0	558.5	558.0	558.2	558.5	558.8	559.0	559.8
170°	565.2	565.0	564.8	564.5	564.2	564.0	564.5	565.0	565.5	566.0	567.0
172.5°	568.8	569.0	568.5	568.0	567.5	567.0	567.2	567.5	567.8	568.0	568.6
175°	572.8	573.0	572.2	571.5	570.8	570.0	569.5	569.0	568.5	568.0	568.6
177.5°	577.0	577.0	576.2	575.5	574.8	574.0	574.0	574.0	574.0	574.0	574.6
180°	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0



REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

**CANDELA DISTRIBUTION (continued):**

	77.5°	80°	82.5°	85°	87.5°	90°	95°	100°	102.5°	105°	107.5°
0°	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6
2.5°	256.5	258.5	255.9	255.9	252.7	254.6	252.7	250.8	247.5	248.2	243.7
5°	261.0	262.3	259.1	257.8	255.9	255.3	251.4	247.5	243.0	243.0	237.9
7.5°	265.5	265.5	261.0	261.0	256.5	255.3	249.5	243.0	236.6	236.0	228.3
10°	268.1	267.5	261.7	261.7	255.3	254.6	247.5	237.9	228.9	226.3	215.4
12.5°	273.3	272.6	265.5	264.3	255.9	255.9	245.6	232.8	219.9	215.4	200.0
15°	279.7	280.3	272.0	270.0	260.4	259.8	245.6	226.3	209.0	201.9	183.2
17.5°	290.0	290.6	279.1	277.1	265.5	263.6	246.3	218.6	194.2	186.5	169.7
20°	303.5	301.6	286.1	285.5	270.0	268.1	245.6	207.0	179.4	171.7	156.9
22.5°	320.2	318.3	298.3	296.4	278.4	275.2	245.0	194.8	165.9	157.5	147.9
25°	343.3	340.8	316.3	313.8	291.3	286.1	244.3	182.0	154.3	147.9	142.1
27.5°	372.3	367.1	337.6	335.0	304.8	298.3	241.8	167.2	142.7	138.2	135.7
30°	407.0	402.5	364.6	360.7	322.8	314.4	239.2	153.7	134.4	132.5	130.5
32.5°	448.2	443.7	397.4	392.9	345.9	333.7	234.7	142.7	129.2	129.2	126.7
35°	491.2	487.4	432.7	429.5	371.6	355.6	228.9	133.1	124.7	124.7	122.2
37.5°	529.8	533.0	471.3	468.7	397.4	377.4	222.5	126.7	120.9	119.6	117.0
40°	571.6	579.3	507.3	509.2	424.4	400.6	214.8	121.5	116.4	115.1	114.4
42.5°	614.0	628.8	545.2	552.3	451.4	424.4	209.0	118.3	114.4	111.9	111.2
45°	666.8	688.0	592.2	605.7	482.9	453.3	207.0	114.4	108.7	105.4	103.5
47.5°	732.3	760.6	650.0	665.5	524.7	488.0	210.9	113.2	104.8	100.9	97.1
50°	810.1	837.2	718.8	725.3	571.6	526.0	219.3	115.1	103.5	97.7	91.9
52.5°	892.4	913.0	791.5	784.4	620.5	563.2	228.9	115.7	100.3	94.5	87.4
55°	977.3	988.9	859.0	840.4	664.8	600.5	241.8	115.1	97.7	91.3	82.3
57.5°	1060.3	1064.1	918.8	900.8	708.6	644.9	257.8	113.2	93.9	87.4	77.8
60°	1141.3	1147.7	985.0	968.3	756.1	702.1	281.0	109.9	88.7	84.2	73.9
62.5°	1230.0	1251.2	1064.1	1066.7	821.7	791.5	324.7	106.1	83.6	78.4	68.2
65°	1350.9	1431.9	1194.6	1255.1	947.7	960.0	408.3	95.2	76.5	70.1	63.0
67.5°	1653.7	1742.5	1511.6	1536.1	1242.9	1170.2	461.0	81.0	67.5	63.0	58.5
70°	2033.1	1969.4	1805.5	1657.6	1415.2	1203.0	405.7	68.2	59.8	57.2	54.7
72.5°	2137.2	1909.0	1774.0	1552.1	1308.5	1049.3	310.6	58.5	53.4	52.1	50.2
75°	1878.1	1547.6	1555.4	1233.2	1084.7	799.9	212.2	50.2	46.3	45.7	45.0
77.5°	1201.1	795.4	968.3	609.5	626.3	370.4	103.5	41.8	39.9	39.9	38.6
80°	426.9	264.9	299.6	192.2	174.9	117.7	55.9	33.4	32.1	32.8	32.1
82.5°	128.0	101.6	99.7	77.8	60.4	49.5	30.9	25.7	24.4	25.1	23.8
85°	51.4	39.9	33.4	25.7	21.2	19.3	16.7	17.4	15.4	16.7	14.8
87.5°	3.2	2.6	1.9	2.6	0.0	1.3	3.2	2.6	0.6	2.6	1.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
92.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95°	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
97.5°	4.8	4.5	4.2	4.0	4.0	4.0	4.0	4.5	4.8	5.0	5.5
100°	26.8	26.5	26.2	26.0	25.5	25.0	26.0	26.5	26.8	27.0	27.8
102.5°	48.2	48.5	48.8	49.0	48.5	48.0	49.0	48.5	48.2	48.0	48.5
105°	69.5	70.0	70.5	71.0	70.0	69.0	71.0	70.0	69.5	69.0	69.5
107.5°	91.2	91.5	91.8	92.0	91.5	91.0	92.0	91.5	91.2	91.0	91.2
110°	113.2	113.5	113.8	114.0	113.5	113.0	114.0	113.5	113.2	113.0	113.2



REPORT NUMBER: P227548  
 CATALOG NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

REPORT N  
 CATALOG

**CANDELA DISTRIBUTION (continued):**

**CANDELA**

	77.5°	80°	82.5°	85°	87.5°	90°	95°	100°	102.5°	105°	107.5°	
112.5°	135.5	136.0	136.5	137.0	136.0	135.0	137.0	136.0	135.5	135.0	135.2	0°
115°	158.5	159.0	159.5	160.0	159.5	159.0	160.0	159.0	158.5	158.0	158.0	2.5°
117.5°	180.5	181.0	181.5	182.0	181.0	180.0	182.0	181.0	180.5	180.0	180.2	5°
120°	204.5	205.0	205.5	206.0	205.0	204.0	206.0	205.0	204.5	204.0	204.0	7.5°
122.5°	230.0	231.0	232.0	233.0	232.5	232.0	233.0	231.0	230.0	229.0	228.8	10°
125°	254.8	255.5	256.2	257.0	256.5	256.0	257.0	255.5	254.8	254.0	254.0	12.5°
127.5°	278.8	279.5	280.2	281.0	279.5	278.0	281.0	279.5	278.8	278.0	277.8	15°
130°	302.8	303.5	304.2	305.0	304.0	303.0	305.0	303.5	302.8	302.0	301.8	17.5°
132.5°	326.8	327.5	328.2	329.0	328.0	327.0	329.0	327.5	326.8	326.0	325.8	20°
135°	349.5	350.0	350.5	351.0	350.5	350.0	351.0	350.0	349.5	349.0	348.8	22.5°
137.5°	371.0	372.0	373.0	374.0	373.0	372.0	374.0	372.0	371.0	370.0	369.8	25°
140°	393.0	394.0	395.0	396.0	395.0	394.0	396.0	394.0	393.0	392.0	391.5	27.5°
142.5°	413.8	414.5	415.2	416.0	415.5	415.0	416.0	414.5	413.8	413.0	412.8	30°
145°	434.8	435.5	436.2	437.0	436.0	435.0	437.0	435.5	434.8	434.0	433.8	32.5°
147.5°	453.8	454.5	455.2	456.0	454.5	453.0	456.0	454.5	453.8	453.0	452.8	35°
150°	470.0	471.0	472.0	473.0	471.5	470.0	473.0	471.0	470.0	469.0	469.0	37.5°
152.5°	486.8	487.5	488.2	489.0	487.5	486.0	489.0	487.5	486.8	486.0	486.0	40°
155°	504.8	505.5	506.2	507.0	506.0	505.0	507.0	505.5	504.8	504.0	503.8	42.5°
157.5°	519.2	520.5	521.8	523.0	521.5	520.0	523.0	520.5	519.2	518.0	517.8	45°
160°	530.8	531.5	532.2	533.0	532.0	531.0	533.0	531.5	530.8	530.0	530.0	47.5°
162.5°	538.5	539.0	539.5	540.0	538.5	537.0	540.0	539.0	538.5	538.0	538.5	50°
165°	548.5	549.0	549.5	550.0	549.0	548.0	550.0	549.0	548.5	548.0	548.5	52.5°
167.5°	560.0	561.0	562.0	563.0	562.0	561.0	563.0	561.0	560.0	559.0	558.8	55°
170°	567.2	568.5	569.8	571.0	570.0	569.0	571.0	568.5	567.2	566.0	565.5	57.5°
172.5°	568.8	569.5	570.2	571.0	569.5	568.0	571.0	569.5	568.8	568.0	567.8	60°
175°	568.8	569.5	570.2	571.0	569.5	568.0	571.0	569.5	568.8	568.0	568.5	62.5°
177.5°	574.8	575.5	576.2	577.0	575.5	574.0	577.0	575.5	574.8	574.0	574.0	65°
180°	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	67.5°
												70°
												72.5°
												75°
												77.5°
												80°
												82.5°
												85°
												87.5°
												90°
												92.5°
												95°
												97.5°
												100°
												102.5°
												105°
												107.5°
												110°

NUMBER: P227548  
 NUMBER: ISS-AF-350-LED-E1-T2-8030-ULG

REPORT NUMBER: P  
 CATALOG NUMBER:

**DISTRIBUTION (continued):**

**CANDELA DISTRIBUTION**

110°	112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	135°	145°	110°	
254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	254.6	112.5°	135.5
246.9	242.4	244.3	242.4	243.7	239.8	241.1	237.9	237.9	237.3	234.0	115°	158.0
238.5	234.0	233.4	228.9	229.5	224.4	223.8	218.0	218.0	212.8	203.2	117.5°	180.5
227.0	219.9	219.3	210.3	209.6	202.5	200.0	193.5	192.9	187.1	181.3	120°	204.0
212.2	201.3	199.3	187.7	188.4	180.7	180.0	175.5	175.5	173.0	173.0	122.5°	228.5
195.5	183.2	182.0	173.0	173.6	168.5	169.1	166.5	167.8	169.1	173.6	125°	254.0
180.0	170.4	169.1	163.3	164.0	162.7	164.6	164.6	166.5	169.7	177.5	127.5°	277.5
167.2	158.8	159.5	156.9	159.5	158.8	162.7	162.0	165.9	169.7	179.4	130°	301.5
155.6	151.1	153.0	152.4	155.6	155.6	158.8	159.5	162.7	167.8	178.7	132.5°	325.5
147.9	146.6	148.5	148.5	151.1	151.7	155.0	156.9	158.8	164.0	173.6	135°	348.5
143.4	142.7	144.7	145.3	147.2	147.9	151.1	151.1	154.3	157.5	162.7	137.5°	369.5
137.0	135.7	138.2	138.2	140.8	140.2	144.0	142.7	146.0	147.2	148.5	140°	391.0
132.5	130.5	132.5	131.8	133.7	131.8	133.7	131.8	133.7	133.7	131.8	142.5°	412.5
128.0	126.0	126.7	124.1	126.0	123.5	124.1	121.5	122.8	121.5	122.2	145°	433.5
123.5	120.9	120.9	117.7	117.7	114.4	115.7	113.2	115.7	117.7	117.0	147.5°	452.5
117.0	115.1	115.1	112.5	113.8	112.5	115.1	113.8	114.4	111.9	107.4	150°	469.0
113.2	114.4	113.8	115.7	114.4	112.5	110.6	106.7	106.1	104.8	102.2	152.5°	486.0
107.4	108.7	105.4	108.0	106.1	106.7	105.4	103.5	102.2	100.9	98.4	155°	503.5
99.0	99.0	96.4	100.3	98.4	102.2	100.9	100.9	99.7	97.7	95.8	157.5°	517.5
91.9	92.6	90.0	93.2	91.9	97.1	96.4	98.4	98.4	97.1	91.9	160°	530.0
87.4	86.2	84.2	87.4	86.8	91.3	91.9	95.8	95.2	95.8	91.3	162.5°	539.0
83.6	81.0	79.1	81.0	81.0	84.9	86.2	90.7	91.3	92.6	90.0	165°	549.0
79.1	75.9	74.6	75.9	75.9	79.7	81.7	84.9	86.8	90.7	89.4	167.5°	558.5
75.2	70.7	69.4	70.7	71.4	75.2	77.2	80.4	82.9	88.1	87.4	170°	565.0
70.7	66.9	65.6	67.5	68.2	72.0	73.9	77.2	79.1	84.9	84.9	172.5°	567.5
65.6	62.4	62.4	63.0	64.3	68.2	69.4	73.9	74.6	81.7	82.3	175°	569.0
61.1	59.2	59.2	59.8	61.1	64.3	64.9	69.4	70.1	77.2	79.1	177.5°	574.0
57.2	55.9	55.9	56.6	57.2	59.8	60.4	64.9	66.2	72.7	75.9	180°	576.0
53.4	52.1	51.4	51.4	53.4	55.3	56.6	61.1	61.7	67.5	71.4		
48.9	47.6	47.6	46.9	48.9	50.2	52.7	55.3	56.6	62.4	64.9		
44.4	43.1	43.1	42.4	43.7	46.3	46.9	49.5	50.2	55.3	57.9		
38.6	37.3	37.3	37.3	38.6	39.2	39.9	42.4	43.7	48.2	50.8		
32.1	30.9	31.5	30.9	32.8	30.2	32.1	34.7	36.0	38.6	37.3		
24.4	22.5	23.1	23.1	23.8	21.9	23.1	24.4	25.7	27.6	27.0		
15.4	13.5	14.8	13.5	14.8	12.9	14.1	14.1	15.4	14.1	13.5		
3.2	1.3	3.2	1.3	3.9	0.0	1.9	0.0	1.3	0.6	0.0		
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0		
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0		
6.0	6.5	7.0	8.5	10.0	11.5	13.0	12.0	11.0	9.0	4.0		
28.5	29.2	30.0	30.5	31.0	31.5	32.0	31.5	31.0	30.0	22.0		
49.0	49.5	50.0	50.2	50.5	50.8	51.0	50.8	50.5	50.0	45.0		
70.0	70.5	71.0	71.0	71.0	71.0	71.0	70.8	70.5	70.0	66.0		
91.5	91.8	92.0	92.2	92.5	92.8	93.0	92.5	92.0	91.0	88.0		
113.5	113.8	114.0	114.0	114.0	114.0	114.0	113.5	113.0	112.0	110.0		

'227548  
 ISS-AF-350-LED-E1-T2-8030-ULG

REPORT NUMBER: P227548  
 CATALOG NUMBER: ISS-AF-350

**TION (continued):**

**CANDELA DISTRIBUTION (con**

112.5°	115°	117.5°	120°	122.5°	125°	127.5°	130°	135°	145°		155°	165°
135.8	136.0	136.0	136.0	136.0	136.0	135.5	135.0	134.0	132.0	0°	254.6	254.6
158.0	158.0	158.0	158.0	158.0	158.0	157.5	157.0	156.0	154.0	2.5°	230.8	228.3
180.8	181.0	180.8	180.5	180.2	180.0	179.8	179.5	179.0	177.0	5°	198.0	193.5
204.0	204.0	204.0	204.0	204.0	204.0	203.5	203.0	202.0	201.0	7.5°	178.1	176.8
228.2	228.0	228.0	228.0	228.0	228.0	227.8	227.5	227.0	226.0	10°	174.2	176.2
254.0	254.0	253.8	253.5	253.2	253.0	252.8	252.5	252.0	251.0	12.5°	178.7	182.0
277.2	277.0	277.2	277.5	277.8	278.0	277.5	277.0	276.0	274.0	15°	184.5	190.3
301.2	301.0	301.0	301.0	301.0	301.0	300.5	300.0	299.0	298.0	17.5°	189.0	196.8
325.2	325.0	325.0	325.0	325.0	325.0	324.2	323.5	322.0	321.0	20°	189.7	197.4
348.2	348.0	348.0	348.0	348.0	348.0	347.2	346.5	345.0	345.0	22.5°	183.9	189.0
369.2	369.0	369.0	369.0	369.0	369.0	368.5	368.0	367.0	367.0	25°	169.1	171.7
390.5	390.0	390.0	390.0	390.0	390.0	389.8	389.5	389.0	388.0	27.5°	150.5	149.8
412.2	412.0	412.0	412.0	412.0	412.0	411.5	411.0	410.0	410.0	30°	131.2	129.9
433.2	433.0	433.2	433.5	433.8	434.0	433.5	433.0	432.0	431.0	32.5°	124.1	119.6
452.2	452.0	452.5	453.0	453.5	454.0	453.8	453.5	453.0	452.0	35°	113.2	111.9
469.0	469.0	469.5	470.0	470.5	471.0	470.8	470.5	470.0	469.0	37.5°	109.3	120.2
486.0	486.0	486.2	486.5	486.8	487.0	486.8	486.5	486.0	485.0	40°	104.8	118.3
503.2	503.0	503.2	503.5	503.8	504.0	503.8	503.5	503.0	503.0	42.5°	100.9	108.7
517.2	517.0	517.5	518.0	518.5	519.0	519.0	519.0	519.0	519.0	45°	93.9	97.1
530.0	530.0	530.5	531.0	531.5	532.0	532.0	532.0	532.0	532.0	47.5°	90.7	89.4
539.5	540.0	540.5	541.0	541.5	542.0	541.8	541.5	541.0	541.0	50°	88.1	88.1
549.5	550.0	550.8	551.5	552.2	553.0	552.8	552.5	552.0	552.0	52.5°	86.2	84.9
558.2	558.0	558.5	559.0	559.5	560.0	560.0	560.0	560.0	561.0	55°	83.6	82.3
564.5	564.0	564.2	564.5	564.8	565.0	565.2	565.5	566.0	567.0	57.5°	81.7	78.4
567.2	567.0	567.5	568.0	568.5	569.0	568.8	568.5	568.0	569.0	60°	79.7	76.5
569.5	570.0	570.8	571.5	572.2	573.0	572.8	572.5	572.0	572.0	62.5°	78.4	74.6
574.0	574.0	574.8	575.5	576.2	577.0	577.0	577.0	577.0	578.0	65°	76.5	72.7
576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	576.0	67.5°	73.9	68.8
										70°	68.8	64.3
										72.5°	63.7	58.5
										75°	55.9	51.4
										77.5°	46.9	41.8
										80°	35.4	32.1
										82.5°	25.7	21.9
										85°	11.6	8.4
										87.5°	0.0	0.0
										90°	0.0	0.0
										92.5°	0.0	0.0
										95°	1.0	1.0
										97.5°	3.0	2.0
										100°	14.0	10.0
										102.5°	38.0	32.0
										105°	61.0	56.0
										107.5°	84.0	80.0
										110°	106.0	103.0



REPORT NUMBER: P227548

CATALOG NUMBER: ISS-AF-350-LED-E1-1

0-LED-E1-T2-8030-ULG

**tinued):**

175°	180°
254.6	254.6
227.0	226.3
192.2	191.0
176.8	176.2
176.8	176.8
184.5	184.5
193.5	193.5
200.0	200.6
201.9	202.5
192.2	192.2
173.6	173.6
149.2	151.7
127.3	129.9
113.2	115.1
108.7	109.3
119.6	120.2
117.7	119.0
100.9	101.6
90.7	90.7
86.8	86.2
86.8	85.5
89.4	88.7
85.5	85.5
83.6	83.6
81.7	81.7
81.0	80.4
81.0	79.7
79.7	77.8
75.2	70.1
64.3	59.8
52.1	51.4
40.5	41.2
30.9	30.9
22.5	18.6
6.4	6.4
0.0	0.0
0.0	0.0
0.0	0.0
1.0	1.0
2.0	2.0
8.0	8.0
28.0	28.0
54.0	54.0
77.0	78.0
102.0	101.0

**CANDELA DISTRIBUTION (continued):**

	155°	165°	175°
112.5°	129.0	126.0	124.0
115°	151.0	149.0	147.0
117.5°	174.0	172.0	170.0
120°	198.0	196.0	195.0
122.5°	223.0	221.0	220.0
125°	248.0	247.0	246.0
127.5°	272.0	270.0	269.0
130°	294.0	293.0	292.0
132.5°	318.0	317.0	314.0
135°	341.0	339.0	337.0
137.5°	364.0	363.0	360.0
140°	386.0	385.0	383.0
142.5°	407.0	408.0	406.0
145°	428.0	428.0	426.0
147.5°	448.0	447.0	444.0
150°	465.0	464.0	462.0
152.5°	482.0	483.0	480.0
155°	501.0	502.0	500.0
157.5°	516.0	517.0	515.0
160°	529.0	529.0	527.0
162.5°	538.0	539.0	536.0
165°	548.0	549.0	547.0
167.5°	558.0	559.0	556.0
170°	565.0	566.0	563.0
172.5°	567.0	569.0	566.0
175°	569.0	570.0	569.0
177.5°	574.0	575.0	573.0
180°	576.0	576.0	576.0



12-8030-ULG

180°
124.0
146.0
169.0
193.0
219.0
244.0
267.0
290.0
313.0
336.0
359.0
382.0
404.0
425.0
444.0
461.0
479.0
499.0
513.0
525.0
535.0
546.0
555.0
562.0
565.0
567.0
572.0
576.0

(END OF REPORT)