

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P334059

Luminaire Tested: **S123RDS-S1165D830-4F0-1E-UDD-F**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P334059
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1802-639-25)
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDS-S1165D830-4F0-1E-UDD-F
Description: DEFINE 3 REGRESSED DIRECT LED LUMINAIRE, FLUSH SATIN WHITE DIFFUSER
PENDANT/SURFACE/WALL MOUNT, 1165 LUMENS PER FOOT
Light Source: 3000K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3891.2 lumens
Efficiency: N/A
Efficacy: 94.7 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.07 / 1.22
Luminous Opening: Rectangular (W 0.25' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 41.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P334059

CATALOG NUMBER: S123RDS-S1165D830-4F0-1E-UDD-F

Luminous Intensity Polar Plot





TEST NUMBER: P334059

CATALOG NUMBER: S123RDS-S1165D830-4F0-1E-UDD-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	110	105	101	98	107	103	99	96	99	96	93	95	93	90	91	89	88					86				
2	100	93	86	81	98	91	85	80	87	83	78	84	80	77	81	78	75					73				
3	92	82	75	68	90	81	74	68	78	72	67	75	70	66	73	68	64					62				
4	85	73	65	59	83	72	64	58	70	63	58	67	62	57	65	60	56					54				
5	78	66	57	51	76	65	57	51	63	56	50	61	55	50	59	54	49					47				
6	73	60	51	45	71	59	51	45	57	50	45	55	49	44	54	48	44					42				
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	44	39					37				
8	63	50	42	36	61	49	41	36	48	41	36	47	40	36	46	40	35					34				
9	59	46	38	33	58	45	38	33	44	37	32	43	37	32	42	36	32					30				
10	55	43	35	30	54	42	35	30	41	34	30	40	34	29	39	34	29					28				

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	18540	18540	18540
5°	18611	18355	18459
10°	18506	18123	18063
15°	18307	17699	17512
20°	18033	17169	16770
25°	17752	16574	16043
30°	17380	15887	15018
35°	16998	15199	14079
40°	16645	14387	12916
45°	16183	13588	11866
50°	15672	12678	10690
55°	15152	11639	9595
60°	14676	10525	8389
65°	14054	9322	7188
70°	13278	7827	5803
75°	12144	6159	5461
80°	10823	5455	5021
85°	9139	4829	4483



TEST NUMBER: P334059

CATALOG NUMBER: S123RDS-S1165D830-4F0-1E-UDD-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	161.9	4.2
10°-20°	450.4	11.6
20°-30°	648.5	16.7
30°-40°	730.3	18.8
40°-50°	698.6	18.0
50°-60°	571.9	14.7
60°-70°	385.6	9.9
70°-80°	193.4	5.0
80°-90°	50.6	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1260.9	32.4
0°-40°	1991.2	51.2
0°-60°	3261.7	83.8
0°-90°	3891.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3891.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1722	1722	1722	1722	1722	
5°	1722	1715	1699	1711	1708	163
15°	1643	1627	1588	1581	1572	463
25°	1495	1460	1396	1366	1351	688
35°	1294	1243	1157	1097	1071	810
45°	1063	1000	893	813	780	820
55°	807	739	620	539	511	724
65°	552	475	366	298	282	546
75°	292	225	148	134	131	311
85°	74	43	39	36	36	86
90°	0	0	0	0	0	



TEST NUMBER: P334059

CATALOG NUMBER: S123RDS-S1165D830-4F0-1E-UDD-F

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1722.4	1722.4	1722.4	1722.4	1722.4
2.5°	1729.4	1723.8	1707.0	1722.4	1719.6
5°	1722.4	1715.4	1698.7	1711.2	1708.4
7.5°	1709.8	1702.8	1681.9	1690.3	1686.1
10°	1693.1	1683.3	1658.1	1659.5	1652.6
12.5°	1669.3	1658.1	1626.0	1624.6	1616.2
15°	1642.8	1627.4	1588.3	1581.3	1571.5
17.5°	1610.7	1593.9	1545.0	1531.0	1517.1
20°	1574.3	1552.0	1498.9	1480.7	1464.0
22.5°	1533.8	1507.3	1450.0	1426.3	1410.9
25°	1494.7	1459.8	1395.5	1366.2	1350.8
27.5°	1447.2	1409.5	1339.6	1300.5	1276.8
30°	1398.3	1356.4	1278.2	1230.7	1208.3
32.5°	1349.4	1300.5	1216.7	1163.6	1139.9
35°	1293.6	1243.3	1156.7	1096.6	1071.4
37.5°	1237.7	1183.2	1092.4	1025.3	994.6
40°	1184.6	1123.1	1023.9	951.3	919.2
42.5°	1124.5	1063.1	959.7	878.7	850.7
45°	1063.1	1000.2	892.6	813.0	779.5
47.5°	1003.0	933.1	827.0	740.4	711.0
50°	935.9	870.3	757.1	670.5	638.4
52.5°	875.9	803.2	691.5	600.7	572.7
55°	807.4	739.0	620.2	539.2	511.3
57.5°	746.0	671.9	551.8	475.0	451.2
60°	681.7	604.9	488.9	413.5	389.7
62.5°	617.4	540.6	424.7	354.8	329.7
65°	551.8	475.0	366.0	297.5	282.2
67.5°	486.1	407.9	301.7	250.0	233.3
70°	421.9	346.4	248.7	199.8	184.4
72.5°	357.6	283.6	197.0	159.2	155.1
75°	292.0	224.9	148.1	134.1	131.3
77.5°	231.9	170.4	115.9	107.6	104.8
80°	174.6	117.3	88.0	83.8	81.0
82.5°	120.1	72.6	62.9	58.7	58.7
85°	74.0	43.3	39.1	36.3	36.3
87.5°	33.5	18.2	18.2	16.8	15.4
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)