

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930715

Luminaire Tested: DFN2DS-PN4F0-080DS930-FLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930715
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333812)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-PN4F0-080DS930-FLL
Description: 4 foot, Pentagon Define Geo, with Direct Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6454.8 lumens
Efficiency: N/A
Efficacy: 78.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular (W 3.94' x L: 3.74' x H: 0')
CIE Type: Direct

Input Watts (W): 81.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9971
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930715

CATALOG NUMBER: DFN2DS-PN4F0-080DS930-FLL

Luminous Intensity Polar Plot



TEST NUMBER: P930715

CATALOG NUMBER: DFN2DS-PN4F0-080DS930-FLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	109	104	100	96	106	102	98	95	98	95	92		94	91	89		90
2	99	91	85	79	97	89	83	78	86	81	76		83	78	74		80
3	91	80	72	66	88	79	71	65	76	69	64		73	68	63		71
4	83	71	63	56	81	70	62	56	68	61	55		65	59	54		63
5	77	64	55	49	75	63	55	48	61	53	48		59	52	47		57
6	71	58	49	43	69	57	48	42	55	48	42		53	47	42		52
7	66	52	44	38	64	52	43	38	50	43	37		49	42	37		47
8	61	48	40	34	60	47	39	34	46	39	33		45	38	33		44
9	57	44	36	30	56	43	36	30	42	35	30		41	35	30		40
10	54	41	33	28	53	40	33	28	39	32	27		38	32	27		37

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1852	1852	1852
5°	1859	1832	1843
10°	1848	1814	1823
15°	1825	1790	1788
20°	1793	1755	1753
25°	1760	1711	1711
30°	1719	1672	1657
35°	1680	1624	1600
40°	1632	1576	1546
45°	1584	1529	1491
50°	1532	1479	1427
55°	1478	1422	1369
60°	1417	1353	1304
65°	1353	1285	1226
70°	1271	1203	1146
75°	1155	1108	1080
80°	1026	995	943
85°	837	798	715

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1584 cd/sqm

TEST NUMBER: P930715

CATALOG NUMBER: DFN2DS-PN4F0-080DS930-FLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	238.8	3.7
10°-20°	671.8	10.4
20°-30°	987.3	15.3
30°-40°	1146.7	17.8
40°-50°	1145.3	17.7
50°-60°	998.7	15.5
60°-70°	738.2	11.4
70°-80°	417.7	6.5
80°-90°	110.2	1.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1898.0	29.4
0°-40°	3044.7	47.2
0°-60°	5188.6	80.4
0°-90°	6454.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6454.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2537	2537	2537	2537	2537	
5°	2537	2527	2500	2520	2515	241
15°	2415	2401	2369	2379	2366	680
25°	2186	2166	2125	2130	2125	1006
35°	1886	1862	1822	1808	1795	1178
45°	1535	1517	1481	1454	1444	1184
55°	1161	1146	1117	1088	1076	1038
65°	783	768	744	722	710	774
75°	410	405	393	378	383	437
85°	100	98	95	88	85	117
90°	0	0	0	0	0	

TEST NUMBER: P930715

CATALOG NUMBER: DFN2DS-PN4F0-080DS930-FLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2536.9	2536.9	2536.9	2536.9	2536.9
2.5°	2551.7	2539.5	2512.6	2536.9	2532.3
5°	2536.9	2527.4	2500.5	2519.9	2515.3
7.5°	2519.9	2505.4	2478.5	2498.1	2493.2
10°	2493.2	2476.1	2446.9	2466.3	2459.1
12.5°	2456.5	2442.0	2412.7	2424.9	2420.0
15°	2415.1	2400.6	2368.7	2378.6	2366.4
17.5°	2363.8	2349.3	2317.5	2329.7	2317.5
20°	2307.7	2293.2	2259.0	2266.3	2256.7
22.5°	2251.8	2229.8	2197.9	2197.9	2193.0
25°	2185.7	2166.4	2124.9	2129.6	2124.9
27.5°	2112.5	2095.4	2063.8	2056.6	2044.4
30°	2039.5	2019.8	1983.4	1976.1	1966.3
32.5°	1961.4	1946.9	1907.8	1893.0	1883.2
35°	1885.7	1861.5	1822.3	1807.6	1795.4
37.5°	1800.3	1778.3	1739.3	1722.2	1710.0
40°	1712.6	1692.9	1653.9	1632.1	1622.3
42.5°	1627.2	1607.5	1568.7	1544.1	1529.7
45°	1534.6	1517.4	1480.7	1454.0	1444.3
47.5°	1444.3	1427.1	1388.0	1361.1	1346.6
50°	1349.0	1336.8	1302.6	1268.5	1256.3
52.5°	1256.3	1239.2	1207.7	1180.8	1163.7
55°	1161.3	1146.5	1117.4	1088.1	1075.9
57.5°	1066.1	1054.0	1022.1	992.8	983.0
60°	970.8	961.3	927.1	900.2	892.9
62.5°	878.2	861.1	836.8	812.5	802.6
65°	783.2	768.5	744.1	722.1	709.9
67.5°	685.6	673.2	651.4	634.4	624.5
70°	595.3	585.4	563.5	546.4	536.8
72.5°	502.6	492.8	480.6	463.6	456.3
75°	409.7	405.1	392.7	378.2	383.0
77.5°	326.9	317.0	312.1	304.9	297.6
80°	244.1	241.5	236.6	229.3	224.4
82.5°	165.9	165.9	163.6	153.7	153.7
85°	99.9	97.6	95.3	87.8	85.4
87.5°	44.0	39.1	34.1	26.9	24.4
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930715

CATALOG NUMBER: DFN2DS-PN4F0-080DS930-FLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.42	15.03	13.79	15.35	15.66	12.98	14.59	13.34	14.90	15.22
	3H	15.17	16.63	15.55	16.95	17.32	14.68	16.14	15.06	16.46	16.82
	4H	15.82	17.19	16.22	17.54	17.91	15.32	16.69	15.72	17.04	17.42
	6H	16.29	17.56	16.70	17.92	18.31	15.79	17.06	16.20	17.42	17.81
	8H	16.43	17.64	16.86	18.03	18.43	15.93	17.14	16.35	17.53	17.93
	12H	16.52	17.68	16.95	18.06	18.49	16.01	17.17	16.44	17.55	17.98
4H	2H	13.98	15.35	14.38	15.70	16.08	13.63	15.00	14.03	15.35	15.72
	3H	15.96	17.11	16.37	17.50	17.90	15.55	16.70	15.96	17.10	17.50
	4H	16.74	17.77	17.17	18.19	18.62	16.31	17.35	16.74	17.76	18.20
	6H	17.33	18.24	17.79	18.68	19.13	16.90	17.80	17.35	18.25	18.70
	8H	17.52	18.37	17.98	18.81	19.28	17.08	17.93	17.54	18.37	18.84
	12H	17.65	18.41	18.13	18.89	19.36	17.20	17.96	17.68	18.44	18.91
8H	4H	17.01	17.86	17.47	18.30	18.76	16.63	17.48	17.10	17.92	18.39
	6H	17.72	18.43	18.22	18.91	19.39	17.34	18.04	17.84	18.53	19.01
	8H	17.98	18.61	18.49	19.12	19.61	17.59	18.22	18.10	18.73	19.21
	12H	18.18	18.74	18.69	19.23	19.79	17.77	18.33	18.28	18.82	19.38
12H	4H	17.03	17.79	17.52	18.27	18.74	16.67	17.43	17.15	17.91	18.38
	6H	17.77	18.40	18.28	18.91	19.39	17.40	18.03	17.91	18.54	19.02
	8H	18.08	18.64	18.59	19.13	19.69	17.70	18.26	18.21	18.75	19.31