

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P930930

Luminaire Tested: DFN2DS-SQ3F0-050DS927-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P930930
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-SQ3F0-050DS927-RLL
Description: 3 foot, Square Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3366.0 lumens
Efficiency: N/A
Efficacy: 70.1 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.06' x L: 3.06' x H: 0')
CIE Type: Direct

Input Watts (W): 48
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9789
Total Harmonic Distortion (THDi): 0.074
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P930930

CATALOG NUMBER: DFN2DS-SQ3F0-050DS927-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P930930

CATALOG NUMBER: DFN2DS-SQ3F0-050DS927-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1875	1875	1875
5°	1882	1852	1862
10°	1868	1822	1806
15°	1847	1768	1717
20°	1817	1690	1606
25°	1786	1603	1498
30°	1744	1513	1360
35°	1703	1415	1239
40°	1662	1314	1099
45°	1613	1200	972
50°	1563	1085	848
55°	1512	961	728
60°	1453	831	604
65°	1385	699	550
70°	1305	576	506
75°	1206	525	472
80°	1065	468	430
85°	837	369	369

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1613 cd/sqm

TEST NUMBER: P930930

CATALOG NUMBER: DFN2DS-SQ3F0-050DS927-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	153.4	4.6
10°-20°	421.1	12.5
20°-30°	591.2	17.6
30°-40°	644.4	19.1
40°-50°	592.3	17.6
50°-60°	465.2	13.8
60°-70°	302.8	9.0
70°-80°	155.9	4.6
80°-90°	39.8	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1165.7	34.6
0°-40°	1810.1	53.8
0°-60°	2867.6	85.2
0°-90°	3366.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3366.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1637	1637	1637	1637	1637	
5°	1637	1629	1610	1623	1619	155
15°	1557	1540	1490	1462	1447	439
25°	1413	1366	1268	1207	1185	650
35°	1218	1142	1012	918	886	762
45°	995	896	741	635	600	769
55°	757	641	481	392	364	676
65°	511	391	258	207	203	507
75°	272	169	118	108	107	288
85°	64	33	28	28	28	76
90°	0	0	0	0	0	

TEST NUMBER: P930930

CATALOG NUMBER: DFN2DS-SQ3F0-050DS927-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1636.7	1636.7	1636.7	1636.7	1636.7
2.5°	1644.0	1636.7	1620.4	1635.2	1632.2
5°	1636.7	1629.3	1610.0	1623.3	1618.9
7.5°	1623.3	1614.5	1593.7	1599.6	1592.2
10°	1605.5	1595.2	1565.6	1561.1	1552.2
12.5°	1583.4	1570.1	1530.0	1521.2	1504.8
15°	1556.7	1540.4	1490.1	1462.0	1447.1
17.5°	1525.6	1501.9	1439.6	1407.1	1383.3
20°	1490.1	1460.4	1386.3	1349.4	1316.7
22.5°	1451.6	1417.4	1331.5	1281.2	1259.0
25°	1413.0	1365.6	1267.8	1207.2	1184.8
27.5°	1367.2	1316.7	1208.6	1139.0	1104.9
30°	1318.3	1261.9	1143.4	1067.9	1027.9
32.5°	1270.8	1202.7	1081.3	992.4	955.3
35°	1217.5	1142.0	1011.7	918.3	885.7
37.5°	1165.7	1084.2	946.5	844.2	807.3
40°	1110.9	1022.1	878.2	773.2	734.7
42.5°	1054.6	959.8	810.2	700.5	663.6
45°	995.4	896.1	740.6	635.3	599.8
47.5°	939.1	834.0	674.0	568.7	536.2
50°	876.9	771.7	608.8	506.5	475.5
52.5°	816.1	705.0	546.6	448.8	420.7
55°	756.8	641.3	481.3	392.5	364.4
57.5°	696.2	577.7	423.6	340.7	317.0
60°	633.9	515.4	362.8	287.4	263.7
62.5°	573.2	454.8	311.0	240.0	228.2
65°	511.0	391.0	257.7	207.4	202.9
67.5°	451.8	331.8	207.4	182.2	177.7
70°	389.6	274.0	171.8	157.0	151.0
72.5°	330.3	220.7	143.7	131.9	128.9
75°	272.5	168.8	118.5	108.1	106.7
77.5°	214.8	119.9	93.4	87.4	84.3
80°	161.4	85.9	71.0	65.2	65.2
82.5°	112.5	57.8	48.9	45.9	45.9
85°	63.7	32.6	28.1	28.1	28.1
87.5°	23.8	11.8	11.8	10.4	10.4
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P930930

CATALOG NUMBER: DFN2DS-SQ3F0-050DS927-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.42	14.94	13.78	15.25	15.57	9.38	10.90	9.74	11.22	11.53
	3H	15.18	16.55	15.56	16.88	17.24	10.65	12.01	11.02	12.34	12.70
	4H	15.85	17.13	16.25	17.48	17.86	11.15	12.43	11.55	12.78	13.15
	6H	16.34	17.52	16.75	17.89	18.28	11.53	12.71	11.94	13.08	13.47
	8H	16.51	17.63	16.93	18.02	18.42	11.65	12.78	12.08	13.17	13.57
	12H	16.61	17.69	17.04	18.07	18.50	11.73	12.81	12.16	13.19	13.62
4H	2H	13.52	14.80	13.92	15.15	15.53	10.08	11.36	10.48	11.70	12.08
	3H	15.46	16.52	15.87	16.92	17.32	11.52	12.58	11.93	12.98	13.38
	4H	16.21	17.16	16.64	17.58	18.02	12.12	13.07	12.55	13.49	13.93
	6H	16.80	17.63	17.26	18.07	18.53	12.61	13.44	13.06	13.88	14.34
	8H	17.01	17.79	17.48	18.23	18.70	12.77	13.55	13.23	13.99	14.46
	12H	17.17	17.86	17.65	18.34	18.81	12.89	13.58	13.37	14.06	14.53
8H	4H	16.23	17.01	16.69	17.45	17.92	12.47	13.25	12.94	13.69	14.16
	6H	16.87	17.51	17.36	18.00	18.48	13.06	13.70	13.56	14.19	14.67
	8H	17.12	17.69	17.63	18.20	18.69	13.28	13.86	13.79	14.37	14.85
	12H	17.32	17.83	17.83	18.32	18.89	13.46	13.97	13.97	14.46	15.03
12H	4H	16.21	16.91	16.70	17.39	17.86	12.52	13.21	13.00	13.69	14.16
	6H	16.85	17.43	17.36	17.94	18.42	13.12	13.70	13.64	14.21	14.70
	8H	17.13	17.64	17.64	18.13	18.70	13.40	13.90	13.90	14.40	14.96

END OF REPORT