

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P931570

Luminaire Tested: DFN2DS-TR4F0-110DS830-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P931570
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-TR4F0-110DS830-RLL
Description: 4 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8807.7 lumens
Efficiency: N/A
Efficacy: 74.1 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.96' x L: 3.43' x H: 0')
CIE Type: Direct

Input Watts (W): 118.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9613
Total Harmonic Distortion (THDi): 0.083
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P931570

CATALOG NUMBER: DFN2DS-TR4F0-110DS830-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P931570

CATALOG NUMBER: DFN2DS-TR4F0-110DS830-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3402	3402	3402
5°	3415	3359	3378
10°	3389	3305	3277
15°	3350	3207	3114
20°	3296	3067	2913
25°	3241	2908	2718
30°	3164	2745	2467
35°	3090	2567	2248
40°	3014	2383	1994
45°	2926	2177	1763
50°	2836	1969	1538
55°	2743	1744	1321
60°	2636	1508	1096
65°	2514	1268	998
70°	2368	1044	918
75°	2189	952	857
80°	1932	850	781
85°	1518	671	671

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2926 cd/sqm

TEST NUMBER: P931570

CATALOG NUMBER: DFN2DS-TR4F0-110DS830-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	401.4	4.6
10°-20°	1101.8	12.5
20°-30°	1546.9	17.6
30°-40°	1686.3	19.1
40°-50°	1549.9	17.6
50°-60°	1217.2	13.8
60°-70°	792.3	9.0
70°-80°	407.8	4.6
80°-90°	104.1	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3050.2	34.6
0°-40°	4736.4	53.8
0°-60°	7503.5	85.2
0°-90°	8807.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8807.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	4283	4283	4283	4283	4283	
5°	4283	4263	4213	4248	4236	406
15°	4073	4030	3899	3825	3787	1148
25°	3697	3573	3318	3159	3100	1700
35°	3186	2988	2647	2403	2318	1994
45°	2604	2345	1938	1662	1570	2011
55°	1980	1678	1260	1027	954	1770
65°	1337	1023	674	543	531	1326
75°	713	442	310	283	279	754
85°	166	85	74	74	74	200
90°	0	0	0	0	0	

TEST NUMBER: P931570

CATALOG NUMBER: DFN2DS-TR4F0-110DS830-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	4282.6	4282.6	4282.6	4282.6	4282.6
2.5°	4301.9	4282.6	4239.8	4278.9	4271.1
5°	4282.6	4263.3	4212.7	4247.7	4236.2
7.5°	4247.7	4224.6	4170.3	4185.6	4166.2
10°	4201.2	4174.0	4096.8	4084.8	4061.8
12.5°	4143.2	4108.3	4003.4	3980.3	3937.6
15°	4073.3	4030.5	3898.9	3825.4	3786.7
17.5°	3991.9	3929.8	3767.0	3681.8	3619.7
20°	3898.9	3821.2	3627.5	3530.9	3445.4
22.5°	3798.2	3708.9	3484.1	3352.5	3294.5
25°	3697.4	3573.3	3317.5	3158.8	3100.4
27.5°	3577.4	3445.4	3162.5	2980.3	2891.1
30°	3449.5	3301.9	2991.9	2794.4	2689.6
32.5°	3325.4	3146.8	2829.4	2596.7	2499.7
35°	3185.9	2988.1	2647.3	2403.0	2317.5
37.5°	3050.3	2836.8	2476.6	2208.9	2112.3
40°	2906.7	2674.4	2298.2	2023.0	1922.3
42.5°	2759.5	2511.6	2120.2	1833.1	1736.5
45°	2604.5	2344.6	1938.0	1662.4	1569.6
47.5°	2457.3	2182.2	1763.6	1488.1	1403.0
50°	2294.4	2019.4	1593.0	1325.3	1244.3
52.5°	2135.3	1844.6	1430.1	1174.4	1100.7
55°	1980.3	1678.1	1259.5	1027.2	953.6
57.5°	1821.6	1511.5	1108.5	891.5	829.3
60°	1658.8	1348.8	949.4	752.1	690.0
62.5°	1500.0	1190.0	813.8	627.9	597.0
65°	1337.2	1023.0	674.4	542.8	530.8
67.5°	1182.2	868.1	542.8	476.6	465.1
70°	1019.3	717.1	449.4	410.8	395.2
72.5°	864.3	577.4	375.9	345.0	337.1
75°	713.0	441.6	310.0	282.9	279.2
77.5°	562.1	313.8	244.3	228.6	220.8
80°	422.3	224.9	185.9	170.7	170.7
82.5°	294.4	151.3	127.9	120.1	120.1
85°	166.5	85.2	73.6	73.6	73.6
87.5°	62.1	30.8	30.8	27.1	27.1
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P931570

CATALOG NUMBER: DFN2DS-TR4F0-110DS830-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.49	17.01	15.85	17.32	17.64	11.45	12.97	11.81	13.28	13.60
	3H	17.25	18.62	17.63	18.95	19.31	12.71	14.08	13.09	14.41	14.77
	4H	17.92	19.20	18.32	19.55	19.93	13.22	14.50	13.62	14.85	15.22
	6H	18.41	19.59	18.82	19.96	20.35	13.60	14.78	14.01	15.15	15.54
	8H	18.57	19.70	19.00	20.09	20.49	13.72	14.85	14.15	15.24	15.64
	12H	18.68	19.76	19.11	20.14	20.57	13.80	14.88	14.23	15.26	15.69
4H	2H	15.59	16.87	15.99	17.22	17.60	12.15	13.43	12.54	13.77	14.15
	3H	17.53	18.59	17.94	18.99	19.39	13.59	14.65	14.00	15.05	15.45
	4H	18.28	19.23	18.71	19.65	20.09	14.19	15.14	14.62	15.56	16.00
	6H	18.87	19.70	19.32	20.14	20.60	14.68	15.51	15.13	15.95	16.41
	8H	19.08	19.86	19.55	20.30	20.77	14.84	15.62	15.30	16.06	16.53
	12H	19.24	19.93	19.72	20.41	20.88	14.96	15.65	15.44	16.13	16.60
8H	4H	18.30	19.08	18.76	19.52	19.99	14.54	15.32	15.00	15.76	16.23
	6H	18.94	19.58	19.43	20.07	20.55	15.13	15.77	15.62	16.26	16.74
	8H	19.19	19.76	19.70	20.27	20.76	15.35	15.93	15.86	16.44	16.92
	12H	19.39	19.90	19.90	20.39	20.96	15.53	16.04	16.04	16.53	17.10
12H	4H	18.28	18.98	18.77	19.46	19.93	14.58	15.28	15.07	15.76	16.23
	6H	18.92	19.50	19.43	20.01	20.49	15.19	15.77	15.71	16.28	16.77
	8H	19.20	19.71	19.71	20.20	20.77	15.46	15.97	15.97	16.47	17.03