

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P931450

Luminaire Tested: DFN2DS-TR4F0-040DS850-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P931450
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-TR4F0-040DS850-RLL
Description: 4 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3770.6 lumens
Efficiency: N/A
Efficacy: 98.7 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.96' x L: 3.43' x H: 0')
CIE Type: Direct

Input Watts (W): 38.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9952
Total Harmonic Distortion (THDi): 0.069
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P931450

CATALOG NUMBER: DFN2DS-TR4F0-040DS850-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P931450

CATALOG NUMBER: DFN2DS-TR4F0-040DS850-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1457	1457	1457
5°	1462	1438	1446
10°	1451	1415	1403
15°	1434	1373	1333
20°	1411	1313	1247
25°	1388	1245	1163
30°	1355	1175	1056
35°	1323	1099	962
40°	1291	1020	853
45°	1253	932	755
50°	1214	843	658
55°	1174	747	565
60°	1128	646	469
65°	1076	543	427
70°	1014	447	393
75°	937	407	367
80°	827	364	334
85°	650	287	287

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1253 cd/sqm

TEST NUMBER: P931450

CATALOG NUMBER: DFN2DS-TR4F0-040DS850-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	171.8	4.6
10°-20°	471.7	12.5
20°-30°	662.3	17.6
30°-40°	721.9	19.1
40°-50°	663.5	17.6
50°-60°	521.1	13.8
60°-70°	339.2	9.0
70°-80°	174.6	4.6
80°-90°	44.6	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1305.8	34.6
0°-40°	2027.7	53.8
0°-60°	3212.2	85.2
0°-90°	3770.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3770.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1833	1833	1833	1833	1833	
5°	1833	1825	1804	1818	1814	174
15°	1744	1726	1669	1638	1621	491
25°	1583	1530	1420	1352	1327	728
35°	1364	1279	1133	1029	992	854
45°	1115	1004	830	712	672	861
55°	848	718	539	440	408	758
65°	572	438	289	232	227	568
75°	305	189	133	121	120	323
85°	71	36	32	32	32	86
90°	0	0	0	0	0	

TEST NUMBER: P931450

CATALOG NUMBER: DFN2DS-TR4F0-040DS850-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1833.4	1833.4	1833.4	1833.4	1833.4
2.5°	1841.7	1833.4	1815.1	1831.8	1828.4
5°	1833.4	1825.1	1803.5	1818.4	1813.5
7.5°	1818.4	1808.6	1785.4	1791.8	1783.6
10°	1798.6	1786.9	1753.8	1748.7	1738.9
12.5°	1773.7	1758.8	1713.8	1704.0	1685.7
15°	1743.8	1725.5	1669.2	1637.7	1621.1
17.5°	1709.0	1682.4	1612.6	1576.2	1549.6
20°	1669.2	1635.9	1552.9	1511.6	1475.0
22.5°	1626.0	1587.9	1491.5	1435.2	1410.4
25°	1582.9	1529.8	1420.2	1352.3	1327.3
27.5°	1531.5	1475.0	1353.9	1275.9	1237.6
30°	1476.7	1413.5	1280.8	1196.3	1151.5
32.5°	1423.6	1347.2	1211.2	1111.7	1070.1
35°	1364.0	1279.2	1133.3	1028.7	992.1
37.5°	1305.8	1214.5	1060.2	945.6	904.3
40°	1244.4	1144.9	983.9	866.1	823.0
42.5°	1181.3	1075.2	907.6	784.7	743.4
45°	1115.0	1003.8	829.6	711.8	671.9
47.5°	1052.0	934.2	755.0	637.1	600.6
50°	982.2	864.5	681.9	567.4	532.7
52.5°	914.1	789.7	612.3	502.7	471.2
55°	847.8	718.4	539.2	439.7	408.2
57.5°	779.8	647.1	474.5	381.6	355.1
60°	710.1	577.3	406.4	321.9	295.4
62.5°	642.2	509.5	348.3	268.8	255.6
65°	572.5	437.9	288.7	232.3	227.2
67.5°	506.1	371.6	232.3	204.1	199.1
70°	436.4	307.0	192.4	175.9	169.1
72.5°	370.1	247.2	160.9	147.7	144.4
75°	305.2	189.1	132.7	121.1	119.6
77.5°	240.7	134.3	104.6	97.9	94.5
80°	180.8	96.3	79.5	73.1	73.1
82.5°	126.1	64.8	54.8	51.3	51.3
85°	71.3	36.5	31.5	31.5	31.5
87.5°	26.6	13.2	13.2	11.6	11.6
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P931450

CATALOG NUMBER: DFN2DS-TR4F0-040DS850-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.54	14.06	12.91	14.38	14.69	8.50	10.02	8.87	10.34	10.65
	3H	14.31	15.67	14.68	16.00	16.36	9.77	11.13	10.14	11.46	11.82
	4H	14.97	16.25	15.37	16.60	16.98	10.27	11.55	10.67	11.90	12.28
	6H	15.46	16.64	15.87	17.01	17.40	10.65	11.83	11.06	12.20	12.59
	8H	15.63	16.75	16.05	17.14	17.54	10.77	11.90	11.20	12.29	12.69
	12H	15.73	16.81	16.16	17.19	17.62	10.85	11.93	11.29	12.32	12.74
4H	2H	12.65	13.93	13.04	14.27	14.65	9.20	10.48	9.60	10.83	11.20
	3H	14.58	15.64	14.99	16.04	16.44	10.64	11.70	11.05	12.10	12.50
	4H	15.33	16.28	15.76	16.70	17.14	11.24	12.20	11.67	12.61	13.05
	6H	15.92	16.75	16.38	17.19	17.65	11.73	12.56	12.19	13.00	13.46
	8H	16.13	16.91	16.60	17.36	17.82	11.89	12.67	12.35	13.11	13.58
	12H	16.29	16.98	16.77	17.46	17.93	12.01	12.70	12.49	13.18	13.65
8H	4H	15.35	16.13	15.82	16.57	17.04	11.59	12.37	12.06	12.82	13.28
	6H	15.99	16.63	16.49	17.12	17.60	12.18	12.82	12.68	13.31	13.79
	8H	16.24	16.82	16.75	17.33	17.81	12.40	12.98	12.91	13.49	13.98
	12H	16.44	16.95	16.95	17.45	18.01	12.58	13.09	13.09	13.58	14.15
12H	4H	15.34	16.03	15.82	16.51	16.98	11.64	12.33	12.12	12.81	13.28
	6H	15.97	16.55	16.48	17.06	17.55	12.24	12.82	12.76	13.33	13.82
	8H	16.26	16.77	16.76	17.26	17.82	12.52	13.03	13.03	13.52	14.08