

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P931488

Luminaire Tested: DFN2DS-TR4F0-060DS927-RLL

Issue Date: 11/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P931488
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P333882)
Test Lab: INNOVATION CENTER
Issue Date: 11/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DS-TR4F0-060DS927-RLL
Description: 4 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4039.2 lumens
Efficiency: N/A
Efficacy: 67.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular (W 3.96' x L: 3.43' x H: 0')
CIE Type: Direct

Input Watts (W): 59.6
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9781
Total Harmonic Distortion (THDi): 0.075
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P931488

CATALOG NUMBER: DFN2DS-TR4F0-060DS927-RLL

Luminous Intensity Polar Plot



TEST NUMBER: P931488

CATALOG NUMBER: DFN2DS-TR4F0-060DS927-RLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	98	107	103	100	97	99	96	94		95	93	91		92
2	101	94	87	82	98	92	86	81	88	83	79		85	81	78		82
3	93	83	76	70	90	82	75	69	79	73	68		76	71	67		74
4	86	75	66	60	83	73	66	60	71	64	59		69	63	58		66
5	79	67	59	53	77	66	58	52	64	57	52		62	56	51		60
6	74	61	53	47	72	60	52	46	58	51	46		57	50	46		55
7	68	56	47	42	67	55	47	42	53	46	41		52	46	41		51
8	64	51	43	38	62	51	43	37	49	42	37		48	42	37		47
9	60	47	39	34	59	47	39	34	46	39	34		44	38	34		44
10	56	44	36	31	55	43	36	31	42	36	31		41	35	31		41

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1560	1560	1560
5°	1566	1541	1549
10°	1554	1516	1503
15°	1536	1471	1428
20°	1512	1406	1336
25°	1486	1334	1246
30°	1451	1259	1132
35°	1417	1177	1031
40°	1382	1093	914
45°	1342	999	809
50°	1301	903	705
55°	1258	800	606
60°	1209	692	503
65°	1153	581	458
70°	1086	479	421
75°	1004	436	393
80°	886	390	358
85°	695	307	307

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1342 cd/sqm

TEST NUMBER: P931488

CATALOG NUMBER: DFN2DS-TR4F0-060DS927-RLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	184.1	4.6
10°-20°	505.3	12.5
20°-30°	709.4	17.6
30°-40°	773.3	19.1
40°-50°	710.8	17.6
50°-60°	558.2	13.8
60°-70°	363.3	9.0
70°-80°	187.0	4.6
80°-90°	47.7	1.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1398.8	34.6
0°-40°	2172.1	53.8
0°-60°	3441.1	85.2
0°-90°	4039.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4039.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1964	1964	1964	1964	1964	
5°	1964	1955	1932	1948	1943	186
15°	1868	1848	1788	1754	1736	526
25°	1696	1639	1521	1449	1422	780
35°	1461	1370	1214	1102	1063	914
45°	1194	1075	889	762	720	922
55°	908	770	578	471	437	812
65°	613	469	309	249	244	608
75°	327	202	142	130	128	346
85°	76	39	34	34	34	92
90°	0	0	0	0	0	

TEST NUMBER: P931488

CATALOG NUMBER: DFN2DS-TR4F0-060DS927-RLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1964.0	1964.0	1964.0	1964.0	1964.0
2.5°	1972.9	1964.0	1944.4	1962.3	1958.7
5°	1964.0	1955.1	1931.9	1948.0	1942.7
7.5°	1948.0	1937.4	1912.5	1919.5	1910.6
10°	1926.6	1914.2	1878.8	1873.3	1862.7
12.5°	1900.1	1884.0	1835.9	1825.4	1805.8
15°	1868.0	1848.4	1788.0	1754.3	1736.5
17.5°	1830.7	1802.2	1727.5	1688.5	1660.0
20°	1788.0	1752.4	1663.6	1619.2	1580.0
22.5°	1741.8	1700.9	1597.8	1537.4	1510.8
25°	1695.7	1638.7	1521.4	1448.6	1421.9
27.5°	1640.6	1580.0	1450.3	1366.8	1325.9
30°	1581.9	1514.2	1372.1	1281.5	1233.5
32.5°	1525.0	1443.2	1297.6	1190.9	1146.3
35°	1461.1	1370.4	1214.1	1102.0	1062.8
37.5°	1398.8	1300.9	1135.8	1013.0	968.7
40°	1333.0	1226.5	1053.9	927.7	881.6
42.5°	1265.5	1151.8	972.3	840.6	796.4
45°	1194.4	1075.2	888.8	762.4	719.8
47.5°	1126.9	1000.8	808.8	682.5	643.4
50°	1052.3	926.1	730.5	607.8	570.6
52.5°	979.2	845.9	655.9	538.6	504.8
55°	908.2	769.6	577.6	471.1	437.3
57.5°	835.4	693.2	508.4	408.8	380.3
60°	760.7	618.6	435.4	344.9	316.4
62.5°	687.9	545.8	373.2	288.0	273.8
65°	613.2	469.2	309.3	248.9	243.5
67.5°	542.1	398.1	248.9	218.6	213.3
70°	467.4	328.8	206.1	188.4	181.2
72.5°	396.4	264.8	172.3	158.2	154.6
75°	327.0	202.5	142.2	129.7	128.1
77.5°	257.8	143.9	112.0	104.9	101.3
80°	193.6	103.1	85.2	78.2	78.2
82.5°	135.0	69.4	58.6	55.0	55.0
85°	76.3	39.0	33.7	33.7	33.7
87.5°	28.5	14.2	14.2	12.4	12.4
90°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P931488

CATALOG NUMBER: DFN2DS-TR4F0-060DS927-RLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.78	14.30	13.15	14.62	14.93	8.74	10.26	9.11	10.58	10.89
	3H	14.55	15.91	14.92	16.24	16.60	10.01	11.37	10.38	11.70	12.06
	4H	15.21	16.49	15.61	16.84	17.22	10.51	11.79	10.91	12.14	12.52
	6H	15.70	16.88	16.11	17.25	17.64	10.89	12.07	11.30	12.44	12.83
	8H	15.87	16.99	16.29	17.38	17.78	11.01	12.14	11.44	12.53	12.93
	12H	15.97	17.05	16.40	17.43	17.86	11.09	12.17	11.52	12.55	12.98
4H	2H	12.88	14.17	13.28	14.51	14.89	9.44	10.72	9.84	11.07	11.44
	3H	14.82	15.88	15.23	16.28	16.68	10.88	11.94	11.29	12.34	12.74
	4H	15.57	16.52	16.00	16.94	17.38	11.48	12.44	11.91	12.85	13.29
	6H	16.16	16.99	16.62	17.43	17.89	11.97	12.80	12.42	13.24	13.70
	8H	16.37	17.15	16.84	17.59	18.06	12.13	12.91	12.59	13.35	13.82
	12H	16.53	17.22	17.01	17.70	18.17	12.25	12.94	12.73	13.42	13.89
8H	4H	15.59	16.37	16.05	16.81	17.28	11.83	12.61	12.30	13.05	13.52
	6H	16.23	16.87	16.73	17.36	17.84	12.42	13.06	12.92	13.55	14.03
	8H	16.48	17.06	16.99	17.56	18.05	12.64	13.22	13.15	13.73	14.21
	12H	16.68	17.19	17.19	17.68	18.25	12.82	13.33	13.33	13.82	14.38
12H	4H	15.58	16.27	16.06	16.75	17.22	11.88	12.57	12.36	13.05	13.52
	6H	16.21	16.79	16.72	17.30	17.78	12.48	13.06	13.00	13.57	14.06
	8H	16.49	17.00	17.00	17.50	18.06	12.75	13.26	13.26	13.76	14.32