

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331450-930

Luminaire Tested: **S122DIP-S1005D925U930-4F0-1E-UDD-D**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P331450-930
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-2,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S122DIP-S1005D925U930-4F0-1E-UDD-D
Description: DEFINE 2 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1005 LUMENS PER FOOT, DROP SATIN WHITE DIFFUSER
UPLIGHT 925 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6307.3 lumens
Efficiency: N/A
Efficacy: 94.4 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.32 / 1.42
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.08')
CIE Type: General Diffuse


Input Watts (W): 66.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

Luminous Intensity Polar Plot





TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	106	106	106	106	98	98	98	98	81	81	81	66	66	66	53	53	53	46
1	96	91	86	82	87	83	79	76	69	66	64	56	54	52	44	43	42	36
2	86	78	72	66	79	72	66	61	60	55	52	49	45	43	38	36	34	29
3	79	68	61	54	72	63	56	50	52	47	43	43	39	36	33	31	28	24
4	72	60	52	46	65	55	48	42	46	41	36	38	33	30	30	27	24	20
5	66	53	45	39	60	49	42	36	41	35	31	34	29	26	27	23	21	17
6	60	48	39	33	55	44	37	31	37	31	27	30	26	22	24	21	18	15
7	56	43	35	29	51	40	32	27	33	28	23	27	23	20	22	18	16	13
8	52	39	31	26	47	36	29	24	30	25	21	25	21	17	20	17	14	12
9	48	35	28	23	44	33	26	21	28	22	18	23	19	16	18	15	13	11
10	45	32	25	20	41	30	23	19	25	20	16	21	17	14	17	14	12	10

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	13919	13919	13919
5°	13988	13400	13350
10°	13899	13004	12858
15°	13709	12584	12339
20°	13467	12136	11842
25°	13227	11701	11390
30°	12890	11257	10936
35°	12550	10828	10617
40°	12191	10461	10297
45°	11850	10133	10022
50°	11485	9837	9754
55°	11101	9519	9479
60°	10631	9187	9189
65°	10145	8801	8846
70°	9596	8384	8474
75°	8897	7976	8132
80°	7792	7559	7784
85°	6733	7197	7515



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	81.7	1.3
10°-20°	234.3	3.7
20°-30°	355.0	5.6
30°-40°	432.4	6.9
40°-50°	465.2	7.4
50°-60°	451.7	7.2
60°-70°	394.4	6.3
70°-80°	303.7	4.8
80°-90°	206.3	3.3
90°-100°	174.7	2.8
100°-110°	228.4	3.6
110°-120°	404.2	6.4
120°-130°	593.2	9.4
130°-140°	606.6	9.6
140°-150°	551.8	8.7
150°-160°	441.4	7.0
160°-170°	284.5	4.5
170°-180°	97.9	1.6
0°-30°	670.9	10.6
0°-40°	1103.3	17.5
0°-60°	2020.2	32.0
0°-90°	2924.6	46.4
90°-120°	807.3	12.8
90°-150°	2558.9	40.6
90°-180°	3383.0	53.6
0°-180°	6307.3	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	862	862	862	862	862	
5°	865	861	853	860	860	82
15°	825	827	827	838	837	232
25°	750	759	770	784	788	345
35°	646	667	691	717	727	404
45°	530	564	607	644	658	409
55°	406	452	516	559	577	363
65°	277	339	412	462	480	275
75°	154	224	304	355	374	163
85°	45	123	202	253	272	48
90°	13	94	180	232	250	11
95°	58	95	173	222	238	67
105°	233	280	153	203	222	249
115°	433	462	534	242	187	426
125°	608	620	672	709	724	542
135°	750	763	782	814	824	580
145°	869	869	881	893	896	544
155°	957	951	959	963	958	441
165°	1008	1004	1006	1011	1006	285
175°	1031	1026	1028	1032	1025	98
180°	1029	1029	1029	1029	1029	



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	862.1	862.1	862.1	862.1	862.1	862.1	862.1	862.1	862.1	862.1	862.1
2.5°	867.2	866.5	865.8	865.1	864.5	863.3	861.8	860.2	858.7	857.1	858.3
5°	864.6	863.8	863.0	862.1	861.3	860.1	858.4	856.7	855.1	853.4	855.1
7.5°	856.9	856.3	855.7	855.2	854.7	853.8	852.5	851.2	849.9	848.6	850.6
10°	850.9	850.4	849.8	849.2	848.6	848.0	847.2	846.3	845.5	844.7	846.9
12.5°	840.9	841.0	841.1	841.2	841.3	841.1	840.5	839.8	839.3	838.6	840.9
15°	824.7	825.2	825.7	826.3	826.9	827.1	827.1	827.1	827.1	827.1	829.6
17.5°	803.6	804.9	806.0	807.1	808.3	809.3	810.2	811.1	812.0	812.9	815.5
20°	789.7	791.1	792.5	793.9	795.2	796.5	797.6	798.7	799.8	801.0	804.0
22.5°	774.7	776.2	777.9	779.5	781.1	782.7	784.2	785.8	787.3	788.9	792.0
25°	749.7	751.6	753.6	755.5	757.5	759.7	762.1	764.7	767.2	769.6	773.0
27.5°	719.7	722.8	726.0	729.2	732.4	735.4	738.3	741.3	744.2	747.2	751.4
30°	699.7	703.3	706.9	710.5	714.1	717.8	721.4	725.0	728.6	732.2	736.6
32.5°	677.7	681.8	685.8	689.9	693.9	698.1	702.4	706.6	710.9	715.2	720.3
35°	646.0	650.7	655.4	660.1	664.9	669.8	675.1	680.4	685.7	691.0	697.1
37.5°	611.5	616.9	622.4	627.8	633.2	639.4	646.2	653.1	659.9	666.8	673.5
40°	588.5	594.6	600.7	606.8	612.9	619.7	627.2	634.7	642.2	649.7	657.0
42.5°	566.6	572.6	578.7	584.8	590.9	598.3	606.9	615.6	624.1	632.8	640.6
45°	529.8	537.3	544.8	552.3	559.8	568.3	578.1	587.8	597.5	607.2	615.9
47.5°	493.6	501.7	509.9	518.0	526.2	536.0	547.4	558.7	570.1	581.5	590.5
50°	468.6	477.2	485.8	494.4	503.0	513.6	526.0	538.5	551.0	563.5	573.0
52.5°	444.6	453.6	462.7	471.7	480.8	491.9	505.0	518.2	531.3	544.5	554.2
55°	406.1	416.0	426.1	436.1	446.1	458.3	472.7	487.1	501.6	516.0	526.0
57.5°	368.1	379.4	390.6	401.9	413.2	426.2	440.9	455.6	470.3	485.0	495.8
60°	341.1	353.0	365.0	376.9	388.9	402.8	418.6	434.4	450.2	466.0	476.6
62.5°	317.2	329.5	341.9	354.2	366.6	380.7	396.6	412.4	428.3	444.1	455.3
65°	277.4	291.0	304.6	318.2	331.8	346.8	363.2	379.5	395.9	412.3	423.7
67.5°	240.9	255.1	269.3	283.6	297.7	313.2	330.0	346.8	363.5	380.3	391.8
70°	214.9	229.3	243.8	258.2	272.6	288.5	305.7	322.9	340.1	357.3	369.2
72.5°	190.9	205.8	220.7	235.5	250.5	266.6	284.1	301.5	318.9	336.4	348.1
75°	153.7	169.3	184.7	200.3	215.9	232.5	250.3	268.1	285.8	303.6	315.5
77.5°	117.7	134.0	150.3	166.5	182.8	199.9	218.0	236.0	254.0	272.1	284.1
80°	93.7	110.6	127.6	144.6	161.4	179.0	197.0	215.1	233.1	251.1	262.8
82.5°	73.7	90.4	107.1	123.8	140.6	158.1	176.3	194.6	212.9	231.1	242.8
85°	45.0	62.2	79.4	96.6	113.8	131.3	149.1	166.9	184.7	202.4	214.1
87.5°	24.6	41.6	58.5	75.4	92.3	109.7	127.8	145.9	163.9	181.9	193.4
90°	13.2	31.1	49.1	67.0	85.0	103.5	122.5	141.6	160.7	179.9	191.8
92.5°	26.5	41.3	56.2	71.0	85.9	102.2	119.9	137.7	155.5	173.2	184.5
95°	58.4	66.0	73.5	81.2	88.8	101.4	119.3	137.1	154.9	172.8	184.1
97.5°	104.8	101.0	97.3	93.4	89.7	97.1	115.8	134.4	153.1	171.8	182.7
100°	140.6	128.2	115.8	103.4	91.0	93.9	112.3	130.7	149.0	167.4	179.0
102.5°	178.9	183.4	188.0	192.7	197.2	195.3	186.9	178.5	170.0	161.6	173.3
105°	232.6	245.6	258.6	271.7	284.7	275.8	245.1	214.3	183.6	152.9	164.4
107.5°	295.4	305.8	316.3	326.7	337.1	322.2	281.8	241.5	201.1	160.8	168.3
110°	334.8	343.9	352.9	361.9	371.0	358.4	324.2	289.9	255.8	221.5	213.9



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	373.0	380.7	388.5	396.2	404.0	408.4	409.5	410.7	411.7	412.9	361.4
115°	433.2	439.0	444.9	450.8	456.6	467.9	484.5	501.2	517.8	534.4	466.1
117.5°	485.7	490.8	495.9	501.1	506.2	516.0	530.4	544.8	559.2	573.6	563.3
120°	525.0	528.6	532.1	535.7	539.3	548.2	562.2	576.3	590.4	604.5	614.2
122.5°	558.3	561.4	564.4	567.5	570.5	578.9	592.6	606.3	620.0	633.7	642.4
125°	607.9	610.0	612.1	614.3	616.4	623.5	635.6	647.6	659.7	671.6	680.4
127.5°	653.9	656.0	658.1	660.2	662.3	668.1	677.6	687.1	696.7	706.1	714.8
130°	683.1	685.4	687.8	690.2	692.5	697.6	705.2	712.9	720.5	728.1	736.6
132.5°	712.8	714.9	716.8	718.8	720.7	724.9	731.2	737.5	743.9	750.2	758.1
135°	750.3	753.0	755.6	758.2	760.9	764.3	768.7	772.9	777.1	781.5	788.9
137.5°	789.5	791.3	793.1	794.9	796.7	799.1	801.9	804.9	807.8	810.7	817.4
140°	815.1	816.1	817.2	818.2	819.3	821.0	823.4	825.7	828.1	830.5	836.4
142.5°	836.6	837.5	838.4	839.3	840.2	841.8	843.9	846.1	848.3	850.5	855.5
145°	868.9	868.8	868.6	868.5	868.3	869.6	872.5	875.2	878.1	880.8	883.7
147.5°	898.3	897.6	897.1	896.4	895.8	896.8	899.6	902.5	905.2	908.0	909.1
150°	917.4	916.2	915.0	913.9	912.7	913.5	916.2	918.8	921.5	924.1	925.0
152.5°	933.4	932.1	930.8	929.6	928.3	928.9	931.4	933.9	936.5	939.0	940.0
155°	956.8	955.4	953.8	952.4	950.9	951.1	953.1	955.1	957.1	959.0	960.0
157.5°	975.1	973.9	972.7	971.3	970.1	970.2	971.6	973.0	974.4	975.8	976.9
160°	985.9	984.9	983.9	982.8	981.9	981.9	982.8	983.9	984.9	985.9	986.8
162.5°	995.4	994.4	993.4	992.4	991.4	991.3	992.2	993.0	993.9	994.8	995.9
165°	1008.2	1007.2	1006.2	1005.2	1004.2	1004.0	1004.4	1004.9	1005.5	1006.0	1007.1
167.5°	1017.7	1016.8	1015.8	1014.7	1013.7	1013.5	1014.0	1014.4	1014.9	1015.4	1016.5
170°	1023.1	1022.1	1021.1	1020.1	1019.1	1018.8	1019.1	1019.5	1019.8	1020.1	1021.2
172.5°	1026.6	1025.6	1024.7	1023.7	1022.7	1022.4	1022.7	1023.0	1023.4	1023.7	1024.8
175°	1031.3	1030.1	1029.0	1027.8	1026.6	1026.2	1026.5	1026.9	1027.2	1027.5	1028.7
177.5°	1032.0	1031.1	1030.2	1029.2	1028.3	1027.9	1028.1	1028.2	1028.3	1028.4	1029.4
180°	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
0°	862.1	862.1	862.1	862.1	862.1	862.1	862.1	862.1
2.5°	859.3	860.5	861.6	861.9	861.4	861.0	860.5	860.1
5°	856.7	858.4	860.1	860.7	860.5	860.2	859.9	859.7
7.5°	852.6	854.7	856.6	857.5	857.2	857.0	856.6	856.4
10°	849.1	851.3	853.5	854.5	854.2	853.9	853.7	853.4
12.5°	843.1	845.3	847.5	848.5	848.2	847.9	847.7	847.4
15°	832.2	834.6	837.1	838.3	838.0	837.7	837.4	837.1
17.5°	818.2	820.8	823.4	824.7	824.7	824.7	824.7	824.7
20°	807.0	810.1	813.1	814.6	814.6	814.6	814.6	814.6
22.5°	795.0	798.1	801.1	802.9	803.3	803.8	804.2	804.7
25°	776.3	779.7	783.0	785.1	785.9	786.8	787.6	788.4
27.5°	755.6	759.9	764.1	766.5	767.1	767.7	768.3	768.9
30°	741.1	745.5	750.0	752.6	753.4	754.2	755.1	755.9
32.5°	725.5	730.5	735.6	738.9	740.5	741.9	743.5	744.9
35°	703.2	709.3	715.4	719.4	721.4	723.3	725.3	727.2
37.5°	680.3	687.1	693.8	698.2	700.3	702.4	704.4	706.5
40°	664.1	671.4	678.6	683.5	686.0	688.4	691.0	693.5
42.5°	648.5	656.4	664.3	669.4	672.0	674.5	676.9	679.5
45°	624.4	633.1	641.6	647.3	650.1	652.9	655.7	658.4
47.5°	599.5	608.5	617.5	623.5	626.6	629.7	632.7	635.8
50°	582.4	591.8	601.3	607.6	610.6	613.6	616.7	619.7
52.5°	563.9	573.5	583.2	589.6	592.9	596.2	599.5	602.8
55°	536.1	546.0	556.0	562.8	566.4	570.1	573.6	577.2
57.5°	506.6	517.4	528.2	535.3	539.0	542.7	546.3	550.0
60°	487.1	497.7	508.3	515.5	519.3	523.3	527.2	531.0
62.5°	466.5	477.7	488.9	496.4	500.0	503.7	507.4	511.0
65°	435.1	446.5	457.9	465.4	469.0	472.5	476.2	479.8
67.5°	403.3	414.8	426.3	434.0	437.7	441.5	445.3	449.1
70°	381.2	393.1	405.1	412.7	416.0	419.4	422.7	426.1
72.5°	359.8	371.5	383.2	391.1	395.1	399.1	403.1	407.1
75°	327.5	339.4	351.4	359.1	362.7	366.4	370.0	373.6
77.5°	295.9	307.8	319.7	327.6	331.4	335.3	339.2	343.1
80°	274.4	286.2	297.8	305.6	309.5	313.3	317.2	321.1
82.5°	254.5	266.1	277.8	285.4	289.1	292.8	296.4	300.1
85°	225.8	237.4	249.1	256.8	260.7	264.6	268.5	272.4
87.5°	204.9	216.4	227.9	235.5	239.0	242.7	246.3	249.9
90°	203.7	215.6	227.6	235.4	239.0	242.7	246.4	250.0
92.5°	195.8	207.2	218.5	225.9	229.4	232.9	236.5	240.0
95°	195.5	206.8	218.3	225.5	228.7	231.9	235.1	238.1
97.5°	193.7	204.6	215.6	222.7	226.2	229.7	233.2	236.7
100°	190.6	202.2	213.8	221.3	224.6	228.0	231.5	234.8
102.5°	185.2	196.9	208.6	216.3	219.8	223.4	226.9	230.4
105°	175.9	187.5	199.0	206.7	210.3	214.1	217.8	221.5
107.5°	175.8	183.2	190.7	196.3	200.0	203.7	207.4	211.2
110°	206.2	198.5	190.9	188.9	192.6	196.3	200.1	203.7



TEST NUMBER: P331450-930

CATALOG NUMBER: S122DIP-S1005D925U930-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
112.5°	309.9	258.4	207.0	183.0	186.6	190.2	193.8	197.4
115°	397.9	329.5	261.3	222.7	213.9	205.0	196.1	187.3
117.5°	552.9	542.7	532.3	509.0	472.7	436.3	400.1	363.8
120°	624.0	633.8	643.6	638.8	619.5	600.2	581.0	561.7
122.5°	651.2	659.9	668.6	672.1	670.4	668.7	667.0	665.3
125°	689.0	697.7	706.3	712.1	715.1	718.1	721.1	724.1
127.5°	723.3	731.9	740.5	746.0	748.5	751.1	753.7	756.2
130°	745.1	753.6	762.1	767.4	769.4	771.5	773.6	775.6
132.5°	766.1	774.1	782.1	787.2	789.2	791.3	793.4	795.4
135°	796.4	803.9	811.4	816.0	818.0	819.9	821.7	823.6
137.5°	824.1	830.9	837.6	841.6	842.9	844.2	845.6	846.9
140°	842.4	848.3	854.3	857.6	858.4	859.3	860.1	861.0
142.5°	860.4	865.3	870.2	872.9	873.6	874.2	874.8	875.4
145°	886.6	889.3	892.2	893.9	894.4	895.0	895.5	896.1
147.5°	910.1	911.3	912.3	912.8	912.8	912.8	912.7	912.7
150°	926.0	927.1	928.1	928.1	927.3	926.4	925.6	924.8
152.5°	940.9	941.9	942.9	942.9	941.8	940.7	939.6	938.5
155°	961.1	962.1	963.0	962.9	961.6	960.2	958.9	957.6
157.5°	978.0	979.1	980.2	980.2	978.8	977.5	976.2	975.0
160°	987.8	988.9	989.9	989.8	988.6	987.4	986.3	985.1
162.5°	997.0	998.2	999.3	999.1	997.8	996.3	994.9	993.4
165°	1008.3	1009.4	1010.6	1010.6	1009.4	1008.3	1007.1	1006.0
167.5°	1017.7	1018.8	1020.0	1019.8	1018.3	1016.8	1015.4	1013.8
170°	1022.5	1023.6	1024.7	1024.6	1023.1	1021.6	1020.1	1018.6
172.5°	1026.0	1027.2	1028.3	1028.2	1026.6	1025.2	1023.7	1022.2
175°	1029.9	1031.0	1032.2	1031.9	1030.3	1028.7	1027.0	1025.3
177.5°	1030.3	1031.3	1032.2	1032.0	1030.9	1029.6	1028.4	1027.3
180°	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1	1029.1

(END OF REPORT)