

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332265-840

Luminaire Tested: **S123RDIP-S340D1195U840-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P332265-840  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S123RDIP-S340D1195U840-4F0-1E-UDD-A1  
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE  
DOWNLIGHT 340 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING  
UPLIGHT 1195 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5511.3 lumens  
Efficiency: N/A  
Efficacy: 130.6 lumens/watt  
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36  
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')  
CIE Type: Semi-Indirect


Input Watts (W): 42.2  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

### Luminous Intensity Polar Plot



— 0°-180°    - - 45°-225°    - - - 90°-270°    - - - 135°-315°



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	33	33	33	25				
1	92	88	85	81	82	79	76	73	61	59	57	45	43	42	30	29	28	22				
2	84	77	72	67	75	69	64	60	54	51	48	40	38	36	26	25	24	18				
3	77	68	61	56	68	61	55	51	48	44	40	35	33	31	24	22	21	16				
4	71	60	53	47	63	54	48	43	42	38	35	31	29	26	21	20	18	14				
5	65	54	46	41	57	48	42	37	38	33	30	28	25	23	19	17	16	12				
6	60	48	41	35	53	43	37	32	34	29	26	26	22	20	18	16	14	11				
7	55	43	36	31	49	39	33	28	31	26	23	23	20	18	16	14	13	10				
8	51	39	32	27	45	35	29	25	28	24	20	21	18	16	15	13	11	9				
9	47	36	29	24	42	32	26	22	26	21	18	19	16	14	14	12	10	8				
10	44	33	26	21	39	30	24	20	24	19	16	18	15	13	13	11	9	7				

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	5916	5916	5916	5916
5°	7052	5942	5232	5942
10°	8805	5908	4726	5908
15°	10336	5846	4310	5846
20°	11535	5756	3956	5756
25°	11351	5662	3739	5662
30°	8158	5574	3515	5574
35°	5447	5460	3369	5460
40°	4013	5323	3219	5323
45°	3367	5083	3073	5083
50°	2971	4767	2869	4767
55°	2607	4406	2586	4406
60°	2321	4060	2370	4060
65°	2038	3691	2203	3691
70°	1599	3361	2014	3361
75°	1406	2936	1838	2936
80°	1227	2492	1810	2492
85°	988	2013	1927	2013



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	54.0	1.0
10°-20°	168.9	3.1
20°-30°	265.3	4.8
30°-40°	276.8	5.0
40°-50°	236.9	4.3
50°-60°	180.5	3.3
60°-70°	115.7	2.1
70°-80°	55.7	1.0
80°-90°	19.1	0.3
90°-100°	97.3	1.8
100°-110°	291.2	5.3
110°-120°	495.4	9.0
120°-130°	651.6	11.8
130°-140°	732.3	13.3
140°-150°	719.9	13.1
150°-160°	606.0	11.0
160°-170°	403.4	7.3
170°-180°	141.3	2.6
0°-30°	488.2	8.9
0°-40°	764.9	13.9
0°-60°	1182.3	21.5
0°-90°	1372.9	24.9
90°-120°	883.9	16.0
90°-150°	2987.7	54.2
90°-180°	4138.0	75.1
0°-180°	5511.3	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	550	550	550	550	550	
5°	653	550	484	550	653	67
15°	928	525	387	525	928	263
25°	956	477	315	477	956	411
35°	414	416	256	416	414	272
45°	221	334	202	334	221	174
55°	139	235	138	235	139	126
65°	80	145	86	145	80	79
75°	34	71	44	71	34	36
85°	8	16	16	16	8	10
90°	35	1	35	1	35	17
95°	92	69	92	69	92	94
105°	279	264	279	264	279	296
115°	500	499	500	499	500	495
125°	722	730	722	730	722	645
135°	946	947	946	947	946	727
145°	1149	1149	1149	1149	1149	717
155°	1313	1315	1313	1315	1313	605
165°	1428	1433	1428	1433	1428	403
175°	1484	1490	1484	1490	1484	141
180°	1494	1494	1494	1494	1494	



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	585.4	586.1	583.7	583.3	580.5	579.8	579.8	575.7	573.3	570.2	568.3
5°	652.7	656.4	654.5	650.4	643.3	641.6	637.1	630.1	622.1	612.2	607.5
7.5°	736.7	741.8	739.8	733.4	725.9	719.9	707.3	695.6	679.2	664.8	652.5
10°	805.6	800.2	796.0	789.6	782.7	771.7	758.5	740.4	719.5	703.0	684.7
12.5°	857.2	856.3	850.9	844.3	834.8	824.3	808.0	786.0	761.6	737.8	716.8
15°	927.5	928.9	925.3	918.6	904.8	886.3	861.8	852.6	817.8	791.9	766.1
17.5°	976.1	975.8	975.3	965.9	952.0	938.8	916.0	891.9	860.4	823.9	789.1
20°	1007.0	1004.6	1005.1	994.5	984.2	968.9	946.7	911.7	885.9	843.7	807.7
22.5°	1006.2	1005.7	1007.5	1003.9	996.4	984.7	967.2	937.7	904.6	862.1	821.6
25°	955.7	953.8	964.8	968.0	980.0	982.1	976.8	960.7	929.4	885.6	835.5
27.5°	799.8	798.8	819.3	845.1	877.6	902.9	927.4	939.2	929.4	898.0	847.8
30°	656.4	678.5	688.9	726.1	767.5	816.9	860.2	901.3	911.5	897.8	856.7
32.5°	545.0	564.3	573.0	604.8	643.5	701.4	766.3	824.6	865.8	876.2	851.4
35°	414.5	414.8	434.5	448.7	484.4	543.9	607.0	685.1	762.8	821.6	827.7
37.5°	330.8	331.9	344.0	358.0	384.9	416.3	471.8	536.7	626.4	716.7	769.7
40°	285.6	287.7	296.7	310.5	329.8	353.7	396.9	458.1	532.9	633.4	715.5
42.5°	256.6	260.0	264.7	275.4	287.3	309.6	344.6	391.8	459.9	554.9	649.6
45°	221.2	223.1	226.6	231.6	242.4	257.8	281.3	313.2	369.6	446.1	540.9
47.5°	195.1	194.1	197.8	201.8	209.0	219.6	235.4	261.3	301.5	362.9	443.3
50°	177.4	177.1	179.8	182.8	189.7	197.4	210.4	229.8	261.9	312.7	386.4
52.5°	160.9	161.7	163.6	167.3	172.3	178.5	190.2	204.3	231.8	275.6	337.0
55°	138.9	139.6	142.1	144.2	147.7	154.1	161.4	173.2	192.0	222.6	273.2
57.5°	120.2	119.9	122.3	122.9	126.8	132.0	137.6	146.8	160.5	183.2	217.2
60°	107.8	107.0	109.2	110.8	112.9	117.1	121.9	130.8	141.7	158.3	187.5
62.5°	96.4	96.1	97.7	99.4	101.1	104.9	108.9	115.7	124.3	138.4	161.6
65°	80.0	80.7	81.4	82.1	83.0	85.4	89.2	93.9	99.8	109.7	126.3
67.5°	62.9	63.6	63.8	65.2	67.3	68.8	71.1	75.2	79.4	87.7	97.1
70°	50.8	50.6	50.8	51.5	54.1	56.7	59.8	62.8	65.4	71.3	79.3
72.5°	43.6	43.2	43.8	44.0	45.2	45.9	47.9	50.8	54.1	58.1	63.8
75°	33.8	33.8	33.8	33.8	34.8	35.2	36.0	36.7	37.9	39.8	44.0
77.5°	25.0	25.0	25.4	25.7	25.9	26.2	26.6	27.3	27.7	28.7	30.5
80°	19.8	20.0	19.8	20.0	20.0	20.5	20.7	21.4	21.6	22.8	23.5
82.5°	14.8	14.7	14.8	15.1	15.1	15.6	15.7	16.2	16.2	16.8	17.5
85°	8.0	7.6	8.0	7.8	8.3	7.8	8.0	8.5	8.5	8.7	9.7
87.5°	8.9	9.2	8.7	8.8	8.7	8.7	8.5	8.3	8.5	8.1	7.6
90°	35.2	34.6	34.1	33.6	33.1	32.3	31.3	30.3	29.2	28.2	24.7
92.5°	47.4	47.7	48.1	48.4	48.7	48.4	47.6	46.8	45.8	45.0	43.1
95°	91.5	91.5	91.5	91.5	91.5	91.0	90.0	88.9	87.9	86.8	84.7
97.5°	140.8	140.9	141.0	141.1	141.2	140.7	139.5	138.3	137.0	135.8	134.3
100°	178.3	177.8	177.3	176.8	176.2	175.6	174.8	174.0	173.3	172.5	171.2
102.5°	216.8	216.9	217.0	217.1	217.2	216.9	216.1	215.3	214.6	213.8	212.1
105°	279.2	278.7	278.2	277.7	277.2	276.9	276.9	276.9	276.9	276.9	274.6
107.5°	344.3	344.6	344.9	345.2	345.5	345.3	344.5	343.6	342.7	341.9	340.9
110°	388.4	388.9	389.4	389.9	390.4	390.2	389.2	388.1	387.1	386.1	385.5



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	435.4	435.5	435.6	435.7	435.8	435.2	433.9	432.6	431.4	430.1	430.0
115°	499.9	500.1	500.4	500.6	500.9	500.9	500.6	500.4	500.1	499.9	500.4
117.5°	565.3	566.0	566.7	567.5	568.3	568.7	568.7	568.8	568.8	568.9	569.6
120°	611.3	611.9	612.4	612.9	613.4	613.8	614.1	614.3	614.6	614.8	616.1
122.5°	655.4	656.1	656.9	657.6	658.3	659.0	659.7	660.5	661.1	661.8	662.5
125°	721.6	722.7	723.7	724.8	725.8	726.8	727.9	728.9	729.9	731.0	731.5
127.5°	787.6	788.7	789.9	791.1	792.3	793.7	795.2	796.6	798.1	799.5	800.1
130°	830.7	832.5	834.4	836.2	838.0	839.5	840.5	841.5	842.6	843.6	844.4
132.5°	875.8	877.2	878.6	880.0	881.4	882.7	884.0	885.2	886.5	887.8	888.3
135°	945.7	946.2	946.7	947.3	947.8	948.6	949.6	950.7	951.7	952.7	953.0
137.5°	1007.4	1008.5	1009.5	1010.4	1011.4	1012.4	1013.5	1014.6	1015.7	1016.8	1016.1
140°	1047.8	1049.7	1051.5	1053.3	1055.1	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9
142.5°	1089.1	1090.6	1091.9	1093.3	1094.7	1095.6	1095.8	1096.1	1096.3	1096.6	1096.1
145°	1148.7	1149.7	1150.7	1151.9	1152.9	1153.6	1153.8	1154.1	1154.3	1154.6	1153.8
147.5°	1201.7	1203.3	1204.9	1206.4	1208.0	1208.8	1208.8	1208.8	1208.8	1208.8	1208.0
150°	1235.6	1237.1	1238.7	1240.2	1241.8	1242.5	1242.5	1242.5	1242.5	1242.5	1242.0
152.5°	1268.4	1269.7	1271.1	1272.4	1273.8	1274.2	1273.8	1273.4	1273.0	1272.6	1272.3
155°	1312.9	1314.8	1316.7	1318.5	1320.3	1320.7	1319.6	1318.6	1317.6	1316.5	1316.3
157.5°	1353.5	1355.0	1356.5	1358.0	1359.4	1359.6	1358.5	1357.4	1356.3	1355.2	1355.0
160°	1379.9	1380.9	1381.9	1383.0	1384.0	1383.9	1382.6	1381.3	1380.0	1378.7	1378.7
162.5°	1399.6	1401.2	1402.9	1404.5	1406.2	1406.4	1405.1	1403.8	1402.5	1401.2	1401.0
165°	1427.9	1429.8	1431.6	1433.4	1435.2	1435.4	1433.8	1432.3	1430.7	1429.2	1429.2
167.5°	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5	1456.9	1455.3	1453.7	1452.1	1451.9
170°	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7	1469.9	1467.9	1466.1	1464.3	1464.3
172.5°	1473.7	1475.5	1477.3	1479.1	1481.1	1481.2	1479.6	1477.9	1476.3	1474.7	1474.7
175°	1484.3	1486.1	1487.9	1489.8	1491.6	1491.7	1490.2	1488.5	1487.0	1485.4	1485.4
177.5°	1490.0	1491.4	1492.8	1494.3	1495.7	1495.8	1494.6	1493.4	1492.1	1490.9	1490.9
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	567.4	566.9	564.3	561.3	557.3	554.7	552.6	551.5	548.1	543.9	541.2
5°	602.6	595.5	587.9	578.8	570.3	561.6	556.2	549.9	542.1	533.4	527.3
7.5°	640.1	626.2	611.4	595.9	580.8	567.1	555.0	544.7	532.4	519.9	511.2
10°	668.9	648.6	627.7	606.3	586.8	568.5	554.3	540.5	525.6	511.3	500.4
12.5°	695.1	668.4	644.3	617.9	593.0	571.1	550.8	534.4	516.5	501.3	489.0
15°	728.2	700.8	671.8	631.7	598.5	570.8	546.0	524.6	503.0	484.2	472.2
17.5°	759.1	718.1	678.8	645.5	602.4	567.7	537.6	512.0	488.2	468.3	453.4
20°	771.9	732.2	689.6	647.0	604.7	565.8	530.8	502.5	477.9	455.2	441.6
22.5°	779.6	734.7	689.7	644.0	599.1	558.7	524.0	492.9	466.2	444.7	427.9
25°	788.6	735.0	685.6	640.5	594.5	550.8	509.6	476.7	447.8	425.0	407.1
27.5°	794.6	731.4	673.1	622.9	576.3	532.8	495.0	460.1	430.7	406.6	387.4
30°	795.7	728.6	663.5	609.2	561.9	521.8	481.8	448.5	417.4	391.7	373.9
32.5°	797.2	721.6	650.5	592.8	544.3	504.7	468.5	436.6	404.8	379.5	361.2
35°	791.0	717.8	630.8	564.4	515.9	477.6	444.9	415.5	384.3	359.7	341.1
37.5°	764.3	702.6	610.4	532.5	481.8	446.4	419.7	394.0	365.4	338.9	321.4
40°	737.4	687.5	594.5	513.1	460.2	423.7	399.7	378.8	351.0	326.3	307.5
42.5°	697.3	666.9	579.5	492.8	435.8	400.6	380.3	360.7	336.4	311.2	293.6
45°	623.7	627.7	548.7	460.4	401.8	366.6	347.5	333.9	312.3	291.5	273.4
47.5°	531.5	568.9	512.5	426.0	366.2	333.1	316.4	304.5	289.8	269.5	253.0
50°	471.3	524.6	483.5	402.8	343.8	310.8	294.4	284.7	272.0	256.0	240.2
52.5°	415.8	473.1	448.5	377.0	319.4	289.3	273.3	265.3	255.2	240.1	225.9
55°	339.0	397.2	391.5	338.1	283.1	256.0	243.8	234.8	228.0	216.7	205.4
57.5°	274.3	329.3	332.2	294.8	251.0	224.2	213.7	206.9	202.5	194.0	183.5
60°	233.4	284.0	293.9	265.6	228.0	204.5	194.1	188.6	185.2	178.3	170.4
62.5°	199.5	242.6	253.8	233.5	206.0	183.9	175.8	170.7	168.2	162.4	155.3
65°	152.7	188.4	199.2	188.0	173.6	156.0	149.4	144.9	142.8	139.6	134.3
67.5°	114.8	140.9	152.8	144.8	139.6	128.5	124.3	121.9	120.0	117.8	113.4
70°	92.2	111.5	123.7	121.7	117.4	111.5	108.5	106.8	104.9	103.0	99.3
72.5°	74.1	87.5	98.9	100.0	96.5	95.3	92.6	91.9	90.8	88.6	86.4
75°	49.2	58.4	66.3	69.4	70.8	72.0	70.8	70.6	70.4	68.5	67.3
77.5°	32.2	37.2	42.2	47.5	49.7	51.2	51.6	52.5	51.8	50.9	50.3
80°	24.7	25.9	29.4	33.8	37.4	38.8	39.8	40.2	40.0	39.8	38.8
82.5°	18.0	18.9	20.6	23.7	26.7	29.0	29.6	29.5	30.0	30.2	29.4
85°	9.7	9.9	10.4	10.8	12.4	15.0	15.8	16.3	16.7	16.7	15.2
87.5°	7.3	6.5	6.2	5.6	5.6	5.3	5.9	6.3	7.0	6.8	7.3
90°	21.4	18.0	14.6	11.6	9.0	6.4	3.7	1.2	3.7	6.4	9.0
92.5°	41.2	39.3	37.4	35.4	33.7	31.9	30.2	28.4	30.2	31.9	33.7
95°	82.6	80.6	78.5	76.5	74.7	72.9	71.1	69.3	71.1	72.9	74.7
97.5°	132.9	131.4	129.9	128.4	127.0	125.7	124.3	123.0	124.3	125.7	127.0
100°	169.9	168.5	167.2	165.8	164.3	162.7	161.2	159.6	161.2	162.7	164.3
102.5°	210.4	208.6	206.9	205.6	204.6	203.7	202.8	201.8	202.8	203.7	204.6
105°	272.3	269.8	267.5	266.1	265.6	265.1	264.5	264.0	264.5	265.1	265.6
107.5°	340.0	339.1	338.2	337.5	337.2	336.9	336.6	336.3	336.6	336.9	337.2
110°	385.0	384.5	384.0	383.4	382.9	382.3	381.8	381.3	381.8	382.3	382.9





TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	429.9	429.8	429.7	429.5	429.2	428.9	428.6	428.3	428.6	428.9	429.2
115°	500.9	501.4	501.9	501.8	501.0	500.2	499.5	498.7	499.5	500.2	501.0
117.5°	570.2	570.9	571.6	571.6	571.1	570.6	570.1	569.6	570.1	570.6	571.1
120°	617.4	618.7	620.1	620.0	618.3	616.8	615.2	613.7	615.2	616.8	618.3
122.5°	663.1	663.8	664.5	664.3	663.1	662.0	660.8	659.6	660.8	662.0	663.1
125°	732.1	732.6	733.1	733.0	732.2	731.3	730.6	729.8	730.6	731.3	732.2
127.5°	800.6	801.2	801.8	801.2	799.6	797.9	796.3	794.6	796.3	797.9	799.6
130°	845.2	846.0	846.8	846.1	844.0	841.9	839.8	837.8	839.8	841.9	844.0
132.5°	888.9	889.5	890.1	889.3	887.2	885.1	883.0	880.9	883.0	885.1	887.2
135°	953.3	953.5	953.8	953.1	951.6	950.0	948.5	946.8	948.5	950.0	951.6
137.5°	1015.4	1014.8	1014.1	1013.1	1011.8	1010.5	1009.2	1007.9	1009.2	1010.5	1011.8
140°	1056.6	1056.4	1056.1	1055.3	1054.1	1052.8	1051.5	1050.2	1051.5	1052.8	1054.1
142.5°	1095.7	1095.2	1094.7	1093.9	1092.6	1091.3	1089.9	1088.6	1089.9	1091.3	1092.6
145°	1153.0	1152.3	1151.4	1150.7	1150.2	1149.7	1149.2	1148.7	1149.2	1149.7	1150.2
147.5°	1207.3	1206.6	1205.9	1205.1	1204.1	1203.2	1202.2	1201.2	1202.2	1203.2	1204.1
150°	1241.5	1241.0	1240.5	1240.0	1239.4	1238.9	1238.4	1237.9	1238.4	1238.9	1239.4
152.5°	1272.0	1271.6	1271.3	1270.8	1270.1	1269.4	1268.7	1267.9	1268.7	1269.4	1270.1
155°	1316.0	1315.8	1315.5	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3
157.5°	1354.8	1354.6	1354.3	1354.4	1354.7	1355.0	1355.3	1355.6	1355.3	1355.0	1354.7
160°	1378.7	1378.7	1378.7	1379.0	1379.5	1380.0	1380.5	1381.0	1380.5	1380.0	1379.5
162.5°	1400.8	1400.6	1400.4	1400.7	1401.4	1402.1	1402.8	1403.5	1402.8	1402.1	1401.4
165°	1429.2	1429.2	1429.2	1429.6	1430.3	1431.1	1431.9	1432.7	1431.9	1431.1	1430.3
167.5°	1451.7	1451.5	1451.3	1451.7	1452.8	1453.8	1454.8	1455.9	1454.8	1453.8	1452.8
170°	1464.3	1464.3	1464.3	1464.8	1465.9	1466.9	1467.9	1469.1	1467.9	1466.9	1465.9
172.5°	1474.7	1474.7	1474.7	1475.2	1476.2	1477.2	1478.3	1479.4	1478.3	1477.2	1476.2
175°	1485.4	1485.4	1485.4	1486.0	1487.0	1488.0	1489.1	1490.2	1489.1	1488.0	1487.0
177.5°	1490.9	1490.9	1490.9	1491.3	1492.1	1493.0	1493.8	1494.6	1493.8	1493.0	1492.1
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	540.2	537.8	536.0	532.3	529.9	527.3	524.6	526.2	526.0	525.9	525.9
5°	522.1	516.6	511.7	505.3	501.4	496.4	492.7	492.2	493.1	489.9	488.0
7.5°	504.1	496.8	489.7	482.7	475.2	469.3	465.6	463.8	461.5	459.5	457.4
10°	491.5	482.8	475.9	467.3	459.3	452.2	447.8	444.6	443.0	441.4	438.3
12.5°	478.5	470.0	461.3	451.4	443.8	435.7	432.3	428.9	425.8	423.8	419.7
15°	459.5	448.5	439.3	428.9	420.4	412.4	407.8	400.9	400.0	397.6	393.3
17.5°	440.4	428.5	415.8	408.1	398.6	390.2	383.0	380.8	374.1	371.5	367.8
20°	425.4	414.3	404.7	394.6	380.7	372.9	367.3	364.3	358.8	355.5	353.1
22.5°	412.4	401.1	390.0	378.2	366.8	358.0	353.9	349.1	346.2	341.5	339.0
25°	393.8	381.6	368.2	355.5	347.3	340.7	334.1	329.8	325.6	323.5	318.8
27.5°	372.3	359.5	347.0	337.3	327.2	320.7	314.8	311.0	305.9	302.4	299.7
30°	360.4	345.4	334.6	325.9	313.0	306.8	302.4	297.6	293.9	290.1	287.5
32.5°	346.7	333.0	322.8	311.9	302.1	295.3	289.5	285.4	282.2	278.6	276.0
35°	325.2	313.7	303.1	292.3	284.9	278.1	271.2	267.7	264.7	261.4	259.0
37.5°	305.7	294.9	284.8	274.6	265.5	259.9	254.5	251.8	247.6	245.4	243.1
40°	293.7	283.1	272.3	262.4	253.0	248.7	243.8	239.7	236.0	234.3	231.8
42.5°	280.4	269.8	260.7	250.1	242.4	236.6	232.1	227.7	224.9	222.5	221.1
45°	260.9	251.6	242.6	232.0	224.7	219.7	214.6	210.6	208.0	206.3	203.8
47.5°	242.0	232.6	223.5	214.3	207.2	201.6	196.3	193.6	190.2	188.1	186.4
50°	228.2	219.7	210.2	201.7	194.6	188.9	184.7	181.2	178.1	175.5	174.3
52.5°	215.6	206.6	198.2	190.4	182.9	176.5	172.7	169.0	166.6	163.7	162.3
55°	194.8	186.1	179.0	171.3	164.0	158.5	153.9	150.6	148.2	144.9	143.1
57.5°	175.3	167.4	159.1	152.3	144.8	140.3	136.3	131.9	129.0	126.4	124.5
60°	162.1	153.2	145.8	139.6	132.9	127.0	123.5	120.0	116.9	114.3	112.7
62.5°	148.3	140.6	133.6	126.7	120.7	115.5	111.5	108.6	105.8	104.2	102.5
65°	127.2	121.2	114.1	108.5	102.8	99.1	95.7	93.2	91.3	90.1	88.7
67.5°	107.9	102.0	95.8	90.3	86.4	83.6	81.5	79.3	78.3	76.7	75.8
70°	95.3	89.2	83.7	79.5	75.7	73.6	72.2	70.6	69.7	67.8	66.9
72.5°	81.6	77.2	73.2	69.8	66.8	64.8	63.0	61.0	59.5	57.4	56.5
75°	64.2	60.2	57.2	54.8	52.9	50.4	47.8	45.6	44.9	44.2	44.0
77.5°	47.6	45.0	42.8	40.8	38.5	36.7	36.1	35.5	35.4	35.0	35.0
80°	37.4	35.0	33.4	31.1	29.7	29.7	29.7	29.2	29.4	29.4	29.4
82.5°	27.8	25.7	24.7	23.9	23.6	23.8	23.8	23.9	23.7	24.1	23.9
85°	14.3	14.5	15.0	14.8	15.0	15.0	15.6	15.2	15.6	15.0	15.6
87.5°	7.6	8.8	9.6	10.5	11.3	11.8	12.2	12.4	12.8	13.0	13.2
90°	11.6	14.6	18.0	21.4	24.7	28.2	29.2	30.3	31.3	32.3	33.1
92.5°	35.4	37.4	39.3	41.2	43.1	45.0	45.8	46.8	47.6	48.4	48.7
95°	76.5	78.5	80.6	82.6	84.7	86.8	87.9	88.9	90.0	91.0	91.5
97.5°	128.4	129.9	131.4	132.9	134.3	135.8	137.0	138.3	139.5	140.7	141.2
100°	165.8	167.2	168.5	169.9	171.2	172.5	173.3	174.0	174.8	175.6	176.2
102.5°	205.6	206.9	208.6	210.4	212.1	213.8	214.6	215.3	216.1	216.9	217.2
105°	266.1	267.5	269.8	272.3	274.6	276.9	276.9	276.9	276.9	276.9	277.2
107.5°	337.5	338.2	339.1	340.0	340.9	341.9	342.7	343.6	344.5	345.3	345.5
110°	383.4	384.0	384.5	385.0	385.5	386.1	387.1	388.1	389.2	390.2	390.4



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	429.5	429.7	429.8	429.9	430.0	430.1	431.4	432.6	433.9	435.2	435.8
115°	501.8	501.9	501.4	500.9	500.4	499.9	500.1	500.4	500.6	500.9	500.9
117.5°	571.6	571.6	570.9	570.2	569.6	568.9	568.8	568.8	568.7	568.7	568.3
120°	620.0	620.1	618.7	617.4	616.1	614.8	614.6	614.3	614.1	613.8	613.4
122.5°	664.3	664.5	663.8	663.1	662.5	661.8	661.1	660.5	659.7	659.0	658.3
125°	733.0	733.1	732.6	732.1	731.5	731.0	729.9	728.9	727.9	726.8	725.8
127.5°	801.2	801.8	801.2	800.6	800.1	799.5	798.1	796.6	795.2	793.7	792.3
130°	846.1	846.8	846.0	845.2	844.4	843.6	842.6	841.5	840.5	839.5	838.0
132.5°	889.3	890.1	889.5	888.9	888.3	887.8	886.5	885.2	884.0	882.7	881.4
135°	953.1	953.8	953.5	953.3	953.0	952.7	951.7	950.7	949.6	948.6	947.8
137.5°	1013.1	1014.1	1014.8	1015.4	1016.1	1016.8	1015.7	1014.6	1013.5	1012.4	1011.4
140°	1055.3	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9	1056.6	1056.4	1056.1	1055.1
142.5°	1093.9	1094.7	1095.2	1095.7	1096.1	1096.6	1096.3	1096.1	1095.8	1095.6	1094.7
145°	1150.7	1151.4	1152.3	1153.0	1153.8	1154.6	1154.3	1154.1	1153.8	1153.6	1152.9
147.5°	1205.1	1205.9	1206.6	1207.3	1208.0	1208.8	1208.8	1208.8	1208.8	1208.8	1208.0
150°	1240.0	1240.5	1241.0	1241.5	1242.0	1242.5	1242.5	1242.5	1242.5	1242.5	1241.8
152.5°	1270.8	1271.3	1271.6	1272.0	1272.3	1272.6	1273.0	1273.4	1273.8	1274.2	1273.8
155°	1315.3	1315.5	1315.8	1316.0	1316.3	1316.5	1317.6	1318.6	1319.6	1320.7	1320.3
157.5°	1354.4	1354.3	1354.6	1354.8	1355.0	1355.2	1356.3	1357.4	1358.5	1359.6	1359.4
160°	1379.0	1378.7	1378.7	1378.7	1378.7	1378.7	1380.0	1381.3	1382.6	1383.9	1384.0
162.5°	1400.7	1400.4	1400.6	1400.8	1401.0	1401.2	1402.5	1403.8	1405.1	1406.4	1406.2
165°	1429.6	1429.2	1429.2	1429.2	1429.2	1429.2	1430.7	1432.3	1433.8	1435.4	1435.2
167.5°	1451.7	1451.3	1451.5	1451.7	1451.9	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5
170°	1464.8	1464.3	1464.3	1464.3	1464.3	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7
172.5°	1475.2	1474.7	1474.7	1474.7	1474.7	1474.7	1476.3	1477.9	1479.6	1481.2	1481.1
175°	1486.0	1485.4	1485.4	1485.4	1485.4	1485.4	1487.0	1488.5	1490.2	1491.7	1491.6
177.5°	1491.3	1490.9	1490.9	1490.9	1490.9	1490.9	1492.1	1493.4	1494.6	1495.8	1495.7
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	523.6	523.4	523.6	522.9	523.6	523.4	523.6	525.9	525.9	526.0	526.2
5°	487.3	487.1	486.4	484.2	486.4	487.1	487.3	488.0	489.9	493.1	492.2
7.5°	455.4	455.1	453.1	453.1	453.1	455.1	455.4	457.4	459.5	461.5	463.8
10°	436.7	436.9	434.0	432.4	434.0	436.9	436.7	438.3	441.4	443.0	444.6
12.5°	418.4	417.4	415.1	413.2	415.1	417.4	418.4	419.7	423.8	425.8	428.9
15°	394.4	391.9	386.4	386.8	386.4	391.9	394.4	393.3	397.6	400.0	400.9
17.5°	366.0	364.3	364.2	360.8	364.2	364.3	366.0	367.8	371.5	374.1	380.8
20°	349.4	348.2	348.7	345.4	348.7	348.2	349.4	353.1	355.5	358.8	364.3
22.5°	336.4	335.2	333.3	332.2	333.3	335.2	336.4	339.0	341.5	346.2	349.1
25°	317.4	315.5	313.7	314.8	313.7	315.5	317.4	318.8	323.5	325.6	329.8
27.5°	298.4	297.0	295.1	294.9	295.1	297.0	298.4	299.7	302.4	305.9	311.0
30°	286.3	284.9	284.0	282.8	284.0	284.9	286.3	287.5	290.1	293.9	297.6
32.5°	274.1	273.8	272.2	271.9	272.2	273.8	274.1	276.0	278.6	282.2	285.4
35°	258.1	256.7	256.2	256.4	256.2	256.7	258.1	259.0	261.4	264.7	267.7
37.5°	242.9	241.1	240.1	239.3	240.1	241.1	242.9	243.1	245.4	247.6	251.8
40°	232.0	230.1	229.6	229.1	229.6	230.1	232.0	231.8	234.3	236.0	239.7
42.5°	219.7	219.0	218.7	217.8	218.7	219.0	219.7	221.1	222.5	224.9	227.7
45°	203.1	202.8	201.4	201.9	201.4	202.8	203.1	203.8	206.3	208.0	210.6
47.5°	185.4	184.4	183.4	184.1	183.4	184.4	185.4	186.4	188.1	190.2	193.6
50°	173.4	172.9	170.8	171.3	170.8	172.9	173.4	174.3	175.5	178.1	181.2
52.5°	161.4	159.6	158.8	158.4	158.8	159.6	161.4	162.3	163.7	166.6	169.0
55°	141.4	139.3	138.4	137.8	138.4	139.3	141.4	143.1	144.9	148.2	150.6
57.5°	121.8	121.3	120.5	121.0	120.5	121.3	121.8	124.5	126.4	129.0	131.9
60°	110.4	110.4	110.4	110.1	110.4	110.4	110.4	112.7	114.3	116.9	120.0
62.5°	101.5	100.9	100.8	101.1	100.8	100.9	101.5	102.5	104.2	105.8	108.6
65°	88.0	87.8	86.8	86.5	86.8	87.8	88.0	88.7	90.1	91.3	93.2
67.5°	75.2	74.4	74.1	73.8	74.1	74.4	75.2	75.8	76.7	78.3	79.3
70°	65.6	65.1	63.7	64.0	63.7	65.1	65.6	66.9	67.8	69.7	70.6
72.5°	55.3	54.8	54.5	54.2	54.5	54.8	55.3	56.5	57.4	59.5	61.0
75°	43.7	43.5	43.3	44.2	43.3	43.5	43.7	44.0	44.2	44.9	45.6
77.5°	35.0	35.0	35.2	34.8	35.2	35.0	35.0	35.0	35.0	35.4	35.5
80°	29.4	29.4	29.2	29.2	29.2	29.4	29.4	29.4	29.4	29.4	29.2
82.5°	23.5	23.7	23.9	23.5	23.9	23.7	23.5	23.9	24.1	23.7	23.9
85°	15.6	15.2	15.8	15.6	15.8	15.2	15.6	15.6	15.0	15.6	15.2
87.5°	13.7	13.4	13.5	13.8	13.5	13.4	13.7	13.2	13.0	12.8	12.4
90°	33.6	34.1	34.6	35.2	34.6	34.1	33.6	33.1	32.3	31.3	30.3
92.5°	48.4	48.1	47.7	47.4	47.7	48.1	48.4	48.7	48.4	47.6	46.8
95°	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.0	90.0	88.9
97.5°	141.1	141.0	140.9	140.8	140.9	141.0	141.1	141.2	140.7	139.5	138.3
100°	176.8	177.3	177.8	178.3	177.8	177.3	176.8	176.2	175.6	174.8	174.0
102.5°	217.1	217.0	216.9	216.8	216.9	217.0	217.1	217.2	216.9	216.1	215.3
105°	277.7	278.2	278.7	279.2	278.7	278.2	277.7	277.2	276.9	276.9	276.9
107.5°	345.2	344.9	344.6	344.3	344.6	344.9	345.2	345.5	345.3	344.5	343.6
110°	389.9	389.4	388.9	388.4	388.9	389.4	389.9	390.4	390.2	389.2	388.1



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	435.7	435.6	435.5	435.4	435.5	435.6	435.7	435.8	435.2	433.9	432.6
115°	500.6	500.4	500.1	499.9	500.1	500.4	500.6	500.9	500.9	500.6	500.4
117.5°	567.5	566.7	566.0	565.3	566.0	566.7	567.5	568.3	568.7	568.7	568.8
120°	612.9	612.4	611.9	611.3	611.9	612.4	612.9	613.4	613.8	614.1	614.3
122.5°	657.6	656.9	656.1	655.4	656.1	656.9	657.6	658.3	659.0	659.7	660.5
125°	724.8	723.7	722.7	721.6	722.7	723.7	724.8	725.8	726.8	727.9	728.9
127.5°	791.1	789.9	788.7	787.6	788.7	789.9	791.1	792.3	793.7	795.2	796.6
130°	836.2	834.4	832.5	830.7	832.5	834.4	836.2	838.0	839.5	840.5	841.5
132.5°	880.0	878.6	877.2	875.8	877.2	878.6	880.0	881.4	882.7	884.0	885.2
135°	947.3	946.7	946.2	945.7	946.2	946.7	947.3	947.8	948.6	949.6	950.7
137.5°	1010.4	1009.5	1008.5	1007.4	1008.5	1009.5	1010.4	1011.4	1012.4	1013.5	1014.6
140°	1053.3	1051.5	1049.7	1047.8	1049.7	1051.5	1053.3	1055.1	1056.1	1056.4	1056.6
142.5°	1093.3	1091.9	1090.6	1089.1	1090.6	1091.9	1093.3	1094.7	1095.6	1095.8	1096.1
145°	1151.9	1150.7	1149.7	1148.7	1149.7	1150.7	1151.9	1152.9	1153.6	1153.8	1154.1
147.5°	1206.4	1204.9	1203.3	1201.7	1203.3	1204.9	1206.4	1208.0	1208.8	1208.8	1208.8
150°	1240.2	1238.7	1237.1	1235.6	1237.1	1238.7	1240.2	1241.8	1242.5	1242.5	1242.5
152.5°	1272.4	1271.1	1269.7	1268.4	1269.7	1271.1	1272.4	1273.8	1274.2	1273.8	1273.4
155°	1318.5	1316.7	1314.8	1312.9	1314.8	1316.7	1318.5	1320.3	1320.7	1319.6	1318.6
157.5°	1358.0	1356.5	1355.0	1353.5	1355.0	1356.5	1358.0	1359.4	1359.6	1358.5	1357.4
160°	1383.0	1381.9	1380.9	1379.9	1380.9	1381.9	1383.0	1384.0	1383.9	1382.6	1381.3
162.5°	1404.5	1402.9	1401.2	1399.6	1401.2	1402.9	1404.5	1406.2	1406.4	1405.1	1403.8
165°	1433.4	1431.6	1429.8	1427.9	1429.8	1431.6	1433.4	1435.2	1435.4	1433.8	1432.3
167.5°	1456.9	1455.3	1453.7	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5	1456.9	1455.3
170°	1469.9	1467.9	1466.1	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7	1469.9	1467.9
172.5°	1479.1	1477.3	1475.5	1473.7	1475.5	1477.3	1479.1	1481.1	1481.2	1479.6	1477.9
175°	1489.8	1487.9	1486.1	1484.3	1486.1	1487.9	1489.8	1491.6	1491.7	1490.2	1488.5
177.5°	1494.3	1492.8	1491.4	1490.0	1491.4	1492.8	1494.3	1495.7	1495.8	1494.6	1493.4
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	524.6	527.3	529.9	532.3	536.0	537.8	540.2	541.2	543.9	548.1	551.5
5°	492.7	496.4	501.4	505.3	511.7	516.6	522.1	527.3	533.4	542.1	549.9
7.5°	465.6	469.3	475.2	482.7	489.7	496.8	504.1	511.2	519.9	532.4	544.7
10°	447.8	452.2	459.3	467.3	475.9	482.8	491.5	500.4	511.3	525.6	540.5
12.5°	432.3	435.7	443.8	451.4	461.3	470.0	478.5	489.0	501.3	516.5	534.4
15°	407.8	412.4	420.4	428.9	439.3	448.5	459.5	472.2	484.2	503.0	524.6
17.5°	383.0	390.2	398.6	408.1	415.8	428.5	440.4	453.4	468.3	488.2	512.0
20°	367.3	372.9	380.7	394.6	404.7	414.3	425.4	441.6	455.2	477.9	502.5
22.5°	353.9	358.0	366.8	378.2	390.0	401.1	412.4	427.9	444.7	466.2	492.9
25°	334.1	340.7	347.3	355.5	368.2	381.6	393.8	407.1	425.0	447.8	476.7
27.5°	314.8	320.7	327.2	337.3	347.0	359.5	372.3	387.4	406.6	430.7	460.1
30°	302.4	306.8	313.0	325.9	334.6	345.4	360.4	373.9	391.7	417.4	448.5
32.5°	289.5	295.3	302.1	311.9	322.8	333.0	346.7	361.2	379.5	404.8	436.6
35°	271.2	278.1	284.9	292.3	303.1	313.7	325.2	341.1	359.7	384.3	415.5
37.5°	254.5	259.9	265.5	274.6	284.8	294.9	305.7	321.4	338.9	365.4	394.0
40°	243.8	248.7	253.0	262.4	272.3	283.1	293.7	307.5	326.3	351.0	378.8
42.5°	232.1	236.6	242.4	250.1	260.7	269.8	280.4	293.6	311.2	336.4	360.7
45°	214.6	219.7	224.7	232.0	242.6	251.6	260.9	273.4	291.5	312.3	333.9
47.5°	196.3	201.6	207.2	214.3	223.5	232.6	242.0	253.0	269.5	289.8	304.5
50°	184.7	188.9	194.6	201.7	210.2	219.7	228.2	240.2	256.0	272.0	284.7
52.5°	172.7	176.5	182.9	190.4	198.2	206.6	215.6	225.9	240.1	255.2	265.3
55°	153.9	158.5	164.0	171.3	179.0	186.1	194.8	205.4	216.7	228.0	234.8
57.5°	136.3	140.3	144.8	152.3	159.1	167.4	175.3	183.5	194.0	202.5	206.9
60°	123.5	127.0	132.9	139.6	145.8	153.2	162.1	170.4	178.3	185.2	188.6
62.5°	111.5	115.5	120.7	126.7	133.6	140.6	148.3	155.3	162.4	168.2	170.7
65°	95.7	99.1	102.8	108.5	114.1	121.2	127.2	134.3	139.6	142.8	144.9
67.5°	81.5	83.6	86.4	90.3	95.8	102.0	107.9	113.4	117.8	120.0	121.9
70°	72.2	73.6	75.7	79.5	83.7	89.2	95.3	99.3	103.0	104.9	106.8
72.5°	63.0	64.8	66.8	69.8	73.2	77.2	81.6	86.4	88.6	90.8	91.9
75°	47.8	50.4	52.9	54.8	57.2	60.2	64.2	67.3	68.5	70.4	70.6
77.5°	36.1	36.7	38.5	40.8	42.8	45.0	47.6	50.3	50.9	51.8	52.5
80°	29.7	29.7	29.7	31.1	33.4	35.0	37.4	38.8	39.8	40.0	40.2
82.5°	23.8	23.8	23.6	23.9	24.7	25.7	27.8	29.4	30.2	30.0	29.5
85°	15.6	15.0	15.0	14.8	15.0	14.5	14.3	15.2	16.7	16.7	16.3
87.5°	12.2	11.8	11.3	10.5	9.6	8.8	7.6	7.3	6.8	7.0	6.3
90°	29.2	28.2	24.7	21.4	18.0	14.6	11.6	9.0	6.4	3.7	1.2
92.5°	45.8	45.0	43.1	41.2	39.3	37.4	35.4	33.7	31.9	30.2	28.4
95°	87.9	86.8	84.7	82.6	80.6	78.5	76.5	74.7	72.9	71.1	69.3
97.5°	137.0	135.8	134.3	132.9	131.4	129.9	128.4	127.0	125.7	124.3	123.0
100°	173.3	172.5	171.2	169.9	168.5	167.2	165.8	164.3	162.7	161.2	159.6
102.5°	214.6	213.8	212.1	210.4	208.6	206.9	205.6	204.6	203.7	202.8	201.8
105°	276.9	276.9	274.6	272.3	269.8	267.5	266.1	265.6	265.1	264.5	264.0
107.5°	342.7	341.9	340.9	340.0	339.1	338.2	337.5	337.2	336.9	336.6	336.3
110°	387.1	386.1	385.5	385.0	384.5	384.0	383.4	382.9	382.3	381.8	381.3



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	431.4	430.1	430.0	429.9	429.8	429.7	429.5	429.2	428.9	428.6	428.3
115°	500.1	499.9	500.4	500.9	501.4	501.9	501.8	501.0	500.2	499.5	498.7
117.5°	568.8	568.9	569.6	570.2	570.9	571.6	571.6	571.1	570.6	570.1	569.6
120°	614.6	614.8	616.1	617.4	618.7	620.1	620.0	618.3	616.8	615.2	613.7
122.5°	661.1	661.8	662.5	663.1	663.8	664.5	664.3	663.1	662.0	660.8	659.6
125°	729.9	731.0	731.5	732.1	732.6	733.1	733.0	732.2	731.3	730.6	729.8
127.5°	798.1	799.5	800.1	800.6	801.2	801.8	801.2	799.6	797.9	796.3	794.6
130°	842.6	843.6	844.4	845.2	846.0	846.8	846.1	844.0	841.9	839.8	837.8
132.5°	886.5	887.8	888.3	888.9	889.5	890.1	889.3	887.2	885.1	883.0	880.9
135°	951.7	952.7	953.0	953.3	953.5	953.8	953.1	951.6	950.0	948.5	946.8
137.5°	1015.7	1016.8	1016.1	1015.4	1014.8	1014.1	1013.1	1011.8	1010.5	1009.2	1007.9
140°	1056.9	1057.2	1056.9	1056.6	1056.4	1056.1	1055.3	1054.1	1052.8	1051.5	1050.2
142.5°	1096.3	1096.6	1096.1	1095.7	1095.2	1094.7	1093.9	1092.6	1091.3	1089.9	1088.6
145°	1154.3	1154.6	1153.8	1153.0	1152.3	1151.4	1150.7	1150.2	1149.7	1149.2	1148.7
147.5°	1208.8	1208.8	1208.0	1207.3	1206.6	1205.9	1205.1	1204.1	1203.2	1202.2	1201.2
150°	1242.5	1242.5	1242.0	1241.5	1241.0	1240.5	1240.0	1239.4	1238.9	1238.4	1237.9
152.5°	1273.0	1272.6	1272.3	1272.0	1271.6	1271.3	1270.8	1270.1	1269.4	1268.7	1267.9
155°	1317.6	1316.5	1316.3	1316.0	1315.8	1315.5	1315.3	1315.3	1315.3	1315.3	1315.3
157.5°	1356.3	1355.2	1355.0	1354.8	1354.6	1354.3	1354.4	1354.7	1355.0	1355.3	1355.6
160°	1380.0	1378.7	1378.7	1378.7	1378.7	1378.7	1379.0	1379.5	1380.0	1380.5	1381.0
162.5°	1402.5	1401.2	1401.0	1400.8	1400.6	1400.4	1400.7	1401.4	1402.1	1402.8	1403.5
165°	1430.7	1429.2	1429.2	1429.2	1429.2	1429.2	1429.6	1430.3	1431.1	1431.9	1432.7
167.5°	1453.7	1452.1	1451.9	1451.7	1451.5	1451.3	1451.7	1452.8	1453.8	1454.8	1455.9
170°	1466.1	1464.3	1464.3	1464.3	1464.3	1464.3	1464.8	1465.9	1466.9	1467.9	1469.1
172.5°	1476.3	1474.7	1474.7	1474.7	1474.7	1474.7	1475.2	1476.2	1477.2	1478.3	1479.4
175°	1487.0	1485.4	1485.4	1485.4	1485.4	1485.4	1486.0	1487.0	1488.0	1489.1	1490.2
177.5°	1492.1	1490.9	1490.9	1490.9	1490.9	1490.9	1491.3	1492.1	1493.0	1493.8	1494.6
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	552.6	554.7	557.3	561.3	564.3	566.9	567.4	568.3	570.2	573.3	575.7
5°	556.2	561.6	570.3	578.8	587.9	595.5	602.6	607.5	612.2	622.1	630.1
7.5°	555.0	567.1	580.8	595.9	611.4	626.2	640.1	652.5	664.8	679.2	695.6
10°	554.3	568.5	586.8	606.3	627.7	648.6	668.9	684.7	703.0	719.5	740.4
12.5°	550.8	571.1	593.0	617.9	644.3	668.4	695.1	716.8	737.8	761.6	786.0
15°	546.0	570.8	598.5	631.7	671.8	700.8	728.2	766.1	791.9	817.8	852.6
17.5°	537.6	567.7	602.4	645.5	678.8	718.1	759.1	789.1	823.9	860.4	891.9
20°	530.8	565.8	604.7	647.0	689.6	732.2	771.9	807.7	843.7	885.9	911.7
22.5°	524.0	558.7	599.1	644.0	689.7	734.7	779.6	821.6	862.1	904.6	937.7
25°	509.6	550.8	594.5	640.5	685.6	735.0	788.6	835.5	885.6	929.4	960.7
27.5°	495.0	532.8	576.3	622.9	673.1	731.4	794.6	847.8	898.0	929.4	939.2
30°	481.8	521.8	561.9	609.2	663.5	728.6	795.7	856.7	897.8	911.5	901.3
32.5°	468.5	504.7	544.3	592.8	650.5	721.6	797.2	851.4	876.2	865.8	824.6
35°	444.9	477.6	515.9	564.4	630.8	717.8	791.0	827.7	821.6	762.8	685.1
37.5°	419.7	446.4	481.8	532.5	610.4	702.6	764.3	769.7	716.7	626.4	536.7
40°	399.7	423.7	460.2	513.1	594.5	687.5	737.4	715.5	633.4	532.9	458.1
42.5°	380.3	400.6	435.8	492.8	579.5	666.9	697.3	649.6	554.9	459.9	391.8
45°	347.5	366.6	401.8	460.4	548.7	627.7	623.7	540.9	446.1	369.6	313.2
47.5°	316.4	333.1	366.2	426.0	512.5	568.9	531.5	443.3	362.9	301.5	261.3
50°	294.4	310.8	343.8	402.8	483.5	524.6	471.3	386.4	312.7	261.9	229.8
52.5°	273.3	289.3	319.4	377.0	448.5	473.1	415.8	337.0	275.6	231.8	204.3
55°	243.8	256.0	283.1	338.1	391.5	397.2	339.0	273.2	222.6	192.0	173.2
57.5°	213.7	224.2	251.0	294.8	332.2	329.3	274.3	217.2	183.2	160.5	146.8
60°	194.1	204.5	228.0	265.6	293.9	284.0	233.4	187.5	158.3	141.7	130.8
62.5°	175.8	183.9	206.0	233.5	253.8	242.6	199.5	161.6	138.4	124.3	115.7
65°	149.4	156.0	173.6	188.0	199.2	188.4	152.7	126.3	109.7	99.8	93.9
67.5°	124.3	128.5	139.6	144.8	152.8	140.9	114.8	97.1	87.7	79.4	75.2
70°	108.5	111.5	117.4	121.7	123.7	111.5	92.2	79.3	71.3	65.4	62.8
72.5°	92.6	95.3	96.5	100.0	98.9	87.5	74.1	63.8	58.1	54.1	50.8
75°	70.8	72.0	70.8	69.4	66.3	58.4	49.2	44.0	39.8	37.9	36.7
77.5°	51.6	51.2	49.7	47.5	42.2	37.2	32.2	30.5	28.7	27.7	27.3
80°	39.8	38.8	37.4	33.8	29.4	25.9	24.7	23.5	22.8	21.6	21.4
82.5°	29.6	29.0	26.7	23.7	20.6	18.9	18.0	17.5	16.8	16.2	16.2
85°	15.8	15.0	12.4	10.8	10.4	9.9	9.7	9.7	8.7	8.5	8.5
87.5°	5.9	5.3	5.6	5.6	6.2	6.5	7.3	7.6	8.1	8.5	8.3
90°	3.7	6.4	9.0	11.6	14.6	18.0	21.4	24.7	28.2	29.2	30.3
92.5°	30.2	31.9	33.7	35.4	37.4	39.3	41.2	43.1	45.0	45.8	46.8
95°	71.1	72.9	74.7	76.5	78.5	80.6	82.6	84.7	86.8	87.9	88.9
97.5°	124.3	125.7	127.0	128.4	129.9	131.4	132.9	134.3	135.8	137.0	138.3
100°	161.2	162.7	164.3	165.8	167.2	168.5	169.9	171.2	172.5	173.3	174.0
102.5°	202.8	203.7	204.6	205.6	206.9	208.6	210.4	212.1	213.8	214.6	215.3
105°	264.5	265.1	265.6	266.1	267.5	269.8	272.3	274.6	276.9	276.9	276.9
107.5°	336.6	336.9	337.2	337.5	338.2	339.1	340.0	340.9	341.9	342.7	343.6
110°	381.8	382.3	382.9	383.4	384.0	384.5	385.0	385.5	386.1	387.1	388.1





TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	428.6	428.9	429.2	429.5	429.7	429.8	429.9	430.0	430.1	431.4	432.6
115°	499.5	500.2	501.0	501.8	501.9	501.4	500.9	500.4	499.9	500.1	500.4
117.5°	570.1	570.6	571.1	571.6	571.6	570.9	570.2	569.6	568.9	568.8	568.8
120°	615.2	616.8	618.3	620.0	620.1	618.7	617.4	616.1	614.8	614.6	614.3
122.5°	660.8	662.0	663.1	664.3	664.5	663.8	663.1	662.5	661.8	661.1	660.5
125°	730.6	731.3	732.2	733.0	733.1	732.6	732.1	731.5	731.0	729.9	728.9
127.5°	796.3	797.9	799.6	801.2	801.8	801.2	800.6	800.1	799.5	798.1	796.6
130°	839.8	841.9	844.0	846.1	846.8	846.0	845.2	844.4	843.6	842.6	841.5
132.5°	883.0	885.1	887.2	889.3	890.1	889.5	888.9	888.3	887.8	886.5	885.2
135°	948.5	950.0	951.6	953.1	953.8	953.5	953.3	953.0	952.7	951.7	950.7
137.5°	1009.2	1010.5	1011.8	1013.1	1014.1	1014.8	1015.4	1016.1	1016.8	1015.7	1014.6
140°	1051.5	1052.8	1054.1	1055.3	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9	1056.6
142.5°	1089.9	1091.3	1092.6	1093.9	1094.7	1095.2	1095.7	1096.1	1096.6	1096.3	1096.1
145°	1149.2	1149.7	1150.2	1150.7	1151.4	1152.3	1153.0	1153.8	1154.6	1154.3	1154.1
147.5°	1202.2	1203.2	1204.1	1205.1	1205.9	1206.6	1207.3	1208.0	1208.8	1208.8	1208.8
150°	1238.4	1238.9	1239.4	1240.0	1240.5	1241.0	1241.5	1242.0	1242.5	1242.5	1242.5
152.5°	1268.7	1269.4	1270.1	1270.8	1271.3	1271.6	1272.0	1272.3	1272.6	1273.0	1273.4
155°	1315.3	1315.3	1315.3	1315.3	1315.5	1315.8	1316.0	1316.3	1316.5	1317.6	1318.6
157.5°	1355.3	1355.0	1354.7	1354.4	1354.3	1354.6	1354.8	1355.0	1355.2	1356.3	1357.4
160°	1380.5	1380.0	1379.5	1379.0	1378.7	1378.7	1378.7	1378.7	1378.7	1380.0	1381.3
162.5°	1402.8	1402.1	1401.4	1400.7	1400.4	1400.6	1400.8	1401.0	1401.2	1402.5	1403.8
165°	1431.9	1431.1	1430.3	1429.6	1429.2	1429.2	1429.2	1429.2	1429.2	1430.7	1432.3
167.5°	1454.8	1453.8	1452.8	1451.7	1451.3	1451.5	1451.7	1451.9	1452.1	1453.7	1455.3
170°	1467.9	1466.9	1465.9	1464.8	1464.3	1464.3	1464.3	1464.3	1464.3	1466.1	1467.9
172.5°	1478.3	1477.2	1476.2	1475.2	1474.7	1474.7	1474.7	1474.7	1474.7	1476.3	1477.9
175°	1489.1	1488.0	1487.0	1486.0	1485.4	1485.4	1485.4	1485.4	1485.4	1487.0	1488.5
177.5°	1493.8	1493.0	1492.1	1491.3	1490.9	1490.9	1490.9	1490.9	1490.9	1492.1	1493.4
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	579.8	579.8	580.5	583.3	583.7	586.1	585.4
5°	637.1	641.6	643.3	650.4	654.5	656.4	652.7
7.5°	707.3	719.9	725.9	733.4	739.8	741.8	736.7
10°	758.5	771.7	782.7	789.6	796.0	800.2	805.6
12.5°	808.0	824.3	834.8	844.3	850.9	856.3	857.2
15°	861.8	886.3	904.8	918.6	925.3	928.9	927.5
17.5°	916.0	938.8	952.0	965.9	975.3	975.8	976.1
20°	946.7	968.9	984.2	994.5	1005.1	1004.6	1007.0
22.5°	967.2	984.7	996.4	1003.9	1007.5	1005.7	1006.2
25°	976.8	982.1	980.0	968.0	964.8	953.8	955.7
27.5°	927.4	902.9	877.6	845.1	819.3	798.8	799.8
30°	860.2	816.9	767.5	726.1	688.9	678.5	656.4
32.5°	766.3	701.4	643.5	604.8	573.0	564.3	545.0
35°	607.0	543.9	484.4	448.7	434.5	414.8	414.5
37.5°	471.8	416.3	384.9	358.0	344.0	331.9	330.8
40°	396.9	353.7	329.8	310.5	296.7	287.7	285.6
42.5°	344.6	309.6	287.3	275.4	264.7	260.0	256.6
45°	281.3	257.8	242.4	231.6	226.6	223.1	221.2
47.5°	235.4	219.6	209.0	201.8	197.8	194.1	195.1
50°	210.4	197.4	189.7	182.8	179.8	177.1	177.4
52.5°	190.2	178.5	172.3	167.3	163.6	161.7	160.9
55°	161.4	154.1	147.7	144.2	142.1	139.6	138.9
57.5°	137.6	132.0	126.8	122.9	122.3	119.9	120.2
60°	121.9	117.1	112.9	110.8	109.2	107.0	107.8
62.5°	108.9	104.9	101.1	99.4	97.7	96.1	96.4
65°	89.2	85.4	83.0	82.1	81.4	80.7	80.0
67.5°	71.1	68.8	67.3	65.2	63.8	63.6	62.9
70°	59.8	56.7	54.1	51.5	50.8	50.6	50.8
72.5°	47.9	45.9	45.2	44.0	43.8	43.2	43.6
75°	36.0	35.2	34.8	33.8	33.8	33.8	33.8
77.5°	26.6	26.2	25.9	25.7	25.4	25.0	25.0
80°	20.7	20.5	20.0	20.0	19.8	20.0	19.8
82.5°	15.7	15.6	15.1	15.1	14.8	14.7	14.8
85°	8.0	7.8	8.3	7.8	8.0	7.6	8.0
87.5°	8.5	8.7	8.7	8.8	8.7	9.2	8.9
90°	31.3	32.3	33.1	33.6	34.1	34.6	35.2
92.5°	47.6	48.4	48.7	48.4	48.1	47.7	47.4
95°	90.0	91.0	91.5	91.5	91.5	91.5	91.5
97.5°	139.5	140.7	141.2	141.1	141.0	140.9	140.8
100°	174.8	175.6	176.2	176.8	177.3	177.8	178.3
102.5°	216.1	216.9	217.2	217.1	217.0	216.9	216.8
105°	276.9	276.9	277.2	277.7	278.2	278.7	279.2
107.5°	344.5	345.3	345.5	345.2	344.9	344.6	344.3
110°	389.2	390.2	390.4	389.9	389.4	388.9	388.4



TEST NUMBER: P332265-840

CATALOG NUMBER: S123RDIP-S340D1195U840-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	433.9	435.2	435.8	435.7	435.6	435.5	435.4
115°	500.6	500.9	500.9	500.6	500.4	500.1	499.9
117.5°	568.7	568.7	568.3	567.5	566.7	566.0	565.3
120°	614.1	613.8	613.4	612.9	612.4	611.9	611.3
122.5°	659.7	659.0	658.3	657.6	656.9	656.1	655.4
125°	727.9	726.8	725.8	724.8	723.7	722.7	721.6
127.5°	795.2	793.7	792.3	791.1	789.9	788.7	787.6
130°	840.5	839.5	838.0	836.2	834.4	832.5	830.7
132.5°	884.0	882.7	881.4	880.0	878.6	877.2	875.8
135°	949.6	948.6	947.8	947.3	946.7	946.2	945.7
137.5°	1013.5	1012.4	1011.4	1010.4	1009.5	1008.5	1007.4
140°	1056.4	1056.1	1055.1	1053.3	1051.5	1049.7	1047.8
142.5°	1095.8	1095.6	1094.7	1093.3	1091.9	1090.6	1089.1
145°	1153.8	1153.6	1152.9	1151.9	1150.7	1149.7	1148.7
147.5°	1208.8	1208.8	1208.0	1206.4	1204.9	1203.3	1201.7
150°	1242.5	1242.5	1241.8	1240.2	1238.7	1237.1	1235.6
152.5°	1273.8	1274.2	1273.8	1272.4	1271.1	1269.7	1268.4
155°	1319.6	1320.7	1320.3	1318.5	1316.7	1314.8	1312.9
157.5°	1358.5	1359.6	1359.4	1358.0	1356.5	1355.0	1353.5
160°	1382.6	1383.9	1384.0	1383.0	1381.9	1380.9	1379.9
162.5°	1405.1	1406.4	1406.2	1404.5	1402.9	1401.2	1399.6
165°	1433.8	1435.4	1435.2	1433.4	1431.6	1429.8	1427.9
167.5°	1456.9	1458.5	1458.5	1456.9	1455.3	1453.7	1452.1
170°	1469.9	1471.7	1471.7	1469.9	1467.9	1466.1	1464.3
172.5°	1479.6	1481.2	1481.1	1479.1	1477.3	1475.5	1473.7
175°	1490.2	1491.7	1491.6	1489.8	1487.9	1486.1	1484.3
177.5°	1494.6	1495.8	1495.7	1494.3	1492.8	1491.4	1490.0
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7

(END OF REPORT)