

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332325-840

Luminaire Tested: **S123RDIP-S775D1195U840-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332325-840
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIP-S775D1195U840-4F0-1E-UDD-A1
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 775 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 1195 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7218.0 lumens
Efficiency: N/A
Efficacy: 126.9 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 56.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

Luminous Intensity Polar Plot



57% Up

43% Dn



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	105	105	105	105	96	96	96	96	79	79	79	64	64	64	49	49	49	43																												
1	97	93	89	86	88	85	82	79	70	68	66	57	55	54	44	43	43	37																												
2	88	81	76	71	81	75	70	65	62	58	55	50	48	46	40	38	37	32																												
3	81	72	65	59	74	66	60	55	55	51	47	45	42	39	36	34	32	27																												
4	74	64	56	51	68	59	52	47	49	44	41	40	37	34	32	30	28	24																												
5	68	57	49	44	62	53	46	41	44	39	35	36	33	30	29	27	24	21																												
6	63	51	44	38	57	47	41	36	40	35	31	33	29	26	27	24	22	19																												
7	58	46	39	33	53	43	36	31	36	31	27	30	26	23	24	22	19	17																												
8	54	42	35	30	49	39	32	28	33	28	24	28	24	21	22	20	18	15																												
9	50	39	31	26	46	36	29	25	30	25	22	25	22	19	21	18	16	14																												
10	47	35	28	24	43	33	27	22	28	23	20	24	20	17	19	17	15	13																												

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	13295	13295	13295	13295
5°	15847	13351	11757	13351
10°	19787	13274	10622	13274
15°	23226	13138	9686	13138
20°	25921	12936	8891	12936
25°	25508	12722	8402	12722
30°	18334	12525	7899	12525
35°	12242	12269	7573	12269
40°	9020	11960	7235	11960
45°	7566	11420	6905	11420
50°	6677	10712	6445	10712
55°	5853	9903	5814	9903
60°	5214	9128	5326	9128
65°	4579	8295	4956	8295
70°	3594	7553	4526	7553
75°	3165	6596	4134	6596
80°	2752	5604	4060	5604
85°	2223	4508	4310	4508



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	121.5	1.7
10°-20°	379.5	5.3
20°-30°	596.1	8.3
30°-40°	621.9	8.6
40°-50°	532.3	7.4
50°-60°	405.7	5.6
60°-70°	260.0	3.6
70°-80°	125.1	1.7
80°-90°	37.5	0.5
90°-100°	97.3	1.3
100°-110°	291.2	4.0
110°-120°	495.4	6.9
120°-130°	651.6	9.0
130°-140°	732.3	10.1
140°-150°	719.9	10.0
150°-160°	606.0	8.4
160°-170°	403.4	5.6
170°-180°	141.3	2.0
0°-30°	1097.0	15.2
0°-40°	1719.0	23.8
0°-60°	2656.9	36.8
0°-90°	3079.5	42.7
90°-120°	883.9	12.2
90°-150°	2987.7	41.4
90°-180°	4138.0	57.3
0°-180°	7218.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1235	1235	1235	1235	1235	
5°	1467	1236	1088	1236	1467	151
15°	2084	1179	869	1179	2084	591
25°	2148	1071	707	1071	2148	923
35°	932	934	576	934	932	611
45°	497	750	454	750	497	391
55°	312	528	310	528	312	282
65°	180	326	195	326	180	177
75°	76	159	99	159	76	82
85°	18	36	35	36	18	22
90°	35	1	35	1	35	18
95°	92	69	92	69	92	94
105°	279	264	279	264	279	296
115°	500	499	500	499	500	495
125°	722	730	722	730	722	645
135°	946	947	946	947	946	727
145°	1149	1149	1149	1149	1149	717
155°	1313	1315	1313	1315	1313	605
165°	1428	1433	1428	1433	1428	403
175°	1484	1490	1484	1490	1484	141
180°	1494	1494	1494	1494	1494	



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1315.5	1317.2	1311.6	1310.8	1304.4	1302.7	1302.7	1293.8	1288.4	1281.2	1277.0
5°	1466.6	1475.1	1470.9	1461.4	1445.5	1441.8	1431.8	1415.9	1398.0	1375.7	1365.1
7.5°	1655.5	1667.1	1662.6	1647.9	1631.3	1617.9	1589.5	1563.2	1526.3	1493.9	1466.2
10°	1810.3	1798.2	1788.7	1774.3	1759.1	1734.1	1704.6	1663.9	1616.8	1579.8	1538.5
12.5°	1926.2	1924.2	1912.2	1897.4	1875.8	1852.2	1815.8	1766.3	1711.5	1658.1	1610.9
15°	2084.2	2087.4	2079.4	2064.1	2033.5	1991.7	1936.7	1916.0	1837.9	1779.7	1721.5
17.5°	2193.5	2192.9	2191.8	2170.6	2139.3	2109.6	2058.6	2004.4	1933.5	1851.6	1773.2
20°	2262.9	2257.7	2258.7	2234.8	2211.6	2177.3	2127.6	2048.8	1990.6	1896.0	1815.0
22.5°	2261.2	2260.2	2264.2	2256.0	2239.1	2212.8	2173.6	2107.2	2033.0	1937.4	1846.3
25°	2147.7	2143.4	2168.3	2175.1	2202.1	2206.9	2195.2	2158.8	2088.4	1990.0	1877.4
27.5°	1797.5	1795.1	1841.2	1899.0	1972.1	2029.0	2084.0	2110.5	2088.4	2018.0	1905.2
30°	1475.1	1524.8	1548.1	1631.6	1724.6	1835.7	1933.0	2025.5	2048.2	2017.6	1925.0
32.5°	1224.8	1268.1	1287.5	1359.2	1445.9	1576.0	1721.9	1852.9	1945.5	1968.9	1913.2
35°	931.6	932.1	976.5	1008.2	1088.6	1222.3	1364.1	1539.6	1714.0	1846.2	1860.0
37.5°	743.4	746.0	772.8	804.5	864.7	935.5	1060.3	1206.2	1407.8	1610.6	1729.6
40°	641.9	646.6	666.7	697.9	741.2	794.7	891.9	1029.5	1197.5	1423.3	1607.8
42.5°	576.7	584.4	594.8	618.8	645.7	695.7	774.4	880.5	1033.4	1246.9	1459.8
45°	497.0	501.2	509.2	520.3	544.6	579.5	632.4	703.7	830.6	1002.5	1215.5
47.5°	438.4	436.2	444.5	453.5	469.7	493.5	529.0	587.2	677.7	815.6	996.3
50°	398.7	398.1	403.9	410.8	426.2	443.6	472.7	516.5	588.4	702.7	868.2
52.5°	361.4	363.5	367.6	376.2	387.2	401.3	427.4	459.0	520.8	619.4	757.3
55°	311.9	313.6	319.3	324.1	332.0	346.3	362.7	389.1	431.4	500.2	613.8
57.5°	270.0	269.3	274.9	276.1	285.1	296.7	309.4	329.9	360.6	411.6	488.2
60°	242.2	240.5	245.3	249.0	253.8	263.3	273.9	294.0	318.3	355.8	421.4
62.5°	216.8	216.0	219.5	223.2	227.1	235.8	244.7	260.1	279.3	311.0	363.0
65°	179.8	181.4	182.9	184.5	186.6	191.9	200.4	211.0	224.2	246.4	283.9
67.5°	141.3	142.9	143.4	146.6	151.2	154.5	159.7	169.1	178.2	197.0	218.3
70°	114.2	113.7	114.2	115.8	121.6	127.4	134.3	141.2	146.9	160.2	178.1
72.5°	98.2	97.1	98.6	98.9	101.7	103.3	107.7	114.1	121.6	130.6	143.5
75°	76.1	76.1	76.1	76.1	78.3	79.3	80.9	82.5	85.1	89.4	98.9
77.5°	56.2	56.4	57.1	57.7	58.1	58.7	59.7	61.2	62.2	64.4	68.6
80°	44.4	44.9	44.4	44.9	44.9	45.9	46.6	48.1	48.7	51.3	52.9
82.5°	33.4	33.1	33.4	33.9	33.9	35.0	35.1	36.3	36.4	37.8	39.4
85°	18.0	17.0	18.0	17.5	18.5	17.5	18.0	19.0	19.0	19.6	21.7
87.5°	11.3	12.0	11.1	11.4	11.3	11.5	11.3	11.1	11.7	11.1	10.9
90°	35.2	34.6	34.1	33.6	33.1	32.3	31.3	30.3	29.2	28.2	24.7
92.5°	47.4	47.7	48.1	48.4	48.7	48.4	47.6	46.8	45.8	45.0	43.1
95°	91.5	91.5	91.5	91.5	91.5	91.0	90.0	88.9	87.9	86.8	84.7
97.5°	140.8	140.9	141.0	141.1	141.2	140.7	139.5	138.3	137.0	135.8	134.3
100°	178.3	177.8	177.3	176.8	176.2	175.6	174.8	174.0	173.3	172.5	171.2
102.5°	216.8	216.9	217.0	217.1	217.2	216.9	216.1	215.3	214.6	213.8	212.1
105°	279.2	278.7	278.2	277.7	277.2	276.9	276.9	276.9	276.9	276.9	274.6
107.5°	344.3	344.6	344.9	345.2	345.5	345.3	344.5	343.6	342.7	341.9	340.9
110°	388.4	388.9	389.4	389.9	390.4	390.2	389.2	388.1	387.1	386.1	385.5



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	435.4	435.5	435.6	435.7	435.8	435.2	433.9	432.6	431.4	430.1	430.0
115°	499.9	500.1	500.4	500.6	500.9	500.9	500.6	500.4	500.1	499.9	500.4
117.5°	565.3	566.0	566.7	567.5	568.3	568.7	568.7	568.8	568.8	568.9	569.6
120°	611.3	611.9	612.4	612.9	613.4	613.8	614.1	614.3	614.6	614.8	616.1
122.5°	655.4	656.1	656.9	657.6	658.3	659.0	659.7	660.5	661.1	661.8	662.5
125°	721.6	722.7	723.7	724.8	725.8	726.8	727.9	728.9	729.9	731.0	731.5
127.5°	787.6	788.7	789.9	791.1	792.3	793.7	795.2	796.6	798.1	799.5	800.1
130°	830.7	832.5	834.4	836.2	838.0	839.5	840.5	841.5	842.6	843.6	844.4
132.5°	875.8	877.2	878.6	880.0	881.4	882.7	884.0	885.2	886.5	887.8	888.3
135°	945.7	946.2	946.7	947.3	947.8	948.6	949.6	950.7	951.7	952.7	953.0
137.5°	1007.4	1008.5	1009.5	1010.4	1011.4	1012.4	1013.5	1014.6	1015.7	1016.8	1016.1
140°	1047.8	1049.7	1051.5	1053.3	1055.1	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9
142.5°	1089.1	1090.6	1091.9	1093.3	1094.7	1095.6	1095.8	1096.1	1096.3	1096.6	1096.1
145°	1148.7	1149.7	1150.7	1151.9	1152.9	1153.6	1153.8	1154.1	1154.3	1154.6	1153.8
147.5°	1201.7	1203.3	1204.9	1206.4	1208.0	1208.8	1208.8	1208.8	1208.8	1208.8	1208.0
150°	1235.6	1237.1	1238.7	1240.2	1241.8	1242.5	1242.5	1242.5	1242.5	1242.5	1242.0
152.5°	1268.4	1269.7	1271.1	1272.4	1273.8	1274.2	1273.8	1273.4	1273.0	1272.6	1272.3
155°	1312.9	1314.8	1316.7	1318.5	1320.3	1320.7	1319.6	1318.6	1317.6	1316.5	1316.3
157.5°	1353.5	1355.0	1356.5	1358.0	1359.4	1359.6	1358.5	1357.4	1356.3	1355.2	1355.0
160°	1379.9	1380.9	1381.9	1383.0	1384.0	1383.9	1382.6	1381.3	1380.0	1378.7	1378.7
162.5°	1399.6	1401.2	1402.9	1404.5	1406.2	1406.4	1405.1	1403.8	1402.5	1401.2	1401.0
165°	1427.9	1429.8	1431.6	1433.4	1435.2	1435.4	1433.8	1432.3	1430.7	1429.2	1429.2
167.5°	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5	1456.9	1455.3	1453.7	1452.1	1451.9
170°	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7	1469.9	1467.9	1466.1	1464.3	1464.3
172.5°	1473.7	1475.5	1477.3	1479.1	1481.1	1481.2	1479.6	1477.9	1476.3	1474.7	1474.7
175°	1484.3	1486.1	1487.9	1489.8	1491.6	1491.7	1490.2	1488.5	1487.0	1485.4	1485.4
177.5°	1490.0	1491.4	1492.8	1494.3	1495.7	1495.8	1494.6	1493.4	1492.1	1490.9	1490.9
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1275.3	1273.9	1268.1	1261.3	1252.4	1246.5	1241.8	1239.3	1231.7	1222.3	1216.1
5°	1354.0	1338.2	1321.3	1300.6	1281.6	1262.0	1249.9	1235.6	1218.2	1198.6	1184.9
7.5°	1438.5	1407.3	1373.8	1339.3	1305.0	1274.4	1247.4	1224.2	1196.4	1168.3	1148.7
10°	1503.2	1457.6	1410.6	1362.5	1318.6	1277.4	1245.7	1214.5	1181.1	1148.9	1124.6
12.5°	1562.0	1502.1	1447.8	1388.8	1332.6	1283.3	1237.6	1200.9	1160.8	1126.5	1098.7
15°	1636.4	1575.1	1509.4	1419.6	1345.0	1282.6	1227.2	1179.0	1130.4	1088.1	1061.2
17.5°	1706.0	1613.7	1525.6	1450.6	1353.7	1275.8	1208.0	1150.4	1097.1	1052.3	1019.1
20°	1734.7	1645.4	1549.6	1454.0	1358.8	1271.5	1192.8	1129.3	1073.8	1023.1	992.4
22.5°	1752.0	1650.8	1550.0	1447.2	1346.2	1255.5	1177.6	1107.7	1047.6	999.4	961.5
25°	1772.2	1651.7	1540.7	1439.2	1336.1	1237.7	1145.2	1071.2	1006.1	954.8	914.6
27.5°	1785.5	1643.8	1512.6	1399.7	1295.2	1197.2	1112.4	1034.0	968.0	913.7	870.6
30°	1788.1	1637.4	1491.0	1368.9	1262.5	1172.7	1082.8	1007.7	938.0	880.3	840.1
32.5°	1791.5	1621.7	1461.8	1332.0	1223.2	1134.2	1052.8	981.1	909.6	852.8	811.8
35°	1777.6	1613.2	1417.4	1268.4	1159.4	1073.3	999.8	933.7	863.4	808.4	766.6
37.5°	1717.5	1578.7	1371.6	1196.7	1082.8	1003.0	943.1	885.4	821.0	761.6	722.4
40°	1657.0	1544.9	1336.1	1153.2	1034.2	952.2	898.3	851.2	788.8	733.4	691.1
42.5°	1566.9	1498.8	1302.2	1107.4	979.2	900.2	854.7	810.6	755.9	699.5	659.7
45°	1401.6	1410.6	1232.9	1034.7	903.0	823.7	780.9	750.2	701.7	655.1	614.4
47.5°	1194.4	1278.4	1151.7	957.2	822.7	748.3	710.9	684.2	651.4	605.7	568.6
50°	1059.0	1179.0	1086.5	905.1	772.4	698.4	661.5	639.7	611.2	575.2	539.8
52.5°	934.2	1063.2	1007.8	847.2	717.9	650.3	614.1	596.2	573.5	539.7	507.7
55°	761.8	892.5	879.8	759.7	636.0	575.2	547.8	527.7	512.3	487.0	461.6
57.5°	616.3	740.1	746.7	662.5	563.9	503.8	480.2	465.0	455.0	435.9	412.4
60°	524.5	638.1	660.4	596.9	512.3	459.5	436.2	424.0	416.1	400.8	382.8
62.5°	448.4	545.1	570.3	524.6	462.8	413.3	395.2	383.4	378.0	364.8	348.9
65°	343.2	423.5	447.8	422.4	390.2	350.5	335.8	325.7	320.9	313.6	301.8
67.5°	258.0	316.6	343.3	325.4	313.8	288.7	279.2	273.9	269.6	264.6	254.9
70°	207.2	250.6	278.1	273.4	263.9	250.6	243.8	240.0	235.8	231.6	223.1
72.5°	166.6	196.5	222.3	224.7	216.9	214.2	208.2	206.6	204.1	199.0	194.4
75°	110.5	131.1	149.1	155.9	159.2	161.8	159.2	158.6	158.0	153.9	151.2
77.5°	72.4	83.5	94.8	106.5	111.6	115.1	116.0	118.0	116.5	114.3	113.0
80°	55.5	58.2	66.0	76.1	84.0	87.3	89.4	90.4	89.9	89.4	87.3
82.5°	40.3	42.5	46.3	53.3	60.0	65.2	66.6	66.3	67.5	67.8	66.0
85°	21.7	22.2	23.2	24.3	28.0	33.8	35.4	36.5	37.6	37.6	34.3
87.5°	11.0	9.9	10.1	9.5	10.3	10.2	12.2	13.7	14.7	13.5	14.0
90°	21.4	18.0	14.6	11.6	9.0	6.4	3.7	1.2	3.7	6.4	9.0
92.5°	41.2	39.3	37.4	35.4	33.7	31.9	30.2	28.4	30.2	31.9	33.7
95°	82.6	80.6	78.5	76.5	74.7	72.9	71.1	69.3	71.1	72.9	74.7
97.5°	132.9	131.4	129.9	128.4	127.0	125.7	124.3	123.0	124.3	125.7	127.0
100°	169.9	168.5	167.2	165.8	164.3	162.7	161.2	159.6	161.2	162.7	164.3
102.5°	210.4	208.6	206.9	205.6	204.6	203.7	202.8	201.8	202.8	203.7	204.6
105°	272.3	269.8	267.5	266.1	265.6	265.1	264.5	264.0	264.5	265.1	265.6
107.5°	340.0	339.1	338.2	337.5	337.2	336.9	336.6	336.3	336.6	336.9	337.2
110°	385.0	384.5	384.0	383.4	382.9	382.3	381.8	381.3	381.8	382.3	382.9



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	429.9	429.8	429.7	429.5	429.2	428.9	428.6	428.3	428.6	428.9	429.2
115°	500.9	501.4	501.9	501.8	501.0	500.2	499.5	498.7	499.5	500.2	501.0
117.5°	570.2	570.9	571.6	571.6	571.1	570.6	570.1	569.6	570.1	570.6	571.1
120°	617.4	618.7	620.1	620.0	618.3	616.8	615.2	613.7	615.2	616.8	618.3
122.5°	663.1	663.8	664.5	664.3	663.1	662.0	660.8	659.6	660.8	662.0	663.1
125°	732.1	732.6	733.1	733.0	732.2	731.3	730.6	729.8	730.6	731.3	732.2
127.5°	800.6	801.2	801.8	801.2	799.6	797.9	796.3	794.6	796.3	797.9	799.6
130°	845.2	846.0	846.8	846.1	844.0	841.9	839.8	837.8	839.8	841.9	844.0
132.5°	888.9	889.5	890.1	889.3	887.2	885.1	883.0	880.9	883.0	885.1	887.2
135°	953.3	953.5	953.8	953.1	951.6	950.0	948.5	946.8	948.5	950.0	951.6
137.5°	1015.4	1014.8	1014.1	1013.1	1011.8	1010.5	1009.2	1007.9	1009.2	1010.5	1011.8
140°	1056.6	1056.4	1056.1	1055.3	1054.1	1052.8	1051.5	1050.2	1051.5	1052.8	1054.1
142.5°	1095.7	1095.2	1094.7	1093.9	1092.6	1091.3	1089.9	1088.6	1089.9	1091.3	1092.6
145°	1153.0	1152.3	1151.4	1150.7	1150.2	1149.7	1149.2	1148.7	1149.2	1149.7	1150.2
147.5°	1207.3	1206.6	1205.9	1205.1	1204.1	1203.2	1202.2	1201.2	1202.2	1203.2	1204.1
150°	1241.5	1241.0	1240.5	1240.0	1239.4	1238.9	1238.4	1237.9	1238.4	1238.9	1239.4
152.5°	1272.0	1271.6	1271.3	1270.8	1270.1	1269.4	1268.7	1267.9	1268.7	1269.4	1270.1
155°	1316.0	1315.8	1315.5	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3	1315.3
157.5°	1354.8	1354.6	1354.3	1354.4	1354.7	1355.0	1355.3	1355.6	1355.3	1355.0	1354.7
160°	1378.7	1378.7	1378.7	1379.0	1379.5	1380.0	1380.5	1381.0	1380.5	1380.0	1379.5
162.5°	1400.8	1400.6	1400.4	1400.7	1401.4	1402.1	1402.8	1403.5	1402.8	1402.1	1401.4
165°	1429.2	1429.2	1429.2	1429.6	1430.3	1431.1	1431.9	1432.7	1431.9	1431.1	1430.3
167.5°	1451.7	1451.5	1451.3	1451.7	1452.8	1453.8	1454.8	1455.9	1454.8	1453.8	1452.8
170°	1464.3	1464.3	1464.3	1464.8	1465.9	1466.9	1467.9	1469.1	1467.9	1466.9	1465.9
172.5°	1474.7	1474.7	1474.7	1475.2	1476.2	1477.2	1478.3	1479.4	1478.3	1477.2	1476.2
175°	1485.4	1485.4	1485.4	1486.0	1487.0	1488.0	1489.1	1490.2	1489.1	1488.0	1487.0
177.5°	1490.9	1490.9	1490.9	1491.3	1492.1	1493.0	1493.8	1494.6	1493.8	1493.0	1492.1
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1214.0	1208.4	1204.7	1196.2	1190.6	1184.8	1178.8	1182.7	1182.2	1181.7	1181.7
5°	1173.3	1161.0	1149.9	1135.7	1126.7	1115.6	1107.1	1106.1	1108.2	1100.8	1096.5
7.5°	1132.9	1116.2	1100.4	1084.7	1068.0	1054.7	1046.3	1042.4	1037.0	1032.5	1027.7
10°	1104.5	1084.9	1069.5	1050.1	1032.1	1016.2	1006.1	999.3	995.5	991.9	985.0
12.5°	1075.3	1056.1	1036.6	1014.5	997.3	979.0	971.5	963.7	956.6	952.5	943.1
15°	1032.6	1007.7	987.1	963.8	944.8	926.9	916.3	900.9	898.8	893.5	884.0
17.5°	989.8	962.8	934.3	917.2	895.6	877.0	860.8	855.7	840.5	834.9	826.6
20°	955.9	931.1	909.4	886.7	855.5	838.0	825.4	818.5	806.3	798.9	793.6
22.5°	926.8	901.5	876.4	849.9	824.2	804.6	795.3	784.6	778.0	767.6	761.8
25°	885.0	857.6	827.5	798.9	780.4	765.6	750.7	741.2	731.7	727.0	716.4
27.5°	836.7	807.9	779.7	758.1	735.4	720.7	707.3	698.8	687.4	679.4	673.6
30°	810.0	776.2	751.8	732.3	703.2	689.4	679.4	668.8	660.4	651.9	646.1
32.5°	779.1	748.2	725.2	700.9	678.6	663.7	650.7	641.4	634.1	626.1	620.3
35°	730.6	704.8	681.0	656.6	640.3	624.9	609.7	601.7	594.8	587.4	582.1
37.5°	686.9	662.7	640.1	617.0	596.7	584.2	571.9	565.8	556.5	551.6	546.1
40°	659.8	636.0	611.7	589.6	568.4	558.9	547.8	538.8	530.3	526.6	520.8
42.5°	630.3	606.4	585.9	562.0	544.7	531.8	521.5	511.7	505.3	500.0	496.7
45°	586.3	565.2	545.1	521.3	504.9	493.8	482.2	473.2	467.4	463.7	457.9
47.5°	543.7	522.6	502.2	481.4	465.5	452.9	441.3	435.0	427.3	422.7	418.9
50°	512.8	493.8	472.1	453.1	437.3	424.5	415.1	407.1	400.2	394.5	391.8
52.5°	484.5	464.2	445.5	427.8	411.0	396.7	388.0	379.6	374.5	367.8	364.7
55°	437.8	418.2	402.3	384.9	368.5	356.4	345.8	338.4	333.1	325.7	321.4
57.5°	393.8	376.4	357.4	342.2	325.4	315.1	306.3	296.3	289.8	284.1	279.9
60°	364.3	344.2	327.8	313.6	298.7	285.5	277.6	269.6	262.8	256.9	253.3
62.5°	333.5	315.9	300.3	284.8	271.2	259.7	250.5	243.9	237.8	234.1	230.5
65°	286.0	272.3	256.4	243.8	231.1	222.6	215.2	209.3	205.1	202.5	199.3
67.5°	242.5	229.1	215.3	202.8	194.4	187.9	183.1	178.0	175.9	172.6	170.5
70°	214.1	200.4	188.2	178.7	170.3	165.5	162.3	158.6	156.5	152.3	150.2
72.5°	183.3	173.3	164.5	156.7	150.0	145.6	141.6	137.0	133.7	129.0	126.9
75°	144.3	135.3	128.5	123.2	119.0	113.1	107.3	102.6	101.0	99.4	98.9
77.5°	106.9	101.2	96.2	91.8	86.5	82.3	81.0	80.0	79.6	78.8	78.8
80°	84.0	78.8	75.0	69.8	66.7	66.7	66.7	65.5	66.0	66.0	66.0
82.5°	62.5	57.7	55.6	53.7	53.1	53.5	53.5	53.7	53.4	54.2	53.8
85°	32.2	32.8	33.8	33.3	33.8	33.8	34.9	34.3	34.9	33.8	34.9
87.5°	14.1	16.1	17.2	18.3	19.3	19.6	20.2	20.4	21.1	21.3	21.4
90°	11.6	14.6	18.0	21.4	24.7	28.2	29.2	30.3	31.3	32.3	33.1
92.5°	35.4	37.4	39.3	41.2	43.1	45.0	45.8	46.8	47.6	48.4	48.7
95°	76.5	78.5	80.6	82.6	84.7	86.8	87.9	88.9	90.0	91.0	91.5
97.5°	128.4	129.9	131.4	132.9	134.3	135.8	137.0	138.3	139.5	140.7	141.2
100°	165.8	167.2	168.5	169.9	171.2	172.5	173.3	174.0	174.8	175.6	176.2
102.5°	205.6	206.9	208.6	210.4	212.1	213.8	214.6	215.3	216.1	216.9	217.2
105°	266.1	267.5	269.8	272.3	274.6	276.9	276.9	276.9	276.9	276.9	277.2
107.5°	337.5	338.2	339.1	340.0	340.9	341.9	342.7	343.6	344.5	345.3	345.5
110°	383.4	384.0	384.5	385.0	385.5	386.1	387.1	388.1	389.2	390.2	390.4



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	429.5	429.7	429.8	429.9	430.0	430.1	431.4	432.6	433.9	435.2	435.8
115°	501.8	501.9	501.4	500.9	500.4	499.9	500.1	500.4	500.6	500.9	500.9
117.5°	571.6	571.6	570.9	570.2	569.6	568.9	568.8	568.8	568.7	568.7	568.3
120°	620.0	620.1	618.7	617.4	616.1	614.8	614.6	614.3	614.1	613.8	613.4
122.5°	664.3	664.5	663.8	663.1	662.5	661.8	661.1	660.5	659.7	659.0	658.3
125°	733.0	733.1	732.6	732.1	731.5	731.0	729.9	728.9	727.9	726.8	725.8
127.5°	801.2	801.8	801.2	800.6	800.1	799.5	798.1	796.6	795.2	793.7	792.3
130°	846.1	846.8	846.0	845.2	844.4	843.6	842.6	841.5	840.5	839.5	838.0
132.5°	889.3	890.1	889.5	888.9	888.3	887.8	886.5	885.2	884.0	882.7	881.4
135°	953.1	953.8	953.5	953.3	953.0	952.7	951.7	950.7	949.6	948.6	947.8
137.5°	1013.1	1014.1	1014.8	1015.4	1016.1	1016.8	1015.7	1014.6	1013.5	1012.4	1011.4
140°	1055.3	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9	1056.6	1056.4	1056.1	1055.1
142.5°	1093.9	1094.7	1095.2	1095.7	1096.1	1096.6	1096.3	1096.1	1095.8	1095.6	1094.7
145°	1150.7	1151.4	1152.3	1153.0	1153.8	1154.6	1154.3	1154.1	1153.8	1153.6	1152.9
147.5°	1205.1	1205.9	1206.6	1207.3	1208.0	1208.8	1208.8	1208.8	1208.8	1208.8	1208.0
150°	1240.0	1240.5	1241.0	1241.5	1242.0	1242.5	1242.5	1242.5	1242.5	1242.5	1241.8
152.5°	1270.8	1271.3	1271.6	1272.0	1272.3	1272.6	1273.0	1273.4	1273.8	1274.2	1273.8
155°	1315.3	1315.5	1315.8	1316.0	1316.3	1316.5	1317.6	1318.6	1319.6	1320.7	1320.3
157.5°	1354.4	1354.3	1354.6	1354.8	1355.0	1355.2	1356.3	1357.4	1358.5	1359.6	1359.4
160°	1379.0	1378.7	1378.7	1378.7	1378.7	1378.7	1380.0	1381.3	1382.6	1383.9	1384.0
162.5°	1400.7	1400.4	1400.6	1400.8	1401.0	1401.2	1402.5	1403.8	1405.1	1406.4	1406.2
165°	1429.6	1429.2	1429.2	1429.2	1429.2	1429.2	1430.7	1432.3	1433.8	1435.4	1435.2
167.5°	1451.7	1451.3	1451.5	1451.7	1451.9	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5
170°	1464.8	1464.3	1464.3	1464.3	1464.3	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7
172.5°	1475.2	1474.7	1474.7	1474.7	1474.7	1474.7	1476.3	1477.9	1479.6	1481.2	1481.1
175°	1486.0	1485.4	1485.4	1485.4	1485.4	1485.4	1487.0	1488.5	1490.2	1491.7	1491.6
177.5°	1491.3	1490.9	1490.9	1490.9	1490.9	1490.9	1492.1	1493.4	1494.6	1495.8	1495.7
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1176.7	1176.3	1176.7	1175.0	1176.7	1176.3	1176.7	1181.7	1181.7	1182.2	1182.7
5°	1095.0	1094.4	1092.9	1088.1	1092.9	1094.4	1095.0	1096.5	1100.8	1108.2	1106.1
7.5°	1023.6	1022.9	1018.2	1018.3	1018.2	1022.9	1023.6	1027.7	1032.5	1037.0	1042.4
10°	981.3	981.8	975.5	971.8	975.5	981.8	981.3	985.0	991.9	995.5	999.3
12.5°	940.3	937.9	932.7	928.7	932.7	937.9	940.3	943.1	952.5	956.6	963.7
15°	886.2	880.8	868.2	869.2	868.2	880.8	886.2	884.0	893.5	898.8	900.9
17.5°	822.3	818.5	818.2	810.8	818.2	818.5	822.3	826.6	834.9	840.5	855.7
20°	785.2	782.5	783.6	776.2	783.6	782.5	785.2	793.6	798.9	806.3	818.5
22.5°	756.0	753.4	748.9	746.6	748.9	753.4	756.0	761.8	767.6	778.0	784.6
25°	713.3	709.0	704.8	707.4	704.8	709.0	713.3	716.4	727.0	731.7	741.2
27.5°	670.6	667.3	663.1	662.6	663.1	667.3	670.6	673.6	679.4	687.4	698.8
30°	643.5	640.3	638.1	635.5	638.1	640.3	643.5	646.1	651.9	660.4	668.8
32.5°	615.9	615.3	611.5	611.0	611.5	615.3	615.9	620.3	626.1	634.1	641.4
35°	580.0	576.8	575.7	576.3	575.7	576.8	580.0	582.1	587.4	594.8	601.7
37.5°	545.8	541.6	539.7	537.9	539.7	541.6	545.8	546.1	551.6	556.5	565.8
40°	521.3	517.1	516.0	514.9	516.0	517.1	521.3	520.8	526.6	530.3	538.8
42.5°	493.8	492.1	491.5	489.6	491.5	492.1	493.8	496.7	500.0	505.3	511.7
45°	456.3	455.8	452.6	453.6	452.6	455.8	456.3	457.9	463.7	467.4	473.2
47.5°	416.8	414.4	412.2	413.6	412.2	414.4	416.8	418.9	422.7	427.3	435.0
50°	389.7	388.6	383.8	384.9	383.8	388.6	389.7	391.8	394.5	400.2	407.1
52.5°	362.6	358.6	356.8	356.2	356.8	358.6	362.6	364.7	367.8	374.5	379.6
55°	317.8	313.0	310.8	309.8	310.8	313.0	317.8	321.4	325.7	333.1	338.4
57.5°	273.8	272.5	270.8	272.0	270.8	272.5	273.8	279.9	284.1	289.8	296.3
60°	247.9	247.9	247.9	247.4	247.9	247.9	247.9	253.3	256.9	262.8	269.6
62.5°	228.1	226.8	226.4	227.1	226.4	226.8	228.1	230.5	234.1	237.8	243.9
65°	197.7	197.2	195.1	194.6	195.1	197.2	197.7	199.3	202.5	205.1	209.3
67.5°	169.1	167.1	166.5	165.8	166.5	167.1	169.1	170.5	172.6	175.9	178.0
70°	147.5	146.4	143.3	143.8	143.3	146.4	147.5	150.2	152.3	156.5	158.6
72.5°	124.2	123.2	122.6	121.8	122.6	123.2	124.2	126.9	129.0	133.7	137.0
75°	98.4	97.9	97.3	99.4	97.3	97.9	98.4	98.9	99.4	101.0	102.6
77.5°	78.8	78.8	79.1	78.3	79.1	78.8	78.8	78.8	78.8	79.6	80.0
80°	66.0	66.0	65.5	65.5	65.5	66.0	66.0	66.0	66.0	66.0	65.5
82.5°	53.0	53.4	53.7	52.9	53.7	53.4	53.0	53.8	54.2	53.4	53.7
85°	34.9	34.3	35.4	34.9	35.4	34.3	34.9	34.9	33.8	34.9	34.3
87.5°	22.4	21.6	21.7	22.2	21.7	21.6	22.4	21.4	21.3	21.1	20.4
90°	33.6	34.1	34.6	35.2	34.6	34.1	33.6	33.1	32.3	31.3	30.3
92.5°	48.4	48.1	47.7	47.4	47.7	48.1	48.4	48.7	48.4	47.6	46.8
95°	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.0	90.0	88.9
97.5°	141.1	141.0	140.9	140.8	140.9	141.0	141.1	141.2	140.7	139.5	138.3
100°	176.8	177.3	177.8	178.3	177.8	177.3	176.8	176.2	175.6	174.8	174.0
102.5°	217.1	217.0	216.9	216.8	216.9	217.0	217.1	217.2	216.9	216.1	215.3
105°	277.7	278.2	278.7	279.2	278.7	278.2	277.7	277.2	276.9	276.9	276.9
107.5°	345.2	344.9	344.6	344.3	344.6	344.9	345.2	345.5	345.3	344.5	343.6
110°	389.9	389.4	388.9	388.4	388.9	389.4	389.9	390.4	390.2	389.2	388.1



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	435.7	435.6	435.5	435.4	435.5	435.6	435.7	435.8	435.2	433.9	432.6
115°	500.6	500.4	500.1	499.9	500.1	500.4	500.6	500.9	500.9	500.6	500.4
117.5°	567.5	566.7	566.0	565.3	566.0	566.7	567.5	568.3	568.7	568.7	568.8
120°	612.9	612.4	611.9	611.3	611.9	612.4	612.9	613.4	613.8	614.1	614.3
122.5°	657.6	656.9	656.1	655.4	656.1	656.9	657.6	658.3	659.0	659.7	660.5
125°	724.8	723.7	722.7	721.6	722.7	723.7	724.8	725.8	726.8	727.9	728.9
127.5°	791.1	789.9	788.7	787.6	788.7	789.9	791.1	792.3	793.7	795.2	796.6
130°	836.2	834.4	832.5	830.7	832.5	834.4	836.2	838.0	839.5	840.5	841.5
132.5°	880.0	878.6	877.2	875.8	877.2	878.6	880.0	881.4	882.7	884.0	885.2
135°	947.3	946.7	946.2	945.7	946.2	946.7	947.3	947.8	948.6	949.6	950.7
137.5°	1010.4	1009.5	1008.5	1007.4	1008.5	1009.5	1010.4	1011.4	1012.4	1013.5	1014.6
140°	1053.3	1051.5	1049.7	1047.8	1049.7	1051.5	1053.3	1055.1	1056.1	1056.4	1056.6
142.5°	1093.3	1091.9	1090.6	1089.1	1090.6	1091.9	1093.3	1094.7	1095.6	1095.8	1096.1
145°	1151.9	1150.7	1149.7	1148.7	1149.7	1150.7	1151.9	1152.9	1153.6	1153.8	1154.1
147.5°	1206.4	1204.9	1203.3	1201.7	1203.3	1204.9	1206.4	1208.0	1208.8	1208.8	1208.8
150°	1240.2	1238.7	1237.1	1235.6	1237.1	1238.7	1240.2	1241.8	1242.5	1242.5	1242.5
152.5°	1272.4	1271.1	1269.7	1268.4	1269.7	1271.1	1272.4	1273.8	1274.2	1273.8	1273.4
155°	1318.5	1316.7	1314.8	1312.9	1314.8	1316.7	1318.5	1320.3	1320.7	1319.6	1318.6
157.5°	1358.0	1356.5	1355.0	1353.5	1355.0	1356.5	1358.0	1359.4	1359.6	1358.5	1357.4
160°	1383.0	1381.9	1380.9	1379.9	1380.9	1381.9	1383.0	1384.0	1383.9	1382.6	1381.3
162.5°	1404.5	1402.9	1401.2	1399.6	1401.2	1402.9	1404.5	1406.2	1406.4	1405.1	1403.8
165°	1433.4	1431.6	1429.8	1427.9	1429.8	1431.6	1433.4	1435.2	1435.4	1433.8	1432.3
167.5°	1456.9	1455.3	1453.7	1452.1	1453.7	1455.3	1456.9	1458.5	1458.5	1456.9	1455.3
170°	1469.9	1467.9	1466.1	1464.3	1466.1	1467.9	1469.9	1471.7	1471.7	1469.9	1467.9
172.5°	1479.1	1477.3	1475.5	1473.7	1475.5	1477.3	1479.1	1481.1	1481.2	1479.6	1477.9
175°	1489.8	1487.9	1486.1	1484.3	1486.1	1487.9	1489.8	1491.6	1491.7	1490.2	1488.5
177.5°	1494.3	1492.8	1491.4	1490.0	1491.4	1492.8	1494.3	1495.7	1495.8	1494.6	1493.4
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1178.8	1184.8	1190.6	1196.2	1204.7	1208.4	1214.0	1216.1	1222.3	1231.7	1239.3
5°	1107.1	1115.6	1126.7	1135.7	1149.9	1161.0	1173.3	1184.9	1198.6	1218.2	1235.6
7.5°	1046.3	1054.7	1068.0	1084.7	1100.4	1116.2	1132.9	1148.7	1168.3	1196.4	1224.2
10°	1006.1	1016.2	1032.1	1050.1	1069.5	1084.9	1104.5	1124.6	1148.9	1181.1	1214.5
12.5°	971.5	979.0	997.3	1014.5	1036.6	1056.1	1075.3	1098.7	1126.5	1160.8	1200.9
15°	916.3	926.9	944.8	963.8	987.1	1007.7	1032.6	1061.2	1088.1	1130.4	1179.0
17.5°	860.8	877.0	895.6	917.2	934.3	962.8	989.8	1019.1	1052.3	1097.1	1150.4
20°	825.4	838.0	855.5	886.7	909.4	931.1	955.9	992.4	1023.1	1073.8	1129.3
22.5°	795.3	804.6	824.2	849.9	876.4	901.5	926.8	961.5	999.4	1047.6	1107.7
25°	750.7	765.6	780.4	798.9	827.5	857.6	885.0	914.6	954.8	1006.1	1071.2
27.5°	707.3	720.7	735.4	758.1	779.7	807.9	836.7	870.6	913.7	968.0	1034.0
30°	679.4	689.4	703.2	732.3	751.8	776.2	810.0	840.1	880.3	938.0	1007.7
32.5°	650.7	663.7	678.6	700.9	725.2	748.2	779.1	811.8	852.8	909.6	981.1
35°	609.7	624.9	640.3	656.6	681.0	704.8	730.6	766.6	808.4	863.4	933.7
37.5°	571.9	584.2	596.7	617.0	640.1	662.7	686.9	722.4	761.6	821.0	885.4
40°	547.8	558.9	568.4	589.6	611.7	636.0	659.8	691.1	733.4	788.8	851.2
42.5°	521.5	531.8	544.7	562.0	585.9	606.4	630.3	659.7	699.5	755.9	810.6
45°	482.2	493.8	504.9	521.3	545.1	565.2	586.3	614.4	655.1	701.7	750.2
47.5°	441.3	452.9	465.5	481.4	502.2	522.6	543.7	568.6	605.7	651.4	684.2
50°	415.1	424.5	437.3	453.1	472.1	493.8	512.8	539.8	575.2	611.2	639.7
52.5°	388.0	396.7	411.0	427.8	445.5	464.2	484.5	507.7	539.7	573.5	596.2
55°	345.8	356.4	368.5	384.9	402.3	418.2	437.8	461.6	487.0	512.3	527.7
57.5°	306.3	315.1	325.4	342.2	357.4	376.4	393.8	412.4	435.9	455.0	465.0
60°	277.6	285.5	298.7	313.6	327.8	344.2	364.3	382.8	400.8	416.1	424.0
62.5°	250.5	259.7	271.2	284.8	300.3	315.9	333.5	348.9	364.8	378.0	383.4
65°	215.2	222.6	231.1	243.8	256.4	272.3	286.0	301.8	313.6	320.9	325.7
67.5°	183.1	187.9	194.4	202.8	215.3	229.1	242.5	254.9	264.6	269.6	273.9
70°	162.3	165.5	170.3	178.7	188.2	200.4	214.1	223.1	231.6	235.8	240.0
72.5°	141.6	145.6	150.0	156.7	164.5	173.3	183.3	194.4	199.0	204.1	206.6
75°	107.3	113.1	119.0	123.2	128.5	135.3	144.3	151.2	153.9	158.0	158.6
77.5°	81.0	82.3	86.5	91.8	96.2	101.2	106.9	113.0	114.3	116.5	118.0
80°	66.7	66.7	66.7	69.8	75.0	78.8	84.0	87.3	89.4	89.9	90.4
82.5°	53.5	53.5	53.1	53.7	55.6	57.7	62.5	66.0	67.8	67.5	66.3
85°	34.9	33.8	33.8	33.3	33.8	32.8	32.2	34.3	37.6	37.6	36.5
87.5°	20.2	19.6	19.3	18.3	17.2	16.1	14.1	14.0	13.5	14.7	13.7
90°	29.2	28.2	24.7	21.4	18.0	14.6	11.6	9.0	6.4	3.7	1.2
92.5°	45.8	45.0	43.1	41.2	39.3	37.4	35.4	33.7	31.9	30.2	28.4
95°	87.9	86.8	84.7	82.6	80.6	78.5	76.5	74.7	72.9	71.1	69.3
97.5°	137.0	135.8	134.3	132.9	131.4	129.9	128.4	127.0	125.7	124.3	123.0
100°	173.3	172.5	171.2	169.9	168.5	167.2	165.8	164.3	162.7	161.2	159.6
102.5°	214.6	213.8	212.1	210.4	208.6	206.9	205.6	204.6	203.7	202.8	201.8
105°	276.9	276.9	274.6	272.3	269.8	267.5	266.1	265.6	265.1	264.5	264.0
107.5°	342.7	341.9	340.9	340.0	339.1	338.2	337.5	337.2	336.9	336.6	336.3
110°	387.1	386.1	385.5	385.0	384.5	384.0	383.4	382.9	382.3	381.8	381.3



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	431.4	430.1	430.0	429.9	429.8	429.7	429.5	429.2	428.9	428.6	428.3
115°	500.1	499.9	500.4	500.9	501.4	501.9	501.8	501.0	500.2	499.5	498.7
117.5°	568.8	568.9	569.6	570.2	570.9	571.6	571.6	571.1	570.6	570.1	569.6
120°	614.6	614.8	616.1	617.4	618.7	620.1	620.0	618.3	616.8	615.2	613.7
122.5°	661.1	661.8	662.5	663.1	663.8	664.5	664.3	663.1	662.0	660.8	659.6
125°	729.9	731.0	731.5	732.1	732.6	733.1	733.0	732.2	731.3	730.6	729.8
127.5°	798.1	799.5	800.1	800.6	801.2	801.8	801.2	799.6	797.9	796.3	794.6
130°	842.6	843.6	844.4	845.2	846.0	846.8	846.1	844.0	841.9	839.8	837.8
132.5°	886.5	887.8	888.3	888.9	889.5	890.1	889.3	887.2	885.1	883.0	880.9
135°	951.7	952.7	953.0	953.3	953.5	953.8	953.1	951.6	950.0	948.5	946.8
137.5°	1015.7	1016.8	1016.1	1015.4	1014.8	1014.1	1013.1	1011.8	1010.5	1009.2	1007.9
140°	1056.9	1057.2	1056.9	1056.6	1056.4	1056.1	1055.3	1054.1	1052.8	1051.5	1050.2
142.5°	1096.3	1096.6	1096.1	1095.7	1095.2	1094.7	1093.9	1092.6	1091.3	1089.9	1088.6
145°	1154.3	1154.6	1153.8	1153.0	1152.3	1151.4	1150.7	1150.2	1149.7	1149.2	1148.7
147.5°	1208.8	1208.8	1208.0	1207.3	1206.6	1205.9	1205.1	1204.1	1203.2	1202.2	1201.2
150°	1242.5	1242.5	1242.0	1241.5	1241.0	1240.5	1240.0	1239.4	1238.9	1238.4	1237.9
152.5°	1273.0	1272.6	1272.3	1272.0	1271.6	1271.3	1270.8	1270.1	1269.4	1268.7	1267.9
155°	1317.6	1316.5	1316.3	1316.0	1315.8	1315.5	1315.3	1315.3	1315.3	1315.3	1315.3
157.5°	1356.3	1355.2	1355.0	1354.8	1354.6	1354.3	1354.4	1354.7	1355.0	1355.3	1355.6
160°	1380.0	1378.7	1378.7	1378.7	1378.7	1378.7	1379.0	1379.5	1380.0	1380.5	1381.0
162.5°	1402.5	1401.2	1401.0	1400.8	1400.6	1400.4	1400.7	1401.4	1402.1	1402.8	1403.5
165°	1430.7	1429.2	1429.2	1429.2	1429.2	1429.2	1429.6	1430.3	1431.1	1431.9	1432.7
167.5°	1453.7	1452.1	1451.9	1451.7	1451.5	1451.3	1451.7	1452.8	1453.8	1454.8	1455.9
170°	1466.1	1464.3	1464.3	1464.3	1464.3	1464.3	1464.8	1465.9	1466.9	1467.9	1469.1
172.5°	1476.3	1474.7	1474.7	1474.7	1474.7	1474.7	1475.2	1476.2	1477.2	1478.3	1479.4
175°	1487.0	1485.4	1485.4	1485.4	1485.4	1485.4	1486.0	1487.0	1488.0	1489.1	1490.2
177.5°	1492.1	1490.9	1490.9	1490.9	1490.9	1490.9	1491.3	1492.1	1493.0	1493.8	1494.6
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1241.8	1246.5	1252.4	1261.3	1268.1	1273.9	1275.3	1277.0	1281.2	1288.4	1293.8
5°	1249.9	1262.0	1281.6	1300.6	1321.3	1338.2	1354.0	1365.1	1375.7	1398.0	1415.9
7.5°	1247.4	1274.4	1305.0	1339.3	1373.8	1407.3	1438.5	1466.2	1493.9	1526.3	1563.2
10°	1245.7	1277.4	1318.6	1362.5	1410.6	1457.6	1503.2	1538.5	1579.8	1616.8	1663.9
12.5°	1237.6	1283.3	1332.6	1388.8	1447.8	1502.1	1562.0	1610.9	1658.1	1711.5	1766.3
15°	1227.2	1282.6	1345.0	1419.6	1509.4	1575.1	1636.4	1721.5	1779.7	1837.9	1916.0
17.5°	1208.0	1275.8	1353.7	1450.6	1525.6	1613.7	1706.0	1773.2	1851.6	1933.5	2004.4
20°	1192.8	1271.5	1358.8	1454.0	1549.6	1645.4	1734.7	1815.0	1896.0	1990.6	2048.8
22.5°	1177.6	1255.5	1346.2	1447.2	1550.0	1650.8	1752.0	1846.3	1937.4	2033.0	2107.2
25°	1145.2	1237.7	1336.1	1439.2	1540.7	1651.7	1772.2	1877.4	1990.0	2088.4	2158.8
27.5°	1112.4	1197.2	1295.2	1399.7	1512.6	1643.8	1785.5	1905.2	2018.0	2088.4	2110.5
30°	1082.8	1172.7	1262.5	1368.9	1491.0	1637.4	1788.1	1925.0	2017.6	2048.2	2025.5
32.5°	1052.8	1134.2	1223.2	1332.0	1461.8	1621.7	1791.5	1913.2	1968.9	1945.5	1852.9
35°	999.8	1073.3	1159.4	1268.4	1417.4	1613.2	1777.6	1860.0	1846.2	1714.0	1539.6
37.5°	943.1	1003.0	1082.8	1196.7	1371.6	1578.7	1717.5	1729.6	1610.6	1407.8	1206.2
40°	898.3	952.2	1034.2	1153.2	1336.1	1544.9	1657.0	1607.8	1423.3	1197.5	1029.5
42.5°	854.7	900.2	979.2	1107.4	1302.2	1498.8	1566.9	1459.8	1246.9	1033.4	880.5
45°	780.9	823.7	903.0	1034.7	1232.9	1410.6	1401.6	1215.5	1002.5	830.6	703.7
47.5°	710.9	748.3	822.7	957.2	1151.7	1278.4	1194.4	996.3	815.6	677.7	587.2
50°	661.5	698.4	772.4	905.1	1086.5	1179.0	1059.0	868.2	702.7	588.4	516.5
52.5°	614.1	650.3	717.9	847.2	1007.8	1063.2	934.2	757.3	619.4	520.8	459.0
55°	547.8	575.2	636.0	759.7	879.8	892.5	761.8	613.8	500.2	431.4	389.1
57.5°	480.2	503.8	563.9	662.5	746.7	740.1	616.3	488.2	411.6	360.6	329.9
60°	436.2	459.5	512.3	596.9	660.4	638.1	524.5	421.4	355.8	318.3	294.0
62.5°	395.2	413.3	462.8	524.6	570.3	545.1	448.4	363.0	311.0	279.3	260.1
65°	335.8	350.5	390.2	422.4	447.8	423.5	343.2	283.9	246.4	224.2	211.0
67.5°	279.2	288.7	313.8	325.4	343.3	316.6	258.0	218.3	197.0	178.2	169.1
70°	243.8	250.6	263.9	273.4	278.1	250.6	207.2	178.1	160.2	146.9	141.2
72.5°	208.2	214.2	216.9	224.7	222.3	196.5	166.6	143.5	130.6	121.6	114.1
75°	159.2	161.8	159.2	155.9	149.1	131.1	110.5	98.9	89.4	85.1	82.5
77.5°	116.0	115.1	111.6	106.5	94.8	83.5	72.4	68.6	64.4	62.2	61.2
80°	89.4	87.3	84.0	76.1	66.0	58.2	55.5	52.9	51.3	48.7	48.1
82.5°	66.6	65.2	60.0	53.3	46.3	42.5	40.3	39.4	37.8	36.4	36.3
85°	35.4	33.8	28.0	24.3	23.2	22.2	21.7	21.7	19.6	19.0	19.0
87.5°	12.2	10.2	10.3	9.5	10.1	9.9	11.0	10.9	11.1	11.7	11.1
90°	3.7	6.4	9.0	11.6	14.6	18.0	21.4	24.7	28.2	29.2	30.3
92.5°	30.2	31.9	33.7	35.4	37.4	39.3	41.2	43.1	45.0	45.8	46.8
95°	71.1	72.9	74.7	76.5	78.5	80.6	82.6	84.7	86.8	87.9	88.9
97.5°	124.3	125.7	127.0	128.4	129.9	131.4	132.9	134.3	135.8	137.0	138.3
100°	161.2	162.7	164.3	165.8	167.2	168.5	169.9	171.2	172.5	173.3	174.0
102.5°	202.8	203.7	204.6	205.6	206.9	208.6	210.4	212.1	213.8	214.6	215.3
105°	264.5	265.1	265.6	266.1	267.5	269.8	272.3	274.6	276.9	276.9	276.9
107.5°	336.6	336.9	337.2	337.5	338.2	339.1	340.0	340.9	341.9	342.7	343.6
110°	381.8	382.3	382.9	383.4	384.0	384.5	385.0	385.5	386.1	387.1	388.1



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	428.6	428.9	429.2	429.5	429.7	429.8	429.9	430.0	430.1	431.4	432.6
115°	499.5	500.2	501.0	501.8	501.9	501.4	500.9	500.4	499.9	500.1	500.4
117.5°	570.1	570.6	571.1	571.6	571.6	570.9	570.2	569.6	568.9	568.8	568.8
120°	615.2	616.8	618.3	620.0	620.1	618.7	617.4	616.1	614.8	614.6	614.3
122.5°	660.8	662.0	663.1	664.3	664.5	663.8	663.1	662.5	661.8	661.1	660.5
125°	730.6	731.3	732.2	733.0	733.1	732.6	732.1	731.5	731.0	729.9	728.9
127.5°	796.3	797.9	799.6	801.2	801.8	801.2	800.6	800.1	799.5	798.1	796.6
130°	839.8	841.9	844.0	846.1	846.8	846.0	845.2	844.4	843.6	842.6	841.5
132.5°	883.0	885.1	887.2	889.3	890.1	889.5	888.9	888.3	887.8	886.5	885.2
135°	948.5	950.0	951.6	953.1	953.8	953.5	953.3	953.0	952.7	951.7	950.7
137.5°	1009.2	1010.5	1011.8	1013.1	1014.1	1014.8	1015.4	1016.1	1016.8	1015.7	1014.6
140°	1051.5	1052.8	1054.1	1055.3	1056.1	1056.4	1056.6	1056.9	1057.2	1056.9	1056.6
142.5°	1089.9	1091.3	1092.6	1093.9	1094.7	1095.2	1095.7	1096.1	1096.6	1096.3	1096.1
145°	1149.2	1149.7	1150.2	1150.7	1151.4	1152.3	1153.0	1153.8	1154.6	1154.3	1154.1
147.5°	1202.2	1203.2	1204.1	1205.1	1205.9	1206.6	1207.3	1208.0	1208.8	1208.8	1208.8
150°	1238.4	1238.9	1239.4	1240.0	1240.5	1241.0	1241.5	1242.0	1242.5	1242.5	1242.5
152.5°	1268.7	1269.4	1270.1	1270.8	1271.3	1271.6	1272.0	1272.3	1272.6	1273.0	1273.4
155°	1315.3	1315.3	1315.3	1315.3	1315.5	1315.8	1316.0	1316.3	1316.5	1317.6	1318.6
157.5°	1355.3	1355.0	1354.7	1354.4	1354.3	1354.6	1354.8	1355.0	1355.2	1356.3	1357.4
160°	1380.5	1380.0	1379.5	1379.0	1378.7	1378.7	1378.7	1378.7	1378.7	1380.0	1381.3
162.5°	1402.8	1402.1	1401.4	1400.7	1400.4	1400.6	1400.8	1401.0	1401.2	1402.5	1403.8
165°	1431.9	1431.1	1430.3	1429.6	1429.2	1429.2	1429.2	1429.2	1429.2	1430.7	1432.3
167.5°	1454.8	1453.8	1452.8	1451.7	1451.3	1451.5	1451.7	1451.9	1452.1	1453.7	1455.3
170°	1467.9	1466.9	1465.9	1464.8	1464.3	1464.3	1464.3	1464.3	1464.3	1466.1	1467.9
172.5°	1478.3	1477.2	1476.2	1475.2	1474.7	1474.7	1474.7	1474.7	1474.7	1476.3	1477.9
175°	1489.1	1488.0	1487.0	1486.0	1485.4	1485.4	1485.4	1485.4	1485.4	1487.0	1488.5
177.5°	1493.8	1493.0	1492.1	1491.3	1490.9	1490.9	1490.9	1490.9	1490.9	1492.1	1493.4
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1	1235.1
2.5°	1302.7	1302.7	1304.4	1310.8	1311.6	1317.2	1315.5
5°	1431.8	1441.8	1445.5	1461.4	1470.9	1475.1	1466.6
7.5°	1589.5	1617.9	1631.3	1647.9	1662.6	1667.1	1655.5
10°	1704.6	1734.1	1759.1	1774.3	1788.7	1798.2	1810.3
12.5°	1815.8	1852.2	1875.8	1897.4	1912.2	1924.2	1926.2
15°	1936.7	1991.7	2033.5	2064.1	2079.4	2087.4	2084.2
17.5°	2058.6	2109.6	2139.3	2170.6	2191.8	2192.9	2193.5
20°	2127.6	2177.3	2211.6	2234.8	2258.7	2257.7	2262.9
22.5°	2173.6	2212.8	2239.1	2256.0	2264.2	2260.2	2261.2
25°	2195.2	2206.9	2202.1	2175.1	2168.3	2143.4	2147.7
27.5°	2084.0	2029.0	1972.1	1899.0	1841.2	1795.1	1797.5
30°	1933.0	1835.7	1724.6	1631.6	1548.1	1524.8	1475.1
32.5°	1721.9	1576.0	1445.9	1359.2	1287.5	1268.1	1224.8
35°	1364.1	1222.3	1088.6	1008.2	976.5	932.1	931.6
37.5°	1060.3	935.5	864.7	804.5	772.8	746.0	743.4
40°	891.9	794.7	741.2	697.9	666.7	646.6	641.9
42.5°	774.4	695.7	645.7	618.8	594.8	584.4	576.7
45°	632.4	579.5	544.6	520.3	509.2	501.2	497.0
47.5°	529.0	493.5	469.7	453.5	444.5	436.2	438.4
50°	472.7	443.6	426.2	410.8	403.9	398.1	398.7
52.5°	427.4	401.3	387.2	376.2	367.6	363.5	361.4
55°	362.7	346.3	332.0	324.1	319.3	313.6	311.9
57.5°	309.4	296.7	285.1	276.1	274.9	269.3	270.0
60°	273.9	263.3	253.8	249.0	245.3	240.5	242.2
62.5°	244.7	235.8	227.1	223.2	219.5	216.0	216.8
65°	200.4	191.9	186.6	184.5	182.9	181.4	179.8
67.5°	159.7	154.5	151.2	146.6	143.4	142.9	141.3
70°	134.3	127.4	121.6	115.8	114.2	113.7	114.2
72.5°	107.7	103.3	101.7	98.9	98.6	97.1	98.2
75°	80.9	79.3	78.3	76.1	76.1	76.1	76.1
77.5°	59.7	58.7	58.1	57.7	57.1	56.4	56.2
80°	46.6	45.9	44.9	44.9	44.4	44.9	44.4
82.5°	35.1	35.0	33.9	33.9	33.4	33.1	33.4
85°	18.0	17.5	18.5	17.5	18.0	17.0	18.0
87.5°	11.3	11.5	11.3	11.4	11.1	12.0	11.3
90°	31.3	32.3	33.1	33.6	34.1	34.6	35.2
92.5°	47.6	48.4	48.7	48.4	48.1	47.7	47.4
95°	90.0	91.0	91.5	91.5	91.5	91.5	91.5
97.5°	139.5	140.7	141.2	141.1	141.0	140.9	140.8
100°	174.8	175.6	176.2	176.8	177.3	177.8	178.3
102.5°	216.1	216.9	217.2	217.1	217.0	216.9	216.8
105°	276.9	276.9	277.2	277.7	278.2	278.7	279.2
107.5°	344.5	345.3	345.5	345.2	344.9	344.6	344.3
110°	389.2	390.2	390.4	389.9	389.4	388.9	388.4



TEST NUMBER: P332325-840

CATALOG NUMBER: S123RDIP-S775D1195U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	433.9	435.2	435.8	435.7	435.6	435.5	435.4
115°	500.6	500.9	500.9	500.6	500.4	500.1	499.9
117.5°	568.7	568.7	568.3	567.5	566.7	566.0	565.3
120°	614.1	613.8	613.4	612.9	612.4	611.9	611.3
122.5°	659.7	659.0	658.3	657.6	656.9	656.1	655.4
125°	727.9	726.8	725.8	724.8	723.7	722.7	721.6
127.5°	795.2	793.7	792.3	791.1	789.9	788.7	787.6
130°	840.5	839.5	838.0	836.2	834.4	832.5	830.7
132.5°	884.0	882.7	881.4	880.0	878.6	877.2	875.8
135°	949.6	948.6	947.8	947.3	946.7	946.2	945.7
137.5°	1013.5	1012.4	1011.4	1010.4	1009.5	1008.5	1007.4
140°	1056.4	1056.1	1055.1	1053.3	1051.5	1049.7	1047.8
142.5°	1095.8	1095.6	1094.7	1093.3	1091.9	1090.6	1089.1
145°	1153.8	1153.6	1152.9	1151.9	1150.7	1149.7	1148.7
147.5°	1208.8	1208.8	1208.0	1206.4	1204.9	1203.3	1201.7
150°	1242.5	1242.5	1241.8	1240.2	1238.7	1237.1	1235.6
152.5°	1273.8	1274.2	1273.8	1272.4	1271.1	1269.7	1268.4
155°	1319.6	1320.7	1320.3	1318.5	1316.7	1314.8	1312.9
157.5°	1358.5	1359.6	1359.4	1358.0	1356.5	1355.0	1353.5
160°	1382.6	1383.9	1384.0	1383.0	1381.9	1380.9	1379.9
162.5°	1405.1	1406.4	1406.2	1404.5	1402.9	1401.2	1399.6
165°	1433.8	1435.4	1435.2	1433.4	1431.6	1429.8	1427.9
167.5°	1456.9	1458.5	1458.5	1456.9	1455.3	1453.7	1452.1
170°	1469.9	1471.7	1471.7	1469.9	1467.9	1466.1	1464.3
172.5°	1479.6	1481.2	1481.1	1479.1	1477.3	1475.5	1473.7
175°	1490.2	1491.7	1491.6	1489.8	1487.9	1486.1	1484.3
177.5°	1494.6	1495.8	1495.7	1494.3	1492.8	1491.4	1490.0
180°	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7	1493.7

(END OF REPORT)