

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332062-940

Luminaire Tested: **S123DIP-S1165D585U940-4F0-1E-UDD-F4**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332062-940
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-17,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123DIP-S1165D585U940-4F0-1E-UDD-F4
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1165 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
UPLIGHT 585 LUMENS PER FOOT, BATWING OPTIC
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6134.1 lumens
Efficiency: N/A
Efficacy: 111.3 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.18 / 1.31
Luminous Opening: Rectangular (W 0.25' x L: 4' x H: 0')
CIE Type: Semi-Direct


Input Watts (W): 55.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

Luminous Intensity Polar Plot





TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	112	112	112	112	106	106	106	106	94	94	94	83	83	83	74	74	74	69
1	102	98	93	90	96	92	89	85	82	80	77	73	71	69	65	64	62	58
2	93	85	79	73	87	81	75	70	72	68	64	64	61	58	57	55	52	49
3	85	75	67	61	80	71	64	59	64	58	54	57	53	49	51	47	44	41
4	78	66	58	52	73	63	56	50	57	51	46	51	46	42	45	41	38	35
5	71	59	51	45	67	56	49	43	51	44	40	46	40	36	41	37	33	31
6	66	53	45	39	62	51	43	37	46	39	35	41	36	32	37	33	29	27
7	61	48	40	34	57	46	38	33	42	35	31	38	32	28	34	29	26	24
8	57	44	36	30	53	42	34	29	38	32	27	34	29	25	31	27	23	21
9	53	40	32	27	50	38	31	26	35	29	25	32	27	23	29	24	21	19
10	49	37	29	24	47	35	28	24	32	26	22	29	24	21	27	22	19	17

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	17546	17546	17546
5°	17629	17386	17507
10°	17511	17235	17343
15°	17307	17041	17072
20°	17068	16763	16778
25°	16747	16431	16397
30°	16394	16063	15940
35°	16025	15674	15471
40°	15638	15244	15008
45°	15213	14850	14487
50°	14788	14364	13966
55°	14230	13863	13440
60°	13670	13276	12854
65°	13173	12638	12246
70°	12441	11909	11383
75°	11366	10959	10493
80°	10253	9819	9732
85°	9003	8657	8312



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	153.6	2.5
10°-20°	433.6	7.1
20°-30°	640.5	10.4
30°-40°	748.2	12.2
40°-50°	752.2	12.3
50°-60°	660.7	10.8
60°-70°	492.2	8.0
70°-80°	280.4	4.6
80°-90°	82.4	1.3
90°-100°	139.8	2.3
100°-110°	395.9	6.5
110°-120°	389.5	6.3
120°-130°	310.7	5.1
130°-140°	244.9	4.0
140°-150°	182.8	3.0
150°-160°	127.4	2.1
160°-170°	74.9	1.2
170°-180°	24.4	0.4
0°-30°	1227.6	20.0
0°-40°	1975.8	32.2
0°-60°	3388.7	55.2
0°-90°	4243.8	69.2
90°-120°	925.2	15.1
90°-150°	1663.7	27.1
90°-180°	1890.0	30.8
0°-180°	6134.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1630	1630	1630	1630	1630	
5°	1632	1624	1609	1622	1620	155
15°	1553	1547	1529	1539	1532	438
25°	1410	1401	1384	1385	1381	649
35°	1220	1211	1193	1185	1177	763
45°	999	993	976	959	952	771
55°	758	756	739	724	716	679
65°	517	510	496	485	481	510
75°	273	268	264	257	252	292
85°	73	70	70	67	67	80
90°	1	6	13	14	15	5
95°	17	56	302	88	59	19
105°	59	87	409	715	647	63
115°	104	130	313	686	787	103
125°	145	171	292	529	620	129
135°	170	203	288	436	503	131
145°	194	222	284	357	393	121
155°	220	238	275	313	326	101
165°	241	247	264	279	284	68
175°	251	251	253	256	256	24
180°	251	251	251	251	251	



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1
2.5°	1635.8	1634.8	1633.8	1632.8	1631.7	1629.9	1627.2	1624.4	1621.7	1618.9	1621.4
5°	1631.6	1630.0	1628.4	1626.9	1625.3	1622.8	1619.4	1616.0	1612.6	1609.1	1612.2
7.5°	1615.6	1614.0	1612.5	1610.9	1609.4	1606.8	1603.2	1599.7	1596.2	1592.6	1595.4
10°	1602.1	1600.5	1599.0	1597.4	1595.9	1593.1	1589.0	1585.0	1580.9	1576.9	1579.7
12.5°	1584.2	1582.9	1581.5	1580.3	1579.0	1576.4	1572.6	1568.8	1565.0	1561.2	1563.3
15°	1553.1	1551.8	1550.6	1549.3	1548.1	1545.4	1541.4	1537.3	1533.3	1529.2	1531.7
17.5°	1516.9	1515.3	1513.7	1512.1	1510.4	1507.6	1503.5	1499.5	1495.4	1491.4	1493.2
20°	1490.0	1488.1	1486.2	1484.3	1482.6	1479.5	1475.5	1471.5	1467.4	1463.4	1464.6
22.5°	1459.7	1457.9	1456.0	1454.1	1452.2	1449.3	1445.2	1441.2	1437.2	1433.1	1434.0
25°	1410.1	1408.2	1406.3	1404.4	1402.7	1399.6	1395.6	1391.6	1387.5	1383.5	1383.8
27.5°	1357.1	1355.3	1353.5	1351.7	1349.9	1346.8	1342.5	1338.1	1333.7	1329.4	1329.6
30°	1319.0	1317.4	1315.9	1314.3	1312.8	1309.8	1305.5	1301.1	1296.7	1292.4	1292.4
32.5°	1280.9	1278.8	1276.8	1274.7	1272.6	1269.9	1266.6	1263.2	1259.8	1256.5	1254.7
35°	1219.5	1217.6	1215.8	1213.9	1212.0	1209.1	1205.0	1201.0	1196.9	1192.8	1191.0
37.5°	1156.6	1154.3	1151.9	1149.6	1147.2	1144.0	1139.9	1135.8	1131.7	1127.5	1125.2
40°	1112.9	1111.1	1109.2	1107.3	1105.5	1102.3	1098.0	1093.6	1089.2	1084.9	1082.4
42.5°	1069.2	1067.1	1065.0	1062.8	1060.7	1057.5	1053.1	1048.7	1044.4	1040.1	1037.6
45°	999.4	998.2	996.9	995.7	994.4	991.8	987.7	983.6	979.6	975.5	971.9
47.5°	930.1	928.4	926.6	924.7	922.9	920.2	916.3	912.5	908.7	904.9	901.3
50°	883.1	881.5	879.9	878.4	876.8	874.1	870.0	865.9	861.8	857.8	854.4
52.5°	833.7	832.7	831.6	830.5	829.5	826.8	822.5	818.2	814.0	809.6	806.6
55°	758.3	758.0	757.7	757.4	757.1	754.9	750.8	746.8	742.7	738.7	735.3
57.5°	686.5	685.5	684.4	683.4	682.3	680.2	676.9	673.7	670.5	667.2	664.1
60°	635.0	634.6	634.4	634.0	633.7	631.7	627.9	624.2	620.5	616.7	613.9
62.5°	589.0	588.2	587.4	586.6	585.8	583.4	579.7	576.0	572.3	568.6	565.7
65°	517.2	515.7	514.1	512.6	511.0	508.6	505.5	502.4	499.3	496.2	493.7
67.5°	441.2	439.9	438.5	437.1	435.8	433.9	431.5	429.2	426.8	424.5	422.2
70°	395.3	393.4	391.6	389.7	387.8	385.9	384.1	382.2	380.3	378.4	376.3
72.5°	347.1	345.7	344.3	343.0	341.6	339.8	337.7	335.6	333.5	331.4	329.4
75°	273.3	272.1	270.8	269.6	268.3	267.2	266.4	265.4	264.5	263.5	262.0
77.5°	208.0	207.3	206.6	206.0	205.3	204.4	203.2	202.2	201.0	199.9	198.9
80°	165.4	164.4	163.5	162.6	161.7	160.9	160.2	159.6	159.0	158.4	158.1
82.5°	123.9	123.7	123.5	123.3	123.1	123.0	122.9	122.8	122.6	122.5	122.0
85°	72.9	72.2	71.6	71.0	70.4	70.1	70.1	70.1	70.1	70.1	69.5
87.5°	29.3	28.8	28.3	27.8	27.3	27.0	27.0	27.1	27.2	27.2	26.8
90°	1.0	2.1	3.0	4.5	5.6	6.6	8.1	9.6	11.1	12.8	12.2
92.5°	6.3	9.4	13.6	17.6	21.8	29.4	42.7	64.6	86.1	78.2	59.0
95°	17.3	18.8	24.4	33.1	46.3	66.1	109.3	185.1	268.6	301.6	244.6
97.5°	29.5	30.1	34.4	41.9	54.9	76.4	117.7	203.1	342.1	467.4	500.1
100°	37.6	38.2	41.7	48.9	61.0	80.9	116.5	191.7	325.5	481.6	581.8
102.5°	46.2	47.1	50.3	57.0	67.9	86.1	118.1	182.0	301.1	455.2	585.9
105°	59.0	60.5	63.6	69.6	79.4	95.1	122.6	175.0	271.1	408.9	554.9
107.5°	72.6	74.2	77.1	83.1	92.2	106.8	130.9	174.4	252.0	368.0	500.6
110°	82.4	83.9	86.5	92.0	100.7	114.9	137.9	176.5	244.6	344.8	466.4



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	91.3	92.9	95.4	101.0	109.7	123.5	144.7	180.6	240.6	329.4	436.7
115°	104.2	106.3	109.3	114.4	123.1	136.8	156.1	187.2	239.1	312.8	400.8
117.5°	117.2	119.5	122.1	126.7	136.4	149.1	168.3	195.9	240.0	303.0	379.2
120°	126.2	127.7	130.2	135.3	145.0	157.7	175.9	202.4	241.6	298.5	367.7
122.5°	133.8	135.4	137.9	143.4	152.7	166.2	184.1	208.6	244.4	295.7	358.4
125°	145.0	146.0	149.0	154.6	164.3	178.0	195.8	218.2	248.7	291.9	346.3
127.5°	153.4	154.9	158.7	164.3	175.0	188.8	206.0	226.1	253.6	290.1	335.8
130°	158.7	160.2	164.8	170.9	181.6	195.3	212.0	231.4	256.8	288.9	330.1
132.5°	162.7	164.7	169.7	177.0	187.7	201.0	217.4	236.3	259.3	288.5	324.8
135°	169.9	171.9	177.5	185.1	195.8	209.6	225.3	242.6	263.0	287.8	317.9
137.5°	176.6	178.7	184.2	192.3	203.0	215.6	230.8	247.3	265.4	286.8	311.9
140°	181.1	183.6	188.7	196.8	207.0	219.7	234.4	249.8	267.0	286.3	308.2
142.5°	185.9	188.1	193.6	200.9	211.1	223.0	237.3	252.2	268.2	285.5	305.0
145°	193.8	195.3	199.9	207.5	216.2	227.8	241.1	254.9	269.0	284.3	300.6
147.5°	201.7	202.6	207.1	213.7	222.0	232.0	244.2	256.5	269.0	282.4	296.3
150°	207.0	207.5	211.6	218.2	225.3	234.4	246.2	256.8	269.0	280.7	293.5
152.5°	212.3	212.4	216.5	222.3	228.5	237.3	247.4	257.7	267.9	278.7	290.3
155°	220.3	220.3	223.3	228.4	234.0	241.1	249.8	257.9	266.5	275.2	285.3
157.5°	226.5	226.9	229.3	233.9	238.6	244.2	251.0	258.4	264.7	272.0	279.8
160°	231.4	231.4	233.4	237.6	241.1	246.2	252.3	258.4	263.9	269.6	276.2
162.5°	235.1	235.1	236.7	240.0	243.1	247.4	252.7	258.0	262.3	267.2	272.5
165°	240.6	240.0	241.1	243.6	245.7	249.2	253.2	256.8	259.9	263.5	267.5
167.5°	244.8	244.2	244.6	246.6	248.0	250.2	253.2	256.0	257.4	259.8	262.8
170°	247.2	246.2	246.6	248.2	249.2	250.2	252.8	254.9	255.8	257.3	259.9
172.5°	248.8	248.2	248.3	249.4	250.0	250.7	252.8	254.4	254.6	255.3	257.1
175°	250.7	250.2	249.8	250.7	250.7	251.3	252.3	253.2	252.8	252.8	253.8
177.5°	251.6	251.3	250.8	251.3	251.3	251.3	251.6	252.4	251.6	251.3	251.6
180°	251.3	251.3	251.3	251.3	251.3	251.3	251.3	251.3	251.3	251.3	251.3



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
0°	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1	1630.1
2.5°	1623.9	1626.4	1628.9	1630.0	1629.8	1629.5	1629.2	1629.1
5°	1615.3	1618.5	1621.6	1622.8	1622.2	1621.6	1621.0	1620.3
7.5°	1598.2	1601.0	1603.8	1605.0	1604.6	1604.3	1603.9	1603.6
10°	1582.5	1585.3	1588.1	1589.2	1588.6	1588.0	1587.3	1586.7
12.5°	1565.3	1567.4	1569.4	1570.3	1569.9	1569.5	1569.1	1568.8
15°	1534.2	1536.7	1539.2	1539.5	1537.7	1535.8	1533.9	1532.0
17.5°	1494.9	1496.6	1498.3	1498.9	1498.3	1497.5	1496.8	1496.2
20°	1465.9	1467.1	1468.4	1468.5	1467.6	1466.6	1465.7	1464.7
22.5°	1435.1	1436.1	1437.1	1437.0	1435.8	1434.6	1433.4	1432.3
25°	1384.1	1384.4	1384.7	1384.4	1383.5	1382.5	1381.6	1380.6
27.5°	1329.9	1330.1	1330.3	1329.9	1328.7	1327.5	1326.3	1325.2
30°	1292.4	1292.4	1292.4	1291.3	1289.1	1286.9	1284.7	1282.5
32.5°	1252.9	1251.2	1249.5	1248.0	1246.9	1245.6	1244.5	1243.3
35°	1189.1	1187.2	1185.4	1183.7	1182.1	1180.5	1178.9	1177.4
37.5°	1123.0	1120.8	1118.6	1117.0	1115.9	1114.9	1113.9	1112.9
40°	1080.0	1077.5	1075.0	1073.1	1071.8	1070.6	1069.3	1068.1
42.5°	1035.1	1032.6	1030.1	1028.2	1027.0	1025.7	1024.5	1023.2
45°	968.1	964.4	960.6	958.0	956.4	954.8	953.3	951.7
47.5°	897.6	893.9	890.2	887.7	886.4	884.9	883.6	882.3
50°	851.0	847.6	844.1	841.5	839.6	837.8	835.9	834.0
52.5°	803.8	800.8	797.9	795.5	793.6	791.8	789.9	788.0
55°	731.8	728.4	725.0	722.5	720.9	719.3	717.8	716.2
57.5°	661.1	658.1	655.0	652.6	650.8	649.0	647.1	645.3
60°	611.2	608.3	605.6	603.3	601.8	600.2	598.7	597.1
62.5°	562.9	560.1	557.3	555.4	554.3	553.2	552.2	551.2
65°	491.2	488.7	486.2	484.6	483.6	482.7	481.7	480.8
67.5°	420.1	417.9	415.7	413.9	412.7	411.3	410.0	408.8
70°	374.1	371.9	369.7	367.8	366.3	364.7	363.2	361.7
72.5°	327.5	325.6	323.6	322.3	321.5	320.7	319.9	319.1
75°	260.4	258.9	257.3	256.0	255.1	254.1	253.2	252.3
77.5°	197.8	196.7	195.6	195.1	195.1	195.1	195.1	195.1
80°	157.7	157.5	157.1	157.0	157.0	157.0	157.0	157.0
82.5°	121.4	120.8	120.3	119.8	119.6	119.4	119.1	118.9
85°	68.8	68.2	67.6	67.3	67.3	67.3	67.3	67.3
87.5°	26.8	26.6	26.4	26.5	26.4	26.5	26.6	26.5
90°	12.8	13.2	13.7	14.7	14.3	14.7	15.2	14.7
92.5°	42.8	34.0	30.1	27.4	26.5	24.9	25.4	24.5
95°	183.1	124.1	97.1	78.8	69.2	64.6	61.0	59.0
97.5°	456.5	365.6	300.0	239.2	201.6	178.7	165.0	160.6
100°	599.7	558.5	498.9	426.7	375.3	338.2	318.4	318.9
102.5°	647.3	646.0	611.3	565.4	525.5	496.1	479.5	467.8
105°	661.2	712.0	721.8	708.5	685.1	665.8	649.5	646.9
107.5°	621.1	703.7	748.2	766.3	766.8	760.3	754.7	750.1
110°	582.8	676.5	740.6	776.1	790.4	794.4	793.4	792.4



TEST NUMBER: P332062-940

CATALOG NUMBER: S123DIP-S1165D585U940-4F0-1E-UDD-F4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
112.5°	545.0	640.6	712.5	758.2	784.3	796.9	800.8	800.9
115°	494.9	583.4	658.2	713.5	751.7	774.1	784.3	786.8
117.5°	458.5	534.9	602.1	658.4	698.1	723.7	738.4	741.8
120°	439.4	508.1	569.1	620.5	660.7	689.2	701.3	704.5
122.5°	424.4	486.5	543.1	590.8	626.5	652.1	665.6	669.4
125°	404.3	459.8	508.6	549.3	581.8	604.2	617.0	620.5
127.5°	386.8	436.3	480.4	517.4	546.4	565.4	576.9	580.2
130°	375.9	421.6	462.8	497.4	524.4	542.7	553.4	557.4
132.5°	365.7	407.8	446.1	479.1	504.4	522.7	532.2	535.0
135°	352.0	388.1	421.2	450.1	475.0	490.3	499.4	503.0
137.5°	339.5	369.1	397.5	422.7	443.6	459.1	466.8	469.1
140°	332.2	358.0	382.5	404.3	423.7	437.9	446.0	445.5
142.5°	325.2	347.5	368.6	387.6	404.1	416.8	424.1	423.6
145°	316.8	333.7	349.9	364.7	377.4	388.1	392.2	393.2
147.5°	310.0	323.3	336.5	347.0	356.6	363.8	367.7	368.1
150°	305.1	316.8	327.5	337.2	344.8	350.4	353.5	353.5
152.5°	300.7	310.8	320.2	328.2	334.2	339.5	341.3	341.3
155°	294.0	302.1	309.8	315.8	320.4	324.5	325.5	326.0
157.5°	286.9	293.6	299.6	304.3	308.4	311.4	312.2	312.1
160°	282.8	288.4	293.5	297.0	300.6	303.6	303.6	303.1
162.5°	277.9	282.7	287.4	290.5	292.8	295.5	295.5	295.0
165°	271.6	274.6	278.2	280.7	282.8	284.8	284.3	284.3
167.5°	266.1	268.4	270.5	272.3	273.2	274.6	274.1	274.1
170°	262.4	263.9	266.0	267.0	267.5	268.6	268.0	268.0
172.5°	259.2	260.3	261.9	262.5	262.6	263.7	262.8	262.3
175°	254.9	255.3	256.4	256.4	256.4	256.8	256.4	255.8
177.5°	252.1	252.4	252.9	252.9	252.4	252.9	252.1	252.1
180°	251.3	251.3	251.3	251.3	251.3	251.3	251.3	251.3

(END OF REPORT)