

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P832315

Luminaire Tested: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

Issue Date: 05/03/2024

**Test Information**


Test Method: LM-79-2019  
Report Number: P832315  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2301-905-2, G3-1807-864-9)  
Test Lab: INNOVATION CENTER  
Issue Date: 05/03/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: S123RDIP-S775D1025U850-4F0-1E-UDD-G1  
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE  
DOWNLIGHT 775 LUMENS PER FOOT, GRAZE OPTIC  
UPLIGHT 1025 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7578.4 lumens  
Efficiency: N/A  
Efficacy: 146.3 lumens/watt  
Spacing Criteria (0/90/45): 0.55 / 1.17 / 0.8  
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')  
CIE Type: General Diffuse  
  
Input Watts (W): 51.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P832315  
CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

### Luminous Intensity Polar Plot





TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	107	107	107	107	98	98	98	98	82	82	82	68	68	68	55	55	55	48					48			
1	98	94	91	87	90	87	84	81	73	71	69	61	60	58	50	49	48					42				
2	90	83	77	73	83	77	72	68	65	62	59	55	52	50	45	43	41					37				
3	83	74	67	62	76	69	63	58	58	54	50	49	46	43	40	38	36					32				
4	76	66	59	53	70	61	55	50	53	48	44	44	41	38	37	34	32					29				
5	70	59	52	46	65	55	49	43	48	42	38	40	36	33	34	31	29					25				
6	65	54	46	41	60	50	43	38	43	38	34	37	33	30	31	28	26					23				
7	60	49	41	36	56	46	39	34	40	34	31	34	30	27	29	26	23					21				
8	56	45	37	32	52	42	35	31	36	31	28	31	27	24	27	24	21					19				
9	53	41	34	29	49	39	32	28	34	29	25	29	25	22	25	22	20					18				
10	49	38	31	26	46	36	29	25	31	26	23	27	23	20	23	20	18					16				

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°	135°	180°
0°	29801	29801	29801	29801	29801
5°	35385	34256	29988	24242	22507
10°	32060	34796	29839	19423	16663
15°	22073	29834	29524	15875	13181
20°	15356	22969	28931	13386	11585
25°	11702	17506	28068	11898	10677
30°	10187	13996	26990	11047	9890
35°	9352	11807	25462	10330	9173
40°	8533	10543	23463	9627	8518
45°	7707	9642	21305	8960	7862
50°	6995	8895	18762	8308	7052
55°	6326	8169	16317	7668	6050
60°	5670	7429	14174	6964	5718
65°	5234	6592	12200	6260	5407
70°	4252	5700	10647	5662	4393
75°	3730	4533	9016	4695	3872
80°	3378	3837	7389	3942	3657
85°	3088	3359	5607	3569	3359

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 80°  
 Vertical Angle: 45°  
 Luminance: 22481 cd/sqm



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	252.4	3.3
10°-20°	583.9	7.7
20°-30°	670.0	8.8
30°-40°	660.4	8.7
40°-50°	582.4	7.7
50°-60°	448.0	5.9
60°-70°	294.6	3.9
70°-80°	143.1	1.9
80°-90°	39.0	0.5
90°-100°	90.7	1.2
100°-110°	274.6	3.6
110°-120°	467.4	6.2
120°-130°	614.9	8.1
130°-140°	691.2	9.1
140°-150°	679.5	9.0
150°-160°	572.1	7.5
160°-170°	380.9	5.0
170°-180°	133.4	1.8
0°-30°	1506.3	19.9
0°-40°	2166.7	28.6
0°-60°	3197.1	42.2
0°-90°	3673.7	48.5
90°-120°	832.7	11.0
90°-150°	2818.3	37.2
90°-180°	3905.0	51.5
0°-180°	7578.4	100.0

**CANDELA DISTRIBUTION:**

	0°	45°	90°	135°	180°	Flux
0°	2769	2769	2769	2769	2769	
5°	3275	3170	2775	2244	2083	299
15°	1981	2677	2649	1425	1183	559
25°	985	1474	2363	1002	899	465
35°	712	898	1938	786	698	444
45°	506	633	1400	589	516	393
55°	337	435	870	409	322	302
65°	206	259	479	246	212	201
75°	90	109	217	113	93	97
85°	25	27	45	29	27	27
90°	33	27	1	27	33	17
95°	86	82	65	82	86	87
105°	264	261	249	261	264	279
115°	472	472	470	472	472	467
125°	681	690	689	690	681	609
135°	892	899	893	899	892	686
145°	1084	1089	1084	1089	1084	677
155°	1239	1242	1241	1242	1239	571
165°	1347	1348	1352	1348	1347	380
175°	1400	1402	1406	1402	1400	133
180°	1409	1409	1409	1409	1409	



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6
2.5°	3068.3	3058.6	3049.0	3046.1	3043.3	3034.2	3025.1	3004.7	2984.3	2963.3	2942.3
5°	3274.9	3276.0	3277.1	3274.3	3271.5	3259.5	3247.6	3222.6	3197.7	3170.4	3143.2
7.5°	3211.3	3229.5	3247.6	3251.0	3254.4	3263.5	3272.6	3266.9	3261.2	3251.0	3240.8
10°	2933.2	2932.0	2930.9	2951.3	2971.8	3032.5	3093.2	3124.5	3155.7	3183.5	3211.3
12.5°	2479.1	2480.8	2482.5	2549.5	2616.5	2673.8	2731.1	2810.6	2890.0	2975.7	3061.5
15°	1980.8	2008.6	2036.4	2096.0	2155.6	2241.9	2328.2	2434.9	2541.6	2677.2	2812.9
17.5°	1626.6	1638.6	1650.5	1707.8	1765.1	1846.9	1928.6	2049.5	2170.4	2345.2	2520.0
20°	1340.6	1351.4	1362.2	1403.6	1445.0	1523.3	1601.7	1716.9	1832.1	2005.2	2178.3
22.5°	1119.2	1140.2	1161.2	1189.1	1216.9	1273.6	1330.4	1447.9	1565.3	1723.1	1880.9
25°	985.3	994.9	1004.6	1028.4	1052.3	1106.8	1161.2	1239.0	1316.8	1474.0	1631.2
27.5°	894.5	897.3	900.2	917.8	935.3	970.5	1005.7	1077.8	1149.9	1279.3	1408.7
30°	819.6	824.7	829.8	843.4	857.0	882.6	908.1	959.2	1010.3	1126.1	1241.8
32.5°	761.7	764.5	767.3	778.7	790.1	808.8	827.5	867.8	908.1	996.6	1085.2
35°	711.7	712.3	712.9	721.4	729.9	748.1	766.2	799.7	833.2	898.5	963.7
37.5°	655.0	658.9	662.9	669.2	675.4	691.3	707.2	734.4	761.7	815.6	869.5
40°	607.3	610.7	614.1	621.5	628.9	641.3	653.8	678.8	703.8	750.3	796.9
42.5°	559.6	561.9	564.2	571.5	578.9	594.2	609.6	629.4	649.3	687.9	726.5
45°	506.3	511.9	517.6	525.6	533.5	546.6	559.6	580.1	600.5	633.4	666.3
47.5°	462.0	464.8	467.7	474.5	481.3	497.2	513.1	531.2	549.4	580.1	610.7
50°	417.7	418.9	420.0	426.2	432.5	446.7	460.9	481.9	502.9	531.2	559.6
52.5°	375.7	378.6	381.4	387.6	393.9	403.5	413.2	434.8	456.3	484.1	511.9
55°	337.1	338.8	340.5	345.1	349.6	361.0	372.3	391.1	409.8	435.3	460.9
57.5°	300.8	303.1	305.4	308.8	312.2	322.4	332.6	349.1	365.5	391.1	416.6
60°	263.4	266.2	269.0	273.0	277.0	284.9	292.9	307.6	322.4	345.1	367.8
62.5°	236.1	236.7	237.2	240.6	244.1	249.7	255.4	267.3	279.2	301.9	324.6
65°	205.5	207.2	208.9	210.6	212.3	216.8	221.4	231.6	241.8	258.8	275.8
67.5°	173.7	175.4	177.1	179.9	182.8	186.7	190.7	197.5	204.3	220.2	236.1
70°	135.1	135.1	135.1	139.6	144.2	151.0	157.8	162.9	168.0	181.1	194.1
72.5°	110.1	110.7	111.2	111.8	112.4	116.4	120.3	128.8	137.4	145.3	153.2
75°	89.7	90.2	90.8	91.4	91.9	93.1	94.2	97.1	99.9	109.0	118.1
77.5°	71.5	72.1	72.6	73.2	73.8	74.9	76.1	77.2	78.3	81.7	85.1
80°	54.5	55.1	55.6	56.2	56.8	57.3	57.9	59.0	60.2	61.9	63.6
82.5°	39.7	39.7	39.7	39.7	39.7	40.9	42.0	42.0	42.0	43.1	44.3
85°	25.0	25.0	25.0	25.5	26.1	26.1	26.1	26.7	27.2	27.2	27.2
87.5°	11.4	10.8	10.2	10.8	11.4	11.4	11.4	11.9	12.5	12.5	12.5
90°	33.2	32.7	32.2	31.7	31.2	30.5	29.5	28.5	27.6	26.6	23.4
92.5°	47.6	48.1	48.6	49.1	49.6	49.4	48.7	48.0	47.2	46.5	45.0
95°	86.3	86.3	86.3	86.3	86.3	85.9	84.9	83.9	82.9	81.9	80.0
97.5°	124.0	124.2	124.5	124.7	125.0	124.5	123.2	122.0	120.8	119.6	118.1
100°	168.3	167.8	167.3	166.8	166.3	165.7	164.9	164.2	163.5	162.7	161.5
102.5°	213.7	213.9	214.1	214.4	214.6	214.4	213.7	212.9	212.2	211.4	209.7
105°	263.5	263.0	262.5	262.0	261.5	261.3	261.3	261.3	261.3	261.3	259.0
107.5°	314.4	314.6	314.9	315.1	315.4	315.1	314.4	313.7	312.9	312.2	311.2
110°	366.4	366.9	367.4	367.9	368.4	368.1	367.2	366.2	365.2	364.2	363.7



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	421.8	421.8	421.8	421.8	421.8	421.2	419.9	418.7	417.5	416.2	416.2
115°	471.6	471.8	472.1	472.3	472.6	472.6	472.3	472.1	471.8	471.6	472.1
117.5°	522.5	523.2	524.0	524.7	525.5	525.8	525.8	525.8	525.8	525.8	526.3
120°	576.8	577.2	577.7	578.2	578.7	579.1	579.3	579.6	579.8	580.1	581.3
122.5°	628.8	629.5	630.3	631.0	631.7	632.5	633.2	633.9	634.7	635.4	635.9
125°	680.8	681.8	682.8	683.8	684.7	685.7	686.7	687.7	688.7	689.7	690.2
127.5°	732.8	733.8	734.8	735.8	736.8	738.0	739.5	741.0	742.4	743.9	744.4
130°	783.8	785.5	787.2	788.9	790.7	792.0	793.0	794.0	795.0	795.9	796.7
132.5°	836.9	838.1	839.4	840.6	841.8	843.1	844.3	845.5	846.7	848.0	848.5
135°	892.3	892.7	893.2	893.7	894.2	895.0	895.9	896.9	897.9	898.9	899.1
137.5°	941.0	941.7	942.4	943.2	943.9	944.9	946.1	947.4	948.6	949.8	949.1
140°	988.6	990.3	992.0	993.7	995.5	996.4	996.7	996.9	997.2	997.4	997.2
142.5°	1037.3	1038.5	1039.7	1041.0	1042.2	1042.9	1043.2	1043.4	1043.7	1043.9	1043.4
145°	1083.8	1084.7	1085.7	1086.7	1087.7	1088.3	1088.6	1088.8	1089.1	1089.3	1088.6
147.5°	1125.8	1127.3	1128.8	1130.3	1131.7	1132.5	1132.5	1132.5	1132.5	1132.5	1131.7
150°	1165.7	1167.2	1168.6	1170.1	1171.6	1172.3	1172.3	1172.3	1172.3	1172.3	1171.8
152.5°	1204.4	1205.7	1206.9	1208.1	1209.4	1209.7	1209.2	1208.7	1208.2	1207.8	1207.5
155°	1238.7	1240.5	1242.2	1243.9	1245.6	1246.0	1245.0	1244.0	1243.1	1242.1	1241.8
157.5°	1270.9	1272.3	1273.8	1275.3	1276.8	1277.0	1276.0	1275.0	1274.0	1273.1	1272.8
160°	1301.8	1302.8	1303.8	1304.8	1305.8	1305.7	1304.4	1303.2	1302.0	1300.7	1300.7
162.5°	1325.1	1326.8	1328.5	1330.3	1332.0	1332.2	1331.0	1329.8	1328.5	1327.3	1327.1
165°	1347.2	1349.0	1350.7	1352.4	1354.1	1354.2	1352.8	1351.3	1349.8	1348.3	1348.3
167.5°	1367.2	1368.6	1370.1	1371.6	1373.1	1373.1	1371.6	1370.1	1368.6	1367.2	1366.9
170°	1381.6	1383.3	1385.0	1386.7	1388.4	1388.4	1386.7	1385.0	1383.3	1381.6	1381.6
172.5°	1392.6	1394.3	1396.1	1397.8	1399.5	1399.6	1398.2	1396.7	1395.2	1393.7	1393.7
175°	1400.4	1402.1	1403.8	1405.5	1407.3	1407.4	1405.9	1404.4	1403.0	1401.5	1401.5
177.5°	1404.8	1406.5	1408.2	1410.0	1411.7	1411.8	1410.3	1408.9	1407.4	1405.9	1405.9
180°	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6
2.5°	2939.4	2936.6	2909.3	2882.1	2855.4	2828.7	2808.9	2789.0	2755.5	2722.0	2701.0
5°	3121.6	3100.0	3056.9	3013.8	2949.1	2884.4	2829.9	2775.4	2706.2	2636.9	2579.0
7.5°	3223.2	3205.6	3153.4	3101.2	3015.5	2929.8	2844.6	2759.5	2657.3	2555.2	2467.8
10°	3226.0	3240.8	3197.7	3154.5	3058.0	2961.6	2845.8	2730.0	2592.6	2455.3	2342.3
12.5°	3125.0	3188.6	3179.5	3170.4	3072.2	2974.0	2833.3	2692.5	2524.0	2355.4	2214.1
15°	2936.0	3059.2	3095.5	3131.8	3050.7	2969.5	2809.5	2649.4	2451.3	2253.2	2090.9
17.5°	2692.5	2865.1	2961.0	3056.9	2997.9	2938.9	2763.5	2588.1	2365.0	2142.0	1965.5
20°	2404.2	2630.1	2780.5	2930.9	2909.3	2887.8	2706.7	2525.7	2285.0	2044.4	1853.1
22.5°	2119.3	2357.7	2565.4	2773.1	2795.3	2817.4	2634.6	2451.9	2188.5	1925.2	1730.5
25°	1873.5	2115.9	2363.3	2610.8	2660.8	2710.7	2537.0	2363.3	2090.3	1817.3	1623.8
27.5°	1639.1	1869.6	2142.0	2414.4	2505.2	2596.0	2437.1	2278.2	1993.9	1709.5	1516.5
30°	1447.9	1653.9	1932.0	2210.1	2336.7	2463.2	2317.4	2171.5	1889.4	1607.3	1418.3
32.5°	1269.6	1454.1	1733.3	2012.6	2159.6	2306.6	2180.6	2054.6	1783.3	1512.0	1325.3
35°	1128.9	1294.1	1554.6	1815.1	1979.7	2144.3	2041.0	1937.7	1672.6	1407.6	1231.1
37.5°	1008.0	1146.5	1391.1	1635.7	1810.5	1985.3	1899.1	1812.8	1563.6	1314.5	1147.6
40°	908.1	1019.3	1246.9	1474.5	1645.9	1817.3	1743.6	1669.8	1446.7	1223.7	1067.6
42.5°	822.4	918.3	1122.6	1327.0	1484.2	1641.4	1592.6	1543.8	1341.7	1139.7	994.9
45°	746.9	827.5	1007.4	1187.3	1332.1	1476.8	1438.2	1399.6	1225.4	1051.1	918.3
47.5°	679.9	749.2	909.8	1070.4	1200.4	1330.4	1294.6	1258.9	1114.7	970.5	849.6
50°	618.6	677.7	811.6	945.6	1062.5	1179.4	1149.9	1120.4	1001.2	882.0	777.6
52.5°	560.8	609.6	729.9	850.2	944.4	1038.6	1015.9	993.2	901.3	809.3	714.6
55°	505.7	550.5	652.1	753.7	834.3	914.9	892.2	869.5	798.0	726.5	643.1
57.5°	455.8	494.9	577.2	659.5	723.6	787.8	777.0	766.2	706.6	647.0	578.3
60°	403.0	438.2	509.1	580.1	631.7	683.3	670.9	658.4	615.8	573.2	514.2
62.5°	355.9	387.1	443.8	500.6	542.6	584.6	575.5	566.4	534.1	501.7	452.9
65°	306.5	337.1	383.1	429.1	462.0	494.9	487.0	479.0	454.6	430.2	391.1
67.5°	261.6	287.2	326.9	366.6	388.8	410.9	406.4	401.8	383.1	364.4	333.7
70°	216.2	238.4	271.3	304.2	319.5	334.9	336.6	338.3	321.2	304.2	281.5
72.5°	170.8	188.4	219.1	249.7	261.6	273.6	273.0	272.4	262.2	252.0	231.6
75°	131.1	144.2	168.0	191.8	202.1	212.3	214.5	216.8	207.2	197.5	186.2
77.5°	94.2	103.3	121.5	139.6	151.0	162.3	163.5	164.6	160.1	155.5	144.7
80°	66.4	69.2	80.6	91.9	103.9	115.8	117.5	119.2	114.6	110.1	103.3
82.5°	46.0	47.7	51.6	55.6	65.3	74.9	77.2	79.5	77.2	74.9	67.5
85°	27.8	28.4	30.1	31.8	36.3	40.9	43.1	45.4	44.3	43.1	39.2
87.5°	12.5	12.5	13.1	13.6	14.8	15.9	18.7	21.6	19.9	18.2	16.5
90°	20.2	17.0	13.8	10.9	8.5	6.0	3.6	1.1	3.6	6.0	8.5
92.5°	43.5	42.1	40.6	39.1	37.6	36.2	34.7	33.2	34.7	36.2	37.6
95°	78.0	76.0	74.0	72.2	70.5	68.8	67.0	65.3	67.0	68.8	70.5
97.5°	116.6	115.1	113.7	112.3	111.1	109.8	108.6	107.4	108.6	109.8	111.1
100°	160.3	159.0	157.8	156.5	155.0	153.5	152.0	150.6	152.0	153.5	155.0
102.5°	208.0	206.3	204.6	203.3	202.6	201.8	201.1	200.4	201.1	201.8	202.6
105°	256.8	254.6	252.4	251.0	250.6	250.1	249.6	249.1	249.6	250.1	250.6
107.5°	310.2	309.2	308.2	307.6	307.4	307.1	306.9	306.6	306.9	307.1	307.4
110°	363.2	362.7	362.2	361.7	361.3	360.8	360.3	359.8	360.3	360.8	361.3



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	416.2	416.2	416.2	416.1	415.9	415.6	415.4	415.1	415.4	415.6	415.9
115°	472.6	473.1	473.6	473.4	472.7	472.0	471.2	470.5	471.2	472.0	472.7
117.5°	526.8	527.3	527.8	527.9	527.7	527.4	527.2	526.9	527.2	527.4	527.7
120°	582.5	583.8	585.0	584.9	583.4	581.9	580.4	579.0	580.4	581.9	583.4
122.5°	636.4	636.9	637.4	637.1	636.2	635.2	634.2	633.2	634.2	635.2	636.2
125°	690.7	691.1	691.6	691.5	690.8	690.0	689.3	688.6	689.3	690.0	690.8
127.5°	744.9	745.4	745.9	745.4	743.9	742.4	741.0	739.5	741.0	742.4	743.9
130°	797.4	798.2	798.9	798.3	796.3	794.3	792.4	790.4	792.4	794.3	796.3
132.5°	849.0	849.4	849.9	849.2	847.2	845.3	843.3	841.3	843.3	845.3	847.2
135°	899.4	899.6	899.9	899.3	897.8	896.3	894.8	893.4	894.8	896.3	897.8
137.5°	948.3	947.6	946.9	945.9	944.7	943.4	942.2	941.0	942.2	943.4	944.7
140°	996.9	996.7	996.4	995.7	994.5	993.2	992.0	990.8	992.0	993.2	994.5
142.5°	1042.9	1042.4	1041.9	1041.1	1039.9	1038.6	1037.4	1036.2	1037.4	1038.6	1039.9
145°	1087.8	1087.1	1086.3	1085.7	1085.2	1084.7	1084.3	1083.8	1084.3	1084.7	1085.2
147.5°	1131.0	1130.3	1129.5	1128.7	1127.7	1126.7	1125.7	1124.7	1125.7	1126.7	1127.7
150°	1171.3	1170.9	1170.4	1169.9	1169.4	1168.9	1168.4	1167.9	1168.4	1168.9	1169.4
152.5°	1207.3	1207.0	1206.8	1206.3	1205.5	1204.8	1204.1	1203.3	1204.1	1204.8	1205.5
155°	1241.6	1241.3	1241.1	1241.0	1241.0	1241.0	1241.0	1241.0	1241.0	1241.0	1241.0
157.5°	1272.6	1272.3	1272.1	1272.1	1272.3	1272.6	1272.8	1273.1	1272.8	1272.6	1272.3
160°	1300.7	1300.7	1300.7	1301.0	1301.5	1302.0	1302.5	1303.0	1302.5	1302.0	1301.5
162.5°	1326.8	1326.6	1326.3	1326.6	1327.3	1328.0	1328.8	1329.5	1328.8	1328.0	1327.3
165°	1348.3	1348.3	1348.3	1348.7	1349.4	1350.2	1350.9	1351.7	1350.9	1350.2	1349.4
167.5°	1366.7	1366.4	1366.2	1366.5	1367.5	1368.5	1369.5	1370.5	1369.5	1368.5	1367.5
170°	1381.6	1381.6	1381.6	1382.0	1383.0	1384.0	1385.0	1386.0	1385.0	1384.0	1383.0
172.5°	1393.7	1393.7	1393.7	1394.2	1395.2	1396.2	1397.2	1398.2	1397.2	1396.2	1395.2
175°	1401.5	1401.5	1401.5	1402.0	1403.0	1403.9	1404.9	1405.9	1404.9	1403.9	1403.0
177.5°	1405.9	1405.9	1405.9	1406.4	1407.4	1408.4	1409.4	1410.3	1409.4	1408.4	1407.4
180°	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6	2768.6
2.5°	2680.0	2647.7	2615.3	2592.1	2568.8	2539.9	2510.9	2509.8	2508.6	2487.1	2465.5
5°	2521.1	2464.9	2408.8	2353.7	2298.6	2243.6	2188.5	2176.0	2163.6	2144.8	2126.1
7.5°	2380.4	2290.7	2201.0	2130.6	2060.3	2005.2	1950.2	1912.7	1875.2	1846.3	1817.3
10°	2229.4	2118.2	2006.9	1921.8	1836.6	1777.0	1717.5	1674.3	1631.2	1610.8	1590.3
12.5°	2072.8	1951.9	1831.0	1747.5	1664.1	1592.6	1521.1	1481.9	1442.8	1414.4	1386.0
15°	1928.6	1798.6	1668.6	1580.1	1491.6	1424.6	1357.6	1318.5	1279.3	1250.9	1222.5
17.5°	1789.0	1657.9	1526.8	1437.1	1347.4	1286.7	1225.9	1187.9	1149.9	1132.3	1114.7
20°	1661.8	1529.6	1397.3	1312.8	1228.2	1168.6	1109.0	1088.6	1068.2	1051.7	1035.2
22.5°	1535.8	1408.7	1281.6	1200.4	1119.2	1076.1	1033.0	1016.5	1000.1	987.6	975.1
25°	1430.3	1303.7	1177.1	1106.2	1035.2	1001.8	968.3	957.5	946.7	934.2	921.7
27.5°	1323.6	1203.2	1082.9	1026.2	969.4	942.2	914.9	901.3	887.7	877.5	867.2
30°	1229.3	1118.1	1006.9	959.8	912.6	888.8	865.0	850.2	835.5	825.8	816.2
32.5°	1138.5	1039.8	941.0	900.7	860.4	837.2	813.9	799.7	785.5	774.2	762.8
35°	1054.5	968.8	883.1	846.2	809.3	786.1	762.8	748.6	734.4	723.1	711.7
37.5°	980.8	903.0	825.2	790.6	756.0	735.6	715.1	700.4	685.6	673.7	661.8
40°	911.5	842.8	774.2	740.7	707.2	685.1	662.9	649.9	636.8	626.0	615.2
42.5°	850.2	787.2	724.2	691.3	658.4	637.4	616.4	601.1	585.7	579.5	573.2
45°	785.5	729.9	674.3	642.5	610.7	588.6	566.4	553.4	540.3	534.6	529.0
47.5°	728.8	677.1	625.5	594.2	563.0	543.2	523.3	513.1	502.9	494.9	487.0
50°	673.1	623.2	573.2	543.2	513.1	496.1	479.0	466.5	454.1	448.4	442.7
52.5°	619.8	574.4	529.0	498.3	467.7	451.2	434.8	424.0	413.2	401.3	389.4
55°	559.6	519.9	480.2	452.9	425.7	408.6	391.6	379.1	366.6	354.2	341.7
57.5°	509.7	470.5	431.4	406.9	382.5	366.1	349.6	336.0	322.4	312.2	301.9
60°	455.2	421.1	387.1	363.2	339.4	323.5	307.6	294.6	281.5	276.4	271.3
62.5°	404.1	372.3	340.5	319.5	298.5	283.2	267.9	259.4	250.9	247.5	244.1
65°	351.9	324.6	297.4	278.1	258.8	245.8	232.7	228.7	224.8	221.9	219.1
67.5°	303.1	279.8	256.5	239.5	222.5	213.4	204.3	199.8	195.2	191.8	188.4
70°	258.8	238.4	217.9	203.2	188.4	179.9	171.4	167.4	163.5	157.2	151.0
72.5°	211.1	195.2	179.4	168.0	156.6	149.3	141.9	133.9	126.0	120.3	114.6
75°	174.8	158.9	143.0	132.2	121.5	112.9	104.4	101.6	98.8	97.1	95.4
77.5°	133.9	120.3	106.7	98.2	89.7	85.7	81.7	80.0	78.3	77.8	77.2
80°	96.5	85.1	73.8	69.2	64.7	63.6	62.4	61.3	60.2	59.6	59.0
82.5°	60.2	54.5	48.8	47.7	46.5	46.0	45.4	44.8	44.3	43.7	43.1
85°	35.2	32.9	30.6	30.1	29.5	28.9	28.4	28.4	28.4	28.4	28.4
87.5°	14.8	14.8	14.8	14.8	14.8	14.8	14.8	14.8	14.8	14.2	13.6
90°	10.9	13.8	17.0	20.2	23.4	26.6	27.6	28.5	29.5	30.5	31.2
92.5°	39.1	40.6	42.1	43.5	45.0	46.5	47.2	48.0	48.7	49.4	49.6
95°	72.2	74.0	76.0	78.0	80.0	81.9	82.9	83.9	84.9	85.9	86.3
97.5°	112.3	113.7	115.1	116.6	118.1	119.6	120.8	122.0	123.2	124.5	125.0
100°	156.5	157.8	159.0	160.3	161.5	162.7	163.5	164.2	164.9	165.7	166.3
102.5°	203.3	204.6	206.3	208.0	209.7	211.4	212.2	212.9	213.7	214.4	214.6
105°	251.0	252.4	254.6	256.8	259.0	261.3	261.3	261.3	261.3	261.3	261.5
107.5°	307.6	308.2	309.2	310.2	311.2	312.2	312.9	313.7	314.4	315.1	315.4
110°	361.7	362.2	362.7	363.2	363.7	364.2	365.2	366.2	367.2	368.1	368.4



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	416.1	416.2	416.2	416.2	416.2	416.2	417.5	418.7	419.9	421.2	421.8
115°	473.4	473.6	473.1	472.6	472.1	471.6	471.8	472.1	472.3	472.6	472.6
117.5°	527.9	527.8	527.3	526.8	526.3	525.8	525.8	525.8	525.8	525.8	525.5
120°	584.9	585.0	583.8	582.5	581.3	580.1	579.8	579.6	579.3	579.1	578.7
122.5°	637.1	637.4	636.9	636.4	635.9	635.4	634.7	633.9	633.2	632.5	631.7
125°	691.5	691.6	691.1	690.7	690.2	689.7	688.7	687.7	686.7	685.7	684.7
127.5°	745.4	745.9	745.4	744.9	744.4	743.9	742.4	741.0	739.5	738.0	736.8
130°	798.3	798.9	798.2	797.4	796.7	795.9	795.0	794.0	793.0	792.0	790.7
132.5°	849.2	849.9	849.4	849.0	848.5	848.0	846.7	845.5	844.3	843.1	841.8
135°	899.3	899.9	899.6	899.4	899.1	898.9	897.9	896.9	895.9	895.0	894.2
137.5°	945.9	946.9	947.6	948.3	949.1	949.8	948.6	947.4	946.1	944.9	943.9
140°	995.7	996.4	996.7	996.9	997.2	997.4	997.2	996.9	996.7	996.4	995.5
142.5°	1041.1	1041.9	1042.4	1042.9	1043.4	1043.9	1043.7	1043.4	1043.2	1042.9	1042.2
145°	1085.7	1086.3	1087.1	1087.8	1088.6	1089.3	1089.1	1088.8	1088.6	1088.3	1087.7
147.5°	1128.7	1129.5	1130.3	1131.0	1131.7	1132.5	1132.5	1132.5	1132.5	1132.5	1131.7
150°	1169.9	1170.4	1170.9	1171.3	1171.8	1172.3	1172.3	1172.3	1172.3	1172.3	1171.6
152.5°	1206.3	1206.8	1207.0	1207.3	1207.5	1207.8	1208.2	1208.7	1209.2	1209.7	1209.4
155°	1241.0	1241.1	1241.3	1241.6	1241.8	1242.1	1243.1	1244.0	1245.0	1246.0	1245.6
157.5°	1272.1	1272.1	1272.3	1272.6	1272.8	1273.1	1274.0	1275.0	1276.0	1277.0	1276.8
160°	1301.0	1300.7	1300.7	1300.7	1300.7	1300.7	1302.0	1303.2	1304.4	1305.7	1305.8
162.5°	1326.6	1326.3	1326.6	1326.8	1327.1	1327.3	1328.5	1329.8	1331.0	1332.2	1332.0
165°	1348.7	1348.3	1348.3	1348.3	1348.3	1348.3	1349.8	1351.3	1352.8	1354.2	1354.1
167.5°	1366.5	1366.2	1366.4	1366.7	1366.9	1367.2	1368.6	1370.1	1371.6	1373.1	1373.1
170°	1382.0	1381.6	1381.6	1381.6	1381.6	1381.6	1383.3	1385.0	1386.7	1388.4	1388.4
172.5°	1394.2	1393.7	1393.7	1393.7	1393.7	1393.7	1395.2	1396.7	1398.2	1399.6	1399.5
175°	1402.0	1401.5	1401.5	1401.5	1401.5	1401.5	1403.0	1404.4	1405.9	1407.4	1407.3
177.5°	1406.4	1405.9	1405.9	1405.9	1405.9	1405.9	1407.4	1408.9	1410.3	1411.8	1411.7
180°	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2	1409.2

TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
0°	2768.6	2768.6	2768.6	2768.6
2.5°	2459.8	2454.2	2451.9	2449.6
5°	2108.5	2090.9	2086.9	2083.0
7.5°	1810.0	1802.6	1778.2	1753.8
10°	1567.6	1544.9	1534.7	1524.5
12.5°	1365.0	1344.0	1340.6	1337.2
15°	1207.8	1193.0	1187.9	1182.8
17.5°	1104.5	1094.3	1088.0	1081.8
20°	1027.9	1020.5	1015.9	1011.4
22.5°	969.4	963.7	960.3	956.9
25°	913.2	904.7	901.9	899.0
27.5°	859.9	852.5	849.6	846.8
30°	809.9	803.7	799.7	795.7
32.5°	755.4	748.1	745.8	743.5
35°	707.2	702.6	700.4	698.1
37.5°	656.1	650.4	647.0	643.6
40°	612.4	609.6	607.9	606.2
42.5°	568.1	563.0	562.5	561.9
45°	523.9	518.8	517.6	516.5
47.5°	482.4	477.9	477.3	476.8
50°	436.5	430.2	425.7	421.1
52.5°	383.7	378.0	374.0	370.1
55°	335.4	329.2	325.8	322.4
57.5°	299.1	296.3	294.6	292.9
60°	269.6	267.9	266.8	265.6
62.5°	242.4	240.6	240.6	240.6
65°	217.4	215.7	214.0	212.3
67.5°	185.0	181.6	181.1	180.5
70°	145.9	140.8	140.2	139.6
72.5°	114.1	113.5	112.4	111.2
75°	94.2	93.1	93.1	93.1
77.5°	76.1	74.9	74.9	74.9
80°	58.5	57.9	58.5	59.0
82.5°	43.1	43.1	42.6	42.0
85°	27.8	27.2	27.2	27.2
87.5°	13.6	13.6	13.6	13.6
90°	31.7	32.2	32.7	33.2
92.5°	49.1	48.6	48.1	47.6
95°	86.3	86.3	86.3	86.3
97.5°	124.7	124.5	124.2	124.0
100°	166.8	167.3	167.8	168.3
102.5°	214.4	214.1	213.9	213.7
105°	262.0	262.5	263.0	263.5
107.5°	315.1	314.9	314.6	314.4
110°	367.9	367.4	366.9	366.4



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
112.5°	421.8	421.8	421.8	421.8
115°	472.3	472.1	471.8	471.6
117.5°	524.7	524.0	523.2	522.5
120°	578.2	577.7	577.2	576.8
122.5°	631.0	630.3	629.5	628.8
125°	683.8	682.8	681.8	680.8
127.5°	735.8	734.8	733.8	732.8
130°	788.9	787.2	785.5	783.8
132.5°	840.6	839.4	838.1	836.9
135°	893.7	893.2	892.7	892.3
137.5°	943.2	942.4	941.7	941.0
140°	993.7	992.0	990.3	988.6
142.5°	1041.0	1039.7	1038.5	1037.3
145°	1086.7	1085.7	1084.7	1083.8
147.5°	1130.3	1128.8	1127.3	1125.8
150°	1170.1	1168.6	1167.2	1165.7
152.5°	1208.1	1206.9	1205.7	1204.4
155°	1243.9	1242.2	1240.5	1238.7
157.5°	1275.3	1273.8	1272.3	1270.9
160°	1304.8	1303.8	1302.8	1301.8
162.5°	1330.3	1328.5	1326.8	1325.1
165°	1352.4	1350.7	1349.0	1347.2
167.5°	1371.6	1370.1	1368.6	1367.2
170°	1386.7	1385.0	1383.3	1381.6
172.5°	1397.8	1396.1	1394.3	1392.6
175°	1405.5	1403.8	1402.1	1400.4
177.5°	1410.0	1408.2	1406.5	1404.8
180°	1409.2	1409.2	1409.2	1409.2



TEST NUMBER: P832315

CATALOG NUMBER: S123RDIP-S775D1025U850-4F0-1E-UDD-G1

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.39	13.19	13.38	14.18	15.47	17.06	17.85	18.04	18.84	20.14
	3H	13.61	14.32	14.60	15.32	16.64	18.55	19.27	19.55	20.26	21.58
	4H	13.99	14.67	15.00	15.67	16.99	19.04	19.72	20.05	20.71	22.04
	6H	14.27	14.89	15.29	15.90	17.23	19.35	19.97	20.37	20.98	22.31
	8H	14.36	14.95	15.38	15.97	17.30	19.43	20.02	20.45	21.04	22.37
	12H	14.41	14.97	15.44	15.98	17.34	19.46	20.02	20.49	21.03	22.39
4H	2H	13.11	13.79	14.12	14.78	16.11	17.05	17.72	18.06	18.72	20.05
	3H	14.48	15.04	15.50	16.07	17.41	18.70	19.26	19.72	20.29	21.63
	4H	14.93	15.44	15.96	16.46	17.83	19.31	19.82	20.34	20.84	22.20
	6H	15.30	15.74	16.34	16.78	18.14	19.75	20.18	20.78	21.23	22.59
	8H	15.42	15.83	16.46	16.87	18.24	19.88	20.28	20.91	21.32	22.70
	12H	15.50	15.87	16.55	16.92	18.30	19.94	20.30	20.99	21.36	22.74
8H	4H	15.25	15.65	16.28	16.69	18.07	19.27	19.68	20.31	20.72	22.09
	6H	15.71	16.04	16.77	17.12	18.50	19.77	20.11	20.83	21.18	22.56
	8H	15.90	16.20	16.97	17.26	18.65	19.96	20.25	21.02	21.31	22.71
	12H	16.04	16.30	17.11	17.36	18.79	20.07	20.33	21.14	21.39	22.82
12H	4H	15.26	15.62	16.31	16.67	18.05	19.22	19.59	20.28	20.64	22.02
	6H	15.77	16.06	16.84	17.13	18.52	19.74	20.04	20.81	21.10	22.49
	8H	15.98	16.24	17.06	17.30	18.74	19.94	20.20	21.01	21.25	22.69