

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P831260

Luminaire Tested: S123DIP-S1165D365U950-4F0-1E-UDD-G4

Issue Date: 05/03/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P831260  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2301-905-1, G3-1807-864-17)  
Test Lab: INNOVATION CENTER  
Issue Date: 05/03/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: S123DIP-S1165D365U950-4F0-1E-UDD-G4  
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE  
DOWNLIGHT 1165 LUMENS PER FOOT, GRAZE OPTIC  
UPLIGHT 365 LUMENS PER FOOT, BATWING OPTIC  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 6333.2 lumens  
Efficiency: N/A  
Efficacy: 121.3 lumens/watt  
Spacing Criteria (0/90/45): 0.65 / 1.19 / 0.89  
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')  
CIE Type: Semi-Direct

Input Watts (W): 52.2  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

### Luminous Intensity Polar Plot





TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	114	114	114	114	109	109	109	109	100	100	100	92	92	92	84	84	84	84	84	84	80	
1	105	101	97	94	101	97	94	91	89	87	84	82	80	78	75	74	73	73	73	73	69	
2	97	89	83	78	92	86	81	76	79	75	71	73	70	67	68	65	62	62	62	62	59	
3	89	80	72	67	85	77	70	65	71	66	61	66	61	58	61	57	54	54	54	54	52	
4	82	71	64	58	78	69	62	56	64	58	53	59	54	51	55	51	48	48	48	48	45	
5	76	64	56	50	73	62	55	49	58	52	47	54	49	45	50	46	43	43	43	43	40	
6	71	59	50	45	67	57	49	44	53	47	42	49	44	40	46	42	38	38	38	38	36	
7	66	54	46	40	63	52	44	39	49	42	38	46	40	36	43	38	35	35	35	35	32	
8	61	49	41	36	59	48	40	35	45	39	34	42	37	33	40	35	31	31	31	31	29	
9	58	45	38	33	55	44	37	32	42	35	31	39	34	30	37	32	29	29	29	29	27	
10	54	42	35	30	52	41	34	30	39	33	29	37	31	28	35	30	27	27	27	27	25	

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°	135°	180°
0°	34013	34013	34013	34013	34013
5°	43015	40599	34317	27654	25412
10°	43432	44746	34088	22045	19264
15°	32712	41545	33857	18668	16291
20°	22793	33617	33424	16325	14797
25°	17380	25852	32687	15020	13879
30°	15035	20539	31510	14097	13140
35°	13950	17341	30154	13429	12620
40°	13207	15556	28247	12795	12444
45°	12767	14397	25825	12298	12365
50°	12548	13480	22958	11848	12301
55°	12080	12810	20142	11419	12356
60°	11649	12090	17362	11016	12152
65°	10942	11410	14976	10588	11915
70°	10106	10543	12737	9876	11213
75°	9145	9453	10917	9179	10243
80°	7544	8269	8635	7996	8635
85°	5978	6706	6336	6793	6879

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 80°  
 Vertical Angle: 45°  
 Luminance: 29486 cd/sqm



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	298.7	4.7
10°-20°	743.2	11.7
20°-30°	880.0	13.9
30°-40°	884.8	14.0
40°-50°	811.8	12.8
50°-60°	670.0	10.6
60°-70°	474.0	7.5
70°-80°	253.0	4.0
80°-90°	65.1	1.0
90°-100°	90.4	1.4
100°-110°	264.6	4.2
110°-120°	258.4	4.1
120°-130°	205.8	3.2
130°-140°	162.3	2.6
140°-150°	121.1	1.9
150°-160°	84.4	1.3
160°-170°	49.6	0.8
170°-180°	16.1	0.3
0°-30°	1921.9	30.3
0°-40°	2806.7	44.3
0°-60°	4288.4	67.7
0°-90°	5080.5	80.2
90°-120°	613.3	9.7
90°-150°	1102.5	17.4
90°-180°	1253.0	19.8
0°-180°	6333.2	100.0

**CANDELA DISTRIBUTION:**

	0°	45°	90°	135°	180°	Flux
0°	3160	3160	3160	3160	3160	
5°	3981	3757	3176	2559	2352	379
15°	2936	3728	3038	1675	1462	811
25°	1463	2177	2752	1265	1169	691
35°	1062	1320	2295	1022	960	667
45°	839	946	1696	808	812	650
55°	644	683	1073	608	658	576
65°	430	448	588	416	468	427
75°	220	227	262	221	246	231
85°	48	54	51	55	56	54
90°	10	8	1	8	10	8
95°	39	200	12	200	39	64
105°	429	271	39	271	429	428
115°	522	207	69	207	522	509
125°	411	194	96	194	411	372
135°	333	191	113	191	333	259
145°	261	188	128	188	261	165
155°	216	182	146	182	216	101
165°	188	175	160	175	188	54
175°	170	168	166	168	170	16
180°	166	166	166	166	166	



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9
2.5°	3561.6	3558.0	3554.3	3536.0	3517.7	3508.9	3500.1	3473.7	3447.3	3417.9	3388.6
5°	3981.0	3991.3	4001.5	3989.8	3978.1	3942.2	3906.2	3858.6	3810.9	3757.4	3703.9
7.5°	4174.6	4180.4	4186.3	4179.0	4171.6	4162.1	4152.6	4110.0	4067.5	4012.5	3957.5
10°	3973.7	3986.9	4000.1	4028.7	4057.3	4089.5	4121.8	4115.9	4110.0	4093.9	4077.8
12.5°	3532.3	3548.4	3564.6	3621.8	3679.0	3752.3	3825.6	3888.6	3951.7	3995.7	4039.7
15°	2935.5	2980.3	3025.0	3077.0	3129.1	3236.9	3344.6	3477.3	3610.0	3728.1	3846.1
17.5°	2417.9	2434.8	2451.7	2507.4	2563.1	2698.7	2834.4	2987.6	3140.8	3336.6	3532.3
20°	1989.8	2005.2	2020.6	2093.9	2167.2	2273.5	2379.8	2552.1	2724.4	2934.8	3145.2
22.5°	1671.6	1695.8	1720.0	1761.0	1802.1	1904.0	2005.9	2159.1	2312.4	2544.8	2777.2
25°	1463.4	1481.0	1498.6	1523.5	1548.4	1629.8	1711.2	1837.3	1963.4	2176.7	2390.1
27.5°	1321.1	1328.5	1335.8	1360.7	1385.7	1438.4	1491.2	1599.7	1708.2	1889.3	2070.4
30°	1209.7	1214.8	1220.0	1242.0	1264.0	1299.9	1335.8	1414.2	1492.7	1652.5	1812.3
32.5°	1132.0	1135.7	1139.3	1156.2	1173.0	1198.7	1224.4	1281.5	1338.7	1470.7	1602.7
35°	1061.6	1063.8	1066.0	1078.5	1090.9	1110.0	1129.1	1172.3	1215.6	1319.7	1423.8
37.5°	1000.0	1003.0	1005.9	1013.2	1020.5	1037.4	1054.3	1088.7	1123.2	1203.1	1283.0
40°	939.9	945.0	950.2	955.3	960.4	974.4	988.3	1014.7	1041.1	1107.1	1173.0
42.5°	888.6	893.7	898.8	901.0	903.2	911.3	919.4	943.6	967.8	1016.9	1066.0
45°	838.7	840.9	843.1	845.3	847.5	854.1	860.7	882.0	903.2	945.8	988.3
47.5°	793.3	793.3	793.3	794.7	796.2	802.1	807.9	823.3	838.7	871.7	904.7
50°	749.3	749.3	749.3	747.1	744.9	748.5	752.2	763.9	775.7	805.0	834.3
52.5°	696.5	696.5	696.5	697.2	698.0	698.0	698.0	708.2	718.5	744.9	771.3
55°	643.7	646.6	649.6	647.4	645.2	646.6	648.1	654.7	661.3	682.6	703.8
57.5°	590.9	592.4	593.9	593.1	592.4	593.1	593.9	599.7	605.6	621.7	637.8
60°	541.1	541.1	541.1	539.6	538.1	539.6	541.1	544.0	546.9	561.6	576.3
62.5°	485.3	486.1	486.8	487.5	488.3	486.8	485.3	489.0	492.7	503.7	514.7
65°	429.6	430.4	431.1	433.3	435.5	434.0	432.6	436.2	439.9	448.0	456.0
67.5°	379.8	378.3	376.8	377.6	378.3	380.5	382.7	383.4	384.2	393.0	401.8
70°	321.1	322.6	324.1	323.3	322.6	323.3	324.1	326.3	328.5	335.0	341.6
72.5°	268.3	269.1	269.8	269.8	269.8	271.3	272.7	274.9	277.1	280.8	284.5
75°	219.9	219.9	219.9	221.4	222.9	223.6	224.3	224.3	224.3	227.3	230.2
77.5°	167.2	170.8	174.5	173.8	173.0	174.5	176.0	178.2	180.4	181.8	183.3
80°	121.7	121.7	121.7	122.4	123.2	125.4	127.6	129.0	130.5	133.4	136.4
82.5°	77.7	78.4	79.2	81.4	83.6	85.0	86.5	88.7	90.9	90.9	90.9
85°	48.4	46.9	45.5	46.9	48.4	49.9	51.3	52.1	52.8	54.3	55.7
87.5°	23.5	23.5	23.5	23.5	23.5	24.2	24.9	24.9	24.9	24.9	24.9
90°	9.8	10.1	9.8	9.4	9.8	9.1	8.8	8.4	8.1	8.4	7.4
92.5°	17.9	18.5	18.2	19.6	20.2	22.6	26.0	33.4	46.9	62.7	69.4
95°	39.1	40.5	42.8	45.8	52.3	64.4	82.3	121.4	162.2	199.9	178.0
97.5°	80.2	83.9	92.0	104.8	127.4	165.9	210.4	278.8	317.9	307.5	229.6
100°	211.4	211.0	224.2	248.8	282.8	330.7	370.2	397.5	385.7	319.3	215.8
102.5°	334.8	344.5	355.0	373.2	397.8	423.8	442.6	436.9	389.0	297.3	195.5
105°	428.8	430.5	441.3	454.1	469.6	478.4	472.0	438.3	367.8	271.0	179.7
107.5°	490.2	493.9	498.3	504.3	506.4	497.3	471.0	418.0	337.5	247.8	168.2
110°	525.2	525.9	526.6	523.9	514.5	490.9	448.4	386.3	309.1	228.6	162.2



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	532.3	532.0	528.6	518.8	499.6	467.6	418.7	355.0	284.5	215.8	158.8
115°	521.5	519.8	513.1	498.3	473.0	436.2	386.7	328.0	265.7	207.3	158.4
117.5°	497.9	495.6	485.5	468.9	442.6	404.6	359.0	307.1	253.2	201.6	158.8
120°	466.9	464.9	456.8	437.9	411.3	377.2	336.8	291.3	243.7	197.9	160.1
122.5°	437.9	435.2	426.1	409.6	386.7	355.7	318.9	278.8	236.0	195.5	162.5
125°	411.3	408.9	400.5	385.7	364.1	337.1	304.8	268.0	229.6	193.5	164.9
127.5°	388.4	386.3	378.6	365.8	346.2	321.3	291.6	258.2	223.5	192.5	167.6
130°	369.5	366.8	359.7	347.6	329.7	306.8	279.5	249.1	218.8	191.5	170.2
132.5°	350.9	349.3	343.2	331.1	314.5	293.0	268.0	240.7	214.4	191.2	172.3
135°	333.4	331.1	325.0	314.9	298.4	279.1	257.2	233.3	210.7	190.8	174.3
137.5°	314.9	312.9	307.8	297.3	283.2	266.0	246.4	226.2	207.3	190.1	175.6
140°	295.3	295.7	290.3	280.8	268.0	253.5	237.3	220.1	204.3	189.8	177.0
142.5°	277.1	277.5	272.7	264.6	254.2	242.1	228.6	214.4	201.6	189.1	178.0
145°	260.6	259.9	257.2	250.1	241.7	231.9	221.2	210.0	199.2	188.5	178.3
147.5°	246.4	246.1	243.4	238.3	231.6	224.5	215.4	206.3	196.9	187.4	178.3
150°	234.3	234.3	232.3	228.6	223.5	217.1	210.0	202.3	194.5	186.1	178.3
152.5°	224.2	224.2	223.2	219.8	216.1	211.0	205.0	198.6	191.8	184.4	177.3
155°	216.1	215.8	215.1	212.4	209.4	205.3	200.3	194.9	189.1	182.4	176.7
157.5°	208.3	208.3	207.7	205.6	202.9	199.6	195.5	190.8	186.1	180.7	175.6
160°	200.9	201.3	201.3	199.2	196.9	194.5	191.2	187.4	183.1	178.7	175.0
162.5°	194.2	194.5	194.5	192.8	191.5	189.5	186.4	183.4	180.0	176.7	173.6
165°	188.5	188.5	188.8	187.4	186.1	184.4	182.0	180.0	177.3	174.6	172.3
167.5°	182.7	182.7	183.1	182.0	181.4	180.0	178.7	177.0	174.6	172.6	170.9
170°	177.7	177.7	178.0	177.3	177.0	176.3	175.0	174.0	172.3	170.6	169.6
172.5°	172.9	173.3	174.0	173.3	173.3	172.9	171.9	171.3	169.9	168.9	168.6
175°	169.6	169.9	170.2	169.9	169.9	169.9	169.2	168.9	168.2	167.6	167.6
177.5°	167.2	167.2	167.9	167.6	167.9	167.9	167.6	167.2	166.9	166.5	166.9
180°	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9
2.5°	3379.8	3371.0	3338.8	3306.5	3269.9	3233.2	3206.1	3178.9	3138.6	3098.3	3065.3
5°	3662.8	3621.8	3553.6	3485.4	3393.0	3300.6	3238.3	3176.0	3092.4	3008.9	2942.1
7.5°	3887.2	3816.8	3721.5	3626.2	3505.2	3384.2	3269.9	3155.5	3027.9	2900.3	2796.2
10°	4030.1	3982.5	3872.5	3762.5	3600.5	3438.5	3278.6	3118.8	2954.6	2790.4	2652.5
12.5°	4044.1	4048.5	3947.3	3846.1	3662.8	3479.5	3285.2	3091.0	2884.2	2677.5	2516.9
15°	3921.6	3997.1	3941.4	3885.7	3700.9	3516.2	3277.2	3038.2	2799.9	2561.6	2376.1
17.5°	3694.3	3856.4	3864.4	3872.5	3687.7	3503.0	3238.3	2973.7	2703.9	2434.1	2239.0
20°	3384.2	3623.2	3705.3	3787.5	3637.2	3486.9	3202.4	2917.9	2615.9	2313.8	2109.3
22.5°	3067.5	3357.8	3508.1	3658.4	3547.0	3435.5	3132.8	2830.0	2511.0	2192.1	1984.6
25°	2706.8	3023.5	3254.5	3485.4	3417.2	3349.0	3050.6	2752.2	2412.8	2073.4	1861.5
27.5°	2392.3	2714.1	2992.7	3271.3	3256.7	3242.0	2945.8	2649.6	2302.1	1954.6	1750.0
30°	2112.2	2412.1	2723.7	3035.2	3071.2	3107.1	2821.2	2535.2	2187.0	1838.7	1641.5
32.5°	1864.4	2126.1	2460.5	2794.8	2865.2	2935.5	2677.5	2419.4	2074.8	1730.2	1540.3
35°	1661.3	1898.9	2233.2	2567.5	2655.5	2743.4	2519.1	2294.8	1959.0	1623.2	1442.1
37.5°	1481.7	1680.4	2006.6	2332.9	2440.7	2548.4	2347.5	2146.7	1832.1	1517.6	1351.2
40°	1332.9	1492.7	1792.6	2092.4	2217.0	2341.7	2176.0	2010.3	1711.9	1413.5	1260.3
42.5°	1208.2	1350.5	1622.5	1894.5	2014.0	2133.5	1993.4	1853.4	1588.0	1322.6	1182.6
45°	1101.9	1215.6	1462.6	1709.7	1823.3	1937.0	1816.7	1696.5	1462.6	1228.8	1098.3
47.5°	1002.2	1099.7	1310.9	1522.0	1623.2	1724.4	1630.5	1536.7	1338.7	1140.8	1022.7
50°	912.8	991.2	1176.0	1360.7	1448.7	1536.7	1453.8	1371.0	1208.2	1045.5	942.8
52.5°	835.1	898.8	1053.5	1208.2	1283.7	1359.3	1288.1	1217.0	1088.0	959.0	869.5
55°	758.1	812.3	946.5	1080.7	1132.0	1183.3	1128.3	1073.3	969.2	865.1	789.6
57.5°	686.2	734.6	844.6	954.6	994.2	1033.7	983.9	934.0	855.6	777.1	714.1
60°	615.8	655.4	747.1	838.7	862.9	887.1	846.8	806.5	751.5	696.5	640.0
62.5°	550.6	586.5	654.7	722.9	739.0	755.1	724.4	693.6	651.8	610.0	566.0
65°	483.1	510.3	566.0	621.7	632.0	642.2	615.1	588.0	556.5	524.9	492.7
67.5°	420.8	439.9	485.3	530.8	531.5	532.3	510.3	488.3	470.7	453.1	427.4
70°	360.0	378.3	408.4	438.4	439.2	439.9	422.3	404.7	391.5	378.3	359.2
72.5°	297.7	310.9	333.6	356.3	354.8	353.4	342.4	331.4	321.1	310.9	296.9
75°	241.2	252.2	267.6	283.0	278.6	274.2	268.3	262.5	253.7	244.9	236.1
77.5°	189.9	196.5	205.3	214.1	211.1	208.2	203.1	198.0	191.4	184.8	181.1
80°	139.3	142.2	148.1	154.0	152.5	151.0	145.2	139.3	137.8	136.4	131.2
82.5°	94.6	98.2	99.7	101.2	100.4	99.7	95.3	90.9	89.4	88.0	87.2
85°	56.5	57.2	57.9	58.7	56.5	54.3	52.8	51.3	51.3	51.3	50.6
87.5°	25.7	26.4	26.4	26.4	25.7	24.9	23.5	22.0	22.7	23.5	23.5
90°	6.4	5.4	4.4	3.7	3.0	2.0	1.3	0.7	1.3	2.0	3.0
92.5°	51.9	34.0	23.3	17.2	13.8	10.8	7.4	5.1	7.4	10.8	13.8
95°	122.7	72.5	43.8	30.7	21.9	16.2	12.5	11.5	12.5	16.2	21.9
97.5°	136.5	78.2	49.9	35.4	26.6	21.6	18.5	18.2	18.5	21.6	26.6
100°	127.1	77.2	53.6	40.5	32.4	27.6	25.3	24.9	25.3	27.6	32.4
102.5°	119.0	78.6	58.0	46.2	39.1	34.7	32.7	32.0	32.7	34.7	39.1
105°	116.0	81.2	63.0	52.6	46.2	42.1	40.1	39.1	40.1	42.1	46.2
107.5°	115.3	85.6	69.4	59.7	53.6	49.6	47.5	46.5	47.5	49.6	53.6
110°	117.0	91.4	76.2	66.8	61.0	57.3	55.6	54.6	55.6	57.3	61.0





TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	120.4	97.1	83.3	74.2	68.4	64.7	63.0	62.0	63.0	64.7	68.4
115°	124.1	103.5	90.7	81.6	75.9	72.5	70.5	69.1	70.5	72.5	75.9
117.5°	128.8	110.2	97.4	89.0	82.6	79.6	77.9	76.2	77.9	79.6	82.6
120°	134.2	116.6	104.5	96.1	89.7	86.3	84.6	83.6	84.6	86.3	89.7
122.5°	139.2	123.4	111.6	102.5	96.4	92.7	91.0	90.0	91.0	92.7	96.4
125°	144.6	129.8	118.0	108.9	102.5	98.8	96.8	96.1	96.8	98.8	102.5
127.5°	149.0	135.5	124.1	115.0	107.9	104.2	101.8	100.8	101.8	104.2	107.9
130°	153.4	140.6	129.5	120.4	113.3	109.2	106.2	105.2	106.2	109.2	113.3
132.5°	157.4	145.0	134.2	125.4	118.3	113.3	109.9	108.6	109.9	113.3	118.3
135°	160.8	149.3	138.9	129.8	122.7	117.7	113.9	112.6	113.9	117.7	122.7
137.5°	163.5	152.4	142.3	133.8	126.8	121.4	117.7	116.3	117.7	121.4	126.8
140°	165.5	155.4	145.6	137.2	130.5	125.1	121.7	120.0	121.7	125.1	130.5
142.5°	167.6	157.8	148.3	140.6	133.8	129.1	125.4	124.1	125.4	129.1	133.8
145°	168.9	159.8	151.0	143.3	137.5	132.5	129.5	128.4	129.5	132.5	137.5
147.5°	169.9	161.5	153.4	146.6	140.9	136.5	133.5	132.8	133.5	136.5	140.9
150°	170.2	163.2	155.4	149.3	144.6	140.2	137.5	137.2	137.5	140.2	144.6
152.5°	170.9	164.2	157.8	152.0	148.0	144.3	141.6	141.6	141.6	144.3	148.0
155°	170.9	165.5	159.8	155.1	151.4	148.0	146.0	146.0	146.0	148.0	151.4
157.5°	171.3	166.2	161.5	157.8	154.4	151.4	149.7	149.3	149.7	151.4	154.4
160°	171.3	167.2	163.2	159.8	157.4	154.7	153.4	153.4	153.4	154.7	157.4
162.5°	170.9	167.6	164.2	161.5	159.5	157.4	156.4	156.4	156.4	157.4	159.5
165°	170.2	167.9	165.2	162.8	161.5	159.8	159.1	159.5	159.1	159.8	161.5
167.5°	169.9	167.9	165.9	164.2	163.2	161.8	161.5	161.8	161.5	161.8	163.2
170°	168.9	167.6	165.9	165.2	164.5	163.5	163.2	163.8	163.2	163.5	164.5
172.5°	168.6	167.6	166.2	165.9	165.5	164.9	164.9	165.2	164.9	164.9	165.5
175°	167.9	167.2	166.5	166.2	166.2	165.5	165.9	166.2	165.9	165.5	166.2
177.5°	167.6	166.9	166.5	166.5	166.5	166.2	166.5	166.9	166.5	166.2	166.5
180°	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9	3159.9
2.5°	3032.3	3003.7	2975.1	2953.1	2931.1	2893.7	2856.4	2847.6	2838.8	2826.3	2813.8
5°	2875.4	2805.0	2734.7	2671.6	2608.6	2559.4	2510.3	2478.0	2445.8	2422.3	2398.9
7.5°	2692.1	2586.6	2481.0	2406.2	2331.4	2260.3	2189.2	2166.5	2143.7	2112.9	2082.1
10°	2514.7	2398.1	2281.6	2184.1	2086.5	2016.9	1947.2	1919.4	1891.5	1852.7	1813.8
12.5°	2356.3	2228.8	2101.2	2003.0	1904.7	1837.3	1769.8	1729.5	1689.2	1667.2	1645.2
15°	2190.7	2054.3	1917.9	1827.0	1736.1	1675.2	1614.4	1579.2	1544.0	1522.8	1501.5
17.5°	2044.0	1909.1	1774.2	1687.0	1599.7	1544.0	1488.3	1457.5	1426.7	1410.6	1394.5
20°	1904.7	1772.8	1640.8	1555.7	1470.7	1425.2	1379.8	1360.0	1340.2	1327.0	1313.8
22.5°	1777.2	1647.4	1517.6	1445.0	1372.5	1335.8	1299.1	1285.2	1271.3	1260.3	1249.3
25°	1649.6	1533.8	1417.9	1356.3	1294.7	1264.7	1234.6	1220.7	1206.8	1195.8	1184.8
27.5°	1545.5	1434.8	1324.1	1271.3	1218.5	1195.0	1171.6	1160.6	1149.6	1139.3	1129.1
30°	1444.3	1345.3	1246.4	1200.9	1155.4	1134.2	1112.9	1101.9	1090.9	1081.4	1071.9
32.5°	1350.5	1265.4	1180.4	1138.6	1096.8	1079.2	1061.6	1048.4	1035.2	1027.9	1020.5
35°	1261.0	1184.8	1108.5	1074.1	1039.6	1022.0	1004.4	993.4	982.4	976.6	970.7
37.5°	1184.8	1116.6	1048.4	1015.4	982.4	965.6	948.7	939.2	929.6	927.4	925.2
40°	1107.1	1048.4	989.8	957.5	925.2	910.6	895.9	890.0	884.2	882.7	881.2
42.5°	1042.5	985.4	928.2	898.8	869.5	857.1	844.6	841.7	838.7	840.9	843.1
45°	967.8	920.1	872.4	845.3	818.2	807.9	797.7	795.5	793.3	797.7	802.1
47.5°	904.7	860.7	816.7	791.1	765.4	758.1	750.7	750.0	749.3	755.1	761.0
50°	840.2	797.7	755.1	734.6	714.1	707.5	700.9	703.1	705.3	714.8	724.4
52.5°	780.1	740.5	700.9	681.8	662.8	658.4	654.0	659.1	664.2	674.5	684.8
55°	714.1	678.2	642.2	627.6	612.9	608.5	604.1	614.4	624.6	634.2	643.7
57.5°	651.0	619.5	588.0	574.8	561.6	560.9	560.1	569.7	579.2	589.5	599.7
60°	583.6	557.2	530.8	520.5	510.3	511.7	513.2	524.2	535.2	543.3	551.3
62.5°	522.0	500.0	478.0	468.5	459.0	462.6	466.3	477.3	488.3	497.8	507.3
65°	460.4	442.1	423.8	417.2	410.6	415.7	420.8	430.4	439.9	446.5	453.1
67.5°	401.8	386.4	371.0	365.8	360.7	365.8	371.0	380.5	390.0	396.6	403.2
70°	340.2	327.7	315.3	311.6	307.9	313.8	319.7	327.7	335.8	342.4	349.0
72.5°	283.0	273.5	263.9	263.2	262.5	267.6	272.7	280.8	288.9	293.3	297.7
75°	227.3	222.1	217.0	216.3	215.5	220.7	225.8	230.2	234.6	238.3	241.9
77.5°	177.4	173.0	168.6	169.4	170.1	173.8	177.4	181.8	186.2	188.4	190.6
80°	126.1	124.6	123.2	124.6	126.1	129.0	132.0	134.9	137.8	139.3	140.8
82.5°	86.5	85.0	83.6	85.8	88.0	90.2	92.4	94.6	96.8	97.5	98.2
85°	49.9	52.1	54.3	54.3	54.3	55.0	55.7	56.5	57.2	56.5	55.7
87.5°	23.5	24.2	24.9	24.9	24.9	25.7	26.4	26.4	26.4	25.7	24.9
90°	3.7	4.4	5.4	6.4	7.4	8.4	8.1	8.4	8.8	9.1	9.8
92.5°	17.2	23.3	34.0	51.9	69.4	62.7	46.9	33.4	26.0	22.6	20.2
95°	30.7	43.8	72.5	122.7	178.0	199.9	162.2	121.4	82.3	64.4	52.3
97.5°	35.4	49.9	78.2	136.5	229.6	307.5	317.9	278.8	210.4	165.9	127.4
100°	40.5	53.6	77.2	127.1	215.8	319.3	385.7	397.5	370.2	330.7	282.8
102.5°	46.2	58.0	78.6	119.0	195.5	297.3	389.0	436.9	442.6	423.8	397.8
105°	52.6	63.0	81.2	116.0	179.7	271.0	367.8	438.3	472.0	478.4	469.6
107.5°	59.7	69.4	85.6	115.3	168.2	247.8	337.5	418.0	471.0	497.3	506.4
110°	66.8	76.2	91.4	117.0	162.2	228.6	309.1	386.3	448.4	490.9	514.5



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	74.2	83.3	97.1	120.4	158.8	215.8	284.5	355.0	418.7	467.6	499.6
115°	81.6	90.7	103.5	124.1	158.4	207.3	265.7	328.0	386.7	436.2	473.0
117.5°	89.0	97.4	110.2	128.8	158.8	201.6	253.2	307.1	359.0	404.6	442.6
120°	96.1	104.5	116.6	134.2	160.1	197.9	243.7	291.3	336.8	377.2	411.3
122.5°	102.5	111.6	123.4	139.2	162.5	195.5	236.0	278.8	318.9	355.7	386.7
125°	108.9	118.0	129.8	144.6	164.9	193.5	229.6	268.0	304.8	337.1	364.1
127.5°	115.0	124.1	135.5	149.0	167.6	192.5	223.5	258.2	291.6	321.3	346.2
130°	120.4	129.5	140.6	153.4	170.2	191.5	218.8	249.1	279.5	306.8	329.7
132.5°	125.4	134.2	145.0	157.4	172.3	191.2	214.4	240.7	268.0	293.0	314.5
135°	129.8	138.9	149.3	160.8	174.3	190.8	210.7	233.3	257.2	279.1	298.4
137.5°	133.8	142.3	152.4	163.5	175.6	190.1	207.3	226.2	246.4	266.0	283.2
140°	137.2	145.6	155.4	165.5	177.0	189.8	204.3	220.1	237.3	253.5	268.0
142.5°	140.6	148.3	157.8	167.6	178.0	189.1	201.6	214.4	228.6	242.1	254.2
145°	143.3	151.0	159.8	168.9	178.3	188.5	199.2	210.0	221.2	231.9	241.7
147.5°	146.6	153.4	161.5	169.9	178.3	187.4	196.9	206.3	215.4	224.5	231.6
150°	149.3	155.4	163.2	170.2	178.3	186.1	194.5	202.3	210.0	217.1	223.5
152.5°	152.0	157.8	164.2	170.9	177.3	184.4	191.8	198.6	205.0	211.0	216.1
155°	155.1	159.8	165.5	170.9	176.7	182.4	189.1	194.9	200.3	205.3	209.4
157.5°	157.8	161.5	166.2	171.3	175.6	180.7	186.1	190.8	195.5	199.6	202.9
160°	159.8	163.2	167.2	171.3	175.0	178.7	183.1	187.4	191.2	194.5	196.9
162.5°	161.5	164.2	167.6	170.9	173.6	176.7	180.0	183.4	186.4	189.5	191.5
165°	162.8	165.2	167.9	170.2	172.3	174.6	177.3	180.0	182.0	184.4	186.1
167.5°	164.2	165.9	167.9	169.9	170.9	172.6	174.6	177.0	178.7	180.0	181.4
170°	165.2	165.9	167.6	168.9	169.6	170.6	172.3	174.0	175.0	176.3	177.0
172.5°	165.9	166.2	167.6	168.6	168.6	168.9	169.9	171.3	171.9	172.9	173.3
175°	166.2	166.5	167.2	167.9	167.6	167.6	168.2	168.9	169.2	169.9	169.9
177.5°	166.5	166.5	166.9	167.6	166.9	166.5	166.9	167.2	167.6	167.9	167.9
180°	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
0°	3159.9	3159.9	3159.9	3159.9
2.5°	2808.7	2803.6	2783.0	2762.5
5°	2381.3	2363.7	2357.8	2351.9
7.5°	2080.7	2079.2	2048.4	2017.6
10°	1816.0	1818.2	1790.4	1762.5
12.5°	1626.9	1608.5	1606.3	1604.1
15°	1484.6	1467.8	1464.8	1461.9
17.5°	1384.2	1373.9	1371.0	1368.1
20°	1307.9	1302.1	1296.9	1291.8
22.5°	1242.0	1234.6	1230.2	1225.8
25°	1178.2	1171.6	1170.1	1168.6
27.5°	1121.0	1112.9	1112.9	1112.9
30°	1066.7	1061.6	1059.4	1057.2
32.5°	1016.1	1011.7	1011.7	1011.7
35°	968.5	966.3	963.4	960.4
37.5°	925.2	925.2	923.8	922.3
40°	883.4	885.6	885.6	885.6
42.5°	845.3	847.5	847.5	847.5
45°	805.7	809.4	810.9	812.3
47.5°	766.9	772.7	774.2	775.7
50°	728.8	733.2	733.9	734.6
52.5°	689.9	695.0	698.7	702.4
55°	648.8	654.0	656.2	658.4
57.5°	604.8	610.0	610.7	611.4
60°	556.5	561.6	563.1	564.5
62.5°	510.3	513.2	514.7	516.1
65°	457.5	461.9	464.8	467.8
67.5°	406.9	410.6	410.6	410.6
70°	350.4	351.9	354.1	356.3
72.5°	298.4	299.1	299.1	299.1
75°	243.4	244.9	245.6	246.3
77.5°	191.4	192.1	192.1	192.1
80°	140.0	139.3	139.3	139.3
82.5°	96.0	93.8	93.8	93.8
85°	55.0	54.3	55.0	55.7
87.5°	24.9	24.9	24.9	24.9
90°	9.4	9.8	10.1	9.8
92.5°	19.6	18.2	18.5	17.9
95°	45.8	42.8	40.5	39.1
97.5°	104.8	92.0	83.9	80.2
100°	248.8	224.2	211.0	211.4
102.5°	373.2	355.0	344.5	334.8
105°	454.1	441.3	430.5	428.8
107.5°	504.3	498.3	493.9	490.2
110°	523.9	526.6	525.9	525.2



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
112.5°	518.8	528.6	532.0	532.3
115°	498.3	513.1	519.8	521.5
117.5°	468.9	485.5	495.6	497.9
120°	437.9	456.8	464.9	466.9
122.5°	409.6	426.1	435.2	437.9
125°	385.7	400.5	408.9	411.3
127.5°	365.8	378.6	386.3	388.4
130°	347.6	359.7	366.8	369.5
132.5°	331.1	343.2	349.3	350.9
135°	314.9	325.0	331.1	333.4
137.5°	297.3	307.8	312.9	314.9
140°	280.8	290.3	295.7	295.3
142.5°	264.6	272.7	277.5	277.1
145°	250.1	257.2	259.9	260.6
147.5°	238.3	243.4	246.1	246.4
150°	228.6	232.3	234.3	234.3
152.5°	219.8	223.2	224.2	224.2
155°	212.4	215.1	215.8	216.1
157.5°	205.6	207.7	208.3	208.3
160°	199.2	201.3	201.3	200.9
162.5°	192.8	194.5	194.5	194.2
165°	187.4	188.8	188.5	188.5
167.5°	182.0	183.1	182.7	182.7
170°	177.3	178.0	177.7	177.7
172.5°	173.3	174.0	173.3	172.9
175°	169.9	170.2	169.9	169.6
177.5°	167.6	167.9	167.2	167.2
180°	166.5	166.5	166.5	166.5



TEST NUMBER: P831260

CATALOG NUMBER: S123DIP-S1165D365U950-4F0-1E-UDD-G4

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	18.29	19.44	18.95	20.10	20.87	20.53	21.68	21.18	22.34	23.11
	3H	19.96	20.99	20.63	21.66	22.46	21.98	23.01	22.64	23.68	24.48
	4H	20.55	21.52	21.24	22.20	23.02	22.44	23.41	23.12	24.09	24.91
	6H	20.94	21.83	21.63	22.52	23.35	22.73	23.62	23.43	24.32	25.14
	8H	21.04	21.89	21.75	22.61	23.44	22.80	23.65	23.51	24.36	25.19
	12H	21.09	21.91	21.81	22.61	23.47	22.83	23.64	23.54	24.35	25.20
4H	2H	18.90	19.87	19.59	20.56	21.37	20.73	21.70	21.42	22.38	23.19
	3H	20.75	21.56	21.46	22.28	23.11	22.37	23.18	23.07	23.90	24.73
	4H	21.46	22.19	22.18	22.92	23.78	22.96	23.69	23.68	24.42	25.28
	6H	21.95	22.59	22.69	23.34	24.21	23.38	24.02	24.12	24.77	25.64
	8H	22.10	22.69	22.84	23.43	24.32	23.50	24.09	24.24	24.84	25.72
	12H	22.18	22.70	22.94	23.48	24.36	23.56	24.09	24.32	24.86	25.75
8H	4H	21.75	22.34	22.49	23.09	23.97	23.09	23.68	23.83	24.43	25.31
	6H	22.35	22.84	23.12	23.63	24.51	23.60	24.09	24.38	24.88	25.77
	8H	22.56	22.99	23.34	23.78	24.68	23.78	24.22	24.57	25.01	25.91
	12H	22.69	23.08	23.48	23.86	24.82	23.90	24.28	24.68	25.06	26.02
12H	4H	21.76	22.29	22.53	23.06	23.95	23.08	23.61	23.84	24.38	25.27
	6H	22.40	22.84	23.18	23.63	24.53	23.62	24.05	24.40	24.84	25.74
	8H	22.65	23.03	23.43	23.81	24.77	23.83	24.21	24.62	24.99	25.95