

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P832032

Luminaire Tested: S123RDIP-S1165D805U950-4F0-1E-UDD-G

Issue Date: 05/03/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P832032  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2301-905-2, G3-1807-864-5)  
Test Lab: INNOVATION CENTER  
Issue Date: 05/03/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: S123RDIP-S1165D805U950-4F0-1E-UDD-G  
Description: DEFINE 3 DIRECT-INDIRECT PENDANT LED LUMINAIRE  
DOWNLIGHT 1165 LUMENS PER FOOT, GRAZE OPTIC  
UPLIGHT 805 LUMENS PER FOOT, NO LENS  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7802.7 lumens  
Efficiency: N/A  
Efficacy: 124.2 lumens/watt  
Spacing Criteria (0/90/45): 0.55 / 1.17 / 0.8  
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')  
CIE Type: Semi-Direct  
  
Input Watts (W): 62.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

### Luminous Intensity Polar Plot





TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									20									20
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	110	110	110	110	103	103	103	103	89	89	89	77	77	77	66	66	66	66	66	66	66	66	66	66	66	66	66	66	66	61																
1	101	97	94	90	95	91	88	85	80	78	75	69	68	66	60	59	58	58	58	58	58	58	58	58	58	58	58	58	58	53																
2	93	86	80	75	87	81	76	72	71	67	64	62	59	57	54	52	50	50	50	50	50	50	50	50	50	50	50	50	50	46																
3	86	77	70	64	80	72	66	61	64	59	55	56	52	50	49	46	44	44	44	44	44	44	44	44	44	44	44	44	44	40																
4	79	69	61	56	74	65	58	53	58	52	48	51	47	44	44	41	39	36	36	36	36	36	36	36	36	36	36	36	36	36																
5	73	62	54	49	68	59	52	47	52	47	43	46	42	39	41	37	35	32	32	32	32	32	32	32	32	32	32	32	32	32																
6	68	56	48	43	63	53	46	41	48	42	38	42	38	35	37	34	31	29	29	29	29	29	29	29	29	29	29	29	29	29																
7	63	51	44	38	59	49	42	37	44	38	34	39	35	31	35	31	28	26	26	26	26	26	26	26	26	26	26	26	26	26																
8	59	47	40	35	55	45	38	33	40	35	31	36	32	28	32	29	26	24	24	24	24	24	24	24	24	24	24	24	24	24																
9	55	43	36	31	52	41	35	30	37	32	28	34	29	26	30	27	24	22	22	22	22	22	22	22	22	22	22	22	22	22																
10	52	40	33	29	49	38	32	28	35	29	26	31	27	24	28	25	22	20	20	20	20	20	20	20	20	20	20	20	20	20																

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°	135°	180°
0°	38485	38485	38485	38485	38485
5°	45697	44239	38727	31306	29066
10°	41402	44935	38534	25083	21518
15°	28505	38528	38128	20501	17022
20°	19832	29662	37362	17287	14961
25°	15112	22607	36248	15365	13789
30°	13155	18074	34855	14266	12772
35°	12077	15247	32881	13340	11846
40°	11020	13616	30300	12431	10999
45°	9952	12452	27515	11571	10153
50°	9034	11489	24229	10727	9108
55°	8171	10550	21073	9903	7812
60°	7322	9593	18303	8994	7384
65°	6757	8512	15755	8084	6981
70°	5489	7358	13747	7311	5674
75°	4816	5852	11645	6068	4999
80°	4364	4953	9540	5089	4723
85°	3989	4347	7237	4619	4347

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 80°  
 Vertical Angle: 45°  
 Luminance: 29032 cd/sqm



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	325.9	4.2
10°-20°	754.1	9.7
20°-30°	865.2	11.1
30°-40°	852.8	10.9
40°-50°	752.1	9.6
50°-60°	578.6	7.4
60°-70°	380.4	4.9
70°-80°	184.7	2.4
80°-90°	48.6	0.6
90°-100°	35.4	0.5
100°-110°	171.1	2.2
110°-120°	419.4	5.4
120°-130°	532.4	6.8
130°-140°	568.8	7.3
140°-150°	531.9	6.8
150°-160°	429.0	5.5
160°-170°	276.9	3.5
170°-180°	95.4	1.2
0°-30°	1945.2	24.9
0°-40°	2798.0	35.9
0°-60°	4128.7	52.9
0°-90°	4742.4	60.8
90°-120°	625.9	8.0
90°-150°	2259.0	29.0
90°-180°	3060.0	39.2
0°-180°	7802.7	100.0

**CANDELA DISTRIBUTION:**

	0°	45°	90°	135°	180°	Flux
0°	3575	3575	3575	3575	3575	
5°	4229	4094	3584	2897	2690	386
15°	2558	3457	3422	1840	1528	722
25°	1272	1904	3052	1294	1161	601
35°	919	1160	2502	1015	902	573
45°	654	818	1808	760	667	508
55°	435	562	1123	528	416	391
65°	265	334	619	317	274	260
75°	116	141	280	146	120	125
85°	32	35	59	37	35	34
90°	22	18	1	18	22	12
95°	28	23	46	23	28	24
105°	33	163	222	163	33	68
115°	438	428	417	428	438	412
125°	600	597	588	597	600	536
135°	739	739	732	739	739	570
145°	852	851	844	851	852	532
155°	929	929	930	929	929	428
165°	978	978	981	978	978	276
175°	1000	1001	1004	1001	1000	95
180°	1004	1004	1004	1004	1004	



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4
2.5°	3962.4	3949.9	3937.5	3933.8	3930.1	3918.4	3906.7	3880.3	3853.9	3826.8	3799.7
5°	4229.2	4230.6	4232.1	4228.4	4224.8	4209.4	4194.0	4161.7	4129.5	4094.3	4059.1
7.5°	4147.1	4170.5	4194.0	4198.4	4202.8	4214.5	4226.2	4218.9	4211.6	4198.4	4185.2
10°	3787.9	3786.5	3785.0	3811.4	3837.8	3916.2	3994.6	4034.9	4075.3	4111.2	4147.1
12.5°	3201.6	3203.8	3206.0	3292.5	3378.9	3453.0	3527.0	3629.6	3732.2	3842.9	3953.6
15°	2558.0	2593.9	2629.9	2706.8	2783.8	2895.2	3006.6	3144.4	3282.2	3457.4	3632.6
17.5°	2100.7	2116.1	2131.4	2205.5	2279.5	2385.1	2490.6	2646.7	2802.8	3028.6	3254.3
20°	1731.3	1745.2	1759.1	1812.6	1866.1	1967.3	2068.4	2217.2	2366.0	2589.5	2813.1
22.5°	1445.4	1472.5	1499.6	1535.6	1571.5	1644.8	1718.1	1869.8	2021.5	2225.3	2429.0
25°	1272.4	1284.9	1297.3	1328.1	1358.9	1429.3	1499.6	1600.1	1700.5	1903.5	2106.5
27.5°	1155.1	1158.8	1162.5	1185.2	1207.9	1253.4	1298.8	1391.9	1485.0	1652.1	1819.2
30°	1058.4	1065.0	1071.6	1089.2	1106.8	1139.8	1172.7	1238.7	1304.7	1454.2	1603.7
32.5°	983.6	987.3	991.0	1005.6	1020.3	1044.5	1068.7	1120.7	1172.7	1287.1	1401.4
35°	919.1	919.9	920.6	931.6	942.6	966.0	989.5	1032.7	1076.0	1160.3	1244.6
37.5°	845.8	851.0	856.1	864.2	872.2	892.7	913.3	948.5	983.6	1053.3	1122.9
40°	784.3	788.7	793.1	802.6	812.1	828.2	844.4	876.6	908.9	969.0	1029.1
42.5°	722.7	725.6	728.6	738.1	747.6	767.4	787.2	812.9	838.5	888.3	938.2
45°	653.8	661.1	668.5	678.7	689.0	705.8	722.7	749.1	775.5	818.0	860.5
47.5°	596.6	600.3	604.0	612.8	621.6	642.1	662.6	686.1	709.5	749.1	788.7
50°	539.5	540.9	542.4	550.5	558.5	576.8	595.2	622.3	649.4	686.1	722.7
52.5°	485.2	488.9	492.5	500.6	508.7	521.1	533.6	561.4	589.3	625.2	661.1
55°	435.4	437.6	439.8	445.6	451.5	466.2	480.8	505.0	529.2	562.2	595.2
57.5°	388.5	391.4	394.3	398.7	403.1	416.3	429.5	450.8	472.0	505.0	538.0
60°	340.1	343.8	347.4	352.6	357.7	367.9	378.2	397.3	416.3	445.6	475.0
62.5°	304.9	305.6	306.4	310.8	315.2	322.5	329.8	345.2	360.6	389.9	419.3
65°	265.3	267.5	269.7	271.9	274.1	280.0	285.9	299.0	312.2	334.2	356.2
67.5°	224.3	226.5	228.7	232.3	236.0	241.1	246.3	255.1	263.9	284.4	304.9
70°	174.4	174.4	174.4	180.3	186.2	195.0	203.8	210.4	217.0	233.8	250.7
72.5°	142.2	142.9	143.7	144.4	145.1	150.3	155.4	166.4	177.4	187.6	197.9
75°	115.8	116.5	117.3	118.0	118.7	120.2	121.7	125.3	129.0	140.7	152.5
77.5°	92.4	93.1	93.8	94.6	95.3	96.8	98.2	99.7	101.1	105.5	109.9
80°	70.4	71.1	71.8	72.6	73.3	74.0	74.8	76.2	77.7	79.9	82.1
82.5°	51.3	51.3	51.3	51.3	51.3	52.8	54.2	54.2	54.2	55.7	57.2
85°	32.3	32.3	32.3	33.0	33.7	33.7	33.7	34.4	35.2	35.2	35.2
87.5°	14.7	13.9	13.2	13.9	14.7	14.7	14.7	15.4	16.1	16.1	16.1
90°	22.4	22.0	21.7	21.4	21.0	20.6	19.9	19.2	18.6	17.9	15.7
92.5°	25.4	25.2	25.0	24.9	24.7	24.0	22.9	21.7	20.6	19.4	17.9
95°	28.3	28.3	28.3	28.3	28.3	27.8	26.6	25.4	24.3	23.1	21.3
97.5°	30.6	30.4	30.2	30.1	29.9	29.2	27.8	26.5	25.2	23.9	32.3
100°	31.3	31.2	31.0	30.8	30.7	29.9	28.6	27.3	25.9	24.6	50.5
102.5°	32.1	31.7	31.4	31.1	30.7	33.3	38.8	44.3	49.7	55.2	84.0
105°	32.8	32.5	32.2	31.8	31.5	46.0	75.3	104.7	134.0	163.3	178.3
107.5°	77.6	99.3	121.0	142.7	164.4	188.0	213.6	239.1	264.6	290.1	287.6
110°	205.1	228.8	252.5	276.2	299.9	314.5	320.0	325.4	330.9	336.4	334.5



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	388.6	388.9	389.2	389.6	389.9	389.3	387.8	386.3	384.8	383.4	381.5
115°	438.5	437.9	437.2	436.6	435.9	434.7	433.1	431.4	429.8	428.1	426.6
117.5°	478.8	478.7	478.5	478.3	478.2	477.4	476.1	474.8	473.4	472.1	471.3
120°	520.6	520.6	520.6	520.6	520.6	519.9	518.6	517.3	515.9	514.6	514.1
122.5°	561.6	561.4	561.3	561.1	560.9	560.5	559.6	558.8	558.0	557.1	556.5
125°	599.6	599.3	599.0	598.7	598.3	598.0	597.7	597.3	597.0	596.7	596.0
127.5°	636.9	637.3	637.6	637.9	638.3	638.2	637.7	637.2	636.7	636.2	635.4
130°	672.7	673.1	673.4	673.7	674.1	673.9	673.2	672.6	671.9	671.2	670.6
132.5°	705.6	706.1	706.6	707.0	707.5	707.5	706.8	706.1	705.5	704.8	704.3
135°	739.1	739.6	740.1	740.6	741.1	741.1	740.6	740.1	739.6	739.1	738.5
137.5°	771.2	771.5	771.9	772.2	772.5	772.3	771.4	770.6	769.8	769.0	768.6
140°	799.5	799.9	800.2	800.5	800.9	800.7	800.0	799.4	798.7	798.0	797.5
142.5°	825.6	826.1	826.6	827.1	827.6	827.6	827.1	826.6	826.1	825.6	825.1
145°	852.5	852.5	852.5	852.5	852.5	852.3	852.0	851.7	851.3	851.0	850.7
147.5°	871.9	872.7	873.5	874.4	875.2	875.4	875.1	874.8	874.4	874.1	873.8
150°	894.3	894.7	895.2	895.7	896.2	896.3	896.0	895.7	895.3	895.0	894.7
152.5°	912.2	913.0	913.8	914.6	915.5	915.6	914.9	914.2	913.6	912.9	912.7
155°	928.6	929.6	930.5	931.5	932.5	932.6	931.8	931.0	930.1	929.3	929.1
157.5°	942.7	944.1	945.4	946.7	948.0	948.2	947.2	946.2	945.2	944.2	944.4
160°	956.2	957.3	958.5	959.6	960.8	960.9	959.9	958.9	957.9	956.9	957.1
162.5°	968.8	969.8	970.8	971.8	972.8	972.7	971.6	970.4	969.3	968.1	968.3
165°	978.5	979.7	980.9	982.0	983.2	983.1	981.8	980.4	979.1	977.8	978.0
167.5°	986.0	987.3	988.6	990.0	991.3	991.3	990.0	988.6	987.3	986.0	986.0
170°	992.7	994.0	995.4	996.7	998.0	998.0	996.7	995.4	994.0	992.7	992.7
172.5°	996.4	997.9	999.4	1000.9	1002.4	1002.5	1001.2	999.8	998.5	997.2	997.0
175°	1000.2	1001.5	1002.8	1004.1	1005.5	1005.5	1004.4	1003.2	1002.1	1000.9	1000.7
177.5°	1000.9	1002.6	1004.2	1005.9	1007.5	1007.7	1006.4	1005.0	1003.7	1002.4	1002.2
180°	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4
2.5°	3796.0	3792.3	3757.2	3722.0	3687.5	3653.1	3627.4	3601.8	3558.5	3515.3	3488.2
5°	4031.3	4003.4	3947.7	3892.0	3808.5	3724.9	3654.5	3584.2	3494.8	3405.3	3330.6
7.5°	4162.5	4139.8	4072.3	4004.9	3894.2	3783.5	3673.6	3563.7	3431.7	3299.8	3186.9
10°	4166.1	4185.2	4129.5	4073.8	3949.2	3824.6	3675.1	3525.5	3348.2	3170.8	3024.9
12.5°	4035.7	4117.8	4106.0	4094.3	3967.5	3840.7	3658.9	3477.2	3259.5	3041.8	2859.3
15°	3791.6	3950.7	3997.6	4044.5	3939.7	3834.8	3628.2	3421.5	3165.7	2909.9	2700.2
17.5°	3477.2	3700.0	3823.9	3947.7	3871.5	3795.3	3568.8	3342.3	3054.2	2766.2	2538.2
20°	3104.8	3396.5	3590.8	3785.0	3757.2	3729.3	3495.5	3261.7	2950.9	2640.1	2393.1
22.5°	2736.9	3044.7	3313.0	3581.2	3609.8	3638.4	3402.4	3166.4	2826.3	2486.2	2234.8
25°	2419.5	2732.5	3052.0	3371.6	3436.1	3500.6	3276.3	3052.0	2699.5	2346.9	2097.0
27.5°	2116.8	2414.4	2766.2	3118.0	3235.3	3352.6	3147.3	2942.1	2574.9	2207.7	1958.5
30°	1869.8	2135.8	2495.0	2854.1	3017.6	3181.0	2992.7	2804.3	2440.0	2075.7	1831.7
32.5°	1639.6	1877.8	2238.5	2599.1	2788.9	2978.8	2816.0	2653.3	2303.0	1952.6	1711.5
35°	1457.9	1671.1	2007.6	2344.0	2556.6	2769.1	2635.7	2502.3	2160.0	1817.7	1589.8
37.5°	1301.7	1480.6	1796.5	2112.4	2338.1	2563.9	2452.5	2341.1	2019.3	1697.5	1482.0
40°	1172.7	1316.4	1610.3	1904.2	2125.6	2346.9	2251.7	2156.4	1868.3	1580.3	1378.7
42.5°	1062.1	1185.9	1449.8	1713.7	1916.7	2119.7	2056.7	1993.7	1732.7	1471.8	1284.9
45°	964.6	1068.7	1301.0	1533.4	1720.3	1907.2	1857.3	1807.5	1582.5	1357.4	1185.9
47.5°	878.1	967.5	1174.9	1382.4	1550.2	1718.1	1671.9	1625.7	1439.5	1253.4	1097.2
50°	798.9	875.2	1048.1	1221.1	1372.1	1523.1	1485.0	1446.9	1292.9	1139.0	1004.2
52.5°	724.2	787.2	942.6	1098.0	1219.6	1341.3	1312.0	1282.7	1163.9	1045.2	922.8
55°	653.1	711.0	842.2	973.4	1077.5	1181.5	1152.2	1122.9	1030.5	938.2	830.4
57.5°	588.6	639.1	745.4	851.7	934.5	1017.3	1003.4	989.5	912.5	835.6	746.9
60°	520.4	565.8	657.5	749.1	815.8	882.5	866.4	850.2	795.3	740.3	664.1
62.5°	459.6	499.9	573.2	646.5	700.7	754.9	743.2	731.5	689.7	647.9	584.9
65°	395.8	435.4	494.7	554.1	596.6	639.1	628.9	618.6	587.1	555.6	505.0
67.5°	337.9	370.9	422.2	473.5	502.1	530.7	524.8	518.9	494.7	470.6	431.0
70°	279.3	307.8	350.4	392.9	412.7	432.4	434.6	436.8	414.9	392.9	363.5
72.5°	220.6	243.3	282.9	322.5	337.9	353.3	352.6	351.8	338.6	325.4	299.0
75°	169.3	186.2	217.0	247.7	260.9	274.1	277.1	280.0	267.5	255.1	240.4
77.5°	121.7	133.4	156.9	180.3	195.0	209.6	211.1	212.6	206.7	200.8	186.9
80°	85.8	89.4	104.1	118.7	134.1	149.5	151.7	153.9	148.1	142.2	133.4
82.5°	59.4	61.6	66.7	71.8	84.3	96.8	99.7	102.6	99.7	96.8	87.2
85°	35.9	36.6	38.8	41.0	46.9	52.8	55.7	58.6	57.2	55.7	50.6
87.5°	16.1	16.1	16.9	17.6	19.1	20.5	24.2	27.9	25.7	23.5	21.3
90°	13.6	11.4	9.3	7.4	5.7	4.1	2.4	0.7	2.4	4.1	5.7
92.5°	16.4	14.9	13.4	13.2	14.2	15.2	16.2	17.2	16.2	15.2	14.2
95°	19.5	17.7	15.8	18.3	25.1	31.9	38.7	45.5	38.7	31.9	25.1
97.5°	40.8	49.2	57.7	64.2	68.9	73.5	78.1	82.8	78.1	73.5	68.9
100°	76.3	102.2	128.0	139.3	136.0	132.7	129.4	126.0	129.4	132.7	136.0
102.5°	112.9	141.7	170.5	183.9	181.7	179.6	177.4	175.3	177.4	179.6	181.7
105°	193.2	208.1	223.0	229.6	227.7	225.9	224.1	222.3	224.1	225.9	227.7
107.5°	285.2	282.7	280.2	278.2	276.7	275.2	273.7	272.2	273.7	275.2	276.7
110°	332.7	330.9	329.1	327.5	326.2	324.9	323.5	322.2	323.5	324.9	326.2





TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	379.7	377.9	376.1	374.6	373.4	372.3	371.1	369.9	371.1	372.3	373.4
115°	425.1	423.6	422.1	420.9	419.9	418.9	417.9	416.9	417.9	418.9	419.9
117.5°	470.5	469.6	468.8	467.8	466.6	465.5	464.3	463.2	464.3	465.5	466.6
120°	513.6	513.1	512.6	511.6	510.1	508.7	507.2	505.7	507.2	508.7	510.1
122.5°	555.8	555.1	554.5	553.6	552.4	551.3	550.1	548.9	550.1	551.3	552.4
125°	595.3	594.7	594.0	593.0	591.7	590.4	589.0	587.7	589.0	590.4	591.7
127.5°	634.5	633.7	632.9	631.8	630.5	629.2	627.8	626.5	627.8	629.2	630.5
130°	669.9	669.3	668.6	667.6	666.3	665.0	663.6	662.3	663.6	665.0	666.3
132.5°	703.8	703.3	702.8	701.9	700.6	699.3	697.9	696.6	697.9	699.3	700.6
135°	737.8	737.1	736.5	735.6	734.6	733.7	732.7	731.7	732.7	733.7	734.6
137.5°	768.3	768.0	767.6	766.8	765.5	764.1	762.8	761.5	762.8	764.1	765.5
140°	797.0	796.5	796.1	795.3	794.3	793.3	792.3	791.3	792.3	793.3	794.3
142.5°	824.6	824.1	823.6	822.9	821.9	820.9	819.9	818.9	819.9	820.9	821.9
145°	850.3	850.0	849.7	848.9	847.8	846.6	845.4	844.3	845.4	846.6	847.8
147.5°	873.5	873.1	872.8	872.2	871.4	870.6	869.7	868.9	869.7	870.6	871.4
150°	894.3	894.0	893.7	893.3	892.8	892.3	891.8	891.3	891.8	892.3	892.8
152.5°	912.6	912.4	912.2	912.1	911.9	911.7	911.6	911.4	911.6	911.7	911.9
155°	929.0	928.8	928.6	928.7	929.1	929.4	929.7	930.1	929.7	929.4	929.1
157.5°	944.6	944.7	944.9	945.0	945.0	945.0	945.0	945.0	945.0	945.0	945.0
160°	957.2	957.4	957.6	957.7	957.9	958.1	958.2	958.4	958.2	958.1	957.9
162.5°	968.4	968.6	968.8	969.1	969.6	970.1	970.6	971.1	970.6	970.1	969.6
165°	978.1	978.3	978.4	978.8	979.3	979.8	980.3	980.8	980.3	979.8	979.3
167.5°	986.0	986.0	986.0	986.3	987.0	987.6	988.3	989.0	988.3	987.6	987.0
170°	992.7	992.7	992.7	993.0	993.7	994.4	995.0	995.7	995.0	994.4	993.7
172.5°	996.8	996.7	996.5	996.8	997.7	998.5	999.3	1000.2	999.3	998.5	997.7
175°	1000.6	1000.4	1000.2	1000.6	1001.4	1002.2	1003.1	1003.9	1003.1	1002.2	1001.4
177.5°	1002.1	1001.9	1001.7	1002.1	1002.9	1003.7	1004.6	1005.4	1004.6	1003.7	1002.9
180°	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4	3575.4
2.5°	3461.0	3419.3	3377.5	3347.4	3317.4	3280.0	3242.6	3241.2	3239.7	3211.8	3184.0
5°	3255.8	3183.2	3110.7	3039.6	2968.5	2897.4	2826.3	2810.2	2794.0	2769.9	2745.7
7.5°	3074.0	2958.2	2842.4	2751.5	2660.6	2589.5	2518.5	2470.1	2421.7	2384.3	2346.9
10°	2879.1	2735.4	2591.7	2481.8	2371.9	2294.9	2217.9	2162.2	2106.5	2080.1	2053.8
12.5°	2676.8	2520.7	2364.5	2256.8	2149.0	2056.7	1964.3	1913.8	1863.2	1826.5	1789.9
15°	2490.6	2322.8	2154.9	2040.6	1926.2	1839.7	1753.2	1702.7	1652.1	1615.4	1578.8
17.5°	2310.3	2141.0	1971.7	1855.9	1740.0	1661.6	1583.2	1534.1	1485.0	1462.3	1439.5
20°	2146.1	1975.3	1804.5	1695.3	1586.1	1509.2	1432.2	1405.8	1379.4	1358.2	1336.9
22.5°	1983.4	1819.2	1655.0	1550.2	1445.4	1389.7	1334.0	1312.7	1291.5	1275.4	1259.2
25°	1847.1	1683.6	1520.2	1428.5	1336.9	1293.7	1250.4	1236.5	1222.6	1206.5	1190.3
27.5°	1709.3	1553.9	1398.5	1325.2	1251.9	1216.7	1181.5	1163.9	1146.3	1133.2	1120.0
30°	1587.6	1443.9	1300.3	1239.4	1178.6	1147.8	1117.0	1098.0	1078.9	1066.5	1054.0
32.5°	1470.3	1342.8	1215.2	1163.2	1111.2	1081.1	1051.1	1032.7	1014.4	999.8	985.1
35°	1361.8	1251.2	1140.5	1092.8	1045.2	1015.2	985.1	966.8	948.5	933.8	919.1
37.5°	1266.6	1166.1	1065.7	1021.0	976.3	949.9	923.5	904.5	885.4	870.0	854.6
40°	1177.1	1088.4	999.8	956.5	913.3	884.7	856.1	839.2	822.4	808.5	794.5
42.5°	1098.0	1016.6	935.3	892.7	850.2	823.1	796.0	776.2	756.4	748.4	740.3
45°	1014.4	942.6	870.8	829.7	788.7	760.1	731.5	714.6	697.8	690.4	683.1
47.5°	941.1	874.4	807.7	767.4	727.1	701.4	675.8	662.6	649.4	639.1	628.9
50°	869.3	804.8	740.3	701.4	662.6	640.6	618.6	602.5	586.4	579.0	571.7
52.5°	800.4	741.8	683.1	643.5	604.0	582.7	561.4	547.5	533.6	518.2	502.8
55°	722.7	671.4	620.1	584.9	549.7	527.7	505.7	489.6	473.5	457.4	441.2
57.5°	658.2	607.6	557.0	525.5	494.0	472.8	451.5	433.9	416.3	403.1	389.9
60°	587.8	543.9	499.9	469.1	438.3	417.8	397.3	380.4	363.5	357.0	350.4
62.5°	521.9	480.8	439.8	412.7	385.5	365.7	346.0	335.0	324.0	319.6	315.2
65°	454.4	419.3	384.1	359.2	334.2	317.4	300.5	295.4	290.3	286.6	282.9
67.5°	391.4	361.3	331.3	309.3	287.3	275.6	263.9	258.0	252.1	247.7	243.3
70°	334.2	307.8	281.5	262.4	243.3	232.3	221.4	216.2	211.1	203.0	195.0
72.5°	272.7	252.1	231.6	217.0	202.3	192.8	183.2	173.0	162.7	155.4	148.1
75°	225.8	205.2	184.7	170.8	156.9	145.9	134.9	131.2	127.5	125.3	123.1
77.5°	173.0	155.4	137.8	126.8	115.8	110.7	105.5	103.3	101.1	100.4	99.7
80°	124.6	109.9	95.3	89.4	83.6	82.1	80.6	79.2	77.7	77.0	76.2
82.5°	77.7	70.4	63.0	61.6	60.1	59.4	58.6	57.9	57.2	56.4	55.7
85°	45.4	42.5	39.6	38.8	38.1	37.4	36.6	36.6	36.6	36.6	36.6
87.5°	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	18.3	17.6
90°	7.4	9.3	11.4	13.6	15.7	17.9	18.6	19.2	19.9	20.6	21.0
92.5°	13.2	13.4	14.9	16.4	17.9	19.4	20.6	21.7	22.9	24.0	24.7
95°	18.3	15.8	17.7	19.5	21.3	23.1	24.3	25.4	26.6	27.8	28.3
97.5°	64.2	57.7	49.2	40.8	32.3	23.9	25.2	26.5	27.8	29.2	29.9
100°	139.3	128.0	102.2	76.3	50.5	24.6	25.9	27.3	28.6	29.9	30.7
102.5°	183.9	170.5	141.7	112.9	84.0	55.2	49.7	44.3	38.8	33.3	30.7
105°	229.6	223.0	208.1	193.2	178.3	163.3	134.0	104.7	75.3	46.0	31.5
107.5°	278.2	280.2	282.7	285.2	287.6	290.1	264.6	239.1	213.6	188.0	164.4
110°	327.5	329.1	330.9	332.7	334.5	336.4	330.9	325.4	320.0	314.5	299.9



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	374.6	376.1	377.9	379.7	381.5	383.4	384.8	386.3	387.8	389.3	389.9
115°	420.9	422.1	423.6	425.1	426.6	428.1	429.8	431.4	433.1	434.7	435.9
117.5°	467.8	468.8	469.6	470.5	471.3	472.1	473.4	474.8	476.1	477.4	478.2
120°	511.6	512.6	513.1	513.6	514.1	514.6	515.9	517.3	518.6	519.9	520.6
122.5°	553.6	554.5	555.1	555.8	556.5	557.1	558.0	558.8	559.6	560.5	560.9
125°	593.0	594.0	594.7	595.3	596.0	596.7	597.0	597.3	597.7	598.0	598.3
127.5°	631.8	632.9	633.7	634.5	635.4	636.2	636.7	637.2	637.7	638.2	638.3
130°	667.6	668.6	669.3	669.9	670.6	671.2	671.9	672.6	673.2	673.9	674.1
132.5°	701.9	702.8	703.3	703.8	704.3	704.8	705.5	706.1	706.8	707.5	707.5
135°	735.6	736.5	737.1	737.8	738.5	739.1	739.6	740.1	740.6	741.1	741.1
137.5°	766.8	767.6	768.0	768.3	768.6	769.0	769.8	770.6	771.4	772.3	772.5
140°	795.3	796.1	796.5	797.0	797.5	798.0	798.7	799.4	800.0	800.7	800.9
142.5°	822.9	823.6	824.1	824.6	825.1	825.6	826.1	826.6	827.1	827.6	827.6
145°	848.9	849.7	850.0	850.3	850.7	851.0	851.3	851.7	852.0	852.3	852.5
147.5°	872.2	872.8	873.1	873.5	873.8	874.1	874.4	874.8	875.1	875.4	875.2
150°	893.3	893.7	894.0	894.3	894.7	895.0	895.3	895.7	896.0	896.3	896.2
152.5°	912.1	912.2	912.4	912.6	912.7	912.9	913.6	914.2	914.9	915.6	915.5
155°	928.7	928.6	928.8	929.0	929.1	929.3	930.1	931.0	931.8	932.6	932.5
157.5°	945.0	944.9	944.7	944.6	944.4	944.2	945.2	946.2	947.2	948.2	948.0
160°	957.7	957.6	957.4	957.2	957.1	956.9	957.9	958.9	959.9	960.9	960.8
162.5°	969.1	968.8	968.6	968.4	968.3	968.1	969.3	970.4	971.6	972.7	972.8
165°	978.8	978.4	978.3	978.1	978.0	977.8	979.1	980.4	981.8	983.1	983.2
167.5°	986.3	986.0	986.0	986.0	986.0	986.0	987.3	988.6	990.0	991.3	991.3
170°	993.0	992.7	992.7	992.7	992.7	992.7	994.0	995.4	996.7	998.0	998.0
172.5°	996.8	996.5	996.7	996.8	997.0	997.2	998.5	999.8	1001.2	1002.5	1002.4
175°	1000.6	1000.2	1000.4	1000.6	1000.7	1000.9	1002.1	1003.2	1004.4	1005.5	1005.5
177.5°	1002.1	1001.7	1001.9	1002.1	1002.2	1002.4	1003.7	1005.0	1006.4	1007.7	1007.5
180°	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9	1003.9



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
0°	3575.4	3575.4	3575.4	3575.4
2.5°	3176.7	3169.3	3166.4	3163.5
5°	2722.9	2700.2	2695.1	2690.0
7.5°	2337.4	2327.9	2296.4	2264.8
10°	2024.4	1995.1	1981.9	1968.7
12.5°	1762.8	1735.7	1731.3	1726.9
15°	1559.7	1540.7	1534.1	1527.5
17.5°	1426.3	1413.1	1405.1	1397.0
20°	1327.4	1317.9	1312.0	1306.1
22.5°	1251.9	1244.6	1240.2	1235.8
25°	1179.3	1168.3	1164.7	1161.0
27.5°	1110.4	1100.9	1097.2	1093.6
30°	1045.9	1037.9	1032.7	1027.6
32.5°	975.6	966.0	963.1	960.2
35°	913.3	907.4	904.5	901.5
37.5°	847.3	840.0	835.6	831.2
40°	790.9	787.2	785.0	782.8
42.5°	733.7	727.1	726.4	725.6
45°	676.5	669.9	668.5	667.0
47.5°	623.0	617.2	616.4	615.7
50°	563.6	555.6	549.7	543.9
52.5°	495.5	488.2	483.0	477.9
55°	433.2	425.1	420.7	416.3
57.5°	386.3	382.6	380.4	378.2
60°	348.2	346.0	344.5	343.0
62.5°	313.0	310.8	310.8	310.8
65°	280.7	278.5	276.3	274.1
67.5°	238.9	234.5	233.8	233.1
70°	188.4	181.8	181.0	180.3
72.5°	147.3	146.6	145.1	143.7
75°	121.7	120.2	120.2	120.2
77.5°	98.2	96.8	96.8	96.8
80°	75.5	74.8	75.5	76.2
82.5°	55.7	55.7	55.0	54.2
85°	35.9	35.2	35.2	35.2
87.5°	17.6	17.6	17.6	17.6
90°	21.4	21.7	22.0	22.4
92.5°	24.9	25.0	25.2	25.4
95°	28.3	28.3	28.3	28.3
97.5°	30.1	30.2	30.4	30.6
100°	30.8	31.0	31.2	31.3
102.5°	31.1	31.4	31.7	32.1
105°	31.8	32.2	32.5	32.8
107.5°	142.7	121.0	99.3	77.6
110°	276.2	252.5	228.8	205.1



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°
112.5°	389.6	389.2	388.9	388.6
115°	436.6	437.2	437.9	438.5
117.5°	478.3	478.5	478.7	478.8
120°	520.6	520.6	520.6	520.6
122.5°	561.1	561.3	561.4	561.6
125°	598.7	599.0	599.3	599.6
127.5°	637.9	637.6	637.3	636.9
130°	673.7	673.4	673.1	672.7
132.5°	707.0	706.6	706.1	705.6
135°	740.6	740.1	739.6	739.1
137.5°	772.2	771.9	771.5	771.2
140°	800.5	800.2	799.9	799.5
142.5°	827.1	826.6	826.1	825.6
145°	852.5	852.5	852.5	852.5
147.5°	874.4	873.5	872.7	871.9
150°	895.7	895.2	894.7	894.3
152.5°	914.6	913.8	913.0	912.2
155°	931.5	930.5	929.6	928.6
157.5°	946.7	945.4	944.1	942.7
160°	959.6	958.5	957.3	956.2
162.5°	971.8	970.8	969.8	968.8
165°	982.0	980.9	979.7	978.5
167.5°	990.0	988.6	987.3	986.0
170°	996.7	995.4	994.0	992.7
172.5°	1000.9	999.4	997.9	996.4
175°	1004.1	1002.8	1001.5	1000.2
177.5°	1005.9	1004.2	1002.6	1000.9
180°	1003.9	1003.9	1003.9	1003.9



TEST NUMBER: P832032

CATALOG NUMBER: S123RDIP-S1165D805U950-4F0-1E-UDD-G

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.39	15.28	15.26	16.17	17.28	19.05	19.95	19.92	20.83	21.95
	3H	15.61	16.42	16.50	17.31	18.45	20.56	21.36	21.44	22.25	23.39
	4H	16.00	16.75	16.90	17.65	18.80	21.05	21.80	21.95	22.70	23.85
	6H	16.28	16.98	17.19	17.88	19.05	21.36	22.06	22.27	22.96	24.13
	8H	16.37	17.03	17.29	17.96	19.12	21.44	22.11	22.36	23.03	24.19
	12H	16.43	17.06	17.35	17.97	19.16	21.48	22.11	22.40	23.02	24.21
4H	2H	15.12	15.87	16.02	16.77	17.92	19.05	19.81	19.96	20.71	21.86
	3H	16.49	17.12	17.41	18.05	19.22	20.72	21.35	21.63	22.28	23.44
	4H	16.95	17.52	17.88	18.45	19.64	21.33	21.90	22.25	22.82	24.02
	6H	17.32	17.81	18.26	18.76	19.96	21.77	22.26	22.71	23.21	24.40
	8H	17.45	17.91	18.39	18.85	20.06	21.90	22.36	22.84	23.30	24.51
	12H	17.53	17.94	18.49	18.90	20.11	21.97	22.38	22.92	23.34	24.55
8H	4H	17.27	17.73	18.21	18.67	19.88	21.30	21.76	22.24	22.70	23.91
	6H	17.74	18.11	18.70	19.10	20.30	21.80	22.18	22.76	23.16	24.36
	8H	17.93	18.26	18.91	19.24	20.46	21.98	22.32	22.96	23.29	24.51
	12H	18.07	18.37	19.05	19.33	20.60	22.10	22.40	23.08	23.36	24.63
12H	4H	17.28	17.70	18.24	18.66	19.87	21.25	21.66	22.21	22.63	23.83
	6H	17.80	18.13	18.77	19.10	20.33	21.77	22.11	22.75	23.08	24.30
	8H	18.02	18.31	18.99	19.28	20.55	21.97	22.26	22.95	23.23	24.50