

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333333-927

Luminaire Tested: **S125DIP-S1270D1205U927-4F0-1E-UDD-A4**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333333-927
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-19,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125DIP-S1270D1205U927-4F0-1E-UDD-A4
Description: DEFINE 5 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1270 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 1205 LUMENS PER FOOT, BATWING OPTIC
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7531.8 lumens
Efficiency: N/A
Efficacy: 105.0 lumens/watt
Spacing Criteria (0/90/45): 1.43 / 1.23 / 1.52
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 71.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

Luminous Intensity Polar Plot





TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	108	108	108	108	100	100	100	100	86	86	86	73	73	73	60	60	60	55
1	99	95	91	88	92	88	85	82	76	73	71	64	63	61	54	53	51	46
2	90	83	77	72	84	77	72	68	67	63	59	57	54	51	48	45	44	39
3	83	73	66	60	76	68	62	57	59	54	50	50	47	44	42	40	37	33
4	76	65	57	51	70	61	54	48	52	47	43	45	41	37	38	35	32	29
5	69	58	50	44	64	54	47	42	47	41	37	40	36	33	34	31	28	25
6	64	52	44	38	59	49	41	36	42	37	32	37	32	29	31	28	25	22
7	59	47	39	33	55	44	37	32	38	33	29	33	29	25	28	25	22	20
8	55	43	35	30	51	40	33	28	35	29	25	30	26	23	26	22	20	18
9	51	39	31	26	48	37	30	25	32	27	23	28	24	20	24	20	18	16
10	48	36	28	24	44	34	27	23	30	24	20	26	21	18	22	19	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	9396	9396	9396	9396
5°	10881	9428	8255	9428
10°	12660	9379	7233	9379
15°	14014	9310	6672	9310
20°	15687	9201	6222	9201
25°	18377	9079	6002	9079
30°	19848	8957	5812	8957
35°	16320	8729	5687	8729
40°	11600	8413	5550	8413
45°	8912	7986	5471	7986
50°	7607	7458	5460	7458
55°	6773	6939	5507	6939
60°	6110	6373	5647	6373
65°	5644	5804	5793	5804
70°	5130	5212	5876	5212
75°	4531	4591	5827	4591
80°	3812	3745	5326	3745
85°	3016	2697	4305	2697



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	140.1	1.9
10°-20°	417.0	5.5
20°-30°	677.1	9.0
30°-40°	826.0	11.0
40°-50°	751.4	10.0
50°-60°	598.5	7.9
60°-70°	416.9	5.5
70°-80°	222.3	3.0
80°-90°	58.7	0.8
90°-100°	330.9	4.4
100°-110°	711.4	9.4
110°-120°	667.6	8.9
120°-130°	541.1	7.2
130°-140°	434.2	5.8
140°-150°	327.7	4.4
150°-160°	230.6	3.1
160°-170°	136.0	1.8
170°-180°	44.2	0.6
0°-30°	1234.2	16.4
0°-40°	2060.2	27.4
0°-60°	3410.1	45.3
0°-90°	4108.0	54.5
90°-120°	1710.0	22.7
90°-150°	3013.0	40.0
90°-180°	3424.0	45.5
0°-180°	7531.8	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1455	1455	1455	1455	1455	
5°	1678	1454	1273	1454	1678	169
15°	2096	1392	998	1392	2096	600
25°	2579	1274	842	1274	2579	1178
35°	2070	1107	721	1107	2070	1267
45°	976	874	599	874	976	781
55°	602	616	489	616	602	542
65°	369	380	379	380	369	367
75°	182	184	234	184	182	196
85°	41	36	58	36	41	48
90°	21	1	21	1	21	16
95°	216	30	216	30	216	306
105°	1220	104	1220	104	1220	1212
115°	1359	186	1359	186	1359	1327
125°	1071	258	1071	258	1071	969
135°	889	302	889	302	889	689
145°	701	352	701	352	701	446
155°	588	401	588	401	588	274
165°	516	438	516	438	516	147
175°	463	456	463	456	463	45
180°	456	456	456	456	456	



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1538.9	1536.9	1534.9	1531.0	1533.9	1525.5	1521.5	1514.7	1506.3	1503.3	1499.8
5°	1678.4	1681.5	1684.6	1671.7	1672.9	1664.2	1644.5	1628.4	1615.4	1598.8	1587.1
7.5°	1846.4	1839.1	1838.5	1830.1	1815.7	1804.0	1783.3	1756.8	1731.3	1702.2	1678.1
10°	1930.4	1931.0	1925.5	1915.6	1900.1	1889.0	1861.9	1835.9	1804.4	1767.4	1740.8
12.5°	1993.6	1996.2	1989.2	1975.9	1968.3	1943.4	1922.1	1891.3	1853.8	1824.2	1783.8
15°	2095.9	2089.1	2084.2	2067.4	2054.5	2028.5	1994.6	1962.5	1921.8	1884.0	1846.4
17.5°	2194.4	2199.9	2190.6	2175.4	2135.2	2104.9	2059.4	2015.3	1964.6	1914.1	1869.2
20°	2282.4	2287.3	2273.1	2246.5	2198.4	2168.1	2108.2	2051.4	1992.7	1927.9	1878.5
22.5°	2392.1	2388.1	2368.9	2328.5	2286.8	2230.9	2166.1	2096.8	2023.4	1950.1	1884.4
25°	2578.8	2552.8	2541.1	2491.1	2436.1	2354.0	2265.1	2163.8	2072.4	1975.5	1891.5
27.5°	2682.3	2674.1	2661.0	2626.2	2568.4	2480.6	2375.8	2252.3	2123.4	2001.1	1891.1
30°	2661.5	2662.8	2664.0	2652.9	2615.9	2549.7	2445.4	2312.6	2159.5	2021.8	1894.6
32.5°	2477.8	2500.2	2521.8	2547.2	2557.6	2544.8	2479.5	2359.6	2201.9	2045.5	1892.6
35°	2070.0	2076.7	2146.5	2215.7	2309.5	2382.4	2431.2	2378.1	2245.3	2065.6	1890.2
37.5°	1614.0	1647.3	1695.6	1773.8	1909.2	2030.5	2186.5	2258.3	2215.4	2072.2	1885.9
40°	1375.9	1406.8	1438.2	1517.9	1632.1	1779.1	1956.3	2107.6	2142.8	2051.4	1871.1
42.5°	1192.1	1216.6	1251.5	1311.4	1406.8	1537.0	1706.4	1904.1	2025.7	1991.2	1840.0
45°	975.7	991.1	1018.3	1065.9	1135.0	1236.9	1386.3	1602.5	1790.8	1853.2	1766.1
47.5°	835.1	835.0	856.1	889.0	938.9	1025.5	1136.0	1305.4	1506.5	1655.3	1648.5
50°	757.1	754.0	770.6	799.1	838.6	896.0	1001.6	1136.9	1330.2	1498.7	1545.6
52.5°	689.9	690.2	700.5	721.5	754.6	803.7	882.6	1004.5	1169.6	1342.6	1431.1
55°	601.5	599.0	610.7	625.0	649.0	681.1	737.9	831.2	965.2	1135.6	1250.5
57.5°	520.5	527.3	532.0	541.9	561.8	583.3	631.2	699.7	806.0	952.2	1073.6
60°	473.0	479.8	483.5	493.4	509.5	528.0	565.1	620.6	710.2	836.1	956.6
62.5°	430.6	435.9	437.0	446.0	459.1	477.1	506.3	552.9	623.7	733.9	851.8
65°	369.3	369.3	371.8	381.0	387.2	403.2	425.5	459.5	516.3	602.1	702.7
67.5°	310.2	313.2	312.6	316.6	322.3	334.9	350.8	378.8	420.9	483.5	564.0
70°	271.7	274.2	273.5	276.6	282.8	290.9	303.8	330.3	360.6	414.4	483.5
72.5°	237.1	238.1	236.5	240.6	244.3	251.4	265.8	280.0	308.2	353.6	410.4
75°	181.6	182.8	184.0	186.5	190.2	193.9	201.3	215.6	234.0	268.0	304.4
77.5°	136.1	133.7	136.7	136.3	138.5	141.3	147.8	155.3	170.6	192.0	220.2
80°	102.5	103.1	103.1	103.8	106.9	108.7	114.2	119.8	131.5	147.6	167.4
82.5°	74.9	76.4	75.5	76.6	79.1	80.5	83.6	88.2	95.0	107.6	121.9
85°	40.7	37.7	38.9	40.2	40.2	40.7	43.3	45.1	48.8	53.7	59.3
87.5°	16.1	17.1	17.4	17.4	17.9	17.5	19.3	19.1	20.4	21.7	23.3
90°	21.2	21.2	20.3	20.3	20.3	18.4	17.5	16.6	15.7	14.7	12.9
92.5°	58.7	60.2	61.5	63.7	75.5	89.1	118.4	163.1	240.3	296.8	301.6
95°	216.3	231.1	238.4	266.0	331.4	408.7	521.9	661.8	798.0	815.6	665.5
97.5°	522.8	534.6	561.3	612.8	669.7	777.3	887.6	985.6	1009.8	870.9	594.3
100°	718.0	732.7	766.8	833.1	896.5	992.3	1087.1	1132.2	1061.3	831.2	530.2
102.5°	936.0	947.0	984.0	1031.1	1099.1	1163.9	1209.3	1181.5	1030.4	761.2	481.6
105°	1219.6	1230.7	1249.1	1279.5	1308.9	1319.1	1278.6	1152.5	931.5	667.3	434.4
107.5°	1370.2	1377.6	1383.7	1383.9	1369.0	1320.9	1216.9	1048.6	830.7	602.7	414.5
110°	1420.3	1420.3	1413.9	1396.4	1354.9	1276.7	1146.9	972.0	773.2	572.5	408.7



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	1414.4	1407.8	1391.8	1361.8	1301.2	1208.9	1077.7	911.6	730.5	554.8	408.7
115°	1358.6	1346.6	1320.9	1276.7	1204.9	1104.5	978.5	835.8	683.9	535.8	411.5
117.5°	1260.8	1253.5	1228.0	1182.3	1110.5	1018.4	909.8	786.8	656.1	526.3	417.6
120°	1197.5	1190.2	1165.3	1121.2	1053.0	972.0	870.8	760.3	640.6	521.9	423.4
122.5°	1141.6	1135.0	1110.1	1069.6	1008.8	933.0	842.8	740.5	627.4	518.2	428.6
125°	1070.6	1061.3	1041.1	1003.3	951.8	885.5	805.4	711.5	609.3	513.7	437.2
127.5°	1009.8	1005.8	986.6	953.2	906.5	844.5	769.7	682.1	592.8	511.4	446.9
130°	976.6	971.1	952.7	922.3	876.3	816.5	744.7	663.7	581.8	509.9	452.9
132.5°	943.5	937.2	920.3	889.9	843.9	786.2	721.1	645.2	572.9	509.9	459.5
135°	889.2	883.7	867.1	836.7	796.2	743.8	684.8	621.3	562.4	509.9	468.5
137.5°	831.2	825.1	809.8	782.2	746.0	701.4	652.4	601.1	553.0	511.0	476.8
140°	790.7	786.1	772.3	748.4	714.3	675.7	633.3	590.0	548.6	511.7	480.5
142.5°	753.1	749.2	736.2	716.0	687.1	653.6	617.1	580.4	544.9	512.5	482.7
145°	701.4	697.8	687.6	671.9	649.8	625.0	596.4	567.9	539.4	511.7	485.1
147.5°	657.6	655.9	650.1	637.5	620.0	601.3	579.3	556.2	533.7	509.4	486.0
150°	633.3	632.4	628.7	617.7	603.8	587.2	569.8	549.5	529.3	507.2	486.0
152.5°	614.2	613.2	609.5	600.7	589.1	576.2	560.2	542.2	524.1	504.2	485.3
155°	588.2	587.2	584.5	578.1	568.9	558.7	545.8	531.1	515.5	498.9	483.2
157.5°	565.0	565.1	562.6	557.2	550.1	542.2	532.2	520.1	507.4	493.4	480.9
160°	549.5	550.5	548.6	544.0	537.6	531.1	521.9	512.7	500.7	489.7	478.6
162.5°	535.5	535.8	535.4	531.5	526.5	520.8	513.1	504.6	494.9	485.3	476.4
165°	515.5	515.5	515.5	513.7	509.9	505.3	499.8	493.4	486.0	478.6	473.1
167.5°	497.1	497.3	498.0	496.3	494.5	491.2	487.0	482.7	477.4	472.2	467.9
170°	486.0	487.0	487.0	486.0	484.2	482.4	479.6	476.8	472.2	468.5	465.8
172.5°	475.7	476.7	478.1	476.4	476.1	475.0	472.9	470.2	467.1	464.1	462.8
175°	463.0	463.9	465.8	464.9	464.9	464.9	463.0	463.0	460.3	459.3	459.3
177.5°	456.5	456.5	458.8	458.0	458.8	458.8	458.8	458.0	457.3	456.5	456.5
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1496.9	1493.4	1489.5	1482.6	1474.2	1469.7	1462.8	1458.3	1449.5	1442.0	1434.2
5°	1572.8	1556.8	1542.0	1522.8	1501.8	1488.2	1472.2	1454.3	1435.8	1416.6	1395.6
7.5°	1651.5	1623.1	1592.2	1559.0	1526.5	1496.6	1468.1	1440.0	1413.9	1382.3	1355.5
10°	1704.4	1668.6	1630.2	1585.2	1541.3	1503.1	1464.1	1430.2	1395.6	1358.5	1325.8
12.5°	1757.2	1709.5	1655.4	1605.9	1553.2	1507.0	1461.2	1417.8	1374.4	1333.3	1295.2
15°	1794.5	1752.5	1702.5	1632.1	1572.8	1509.3	1448.7	1392.5	1340.1	1294.3	1246.2
17.5°	1819.1	1765.0	1711.3	1643.7	1566.1	1494.9	1426.3	1362.0	1302.8	1244.9	1198.5
20°	1823.5	1768.0	1711.7	1645.7	1566.1	1484.5	1415.9	1338.8	1275.2	1215.3	1158.5
22.5°	1822.1	1759.0	1698.0	1629.9	1552.2	1477.1	1394.2	1315.6	1246.5	1187.6	1128.3
25°	1808.1	1740.8	1664.2	1595.7	1519.1	1439.5	1355.5	1274.0	1203.6	1136.2	1077.6
27.5°	1796.5	1709.2	1622.5	1542.5	1468.6	1395.6	1315.2	1231.7	1153.7	1085.4	1030.2
30°	1782.2	1686.5	1588.9	1505.5	1429.6	1358.5	1282.6	1201.1	1119.6	1052.9	993.6
32.5°	1769.3	1657.8	1554.8	1464.0	1383.6	1314.5	1244.5	1167.0	1087.0	1019.3	960.0
35°	1744.5	1615.4	1497.5	1395.0	1309.2	1238.1	1179.5	1107.2	1033.7	968.3	911.5
37.5°	1713.0	1559.9	1433.3	1325.8	1231.7	1156.9	1102.2	1046.8	976.3	913.2	861.8
40°	1688.3	1520.4	1386.3	1276.4	1178.8	1101.1	1050.4	997.9	939.3	880.6	826.2
42.5°	1657.2	1484.8	1338.9	1220.6	1124.0	1048.2	995.1	950.5	898.7	844.1	793.6
45°	1600.0	1420.3	1262.2	1135.0	1037.4	962.7	907.8	874.4	835.5	783.6	741.0
47.5°	1515.9	1342.8	1179.3	1048.1	947.4	878.1	826.6	794.6	767.2	728.6	690.0
50°	1441.3	1285.1	1119.6	989.3	888.6	818.8	771.3	742.3	718.8	689.1	656.4
52.5°	1357.8	1212.4	1060.8	932.0	832.3	763.5	716.9	691.4	671.8	650.6	618.4
55°	1225.2	1101.7	960.8	838.6	746.6	679.3	638.5	616.3	600.2	584.2	564.4
57.5°	1079.0	982.5	857.8	746.0	661.2	600.0	562.0	540.3	527.8	519.6	507.9
60°	976.3	893.6	786.1	684.2	601.5	547.2	510.1	493.4	482.9	476.1	467.5
62.5°	881.0	813.0	713.5	620.5	548.1	496.7	463.7	447.4	437.4	434.1	427.0
65°	740.4	687.9	605.8	528.6	466.8	423.0	395.2	379.8	373.6	369.9	370.5
67.5°	602.0	570.0	504.0	438.2	388.9	352.1	329.9	318.1	315.0	310.0	309.9
70°	517.5	493.4	437.8	380.4	336.5	308.2	288.4	276.0	272.9	270.5	269.9
72.5°	442.9	421.8	373.6	327.6	288.1	263.2	246.9	239.5	234.4	232.9	232.8
75°	332.9	321.2	282.8	246.4	219.2	201.9	190.8	184.0	180.3	179.7	180.3
77.5°	236.6	226.4	202.1	176.3	159.1	146.0	136.6	134.3	130.1	130.2	129.5
80°	177.8	171.0	155.6	135.2	121.0	110.0	105.0	100.7	99.4	97.6	99.4
82.5°	129.0	121.7	111.1	98.2	86.4	79.8	74.9	73.5	72.7	71.9	72.2
85°	63.6	64.2	58.1	48.2	43.3	39.5	36.4	36.4	35.8	35.2	35.8
87.5°	24.2	22.7	20.6	18.8	15.9	14.1	13.2	13.5	12.2	12.1	13.0
90°	12.0	10.1	9.2	7.4	5.5	3.6	1.8	1.0	1.8	3.6	5.5
92.5°	210.1	125.7	75.5	48.6	32.8	21.4	13.6	11.2	13.6	21.4	32.8
95°	411.5	209.0	110.4	69.0	48.8	38.7	31.3	30.3	31.3	38.7	48.8
97.5°	328.4	180.1	114.9	85.1	66.9	56.7	51.6	50.5	51.6	56.7	66.9
100°	298.3	178.6	125.2	97.6	80.1	69.9	66.3	64.4	66.3	69.9	80.1
102.5°	285.7	185.2	137.7	110.8	94.8	84.0	81.0	79.9	81.0	84.0	94.8
105°	280.7	198.8	158.4	132.5	117.8	108.6	104.0	104.0	104.0	108.6	117.8
107.5°	289.2	219.0	179.8	156.7	141.4	133.8	129.4	127.5	129.4	133.8	141.4
110°	297.3	233.8	196.1	172.1	158.4	150.0	146.4	144.5	146.4	150.0	158.4



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	307.6	247.8	211.5	188.3	174.5	166.2	163.3	161.4	163.3	166.2	174.5
115°	323.1	269.7	235.7	212.6	198.8	190.5	187.7	185.9	187.7	190.5	198.8
117.5°	340.8	292.2	259.9	237.7	222.0	213.7	210.8	208.0	210.8	213.7	222.0
120°	352.5	308.4	276.2	253.1	237.5	229.2	225.5	222.8	225.5	229.2	237.5
122.5°	365.8	323.8	291.6	268.6	251.4	243.2	240.3	238.2	240.3	243.2	251.4
125°	383.8	344.3	313.9	289.9	272.4	264.2	259.6	257.7	259.6	264.2	272.4
127.5°	400.4	363.9	334.7	310.8	292.2	281.7	275.8	273.0	275.8	281.7	292.2
130°	411.5	376.4	347.9	324.0	304.7	292.7	285.3	282.6	285.3	292.7	304.7
132.5°	421.0	388.2	359.7	335.8	315.8	302.3	293.4	289.9	293.4	302.3	315.8
135°	434.4	404.1	375.6	350.7	331.4	316.6	305.6	301.9	305.6	316.6	331.4
137.5°	444.4	415.3	389.4	363.8	344.8	330.1	319.8	317.0	319.8	330.1	344.8
140°	451.1	423.4	396.7	371.9	354.4	339.7	328.6	325.8	328.6	339.7	354.4
142.5°	454.7	428.6	403.4	380.0	363.2	348.5	338.2	336.1	338.2	348.5	363.2
145°	460.3	437.2	413.3	392.1	375.6	362.7	353.5	351.6	353.5	362.7	375.6
147.5°	463.6	442.8	421.8	403.1	388.8	376.8	368.9	367.8	368.9	376.8	388.8
150°	465.8	446.4	426.2	410.5	397.7	385.7	379.2	377.4	379.2	385.7	397.7
152.5°	467.2	450.1	431.3	417.2	405.0	394.5	388.8	387.7	388.8	394.5	405.0
155°	468.5	453.8	438.2	425.2	416.1	406.9	401.3	401.3	401.3	406.9	416.1
157.5°	469.4	456.9	443.5	433.7	425.6	417.7	413.3	413.5	413.3	417.7	425.6
160°	469.4	458.4	446.4	438.2	430.8	424.4	420.6	421.6	420.6	424.4	430.8
162.5°	468.7	459.9	449.4	442.6	436.7	430.9	427.3	428.2	427.3	430.9	436.7
165°	467.6	460.3	452.9	447.3	443.7	439.1	436.3	438.2	436.3	439.1	443.7
167.5°	465.4	460.3	454.2	450.7	448.1	445.5	443.9	444.8	443.9	445.5	448.1
170°	463.9	460.3	455.7	452.9	451.1	449.2	448.3	449.2	448.3	449.2	451.1
172.5°	462.5	459.5	455.7	454.3	453.2	451.4	450.5	452.2	450.5	451.4	453.2
175°	460.3	458.4	455.7	455.7	455.7	454.7	453.8	455.7	453.8	454.7	455.7
177.5°	458.0	457.3	455.8	455.8	456.5	455.8	455.8	457.3	455.8	455.8	456.5
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1429.7	1424.3	1419.8	1409.9	1404.5	1397.1	1391.2	1397.6	1390.7	1393.6	1389.2
5°	1385.1	1367.8	1355.5	1337.5	1322.2	1307.9	1297.4	1295.5	1290.6	1288.2	1280.7
7.5°	1331.5	1309.9	1288.6	1265.2	1245.4	1225.3	1212.4	1201.8	1194.8	1185.5	1179.2
10°	1299.9	1270.9	1246.2	1217.7	1193.0	1171.5	1154.1	1145.5	1137.5	1125.8	1121.4
12.5°	1260.8	1230.8	1200.7	1170.4	1146.6	1122.5	1107.7	1094.6	1089.1	1075.9	1074.5
15°	1214.0	1168.9	1139.3	1108.4	1075.7	1056.0	1043.6	1029.4	1023.3	1014.0	1007.2
17.5°	1158.2	1117.9	1080.9	1048.9	1020.9	1004.2	988.9	979.1	968.5	962.5	951.3
20°	1117.7	1079.4	1042.4	1008.4	986.8	967.7	955.3	946.0	934.9	931.8	920.8
22.5°	1083.6	1041.4	1005.8	977.3	953.7	932.1	918.8	912.4	904.8	895.3	893.0
25°	1028.2	984.4	954.1	925.7	904.7	884.9	875.7	867.6	860.2	853.4	851.0
27.5°	980.2	941.1	905.1	879.5	861.2	843.2	835.0	825.3	819.8	814.4	807.7
30°	946.7	906.5	875.0	850.3	830.6	814.5	805.9	799.1	794.2	789.2	785.5
32.5°	912.1	874.9	844.4	820.2	800.4	788.3	780.7	775.9	770.4	764.5	759.8
35°	866.4	825.6	796.0	775.0	759.5	750.3	741.6	737.3	731.2	731.2	726.2
37.5°	814.9	779.7	753.5	734.4	720.5	712.3	702.9	699.9	695.9	693.3	691.7
40°	784.3	751.5	726.8	707.7	692.8	686.0	678.7	673.8	671.2	668.1	666.9
42.5°	752.7	721.4	697.7	680.0	667.2	661.4	654.4	651.0	646.0	642.0	641.3
45°	704.6	674.3	652.8	638.5	627.4	620.6	616.3	608.9	606.4	601.5	600.9
47.5°	659.0	630.0	608.8	597.1	587.4	581.9	575.0	567.6	564.8	562.3	562.1
50°	625.0	598.4	578.6	567.5	558.3	550.2	543.4	538.4	536.6	536.6	537.9
52.5°	590.3	567.8	551.0	537.3	528.6	520.1	513.8	510.8	507.9	511.0	513.2
55°	539.7	516.9	504.5	491.5	482.9	473.0	469.9	468.7	466.8	471.8	474.3
57.5°	486.1	470.1	455.6	442.8	435.0	429.3	425.1	424.4	427.9	430.2	438.2
60°	452.0	433.5	420.6	410.7	401.4	397.7	396.5	395.2	397.7	404.5	414.9
62.5°	414.5	399.4	385.5	378.0	371.2	365.1	364.8	365.6	370.5	378.3	388.8
65°	359.4	346.4	337.2	328.5	323.0	319.2	320.5	323.0	328.5	339.1	350.8
67.5°	303.5	294.5	286.3	279.2	273.9	273.9	275.2	278.8	285.4	297.5	308.2
70°	267.4	257.5	250.7	247.6	243.3	240.8	244.5	250.7	256.3	267.4	276.6
72.5°	231.3	222.9	217.6	215.6	213.7	211.7	212.9	219.6	227.1	238.2	249.0
75°	177.8	174.8	171.0	168.6	166.8	167.9	169.2	175.4	181.6	193.3	205.7
77.5°	129.8	126.6	124.4	123.7	122.8	123.3	126.8	131.4	137.4	146.0	155.3
80°	98.2	97.0	95.7	95.1	95.1	95.7	100.7	103.8	109.3	117.3	124.8
82.5°	71.5	70.7	70.5	70.4	70.9	71.0	74.0	78.0	82.6	88.6	95.1
85°	37.7	36.4	38.3	38.9	37.7	39.5	40.7	43.3	45.1	48.2	51.3
87.5°	13.8	15.2	14.9	15.8	15.9	17.3	17.0	19.1	20.3	21.5	21.3
90°	7.4	9.2	10.1	12.0	12.9	14.7	15.7	16.6	17.5	18.4	20.3
92.5°	48.6	75.5	125.7	210.1	301.6	296.8	240.3	163.1	118.4	89.1	75.5
95°	69.0	110.4	209.0	411.5	665.5	815.6	798.0	661.8	521.9	408.7	331.4
97.5°	85.1	114.9	180.1	328.4	594.3	870.9	1009.8	985.6	887.6	777.3	669.7
100°	97.6	125.2	178.6	298.3	530.2	831.2	1061.3	1132.2	1087.1	992.3	896.5
102.5°	110.8	137.7	185.2	285.7	481.6	761.2	1030.4	1181.5	1209.3	1163.9	1099.1
105°	132.5	158.4	198.8	280.7	434.4	667.3	931.5	1152.5	1278.6	1319.1	1308.9
107.5°	156.7	179.8	219.0	289.2	414.5	602.7	830.7	1048.6	1216.9	1320.9	1369.0
110°	172.1	196.1	233.8	297.3	408.7	572.5	773.2	972.0	1146.9	1276.7	1354.9



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	188.3	211.5	247.8	307.6	408.7	554.8	730.5	911.6	1077.7	1208.9	1301.2
115°	212.6	235.7	269.7	323.1	411.5	535.8	683.9	835.8	978.5	1104.5	1204.9
117.5°	237.7	259.9	292.2	340.8	417.6	526.3	656.1	786.8	909.8	1018.4	1110.5
120°	253.1	276.2	308.4	352.5	423.4	521.9	640.6	760.3	870.8	972.0	1053.0
122.5°	268.6	291.6	323.8	365.8	428.6	518.2	627.4	740.5	842.8	933.0	1008.8
125°	289.9	313.9	344.3	383.8	437.2	513.7	609.3	711.5	805.4	885.5	951.8
127.5°	310.8	334.7	363.9	400.4	446.9	511.4	592.8	682.1	769.7	844.5	906.5
130°	324.0	347.9	376.4	411.5	452.9	509.9	581.8	663.7	744.7	816.5	876.3
132.5°	335.8	359.7	388.2	421.0	459.5	509.9	572.9	645.2	721.1	786.2	843.9
135°	350.7	375.6	404.1	434.4	468.5	509.9	562.4	621.3	684.8	743.8	796.2
137.5°	363.8	389.4	415.3	444.4	476.8	511.0	553.0	601.1	652.4	701.4	746.0
140°	371.9	396.7	423.4	451.1	480.5	511.7	548.6	590.0	633.3	675.7	714.3
142.5°	380.0	403.4	428.6	454.7	482.7	512.5	544.9	580.4	617.1	653.6	687.1
145°	392.1	413.3	437.2	460.3	485.1	511.7	539.4	567.9	596.4	625.0	649.8
147.5°	403.1	421.8	442.8	463.6	486.0	509.4	533.7	556.2	579.3	601.3	620.0
150°	410.5	426.2	446.4	465.8	486.0	507.2	529.3	549.5	569.8	587.2	603.8
152.5°	417.2	431.3	450.1	467.2	485.3	504.2	524.1	542.2	560.2	576.2	589.1
155°	425.2	438.2	453.8	468.5	483.2	498.9	515.5	531.1	545.8	558.7	568.9
157.5°	433.7	443.5	456.9	469.4	480.9	493.4	507.4	520.1	532.2	542.2	550.1
160°	438.2	446.4	458.4	469.4	478.6	489.7	500.7	512.7	521.9	531.1	537.6
162.5°	442.6	449.4	459.9	468.7	476.4	485.3	494.9	504.6	513.1	520.8	526.5
165°	447.3	452.9	460.3	467.6	473.1	478.6	486.0	493.4	499.8	505.3	509.9
167.5°	450.7	454.2	460.3	465.4	467.9	472.2	477.4	482.7	487.0	491.2	494.5
170°	452.9	455.7	460.3	463.9	465.8	468.5	472.2	476.8	479.6	482.4	484.2
172.5°	454.3	455.7	459.5	462.5	462.8	464.1	467.1	470.2	472.9	475.0	476.1
175°	455.7	455.7	458.4	460.3	459.3	459.3	460.3	463.0	463.0	464.9	464.9
177.5°	455.8	455.8	457.3	458.0	456.5	456.5	457.3	458.0	458.8	458.8	458.8
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1386.2	1389.6	1386.7	1390.7	1386.7	1389.6	1386.2	1389.2	1393.6	1390.7	1397.6
5°	1277.6	1272.1	1275.8	1273.4	1275.8	1272.1	1277.6	1280.7	1288.2	1290.6	1295.5
7.5°	1177.3	1172.0	1166.0	1163.2	1166.0	1172.0	1177.3	1179.2	1185.5	1194.8	1201.8
10°	1114.6	1107.9	1107.2	1102.9	1107.2	1107.9	1114.6	1121.4	1125.8	1137.5	1145.5
12.5°	1068.7	1062.4	1055.3	1053.5	1055.3	1062.4	1068.7	1074.5	1075.9	1089.1	1094.6
15°	1003.5	998.5	994.2	997.9	994.2	998.5	1003.5	1007.2	1014.0	1023.3	1029.4
17.5°	949.3	945.2	944.4	939.8	944.4	945.2	949.3	951.3	962.5	968.5	979.1
20°	915.2	912.1	913.3	905.3	913.3	912.1	915.2	920.8	931.8	934.9	946.0
22.5°	888.0	881.9	881.2	879.6	881.2	881.9	888.0	893.0	895.3	904.8	912.4
25°	845.4	842.3	839.2	842.3	839.2	842.3	845.4	851.0	853.4	860.2	867.6
27.5°	808.2	804.5	803.7	804.0	803.7	804.5	808.2	807.7	814.4	819.8	825.3
30°	785.5	779.3	779.9	779.3	779.9	779.3	785.5	785.5	789.2	794.2	799.1
32.5°	760.8	756.6	755.7	754.6	755.7	756.6	760.8	759.8	764.5	770.4	775.9
35°	724.4	724.4	721.3	721.3	721.3	724.4	724.4	726.2	731.2	731.2	737.3
37.5°	690.1	689.5	687.7	687.9	687.7	689.5	690.1	691.7	693.3	695.9	699.9
40°	664.5	663.8	661.9	658.3	661.9	663.8	664.5	666.9	668.1	671.2	673.8
42.5°	639.8	637.6	636.8	635.6	636.8	637.6	639.8	641.3	642.0	646.0	651.0
45°	600.9	600.9	599.6	599.0	599.6	600.9	600.9	600.9	601.5	606.4	608.9
47.5°	563.1	564.2	566.5	566.2	566.5	564.2	563.1	562.1	562.3	564.8	567.6
50°	540.3	541.0	542.8	543.4	542.8	541.0	540.3	537.9	536.6	536.6	538.4
52.5°	515.2	518.7	521.1	520.7	521.1	518.7	515.2	513.2	511.0	507.9	510.8
55°	479.8	484.1	488.5	489.1	488.5	484.1	479.8	474.3	471.8	466.8	468.7
57.5°	444.9	450.9	455.5	456.9	455.5	450.9	444.9	438.2	430.2	427.9	424.4
60°	421.1	429.2	434.7	437.2	434.7	429.2	421.1	414.9	404.5	397.7	395.2
62.5°	398.4	407.4	413.0	413.5	413.0	407.4	398.4	388.8	378.3	370.5	365.6
65°	361.2	370.5	375.4	379.1	375.4	370.5	361.2	350.8	339.1	328.5	323.0
67.5°	321.2	330.5	336.0	338.9	336.0	330.5	321.2	308.2	297.5	285.4	278.8
70°	292.1	301.3	308.8	311.2	308.8	301.3	292.1	276.6	267.4	256.3	250.7
72.5°	263.4	271.7	277.7	280.6	277.7	271.7	263.4	249.0	238.2	227.1	219.6
75°	213.7	224.7	230.4	233.5	230.4	224.7	213.7	205.7	193.3	181.6	175.4
77.5°	164.8	174.9	178.2	179.8	178.2	174.9	164.8	155.3	146.0	137.4	131.4
80°	132.1	138.3	142.7	143.2	142.7	138.3	132.1	124.8	117.3	109.3	103.8
82.5°	101.6	106.7	108.1	109.6	108.1	106.7	101.6	95.1	88.6	82.6	78.0
85°	55.6	58.1	58.7	58.1	58.7	58.1	55.6	51.3	48.2	45.1	43.3
87.5°	22.3	21.9	22.0	23.0	22.0	21.9	22.3	21.3	21.5	20.3	19.1
90°	20.3	20.3	21.2	21.2	21.2	20.3	20.3	20.3	18.4	17.5	16.6
92.5°	63.7	61.5	60.2	58.7	60.2	61.5	63.7	75.5	89.1	118.4	163.1
95°	266.0	238.4	231.1	216.3	231.1	238.4	266.0	331.4	408.7	521.9	661.8
97.5°	612.8	561.3	534.6	522.8	534.6	561.3	612.8	669.7	777.3	887.6	985.6
100°	833.1	766.8	732.7	718.0	732.7	766.8	833.1	896.5	992.3	1087.1	1132.2
102.5°	1031.1	984.0	947.0	936.0	947.0	984.0	1031.1	1099.1	1163.9	1209.3	1181.5
105°	1279.5	1249.1	1230.7	1219.6	1230.7	1249.1	1279.5	1308.9	1319.1	1278.6	1152.5
107.5°	1383.9	1383.7	1377.6	1370.2	1377.6	1383.7	1383.9	1369.0	1320.9	1216.9	1048.6
110°	1396.4	1413.9	1420.3	1420.3	1420.3	1413.9	1396.4	1354.9	1276.7	1146.9	972.0



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	1361.8	1391.8	1407.8	1414.4	1407.8	1391.8	1361.8	1301.2	1208.9	1077.7	911.6
115°	1276.7	1320.9	1346.6	1358.6	1346.6	1320.9	1276.7	1204.9	1104.5	978.5	835.8
117.5°	1182.3	1228.0	1253.5	1260.8	1253.5	1228.0	1182.3	1110.5	1018.4	909.8	786.8
120°	1121.2	1165.3	1190.2	1197.5	1190.2	1165.3	1121.2	1053.0	972.0	870.8	760.3
122.5°	1069.6	1110.1	1135.0	1141.6	1135.0	1110.1	1069.6	1008.8	933.0	842.8	740.5
125°	1003.3	1041.1	1061.3	1070.6	1061.3	1041.1	1003.3	951.8	885.5	805.4	711.5
127.5°	953.2	986.6	1005.8	1009.8	1005.8	986.6	953.2	906.5	844.5	769.7	682.1
130°	922.3	952.7	971.1	976.6	971.1	952.7	922.3	876.3	816.5	744.7	663.7
132.5°	889.9	920.3	937.2	943.5	937.2	920.3	889.9	843.9	786.2	721.1	645.2
135°	836.7	867.1	883.7	889.2	883.7	867.1	836.7	796.2	743.8	684.8	621.3
137.5°	782.2	809.8	825.1	831.2	825.1	809.8	782.2	746.0	701.4	652.4	601.1
140°	748.4	772.3	786.1	790.7	786.1	772.3	748.4	714.3	675.7	633.3	590.0
142.5°	716.0	736.2	749.2	753.1	749.2	736.2	716.0	687.1	653.6	617.1	580.4
145°	671.9	687.6	697.8	701.4	697.8	687.6	671.9	649.8	625.0	596.4	567.9
147.5°	637.5	650.1	655.9	657.6	655.9	650.1	637.5	620.0	601.3	579.3	556.2
150°	617.7	628.7	632.4	633.3	632.4	628.7	617.7	603.8	587.2	569.8	549.5
152.5°	600.7	609.5	613.2	614.2	613.2	609.5	600.7	589.1	576.2	560.2	542.2
155°	578.1	584.5	587.2	588.2	587.2	584.5	578.1	568.9	558.7	545.8	531.1
157.5°	557.2	562.6	565.1	565.0	565.1	562.6	557.2	550.1	542.2	532.2	520.1
160°	544.0	548.6	550.5	549.5	550.5	548.6	544.0	537.6	531.1	521.9	512.7
162.5°	531.5	535.4	535.8	535.5	535.8	535.4	531.5	526.5	520.8	513.1	504.6
165°	513.7	515.5	515.5	515.5	515.5	515.5	513.7	509.9	505.3	499.8	493.4
167.5°	496.3	498.0	497.3	497.1	497.3	498.0	496.3	494.5	491.2	487.0	482.7
170°	486.0	487.0	487.0	486.0	487.0	487.0	486.0	484.2	482.4	479.6	476.8
172.5°	476.4	478.1	476.7	475.7	476.7	478.1	476.4	476.1	475.0	472.9	470.2
175°	464.9	465.8	463.9	463.0	463.9	465.8	464.9	464.9	464.9	463.0	463.0
177.5°	458.0	458.8	456.5	456.5	456.5	458.8	458.0	458.8	458.8	458.8	458.0
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1391.2	1397.1	1404.5	1409.9	1419.8	1424.3	1429.7	1434.2	1442.0	1449.5	1458.3
5°	1297.4	1307.9	1322.2	1337.5	1355.5	1367.8	1385.1	1395.6	1416.6	1435.8	1454.3
7.5°	1212.4	1225.3	1245.4	1265.2	1288.6	1309.9	1331.5	1355.5	1382.3	1413.9	1440.0
10°	1154.1	1171.5	1193.0	1217.7	1246.2	1270.9	1299.9	1325.8	1358.5	1395.6	1430.2
12.5°	1107.7	1122.5	1146.6	1170.4	1200.7	1230.8	1260.8	1295.2	1333.3	1374.4	1417.8
15°	1043.6	1056.0	1075.7	1108.4	1139.3	1168.9	1214.0	1246.2	1294.3	1340.1	1392.5
17.5°	988.9	1004.2	1020.9	1048.9	1080.9	1117.9	1158.2	1198.5	1244.9	1302.8	1362.0
20°	955.3	967.7	986.8	1008.4	1042.4	1079.4	1117.7	1158.5	1215.3	1275.2	1338.8
22.5°	918.8	932.1	953.7	977.3	1005.8	1041.4	1083.6	1128.3	1187.6	1246.5	1315.6
25°	875.7	884.9	904.7	925.7	954.1	984.4	1028.2	1077.6	1136.2	1203.6	1274.0
27.5°	835.0	843.2	861.2	879.5	905.1	941.1	980.2	1030.2	1085.4	1153.7	1231.7
30°	805.9	814.5	830.6	850.3	875.0	906.5	946.7	993.6	1052.9	1119.6	1201.1
32.5°	780.7	788.3	800.4	820.2	844.4	874.9	912.1	960.0	1019.3	1087.0	1167.0
35°	741.6	750.3	759.5	775.0	796.0	825.6	866.4	911.5	968.3	1033.7	1107.2
37.5°	702.9	712.3	720.5	734.4	753.5	779.7	814.9	861.8	913.2	976.3	1046.8
40°	678.7	686.0	692.8	707.7	726.8	751.5	784.3	826.2	880.6	939.3	997.9
42.5°	654.4	661.4	667.2	680.0	697.7	721.4	752.7	793.6	844.1	898.7	950.5
45°	616.3	620.6	627.4	638.5	652.8	674.3	704.6	741.0	783.6	835.5	874.4
47.5°	575.0	581.9	587.4	597.1	608.8	630.0	659.0	690.0	728.6	767.2	794.6
50°	543.4	550.2	558.3	567.5	578.6	598.4	625.0	656.4	689.1	718.8	742.3
52.5°	513.8	520.1	528.6	537.3	551.0	567.8	590.3	618.4	650.6	671.8	691.4
55°	469.9	473.0	482.9	491.5	504.5	516.9	539.7	564.4	584.2	600.2	616.3
57.5°	425.1	429.3	435.0	442.8	455.6	470.1	486.1	507.9	519.6	527.8	540.3
60°	396.5	397.7	401.4	410.7	420.6	433.5	452.0	467.5	476.1	482.9	493.4
62.5°	364.8	365.1	371.2	378.0	385.5	399.4	414.5	427.0	434.1	437.4	447.4
65°	320.5	319.2	323.0	328.5	337.2	346.4	359.4	370.5	369.9	373.6	379.8
67.5°	275.2	273.9	273.9	279.2	286.3	294.5	303.5	309.9	310.0	315.0	318.1
70°	244.5	240.8	243.3	247.6	250.7	257.5	267.4	269.9	270.5	272.9	276.0
72.5°	212.9	211.7	213.7	215.6	217.6	222.9	231.3	232.8	232.9	234.4	239.5
75°	169.2	167.9	166.8	168.6	171.0	174.8	177.8	180.3	179.7	180.3	184.0
77.5°	126.8	123.3	122.8	123.7	124.4	126.6	129.8	129.5	130.2	130.1	134.3
80°	100.7	95.7	95.1	95.1	95.7	97.0	98.2	99.4	97.6	99.4	100.7
82.5°	74.0	71.0	70.9	70.4	70.5	70.7	71.5	72.2	71.9	72.7	73.5
85°	40.7	39.5	37.7	38.9	38.3	36.4	37.7	35.8	35.2	35.8	36.4
87.5°	17.0	17.3	15.9	15.8	14.9	15.2	13.8	13.0	12.1	12.2	13.5
90°	15.7	14.7	12.9	12.0	10.1	9.2	7.4	5.5	3.6	1.8	1.0
92.5°	240.3	296.8	301.6	210.1	125.7	75.5	48.6	32.8	21.4	13.6	11.2
95°	798.0	815.6	665.5	411.5	209.0	110.4	69.0	48.8	38.7	31.3	30.3
97.5°	1009.8	870.9	594.3	328.4	180.1	114.9	85.1	66.9	56.7	51.6	50.5
100°	1061.3	831.2	530.2	298.3	178.6	125.2	97.6	80.1	69.9	66.3	64.4
102.5°	1030.4	761.2	481.6	285.7	185.2	137.7	110.8	94.8	84.0	81.0	79.9
105°	931.5	667.3	434.4	280.7	198.8	158.4	132.5	117.8	108.6	104.0	104.0
107.5°	830.7	602.7	414.5	289.2	219.0	179.8	156.7	141.4	133.8	129.4	127.5
110°	773.2	572.5	408.7	297.3	233.8	196.1	172.1	158.4	150.0	146.4	144.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	730.5	554.8	408.7	307.6	247.8	211.5	188.3	174.5	166.2	163.3	161.4
115°	683.9	535.8	411.5	323.1	269.7	235.7	212.6	198.8	190.5	187.7	185.9
117.5°	656.1	526.3	417.6	340.8	292.2	259.9	237.7	222.0	213.7	210.8	208.0
120°	640.6	521.9	423.4	352.5	308.4	276.2	253.1	237.5	229.2	225.5	222.8
122.5°	627.4	518.2	428.6	365.8	323.8	291.6	268.6	251.4	243.2	240.3	238.2
125°	609.3	513.7	437.2	383.8	344.3	313.9	289.9	272.4	264.2	259.6	257.7
127.5°	592.8	511.4	446.9	400.4	363.9	334.7	310.8	292.2	281.7	275.8	273.0
130°	581.8	509.9	452.9	411.5	376.4	347.9	324.0	304.7	292.7	285.3	282.6
132.5°	572.9	509.9	459.5	421.0	388.2	359.7	335.8	315.8	302.3	293.4	289.9
135°	562.4	509.9	468.5	434.4	404.1	375.6	350.7	331.4	316.6	305.6	301.9
137.5°	553.0	511.0	476.8	444.4	415.3	389.4	363.8	344.8	330.1	319.8	317.0
140°	548.6	511.7	480.5	451.1	423.4	396.7	371.9	354.4	339.7	328.6	325.8
142.5°	544.9	512.5	482.7	454.7	428.6	403.4	380.0	363.2	348.5	338.2	336.1
145°	539.4	511.7	485.1	460.3	437.2	413.3	392.1	375.6	362.7	353.5	351.6
147.5°	533.7	509.4	486.0	463.6	442.8	421.8	403.1	388.8	376.8	368.9	367.8
150°	529.3	507.2	486.0	465.8	446.4	426.2	410.5	397.7	385.7	379.2	377.4
152.5°	524.1	504.2	485.3	467.2	450.1	431.3	417.2	405.0	394.5	388.8	387.7
155°	515.5	498.9	483.2	468.5	453.8	438.2	425.2	416.1	406.9	401.3	401.3
157.5°	507.4	493.4	480.9	469.4	456.9	443.5	433.7	425.6	417.7	413.3	413.5
160°	500.7	489.7	478.6	469.4	458.4	446.4	438.2	430.8	424.4	420.6	421.6
162.5°	494.9	485.3	476.4	468.7	459.9	449.4	442.6	436.7	430.9	427.3	428.2
165°	486.0	478.6	473.1	467.6	460.3	452.9	447.3	443.7	439.1	436.3	438.2
167.5°	477.4	472.2	467.9	465.4	460.3	454.2	450.7	448.1	445.5	443.9	444.8
170°	472.2	468.5	465.8	463.9	460.3	455.7	452.9	451.1	449.2	448.3	449.2
172.5°	467.1	464.1	462.8	462.5	459.5	455.7	454.3	453.2	451.4	450.5	452.2
175°	460.3	459.3	459.3	460.3	458.4	455.7	455.7	455.7	454.7	453.8	455.7
177.5°	457.3	456.5	456.5	458.0	457.3	455.8	455.8	456.5	455.8	455.8	457.3
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1462.8	1469.7	1474.2	1482.6	1489.5	1493.4	1496.9	1499.8	1503.3	1506.3	1514.7
5°	1472.2	1488.2	1501.8	1522.8	1542.0	1556.8	1572.8	1587.1	1598.8	1615.4	1628.4
7.5°	1468.1	1496.6	1526.5	1559.0	1592.2	1623.1	1651.5	1678.1	1702.2	1731.3	1756.8
10°	1464.1	1503.1	1541.3	1585.2	1630.2	1668.6	1704.4	1740.8	1767.4	1804.4	1835.9
12.5°	1461.2	1507.0	1553.2	1605.9	1655.4	1709.5	1757.2	1783.8	1824.2	1853.8	1891.3
15°	1448.7	1509.3	1572.8	1632.1	1702.5	1752.5	1794.5	1846.4	1884.0	1921.8	1962.5
17.5°	1426.3	1494.9	1566.1	1643.7	1711.3	1765.0	1819.1	1869.2	1914.1	1964.6	2015.3
20°	1415.9	1484.5	1566.1	1645.7	1711.7	1768.0	1823.5	1878.5	1927.9	1992.7	2051.4
22.5°	1394.2	1477.1	1552.2	1629.9	1698.0	1759.0	1822.1	1884.4	1950.1	2023.4	2096.8
25°	1355.5	1439.5	1519.1	1595.7	1664.2	1740.8	1808.1	1891.5	1975.5	2072.4	2163.8
27.5°	1315.2	1395.6	1468.6	1542.5	1622.5	1709.2	1796.5	1891.1	2001.1	2123.4	2252.3
30°	1282.6	1358.5	1429.6	1505.5	1588.9	1686.5	1782.2	1894.6	2021.8	2159.5	2312.6
32.5°	1244.5	1314.5	1383.6	1464.0	1554.8	1657.8	1769.3	1892.6	2045.5	2201.9	2359.6
35°	1179.5	1238.1	1309.2	1395.0	1497.5	1615.4	1744.5	1890.2	2065.6	2245.3	2378.1
37.5°	1102.2	1156.9	1231.7	1325.8	1433.3	1559.9	1713.0	1885.9	2072.2	2215.4	2258.3
40°	1050.4	1101.1	1178.8	1276.4	1386.3	1520.4	1688.3	1871.1	2051.4	2142.8	2107.6
42.5°	995.1	1048.2	1124.0	1220.6	1338.9	1484.8	1657.2	1840.0	1991.2	2025.7	1904.1
45°	907.8	962.7	1037.4	1135.0	1262.2	1420.3	1600.0	1766.1	1853.2	1790.8	1602.5
47.5°	826.6	878.1	947.4	1048.1	1179.3	1342.8	1515.9	1648.5	1655.3	1506.5	1305.4
50°	771.3	818.8	888.6	989.3	1119.6	1285.1	1441.3	1545.6	1498.7	1330.2	1136.9
52.5°	716.9	763.5	832.3	932.0	1060.8	1212.4	1357.8	1431.1	1342.6	1169.6	1004.5
55°	638.5	679.3	746.6	838.6	960.8	1101.7	1225.2	1250.5	1135.6	965.2	831.2
57.5°	562.0	600.0	661.2	746.0	857.8	982.5	1079.0	1073.6	952.2	806.0	699.7
60°	510.1	547.2	601.5	684.2	786.1	893.6	976.3	956.6	836.1	710.2	620.6
62.5°	463.7	496.7	548.1	620.5	713.5	813.0	881.0	851.8	733.9	623.7	552.9
65°	395.2	423.0	466.8	528.6	605.8	687.9	740.4	702.7	602.1	516.3	459.5
67.5°	329.9	352.1	388.9	438.2	504.0	570.0	602.0	564.0	483.5	420.9	378.8
70°	288.4	308.2	336.5	380.4	437.8	493.4	517.5	483.5	414.4	360.6	330.3
72.5°	246.9	263.2	288.1	327.6	373.6	421.8	442.9	410.4	353.6	308.2	280.0
75°	190.8	201.9	219.2	246.4	282.8	321.2	332.9	304.4	268.0	234.0	215.6
77.5°	136.6	146.0	159.1	176.3	202.1	226.4	236.6	220.2	192.0	170.6	155.3
80°	105.0	110.0	121.0	135.2	155.6	171.0	177.8	167.4	147.6	131.5	119.8
82.5°	74.9	79.8	86.4	98.2	111.1	121.7	129.0	121.9	107.6	95.0	88.2
85°	36.4	39.5	43.3	48.2	58.1	64.2	63.6	59.3	53.7	48.8	45.1
87.5°	13.2	14.1	15.9	18.8	20.6	22.7	24.2	23.3	21.7	20.4	19.1
90°	1.8	3.6	5.5	7.4	9.2	10.1	12.0	12.9	14.7	15.7	16.6
92.5°	13.6	21.4	32.8	48.6	75.5	125.7	210.1	301.6	296.8	240.3	163.1
95°	31.3	38.7	48.8	69.0	110.4	209.0	411.5	665.5	815.6	798.0	661.8
97.5°	51.6	56.7	66.9	85.1	114.9	180.1	328.4	594.3	870.9	1009.8	985.6
100°	66.3	69.9	80.1	97.6	125.2	178.6	298.3	530.2	831.2	1061.3	1132.2
102.5°	81.0	84.0	94.8	110.8	137.7	185.2	285.7	481.6	761.2	1030.4	1181.5
105°	104.0	108.6	117.8	132.5	158.4	198.8	280.7	434.4	667.3	931.5	1152.5
107.5°	129.4	133.8	141.4	156.7	179.8	219.0	289.2	414.5	602.7	830.7	1048.6
110°	146.4	150.0	158.4	172.1	196.1	233.8	297.3	408.7	572.5	773.2	972.0



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	163.3	166.2	174.5	188.3	211.5	247.8	307.6	408.7	554.8	730.5	911.6
115°	187.7	190.5	198.8	212.6	235.7	269.7	323.1	411.5	535.8	683.9	835.8
117.5°	210.8	213.7	222.0	237.7	259.9	292.2	340.8	417.6	526.3	656.1	786.8
120°	225.5	229.2	237.5	253.1	276.2	308.4	352.5	423.4	521.9	640.6	760.3
122.5°	240.3	243.2	251.4	268.6	291.6	323.8	365.8	428.6	518.2	627.4	740.5
125°	259.6	264.2	272.4	289.9	313.9	344.3	383.8	437.2	513.7	609.3	711.5
127.5°	275.8	281.7	292.2	310.8	334.7	363.9	400.4	446.9	511.4	592.8	682.1
130°	285.3	292.7	304.7	324.0	347.9	376.4	411.5	452.9	509.9	581.8	663.7
132.5°	293.4	302.3	315.8	335.8	359.7	388.2	421.0	459.5	509.9	572.9	645.2
135°	305.6	316.6	331.4	350.7	375.6	404.1	434.4	468.5	509.9	562.4	621.3
137.5°	319.8	330.1	344.8	363.8	389.4	415.3	444.4	476.8	511.0	553.0	601.1
140°	328.6	339.7	354.4	371.9	396.7	423.4	451.1	480.5	511.7	548.6	590.0
142.5°	338.2	348.5	363.2	380.0	403.4	428.6	454.7	482.7	512.5	544.9	580.4
145°	353.5	362.7	375.6	392.1	413.3	437.2	460.3	485.1	511.7	539.4	567.9
147.5°	368.9	376.8	388.8	403.1	421.8	442.8	463.6	486.0	509.4	533.7	556.2
150°	379.2	385.7	397.7	410.5	426.2	446.4	465.8	486.0	507.2	529.3	549.5
152.5°	388.8	394.5	405.0	417.2	431.3	450.1	467.2	485.3	504.2	524.1	542.2
155°	401.3	406.9	416.1	425.2	438.2	453.8	468.5	483.2	498.9	515.5	531.1
157.5°	413.3	417.7	425.6	433.7	443.5	456.9	469.4	480.9	493.4	507.4	520.1
160°	420.6	424.4	430.8	438.2	446.4	458.4	469.4	478.6	489.7	500.7	512.7
162.5°	427.3	430.9	436.7	442.6	449.4	459.9	468.7	476.4	485.3	494.9	504.6
165°	436.3	439.1	443.7	447.3	452.9	460.3	467.6	473.1	478.6	486.0	493.4
167.5°	443.9	445.5	448.1	450.7	454.2	460.3	465.4	467.9	472.2	477.4	482.7
170°	448.3	449.2	451.1	452.9	455.7	460.3	463.9	465.8	468.5	472.2	476.8
172.5°	450.5	451.4	453.2	454.3	455.7	459.5	462.5	462.8	464.1	467.1	470.2
175°	453.8	454.7	455.7	455.7	455.7	458.4	460.3	459.3	459.3	460.3	463.0
177.5°	455.8	455.8	456.5	455.8	455.8	457.3	458.0	456.5	456.5	457.3	458.0
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5	456.5



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9	1454.9
2.5°	1521.5	1525.5	1533.9	1531.0	1534.9	1536.9	1538.9
5°	1644.5	1664.2	1672.9	1671.7	1684.6	1681.5	1678.4
7.5°	1783.3	1804.0	1815.7	1830.1	1838.5	1839.1	1846.4
10°	1861.9	1889.0	1900.1	1915.6	1925.5	1931.0	1930.4
12.5°	1922.1	1943.4	1968.3	1975.9	1989.2	1996.2	1993.6
15°	1994.6	2028.5	2054.5	2067.4	2084.2	2089.1	2095.9
17.5°	2059.4	2104.9	2135.2	2175.4	2190.6	2199.9	2194.4
20°	2108.2	2168.1	2198.4	2246.5	2273.1	2287.3	2282.4
22.5°	2166.1	2230.9	2286.8	2328.5	2368.9	2388.1	2392.1
25°	2265.1	2354.0	2436.1	2491.1	2541.1	2552.8	2578.8
27.5°	2375.8	2480.6	2568.4	2626.2	2661.0	2674.1	2682.3
30°	2445.4	2549.7	2615.9	2652.9	2664.0	2662.8	2661.5
32.5°	2479.5	2544.8	2557.6	2547.2	2521.8	2500.2	2477.8
35°	2431.2	2382.4	2309.5	2215.7	2146.5	2076.7	2070.0
37.5°	2186.5	2030.5	1909.2	1773.8	1695.6	1647.3	1614.0
40°	1956.3	1779.1	1632.1	1517.9	1438.2	1406.8	1375.9
42.5°	1706.4	1537.0	1406.8	1311.4	1251.5	1216.6	1192.1
45°	1386.3	1236.9	1135.0	1065.9	1018.3	991.1	975.7
47.5°	1136.0	1025.5	938.9	889.0	856.1	835.0	835.1
50°	1001.6	896.0	838.6	799.1	770.6	754.0	757.1
52.5°	882.6	803.7	754.6	721.5	700.5	690.2	689.9
55°	737.9	681.1	649.0	625.0	610.7	599.0	601.5
57.5°	631.2	583.3	561.8	541.9	532.0	527.3	520.5
60°	565.1	528.0	509.5	493.4	483.5	479.8	473.0
62.5°	506.3	477.1	459.1	446.0	437.0	435.9	430.6
65°	425.5	403.2	387.2	381.0	371.8	369.3	369.3
67.5°	350.8	334.9	322.3	316.6	312.6	313.2	310.2
70°	303.8	290.9	282.8	276.6	273.5	274.2	271.7
72.5°	265.8	251.4	244.3	240.6	236.5	238.1	237.1
75°	201.3	193.9	190.2	186.5	184.0	182.8	181.6
77.5°	147.8	141.3	138.5	136.3	136.7	133.7	136.1
80°	114.2	108.7	106.9	103.8	103.1	103.1	102.5
82.5°	83.6	80.5	79.1	76.6	75.5	76.4	74.9
85°	43.3	40.7	40.2	40.2	38.9	37.7	40.7
87.5°	19.3	17.5	17.9	17.4	17.4	17.1	16.1
90°	17.5	18.4	20.3	20.3	20.3	21.2	21.2
92.5°	118.4	89.1	75.5	63.7	61.5	60.2	58.7
95°	521.9	408.7	331.4	266.0	238.4	231.1	216.3
97.5°	887.6	777.3	669.7	612.8	561.3	534.6	522.8
100°	1087.1	992.3	896.5	833.1	766.8	732.7	718.0
102.5°	1209.3	1163.9	1099.1	1031.1	984.0	947.0	936.0
105°	1278.6	1319.1	1308.9	1279.5	1249.1	1230.7	1219.6
107.5°	1216.9	1320.9	1369.0	1383.9	1383.7	1377.6	1370.2
110°	1146.9	1276.7	1354.9	1396.4	1413.9	1420.3	1420.3



TEST NUMBER: P333333-927

CATALOG NUMBER: S125DIP-S1270D1205U927-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	1077.7	1208.9	1301.2	1361.8	1391.8	1407.8	1414.4
115°	978.5	1104.5	1204.9	1276.7	1320.9	1346.6	1358.6
117.5°	909.8	1018.4	1110.5	1182.3	1228.0	1253.5	1260.8
120°	870.8	972.0	1053.0	1121.2	1165.3	1190.2	1197.5
122.5°	842.8	933.0	1008.8	1069.6	1110.1	1135.0	1141.6
125°	805.4	885.5	951.8	1003.3	1041.1	1061.3	1070.6
127.5°	769.7	844.5	906.5	953.2	986.6	1005.8	1009.8
130°	744.7	816.5	876.3	922.3	952.7	971.1	976.6
132.5°	721.1	786.2	843.9	889.9	920.3	937.2	943.5
135°	684.8	743.8	796.2	836.7	867.1	883.7	889.2
137.5°	652.4	701.4	746.0	782.2	809.8	825.1	831.2
140°	633.3	675.7	714.3	748.4	772.3	786.1	790.7
142.5°	617.1	653.6	687.1	716.0	736.2	749.2	753.1
145°	596.4	625.0	649.8	671.9	687.6	697.8	701.4
147.5°	579.3	601.3	620.0	637.5	650.1	655.9	657.6
150°	569.8	587.2	603.8	617.7	628.7	632.4	633.3
152.5°	560.2	576.2	589.1	600.7	609.5	613.2	614.2
155°	545.8	558.7	568.9	578.1	584.5	587.2	588.2
157.5°	532.2	542.2	550.1	557.2	562.6	565.1	565.0
160°	521.9	531.1	537.6	544.0	548.6	550.5	549.5
162.5°	513.1	520.8	526.5	531.5	535.4	535.8	535.5
165°	499.8	505.3	509.9	513.7	515.5	515.5	515.5
167.5°	487.0	491.2	494.5	496.3	498.0	497.3	497.1
170°	479.6	482.4	484.2	486.0	487.0	487.0	486.0
172.5°	472.9	475.0	476.1	476.4	478.1	476.7	475.7
175°	463.0	464.9	464.9	464.9	465.8	463.9	463.0
177.5°	458.8	458.8	458.8	458.0	458.8	456.5	456.5
180°	456.5	456.5	456.5	456.5	456.5	456.5	456.5

(END OF REPORT)