

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333288-935

Luminaire Tested: **S125DIP-S1090D1205U935-4F0-1E-UDD-A4**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333288-935
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-19,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125DIP-S1090D1205U935-4F0-1E-UDD-A4
Description: DEFINE 5 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1090 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 1205 LUMENS PER FOOT, BATWING OPTIC
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7587.5 lumens
Efficiency: N/A
Efficacy: 116.0 lumens/watt
Spacing Criteria (0/90/45): 1.43 / 1.23 / 1.52
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 65.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

Luminous Intensity Polar Plot





TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	107	107	107	107	99	99	99	99	84	84	84	70	70	70	57	57	57	51
1	98	94	90	87	91	87	84	81	74	72	69	62	60	59	51	50	49	43
2	90	82	76	71	83	76	71	67	65	61	58	55	52	49	45	43	41	37
3	82	73	65	60	75	67	61	56	57	53	49	48	45	42	40	37	35	31
4	75	64	56	50	69	60	53	48	51	46	42	43	39	36	36	33	31	27
5	69	57	49	43	63	53	46	41	46	40	36	39	35	31	32	29	27	23
6	63	51	43	38	58	48	41	36	41	36	31	35	31	27	29	26	24	21
7	59	46	39	33	54	43	36	31	37	32	28	32	28	24	27	23	21	18
8	54	42	34	29	50	39	32	28	34	29	25	29	25	22	25	21	19	16
9	51	38	31	26	47	36	29	25	31	26	22	27	23	19	23	19	17	15
10	47	35	28	23	44	33	27	22	29	24	20	25	21	18	21	18	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	8843	8843	8843	8843
5°	10240	8873	7769	8873
10°	11913	8826	6807	8826
15°	13188	8762	6279	8762
20°	14762	8659	5856	8659
25°	17293	8543	5648	8543
30°	18678	8429	5469	8429
35°	15358	8215	5351	8215
40°	10916	7917	5223	7917
45°	8386	7516	5149	7516
50°	7159	7018	5138	7018
55°	6373	6531	5183	6531
60°	5749	5997	5315	5997
65°	5310	5462	5453	5462
70°	4828	4906	5531	4906
75°	4262	4319	5480	4319
80°	3585	3522	5013	3522
85°	2838	2542	4046	2542



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.8	1.7
10°-20°	392.4	5.2
20°-30°	637.2	8.4
30°-40°	777.3	10.2
40°-50°	707.1	9.3
50°-60°	563.2	7.4
60°-70°	392.3	5.2
70°-80°	209.2	2.8
80°-90°	55.6	0.7
90°-100°	359.7	4.7
100°-110°	773.2	10.2
110°-120°	725.6	9.6
120°-130°	588.1	7.8
130°-140°	471.9	6.2
140°-150°	356.1	4.7
150°-160°	250.7	3.3
160°-170°	147.8	1.9
170°-180°	48.1	0.6
0°-30°	1161.5	15.3
0°-40°	1938.8	25.6
0°-60°	3209.2	42.3
0°-90°	3866.2	51.0
90°-120°	1858.5	24.5
90°-150°	3274.7	43.2
90°-180°	3721.0	49.0
0°-180°	7587.5	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1369	1369	1369	1369	1369	
5°	1580	1369	1198	1369	1580	159
15°	1972	1310	939	1310	1972	565
25°	2427	1199	793	1199	2427	1108
35°	1948	1042	679	1042	1948	1192
45°	918	823	564	823	918	735
55°	566	580	460	580	566	510
65°	348	357	357	357	348	345
75°	171	173	220	173	171	184
85°	38	34	55	34	38	45
90°	23	1	23	1	23	17
95°	235	33	235	33	235	333
105°	1326	113	1326	113	1326	1318
115°	1477	202	1477	202	1477	1443
125°	1164	280	1164	280	1164	1053
135°	966	328	966	328	966	749
145°	762	382	762	382	762	484
155°	639	436	639	436	639	298
165°	560	476	560	476	560	160
175°	503	495	503	495	503	49
180°	496	496	496	496	496	



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1448.2	1446.3	1444.5	1440.7	1443.6	1435.6	1431.9	1425.4	1417.5	1414.7	1411.4
5°	1579.5	1582.4	1585.4	1573.1	1574.3	1566.2	1547.6	1532.4	1520.3	1504.5	1493.5
7.5°	1737.6	1730.7	1730.2	1722.3	1708.7	1697.7	1678.2	1653.3	1629.3	1601.8	1579.2
10°	1816.6	1817.2	1812.0	1802.7	1788.1	1777.7	1752.1	1727.7	1698.1	1663.2	1638.2
12.5°	1876.1	1878.5	1872.0	1859.4	1852.3	1828.9	1808.9	1779.8	1744.6	1716.7	1678.7
15°	1972.4	1966.0	1961.4	1945.6	1933.5	1909.0	1877.1	1846.8	1808.4	1773.1	1737.6
17.5°	2065.1	2070.2	2061.5	2047.2	2009.3	1980.8	1937.9	1896.6	1848.8	1801.3	1758.9
20°	2147.9	2152.5	2139.2	2114.2	2068.8	2040.4	1984.0	1930.5	1875.3	1814.3	1767.8
22.5°	2251.1	2247.4	2229.3	2191.3	2152.1	2099.4	2038.4	1973.3	1904.1	1835.2	1773.4
25°	2426.8	2402.4	2391.3	2344.3	2292.6	2215.3	2131.6	2036.3	1950.3	1859.1	1780.0
27.5°	2524.2	2516.5	2504.2	2471.4	2417.1	2334.4	2235.8	2119.6	1998.3	1883.1	1779.7
30°	2504.6	2505.9	2507.0	2496.6	2461.7	2399.5	2301.3	2176.3	2032.2	1902.6	1782.9
32.5°	2331.8	2352.9	2373.1	2397.0	2406.8	2394.9	2333.4	2220.5	2072.2	1924.9	1781.1
35°	1947.9	1954.4	2020.0	2085.1	2173.4	2242.0	2287.9	2237.9	2113.0	1943.9	1778.8
37.5°	1518.9	1550.2	1595.7	1669.2	1796.7	1910.9	2057.7	2125.2	2084.9	1950.1	1774.8
40°	1294.8	1323.8	1353.5	1428.4	1535.9	1674.2	1841.0	1983.4	2016.5	1930.5	1760.8
42.5°	1121.8	1144.9	1177.8	1234.1	1324.0	1446.5	1605.8	1791.8	1906.3	1873.8	1731.6
45°	918.2	932.7	958.3	1003.1	1068.2	1164.0	1304.7	1508.0	1685.3	1744.0	1662.1
47.5°	785.9	785.8	805.7	836.6	883.6	965.0	1069.0	1228.4	1417.7	1557.8	1551.3
50°	712.5	709.6	725.2	752.0	789.2	843.3	942.6	1069.9	1251.7	1410.4	1454.6
52.5°	649.3	649.6	659.3	679.0	710.2	756.3	830.5	945.3	1100.7	1263.5	1346.7
55°	566.0	563.7	574.7	588.1	610.8	641.0	694.5	782.2	908.3	1068.7	1176.8
57.5°	489.7	496.2	500.6	509.9	528.7	549.0	594.0	658.4	758.5	896.1	1010.4
60°	445.1	451.5	455.0	464.3	479.4	496.9	531.8	584.0	668.3	786.9	900.2
62.5°	405.2	410.2	411.3	419.7	432.0	449.0	476.4	520.4	586.9	690.6	801.6
65°	347.5	347.5	349.8	358.5	364.4	379.4	400.4	432.4	485.9	566.6	661.3
67.5°	292.0	294.7	294.2	298.0	303.3	315.1	330.1	356.5	396.1	455.0	530.8
70°	255.7	258.0	257.4	260.4	266.1	273.7	285.9	310.9	339.4	389.9	455.0
72.5°	223.2	224.1	222.6	226.4	229.9	236.5	250.1	263.5	290.1	332.8	386.2
75°	170.8	172.0	173.1	175.5	179.0	182.4	189.4	202.9	220.2	252.2	286.5
77.5°	128.1	125.9	128.6	128.3	130.3	132.9	139.1	146.2	160.5	180.7	207.2
80°	96.4	97.0	97.0	97.6	100.6	102.3	107.5	112.7	123.8	138.9	157.5
82.5°	70.4	72.0	71.0	72.1	74.5	75.8	78.7	83.0	89.4	101.3	114.7
85°	38.3	35.5	36.6	37.8	37.8	38.3	40.6	42.4	45.9	50.5	55.8
87.5°	15.8	16.7	17.0	17.0	17.4	17.0	18.7	18.5	19.6	20.8	22.3
90°	23.0	23.0	22.0	22.0	22.0	20.0	19.0	18.0	17.0	16.0	14.0
92.5°	63.8	65.4	66.8	69.2	82.1	96.9	128.6	177.3	261.1	322.5	327.8
95°	235.1	251.2	259.1	289.1	360.2	444.2	567.2	719.3	867.4	886.4	723.3
97.5°	568.3	581.1	610.1	666.1	727.9	844.8	964.7	1071.3	1097.5	946.6	645.9
100°	780.3	796.3	833.4	905.4	974.4	1078.5	1181.6	1230.5	1153.5	903.4	576.3
102.5°	1017.3	1029.2	1069.4	1120.7	1194.6	1265.0	1314.4	1284.2	1119.9	827.3	523.4
105°	1325.6	1337.6	1357.6	1390.6	1422.6	1433.7	1389.7	1252.6	1012.4	725.3	472.2
107.5°	1489.3	1497.3	1503.9	1504.1	1487.9	1435.6	1322.6	1139.7	902.8	655.0	450.6
110°	1543.7	1543.7	1536.7	1517.7	1472.7	1387.6	1246.6	1056.4	840.3	622.2	444.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	1537.3	1530.1	1512.7	1480.1	1414.2	1314.0	1171.3	990.8	793.9	603.0	444.2
115°	1476.6	1463.6	1435.6	1387.6	1309.6	1200.5	1063.5	908.4	743.3	582.3	447.2
117.5°	1370.4	1362.4	1334.6	1285.0	1206.9	1106.9	988.9	855.1	713.1	572.0	453.8
120°	1301.6	1293.6	1266.5	1218.6	1144.5	1056.4	946.4	826.4	696.3	567.2	460.2
122.5°	1240.8	1233.6	1206.5	1162.5	1096.5	1014.1	916.0	804.8	681.9	563.3	465.8
125°	1163.6	1153.5	1131.5	1090.5	1034.5	962.4	875.4	773.4	662.3	558.3	475.2
127.5°	1097.5	1093.1	1072.3	1036.0	985.2	917.8	836.5	741.3	644.3	555.9	485.8
130°	1061.4	1055.5	1035.4	1002.5	952.4	887.4	809.3	721.3	632.3	554.2	492.2
132.5°	1025.5	1018.6	1000.2	967.2	917.2	854.5	783.8	701.3	622.7	554.2	499.4
135°	966.5	960.4	942.5	909.4	865.4	808.4	744.3	675.3	611.3	554.2	509.2
137.5°	903.4	896.8	880.2	850.2	810.8	762.3	709.1	653.3	601.1	555.4	518.2
140°	859.4	854.4	839.4	813.4	776.4	734.3	688.3	641.3	596.2	556.2	522.2
142.5°	818.6	814.3	800.1	778.2	746.7	710.3	670.7	630.9	592.3	557.1	524.6
145°	762.3	758.4	747.3	730.3	706.3	679.3	648.2	617.3	586.3	556.2	527.3
147.5°	714.7	712.9	706.5	692.9	673.9	653.5	629.6	604.5	580.1	553.6	528.2
150°	688.3	687.3	683.3	671.3	656.3	638.3	619.3	597.3	575.2	551.2	528.2
152.5°	667.5	666.5	662.5	652.9	640.3	626.3	608.9	589.3	569.6	548.0	527.4
155°	639.3	638.3	635.2	628.3	618.3	607.3	593.2	577.2	560.3	542.3	525.2
157.5°	614.1	614.2	611.5	605.6	597.9	589.3	578.4	565.2	551.5	536.2	522.6
160°	597.3	598.3	596.2	591.2	584.3	577.2	567.2	557.2	544.2	532.3	520.2
162.5°	582.0	582.3	581.9	577.6	572.2	566.0	557.7	548.5	537.9	527.4	517.8
165°	560.3	560.3	560.3	558.3	554.2	549.2	543.2	536.2	528.2	520.2	514.2
167.5°	540.3	540.4	541.2	539.4	537.4	533.8	529.3	524.6	518.8	513.2	508.6
170°	528.2	529.3	529.3	528.2	526.2	524.3	521.2	518.2	513.2	509.2	506.3
172.5°	517.0	518.1	519.6	517.8	517.5	516.3	514.0	511.0	507.6	504.5	503.0
175°	503.3	504.2	506.3	505.2	505.2	505.2	503.3	503.3	500.2	499.2	499.2
177.5°	496.2	496.2	498.6	497.8	498.6	498.6	498.6	497.8	497.1	496.2	496.2
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1408.7	1405.4	1401.7	1395.2	1387.2	1383.1	1376.6	1372.4	1364.0	1357.0	1349.6
5°	1480.1	1465.1	1451.1	1433.0	1413.3	1400.5	1385.4	1368.6	1351.2	1333.1	1313.4
7.5°	1554.2	1527.4	1498.4	1467.1	1436.6	1408.4	1381.6	1355.2	1330.6	1300.8	1275.6
10°	1604.0	1570.2	1534.2	1491.8	1450.5	1414.5	1377.9	1345.9	1313.4	1278.5	1247.7
12.5°	1653.6	1608.8	1557.9	1511.3	1461.6	1418.2	1375.1	1334.3	1293.4	1254.8	1218.8
15°	1688.8	1649.2	1602.1	1535.9	1480.1	1420.3	1363.3	1310.4	1261.0	1218.1	1172.8
17.5°	1711.9	1661.0	1610.4	1546.9	1473.8	1406.8	1342.3	1281.8	1226.1	1171.6	1127.8
20°	1716.1	1663.8	1610.9	1548.7	1473.8	1397.1	1332.6	1259.9	1200.1	1143.7	1090.2
22.5°	1714.7	1655.4	1597.8	1533.9	1460.8	1390.1	1312.1	1238.0	1173.1	1117.7	1061.9
25°	1701.6	1638.2	1566.2	1501.7	1429.6	1354.6	1275.6	1198.9	1132.6	1069.3	1014.1
27.5°	1690.7	1608.4	1526.9	1451.6	1382.1	1313.4	1237.7	1159.2	1085.6	1021.5	969.5
30°	1677.1	1587.1	1495.2	1416.8	1345.3	1278.5	1207.0	1130.3	1053.6	990.8	935.0
32.5°	1665.1	1560.1	1463.2	1377.8	1302.1	1237.1	1171.2	1098.2	1022.9	959.2	903.4
35°	1641.7	1520.3	1409.3	1312.8	1232.0	1165.2	1110.0	1042.0	972.8	911.2	857.7
37.5°	1612.1	1467.9	1348.8	1247.7	1159.2	1088.7	1037.3	985.2	918.8	859.4	811.1
40°	1588.8	1430.7	1304.7	1201.2	1109.4	1036.1	988.5	939.1	883.9	828.7	777.6
42.5°	1559.5	1397.3	1260.0	1148.7	1057.7	986.4	936.4	894.5	845.8	794.3	746.8
45°	1505.7	1336.6	1187.8	1068.2	976.3	905.9	854.3	822.9	786.3	737.4	697.3
47.5°	1426.6	1263.7	1109.8	986.3	891.6	826.4	777.9	747.8	722.0	685.7	649.4
50°	1356.3	1209.4	1053.6	931.0	836.3	770.6	725.8	698.5	676.4	648.5	617.8
52.5°	1277.8	1141.0	998.2	877.0	783.3	718.5	674.7	650.7	632.2	612.3	581.9
55°	1153.0	1036.7	904.2	789.2	702.6	639.2	600.9	580.0	564.9	549.7	531.2
57.5°	1015.5	924.5	807.2	702.0	622.2	564.6	528.8	508.5	496.7	489.0	478.0
60°	918.8	840.9	739.8	643.9	566.0	514.9	480.0	464.3	454.4	448.1	439.9
62.5°	829.1	765.1	671.4	583.9	515.8	467.4	436.4	421.1	411.6	408.5	401.8
65°	696.8	647.4	570.1	497.5	439.4	398.0	372.0	357.4	351.5	348.1	348.7
67.5°	566.5	536.4	474.3	412.3	366.0	331.4	310.5	299.3	296.4	291.7	291.6
70°	487.0	464.3	412.0	358.0	316.7	290.0	271.4	259.8	256.8	254.5	254.0
72.5°	416.8	396.9	351.5	308.2	271.1	247.7	232.3	225.3	220.6	219.2	219.1
75°	313.2	302.2	266.1	231.9	206.3	190.0	179.6	173.1	169.7	169.1	169.7
77.5°	222.7	213.0	190.1	165.8	149.7	137.4	128.5	126.3	122.3	122.5	121.9
80°	167.4	161.0	146.5	127.3	113.9	103.4	98.8	94.7	93.6	91.8	93.6
82.5°	121.3	114.5	104.6	92.4	81.4	75.1	70.4	69.1	68.4	67.7	68.0
85°	59.8	60.4	54.6	45.3	40.6	37.2	34.3	34.3	33.7	33.1	33.7
87.5°	23.1	21.7	19.6	17.9	15.2	13.3	12.5	12.7	11.5	11.5	12.4
90°	13.0	11.0	10.0	8.0	6.0	4.0	2.0	1.0	2.0	4.0	6.0
92.5°	228.3	136.6	82.1	52.9	35.6	23.2	14.8	12.2	14.8	23.2	35.6
95°	447.2	227.1	120.0	75.0	53.0	42.0	34.0	33.0	34.0	42.0	53.0
97.5°	357.0	195.7	124.8	92.5	72.7	61.6	56.1	54.8	56.1	61.6	72.7
100°	324.2	194.1	136.0	106.1	87.0	76.0	72.1	70.0	72.1	76.0	87.0
102.5°	310.6	201.3	149.6	120.5	103.1	91.3	88.1	86.9	88.1	91.3	103.1
105°	305.1	216.1	172.1	144.0	128.0	118.0	113.0	113.0	113.0	118.0	128.0
107.5°	314.4	238.1	195.4	170.3	153.7	145.4	140.7	138.6	140.7	145.4	153.7
110°	323.1	254.1	213.1	187.1	172.1	163.1	159.1	157.0	159.1	163.1	172.1



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	334.3	269.3	229.9	204.7	189.7	180.6	177.5	175.5	177.5	180.6	189.7
115°	351.1	293.2	256.1	231.1	216.1	207.1	204.1	202.1	204.1	207.1	216.1
117.5°	370.4	317.5	282.5	258.3	241.3	232.3	229.1	226.1	229.1	232.3	241.3
120°	383.1	335.2	300.1	275.1	258.1	249.1	245.1	242.1	245.1	249.1	258.1
122.5°	397.6	352.0	316.9	292.0	273.3	264.3	261.1	258.9	261.1	264.3	273.3
125°	417.2	374.2	341.1	315.1	296.1	287.1	282.1	280.1	282.1	287.1	296.1
127.5°	435.2	395.5	363.8	337.8	317.5	306.2	299.7	296.7	299.7	306.2	317.5
130°	447.2	409.1	378.2	352.1	331.1	318.1	310.1	307.1	310.1	318.1	331.1
132.5°	457.6	422.0	391.0	365.0	343.2	328.6	318.9	315.1	318.9	328.6	343.2
135°	472.2	439.2	408.2	381.2	360.2	344.1	332.2	328.1	332.2	344.1	360.2
137.5°	483.0	451.4	423.2	395.4	374.8	358.8	347.6	344.6	347.6	358.8	374.8
140°	490.3	460.2	431.2	404.2	385.2	369.2	357.1	354.1	357.1	369.2	385.2
142.5°	494.2	465.8	438.4	413.0	394.8	378.8	367.6	365.3	367.6	378.8	394.8
145°	500.2	475.2	449.2	426.2	408.2	394.2	384.2	382.2	384.2	394.2	408.2
147.5°	503.9	481.2	458.4	438.2	422.6	409.6	401.0	399.8	401.0	409.6	422.6
150°	506.3	485.2	463.2	446.2	432.2	419.2	412.2	410.2	412.2	419.2	432.2
152.5°	507.8	489.2	468.8	453.4	440.2	428.8	422.6	421.4	422.6	428.8	440.2
155°	509.2	493.2	476.2	462.2	452.2	442.2	436.2	436.2	436.2	442.2	452.2
157.5°	510.2	496.6	482.0	471.4	462.6	454.0	449.2	449.4	449.2	454.0	462.6
160°	510.2	498.3	485.2	476.2	468.2	461.2	457.2	458.2	457.2	461.2	468.2
162.5°	509.5	499.8	488.4	481.0	474.6	468.4	464.4	465.4	464.4	468.4	474.6
165°	508.2	500.2	492.2	486.2	482.2	477.3	474.2	476.2	474.2	477.3	482.2
167.5°	505.8	500.2	493.6	489.8	487.0	484.2	482.4	483.5	482.4	484.2	487.0
170°	504.2	500.2	495.2	492.2	490.3	488.2	487.2	488.2	487.2	488.2	490.3
172.5°	502.7	499.4	495.2	493.8	492.6	490.6	489.7	491.5	489.7	490.6	492.6
175°	500.2	498.3	495.2	495.2	495.2	494.2	493.2	495.2	493.2	494.2	495.2
177.5°	497.8	497.1	495.4	495.4	496.2	495.4	495.4	497.1	495.4	495.4	496.2
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1345.4	1340.3	1336.1	1326.8	1321.7	1314.7	1309.2	1315.2	1308.7	1311.5	1307.3
5°	1303.5	1287.2	1275.6	1258.7	1244.2	1230.8	1221.0	1219.2	1214.5	1212.2	1205.2
7.5°	1253.0	1232.7	1212.7	1190.6	1172.0	1153.1	1141.0	1131.0	1124.4	1115.7	1109.7
10°	1223.3	1195.9	1172.8	1146.0	1122.7	1102.4	1086.2	1078.0	1070.5	1059.4	1055.3
12.5°	1186.5	1158.3	1130.0	1101.4	1079.0	1056.4	1042.4	1030.1	1024.8	1012.4	1011.2
15°	1142.5	1100.1	1072.2	1043.1	1012.4	993.8	982.1	968.7	962.9	954.2	947.8
17.5°	1089.9	1052.1	1017.2	987.1	960.7	945.0	930.7	921.4	911.5	905.8	895.3
20°	1051.9	1015.8	980.9	949.0	928.7	910.6	899.0	890.3	879.9	876.9	866.5
22.5°	1019.8	980.0	946.6	919.7	897.5	877.2	864.6	858.7	851.4	842.5	840.4
25°	967.6	926.3	897.9	871.2	851.4	832.8	824.1	816.5	809.5	803.1	800.8
27.5°	922.5	885.6	851.8	827.7	810.5	793.5	785.8	776.6	771.5	766.4	760.1
30°	890.9	853.1	823.5	800.2	781.6	766.5	758.4	752.0	747.3	742.7	739.2
32.5°	858.3	823.4	794.6	771.9	753.3	741.8	734.7	730.1	725.0	719.5	715.1
35°	815.4	777.0	749.1	729.4	714.8	706.1	697.9	693.9	688.0	688.0	683.4
37.5°	766.9	733.7	709.1	691.1	678.0	670.3	661.4	658.7	655.0	652.5	650.8
40°	738.0	707.2	684.0	666.0	652.0	645.7	638.7	634.0	631.7	628.8	627.6
42.5°	708.3	678.9	656.6	640.0	627.8	622.4	615.9	612.6	608.0	604.2	603.5
45°	663.1	634.6	614.2	600.9	590.4	584.0	580.0	573.0	570.7	566.0	565.4
47.5°	620.2	592.9	572.9	562.0	552.8	547.5	541.1	534.2	531.5	529.2	528.9
50°	588.1	563.1	544.5	534.1	525.4	517.8	511.4	506.8	505.0	505.0	506.2
52.5°	555.6	534.3	518.5	505.7	497.5	489.4	483.5	480.7	478.0	480.9	482.9
55°	507.9	486.4	474.8	462.6	454.4	445.1	442.2	441.1	439.4	444.0	446.3
57.5°	457.4	442.4	428.8	416.6	409.3	404.0	400.0	399.3	402.6	404.8	412.3
60°	425.4	407.9	395.7	386.4	377.7	374.3	373.1	372.0	374.3	380.6	390.5
62.5°	390.0	375.9	362.7	355.8	349.4	343.5	343.4	344.1	348.7	356.0	365.8
65°	338.2	326.0	317.3	309.2	303.9	300.4	301.6	303.9	309.2	319.0	330.1
67.5°	285.6	277.2	269.4	262.8	257.8	257.8	259.0	262.4	268.6	280.0	290.1
70°	251.7	242.4	235.9	233.1	228.9	226.6	230.1	235.9	241.2	251.7	260.4
72.5°	217.7	209.8	204.8	202.9	201.0	199.2	200.4	206.6	213.7	224.2	234.3
75°	167.4	164.5	161.0	158.7	156.9	158.1	159.2	165.1	170.8	181.9	193.6
77.5°	122.2	119.2	117.0	116.5	115.5	116.1	119.3	123.6	129.3	137.4	146.2
80°	92.4	91.3	90.1	89.5	89.5	90.1	94.7	97.6	102.9	110.4	117.4
82.5°	67.3	66.6	66.4	66.2	66.7	66.8	69.7	73.4	77.7	83.4	89.5
85°	35.5	34.3	36.0	36.6	35.5	37.2	38.3	40.6	42.4	45.3	48.2
87.5°	13.3	14.6	14.3	15.2	15.3	16.7	16.4	18.5	19.6	20.8	20.7
90°	8.0	10.0	11.0	13.0	14.0	16.0	17.0	18.0	19.0	20.0	22.0
92.5°	52.9	82.1	136.6	228.3	327.8	322.5	261.1	177.3	128.6	96.9	82.1
95°	75.0	120.0	227.1	447.2	723.3	886.4	867.4	719.3	567.2	444.2	360.2
97.5°	92.5	124.8	195.7	357.0	645.9	946.6	1097.5	1071.3	964.7	844.8	727.9
100°	106.1	136.0	194.1	324.2	576.3	903.4	1153.5	1230.5	1181.6	1078.5	974.4
102.5°	120.5	149.6	201.3	310.6	523.4	827.3	1119.9	1284.2	1314.4	1265.0	1194.6
105°	144.0	172.1	216.1	305.1	472.2	725.3	1012.4	1252.6	1389.7	1433.7	1422.6
107.5°	170.3	195.4	238.1	314.4	450.6	655.0	902.8	1139.7	1322.6	1435.6	1487.9
110°	187.1	213.1	254.1	323.1	444.2	622.2	840.3	1056.4	1246.6	1387.6	1472.7



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	204.7	229.9	269.3	334.3	444.2	603.0	793.9	990.8	1171.3	1314.0	1414.2
115°	231.1	256.1	293.2	351.1	447.2	582.3	743.3	908.4	1063.5	1200.5	1309.6
117.5°	258.3	282.5	317.5	370.4	453.8	572.0	713.1	855.1	988.9	1106.9	1206.9
120°	275.1	300.1	335.2	383.1	460.2	567.2	696.3	826.4	946.4	1056.4	1144.5
122.5°	292.0	316.9	352.0	397.6	465.8	563.3	681.9	804.8	916.0	1014.1	1096.5
125°	315.1	341.1	374.2	417.2	475.2	558.3	662.3	773.4	875.4	962.4	1034.5
127.5°	337.8	363.8	395.5	435.2	485.8	555.9	644.3	741.3	836.5	917.8	985.2
130°	352.1	378.2	409.1	447.2	492.2	554.2	632.3	721.3	809.3	887.4	952.4
132.5°	365.0	391.0	422.0	457.6	499.4	554.2	622.7	701.3	783.8	854.5	917.2
135°	381.2	408.2	439.2	472.2	509.2	554.2	611.3	675.3	744.3	808.4	865.4
137.5°	395.4	423.2	451.4	483.0	518.2	555.4	601.1	653.3	709.1	762.3	810.8
140°	404.2	431.2	460.2	490.3	522.2	556.2	596.2	641.3	688.3	734.3	776.4
142.5°	413.0	438.4	465.8	494.2	524.6	557.1	592.3	630.9	670.7	710.3	746.7
145°	426.2	449.2	475.2	500.2	527.3	556.2	586.3	617.3	648.2	679.3	706.3
147.5°	438.2	458.4	481.2	503.9	528.2	553.6	580.1	604.5	629.6	653.5	673.9
150°	446.2	463.2	485.2	506.3	528.2	551.2	575.2	597.3	619.3	638.3	656.3
152.5°	453.4	468.8	489.2	507.8	527.4	548.0	569.6	589.3	608.9	626.3	640.3
155°	462.2	476.2	493.2	509.2	525.2	542.3	560.3	577.2	593.2	607.3	618.3
157.5°	471.4	482.0	496.6	510.2	522.6	536.2	551.5	565.2	578.4	589.3	597.9
160°	476.2	485.2	498.3	510.2	520.2	532.3	544.2	557.2	567.2	577.2	584.3
162.5°	481.0	488.4	499.8	509.5	517.8	527.4	537.9	548.5	557.7	566.0	572.2
165°	486.2	492.2	500.2	508.2	514.2	520.2	528.2	536.2	543.2	549.2	554.2
167.5°	489.8	493.6	500.2	505.8	508.6	513.2	518.8	524.6	529.3	533.8	537.4
170°	492.2	495.2	500.2	504.2	506.3	509.2	513.2	518.2	521.2	524.3	526.2
172.5°	493.8	495.2	499.4	502.7	503.0	504.5	507.6	511.0	514.0	516.3	517.5
175°	495.2	495.2	498.3	500.2	499.2	499.2	500.2	503.3	503.3	505.2	505.2
177.5°	495.4	495.4	497.1	497.8	496.2	496.2	497.1	497.8	498.6	498.6	498.6
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1304.5	1307.8	1305.0	1308.7	1305.0	1307.8	1304.5	1307.3	1311.5	1308.7	1315.2
5°	1202.4	1197.1	1200.6	1198.3	1200.6	1197.1	1202.4	1205.2	1212.2	1214.5	1219.2
7.5°	1108.0	1103.0	1097.3	1094.6	1097.3	1103.0	1108.0	1109.7	1115.7	1124.4	1131.0
10°	1049.0	1042.6	1042.0	1037.9	1042.0	1042.6	1049.0	1055.3	1059.4	1070.5	1078.0
12.5°	1005.7	999.8	993.2	991.4	993.2	999.8	1005.7	1011.2	1012.4	1024.8	1030.1
15°	944.3	939.7	935.6	939.1	935.6	939.7	944.3	947.8	954.2	962.9	968.7
17.5°	893.3	889.5	888.8	884.5	888.8	889.5	893.3	895.3	905.8	911.5	921.4
20°	861.3	858.3	859.5	852.0	859.5	858.3	861.3	866.5	876.9	879.9	890.3
22.5°	835.7	830.0	829.3	827.8	829.3	830.0	835.7	840.4	842.5	851.4	858.7
25°	795.6	792.6	789.8	792.6	789.8	792.6	795.6	800.8	803.1	809.5	816.5
27.5°	760.6	757.1	756.3	756.6	756.3	757.1	760.6	760.1	766.4	771.5	776.6
30°	739.2	733.4	734.0	733.4	734.0	733.4	739.2	739.2	742.7	747.3	752.0
32.5°	715.9	712.0	711.2	710.2	711.2	712.0	715.9	715.1	719.5	725.0	730.1
35°	681.7	681.7	678.7	678.7	678.7	681.7	681.7	683.4	688.0	688.0	693.9
37.5°	649.5	648.8	647.1	647.4	647.1	648.8	649.5	650.8	652.5	655.0	658.7
40°	625.3	624.7	622.9	619.5	622.9	624.7	625.3	627.6	628.8	631.7	634.0
42.5°	602.0	600.1	599.3	598.1	599.3	600.1	602.0	603.5	604.2	608.0	612.6
45°	565.4	565.4	564.3	563.7	564.3	565.4	565.4	565.4	566.0	570.7	573.0
47.5°	529.9	530.9	533.1	532.8	533.1	530.9	529.9	528.9	529.2	531.5	534.2
50°	508.5	509.1	510.8	511.4	510.8	509.1	508.5	506.2	505.0	505.0	506.8
52.5°	484.7	488.2	490.3	490.0	490.3	488.2	484.7	482.9	480.9	478.0	480.7
55°	451.5	455.6	459.7	460.3	459.7	455.6	451.5	446.3	444.0	439.4	441.1
57.5°	418.6	424.3	428.6	430.1	428.6	424.3	418.6	412.3	404.8	402.6	399.3
60°	396.3	403.9	409.1	411.5	409.1	403.9	396.3	390.5	380.6	374.3	372.0
62.5°	375.0	383.4	388.7	389.1	388.7	383.4	375.0	365.8	356.0	348.7	344.1
65°	339.9	348.7	353.4	356.8	353.4	348.7	339.9	330.1	319.0	309.2	303.9
67.5°	302.3	311.0	316.2	318.9	316.2	311.0	302.3	290.1	280.0	268.6	262.4
70°	274.9	283.6	290.6	292.9	290.6	283.6	274.9	260.4	251.7	241.2	235.9
72.5°	247.9	255.7	261.3	264.1	261.3	255.7	247.9	234.3	224.2	213.7	206.6
75°	201.0	211.5	216.8	219.6	216.8	211.5	201.0	193.6	181.9	170.8	165.1
77.5°	155.1	164.5	167.7	169.2	167.7	164.5	155.1	146.2	137.4	129.3	123.6
80°	124.3	130.2	134.2	134.8	134.2	130.2	124.3	117.4	110.4	102.9	97.6
82.5°	95.6	100.4	101.7	103.2	101.7	100.4	95.6	89.5	83.4	77.7	73.4
85°	52.3	54.6	55.2	54.6	55.2	54.6	52.3	48.2	45.3	42.4	40.6
87.5°	21.6	21.2	21.4	22.3	21.4	21.2	21.6	20.7	20.8	19.6	18.5
90°	22.0	22.0	23.0	23.0	23.0	22.0	22.0	22.0	20.0	19.0	18.0
92.5°	69.2	66.8	65.4	63.8	65.4	66.8	69.2	82.1	96.9	128.6	177.3
95°	289.1	259.1	251.2	235.1	251.2	259.1	289.1	360.2	444.2	567.2	719.3
97.5°	666.1	610.1	581.1	568.3	581.1	610.1	666.1	727.9	844.8	964.7	1071.3
100°	905.4	833.4	796.3	780.3	796.3	833.4	905.4	974.4	1078.5	1181.6	1230.5
102.5°	1120.7	1069.4	1029.2	1017.3	1029.2	1069.4	1120.7	1194.6	1265.0	1314.4	1284.2
105°	1390.6	1357.6	1337.6	1325.6	1337.6	1357.6	1390.6	1422.6	1433.7	1389.7	1252.6
107.5°	1504.1	1503.9	1497.3	1489.3	1497.3	1503.9	1504.1	1487.9	1435.6	1322.6	1139.7
110°	1517.7	1536.7	1543.7	1543.7	1543.7	1536.7	1517.7	1472.7	1387.6	1246.6	1056.4



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	1480.1	1512.7	1530.1	1537.3	1530.1	1512.7	1480.1	1414.2	1314.0	1171.3	990.8
115°	1387.6	1435.6	1463.6	1476.6	1463.6	1435.6	1387.6	1309.6	1200.5	1063.5	908.4
117.5°	1285.0	1334.6	1362.4	1370.4	1362.4	1334.6	1285.0	1206.9	1106.9	988.9	855.1
120°	1218.6	1266.5	1293.6	1301.6	1293.6	1266.5	1218.6	1144.5	1056.4	946.4	826.4
122.5°	1162.5	1206.5	1233.6	1240.8	1233.6	1206.5	1162.5	1096.5	1014.1	916.0	804.8
125°	1090.5	1131.5	1153.5	1163.6	1153.5	1131.5	1090.5	1034.5	962.4	875.4	773.4
127.5°	1036.0	1072.3	1093.1	1097.5	1093.1	1072.3	1036.0	985.2	917.8	836.5	741.3
130°	1002.5	1035.4	1055.5	1061.4	1055.5	1035.4	1002.5	952.4	887.4	809.3	721.3
132.5°	967.2	1000.2	1018.6	1025.5	1018.6	1000.2	967.2	917.2	854.5	783.8	701.3
135°	909.4	942.5	960.4	966.5	960.4	942.5	909.4	865.4	808.4	744.3	675.3
137.5°	850.2	880.2	896.8	903.4	896.8	880.2	850.2	810.8	762.3	709.1	653.3
140°	813.4	839.4	854.4	859.4	854.4	839.4	813.4	776.4	734.3	688.3	641.3
142.5°	778.2	800.1	814.3	818.6	814.3	800.1	778.2	746.7	710.3	670.7	630.9
145°	730.3	747.3	758.4	762.3	758.4	747.3	730.3	706.3	679.3	648.2	617.3
147.5°	692.9	706.5	712.9	714.7	712.9	706.5	692.9	673.9	653.5	629.6	604.5
150°	671.3	683.3	687.3	688.3	687.3	683.3	671.3	656.3	638.3	619.3	597.3
152.5°	652.9	662.5	666.5	667.5	666.5	662.5	652.9	640.3	626.3	608.9	589.3
155°	628.3	635.2	638.3	639.3	638.3	635.2	628.3	618.3	607.3	593.2	577.2
157.5°	605.6	611.5	614.2	614.1	614.2	611.5	605.6	597.9	589.3	578.4	565.2
160°	591.2	596.2	598.3	597.3	598.3	596.2	591.2	584.3	577.2	567.2	557.2
162.5°	577.6	581.9	582.3	582.0	582.3	581.9	577.6	572.2	566.0	557.7	548.5
165°	558.3	560.3	560.3	560.3	560.3	560.3	558.3	554.2	549.2	543.2	536.2
167.5°	539.4	541.2	540.4	540.3	540.4	541.2	539.4	537.4	533.8	529.3	524.6
170°	528.2	529.3	529.3	528.2	529.3	529.3	528.2	526.2	524.3	521.2	518.2
172.5°	517.8	519.6	518.1	517.0	518.1	519.6	517.8	517.5	516.3	514.0	511.0
175°	505.2	506.3	504.2	503.3	504.2	506.3	505.2	505.2	505.2	503.3	503.3
177.5°	497.8	498.6	496.2	496.2	496.2	498.6	497.8	498.6	498.6	498.6	497.8
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1309.2	1314.7	1321.7	1326.8	1336.1	1340.3	1345.4	1349.6	1357.0	1364.0	1372.4
5°	1221.0	1230.8	1244.2	1258.7	1275.6	1287.2	1303.5	1313.4	1333.1	1351.2	1368.6
7.5°	1141.0	1153.1	1172.0	1190.6	1212.7	1232.7	1253.0	1275.6	1300.8	1330.6	1355.2
10°	1086.2	1102.4	1122.7	1146.0	1172.8	1195.9	1223.3	1247.7	1278.5	1313.4	1345.9
12.5°	1042.4	1056.4	1079.0	1101.4	1130.0	1158.3	1186.5	1218.8	1254.8	1293.4	1334.3
15°	982.1	993.8	1012.4	1043.1	1072.2	1100.1	1142.5	1172.8	1218.1	1261.0	1310.4
17.5°	930.7	945.0	960.7	987.1	1017.2	1052.1	1089.9	1127.8	1171.6	1226.1	1281.8
20°	899.0	910.6	928.7	949.0	980.9	1015.8	1051.9	1090.2	1143.7	1200.1	1259.9
22.5°	864.6	877.2	897.5	919.7	946.6	980.0	1019.8	1061.9	1117.7	1173.1	1238.0
25°	824.1	832.8	851.4	871.2	897.9	926.3	967.6	1014.1	1069.3	1132.6	1198.9
27.5°	785.8	793.5	810.5	827.7	851.8	885.6	922.5	969.5	1021.5	1085.6	1159.2
30°	758.4	766.5	781.6	800.2	823.5	853.1	890.9	935.0	990.8	1053.6	1130.3
32.5°	734.7	741.8	753.3	771.9	794.6	823.4	858.3	903.4	959.2	1022.9	1098.2
35°	697.9	706.1	714.8	729.4	749.1	777.0	815.4	857.7	911.2	972.8	1042.0
37.5°	661.4	670.3	678.0	691.1	709.1	733.7	766.9	811.1	859.4	918.8	985.2
40°	638.7	645.7	652.0	666.0	684.0	707.2	738.0	777.6	828.7	883.9	939.1
42.5°	615.9	622.4	627.8	640.0	656.6	678.9	708.3	746.8	794.3	845.8	894.5
45°	580.0	584.0	590.4	600.9	614.2	634.6	663.1	697.3	737.4	786.3	822.9
47.5°	541.1	547.5	552.8	562.0	572.9	592.9	620.2	649.4	685.7	722.0	747.8
50°	511.4	517.8	525.4	534.1	544.5	563.1	588.1	617.8	648.5	676.4	698.5
52.5°	483.5	489.4	497.5	505.7	518.5	534.3	555.6	581.9	612.3	632.2	650.7
55°	442.2	445.1	454.4	462.6	474.8	486.4	507.9	531.2	549.7	564.9	580.0
57.5°	400.0	404.0	409.3	416.6	428.8	442.4	457.4	478.0	489.0	496.7	508.5
60°	373.1	374.3	377.7	386.4	395.7	407.9	425.4	439.9	448.1	454.4	464.3
62.5°	343.4	343.5	349.4	355.8	362.7	375.9	390.0	401.8	408.5	411.6	421.1
65°	301.6	300.4	303.9	309.2	317.3	326.0	338.2	348.7	348.1	351.5	357.4
67.5°	259.0	257.8	257.8	262.8	269.4	277.2	285.6	291.6	291.7	296.4	299.3
70°	230.1	226.6	228.9	233.1	235.9	242.4	251.7	254.0	254.5	256.8	259.8
72.5°	200.4	199.2	201.0	202.9	204.8	209.8	217.7	219.1	219.2	220.6	225.3
75°	159.2	158.1	156.9	158.7	161.0	164.5	167.4	169.7	169.1	169.7	173.1
77.5°	119.3	116.1	115.5	116.5	117.0	119.2	122.2	121.9	122.5	122.3	126.3
80°	94.7	90.1	89.5	89.5	90.1	91.3	92.4	93.6	91.8	93.6	94.7
82.5°	69.7	66.8	66.7	66.2	66.4	66.6	67.3	68.0	67.7	68.4	69.1
85°	38.3	37.2	35.5	36.6	36.0	34.3	35.5	33.7	33.1	33.7	34.3
87.5°	16.4	16.7	15.3	15.2	14.3	14.6	13.3	12.4	11.5	11.5	12.7
90°	17.0	16.0	14.0	13.0	11.0	10.0	8.0	6.0	4.0	2.0	1.0
92.5°	261.1	322.5	327.8	228.3	136.6	82.1	52.9	35.6	23.2	14.8	12.2
95°	867.4	886.4	723.3	447.2	227.1	120.0	75.0	53.0	42.0	34.0	33.0
97.5°	1097.5	946.6	645.9	357.0	195.7	124.8	92.5	72.7	61.6	56.1	54.8
100°	1153.5	903.4	576.3	324.2	194.1	136.0	106.1	87.0	76.0	72.1	70.0
102.5°	1119.9	827.3	523.4	310.6	201.3	149.6	120.5	103.1	91.3	88.1	86.9
105°	1012.4	725.3	472.2	305.1	216.1	172.1	144.0	128.0	118.0	113.0	113.0
107.5°	902.8	655.0	450.6	314.4	238.1	195.4	170.3	153.7	145.4	140.7	138.6
110°	840.3	622.2	444.2	323.1	254.1	213.1	187.1	172.1	163.1	159.1	157.0



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	793.9	603.0	444.2	334.3	269.3	229.9	204.7	189.7	180.6	177.5	175.5
115°	743.3	582.3	447.2	351.1	293.2	256.1	231.1	216.1	207.1	204.1	202.1
117.5°	713.1	572.0	453.8	370.4	317.5	282.5	258.3	241.3	232.3	229.1	226.1
120°	696.3	567.2	460.2	383.1	335.2	300.1	275.1	258.1	249.1	245.1	242.1
122.5°	681.9	563.3	465.8	397.6	352.0	316.9	292.0	273.3	264.3	261.1	258.9
125°	662.3	558.3	475.2	417.2	374.2	341.1	315.1	296.1	287.1	282.1	280.1
127.5°	644.3	555.9	485.8	435.2	395.5	363.8	337.8	317.5	306.2	299.7	296.7
130°	632.3	554.2	492.2	447.2	409.1	378.2	352.1	331.1	318.1	310.1	307.1
132.5°	622.7	554.2	499.4	457.6	422.0	391.0	365.0	343.2	328.6	318.9	315.1
135°	611.3	554.2	509.2	472.2	439.2	408.2	381.2	360.2	344.1	332.2	328.1
137.5°	601.1	555.4	518.2	483.0	451.4	423.2	395.4	374.8	358.8	347.6	344.6
140°	596.2	556.2	522.2	490.3	460.2	431.2	404.2	385.2	369.2	357.1	354.1
142.5°	592.3	557.1	524.6	494.2	465.8	438.4	413.0	394.8	378.8	367.6	365.3
145°	586.3	556.2	527.3	500.2	475.2	449.2	426.2	408.2	394.2	384.2	382.2
147.5°	580.1	553.6	528.2	503.9	481.2	458.4	438.2	422.6	409.6	401.0	399.8
150°	575.2	551.2	528.2	506.3	485.2	463.2	446.2	432.2	419.2	412.2	410.2
152.5°	569.6	548.0	527.4	507.8	489.2	468.8	453.4	440.2	428.8	422.6	421.4
155°	560.3	542.3	525.2	509.2	493.2	476.2	462.2	452.2	442.2	436.2	436.2
157.5°	551.5	536.2	522.6	510.2	496.6	482.0	471.4	462.6	454.0	449.2	449.4
160°	544.2	532.3	520.2	510.2	498.3	485.2	476.2	468.2	461.2	457.2	458.2
162.5°	537.9	527.4	517.8	509.5	499.8	488.4	481.0	474.6	468.4	464.4	465.4
165°	528.2	520.2	514.2	508.2	500.2	492.2	486.2	482.2	477.3	474.2	476.2
167.5°	518.8	513.2	508.6	505.8	500.2	493.6	489.8	487.0	484.2	482.4	483.5
170°	513.2	509.2	506.3	504.2	500.2	495.2	492.2	490.3	488.2	487.2	488.2
172.5°	507.6	504.5	503.0	502.7	499.4	495.2	493.8	492.6	490.6	489.7	491.5
175°	500.2	499.2	499.2	500.2	498.3	495.2	495.2	495.2	494.2	493.2	495.2
177.5°	497.1	496.2	496.2	497.8	497.1	495.4	495.4	496.2	495.4	495.4	497.1
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1376.6	1383.1	1387.2	1395.2	1401.7	1405.4	1408.7	1411.4	1414.7	1417.5	1425.4
5°	1385.4	1400.5	1413.3	1433.0	1451.1	1465.1	1480.1	1493.5	1504.5	1520.3	1532.4
7.5°	1381.6	1408.4	1436.6	1467.1	1498.4	1527.4	1554.2	1579.2	1601.8	1629.3	1653.3
10°	1377.9	1414.5	1450.5	1491.8	1534.2	1570.2	1604.0	1638.2	1663.2	1698.1	1727.7
12.5°	1375.1	1418.2	1461.6	1511.3	1557.9	1608.8	1653.6	1678.7	1716.7	1744.6	1779.8
15°	1363.3	1420.3	1480.1	1535.9	1602.1	1649.2	1688.8	1737.6	1773.1	1808.4	1846.8
17.5°	1342.3	1406.8	1473.8	1546.9	1610.4	1661.0	1711.9	1758.9	1801.3	1848.8	1896.6
20°	1332.6	1397.1	1473.8	1548.7	1610.9	1663.8	1716.1	1767.8	1814.3	1875.3	1930.5
22.5°	1312.1	1390.1	1460.8	1533.9	1597.8	1655.4	1714.7	1773.4	1835.2	1904.1	1973.3
25°	1275.6	1354.6	1429.6	1501.7	1566.2	1638.2	1701.6	1780.0	1859.1	1950.3	2036.3
27.5°	1237.7	1313.4	1382.1	1451.6	1526.9	1608.4	1690.7	1779.7	1883.1	1998.3	2119.6
30°	1207.0	1278.5	1345.3	1416.8	1495.2	1587.1	1677.1	1782.9	1902.6	2032.2	2176.3
32.5°	1171.2	1237.1	1302.1	1377.8	1463.2	1560.1	1665.1	1781.1	1924.9	2072.2	2220.5
35°	1110.0	1165.2	1232.0	1312.8	1409.3	1520.3	1641.7	1778.8	1943.9	2113.0	2237.9
37.5°	1037.3	1088.7	1159.2	1247.7	1348.8	1467.9	1612.1	1774.8	1950.1	2084.9	2125.2
40°	988.5	1036.1	1109.4	1201.2	1304.7	1430.7	1588.8	1760.8	1930.5	2016.5	1983.4
42.5°	936.4	986.4	1057.7	1148.7	1260.0	1397.3	1559.5	1731.6	1873.8	1906.3	1791.8
45°	854.3	905.9	976.3	1068.2	1187.8	1336.6	1505.7	1662.1	1744.0	1685.3	1508.0
47.5°	777.9	826.4	891.6	986.3	1109.8	1263.7	1426.6	1551.3	1557.8	1417.7	1228.4
50°	725.8	770.6	836.3	931.0	1053.6	1209.4	1356.3	1454.6	1410.4	1251.7	1069.9
52.5°	674.7	718.5	783.3	877.0	998.2	1141.0	1277.8	1346.7	1263.5	1100.7	945.3
55°	600.9	639.2	702.6	789.2	904.2	1036.7	1153.0	1176.8	1068.7	908.3	782.2
57.5°	528.8	564.6	622.2	702.0	807.2	924.5	1015.5	1010.4	896.1	758.5	658.4
60°	480.0	514.9	566.0	643.9	739.8	840.9	918.8	900.2	786.9	668.3	584.0
62.5°	436.4	467.4	515.8	583.9	671.4	765.1	829.1	801.6	690.6	586.9	520.4
65°	372.0	398.0	439.4	497.5	570.1	647.4	696.8	661.3	566.6	485.9	432.4
67.5°	310.5	331.4	366.0	412.3	474.3	536.4	566.5	530.8	455.0	396.1	356.5
70°	271.4	290.0	316.7	358.0	412.0	464.3	487.0	455.0	389.9	339.4	310.9
72.5°	232.3	247.7	271.1	308.2	351.5	396.9	416.8	386.2	332.8	290.1	263.5
75°	179.6	190.0	206.3	231.9	266.1	302.2	313.2	286.5	252.2	220.2	202.9
77.5°	128.5	137.4	149.7	165.8	190.1	213.0	222.7	207.2	180.7	160.5	146.2
80°	98.8	103.4	113.9	127.3	146.5	161.0	167.4	157.5	138.9	123.8	112.7
82.5°	70.4	75.1	81.4	92.4	104.6	114.5	121.3	114.7	101.3	89.4	83.0
85°	34.3	37.2	40.6	45.3	54.6	60.4	59.8	55.8	50.5	45.9	42.4
87.5°	12.5	13.3	15.2	17.9	19.6	21.7	23.1	22.3	20.8	19.6	18.5
90°	2.0	4.0	6.0	8.0	10.0	11.0	13.0	14.0	16.0	17.0	18.0
92.5°	14.8	23.2	35.6	52.9	82.1	136.6	228.3	327.8	322.5	261.1	177.3
95°	34.0	42.0	53.0	75.0	120.0	227.1	447.2	723.3	886.4	867.4	719.3
97.5°	56.1	61.6	72.7	92.5	124.8	195.7	357.0	645.9	946.6	1097.5	1071.3
100°	72.1	76.0	87.0	106.1	136.0	194.1	324.2	576.3	903.4	1153.5	1230.5
102.5°	88.1	91.3	103.1	120.5	149.6	201.3	310.6	523.4	827.3	1119.9	1284.2
105°	113.0	118.0	128.0	144.0	172.1	216.1	305.1	472.2	725.3	1012.4	1252.6
107.5°	140.7	145.4	153.7	170.3	195.4	238.1	314.4	450.6	655.0	902.8	1139.7
110°	159.1	163.1	172.1	187.1	213.1	254.1	323.1	444.2	622.2	840.3	1056.4



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	177.5	180.6	189.7	204.7	229.9	269.3	334.3	444.2	603.0	793.9	990.8
115°	204.1	207.1	216.1	231.1	256.1	293.2	351.1	447.2	582.3	743.3	908.4
117.5°	229.1	232.3	241.3	258.3	282.5	317.5	370.4	453.8	572.0	713.1	855.1
120°	245.1	249.1	258.1	275.1	300.1	335.2	383.1	460.2	567.2	696.3	826.4
122.5°	261.1	264.3	273.3	292.0	316.9	352.0	397.6	465.8	563.3	681.9	804.8
125°	282.1	287.1	296.1	315.1	341.1	374.2	417.2	475.2	558.3	662.3	773.4
127.5°	299.7	306.2	317.5	337.8	363.8	395.5	435.2	485.8	555.9	644.3	741.3
130°	310.1	318.1	331.1	352.1	378.2	409.1	447.2	492.2	554.2	632.3	721.3
132.5°	318.9	328.6	343.2	365.0	391.0	422.0	457.6	499.4	554.2	622.7	701.3
135°	332.2	344.1	360.2	381.2	408.2	439.2	472.2	509.2	554.2	611.3	675.3
137.5°	347.6	358.8	374.8	395.4	423.2	451.4	483.0	518.2	555.4	601.1	653.3
140°	357.1	369.2	385.2	404.2	431.2	460.2	490.3	522.2	556.2	596.2	641.3
142.5°	367.6	378.8	394.8	413.0	438.4	465.8	494.2	524.6	557.1	592.3	630.9
145°	384.2	394.2	408.2	426.2	449.2	475.2	500.2	527.3	556.2	586.3	617.3
147.5°	401.0	409.6	422.6	438.2	458.4	481.2	503.9	528.2	553.6	580.1	604.5
150°	412.2	419.2	432.2	446.2	463.2	485.2	506.3	528.2	551.2	575.2	597.3
152.5°	422.6	428.8	440.2	453.4	468.8	489.2	507.8	527.4	548.0	569.6	589.3
155°	436.2	442.2	452.2	462.2	476.2	493.2	509.2	525.2	542.3	560.3	577.2
157.5°	449.2	454.0	462.6	471.4	482.0	496.6	510.2	522.6	536.2	551.5	565.2
160°	457.2	461.2	468.2	476.2	485.2	498.3	510.2	520.2	532.3	544.2	557.2
162.5°	464.4	468.4	474.6	481.0	488.4	499.8	509.5	517.8	527.4	537.9	548.5
165°	474.2	477.3	482.2	486.2	492.2	500.2	508.2	514.2	520.2	528.2	536.2
167.5°	482.4	484.2	487.0	489.8	493.6	500.2	505.8	508.6	513.2	518.8	524.6
170°	487.2	488.2	490.3	492.2	495.2	500.2	504.2	506.3	509.2	513.2	518.2
172.5°	489.7	490.6	492.6	493.8	495.2	499.4	502.7	503.0	504.5	507.6	511.0
175°	493.2	494.2	495.2	495.2	495.2	498.3	500.2	499.2	499.2	500.2	503.3
177.5°	495.4	495.4	496.2	495.4	495.4	497.1	497.8	496.2	496.2	497.1	497.8
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2	496.2



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2	1369.2
2.5°	1431.9	1435.6	1443.6	1440.7	1444.5	1446.3	1448.2
5°	1547.6	1566.2	1574.3	1573.1	1585.4	1582.4	1579.5
7.5°	1678.2	1697.7	1708.7	1722.3	1730.2	1730.7	1737.6
10°	1752.1	1777.7	1788.1	1802.7	1812.0	1817.2	1816.6
12.5°	1808.9	1828.9	1852.3	1859.4	1872.0	1878.5	1876.1
15°	1877.1	1909.0	1933.5	1945.6	1961.4	1966.0	1972.4
17.5°	1937.9	1980.8	2009.3	2047.2	2061.5	2070.2	2065.1
20°	1984.0	2040.4	2068.8	2114.2	2139.2	2152.5	2147.9
22.5°	2038.4	2099.4	2152.1	2191.3	2229.3	2247.4	2251.1
25°	2131.6	2215.3	2292.6	2344.3	2391.3	2402.4	2426.8
27.5°	2235.8	2334.4	2417.1	2471.4	2504.2	2516.5	2524.2
30°	2301.3	2399.5	2461.7	2496.6	2507.0	2505.9	2504.6
32.5°	2333.4	2394.9	2406.8	2397.0	2373.1	2352.9	2331.8
35°	2287.9	2242.0	2173.4	2085.1	2020.0	1954.4	1947.9
37.5°	2057.7	1910.9	1796.7	1669.2	1595.7	1550.2	1518.9
40°	1841.0	1674.2	1535.9	1428.4	1353.5	1323.8	1294.8
42.5°	1605.8	1446.5	1324.0	1234.1	1177.8	1144.9	1121.8
45°	1304.7	1164.0	1068.2	1003.1	958.3	932.7	918.2
47.5°	1069.0	965.0	883.6	836.6	805.7	785.8	785.9
50°	942.6	843.3	789.2	752.0	725.2	709.6	712.5
52.5°	830.5	756.3	710.2	679.0	659.3	649.6	649.3
55°	694.5	641.0	610.8	588.1	574.7	563.7	566.0
57.5°	594.0	549.0	528.7	509.9	500.6	496.2	489.7
60°	531.8	496.9	479.4	464.3	455.0	451.5	445.1
62.5°	476.4	449.0	432.0	419.7	411.3	410.2	405.2
65°	400.4	379.4	364.4	358.5	349.8	347.5	347.5
67.5°	330.1	315.1	303.3	298.0	294.2	294.7	292.0
70°	285.9	273.7	266.1	260.4	257.4	258.0	255.7
72.5°	250.1	236.5	229.9	226.4	222.6	224.1	223.2
75°	189.4	182.4	179.0	175.5	173.1	172.0	170.8
77.5°	139.1	132.9	130.3	128.3	128.6	125.9	128.1
80°	107.5	102.3	100.6	97.6	97.0	97.0	96.4
82.5°	78.7	75.8	74.5	72.1	71.0	72.0	70.4
85°	40.6	38.3	37.8	37.8	36.6	35.5	38.3
87.5°	18.7	17.0	17.4	17.0	17.0	16.7	15.8
90°	19.0	20.0	22.0	22.0	22.0	23.0	23.0
92.5°	128.6	96.9	82.1	69.2	66.8	65.4	63.8
95°	567.2	444.2	360.2	289.1	259.1	251.2	235.1
97.5°	964.7	844.8	727.9	666.1	610.1	581.1	568.3
100°	1181.6	1078.5	974.4	905.4	833.4	796.3	780.3
102.5°	1314.4	1265.0	1194.6	1120.7	1069.4	1029.2	1017.3
105°	1389.7	1433.7	1422.6	1390.6	1357.6	1337.6	1325.6
107.5°	1322.6	1435.6	1487.9	1504.1	1503.9	1497.3	1489.3
110°	1246.6	1387.6	1472.7	1517.7	1536.7	1543.7	1543.7



TEST NUMBER: P333288-935

CATALOG NUMBER: S125DIP-S1090D1205U935-4F0-1E-UDD-A4

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	1171.3	1314.0	1414.2	1480.1	1512.7	1530.1	1537.3
115°	1063.5	1200.5	1309.6	1387.6	1435.6	1463.6	1476.6
117.5°	988.9	1106.9	1206.9	1285.0	1334.6	1362.4	1370.4
120°	946.4	1056.4	1144.5	1218.6	1266.5	1293.6	1301.6
122.5°	916.0	1014.1	1096.5	1162.5	1206.5	1233.6	1240.8
125°	875.4	962.4	1034.5	1090.5	1131.5	1153.5	1163.6
127.5°	836.5	917.8	985.2	1036.0	1072.3	1093.1	1097.5
130°	809.3	887.4	952.4	1002.5	1035.4	1055.5	1061.4
132.5°	783.8	854.5	917.2	967.2	1000.2	1018.6	1025.5
135°	744.3	808.4	865.4	909.4	942.5	960.4	966.5
137.5°	709.1	762.3	810.8	850.2	880.2	896.8	903.4
140°	688.3	734.3	776.4	813.4	839.4	854.4	859.4
142.5°	670.7	710.3	746.7	778.2	800.1	814.3	818.6
145°	648.2	679.3	706.3	730.3	747.3	758.4	762.3
147.5°	629.6	653.5	673.9	692.9	706.5	712.9	714.7
150°	619.3	638.3	656.3	671.3	683.3	687.3	688.3
152.5°	608.9	626.3	640.3	652.9	662.5	666.5	667.5
155°	593.2	607.3	618.3	628.3	635.2	638.3	639.3
157.5°	578.4	589.3	597.9	605.6	611.5	614.2	614.1
160°	567.2	577.2	584.3	591.2	596.2	598.3	597.3
162.5°	557.7	566.0	572.2	577.6	581.9	582.3	582.0
165°	543.2	549.2	554.2	558.3	560.3	560.3	560.3
167.5°	529.3	533.8	537.4	539.4	541.2	540.4	540.3
170°	521.2	524.3	526.2	528.2	529.3	529.3	528.2
172.5°	514.0	516.3	517.5	517.8	519.6	518.1	517.0
175°	503.3	505.2	505.2	505.2	506.3	504.2	503.3
177.5°	498.6	498.6	498.6	497.8	498.6	496.2	496.2
180°	496.2	496.2	496.2	496.2	496.2	496.2	496.2

(END OF REPORT)