

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333287-840

Luminaire Tested: **S125DIP-S1090D1205U840-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333287-840
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-11,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125DIP-S1090D1205U840-4F0-1E-UDD-A1
Description: DEFINE 5 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1090 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 1205 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8742.6 lumens
Efficiency: N/A
Efficacy: 133.7 lumens/watt
Spacing Criteria (0/90/45): 1.43 / 1.23 / 1.52
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 65.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

Luminous Intensity Polar Plot



48% Up

52% Dn



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	108	108	108	108	99	99	99	99	84	84	84	71	71	71	58	58	58	52
1	98	94	90	87	91	87	84	81	74	72	70	62	61	59	51	50	49	44
2	90	83	76	71	83	77	71	67	65	61	58	55	52	50	46	44	42	37
3	82	73	65	60	76	68	61	56	58	53	49	49	45	42	41	38	36	32
4	75	64	57	51	69	60	53	48	51	46	42	44	40	36	36	33	31	27
5	69	57	49	43	64	54	46	41	46	41	36	39	35	32	33	30	27	24
6	64	52	44	38	59	48	41	36	42	36	32	35	31	28	30	26	24	21
7	59	47	39	33	54	44	36	31	38	32	28	32	28	25	27	24	21	19
8	55	42	35	29	50	40	33	28	34	29	25	30	25	22	25	22	19	17
9	51	39	31	26	47	36	29	25	32	26	22	27	23	20	23	20	17	15
10	47	35	28	23	44	33	27	22	29	24	20	25	21	18	21	18	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	10371	10371	10371	10371
5°	12010	10407	9111	10407
10°	13973	10352	7984	10352
15°	15468	10277	7365	10277
20°	17314	10156	6868	10156
25°	20283	10020	6625	10020
30°	21908	9887	6415	9887
35°	18013	9635	6277	9635
40°	12803	9286	6126	9286
45°	9836	8815	6039	8815
50°	8397	8232	6027	8232
55°	7475	7659	6079	7659
60°	6744	7034	6234	7034
65°	6229	6406	6395	6406
70°	5663	5754	6488	5754
75°	5001	5068	6428	5068
80°	4206	4132	5880	4132
85°	3327	2979	4742	2979



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.6	1.8
10°-20°	460.3	5.3
20°-30°	747.4	8.5
30°-40°	911.7	10.4
40°-50°	829.4	9.5
50°-60°	660.6	7.6
60°-70°	460.1	5.3
70°-80°	245.4	2.8
80°-90°	65.2	0.7
90°-100°	101.0	1.2
100°-110°	298.2	3.4
110°-120°	505.2	5.8
120°-130°	664.8	7.6
130°-140°	745.0	8.5
140°-150°	730.1	8.4
150°-160°	613.2	7.0
160°-170°	407.6	4.7
170°-180°	142.7	1.6
0°-30°	1362.3	15.6
0°-40°	2274.0	26.0
0°-60°	3764.0	43.1
0°-90°	4534.8	51.9
90°-120°	904.4	10.3
90°-150°	3044.3	34.8
90°-180°	4208.0	48.1
0°-180°	8742.6	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1606	1606	1606	1606	1606	
5°	1853	1605	1405	1605	1853	187
15°	2313	1537	1102	1537	2313	662
25°	2846	1406	930	1406	2846	1300
35°	2285	1222	796	1222	2285	1398
45°	1077	965	661	965	1077	862
55°	664	680	540	680	664	598
65°	408	419	418	419	408	405
75°	200	203	258	203	200	216
85°	45	40	64	40	45	53
90°	28	1	28	1	28	18
95°	101	76	101	76	101	103
105°	291	268	291	268	291	308
115°	510	506	510	506	510	505
125°	743	738	743	738	743	663
135°	963	960	963	960	963	743
145°	1168	1163	1168	1163	1168	729
155°	1331	1331	1331	1331	1331	612
165°	1443	1447	1443	1447	1443	407
175°	1498	1504	1498	1504	1498	142
180°	1508	1508	1508	1508	1508	



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1698.6	1696.4	1694.3	1689.8	1693.1	1683.8	1679.5	1671.8	1662.5	1659.3	1655.5
5°	1852.6	1856.0	1859.5	1845.1	1846.4	1836.9	1815.1	1797.4	1783.1	1764.6	1751.7
7.5°	2038.0	2029.9	2029.3	2020.0	2004.1	1991.3	1968.3	1939.1	1911.0	1878.8	1852.2
10°	2130.7	2131.4	2125.3	2114.4	2097.3	2085.1	2055.1	2026.4	1991.7	1950.8	1921.5
12.5°	2200.5	2203.3	2195.6	2180.9	2172.5	2145.1	2121.6	2087.5	2046.2	2013.5	1968.9
15°	2313.4	2305.9	2300.5	2282.0	2267.8	2239.1	2201.6	2166.2	2121.1	2079.6	2038.0
17.5°	2422.2	2428.1	2417.9	2401.2	2356.7	2323.3	2273.0	2224.5	2168.5	2112.7	2063.1
20°	2519.2	2524.7	2509.0	2479.7	2426.5	2393.2	2327.0	2264.3	2199.6	2128.0	2073.5
22.5°	2640.3	2635.9	2614.7	2570.2	2524.2	2462.4	2390.9	2314.5	2233.3	2152.5	2080.0
25°	2846.4	2817.7	2804.8	2749.7	2689.0	2598.3	2500.1	2388.3	2287.4	2180.5	2087.8
27.5°	2960.6	2951.6	2937.2	2898.7	2835.0	2738.0	2622.3	2486.1	2343.8	2208.7	2087.4
30°	2937.7	2939.1	2940.4	2928.2	2887.3	2814.4	2699.2	2552.6	2383.6	2231.6	2091.1
32.5°	2734.9	2759.7	2783.4	2811.5	2823.0	2808.9	2736.8	2604.4	2430.4	2257.8	2089.0
35°	2284.7	2292.3	2369.2	2445.6	2549.2	2629.7	2683.5	2624.8	2478.3	2280.0	2086.4
37.5°	1781.5	1818.3	1871.6	1957.8	2107.4	2241.3	2413.5	2492.6	2445.4	2287.2	2081.6
40°	1518.6	1552.7	1587.5	1675.4	1801.5	1963.7	2159.3	2326.3	2365.2	2264.3	2065.3
42.5°	1315.8	1342.8	1381.4	1447.4	1552.9	1696.6	1883.4	2101.6	2235.9	2197.8	2030.9
45°	1076.9	1094.0	1124.0	1176.5	1252.8	1365.2	1530.2	1768.8	1976.7	2045.5	1949.4
47.5°	921.8	921.7	945.0	981.3	1036.3	1131.9	1253.8	1440.8	1662.8	1827.1	1819.5
50°	835.7	832.2	850.6	882.0	925.6	989.1	1105.6	1254.9	1468.1	1654.3	1706.1
52.5°	761.5	761.9	773.3	796.4	832.9	887.1	974.1	1108.7	1291.0	1482.0	1579.5
55°	663.9	661.2	674.1	689.8	716.4	751.8	814.6	917.5	1065.3	1253.4	1380.3
57.5°	574.4	582.0	587.1	598.0	620.2	643.9	696.7	772.2	889.6	1051.1	1185.1
60°	522.1	529.6	533.7	544.6	562.3	582.8	623.7	685.0	783.9	922.9	1055.8
62.5°	475.2	481.1	482.4	492.2	506.8	526.6	558.8	610.4	688.4	810.0	940.2
65°	407.6	407.6	410.3	420.5	427.4	445.0	469.6	507.2	569.9	664.6	775.7
67.5°	342.4	345.7	345.1	349.5	355.8	369.6	387.2	418.1	464.5	533.7	622.6
70°	299.9	302.7	301.9	305.4	312.1	321.0	335.4	364.7	398.1	457.4	533.7
72.5°	261.8	262.9	261.1	265.6	269.6	277.4	293.4	309.0	340.2	390.3	453.0
75°	200.4	201.8	203.1	205.8	210.0	214.0	222.2	237.9	258.3	295.8	336.1
77.5°	150.3	147.6	150.9	150.5	152.8	155.9	163.2	171.5	188.2	212.0	243.1
80°	113.1	113.8	113.8	114.5	118.0	120.0	126.1	132.2	145.2	162.9	184.7
82.5°	82.6	84.4	83.3	84.5	87.4	88.9	92.3	97.4	104.8	118.8	134.5
85°	44.9	41.6	42.9	44.3	44.3	44.9	47.7	49.8	53.8	59.3	65.4
87.5°	18.7	19.7	20.0	19.9	20.3	20.1	22.0	21.7	23.1	24.4	26.3
90°	28.2	27.4	26.6	25.9	25.0	24.0	22.7	21.4	20.1	18.8	17.0
92.5°	55.3	54.8	54.2	53.6	53.1	51.9	50.2	48.5	46.8	45.0	42.8
95°	100.9	100.4	99.9	99.4	98.9	97.7	95.8	94.0	92.2	90.4	87.8
97.5°	153.0	152.7	152.4	152.1	151.8	150.8	149.1	147.3	145.6	143.9	140.3
100°	192.5	192.0	191.4	190.9	190.4	188.9	186.6	184.2	181.9	179.6	176.1
102.5°	231.9	231.2	230.5	229.7	228.9	227.3	224.8	222.2	219.6	217.1	215.4
105°	291.0	290.2	289.4	288.7	287.9	286.7	285.2	283.6	282.1	280.4	278.9
107.5°	351.5	351.6	351.7	351.7	351.8	351.4	350.6	349.8	349.1	348.3	347.1
110°	396.7	396.9	397.2	397.4	397.7	397.4	396.7	395.9	395.1	394.3	393.5



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	440.8	441.2	441.7	442.2	442.6	442.7	442.3	442.0	441.6	441.2	440.2
115°	510.5	510.7	511.0	511.3	511.5	511.8	512.0	512.3	512.6	512.8	512.3
117.5°	578.6	579.6	580.7	581.7	582.7	583.1	582.9	582.7	582.5	582.3	581.8
120°	625.5	626.5	627.5	628.6	629.7	630.2	630.2	630.2	630.2	630.2	630.0
122.5°	672.5	673.3	674.1	674.9	675.8	676.3	676.5	676.7	676.9	677.1	676.4
125°	742.9	743.1	743.4	743.7	743.9	744.3	744.8	745.3	745.8	746.4	746.1
127.5°	810.4	810.9	811.4	812.0	812.5	812.9	813.1	813.4	813.6	814.0	813.6
130°	855.5	856.0	856.6	857.1	857.6	858.0	858.2	858.5	858.8	859.0	858.5
132.5°	897.8	898.5	899.2	899.9	900.7	901.1	901.4	901.7	901.9	902.2	902.3
135°	963.4	964.5	965.5	966.5	967.7	968.2	968.2	968.2	968.2	968.2	967.9
137.5°	1027.7	1029.1	1030.4	1031.7	1033.0	1033.5	1033.2	1032.9	1032.5	1032.2	1031.7
140°	1069.0	1070.4	1071.7	1073.0	1074.3	1074.7	1074.2	1073.6	1073.1	1072.6	1071.8
142.5°	1108.5	1109.8	1111.2	1112.4	1113.7	1114.2	1113.9	1113.6	1113.3	1113.0	1112.0
145°	1167.6	1168.4	1169.2	1170.0	1170.7	1171.1	1171.1	1171.1	1171.1	1171.1	1170.3
147.5°	1218.1	1219.9	1221.6	1223.5	1225.2	1225.8	1225.2	1224.6	1223.9	1223.2	1222.6
150°	1255.7	1256.2	1256.7	1257.2	1257.8	1258.0	1258.0	1258.0	1258.0	1258.0	1257.0
152.5°	1286.7	1287.6	1288.5	1289.5	1290.4	1290.5	1289.9	1289.3	1288.7	1288.1	1287.7
155°	1330.8	1332.1	1333.3	1334.6	1336.0	1336.2	1335.0	1334.0	1333.0	1331.9	1331.7
157.5°	1367.7	1369.4	1371.1	1372.8	1374.5	1374.8	1373.8	1372.7	1371.7	1370.7	1370.4
160°	1393.0	1394.2	1395.5	1396.8	1398.2	1398.3	1397.2	1396.2	1395.1	1394.1	1393.9
162.5°	1414.5	1416.0	1417.5	1419.1	1420.6	1420.8	1419.5	1418.3	1416.9	1415.7	1415.6
165°	1443.4	1445.0	1446.5	1448.1	1449.7	1450.0	1448.9	1447.8	1446.8	1445.7	1445.5
167.5°	1466.4	1468.0	1469.7	1471.3	1472.9	1472.9	1471.4	1469.8	1468.2	1466.6	1466.6
170°	1478.6	1480.5	1482.3	1484.1	1485.9	1486.0	1484.5	1482.9	1481.4	1479.8	1479.8
172.5°	1488.9	1490.6	1492.2	1493.8	1495.4	1495.4	1493.9	1492.3	1490.8	1489.1	1489.1
175°	1498.5	1500.4	1502.3	1504.1	1505.9	1506.0	1504.4	1502.9	1501.3	1499.8	1499.8
177.5°	1504.2	1505.7	1507.1	1508.6	1510.1	1510.2	1508.9	1507.6	1506.4	1505.1	1505.3
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1652.2	1648.4	1644.1	1636.4	1627.1	1622.2	1614.6	1609.7	1599.8	1591.6	1583.0
5°	1736.1	1718.4	1702.0	1680.8	1657.7	1642.6	1625.0	1605.2	1584.8	1563.6	1540.4
7.5°	1822.9	1791.5	1757.5	1720.8	1685.0	1651.9	1620.4	1589.5	1560.6	1525.7	1496.1
10°	1881.3	1841.7	1799.5	1749.7	1701.3	1659.0	1616.1	1578.6	1540.4	1499.5	1463.4
12.5°	1939.5	1886.9	1827.2	1772.6	1714.3	1663.3	1612.9	1565.0	1517.0	1471.8	1429.6
15°	1980.7	1934.4	1879.2	1801.5	1736.1	1665.9	1599.0	1537.0	1479.0	1428.7	1375.5
17.5°	2007.9	1948.1	1888.9	1814.3	1728.6	1650.0	1574.4	1503.4	1438.0	1374.1	1322.8
20°	2012.8	1951.5	1889.5	1816.4	1728.6	1638.6	1563.0	1477.7	1407.5	1341.4	1278.7
22.5°	2011.1	1941.7	1874.1	1799.1	1713.3	1630.4	1538.9	1452.1	1375.9	1310.9	1245.5
25°	1995.8	1921.5	1836.9	1761.3	1676.8	1588.8	1496.1	1406.1	1328.5	1254.2	1189.4
27.5°	1983.0	1886.5	1790.9	1702.6	1621.0	1540.4	1451.7	1359.6	1273.3	1198.1	1137.1
30°	1967.1	1861.5	1753.7	1661.7	1577.9	1499.5	1415.7	1325.8	1235.8	1162.2	1096.7
32.5°	1953.0	1829.9	1716.2	1616.0	1527.2	1451.0	1373.7	1288.1	1199.7	1125.1	1059.7
35°	1925.5	1783.1	1652.9	1539.7	1445.0	1366.7	1301.9	1222.1	1141.0	1068.7	1006.0
37.5°	1890.8	1721.7	1582.1	1463.4	1359.6	1277.0	1216.7	1155.5	1077.6	1007.9	951.3
40°	1863.5	1678.1	1530.2	1408.9	1301.2	1215.3	1159.4	1101.5	1036.7	972.0	912.0
42.5°	1829.2	1638.9	1477.8	1347.3	1240.6	1157.0	1098.3	1049.1	992.0	931.6	876.0
45°	1766.1	1567.7	1393.2	1252.8	1145.1	1062.6	1002.0	965.1	922.2	864.9	817.9
47.5°	1673.2	1482.2	1301.7	1156.8	1045.7	969.3	912.4	877.1	846.9	804.3	761.6
50°	1590.8	1418.5	1235.8	1092.0	980.9	903.8	851.3	819.3	793.3	760.6	724.6
52.5°	1498.7	1338.3	1170.8	1028.6	918.7	842.7	791.3	763.2	741.5	718.1	682.6
55°	1352.3	1216.0	1060.6	925.6	824.0	749.7	704.8	680.2	662.6	644.8	623.0
57.5°	1191.0	1084.4	946.7	823.3	729.8	662.3	620.3	596.4	582.6	573.5	560.7
60°	1077.6	986.3	867.7	755.2	663.9	603.9	563.0	544.6	533.0	525.5	515.9
62.5°	972.4	897.4	787.5	684.9	605.0	548.3	511.8	493.9	482.8	479.2	471.3
65°	817.3	759.3	668.6	583.5	515.3	466.9	436.3	419.2	412.3	408.3	409.0
67.5°	664.4	629.1	556.3	483.6	429.3	388.7	364.2	351.0	347.6	342.1	342.0
70°	571.2	544.6	483.2	419.9	371.4	340.1	318.3	304.7	301.2	298.5	297.9
72.5°	488.9	465.5	412.3	361.5	318.0	290.5	272.5	264.3	258.7	257.1	257.0
75°	367.4	354.5	312.1	272.0	242.0	222.9	210.7	203.1	199.0	198.3	199.0
77.5°	261.2	249.8	223.0	194.5	175.6	161.2	150.8	148.1	143.5	143.7	143.0
80°	196.3	188.8	171.8	149.3	133.6	121.3	115.8	111.1	109.8	107.7	109.8
82.5°	142.3	134.3	122.7	108.4	95.4	88.1	82.6	81.1	80.3	79.4	79.8
85°	70.2	70.9	64.0	53.1	47.7	43.6	40.2	40.2	39.5	38.9	39.5
87.5°	27.1	25.5	23.0	21.0	17.9	15.8	14.8	14.9	13.7	13.6	14.5
90°	15.1	13.3	11.5	9.5	7.5	5.4	3.2	1.2	3.2	5.4	7.5
92.5°	40.6	38.4	36.1	34.2	32.8	31.3	29.9	28.4	29.9	31.3	32.8
95°	85.1	82.5	79.9	78.4	77.9	77.4	76.7	76.2	76.7	77.4	77.9
97.5°	136.6	133.1	129.5	127.5	127.3	127.1	126.9	126.7	126.9	127.1	127.3
100°	172.8	169.4	166.0	164.3	164.3	164.3	164.3	164.3	164.3	164.3	164.3
102.5°	213.7	212.0	210.3	208.8	207.8	206.7	205.7	204.7	205.7	206.7	207.8
105°	277.3	275.8	274.2	272.8	271.5	270.1	268.8	267.5	268.8	270.1	271.5
107.5°	345.9	344.7	343.5	342.2	340.9	339.6	338.3	337.0	338.3	339.6	340.9
110°	392.7	391.9	391.1	390.1	388.8	387.5	386.2	385.0	386.2	387.5	388.8



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	439.3	438.3	437.3	436.5	435.8	435.0	434.4	433.7	434.4	435.0	435.8
115°	511.8	511.3	510.7	510.0	508.9	507.9	506.9	505.7	506.9	507.9	508.9
117.5°	581.4	580.9	580.4	580.0	579.5	579.1	578.6	578.0	578.6	579.1	579.5
120°	629.7	629.3	629.1	628.3	627.0	625.7	624.4	623.1	624.4	625.7	627.0
122.5°	675.8	675.1	674.4	673.8	673.4	672.9	672.5	672.0	672.5	672.9	673.4
125°	745.8	745.6	745.3	744.4	742.9	741.2	739.7	738.1	739.7	741.2	742.9
127.5°	813.3	813.0	812.7	812.1	811.2	810.3	809.4	808.6	809.4	810.3	811.2
130°	858.0	857.5	857.0	856.0	854.7	853.4	852.1	850.8	852.1	853.4	854.7
132.5°	902.4	902.5	902.6	901.6	899.5	897.4	895.1	893.0	895.1	897.4	899.5
135°	967.7	967.3	967.1	966.2	964.6	963.1	961.5	960.0	961.5	963.1	964.6
137.5°	1031.1	1030.5	1030.0	1028.9	1027.3	1025.8	1024.3	1022.8	1024.3	1025.8	1027.3
140°	1071.1	1070.3	1069.4	1068.4	1067.1	1065.8	1064.5	1063.2	1064.5	1065.8	1067.1
142.5°	1111.0	1109.9	1109.0	1107.9	1106.8	1105.8	1104.7	1103.6	1104.7	1105.8	1106.8
145°	1169.6	1168.8	1168.0	1167.1	1166.1	1165.1	1164.0	1163.0	1164.0	1165.1	1166.1
147.5°	1222.0	1221.4	1220.7	1220.1	1219.6	1219.0	1218.4	1217.9	1218.4	1219.0	1219.6
150°	1255.9	1254.9	1253.8	1253.4	1253.7	1253.9	1254.3	1254.5	1254.3	1253.9	1253.7
152.5°	1287.2	1286.8	1286.4	1286.0	1285.7	1285.3	1284.9	1284.5	1284.9	1285.3	1285.7
155°	1331.4	1331.2	1330.9	1330.8	1330.8	1330.8	1330.8	1330.8	1330.8	1330.8	1330.8
157.5°	1370.2	1369.9	1369.6	1369.8	1370.4	1370.9	1371.5	1372.1	1371.5	1370.9	1370.4
160°	1393.6	1393.3	1393.1	1393.3	1394.1	1394.9	1395.7	1396.4	1395.7	1394.9	1394.1
162.5°	1415.6	1415.5	1415.5	1415.7	1416.3	1416.9	1417.5	1418.1	1417.5	1416.9	1416.3
165°	1445.2	1445.0	1444.7	1444.8	1445.4	1445.9	1446.4	1446.9	1446.4	1445.9	1445.4
167.5°	1466.6	1466.6	1466.6	1467.1	1468.2	1469.3	1470.3	1471.4	1470.3	1469.3	1468.2
170°	1479.8	1479.8	1479.8	1480.4	1481.4	1482.4	1483.5	1484.5	1483.5	1482.4	1481.4
172.5°	1489.1	1489.1	1489.1	1489.8	1490.8	1491.8	1492.9	1493.9	1492.9	1491.8	1490.8
175°	1499.8	1499.8	1499.8	1500.3	1501.3	1502.4	1503.4	1504.4	1503.4	1502.4	1501.3
177.5°	1505.6	1505.8	1506.0	1506.5	1507.3	1508.1	1509.0	1509.8	1509.0	1508.1	1507.3
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1578.0	1572.1	1567.1	1556.2	1550.2	1542.1	1535.5	1542.6	1535.0	1538.2	1533.4
5°	1528.8	1509.7	1496.1	1476.3	1459.4	1443.6	1432.1	1430.0	1424.5	1421.8	1413.6
7.5°	1469.7	1445.8	1422.4	1396.4	1374.6	1352.4	1338.3	1326.6	1318.8	1308.6	1301.6
10°	1434.8	1402.7	1375.5	1344.1	1316.9	1293.0	1273.9	1264.4	1255.6	1242.5	1237.8
12.5°	1391.7	1358.6	1325.3	1291.8	1265.6	1239.0	1222.6	1208.2	1202.0	1187.5	1186.0
15°	1340.1	1290.3	1257.6	1223.5	1187.4	1165.6	1152.0	1136.2	1129.4	1119.2	1111.7
17.5°	1278.4	1234.0	1193.1	1157.8	1126.8	1108.4	1091.6	1080.8	1069.0	1062.4	1050.1
20°	1233.8	1191.4	1150.5	1113.1	1089.2	1068.0	1054.4	1044.2	1032.0	1028.5	1016.3
22.5°	1196.1	1149.4	1110.2	1078.7	1052.7	1028.9	1014.1	1007.1	998.7	988.2	985.7
25°	1134.9	1086.5	1053.1	1021.8	998.6	976.7	966.5	957.7	949.5	942.0	939.3
27.5°	1082.0	1038.7	999.1	970.8	950.6	930.7	921.7	910.9	904.9	898.9	891.5
30°	1044.9	1000.6	965.8	938.6	916.8	899.1	889.5	882.0	876.6	871.1	867.0
32.5°	1006.7	965.7	932.0	905.3	883.5	870.1	861.7	856.4	850.4	843.8	838.7
35°	956.3	911.3	878.6	855.5	838.4	828.2	818.6	813.9	807.0	807.0	801.5
37.5°	899.5	860.6	831.7	810.6	795.3	786.2	775.8	772.5	768.2	765.3	763.4
40°	865.7	829.5	802.2	781.1	764.8	757.3	749.1	743.7	740.9	737.5	736.1
42.5°	830.7	796.3	770.1	750.6	736.4	730.0	722.4	718.5	713.1	708.6	707.8
45°	777.7	744.3	720.4	704.8	692.5	685.0	680.2	672.1	669.3	663.9	663.2
47.5°	727.4	695.4	672.0	659.1	648.3	642.2	634.7	626.5	623.4	620.7	620.4
50°	689.8	660.5	638.6	626.4	616.2	607.3	599.9	594.4	592.3	592.3	593.7
52.5°	651.7	626.6	608.1	593.1	583.5	574.0	567.1	563.8	560.7	564.0	566.4
55°	595.7	570.5	556.8	542.6	533.0	522.1	518.7	517.4	515.3	520.8	523.5
57.5°	536.5	518.9	502.9	488.7	480.1	473.8	469.2	468.4	472.2	474.8	483.6
60°	499.0	478.5	464.1	453.2	443.0	439.0	437.6	436.3	439.0	446.5	458.1
62.5°	457.5	440.9	425.5	417.3	409.8	402.9	402.7	403.5	409.0	417.6	429.1
65°	396.7	382.3	372.1	362.6	356.5	352.3	353.8	356.5	362.6	374.2	387.2
67.5°	335.0	325.2	316.0	308.2	302.4	302.4	303.8	307.8	315.1	328.4	340.2
70°	295.2	284.3	276.7	273.4	268.5	265.8	269.9	276.7	282.9	295.2	305.4
72.5°	255.3	246.1	240.2	237.9	235.8	233.7	235.0	242.4	250.6	263.0	274.8
75°	196.3	192.9	188.8	186.1	184.0	185.4	186.7	193.6	200.4	213.4	227.0
77.5°	143.3	139.8	137.2	136.6	135.5	136.2	140.0	145.0	151.7	161.2	171.5
80°	108.4	107.0	105.6	104.9	104.9	105.6	111.1	114.5	120.7	129.5	137.6
82.5°	79.0	78.1	77.9	77.7	78.3	78.4	81.7	86.1	91.2	97.9	104.9
85°	41.6	40.2	42.2	42.9	41.6	43.6	44.9	47.7	49.8	53.1	56.6
87.5°	15.6	17.1	16.9	17.8	18.1	19.6	19.3	21.7	23.1	24.4	24.1
90°	9.5	11.5	13.3	15.1	17.0	18.8	20.1	21.4	22.7	24.0	25.0
92.5°	34.2	36.1	38.4	40.6	42.8	45.0	46.8	48.5	50.2	51.9	53.1
95°	78.4	79.9	82.5	85.1	87.8	90.4	92.2	94.0	95.8	97.7	98.9
97.5°	127.5	129.5	133.1	136.6	140.3	143.9	145.6	147.3	149.1	150.8	151.8
100°	164.3	166.0	169.4	172.8	176.1	179.6	181.9	184.2	186.6	188.9	190.4
102.5°	208.8	210.3	212.0	213.7	215.4	217.1	219.6	222.2	224.8	227.3	228.9
105°	272.8	274.2	275.8	277.3	278.9	280.4	282.1	283.6	285.2	286.7	287.9
107.5°	342.2	343.5	344.7	345.9	347.1	348.3	349.1	349.8	350.6	351.4	351.8
110°	390.1	391.1	391.9	392.7	393.5	394.3	395.1	395.9	396.7	397.4	397.7



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	436.5	437.3	438.3	439.3	440.2	441.2	441.6	442.0	442.3	442.7	442.6
115°	510.0	510.7	511.3	511.8	512.3	512.8	512.6	512.3	512.0	511.8	511.5
117.5°	580.0	580.4	580.9	581.4	581.8	582.3	582.5	582.7	582.9	583.1	582.7
120°	628.3	629.1	629.3	629.7	630.0	630.2	630.2	630.2	630.2	630.2	629.7
122.5°	673.8	674.4	675.1	675.8	676.4	677.1	676.9	676.7	676.5	676.3	675.8
125°	744.4	745.3	745.6	745.8	746.1	746.4	745.8	745.3	744.8	744.3	743.9
127.5°	812.1	812.7	813.0	813.3	813.6	814.0	813.6	813.4	813.1	812.9	812.5
130°	856.0	857.0	857.5	858.0	858.5	859.0	858.8	858.5	858.2	858.0	857.6
132.5°	901.6	902.6	902.5	902.4	902.3	902.2	901.9	901.7	901.4	901.1	900.7
135°	966.2	967.1	967.3	967.7	967.9	968.2	968.2	968.2	968.2	968.2	967.7
137.5°	1028.9	1030.0	1030.5	1031.1	1031.7	1032.2	1032.5	1032.9	1033.2	1033.5	1033.0
140°	1068.4	1069.4	1070.3	1071.1	1071.8	1072.6	1073.1	1073.6	1074.2	1074.7	1074.3
142.5°	1107.9	1109.0	1109.9	1111.0	1112.0	1113.0	1113.3	1113.6	1113.9	1114.2	1113.7
145°	1167.1	1168.0	1168.8	1169.6	1170.3	1171.1	1171.1	1171.1	1171.1	1171.1	1170.7
147.5°	1220.1	1220.7	1221.4	1222.0	1222.6	1223.2	1223.9	1224.6	1225.2	1225.8	1225.2
150°	1253.4	1253.8	1254.9	1255.9	1257.0	1258.0	1258.0	1258.0	1258.0	1258.0	1257.8
152.5°	1286.0	1286.4	1286.8	1287.2	1287.7	1288.1	1288.7	1289.3	1289.9	1290.5	1290.4
155°	1330.8	1330.9	1331.2	1331.4	1331.7	1331.9	1333.0	1334.0	1335.0	1336.2	1336.0
157.5°	1369.8	1369.6	1369.9	1370.2	1370.4	1370.7	1371.7	1372.7	1373.8	1374.8	1374.5
160°	1393.3	1393.1	1393.3	1393.6	1393.9	1394.1	1395.1	1396.2	1397.2	1398.3	1398.2
162.5°	1415.7	1415.5	1415.5	1415.6	1415.6	1415.7	1416.9	1418.3	1419.5	1420.8	1420.6
165°	1444.8	1444.7	1445.0	1445.2	1445.5	1445.7	1446.8	1447.8	1448.9	1450.0	1449.7
167.5°	1467.1	1466.6	1466.6	1466.6	1466.6	1466.6	1468.2	1469.8	1471.4	1472.9	1472.9
170°	1480.4	1479.8	1479.8	1479.8	1479.8	1479.8	1481.4	1482.9	1484.5	1486.0	1485.9
172.5°	1489.8	1489.1	1489.1	1489.1	1489.1	1489.1	1490.8	1492.3	1493.9	1495.4	1495.4
175°	1500.3	1499.8	1499.8	1499.8	1499.8	1499.8	1501.3	1502.9	1504.4	1506.0	1505.9
177.5°	1506.5	1506.0	1505.8	1505.6	1505.3	1505.1	1506.4	1507.6	1508.9	1510.2	1510.1
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1530.0	1533.9	1530.7	1535.0	1530.7	1533.9	1530.0	1533.4	1538.2	1535.0	1542.6
5°	1410.3	1404.1	1408.2	1405.4	1408.2	1404.1	1410.3	1413.6	1421.8	1424.5	1430.0
7.5°	1299.6	1293.7	1287.0	1283.8	1287.0	1293.7	1299.6	1301.6	1308.6	1318.8	1326.6
10°	1230.3	1222.8	1222.1	1217.4	1222.1	1222.8	1230.3	1237.8	1242.5	1255.6	1264.4
12.5°	1179.6	1172.7	1164.9	1162.9	1164.9	1172.7	1179.6	1186.0	1187.5	1202.0	1208.2
15°	1107.6	1102.2	1097.4	1101.5	1097.4	1102.2	1107.6	1111.7	1119.2	1129.4	1136.2
17.5°	1047.7	1043.3	1042.5	1037.4	1042.5	1043.3	1047.7	1050.1	1062.4	1069.0	1080.8
20°	1010.2	1006.7	1008.1	999.3	1008.1	1006.7	1010.2	1016.3	1028.5	1032.0	1044.2
22.5°	980.2	973.5	972.7	970.9	972.7	973.5	980.2	985.7	988.2	998.7	1007.1
25°	933.1	929.7	926.3	929.7	926.3	929.7	933.1	939.3	942.0	949.5	957.7
27.5°	892.1	888.0	887.1	887.5	887.1	888.0	892.1	891.5	898.9	904.9	910.9
30°	867.0	860.2	860.9	860.2	860.9	860.2	867.0	867.0	871.1	876.6	882.0
32.5°	839.7	835.1	834.1	832.9	834.1	835.1	839.7	838.7	843.8	850.4	856.4
35°	799.5	799.5	796.1	796.1	796.1	799.5	799.5	801.5	807.0	807.0	813.9
37.5°	761.7	761.0	759.0	759.3	759.0	761.0	761.7	763.4	765.3	768.2	772.5
40°	733.4	732.8	730.6	726.6	730.6	732.8	733.4	736.1	737.5	740.9	743.7
42.5°	706.1	703.9	702.9	701.6	702.9	703.9	706.1	707.8	708.6	713.1	718.5
45°	663.2	663.2	661.9	661.2	661.9	663.2	663.2	663.2	663.9	669.3	672.1
47.5°	621.5	622.7	625.3	624.9	625.3	622.7	621.5	620.4	620.7	623.4	626.5
50°	596.4	597.1	599.2	599.9	599.2	597.1	596.4	593.7	592.3	592.3	594.4
52.5°	568.6	572.6	575.1	574.7	575.1	572.6	568.6	566.4	564.0	560.7	563.8
55°	529.6	534.4	539.2	539.9	539.2	534.4	529.6	523.5	520.8	515.3	517.4
57.5°	491.0	497.7	502.7	504.4	502.7	497.7	491.0	483.6	474.8	472.2	468.4
60°	464.8	473.7	479.9	482.6	479.9	473.7	464.8	458.1	446.5	439.0	436.3
62.5°	439.8	449.7	455.9	456.4	455.9	449.7	439.8	429.1	417.6	409.0	403.5
65°	398.7	409.0	414.4	418.5	414.4	409.0	398.7	387.2	374.2	362.6	356.5
67.5°	354.6	364.8	370.8	374.1	370.8	364.8	354.6	340.2	328.4	315.1	307.8
70°	322.4	332.6	340.8	343.6	340.8	332.6	322.4	305.4	295.2	282.9	276.7
72.5°	290.7	299.9	306.5	309.7	306.5	299.9	290.7	274.8	263.0	250.6	242.4
75°	235.8	248.1	254.3	257.6	254.3	248.1	235.8	227.0	213.4	200.4	193.6
77.5°	181.9	193.0	196.7	198.4	196.7	193.0	181.9	171.5	161.2	151.7	145.0
80°	145.8	152.7	157.4	158.1	157.4	152.7	145.8	137.6	129.5	120.7	114.5
82.5°	112.1	117.8	119.3	121.1	119.3	117.8	112.1	104.9	97.9	91.2	86.1
85°	61.3	64.0	64.7	64.0	64.7	64.0	61.3	56.6	53.1	49.8	47.7
87.5°	25.3	24.9	25.1	26.4	25.1	24.9	25.3	24.1	24.4	23.1	21.7
90°	25.9	26.6	27.4	28.2	27.4	26.6	25.9	25.0	24.0	22.7	21.4
92.5°	53.6	54.2	54.8	55.3	54.8	54.2	53.6	53.1	51.9	50.2	48.5
95°	99.4	99.9	100.4	100.9	100.4	99.9	99.4	98.9	97.7	95.8	94.0
97.5°	152.1	152.4	152.7	153.0	152.7	152.4	152.1	151.8	150.8	149.1	147.3
100°	190.9	191.4	192.0	192.5	192.0	191.4	190.9	190.4	188.9	186.6	184.2
102.5°	229.7	230.5	231.2	231.9	231.2	230.5	229.7	228.9	227.3	224.8	222.2
105°	288.7	289.4	290.2	291.0	290.2	289.4	288.7	287.9	286.7	285.2	283.6
107.5°	351.7	351.7	351.6	351.5	351.6	351.7	351.7	351.8	351.4	350.6	349.8
110°	397.4	397.2	396.9	396.7	396.9	397.2	397.4	397.7	397.4	396.7	395.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	442.2	441.7	441.2	440.8	441.2	441.7	442.2	442.6	442.7	442.3	442.0
115°	511.3	511.0	510.7	510.5	510.7	511.0	511.3	511.5	511.8	512.0	512.3
117.5°	581.7	580.7	579.6	578.6	579.6	580.7	581.7	582.7	583.1	582.9	582.7
120°	628.6	627.5	626.5	625.5	626.5	627.5	628.6	629.7	630.2	630.2	630.2
122.5°	674.9	674.1	673.3	672.5	673.3	674.1	674.9	675.8	676.3	676.5	676.7
125°	743.7	743.4	743.1	742.9	743.1	743.4	743.7	743.9	744.3	744.8	745.3
127.5°	812.0	811.4	810.9	810.4	810.9	811.4	812.0	812.5	812.9	813.1	813.4
130°	857.1	856.6	856.0	855.5	856.0	856.6	857.1	857.6	858.0	858.2	858.5
132.5°	899.9	899.2	898.5	897.8	898.5	899.2	899.9	900.7	901.1	901.4	901.7
135°	966.5	965.5	964.5	963.4	964.5	965.5	966.5	967.7	968.2	968.2	968.2
137.5°	1031.7	1030.4	1029.1	1027.7	1029.1	1030.4	1031.7	1033.0	1033.5	1033.2	1032.9
140°	1073.0	1071.7	1070.4	1069.0	1070.4	1071.7	1073.0	1074.3	1074.7	1074.2	1073.6
142.5°	1112.4	1111.2	1109.8	1108.5	1109.8	1111.2	1112.4	1113.7	1114.2	1113.9	1113.6
145°	1170.0	1169.2	1168.4	1167.6	1168.4	1169.2	1170.0	1170.7	1171.1	1171.1	1171.1
147.5°	1223.5	1221.6	1219.9	1218.1	1219.9	1221.6	1223.5	1225.2	1225.8	1225.2	1224.6
150°	1257.2	1256.7	1256.2	1255.7	1256.2	1256.7	1257.2	1257.8	1258.0	1258.0	1258.0
152.5°	1289.5	1288.5	1287.6	1286.7	1287.6	1288.5	1289.5	1290.4	1290.5	1289.9	1289.3
155°	1334.6	1333.3	1332.1	1330.8	1332.1	1333.3	1334.6	1336.0	1336.2	1335.0	1334.0
157.5°	1372.8	1371.1	1369.4	1367.7	1369.4	1371.1	1372.8	1374.5	1374.8	1373.8	1372.7
160°	1396.8	1395.5	1394.2	1393.0	1394.2	1395.5	1396.8	1398.2	1398.3	1397.2	1396.2
162.5°	1419.1	1417.5	1416.0	1414.5	1416.0	1417.5	1419.1	1420.6	1420.8	1419.5	1418.3
165°	1448.1	1446.5	1445.0	1443.4	1445.0	1446.5	1448.1	1449.7	1450.0	1448.9	1447.8
167.5°	1471.3	1469.7	1468.0	1466.4	1468.0	1469.7	1471.3	1472.9	1472.9	1471.4	1469.8
170°	1484.1	1482.3	1480.5	1478.6	1480.5	1482.3	1484.1	1485.9	1486.0	1484.5	1482.9
172.5°	1493.8	1492.2	1490.6	1488.9	1490.6	1492.2	1493.8	1495.4	1495.4	1493.9	1492.3
175°	1504.1	1502.3	1500.4	1498.5	1500.4	1502.3	1504.1	1505.9	1506.0	1504.4	1502.9
177.5°	1508.6	1507.1	1505.7	1504.2	1505.7	1507.1	1508.6	1510.1	1510.2	1508.9	1507.6
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1535.5	1542.1	1550.2	1556.2	1567.1	1572.1	1578.0	1583.0	1591.6	1599.8	1609.7
5°	1432.1	1443.6	1459.4	1476.3	1496.1	1509.7	1528.8	1540.4	1563.6	1584.8	1605.2
7.5°	1338.3	1352.4	1374.6	1396.4	1422.4	1445.8	1469.7	1496.1	1525.7	1560.6	1589.5
10°	1273.9	1293.0	1316.9	1344.1	1375.5	1402.7	1434.8	1463.4	1499.5	1540.4	1578.6
12.5°	1222.6	1239.0	1265.6	1291.8	1325.3	1358.6	1391.7	1429.6	1471.8	1517.0	1565.0
15°	1152.0	1165.6	1187.4	1223.5	1257.6	1290.3	1340.1	1375.5	1428.7	1479.0	1537.0
17.5°	1091.6	1108.4	1126.8	1157.8	1193.1	1234.0	1278.4	1322.8	1374.1	1438.0	1503.4
20°	1054.4	1068.0	1089.2	1113.1	1150.5	1191.4	1233.8	1278.7	1341.4	1407.5	1477.7
22.5°	1014.1	1028.9	1052.7	1078.7	1110.2	1149.4	1196.1	1245.5	1310.9	1375.9	1452.1
25°	966.5	976.7	998.6	1021.8	1053.1	1086.5	1134.9	1189.4	1254.2	1328.5	1406.1
27.5°	921.7	930.7	950.6	970.8	999.1	1038.7	1082.0	1137.1	1198.1	1273.3	1359.6
30°	889.5	899.1	916.8	938.6	965.8	1000.6	1044.9	1096.7	1162.2	1235.8	1325.8
32.5°	861.7	870.1	883.5	905.3	932.0	965.7	1006.7	1059.7	1125.1	1199.7	1288.1
35°	818.6	828.2	838.4	855.5	878.6	911.3	956.3	1006.0	1068.7	1141.0	1222.1
37.5°	775.8	786.2	795.3	810.6	831.7	860.6	899.5	951.3	1007.9	1077.6	1155.5
40°	749.1	757.3	764.8	781.1	802.2	829.5	865.7	912.0	972.0	1036.7	1101.5
42.5°	722.4	730.0	736.4	750.6	770.1	796.3	830.7	876.0	931.6	992.0	1049.1
45°	680.2	685.0	692.5	704.8	720.4	744.3	777.7	817.9	864.9	922.2	965.1
47.5°	634.7	642.2	648.3	659.1	672.0	695.4	727.4	761.6	804.3	846.9	877.1
50°	599.9	607.3	616.2	626.4	638.6	660.5	689.8	724.6	760.6	793.3	819.3
52.5°	567.1	574.0	583.5	593.1	608.1	626.6	651.7	682.6	718.1	741.5	763.2
55°	518.7	522.1	533.0	542.6	556.8	570.5	595.7	623.0	644.8	662.6	680.2
57.5°	469.2	473.8	480.1	488.7	502.9	518.9	536.5	560.7	573.5	582.6	596.4
60°	437.6	439.0	443.0	453.2	464.1	478.5	499.0	515.9	525.5	533.0	544.6
62.5°	402.7	402.9	409.8	417.3	425.5	440.9	457.5	471.3	479.2	482.8	493.9
65°	353.8	352.3	356.5	362.6	372.1	382.3	396.7	409.0	408.3	412.3	419.2
67.5°	303.8	302.4	302.4	308.2	316.0	325.2	335.0	342.0	342.1	347.6	351.0
70°	269.9	265.8	268.5	273.4	276.7	284.3	295.2	297.9	298.5	301.2	304.7
72.5°	235.0	233.7	235.8	237.9	240.2	246.1	255.3	257.0	257.1	258.7	264.3
75°	186.7	185.4	184.0	186.1	188.8	192.9	196.3	199.0	198.3	199.0	203.1
77.5°	140.0	136.2	135.5	136.6	137.2	139.8	143.3	143.0	143.7	143.5	148.1
80°	111.1	105.6	104.9	104.9	105.6	107.0	108.4	109.8	107.7	109.8	111.1
82.5°	81.7	78.4	78.3	77.7	77.9	78.1	79.0	79.8	79.4	80.3	81.1
85°	44.9	43.6	41.6	42.9	42.2	40.2	41.6	39.5	38.9	39.5	40.2
87.5°	19.3	19.6	18.1	17.8	16.9	17.1	15.6	14.5	13.6	13.7	14.9
90°	20.1	18.8	17.0	15.1	13.3	11.5	9.5	7.5	5.4	3.2	1.2
92.5°	46.8	45.0	42.8	40.6	38.4	36.1	34.2	32.8	31.3	29.9	28.4
95°	92.2	90.4	87.8	85.1	82.5	79.9	78.4	77.9	77.4	76.7	76.2
97.5°	145.6	143.9	140.3	136.6	133.1	129.5	127.5	127.3	127.1	126.9	126.7
100°	181.9	179.6	176.1	172.8	169.4	166.0	164.3	164.3	164.3	164.3	164.3
102.5°	219.6	217.1	215.4	213.7	212.0	210.3	208.8	207.8	206.7	205.7	204.7
105°	282.1	280.4	278.9	277.3	275.8	274.2	272.8	271.5	270.1	268.8	267.5
107.5°	349.1	348.3	347.1	345.9	344.7	343.5	342.2	340.9	339.6	338.3	337.0
110°	395.1	394.3	393.5	392.7	391.9	391.1	390.1	388.8	387.5	386.2	385.0



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	441.6	441.2	440.2	439.3	438.3	437.3	436.5	435.8	435.0	434.4	433.7
115°	512.6	512.8	512.3	511.8	511.3	510.7	510.0	508.9	507.9	506.9	505.7
117.5°	582.5	582.3	581.8	581.4	580.9	580.4	580.0	579.5	579.1	578.6	578.0
120°	630.2	630.2	630.0	629.7	629.3	629.1	628.3	627.0	625.7	624.4	623.1
122.5°	676.9	677.1	676.4	675.8	675.1	674.4	673.8	673.4	672.9	672.5	672.0
125°	745.8	746.4	746.1	745.8	745.6	745.3	744.4	742.9	741.2	739.7	738.1
127.5°	813.6	814.0	813.6	813.3	813.0	812.7	812.1	811.2	810.3	809.4	808.6
130°	858.8	859.0	858.5	858.0	857.5	857.0	856.0	854.7	853.4	852.1	850.8
132.5°	901.9	902.2	902.3	902.4	902.5	902.6	901.6	899.5	897.4	895.1	893.0
135°	968.2	968.2	967.9	967.7	967.3	967.1	966.2	964.6	963.1	961.5	960.0
137.5°	1032.5	1032.2	1031.7	1031.1	1030.5	1030.0	1028.9	1027.3	1025.8	1024.3	1022.8
140°	1073.1	1072.6	1071.8	1071.1	1070.3	1069.4	1068.4	1067.1	1065.8	1064.5	1063.2
142.5°	1113.3	1113.0	1112.0	1111.0	1109.9	1109.0	1107.9	1106.8	1105.8	1104.7	1103.6
145°	1171.1	1171.1	1170.3	1169.6	1168.8	1168.0	1167.1	1166.1	1165.1	1164.0	1163.0
147.5°	1223.9	1223.2	1222.6	1222.0	1221.4	1220.7	1220.1	1219.6	1219.0	1218.4	1217.9
150°	1258.0	1258.0	1257.0	1255.9	1254.9	1253.8	1253.4	1253.7	1253.9	1254.3	1254.5
152.5°	1288.7	1288.1	1287.7	1287.2	1286.8	1286.4	1286.0	1285.7	1285.3	1284.9	1284.5
155°	1333.0	1331.9	1331.7	1331.4	1331.2	1330.9	1330.8	1330.8	1330.8	1330.8	1330.8
157.5°	1371.7	1370.7	1370.4	1370.2	1369.9	1369.6	1369.8	1370.4	1370.9	1371.5	1372.1
160°	1395.1	1394.1	1393.9	1393.6	1393.3	1393.1	1393.3	1394.1	1394.9	1395.7	1396.4
162.5°	1416.9	1415.7	1415.6	1415.6	1415.5	1415.5	1415.7	1416.3	1416.9	1417.5	1418.1
165°	1446.8	1445.7	1445.5	1445.2	1445.0	1444.7	1444.8	1445.4	1445.9	1446.4	1446.9
167.5°	1468.2	1466.6	1466.6	1466.6	1466.6	1466.6	1467.1	1468.2	1469.3	1470.3	1471.4
170°	1481.4	1479.8	1479.8	1479.8	1479.8	1479.8	1480.4	1481.4	1482.4	1483.5	1484.5
172.5°	1490.8	1489.1	1489.1	1489.1	1489.1	1489.1	1489.8	1490.8	1491.8	1492.9	1493.9
175°	1501.3	1499.8	1499.8	1499.8	1499.8	1499.8	1500.3	1501.3	1502.4	1503.4	1504.4
177.5°	1506.4	1505.1	1505.3	1505.6	1505.8	1506.0	1506.5	1507.3	1508.1	1509.0	1509.8
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1614.6	1622.2	1627.1	1636.4	1644.1	1648.4	1652.2	1655.5	1659.3	1662.5	1671.8
5°	1625.0	1642.6	1657.7	1680.8	1702.0	1718.4	1736.1	1751.7	1764.6	1783.1	1797.4
7.5°	1620.4	1651.9	1685.0	1720.8	1757.5	1791.5	1822.9	1852.2	1878.8	1911.0	1939.1
10°	1616.1	1659.0	1701.3	1749.7	1799.5	1841.7	1881.3	1921.5	1950.8	1991.7	2026.4
12.5°	1612.9	1663.3	1714.3	1772.6	1827.2	1886.9	1939.5	1968.9	2013.5	2046.2	2087.5
15°	1599.0	1665.9	1736.1	1801.5	1879.2	1934.4	1980.7	2038.0	2079.6	2121.1	2166.2
17.5°	1574.4	1650.0	1728.6	1814.3	1888.9	1948.1	2007.9	2063.1	2112.7	2168.5	2224.5
20°	1563.0	1638.6	1728.6	1816.4	1889.5	1951.5	2012.8	2073.5	2128.0	2199.6	2264.3
22.5°	1538.9	1630.4	1713.3	1799.1	1874.1	1941.7	2011.1	2080.0	2152.5	2233.3	2314.5
25°	1496.1	1588.8	1676.8	1761.3	1836.9	1921.5	1995.8	2087.8	2180.5	2287.4	2388.3
27.5°	1451.7	1540.4	1621.0	1702.6	1790.9	1886.5	1983.0	2087.4	2208.7	2343.8	2486.1
30°	1415.7	1499.5	1577.9	1661.7	1753.7	1861.5	1967.1	2091.1	2231.6	2383.6	2552.6
32.5°	1373.7	1451.0	1527.2	1616.0	1716.2	1829.9	1953.0	2089.0	2257.8	2430.4	2604.4
35°	1301.9	1366.7	1445.0	1539.7	1652.9	1783.1	1925.5	2086.4	2280.0	2478.3	2624.8
37.5°	1216.7	1277.0	1359.6	1463.4	1582.1	1721.7	1890.8	2081.6	2287.2	2445.4	2492.6
40°	1159.4	1215.3	1301.2	1408.9	1530.2	1678.1	1863.5	2065.3	2264.3	2365.2	2326.3
42.5°	1098.3	1157.0	1240.6	1347.3	1477.8	1638.9	1829.2	2030.9	2197.8	2235.9	2101.6
45°	1002.0	1062.6	1145.1	1252.8	1393.2	1567.7	1766.1	1949.4	2045.5	1976.7	1768.8
47.5°	912.4	969.3	1045.7	1156.8	1301.7	1482.2	1673.2	1819.5	1827.1	1662.8	1440.8
50°	851.3	903.8	980.9	1092.0	1235.8	1418.5	1590.8	1706.1	1654.3	1468.1	1254.9
52.5°	791.3	842.7	918.7	1028.6	1170.8	1338.3	1498.7	1579.5	1482.0	1291.0	1108.7
55°	704.8	749.7	824.0	925.6	1060.6	1216.0	1352.3	1380.3	1253.4	1065.3	917.5
57.5°	620.3	662.3	729.8	823.3	946.7	1084.4	1191.0	1185.1	1051.1	889.6	772.2
60°	563.0	603.9	663.9	755.2	867.7	986.3	1077.6	1055.8	922.9	783.9	685.0
62.5°	511.8	548.3	605.0	684.9	787.5	897.4	972.4	940.2	810.0	688.4	610.4
65°	436.3	466.9	515.3	583.5	668.6	759.3	817.3	775.7	664.6	569.9	507.2
67.5°	364.2	388.7	429.3	483.6	556.3	629.1	664.4	622.6	533.7	464.5	418.1
70°	318.3	340.1	371.4	419.9	483.2	544.6	571.2	533.7	457.4	398.1	364.7
72.5°	272.5	290.5	318.0	361.5	412.3	465.5	488.9	453.0	390.3	340.2	309.0
75°	210.7	222.9	242.0	272.0	312.1	354.5	367.4	336.1	295.8	258.3	237.9
77.5°	150.8	161.2	175.6	194.5	223.0	249.8	261.2	243.1	212.0	188.2	171.5
80°	115.8	121.3	133.6	149.3	171.8	188.8	196.3	184.7	162.9	145.2	132.2
82.5°	82.6	88.1	95.4	108.4	122.7	134.3	142.3	134.5	118.8	104.8	97.4
85°	40.2	43.6	47.7	53.1	64.0	70.9	70.2	65.4	59.3	53.8	49.8
87.5°	14.8	15.8	17.9	21.0	23.0	25.5	27.1	26.3	24.4	23.1	21.7
90°	3.2	5.4	7.5	9.5	11.5	13.3	15.1	17.0	18.8	20.1	21.4
92.5°	29.9	31.3	32.8	34.2	36.1	38.4	40.6	42.8	45.0	46.8	48.5
95°	76.7	77.4	77.9	78.4	79.9	82.5	85.1	87.8	90.4	92.2	94.0
97.5°	126.9	127.1	127.3	127.5	129.5	133.1	136.6	140.3	143.9	145.6	147.3
100°	164.3	164.3	164.3	164.3	166.0	169.4	172.8	176.1	179.6	181.9	184.2
102.5°	205.7	206.7	207.8	208.8	210.3	212.0	213.7	215.4	217.1	219.6	222.2
105°	268.8	270.1	271.5	272.8	274.2	275.8	277.3	278.9	280.4	282.1	283.6
107.5°	338.3	339.6	340.9	342.2	343.5	344.7	345.9	347.1	348.3	349.1	349.8
110°	386.2	387.5	388.8	390.1	391.1	391.9	392.7	393.5	394.3	395.1	395.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	434.4	435.0	435.8	436.5	437.3	438.3	439.3	440.2	441.2	441.6	442.0
115°	506.9	507.9	508.9	510.0	510.7	511.3	511.8	512.3	512.8	512.6	512.3
117.5°	578.6	579.1	579.5	580.0	580.4	580.9	581.4	581.8	582.3	582.5	582.7
120°	624.4	625.7	627.0	628.3	629.1	629.3	629.7	630.0	630.2	630.2	630.2
122.5°	672.5	672.9	673.4	673.8	674.4	675.1	675.8	676.4	677.1	676.9	676.7
125°	739.7	741.2	742.9	744.4	745.3	745.6	745.8	746.1	746.4	745.8	745.3
127.5°	809.4	810.3	811.2	812.1	812.7	813.0	813.3	813.6	814.0	813.6	813.4
130°	852.1	853.4	854.7	856.0	857.0	857.5	858.0	858.5	859.0	858.8	858.5
132.5°	895.1	897.4	899.5	901.6	902.6	902.5	902.4	902.3	902.2	901.9	901.7
135°	961.5	963.1	964.6	966.2	967.1	967.3	967.7	967.9	968.2	968.2	968.2
137.5°	1024.3	1025.8	1027.3	1028.9	1030.0	1030.5	1031.1	1031.7	1032.2	1032.5	1032.9
140°	1064.5	1065.8	1067.1	1068.4	1069.4	1070.3	1071.1	1071.8	1072.6	1073.1	1073.6
142.5°	1104.7	1105.8	1106.8	1107.9	1109.0	1109.9	1111.0	1112.0	1113.0	1113.3	1113.6
145°	1164.0	1165.1	1166.1	1167.1	1168.0	1168.8	1169.6	1170.3	1171.1	1171.1	1171.1
147.5°	1218.4	1219.0	1219.6	1220.1	1220.7	1221.4	1222.0	1222.6	1223.2	1223.9	1224.6
150°	1254.3	1253.9	1253.7	1253.4	1253.8	1254.9	1255.9	1257.0	1258.0	1258.0	1258.0
152.5°	1284.9	1285.3	1285.7	1286.0	1286.4	1286.8	1287.2	1287.7	1288.1	1288.7	1289.3
155°	1330.8	1330.8	1330.8	1330.8	1330.9	1331.2	1331.4	1331.7	1331.9	1333.0	1334.0
157.5°	1371.5	1370.9	1370.4	1369.8	1369.6	1369.9	1370.2	1370.4	1370.7	1371.7	1372.7
160°	1395.7	1394.9	1394.1	1393.3	1393.1	1393.3	1393.6	1393.9	1394.1	1395.1	1396.2
162.5°	1417.5	1416.9	1416.3	1415.7	1415.5	1415.5	1415.6	1415.6	1415.7	1416.9	1418.3
165°	1446.4	1445.9	1445.4	1444.8	1444.7	1445.0	1445.2	1445.5	1445.7	1446.8	1447.8
167.5°	1470.3	1469.3	1468.2	1467.1	1466.6	1466.6	1466.6	1466.6	1466.6	1468.2	1469.8
170°	1483.5	1482.4	1481.4	1480.4	1479.8	1479.8	1479.8	1479.8	1479.8	1481.4	1482.9
172.5°	1492.9	1491.8	1490.8	1489.8	1489.1	1489.1	1489.1	1489.1	1489.1	1490.8	1492.3
175°	1503.4	1502.4	1501.3	1500.3	1499.8	1499.8	1499.8	1499.8	1499.8	1501.3	1502.9
177.5°	1509.0	1508.1	1507.3	1506.5	1506.0	1505.8	1505.6	1505.3	1505.1	1506.4	1507.6
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9	1605.9
2.5°	1679.5	1683.8	1693.1	1689.8	1694.3	1696.4	1698.6
5°	1815.1	1836.9	1846.4	1845.1	1859.5	1856.0	1852.6
7.5°	1968.3	1991.3	2004.1	2020.0	2029.3	2029.9	2038.0
10°	2055.1	2085.1	2097.3	2114.4	2125.3	2131.4	2130.7
12.5°	2121.6	2145.1	2172.5	2180.9	2195.6	2203.3	2200.5
15°	2201.6	2239.1	2267.8	2282.0	2300.5	2305.9	2313.4
17.5°	2273.0	2323.3	2356.7	2401.2	2417.9	2428.1	2422.2
20°	2327.0	2393.2	2426.5	2479.7	2509.0	2524.7	2519.2
22.5°	2390.9	2462.4	2524.2	2570.2	2614.7	2635.9	2640.3
25°	2500.1	2598.3	2689.0	2749.7	2804.8	2817.7	2846.4
27.5°	2622.3	2738.0	2835.0	2898.7	2937.2	2951.6	2960.6
30°	2699.2	2814.4	2887.3	2928.2	2940.4	2939.1	2937.7
32.5°	2736.8	2808.9	2823.0	2811.5	2783.4	2759.7	2734.9
35°	2683.5	2629.7	2549.2	2445.6	2369.2	2292.3	2284.7
37.5°	2413.5	2241.3	2107.4	1957.8	1871.6	1818.3	1781.5
40°	2159.3	1963.7	1801.5	1675.4	1587.5	1552.7	1518.6
42.5°	1883.4	1696.6	1552.9	1447.4	1381.4	1342.8	1315.8
45°	1530.2	1365.2	1252.8	1176.5	1124.0	1094.0	1076.9
47.5°	1253.8	1131.9	1036.3	981.3	945.0	921.7	921.8
50°	1105.6	989.1	925.6	882.0	850.6	832.2	835.7
52.5°	974.1	887.1	832.9	796.4	773.3	761.9	761.5
55°	814.6	751.8	716.4	689.8	674.1	661.2	663.9
57.5°	696.7	643.9	620.2	598.0	587.1	582.0	574.4
60°	623.7	582.8	562.3	544.6	533.7	529.6	522.1
62.5°	558.8	526.6	506.8	492.2	482.4	481.1	475.2
65°	469.6	445.0	427.4	420.5	410.3	407.6	407.6
67.5°	387.2	369.6	355.8	349.5	345.1	345.7	342.4
70°	335.4	321.0	312.1	305.4	301.9	302.7	299.9
72.5°	293.4	277.4	269.6	265.6	261.1	262.9	261.8
75°	222.2	214.0	210.0	205.8	203.1	201.8	200.4
77.5°	163.2	155.9	152.8	150.5	150.9	147.6	150.3
80°	126.1	120.0	118.0	114.5	113.8	113.8	113.1
82.5°	92.3	88.9	87.4	84.5	83.3	84.4	82.6
85°	47.7	44.9	44.3	44.3	42.9	41.6	44.9
87.5°	22.0	20.1	20.3	19.9	20.0	19.7	18.7
90°	22.7	24.0	25.0	25.9	26.6	27.4	28.2
92.5°	50.2	51.9	53.1	53.6	54.2	54.8	55.3
95°	95.8	97.7	98.9	99.4	99.9	100.4	100.9
97.5°	149.1	150.8	151.8	152.1	152.4	152.7	153.0
100°	186.6	188.9	190.4	190.9	191.4	192.0	192.5
102.5°	224.8	227.3	228.9	229.7	230.5	231.2	231.9
105°	285.2	286.7	287.9	288.7	289.4	290.2	291.0
107.5°	350.6	351.4	351.8	351.7	351.7	351.6	351.5
110°	396.7	397.4	397.7	397.4	397.2	396.9	396.7



TEST NUMBER: P333287-840

CATALOG NUMBER: S125DIP-S1090D1205U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	442.3	442.7	442.6	442.2	441.7	441.2	440.8
115°	512.0	511.8	511.5	511.3	511.0	510.7	510.5
117.5°	582.9	583.1	582.7	581.7	580.7	579.6	578.6
120°	630.2	630.2	629.7	628.6	627.5	626.5	625.5
122.5°	676.5	676.3	675.8	674.9	674.1	673.3	672.5
125°	744.8	744.3	743.9	743.7	743.4	743.1	742.9
127.5°	813.1	812.9	812.5	812.0	811.4	810.9	810.4
130°	858.2	858.0	857.6	857.1	856.6	856.0	855.5
132.5°	901.4	901.1	900.7	899.9	899.2	898.5	897.8
135°	968.2	968.2	967.7	966.5	965.5	964.5	963.4
137.5°	1033.2	1033.5	1033.0	1031.7	1030.4	1029.1	1027.7
140°	1074.2	1074.7	1074.3	1073.0	1071.7	1070.4	1069.0
142.5°	1113.9	1114.2	1113.7	1112.4	1111.2	1109.8	1108.5
145°	1171.1	1171.1	1170.7	1170.0	1169.2	1168.4	1167.6
147.5°	1225.2	1225.8	1225.2	1223.5	1221.6	1219.9	1218.1
150°	1258.0	1258.0	1257.8	1257.2	1256.7	1256.2	1255.7
152.5°	1289.9	1290.5	1290.4	1289.5	1288.5	1287.6	1286.7
155°	1335.0	1336.2	1336.0	1334.6	1333.3	1332.1	1330.8
157.5°	1373.8	1374.8	1374.5	1372.8	1371.1	1369.4	1367.7
160°	1397.2	1398.3	1398.2	1396.8	1395.5	1394.2	1393.0
162.5°	1419.5	1420.8	1420.6	1419.1	1417.5	1416.0	1414.5
165°	1448.9	1450.0	1449.7	1448.1	1446.5	1445.0	1443.4
167.5°	1471.4	1472.9	1472.9	1471.3	1469.7	1468.0	1466.4
170°	1484.5	1486.0	1485.9	1484.1	1482.3	1480.5	1478.6
172.5°	1493.9	1495.4	1495.4	1493.8	1492.2	1490.6	1488.9
175°	1504.4	1506.0	1505.9	1504.1	1502.3	1500.4	1498.5
177.5°	1508.9	1510.2	1510.1	1508.6	1507.1	1505.7	1504.2
180°	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9	1507.9

(END OF REPORT)