

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333261-940

Luminaire Tested: **S125DIP-S1090D590U940-4F0-1E-UDD-A4**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P333261-940  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-19,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S125DIP-S1090D590U940-4F0-1E-UDD-A4  
Description: DEFINE 5 DIRECT-INDIRECT PENDANT LED LUMINAIRE  
DOWNLIGHT 1090 LUMENS PER FOOT, ASYMMETRIC DIFFUSER  
UPLIGHT 590 LUMENS PER FOOT, BATWING OPTIC  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5894.7 lumens  
Efficiency: N/A  
Efficacy: 120.8 lumens/watt  
Spacing Criteria (0/90/45): 1.43 / 1.23 / 1.52  
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')  
CIE Type: Semi-Direct


Input Watts (W): 48.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

### Luminous Intensity Polar Plot





TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20			20			20			20
RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	111	111	111	111	105	105	105	105	93	93	93	82	82	82	73	73	73	68
1	102	98	94	90	96	92	89	86	82	80	77	73	71	69	65	63	62	58
2	93	86	80	74	88	81	76	71	73	68	65	65	61	58	57	55	53	49
3	85	76	68	62	80	72	65	60	64	59	55	57	53	50	51	48	45	42
4	78	67	59	53	73	64	56	51	57	51	47	51	47	43	46	42	39	36
5	72	60	52	46	68	57	50	44	51	45	41	46	41	37	41	37	34	31
6	66	54	46	40	62	51	44	38	46	40	36	42	37	33	37	33	30	28
7	61	49	41	35	58	47	39	34	42	36	31	38	33	29	34	30	27	24
8	57	44	37	31	54	42	35	30	39	32	28	35	30	26	31	27	24	22
9	53	41	33	28	50	39	32	27	35	29	25	32	27	23	29	25	22	20
10	50	37	30	25	47	36	29	24	33	27	23	30	25	21	27	23	20	18

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	9158	9158	9158	9158
5°	10605	9189	8045	9189
10°	12338	9141	7050	9141
15°	13658	9074	6503	9074
20°	15289	8968	6064	8968
25°	17910	8848	5850	8848
30°	19345	8730	5665	8730
35°	15906	8508	5542	8508
40°	11306	8200	5409	8200
45°	8685	7784	5332	7784
50°	7414	7268	5322	7268
55°	6600	6764	5368	6764
60°	5955	6212	5504	6212
65°	5500	5656	5647	5656
70°	5000	5080	5729	5080
75°	4414	4474	5677	4474
80°	3715	3649	5192	3649
85°	2942	2631	4187	2631



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	136.5	2.3
10°-20°	406.4	6.9
20°-30°	660.0	11.2
30°-40°	805.0	13.7
40°-50°	732.3	12.4
50°-60°	583.3	9.9
60°-70°	406.3	6.9
70°-80°	216.7	3.7
80°-90°	56.1	1.0
90°-100°	182.9	3.1
100°-110°	393.1	6.7
110°-120°	369.0	6.3
120°-130°	299.0	5.1
130°-140°	240.0	4.1
140°-150°	181.1	3.1
150°-160°	127.5	2.2
160°-170°	75.1	1.3
170°-180°	24.4	0.4
0°-30°	1202.9	20.4
0°-40°	2008.0	34.1
0°-60°	3323.6	56.4
0°-90°	4002.7	67.9
90°-120°	945.0	16.0
90°-150°	1665.0	28.2
90°-180°	1892.0	32.1
0°-180°	5894.7	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1418	1418	1418	1418	1418	
5°	1636	1417	1241	1417	1636	165
15°	2043	1357	973	1357	2043	585
25°	2513	1242	821	1242	2513	1148
35°	2017	1079	703	1079	2017	1235
45°	951	852	584	852	951	761
55°	586	601	477	601	586	528
65°	360	370	370	370	360	357
75°	177	179	228	179	177	191
85°	40	36	56	36	40	46
90°	12	0	12	0	12	10
95°	120	17	120	17	120	169
105°	674	58	674	58	674	670
115°	751	103	751	103	751	734
125°	592	142	592	142	592	535
135°	491	167	491	167	491	381
145°	388	194	388	194	388	246
155°	325	222	325	222	325	151
165°	285	242	285	242	285	81
175°	256	252	256	252	256	25
180°	252	252	252	252	252	



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1499.9	1497.9	1496.0	1492.1	1495.0	1486.8	1483.0	1476.2	1468.0	1465.2	1461.8
5°	1635.8	1638.9	1641.9	1629.2	1630.4	1622.0	1602.8	1587.1	1574.5	1558.2	1546.8
7.5°	1799.6	1792.4	1791.9	1783.7	1769.6	1758.3	1738.0	1712.3	1687.4	1658.9	1635.5
10°	1881.4	1882.0	1876.6	1867.0	1851.9	1841.1	1814.6	1789.3	1758.6	1722.5	1696.7
12.5°	1943.0	1945.5	1938.8	1925.7	1918.3	1894.1	1873.4	1843.3	1806.8	1777.9	1738.6
15°	2042.7	2036.1	2031.3	2015.0	2002.4	1977.1	1944.0	1912.7	1872.9	1836.3	1799.6
17.5°	2138.8	2144.0	2135.0	2120.2	2081.0	2051.5	2007.1	1964.3	1914.8	1865.5	1821.7
20°	2224.5	2229.3	2215.5	2189.6	2142.6	2113.2	2054.8	1999.4	1942.2	1879.0	1830.9
22.5°	2331.4	2327.5	2308.8	2269.5	2228.8	2174.3	2111.1	2043.7	1972.0	1900.7	1836.7
25°	2513.4	2488.1	2476.6	2428.0	2374.4	2294.3	2207.6	2108.9	2019.8	1925.4	1843.5
27.5°	2614.2	2606.3	2593.5	2559.6	2503.3	2417.7	2315.5	2195.2	2069.6	1950.3	1843.2
30°	2594.0	2595.2	2596.4	2585.6	2549.5	2485.1	2383.4	2254.0	2104.7	1970.5	1846.5
32.5°	2414.9	2436.8	2457.7	2482.5	2492.7	2480.3	2416.6	2299.7	2146.1	1993.6	1844.6
35°	2017.4	2024.1	2092.0	2159.5	2250.9	2322.0	2369.5	2317.7	2188.3	2013.2	1842.3
37.5°	1573.1	1605.5	1652.6	1728.8	1860.8	1979.1	2131.1	2201.0	2159.3	2019.6	1838.1
40°	1341.0	1371.0	1401.8	1479.3	1590.7	1733.9	1906.7	2054.1	2088.5	1999.4	1823.6
42.5°	1161.8	1185.7	1219.8	1278.1	1371.2	1498.1	1663.0	1855.7	1974.3	1940.6	1793.3
45°	950.9	966.0	992.5	1038.8	1106.3	1205.5	1351.2	1561.8	1745.4	1806.2	1721.4
47.5°	814.0	813.9	834.5	866.5	915.1	999.4	1107.1	1272.2	1468.3	1613.4	1606.6
50°	737.9	734.9	751.1	778.8	817.3	873.3	976.2	1108.0	1296.4	1460.7	1506.5
52.5°	672.4	672.8	682.8	703.2	735.5	783.3	860.1	979.0	1140.0	1308.6	1394.7
55°	586.2	583.8	595.2	609.1	632.6	663.9	719.3	810.1	940.7	1106.8	1218.8
57.5°	507.2	513.9	518.4	528.1	547.6	568.6	615.2	681.9	785.5	928.1	1046.4
60°	461.0	467.6	471.3	480.9	496.5	514.6	550.7	604.8	692.1	814.9	932.3
62.5°	419.6	424.8	426.0	434.6	447.5	465.0	493.4	539.0	607.9	715.2	830.2
65°	359.9	359.9	362.3	371.3	377.4	393.0	414.6	447.8	503.2	586.8	684.9
67.5°	302.4	305.2	304.7	308.6	314.1	326.4	341.9	369.2	410.2	471.3	549.7
70°	264.8	267.2	266.6	269.7	275.6	283.5	296.1	322.0	351.5	403.9	471.3
72.5°	231.1	232.1	230.5	234.5	238.1	245.0	259.0	272.9	300.4	344.6	400.0
75°	176.9	178.2	179.3	181.7	185.4	189.0	196.2	210.1	228.1	261.2	296.8
77.5°	132.7	130.4	133.2	132.9	134.9	137.7	144.1	151.4	166.2	187.2	214.6
80°	99.9	100.5	100.5	101.1	104.2	105.9	111.4	116.7	128.2	143.8	163.1
82.5°	72.9	74.5	73.6	74.6	77.1	78.5	81.5	86.0	92.6	104.9	118.8
85°	39.7	36.7	37.9	39.1	39.1	39.7	42.1	44.0	47.5	52.3	57.8
87.5°	13.9	14.9	15.2	15.2	15.7	15.5	17.3	17.2	18.5	19.9	21.7
90°	11.7	11.7	11.1	11.1	11.1	10.2	9.6	9.2	8.6	8.1	7.1
92.5°	32.5	33.3	34.0	35.2	41.7	49.2	65.5	90.2	132.8	164.0	166.7
95°	119.6	127.7	131.7	147.0	183.2	225.9	288.4	365.7	441.0	450.7	367.7
97.5°	288.9	295.4	310.1	338.7	370.1	429.5	490.4	544.7	558.0	481.3	328.4
100°	396.7	404.9	423.7	460.3	495.4	548.3	600.7	625.6	586.5	459.3	293.0
102.5°	517.2	523.3	543.8	569.8	607.3	643.1	668.2	652.9	569.4	420.6	266.1
105°	674.0	680.1	690.3	707.0	723.3	728.9	706.5	636.9	514.8	368.8	240.0
107.5°	757.2	761.3	764.6	764.7	756.4	730.0	672.4	579.4	459.1	333.1	229.1
110°	784.9	784.9	781.3	771.6	748.8	705.5	633.8	537.2	427.3	316.4	225.9



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	781.6	777.9	769.1	752.5	719.1	668.1	595.6	503.8	403.7	306.7	225.9
115°	750.8	744.1	730.0	705.5	665.8	610.4	540.7	461.8	377.9	296.0	227.4
117.5°	696.8	692.7	678.6	653.4	613.7	562.8	502.7	434.8	362.6	290.9	230.7
120°	661.7	657.7	644.0	619.6	581.9	537.2	481.2	420.2	354.0	288.4	234.0
122.5°	630.8	627.1	613.4	591.0	557.5	515.6	465.7	409.2	346.7	286.4	236.8
125°	591.6	586.5	575.3	554.5	525.9	489.4	445.1	393.2	336.7	283.8	241.7
127.5°	558.0	555.7	545.2	526.7	501.0	466.6	425.3	376.9	327.6	282.6	247.0
130°	539.7	536.6	526.5	509.7	484.2	451.2	411.5	366.8	321.5	281.8	250.3
132.5°	521.4	517.9	508.5	491.8	466.4	434.5	398.5	356.6	316.6	281.8	254.0
135°	491.3	488.3	479.1	462.4	440.0	411.0	378.4	343.3	310.8	281.8	258.9
137.5°	459.3	455.9	447.5	432.2	412.2	387.6	360.5	332.2	305.6	282.4	263.5
140°	436.9	434.4	426.8	413.6	394.8	373.4	350.0	326.0	303.2	282.9	265.6
142.5°	416.2	414.0	406.8	395.7	379.7	361.1	341.0	320.7	301.1	283.2	266.7
145°	387.6	385.6	380.0	371.3	359.1	345.4	329.6	313.9	298.1	282.9	268.0
147.5°	363.4	362.5	359.2	352.3	342.6	332.3	320.1	307.4	294.9	281.5	268.6
150°	350.0	349.5	347.4	341.3	333.7	324.5	314.9	303.6	292.5	280.3	268.6
152.5°	339.4	338.9	336.8	332.0	325.6	318.4	309.6	299.6	289.6	278.7	268.1
155°	325.0	324.5	323.0	319.4	314.3	308.7	301.7	293.5	284.8	275.7	267.1
157.5°	312.2	312.3	310.9	307.9	304.0	299.6	294.1	287.4	280.4	272.6	265.7
160°	303.6	304.2	303.2	300.6	297.0	293.5	288.4	283.3	276.7	270.6	264.5
162.5°	296.0	296.0	295.9	293.7	291.0	287.8	283.6	278.8	273.5	268.1	263.3
165°	284.8	284.8	284.8	283.8	281.8	279.3	276.2	272.6	268.6	264.5	261.4
167.5°	274.6	274.7	275.2	274.3	273.2	271.4	269.1	266.7	263.8	260.9	258.6
170°	268.6	269.1	269.1	268.6	267.5	266.5	265.0	263.5	260.9	258.9	257.3
172.5°	262.9	263.4	264.2	263.3	263.1	262.4	261.4	259.8	258.1	256.5	255.7
175°	255.8	256.4	257.3	256.9	256.9	256.9	255.8	255.8	254.3	253.8	253.8
177.5°	252.3	252.3	253.5	253.1	253.5	253.5	253.5	253.1	252.7	252.3	252.3
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1458.9	1455.5	1451.7	1444.9	1436.7	1432.4	1425.7	1421.4	1412.6	1405.4	1397.8
5°	1532.9	1517.3	1502.9	1484.2	1463.7	1450.5	1434.9	1417.4	1399.4	1380.6	1360.2
7.5°	1609.6	1581.9	1551.8	1519.5	1487.8	1458.7	1430.8	1403.6	1378.0	1347.2	1321.1
10°	1661.2	1626.2	1588.9	1545.0	1502.3	1464.9	1427.0	1393.9	1360.2	1324.1	1292.2
12.5°	1712.6	1666.2	1613.5	1565.2	1513.8	1468.7	1424.2	1381.9	1339.5	1299.6	1262.3
15°	1749.0	1708.1	1659.3	1590.7	1532.9	1471.0	1411.9	1357.2	1306.0	1261.5	1214.6
17.5°	1773.0	1720.2	1667.9	1602.0	1526.3	1457.0	1390.2	1327.5	1269.8	1213.4	1168.1
20°	1777.3	1723.1	1668.4	1603.9	1526.3	1446.9	1380.1	1304.8	1242.9	1184.5	1129.1
22.5°	1775.8	1714.5	1654.8	1588.6	1512.9	1439.7	1358.9	1282.2	1215.0	1157.5	1099.7
25°	1762.3	1696.7	1622.0	1555.2	1480.6	1402.9	1321.1	1241.6	1173.0	1107.4	1050.3
27.5°	1751.0	1665.8	1581.4	1503.4	1431.4	1360.2	1281.8	1200.5	1124.4	1057.9	1004.1
30°	1737.0	1643.7	1548.5	1467.3	1393.3	1324.1	1250.1	1170.6	1091.2	1026.2	968.4
32.5°	1724.5	1615.8	1515.4	1426.9	1348.5	1281.2	1213.0	1137.4	1059.4	993.5	935.7
35°	1700.2	1574.5	1459.6	1359.6	1275.9	1206.8	1149.6	1079.1	1007.5	943.7	888.3
37.5°	1669.6	1520.3	1397.0	1292.2	1200.5	1127.6	1074.3	1020.3	951.5	890.0	840.0
40°	1645.5	1481.8	1351.2	1244.0	1149.0	1073.1	1023.8	972.6	915.4	858.3	805.3
42.5°	1615.2	1447.2	1304.9	1189.6	1095.5	1021.6	969.8	926.4	875.9	822.6	773.5
45°	1559.4	1384.3	1230.2	1106.3	1011.1	938.3	884.8	852.2	814.3	763.8	722.2
47.5°	1477.5	1308.8	1149.4	1021.5	923.4	855.9	805.7	774.5	747.8	710.2	672.5
50°	1404.7	1252.5	1091.2	964.2	866.1	798.1	751.7	723.4	700.5	671.6	639.8
52.5°	1323.4	1181.7	1033.8	908.3	811.2	744.1	698.7	673.9	654.8	634.1	602.7
55°	1194.1	1073.7	936.5	817.3	727.6	662.0	622.3	600.7	585.1	569.4	550.1
57.5°	1051.7	957.5	836.0	727.0	644.4	584.8	547.7	526.6	514.4	506.4	495.1
60°	951.5	870.9	766.2	666.8	586.2	533.2	497.1	480.9	470.6	464.0	455.6
62.5°	858.6	792.4	695.4	604.8	534.2	484.1	451.9	436.1	426.3	423.1	416.2
65°	721.7	670.5	590.4	515.2	455.0	412.2	385.2	370.1	364.1	360.5	361.1
67.5°	586.7	555.5	491.2	427.0	379.1	343.2	321.6	310.0	306.9	302.1	302.0
70°	504.4	480.9	426.7	370.8	328.0	300.3	281.1	269.0	266.0	263.6	263.1
72.5°	431.7	411.1	364.1	319.2	280.8	256.5	240.6	233.4	228.5	227.0	226.9
75°	324.4	313.0	275.6	240.1	213.7	196.8	186.0	179.3	175.8	175.1	175.8
77.5°	230.6	220.6	196.9	171.7	155.1	142.3	133.1	130.8	126.7	126.9	126.3
80°	173.3	166.7	151.7	131.8	118.0	107.1	102.3	98.1	96.9	95.1	96.9
82.5°	125.6	118.6	108.3	95.7	84.3	77.8	72.9	71.6	70.9	70.1	70.4
85°	62.0	62.6	56.5	46.9	42.1	38.5	35.5	35.5	34.9	34.3	34.9
87.5°	22.5	21.3	19.4	17.7	15.1	13.4	12.8	13.1	11.8	11.5	12.1
90°	6.6	5.6	5.1	4.1	3.0	2.1	1.0	0.5	1.0	2.1	3.0
92.5°	116.1	69.5	41.7	26.8	18.1	11.8	7.5	6.2	7.5	11.8	18.1
95°	227.4	115.5	61.1	38.2	26.9	21.4	17.3	16.8	17.3	21.4	26.9
97.5°	181.5	99.5	63.5	47.0	36.9	31.3	28.4	27.9	28.4	31.3	36.9
100°	164.8	98.7	69.2	53.9	44.2	38.7	36.6	35.6	36.6	38.7	44.2
102.5°	157.9	102.4	76.1	61.3	52.4	46.4	44.8	44.1	44.8	46.4	52.4
105°	155.2	109.9	87.5	73.2	65.1	60.0	57.5	57.5	57.5	60.0	65.1
107.5°	159.8	121.1	99.4	86.6	78.1	73.9	71.5	70.5	71.5	73.9	78.1
110°	164.3	129.2	108.3	95.1	87.5	82.9	80.9	79.9	80.9	82.9	87.5





TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	170.0	137.0	116.9	104.1	96.5	91.8	90.2	89.3	90.2	91.8	96.5
115°	178.5	149.0	130.2	117.5	109.9	105.3	103.8	102.7	103.8	105.3	109.9
117.5°	188.3	161.5	143.7	131.3	122.7	118.2	116.5	114.9	116.5	118.2	122.7
120°	194.8	170.4	152.6	139.9	131.3	126.6	124.7	123.1	124.7	126.6	131.3
122.5°	202.2	179.0	161.1	148.5	138.9	134.4	132.8	131.6	132.8	134.4	138.9
125°	212.1	190.2	173.4	160.2	150.5	146.0	143.5	142.4	143.5	146.0	150.5
127.5°	221.2	201.1	184.9	171.7	161.5	155.7	152.4	150.9	152.4	155.7	161.5
130°	227.4	208.0	192.3	179.1	168.4	161.8	157.7	156.1	157.7	161.8	168.4
132.5°	232.6	214.5	198.8	185.6	174.5	167.0	162.2	160.2	162.2	167.0	174.5
135°	240.0	223.3	207.5	193.8	183.2	175.0	168.9	166.8	168.9	175.0	183.2
137.5°	245.6	229.5	215.2	201.0	190.6	182.4	176.7	175.2	176.7	182.4	190.6
140°	249.2	234.0	219.3	205.5	195.8	187.7	181.6	180.0	181.6	187.7	195.8
142.5°	251.3	236.8	222.9	210.0	200.7	192.6	186.9	185.7	186.9	192.6	200.7
145°	254.3	241.7	228.4	216.7	207.5	200.4	195.3	194.3	195.3	200.4	207.5
147.5°	256.2	244.7	233.1	222.7	214.8	208.2	203.8	203.2	203.8	208.2	214.8
150°	257.3	246.7	235.5	226.9	219.7	213.1	209.6	208.6	209.6	213.1	219.7
152.5°	258.2	248.7	238.4	230.5	223.8	218.0	214.8	214.3	214.8	218.0	223.8
155°	258.9	250.7	242.1	235.0	229.9	224.8	221.8	221.8	221.8	224.8	229.9
157.5°	259.4	252.5	245.0	239.7	235.2	230.9	228.4	228.5	228.4	230.9	235.2
160°	259.4	253.3	246.7	242.1	238.1	234.5	232.5	233.0	232.5	234.5	238.1
162.5°	259.0	254.1	248.3	244.6	241.3	238.2	236.1	236.7	236.1	238.2	241.3
165°	258.4	254.3	250.3	247.2	245.1	242.6	241.1	242.1	241.1	242.6	245.1
167.5°	257.2	254.3	250.9	249.1	247.6	246.2	245.3	245.8	245.3	246.2	247.6
170°	256.4	254.3	251.8	250.3	249.2	248.3	247.7	248.3	247.7	248.3	249.2
172.5°	255.6	254.0	251.8	251.1	250.5	249.4	249.0	249.9	249.0	249.4	250.5
175°	254.3	253.3	251.8	251.8	251.8	251.3	250.7	251.8	250.7	251.3	251.8
177.5°	253.1	252.7	251.9	251.9	252.3	251.9	251.9	252.7	251.9	251.9	252.3
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1393.4	1388.1	1383.8	1374.1	1368.9	1361.6	1355.8	1362.1	1355.4	1358.3	1354.0
5°	1350.0	1333.1	1321.1	1303.6	1288.6	1274.7	1264.5	1262.7	1257.8	1255.4	1248.2
7.5°	1297.7	1276.7	1256.0	1233.1	1213.8	1194.2	1181.7	1171.4	1164.5	1155.5	1149.3
10°	1266.9	1238.6	1214.6	1186.9	1162.8	1141.7	1124.9	1116.4	1108.7	1097.2	1093.0
12.5°	1228.9	1199.6	1170.3	1140.7	1117.5	1094.0	1079.6	1066.8	1061.4	1048.6	1047.2
15°	1183.3	1139.3	1110.4	1080.3	1048.5	1029.2	1017.2	1003.3	997.3	988.3	981.6
17.5°	1128.8	1089.6	1053.5	1022.3	995.0	978.7	963.9	954.3	944.0	938.1	927.2
20°	1089.4	1052.0	1015.9	982.8	961.8	943.1	931.0	922.0	911.2	908.2	897.4
22.5°	1056.1	1014.9	980.3	952.5	929.5	908.5	895.5	889.3	881.8	872.5	870.4
25°	1002.1	959.4	929.9	902.2	881.7	862.5	853.5	845.6	838.4	831.8	829.4
27.5°	955.4	917.2	882.2	857.2	839.4	821.8	813.9	804.3	799.1	793.7	787.2
30°	922.7	883.5	852.8	828.8	809.5	793.9	785.4	778.8	774.0	769.2	765.5
32.5°	888.9	852.7	823.0	799.4	780.2	768.3	760.9	756.2	750.9	745.1	740.6
35°	844.5	804.7	775.8	755.4	740.3	731.3	722.8	718.6	712.6	712.6	707.8
37.5°	794.2	759.9	734.4	715.8	702.2	694.2	685.0	682.2	678.3	675.7	674.0
40°	764.4	732.5	708.4	689.7	675.3	668.7	661.5	656.7	654.2	651.2	650.0
42.5°	733.5	703.1	680.0	662.8	650.2	644.6	637.8	634.5	629.6	625.7	625.0
45°	686.7	657.2	636.1	622.3	611.4	604.8	600.7	593.4	591.0	586.2	585.6
47.5°	642.3	614.0	593.3	582.0	572.5	567.0	560.4	553.2	550.5	548.0	547.8
50°	609.1	583.2	563.9	553.1	544.1	536.3	529.7	524.9	523.0	523.0	524.2
52.5°	575.4	553.3	537.0	523.7	515.2	506.8	500.8	497.8	495.1	498.0	500.2
55°	526.0	503.7	491.7	479.1	470.6	461.0	458.0	456.8	455.0	459.9	462.3
57.5°	473.8	458.2	444.1	431.5	423.9	418.4	414.3	413.6	417.0	419.3	427.0
60°	440.6	422.5	409.8	400.2	391.2	387.6	386.4	385.2	387.6	394.2	404.5
62.5°	403.9	389.3	375.7	368.5	361.9	355.8	355.6	356.3	361.1	368.7	378.9
65°	350.3	337.6	328.6	320.2	314.8	311.1	312.4	314.8	320.2	330.4	341.9
67.5°	295.8	287.1	279.0	272.2	267.0	267.0	268.2	271.8	278.2	290.0	300.4
70°	260.6	251.0	244.3	241.4	237.1	234.7	238.4	244.3	249.8	260.6	269.7
72.5°	225.4	217.3	212.1	210.1	208.2	206.3	207.5	214.0	221.3	232.2	242.6
75°	173.3	170.3	166.7	164.3	162.5	163.7	164.9	170.9	176.9	188.4	200.5
77.5°	126.5	123.4	121.2	120.6	119.7	120.3	123.6	128.0	133.9	142.3	151.4
80°	95.7	94.5	93.3	92.6	92.6	93.3	98.1	101.1	106.6	114.3	121.5
82.5°	69.7	68.9	68.8	68.6	69.1	69.2	72.1	76.1	80.5	86.4	92.6
85°	36.7	35.5	37.3	37.9	36.7	38.5	39.7	42.1	44.0	46.9	49.9
87.5°	12.8	14.0	13.6	14.4	14.4	15.6	15.2	17.2	18.3	19.4	19.1
90°	4.1	5.1	5.6	6.6	7.1	8.1	8.6	9.2	9.6	10.2	11.1
92.5°	26.8	41.7	69.5	116.1	166.7	164.0	132.8	90.2	65.5	49.2	41.7
95°	38.2	61.1	115.5	227.4	367.7	450.7	441.0	365.7	288.4	225.9	183.2
97.5°	47.0	63.5	99.5	181.5	328.4	481.3	558.0	544.7	490.4	429.5	370.1
100°	53.9	69.2	98.7	164.8	293.0	459.3	586.5	625.6	600.7	548.3	495.4
102.5°	61.3	76.1	102.4	157.9	266.1	420.6	569.4	652.9	668.2	643.1	607.3
105°	73.2	87.5	109.9	155.2	240.0	368.8	514.8	636.9	706.5	728.9	723.3
107.5°	86.6	99.4	121.1	159.8	229.1	333.1	459.1	579.4	672.4	730.0	756.4
110°	95.1	108.3	129.2	164.3	225.9	316.4	427.3	537.2	633.8	705.5	748.8



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	104.1	116.9	137.0	170.0	225.9	306.7	403.7	503.8	595.6	668.1	719.1
115°	117.5	130.2	149.0	178.5	227.4	296.0	377.9	461.8	540.7	610.4	665.8
117.5°	131.3	143.7	161.5	188.3	230.7	290.9	362.6	434.8	502.7	562.8	613.7
120°	139.9	152.6	170.4	194.8	234.0	288.4	354.0	420.2	481.2	537.2	581.9
122.5°	148.5	161.1	179.0	202.2	236.8	286.4	346.7	409.2	465.7	515.6	557.5
125°	160.2	173.4	190.2	212.1	241.7	283.8	336.7	393.2	445.1	489.4	525.9
127.5°	171.7	184.9	201.1	221.2	247.0	282.6	327.6	376.9	425.3	466.6	501.0
130°	179.1	192.3	208.0	227.4	250.3	281.8	321.5	366.8	411.5	451.2	484.2
132.5°	185.6	198.8	214.5	232.6	254.0	281.8	316.6	356.6	398.5	434.5	466.4
135°	193.8	207.5	223.3	240.0	258.9	281.8	310.8	343.3	378.4	411.0	440.0
137.5°	201.0	215.2	229.5	245.6	263.5	282.4	305.6	332.2	360.5	387.6	412.2
140°	205.5	219.3	234.0	249.2	265.6	282.9	303.2	326.0	350.0	373.4	394.8
142.5°	210.0	222.9	236.8	251.3	266.7	283.2	301.1	320.7	341.0	361.1	379.7
145°	216.7	228.4	241.7	254.3	268.0	282.9	298.1	313.9	329.6	345.4	359.1
147.5°	222.7	233.1	244.7	256.2	268.6	281.5	294.9	307.4	320.1	332.3	342.6
150°	226.9	235.5	246.7	257.3	268.6	280.3	292.5	303.6	314.9	324.5	333.7
152.5°	230.5	238.4	248.7	258.2	268.1	278.7	289.6	299.6	309.6	318.4	325.6
155°	235.0	242.1	250.7	258.9	267.1	275.7	284.8	293.5	301.7	308.7	314.3
157.5°	239.7	245.0	252.5	259.4	265.7	272.6	280.4	287.4	294.1	299.6	304.0
160°	242.1	246.7	253.3	259.4	264.5	270.6	276.7	283.3	288.4	293.5	297.0
162.5°	244.6	248.3	254.1	259.0	263.3	268.1	273.5	278.8	283.6	287.8	291.0
165°	247.2	250.3	254.3	258.4	261.4	264.5	268.6	272.6	276.2	279.3	281.8
167.5°	249.1	250.9	254.3	257.2	258.6	260.9	263.8	266.7	269.1	271.4	273.2
170°	250.3	251.8	254.3	256.4	257.3	258.9	260.9	263.5	265.0	266.5	267.5
172.5°	251.1	251.8	254.0	255.6	255.7	256.5	258.1	259.8	261.4	262.4	263.1
175°	251.8	251.8	253.3	254.3	253.8	253.8	254.3	255.8	255.8	256.9	256.9
177.5°	251.9	251.9	252.7	253.1	252.3	252.3	252.7	253.1	253.5	253.5	253.5
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1351.0	1354.4	1351.6	1355.4	1351.6	1354.4	1351.0	1354.0	1358.3	1355.4	1362.1
5°	1245.3	1239.8	1243.4	1241.0	1243.4	1239.8	1245.3	1248.2	1255.4	1257.8	1262.7
7.5°	1147.5	1142.4	1136.4	1133.6	1136.4	1142.4	1147.5	1149.3	1155.5	1164.5	1171.4
10°	1086.4	1079.8	1079.1	1075.0	1079.1	1079.8	1086.4	1093.0	1097.2	1108.7	1116.4
12.5°	1041.6	1035.5	1028.6	1026.8	1028.6	1035.5	1041.6	1047.2	1048.6	1061.4	1066.8
15°	978.0	973.2	969.0	972.6	969.0	973.2	978.0	981.6	988.3	997.3	1003.3
17.5°	925.1	921.2	920.5	916.1	920.5	921.2	925.1	927.2	938.1	944.0	954.3
20°	892.0	888.9	890.2	882.3	890.2	888.9	892.0	897.4	908.2	911.2	922.0
22.5°	865.5	859.6	858.9	857.3	858.9	859.6	865.5	870.4	872.5	881.8	889.3
25°	823.9	820.9	818.0	820.9	818.0	820.9	823.9	829.4	831.8	838.4	845.6
27.5°	787.7	784.1	783.3	783.6	783.3	784.1	787.7	787.2	793.7	799.1	804.3
30°	765.5	759.6	760.2	759.6	760.2	759.6	765.5	765.5	769.2	774.0	778.8
32.5°	741.5	737.4	736.6	735.5	736.6	737.4	741.5	740.6	745.1	750.9	756.2
35°	706.0	706.0	702.9	702.9	702.9	706.0	706.0	707.8	712.6	712.6	718.6
37.5°	672.6	672.0	670.2	670.5	670.2	672.0	672.6	674.0	675.7	678.3	682.2
40°	647.6	647.0	645.2	641.6	645.2	647.0	647.6	650.0	651.2	654.2	656.7
42.5°	623.5	621.5	620.6	619.5	620.6	621.5	623.5	625.0	625.7	629.6	634.5
45°	585.6	585.6	584.4	583.8	584.4	585.6	585.6	585.6	586.2	591.0	593.4
47.5°	548.8	549.8	552.1	551.8	552.1	549.8	548.8	547.8	548.0	550.5	553.2
50°	526.6	527.3	529.1	529.7	529.1	527.3	526.6	524.2	523.0	523.0	524.9
52.5°	502.0	505.6	507.8	507.5	507.8	505.6	502.0	500.2	498.0	495.1	497.8
55°	467.6	471.9	476.1	476.7	476.1	471.9	467.6	462.3	459.9	455.0	456.8
57.5°	433.5	439.4	443.9	445.4	443.9	439.4	433.5	427.0	419.3	417.0	413.6
60°	410.5	418.3	423.7	426.1	423.7	418.3	410.5	404.5	394.2	387.6	385.2
62.5°	388.3	397.1	402.5	403.0	402.5	397.1	388.3	378.9	368.7	361.1	356.3
65°	352.0	361.1	366.0	369.5	366.0	361.1	352.0	341.9	330.4	320.2	314.8
67.5°	313.1	322.1	327.4	330.3	327.4	322.1	313.1	300.4	290.0	278.2	271.8
70°	284.7	293.7	301.0	303.4	301.0	293.7	284.7	269.7	260.6	249.8	244.3
72.5°	256.7	264.8	270.6	273.5	270.6	264.8	256.7	242.6	232.2	221.3	214.0
75°	208.2	219.1	224.5	227.5	224.5	219.1	208.2	200.5	188.4	176.9	170.9
77.5°	160.6	170.4	173.7	175.2	173.7	170.4	160.6	151.4	142.3	133.9	128.0
80°	128.8	134.8	139.0	139.6	139.0	134.8	128.8	121.5	114.3	106.6	101.1
82.5°	99.0	104.0	105.3	106.9	105.3	104.0	99.0	92.6	86.4	80.5	76.1
85°	54.1	56.5	57.2	56.5	57.2	56.5	54.1	49.9	46.9	44.0	42.1
87.5°	20.1	19.5	19.7	20.6	19.7	19.5	20.1	19.1	19.4	18.3	17.2
90°	11.1	11.1	11.7	11.7	11.7	11.1	11.1	11.1	10.2	9.6	9.2
92.5°	35.2	34.0	33.3	32.5	33.3	34.0	35.2	41.7	49.2	65.5	90.2
95°	147.0	131.7	127.7	119.6	127.7	131.7	147.0	183.2	225.9	288.4	365.7
97.5°	338.7	310.1	295.4	288.9	295.4	310.1	338.7	370.1	429.5	490.4	544.7
100°	460.3	423.7	404.9	396.7	404.9	423.7	460.3	495.4	548.3	600.7	625.6
102.5°	569.8	543.8	523.3	517.2	523.3	543.8	569.8	607.3	643.1	668.2	652.9
105°	707.0	690.3	680.1	674.0	680.1	690.3	707.0	723.3	728.9	706.5	636.9
107.5°	764.7	764.6	761.3	757.2	761.3	764.6	764.7	756.4	730.0	672.4	579.4
110°	771.6	781.3	784.9	784.9	784.9	781.3	771.6	748.8	705.5	633.8	537.2



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	752.5	769.1	777.9	781.6	777.9	769.1	752.5	719.1	668.1	595.6	503.8
115°	705.5	730.0	744.1	750.8	744.1	730.0	705.5	665.8	610.4	540.7	461.8
117.5°	653.4	678.6	692.7	696.8	692.7	678.6	653.4	613.7	562.8	502.7	434.8
120°	619.6	644.0	657.7	661.7	657.7	644.0	619.6	581.9	537.2	481.2	420.2
122.5°	591.0	613.4	627.1	630.8	627.1	613.4	591.0	557.5	515.6	465.7	409.2
125°	554.5	575.3	586.5	591.6	586.5	575.3	554.5	525.9	489.4	445.1	393.2
127.5°	526.7	545.2	555.7	558.0	555.7	545.2	526.7	501.0	466.6	425.3	376.9
130°	509.7	526.5	536.6	539.7	536.6	526.5	509.7	484.2	451.2	411.5	366.8
132.5°	491.8	508.5	517.9	521.4	517.9	508.5	491.8	466.4	434.5	398.5	356.6
135°	462.4	479.1	488.3	491.3	488.3	479.1	462.4	440.0	411.0	378.4	343.3
137.5°	432.2	447.5	455.9	459.3	455.9	447.5	432.2	412.2	387.6	360.5	332.2
140°	413.6	426.8	434.4	436.9	434.4	426.8	413.6	394.8	373.4	350.0	326.0
142.5°	395.7	406.8	414.0	416.2	414.0	406.8	395.7	379.7	361.1	341.0	320.7
145°	371.3	380.0	385.6	387.6	385.6	380.0	371.3	359.1	345.4	329.6	313.9
147.5°	352.3	359.2	362.5	363.4	362.5	359.2	352.3	342.6	332.3	320.1	307.4
150°	341.3	347.4	349.5	350.0	349.5	347.4	341.3	333.7	324.5	314.9	303.6
152.5°	332.0	336.8	338.9	339.4	338.9	336.8	332.0	325.6	318.4	309.6	299.6
155°	319.4	323.0	324.5	325.0	324.5	323.0	319.4	314.3	308.7	301.7	293.5
157.5°	307.9	310.9	312.3	312.2	312.3	310.9	307.9	304.0	299.6	294.1	287.4
160°	300.6	303.2	304.2	303.6	304.2	303.2	300.6	297.0	293.5	288.4	283.3
162.5°	293.7	295.9	296.0	296.0	296.0	295.9	293.7	291.0	287.8	283.6	278.8
165°	283.8	284.8	284.8	284.8	284.8	284.8	283.8	281.8	279.3	276.2	272.6
167.5°	274.3	275.2	274.7	274.6	274.7	275.2	274.3	273.2	271.4	269.1	266.7
170°	268.6	269.1	269.1	268.6	269.1	269.1	268.6	267.5	266.5	265.0	263.5
172.5°	263.3	264.2	263.4	262.9	263.4	264.2	263.3	263.1	262.4	261.4	259.8
175°	256.9	257.3	256.4	255.8	256.4	257.3	256.9	256.9	256.9	255.8	255.8
177.5°	253.1	253.5	252.3	252.3	252.3	253.5	253.1	253.5	253.5	253.5	253.1
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1355.8	1361.6	1368.9	1374.1	1383.8	1388.1	1393.4	1397.8	1405.4	1412.6	1421.4
5°	1264.5	1274.7	1288.6	1303.6	1321.1	1333.1	1350.0	1360.2	1380.6	1399.4	1417.4
7.5°	1181.7	1194.2	1213.8	1233.1	1256.0	1276.7	1297.7	1321.1	1347.2	1378.0	1403.6
10°	1124.9	1141.7	1162.8	1186.9	1214.6	1238.6	1266.9	1292.2	1324.1	1360.2	1393.9
12.5°	1079.6	1094.0	1117.5	1140.7	1170.3	1199.6	1228.9	1262.3	1299.6	1339.5	1381.9
15°	1017.2	1029.2	1048.5	1080.3	1110.4	1139.3	1183.3	1214.6	1261.5	1306.0	1357.2
17.5°	963.9	978.7	995.0	1022.3	1053.5	1089.6	1128.8	1168.1	1213.4	1269.8	1327.5
20°	931.0	943.1	961.8	982.8	1015.9	1052.0	1089.4	1129.1	1184.5	1242.9	1304.8
22.5°	895.5	908.5	929.5	952.5	980.3	1014.9	1056.1	1099.7	1157.5	1215.0	1282.2
25°	853.5	862.5	881.7	902.2	929.9	959.4	1002.1	1050.3	1107.4	1173.0	1241.6
27.5°	813.9	821.8	839.4	857.2	882.2	917.2	955.4	1004.1	1057.9	1124.4	1200.5
30°	785.4	793.9	809.5	828.8	852.8	883.5	922.7	968.4	1026.2	1091.2	1170.6
32.5°	760.9	768.3	780.2	799.4	823.0	852.7	888.9	935.7	993.5	1059.4	1137.4
35°	722.8	731.3	740.3	755.4	775.8	804.7	844.5	888.3	943.7	1007.5	1079.1
37.5°	685.0	694.2	702.2	715.8	734.4	759.9	794.2	840.0	890.0	951.5	1020.3
40°	661.5	668.7	675.3	689.7	708.4	732.5	764.4	805.3	858.3	915.4	972.6
42.5°	637.8	644.6	650.2	662.8	680.0	703.1	733.5	773.5	822.6	875.9	926.4
45°	600.7	604.8	611.4	622.3	636.1	657.2	686.7	722.2	763.8	814.3	852.2
47.5°	560.4	567.0	572.5	582.0	593.3	614.0	642.3	672.5	710.2	747.8	774.5
50°	529.7	536.3	544.1	553.1	563.9	583.2	609.1	639.8	671.6	700.5	723.4
52.5°	500.8	506.8	515.2	523.7	537.0	553.3	575.4	602.7	634.1	654.8	673.9
55°	458.0	461.0	470.6	479.1	491.7	503.7	526.0	550.1	569.4	585.1	600.7
57.5°	414.3	418.4	423.9	431.5	444.1	458.2	473.8	495.1	506.4	514.4	526.6
60°	386.4	387.6	391.2	400.2	409.8	422.5	440.6	455.6	464.0	470.6	480.9
62.5°	355.6	355.8	361.9	368.5	375.7	389.3	403.9	416.2	423.1	426.3	436.1
65°	312.4	311.1	314.8	320.2	328.6	337.6	350.3	361.1	360.5	364.1	370.1
67.5°	268.2	267.0	267.0	272.2	279.0	287.1	295.8	302.0	302.1	306.9	310.0
70°	238.4	234.7	237.1	241.4	244.3	251.0	260.6	263.1	263.6	266.0	269.0
72.5°	207.5	206.3	208.2	210.1	212.1	217.3	225.4	226.9	227.0	228.5	233.4
75°	164.9	163.7	162.5	164.3	166.7	170.3	173.3	175.8	175.1	175.8	179.3
77.5°	123.6	120.3	119.7	120.6	121.2	123.4	126.5	126.3	126.9	126.7	130.8
80°	98.1	93.3	92.6	92.6	93.3	94.5	95.7	96.9	95.1	96.9	98.1
82.5°	72.1	69.2	69.1	68.6	68.8	68.9	69.7	70.4	70.1	70.9	71.6
85°	39.7	38.5	36.7	37.9	37.3	35.5	36.7	34.9	34.3	34.9	35.5
87.5°	15.2	15.6	14.4	14.4	13.6	14.0	12.8	12.1	11.5	11.8	13.1
90°	8.6	8.1	7.1	6.6	5.6	5.1	4.1	3.0	2.1	1.0	0.5
92.5°	132.8	164.0	166.7	116.1	69.5	41.7	26.8	18.1	11.8	7.5	6.2
95°	441.0	450.7	367.7	227.4	115.5	61.1	38.2	26.9	21.4	17.3	16.8
97.5°	558.0	481.3	328.4	181.5	99.5	63.5	47.0	36.9	31.3	28.4	27.9
100°	586.5	459.3	293.0	164.8	98.7	69.2	53.9	44.2	38.7	36.6	35.6
102.5°	569.4	420.6	266.1	157.9	102.4	76.1	61.3	52.4	46.4	44.8	44.1
105°	514.8	368.8	240.0	155.2	109.9	87.5	73.2	65.1	60.0	57.5	57.5
107.5°	459.1	333.1	229.1	159.8	121.1	99.4	86.6	78.1	73.9	71.5	70.5
110°	427.3	316.4	225.9	164.3	129.2	108.3	95.1	87.5	82.9	80.9	79.9



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	403.7	306.7	225.9	170.0	137.0	116.9	104.1	96.5	91.8	90.2	89.3
115°	377.9	296.0	227.4	178.5	149.0	130.2	117.5	109.9	105.3	103.8	102.7
117.5°	362.6	290.9	230.7	188.3	161.5	143.7	131.3	122.7	118.2	116.5	114.9
120°	354.0	288.4	234.0	194.8	170.4	152.6	139.9	131.3	126.6	124.7	123.1
122.5°	346.7	286.4	236.8	202.2	179.0	161.1	148.5	138.9	134.4	132.8	131.6
125°	336.7	283.8	241.7	212.1	190.2	173.4	160.2	150.5	146.0	143.5	142.4
127.5°	327.6	282.6	247.0	221.2	201.1	184.9	171.7	161.5	155.7	152.4	150.9
130°	321.5	281.8	250.3	227.4	208.0	192.3	179.1	168.4	161.8	157.7	156.1
132.5°	316.6	281.8	254.0	232.6	214.5	198.8	185.6	174.5	167.0	162.2	160.2
135°	310.8	281.8	258.9	240.0	223.3	207.5	193.8	183.2	175.0	168.9	166.8
137.5°	305.6	282.4	263.5	245.6	229.5	215.2	201.0	190.6	182.4	176.7	175.2
140°	303.2	282.9	265.6	249.2	234.0	219.3	205.5	195.8	187.7	181.6	180.0
142.5°	301.1	283.2	266.7	251.3	236.8	222.9	210.0	200.7	192.6	186.9	185.7
145°	298.1	282.9	268.0	254.3	241.7	228.4	216.7	207.5	200.4	195.3	194.3
147.5°	294.9	281.5	268.6	256.2	244.7	233.1	222.7	214.8	208.2	203.8	203.2
150°	292.5	280.3	268.6	257.3	246.7	235.5	226.9	219.7	213.1	209.6	208.6
152.5°	289.6	278.7	268.1	258.2	248.7	238.4	230.5	223.8	218.0	214.8	214.3
155°	284.8	275.7	267.1	258.9	250.7	242.1	235.0	229.9	224.8	221.8	221.8
157.5°	280.4	272.6	265.7	259.4	252.5	245.0	239.7	235.2	230.9	228.4	228.5
160°	276.7	270.6	264.5	259.4	253.3	246.7	242.1	238.1	234.5	232.5	233.0
162.5°	273.5	268.1	263.3	259.0	254.1	248.3	244.6	241.3	238.2	236.1	236.7
165°	268.6	264.5	261.4	258.4	254.3	250.3	247.2	245.1	242.6	241.1	242.1
167.5°	263.8	260.9	258.6	257.2	254.3	250.9	249.1	247.6	246.2	245.3	245.8
170°	260.9	258.9	257.3	256.4	254.3	251.8	250.3	249.2	248.3	247.7	248.3
172.5°	258.1	256.5	255.7	255.6	254.0	251.8	251.1	250.5	249.4	249.0	249.9
175°	254.3	253.8	253.8	254.3	253.3	251.8	251.8	251.8	251.3	250.7	251.8
177.5°	252.7	252.3	252.3	253.1	252.7	251.9	251.9	252.3	251.9	251.9	252.7
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1425.7	1432.4	1436.7	1444.9	1451.7	1455.5	1458.9	1461.8	1465.2	1468.0	1476.2
5°	1434.9	1450.5	1463.7	1484.2	1502.9	1517.3	1532.9	1546.8	1558.2	1574.5	1587.1
7.5°	1430.8	1458.7	1487.8	1519.5	1551.8	1581.9	1609.6	1635.5	1658.9	1687.4	1712.3
10°	1427.0	1464.9	1502.3	1545.0	1588.9	1626.2	1661.2	1696.7	1722.5	1758.6	1789.3
12.5°	1424.2	1468.7	1513.8	1565.2	1613.5	1666.2	1712.6	1738.6	1777.9	1806.8	1843.3
15°	1411.9	1471.0	1532.9	1590.7	1659.3	1708.1	1749.0	1799.6	1836.3	1872.9	1912.7
17.5°	1390.2	1457.0	1526.3	1602.0	1667.9	1720.2	1773.0	1821.7	1865.5	1914.8	1964.3
20°	1380.1	1446.9	1526.3	1603.9	1668.4	1723.1	1777.3	1830.9	1879.0	1942.2	1999.4
22.5°	1358.9	1439.7	1512.9	1588.6	1654.8	1714.5	1775.8	1836.7	1900.7	1972.0	2043.7
25°	1321.1	1402.9	1480.6	1555.2	1622.0	1696.7	1762.3	1843.5	1925.4	2019.8	2108.9
27.5°	1281.8	1360.2	1431.4	1503.4	1581.4	1665.8	1751.0	1843.2	1950.3	2069.6	2195.2
30°	1250.1	1324.1	1393.3	1467.3	1548.5	1643.7	1737.0	1846.5	1970.5	2104.7	2254.0
32.5°	1213.0	1281.2	1348.5	1426.9	1515.4	1615.8	1724.5	1844.6	1993.6	2146.1	2299.7
35°	1149.6	1206.8	1275.9	1359.6	1459.6	1574.5	1700.2	1842.3	2013.2	2188.3	2317.7
37.5°	1074.3	1127.6	1200.5	1292.2	1397.0	1520.3	1669.6	1838.1	2019.6	2159.3	2201.0
40°	1023.8	1073.1	1149.0	1244.0	1351.2	1481.8	1645.5	1823.6	1999.4	2088.5	2054.1
42.5°	969.8	1021.6	1095.5	1189.6	1304.9	1447.2	1615.2	1793.3	1940.6	1974.3	1855.7
45°	884.8	938.3	1011.1	1106.3	1230.2	1384.3	1559.4	1721.4	1806.2	1745.4	1561.8
47.5°	805.7	855.9	923.4	1021.5	1149.4	1308.8	1477.5	1606.6	1613.4	1468.3	1272.2
50°	751.7	798.1	866.1	964.2	1091.2	1252.5	1404.7	1506.5	1460.7	1296.4	1108.0
52.5°	698.7	744.1	811.2	908.3	1033.8	1181.7	1323.4	1394.7	1308.6	1140.0	979.0
55°	622.3	662.0	727.6	817.3	936.5	1073.7	1194.1	1218.8	1106.8	940.7	810.1
57.5°	547.7	584.8	644.4	727.0	836.0	957.5	1051.7	1046.4	928.1	785.5	681.9
60°	497.1	533.2	586.2	666.8	766.2	870.9	951.5	932.3	814.9	692.1	604.8
62.5°	451.9	484.1	534.2	604.8	695.4	792.4	858.6	830.2	715.2	607.9	539.0
65°	385.2	412.2	455.0	515.2	590.4	670.5	721.7	684.9	586.8	503.2	447.8
67.5°	321.6	343.2	379.1	427.0	491.2	555.5	586.7	549.7	471.3	410.2	369.2
70°	281.1	300.3	328.0	370.8	426.7	480.9	504.4	471.3	403.9	351.5	322.0
72.5°	240.6	256.5	280.8	319.2	364.1	411.1	431.7	400.0	344.6	300.4	272.9
75°	186.0	196.8	213.7	240.1	275.6	313.0	324.4	296.8	261.2	228.1	210.1
77.5°	133.1	142.3	155.1	171.7	196.9	220.6	230.6	214.6	187.2	166.2	151.4
80°	102.3	107.1	118.0	131.8	151.7	166.7	173.3	163.1	143.8	128.2	116.7
82.5°	72.9	77.8	84.3	95.7	108.3	118.6	125.6	118.8	104.9	92.6	86.0
85°	35.5	38.5	42.1	46.9	56.5	62.6	62.0	57.8	52.3	47.5	44.0
87.5°	12.8	13.4	15.1	17.7	19.4	21.3	22.5	21.7	19.9	18.5	17.2
90°	1.0	2.1	3.0	4.1	5.1	5.6	6.6	7.1	8.1	8.6	9.2
92.5°	7.5	11.8	18.1	26.8	41.7	69.5	116.1	166.7	164.0	132.8	90.2
95°	17.3	21.4	26.9	38.2	61.1	115.5	227.4	367.7	450.7	441.0	365.7
97.5°	28.4	31.3	36.9	47.0	63.5	99.5	181.5	328.4	481.3	558.0	544.7
100°	36.6	38.7	44.2	53.9	69.2	98.7	164.8	293.0	459.3	586.5	625.6
102.5°	44.8	46.4	52.4	61.3	76.1	102.4	157.9	266.1	420.6	569.4	652.9
105°	57.5	60.0	65.1	73.2	87.5	109.9	155.2	240.0	368.8	514.8	636.9
107.5°	71.5	73.9	78.1	86.6	99.4	121.1	159.8	229.1	333.1	459.1	579.4
110°	80.9	82.9	87.5	95.1	108.3	129.2	164.3	225.9	316.4	427.3	537.2





TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	90.2	91.8	96.5	104.1	116.9	137.0	170.0	225.9	306.7	403.7	503.8
115°	103.8	105.3	109.9	117.5	130.2	149.0	178.5	227.4	296.0	377.9	461.8
117.5°	116.5	118.2	122.7	131.3	143.7	161.5	188.3	230.7	290.9	362.6	434.8
120°	124.7	126.6	131.3	139.9	152.6	170.4	194.8	234.0	288.4	354.0	420.2
122.5°	132.8	134.4	138.9	148.5	161.1	179.0	202.2	236.8	286.4	346.7	409.2
125°	143.5	146.0	150.5	160.2	173.4	190.2	212.1	241.7	283.8	336.7	393.2
127.5°	152.4	155.7	161.5	171.7	184.9	201.1	221.2	247.0	282.6	327.6	376.9
130°	157.7	161.8	168.4	179.1	192.3	208.0	227.4	250.3	281.8	321.5	366.8
132.5°	162.2	167.0	174.5	185.6	198.8	214.5	232.6	254.0	281.8	316.6	356.6
135°	168.9	175.0	183.2	193.8	207.5	223.3	240.0	258.9	281.8	310.8	343.3
137.5°	176.7	182.4	190.6	201.0	215.2	229.5	245.6	263.5	282.4	305.6	332.2
140°	181.6	187.7	195.8	205.5	219.3	234.0	249.2	265.6	282.9	303.2	326.0
142.5°	186.9	192.6	200.7	210.0	222.9	236.8	251.3	266.7	283.2	301.1	320.7
145°	195.3	200.4	207.5	216.7	228.4	241.7	254.3	268.0	282.9	298.1	313.9
147.5°	203.8	208.2	214.8	222.7	233.1	244.7	256.2	268.6	281.5	294.9	307.4
150°	209.6	213.1	219.7	226.9	235.5	246.7	257.3	268.6	280.3	292.5	303.6
152.5°	214.8	218.0	223.8	230.5	238.4	248.7	258.2	268.1	278.7	289.6	299.6
155°	221.8	224.8	229.9	235.0	242.1	250.7	258.9	267.1	275.7	284.8	293.5
157.5°	228.4	230.9	235.2	239.7	245.0	252.5	259.4	265.7	272.6	280.4	287.4
160°	232.5	234.5	238.1	242.1	246.7	253.3	259.4	264.5	270.6	276.7	283.3
162.5°	236.1	238.2	241.3	244.6	248.3	254.1	259.0	263.3	268.1	273.5	278.8
165°	241.1	242.6	245.1	247.2	250.3	254.3	258.4	261.4	264.5	268.6	272.6
167.5°	245.3	246.2	247.6	249.1	250.9	254.3	257.2	258.6	260.9	263.8	266.7
170°	247.7	248.3	249.2	250.3	251.8	254.3	256.4	257.3	258.9	260.9	263.5
172.5°	249.0	249.4	250.5	251.1	251.8	254.0	255.6	255.7	256.5	258.1	259.8
175°	250.7	251.3	251.8	251.8	251.8	253.3	254.3	253.8	253.8	254.3	255.8
177.5°	251.9	251.9	252.3	251.9	251.9	252.7	253.1	252.3	252.3	252.7	253.1
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3	252.3



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0	1418.0
2.5°	1483.0	1486.8	1495.0	1492.1	1496.0	1497.9	1499.9
5°	1602.8	1622.0	1630.4	1629.2	1641.9	1638.9	1635.8
7.5°	1738.0	1758.3	1769.6	1783.7	1791.9	1792.4	1799.6
10°	1814.6	1841.1	1851.9	1867.0	1876.6	1882.0	1881.4
12.5°	1873.4	1894.1	1918.3	1925.7	1938.8	1945.5	1943.0
15°	1944.0	1977.1	2002.4	2015.0	2031.3	2036.1	2042.7
17.5°	2007.1	2051.5	2081.0	2120.2	2135.0	2144.0	2138.8
20°	2054.8	2113.2	2142.6	2189.6	2215.5	2229.3	2224.5
22.5°	2111.1	2174.3	2228.8	2269.5	2308.8	2327.5	2331.4
25°	2207.6	2294.3	2374.4	2428.0	2476.6	2488.1	2513.4
27.5°	2315.5	2417.7	2503.3	2559.6	2593.5	2606.3	2614.2
30°	2383.4	2485.1	2549.5	2585.6	2596.4	2595.2	2594.0
32.5°	2416.6	2480.3	2492.7	2482.5	2457.7	2436.8	2414.9
35°	2369.5	2322.0	2250.9	2159.5	2092.0	2024.1	2017.4
37.5°	2131.1	1979.1	1860.8	1728.8	1652.6	1605.5	1573.1
40°	1906.7	1733.9	1590.7	1479.3	1401.8	1371.0	1341.0
42.5°	1663.0	1498.1	1371.2	1278.1	1219.8	1185.7	1161.8
45°	1351.2	1205.5	1106.3	1038.8	992.5	966.0	950.9
47.5°	1107.1	999.4	915.1	866.5	834.5	813.9	814.0
50°	976.2	873.3	817.3	778.8	751.1	734.9	737.9
52.5°	860.1	783.3	735.5	703.2	682.8	672.8	672.4
55°	719.3	663.9	632.6	609.1	595.2	583.8	586.2
57.5°	615.2	568.6	547.6	528.1	518.4	513.9	507.2
60°	550.7	514.6	496.5	480.9	471.3	467.6	461.0
62.5°	493.4	465.0	447.5	434.6	426.0	424.8	419.6
65°	414.6	393.0	377.4	371.3	362.3	359.9	359.9
67.5°	341.9	326.4	314.1	308.6	304.7	305.2	302.4
70°	296.1	283.5	275.6	269.7	266.6	267.2	264.8
72.5°	259.0	245.0	238.1	234.5	230.5	232.1	231.1
75°	196.2	189.0	185.4	181.7	179.3	178.2	176.9
77.5°	144.1	137.7	134.9	132.9	133.2	130.4	132.7
80°	111.4	105.9	104.2	101.1	100.5	100.5	99.9
82.5°	81.5	78.5	77.1	74.6	73.6	74.5	72.9
85°	42.1	39.7	39.1	39.1	37.9	36.7	39.7
87.5°	17.3	15.5	15.7	15.2	15.2	14.9	13.9
90°	9.6	10.2	11.1	11.1	11.1	11.7	11.7
92.5°	65.5	49.2	41.7	35.2	34.0	33.3	32.5
95°	288.4	225.9	183.2	147.0	131.7	127.7	119.6
97.5°	490.4	429.5	370.1	338.7	310.1	295.4	288.9
100°	600.7	548.3	495.4	460.3	423.7	404.9	396.7
102.5°	668.2	643.1	607.3	569.8	543.8	523.3	517.2
105°	706.5	728.9	723.3	707.0	690.3	680.1	674.0
107.5°	672.4	730.0	756.4	764.7	764.6	761.3	757.2
110°	633.8	705.5	748.8	771.6	781.3	784.9	784.9



TEST NUMBER: P333261-940

CATALOG NUMBER: S125DIP-S1090D590U940-4F0-1E-UDD-A4

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	595.6	668.1	719.1	752.5	769.1	777.9	781.6
115°	540.7	610.4	665.8	705.5	730.0	744.1	750.8
117.5°	502.7	562.8	613.7	653.4	678.6	692.7	696.8
120°	481.2	537.2	581.9	619.6	644.0	657.7	661.7
122.5°	465.7	515.6	557.5	591.0	613.4	627.1	630.8
125°	445.1	489.4	525.9	554.5	575.3	586.5	591.6
127.5°	425.3	466.6	501.0	526.7	545.2	555.7	558.0
130°	411.5	451.2	484.2	509.7	526.5	536.6	539.7
132.5°	398.5	434.5	466.4	491.8	508.5	517.9	521.4
135°	378.4	411.0	440.0	462.4	479.1	488.3	491.3
137.5°	360.5	387.6	412.2	432.2	447.5	455.9	459.3
140°	350.0	373.4	394.8	413.6	426.8	434.4	436.9
142.5°	341.0	361.1	379.7	395.7	406.8	414.0	416.2
145°	329.6	345.4	359.1	371.3	380.0	385.6	387.6
147.5°	320.1	332.3	342.6	352.3	359.2	362.5	363.4
150°	314.9	324.5	333.7	341.3	347.4	349.5	350.0
152.5°	309.6	318.4	325.6	332.0	336.8	338.9	339.4
155°	301.7	308.7	314.3	319.4	323.0	324.5	325.0
157.5°	294.1	299.6	304.0	307.9	310.9	312.3	312.2
160°	288.4	293.5	297.0	300.6	303.2	304.2	303.6
162.5°	283.6	287.8	291.0	293.7	295.9	296.0	296.0
165°	276.2	279.3	281.8	283.8	284.8	284.8	284.8
167.5°	269.1	271.4	273.2	274.3	275.2	274.7	274.6
170°	265.0	266.5	267.5	268.6	269.1	269.1	268.6
172.5°	261.4	262.4	263.1	263.3	264.2	263.4	262.9
175°	255.8	256.9	256.9	256.9	257.3	256.4	255.8
177.5°	253.5	253.5	253.5	253.1	253.5	252.3	252.3
180°	252.3	252.3	252.3	252.3	252.3	252.3	252.3

(END OF REPORT)