

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331450

Luminaire Tested: **SA2XXDIP-C1005D925U835-4F0-1E-UDD-D**

Issue Date: 10/7/2019

Test Information

Test Method: LM-79-08
Report Number: P331450
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-2,
Test Lab: INNOVATION CENTER
Issue Date: 10/7/2019
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D
Description: DEFINE 2 DIRECT-INDIRECT PENDANT LED LUMINAIRE
DOWNLIGHT 1005 LUMENS PER FOOT, DROP SATIN WHITE DIFFUSER
UPLIGHT 925 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7736.2 lumens
Efficiency: N/A
Efficacy: 115.8 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.32 / 1.42
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.08')
CIE Type: General Diffuse

Input Watts (W): 66.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P331450
CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

Luminous Intensity Polar Plot





TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	106	106	106	106	98	98	98	98	81	81	81	66	66	66	53	53	53	46
1	96	91	86	82	87	83	79	76	69	66	64	56	54	52	44	43	42	36
2	86	78	72	66	79	72	66	61	60	55	52	49	45	43	38	36	34	29
3	79	68	61	54	72	63	56	50	52	47	43	43	39	36	33	31	28	24
4	72	60	52	46	65	55	48	42	46	41	36	38	33	30	30	27	24	20
5	66	53	45	39	60	49	42	36	41	35	31	34	29	26	27	23	21	17
6	60	48	39	33	55	44	37	31	37	31	27	30	26	22	24	21	18	15
7	56	43	35	29	51	40	32	27	33	28	23	27	23	20	22	18	16	13
8	52	39	31	26	47	36	29	24	30	25	21	25	21	17	20	17	14	12
9	48	35	28	23	44	33	26	21	28	22	18	23	19	16	18	15	13	11
10	45	32	25	20	41	30	23	19	25	20	16	21	17	14	17	14	12	10

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	17073	17073	17073
5°	17157	16435	16373
10°	17049	15949	15770
15°	16814	15435	15136
20°	16517	14884	14525
25°	16223	14353	13970
30°	15810	13808	13414
35°	15392	13280	13021
40°	14952	12831	12629
45°	14535	12429	12294
50°	14086	12066	11964
55°	13616	11675	11627
60°	13040	11269	11271
65°	12441	10795	10850
70°	11770	10285	10393
75°	10911	9784	9973
80°	9555	9272	9549
85°	8259	8830	9217



TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	100.2	1.3
10°-20°	287.3	3.7
20°-30°	435.4	5.6
30°-40°	530.3	6.9
40°-50°	570.5	7.4
50°-60°	554.1	7.2
60°-70°	483.8	6.3
70°-80°	372.4	4.8
80°-90°	253.1	3.3
90°-100°	214.3	2.8
100°-110°	280.1	3.6
110°-120°	495.8	6.4
120°-130°	727.6	9.4
130°-140°	744.0	9.6
140°-150°	676.8	8.7
150°-160°	541.4	7.0
160°-170°	348.9	4.5
170°-180°	120.1	1.6
0°-30°	822.9	10.6
0°-40°	1353.3	17.5
0°-60°	2477.9	32.0
0°-90°	3587.2	46.4
90°-120°	990.2	12.8
90°-150°	3138.6	40.6
90°-180°	4149.0	53.6
0°-180°	7736.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1057	1057	1057	1057	1057	
5°	1060	1056	1047	1055	1054	101
15°	1012	1014	1014	1028	1027	285
25°	920	930	944	962	967	423
35°	792	819	848	880	892	495
45°	650	692	745	790	808	501
55°	498	555	633	686	708	445
65°	340	416	506	566	588	338
75°	188	275	372	436	458	199
85°	55	150	248	310	334	59
90°	16	116	221	284	307	13
95°	72	117	212	272	292	82
105°	285	344	188	249	272	305
115°	531	567	656	297	230	522
125°	746	760	824	870	888	665
135°	920	935	958	998	1010	711
145°	1066	1066	1080	1095	1099	667
155°	1174	1166	1176	1181	1174	541
165°	1237	1232	1234	1240	1234	349
175°	1265	1259	1260	1266	1258	120
180°	1262	1262	1262	1262	1262	



TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4
2.5°	1063.6	1062.8	1061.9	1061.1	1060.3	1058.9	1057.0	1055.1	1053.2	1051.3	1052.7
5°	1060.5	1059.5	1058.5	1057.4	1056.4	1054.9	1052.9	1050.8	1048.8	1046.7	1048.8
7.5°	1051.0	1050.3	1049.6	1049.0	1048.3	1047.2	1045.6	1044.0	1042.5	1040.9	1043.3
10°	1043.7	1043.0	1042.3	1041.6	1040.9	1040.1	1039.1	1038.0	1037.0	1036.0	1038.7
12.5°	1031.4	1031.5	1031.7	1031.8	1031.9	1031.6	1030.9	1030.1	1029.4	1028.6	1031.4
15°	1011.5	1012.2	1012.8	1013.5	1014.2	1014.5	1014.5	1014.5	1014.5	1014.5	1017.6
17.5°	985.7	987.2	988.6	990.0	991.4	992.7	993.8	994.9	996.0	997.1	1000.3
20°	968.6	970.3	972.0	973.7	975.4	976.9	978.3	979.6	981.0	982.4	986.1
22.5°	950.2	952.1	954.1	956.1	958.1	960.0	961.9	963.8	965.7	967.6	971.4
25°	919.5	921.9	924.3	926.7	929.1	931.8	934.8	937.9	941.0	944.0	948.1
27.5°	882.7	886.6	890.5	894.4	898.3	902.0	905.6	909.2	912.8	916.5	921.6
30°	858.2	862.6	867.1	871.5	875.9	880.4	884.8	889.2	893.6	898.1	903.5
32.5°	831.2	836.2	841.2	846.2	851.1	856.2	861.5	866.7	872.0	877.2	883.5
35°	792.3	798.1	803.9	809.7	815.5	821.6	828.1	834.5	841.0	847.5	855.0
37.5°	750.0	756.7	763.4	770.0	776.7	784.2	792.6	801.0	809.4	817.8	826.1
40°	721.8	729.3	736.8	744.3	751.8	760.1	769.3	778.5	787.7	796.9	805.8
42.5°	694.9	702.3	709.8	717.3	724.8	733.8	744.4	755.0	765.5	776.1	785.7
45°	649.8	659.0	668.2	677.4	686.6	697.1	709.1	721.0	732.9	744.8	755.4
47.5°	605.4	615.4	625.4	635.4	645.4	657.4	671.4	685.3	699.3	713.2	724.3
50°	574.7	585.3	595.8	606.4	616.9	629.9	645.2	660.5	675.8	691.2	702.8
52.5°	545.3	556.4	567.5	578.6	589.7	603.3	619.4	635.6	651.7	667.9	679.7
55°	498.1	510.3	522.6	534.9	547.1	562.1	579.8	597.5	615.2	632.9	645.2
57.5°	451.5	465.3	479.1	493.0	506.8	522.7	540.8	558.8	576.9	594.9	608.1
60°	418.4	433.0	447.7	462.3	477.0	494.0	513.4	532.8	552.2	571.6	584.6
62.5°	389.0	404.1	419.3	434.5	449.7	467.0	486.4	505.8	525.3	544.7	558.4
65°	340.2	356.9	373.6	390.3	407.0	425.4	445.5	465.5	485.6	505.7	519.7
67.5°	295.5	312.9	330.3	347.8	365.2	384.2	404.8	425.4	445.9	466.5	480.6
70°	263.6	281.3	299.0	316.7	334.4	353.8	375.0	396.1	417.2	438.3	452.9
72.5°	234.2	252.4	270.7	288.9	307.2	327.0	348.4	369.8	391.2	412.6	426.9
75°	188.5	207.6	226.6	245.7	264.8	285.2	307.0	328.8	350.6	372.4	387.0
77.5°	144.4	164.3	184.3	204.2	224.2	245.2	267.4	289.5	311.6	333.8	348.4
80°	114.9	135.7	156.5	177.3	198.0	219.5	241.6	263.8	285.9	308.0	322.3
82.5°	90.4	110.9	131.4	151.9	172.4	193.9	216.3	238.7	261.1	283.5	297.8
85°	55.2	76.3	97.4	118.5	139.6	161.1	182.9	204.7	226.5	248.3	262.6
87.5°	30.2	51.0	71.7	92.5	113.2	134.6	156.7	178.9	201.0	223.1	237.2
90°	16.2	38.2	60.2	82.2	104.2	126.9	150.3	173.7	197.1	220.6	235.2
92.5°	32.5	50.7	68.9	87.1	105.3	125.3	147.1	168.9	190.7	212.4	226.3
95°	71.6	80.9	90.2	99.6	108.9	124.4	146.3	168.2	190.0	211.9	225.8
97.5°	128.5	123.9	119.3	114.6	110.0	119.1	142.0	164.9	187.8	210.7	224.1
100°	172.4	157.2	142.0	126.8	111.6	115.2	137.7	160.3	182.8	205.3	219.5
102.5°	219.4	225.0	230.6	236.3	241.9	239.5	229.2	218.9	208.5	198.2	212.6
105°	285.3	301.3	317.2	333.2	349.2	338.3	300.6	262.9	225.2	187.5	201.7
107.5°	362.3	375.1	387.9	400.7	413.5	395.2	345.7	296.2	246.7	197.2	206.4
110°	410.7	421.8	432.9	443.9	455.0	439.6	397.6	355.6	313.7	271.7	262.3



TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	457.5	467.0	476.5	486.0	495.5	500.9	502.3	503.7	505.0	506.4	443.3
115°	531.3	538.5	545.7	552.9	560.1	573.9	594.3	614.7	635.1	655.5	571.7
117.5°	595.7	602.0	608.3	614.6	620.9	632.9	650.6	668.2	685.9	703.5	690.9
120°	643.9	648.3	652.7	657.1	661.5	672.4	689.6	706.9	724.2	741.5	753.4
122.5°	684.8	688.6	692.3	696.1	699.8	710.1	726.9	743.7	760.4	777.2	787.9
125°	745.6	748.2	750.8	753.5	756.1	764.8	779.6	794.3	809.1	823.8	834.5
127.5°	802.0	804.6	807.2	809.8	812.3	819.5	831.1	842.8	854.5	866.1	876.7
130°	837.8	840.7	843.6	846.5	849.4	855.6	865.0	874.4	883.7	893.1	903.5
132.5°	874.3	876.8	879.2	881.6	884.0	889.1	896.9	904.6	912.4	920.1	929.9
135°	920.3	923.6	926.8	930.0	933.3	937.5	942.8	948.0	953.2	958.5	967.6
137.5°	968.3	970.6	972.8	975.0	977.2	980.1	983.6	987.2	990.8	994.3	1002.6
140°	999.8	1001.0	1002.3	1003.6	1004.9	1007.0	1009.9	1012.8	1015.7	1018.6	1025.9
142.5°	1026.1	1027.2	1028.3	1029.4	1030.5	1032.5	1035.1	1037.8	1040.5	1043.2	1049.3
145°	1065.8	1065.6	1065.4	1065.2	1065.0	1066.6	1070.1	1073.5	1077.0	1080.4	1083.9
147.5°	1101.8	1101.0	1100.3	1099.5	1098.7	1100.0	1103.4	1106.9	1110.3	1113.7	1115.0
150°	1125.2	1123.8	1122.3	1120.9	1119.5	1120.4	1123.7	1126.9	1130.2	1133.4	1134.6
152.5°	1144.9	1143.3	1141.7	1140.2	1138.6	1139.3	1142.4	1145.5	1148.6	1151.7	1152.9
155°	1173.6	1171.8	1169.9	1168.1	1166.3	1166.6	1169.0	1171.5	1173.9	1176.3	1177.5
157.5°	1196.0	1194.5	1193.0	1191.4	1189.9	1190.0	1191.7	1193.4	1195.1	1196.8	1198.2
160°	1209.2	1208.0	1206.8	1205.5	1204.3	1204.3	1205.5	1206.8	1208.0	1209.2	1210.4
162.5°	1220.9	1219.7	1218.5	1217.2	1216.0	1215.9	1217.0	1218.0	1219.1	1220.2	1221.5
165°	1236.6	1235.4	1234.2	1232.9	1231.7	1231.4	1232.0	1232.6	1233.3	1233.9	1235.3
167.5°	1248.3	1247.1	1245.9	1244.6	1243.4	1243.1	1243.7	1244.2	1244.8	1245.4	1246.8
170°	1254.9	1253.6	1252.4	1251.2	1250.0	1249.6	1250.0	1250.4	1250.8	1251.2	1252.6
172.5°	1259.2	1258.0	1256.8	1255.6	1254.4	1254.0	1254.4	1254.8	1255.2	1255.6	1257.0
175°	1264.9	1263.5	1262.1	1260.6	1259.2	1258.7	1259.1	1259.5	1259.9	1260.3	1261.8
177.5°	1265.8	1264.7	1263.6	1262.4	1261.3	1260.8	1261.0	1261.1	1261.3	1261.4	1262.6
180°	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2



TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
0°	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4	1057.4
2.5°	1054.0	1055.4	1056.8	1057.2	1056.6	1056.1	1055.5	1055.0
5°	1050.8	1052.9	1054.9	1055.7	1055.4	1055.1	1054.7	1054.4
7.5°	1045.8	1048.3	1050.7	1051.8	1051.4	1051.1	1050.7	1050.4
10°	1041.4	1044.2	1046.9	1048.1	1047.7	1047.4	1047.1	1046.7
12.5°	1034.1	1036.8	1039.5	1040.7	1040.4	1040.0	1039.7	1039.4
15°	1020.7	1023.7	1026.8	1028.2	1027.8	1027.5	1027.1	1026.8
17.5°	1003.5	1006.7	1009.9	1011.5	1011.5	1011.5	1011.5	1011.5
20°	989.8	993.6	997.3	999.2	999.2	999.2	999.2	999.2
22.5°	975.1	978.9	982.6	984.8	985.3	985.9	986.4	987.0
25°	952.2	956.3	960.4	962.9	964.0	965.0	966.0	967.0
27.5°	926.8	932.0	937.2	940.1	940.9	941.6	942.4	943.1
30°	909.0	914.4	919.9	923.1	924.1	925.1	926.2	927.2
32.5°	889.8	896.0	902.3	906.3	908.2	910.0	911.9	913.7
35°	862.5	870.0	877.5	882.4	884.8	887.2	889.6	891.9
37.5°	834.4	842.7	851.0	856.4	858.9	861.5	864.0	866.5
40°	814.6	823.5	832.3	838.3	841.4	844.4	847.5	850.6
42.5°	795.4	805.1	814.8	821.1	824.2	827.3	830.3	833.4
45°	765.9	776.5	787.0	794.0	797.4	800.8	804.2	807.6
47.5°	735.3	746.3	757.4	764.8	768.5	772.3	776.0	779.8
50°	714.3	725.9	737.5	745.2	748.9	752.6	756.4	760.1
52.5°	691.6	703.4	715.3	723.2	727.2	731.3	735.3	739.3
55°	657.5	669.7	682.0	690.3	694.7	699.2	703.6	708.0
57.5°	621.4	634.6	647.8	656.6	661.1	665.6	670.1	674.6
60°	597.5	610.5	623.4	632.3	637.0	641.8	646.6	651.3
62.5°	572.2	585.9	599.7	608.8	613.3	617.8	622.3	626.8
65°	533.7	547.6	561.6	570.8	575.2	579.6	584.1	588.5
67.5°	494.7	508.8	522.9	532.3	536.9	541.5	546.2	550.8
70°	467.6	482.2	496.9	506.2	510.3	514.4	518.5	522.6
72.5°	441.3	455.7	470.0	479.7	484.6	489.5	494.4	499.3
75°	401.7	416.3	431.0	440.5	444.9	449.4	453.8	458.2
77.5°	362.9	377.5	392.1	401.8	406.5	411.3	416.1	420.8
80°	336.6	351.0	365.3	374.8	379.6	384.3	389.1	393.9
82.5°	312.1	326.4	340.7	350.1	354.6	359.1	363.6	368.1
85°	276.9	291.2	305.5	315.0	319.8	324.6	329.3	334.1
87.5°	251.3	265.4	279.5	288.8	293.2	297.7	302.1	306.5
90°	249.8	264.5	279.1	288.7	293.2	297.7	302.2	306.6
92.5°	240.2	254.1	268.0	277.1	281.4	285.7	290.1	294.4
95°	239.8	253.7	267.7	276.6	280.5	284.4	288.3	292.1
97.5°	237.6	251.0	264.4	273.2	277.5	281.7	286.0	290.3
100°	233.8	248.0	262.2	271.4	275.5	279.7	283.9	288.0
102.5°	227.1	241.5	255.9	265.3	269.6	274.0	278.3	282.6
105°	215.8	230.0	244.1	253.5	258.0	262.6	267.1	271.7
107.5°	215.6	224.7	233.9	240.8	245.3	249.9	254.4	259.0
110°	252.9	243.5	234.1	231.7	236.2	240.8	245.4	249.9



TEST NUMBER: P331450

CATALOG NUMBER: SA2XXDIP-C1005D925U835-4F0-1E-UDD-D

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
112.5°	380.1	317.0	253.9	224.5	228.9	233.3	237.7	242.1
115°	488.0	404.2	320.5	273.1	262.3	251.4	240.5	229.7
117.5°	678.2	665.6	652.9	624.3	579.8	535.2	490.7	446.2
120°	765.4	777.4	789.4	783.5	759.9	736.2	712.6	688.9
122.5°	798.7	809.4	820.1	824.4	822.3	820.2	818.1	816.0
125°	845.1	855.7	866.3	873.4	877.1	880.8	884.5	888.1
127.5°	887.2	897.7	908.2	915.0	918.1	921.3	924.4	927.5
130°	913.9	924.3	934.7	941.2	943.7	946.3	948.8	951.3
132.5°	939.7	949.5	959.3	965.5	968.0	970.6	973.1	975.6
135°	976.8	986.0	995.2	1000.9	1003.3	1005.6	1007.9	1010.2
137.5°	1010.8	1019.1	1027.3	1032.3	1033.9	1035.5	1037.2	1038.8
140°	1033.2	1040.5	1047.8	1051.9	1052.9	1054.0	1055.0	1056.0
142.5°	1055.3	1061.3	1067.3	1070.7	1071.5	1072.2	1073.0	1073.7
145°	1087.4	1090.8	1094.3	1096.4	1097.0	1097.7	1098.4	1099.1
147.5°	1116.3	1117.7	1119.0	1119.6	1119.6	1119.6	1119.5	1119.5
150°	1135.8	1137.1	1138.3	1138.4	1137.4	1136.3	1135.3	1134.3
152.5°	1154.1	1155.3	1156.5	1156.5	1155.1	1153.8	1152.5	1151.1
155°	1178.8	1180.0	1181.2	1181.0	1179.4	1177.7	1176.1	1174.5
157.5°	1199.5	1200.9	1202.3	1202.2	1200.6	1199.0	1197.4	1195.9
160°	1211.6	1212.9	1214.1	1214.0	1212.5	1211.1	1209.7	1208.3
162.5°	1222.9	1224.3	1225.7	1225.5	1223.8	1222.0	1220.3	1218.5
165°	1236.7	1238.1	1239.5	1239.5	1238.1	1236.7	1235.3	1233.9
167.5°	1248.2	1249.6	1251.1	1250.8	1249.0	1247.2	1245.4	1243.5
170°	1254.1	1255.5	1256.9	1256.7	1254.9	1253.0	1251.2	1249.4
172.5°	1258.4	1259.9	1261.3	1261.1	1259.2	1257.4	1255.6	1253.8
175°	1263.2	1264.6	1266.0	1265.7	1263.7	1261.7	1259.6	1257.6
177.5°	1263.7	1264.9	1266.0	1265.8	1264.4	1262.9	1261.4	1260.0
180°	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2	1262.2

(END OF REPORT)