

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P902144

Luminaire Tested: DFN2DIP-4P2F0-020D030US830-RLFL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P902144
REPORT IS A COMBINATION OF REPORTS P899018 AND P895899
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-4P2F0-020D030US830-RLLFLL
Description: 2 foot, 90deg - 4way Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4104.8 lumens
Efficiency: N/A
Efficacy: 102.6 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.07' x L: 2.07' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 40
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9967
Total Harmonic Distortion (THDi): 0.063
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	105	105	105	105	95	95	95	95	77	77	77	61	61	61	46	46	46
1	96	92	88	85	87	83	80	78	68	66	64	54	53	51	41	40	40
2	87	80	75	70	79	73	68	64	60	57	54	48	46	44	37	35	34
3	80	71	64	58	73	65	59	54	53	49	46	43	40	37	33	31	29
4	73	63	55	50	66	58	51	46	48	43	39	38	35	32	30	27	26
5	67	56	48	43	61	52	45	40	43	38	34	35	31	28	27	24	22
6	62	51	43	37	56	46	40	35	39	33	30	31	28	25	25	22	20
7	57	46	38	33	52	42	35	30	35	30	26	29	25	22	22	20	18
8	53	41	34	29	49	38	32	27	32	27	23	26	22	20	21	18	16
9	50	38	31	26	45	35	29	24	29	24	21	24	20	18	19	17	15
10	46	35	28	23	42	32	26	22	27	22	19	22	19	16	18	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1951	1951	1951
5°	1950	1915	1929
10°	1927	1872	1863
15°	1896	1806	1763
20°	1857	1716	1641
25°	1818	1616	1524
30°	1765	1514	1376
35°	1714	1405	1247
40°	1661	1293	1099
45°	1601	1169	964
50°	1538	1044	834
55°	1471	911	708
60°	1395	774	580
65°	1306	634	519
70°	1199	504	465
75°	1063	435	417
80°	870	351	351
85°	561	216	248

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1601 cd/sqm

TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.0	1.8
10°-20°	200.4	4.9
20°-30°	281.4	6.9
30°-40°	306.8	7.5
40°-50°	282.0	6.9
50°-60°	221.4	5.4
60°-70°	144.1	3.5
70°-80°	74.2	1.8
80°-90°	21.5	0.5
90°-100°	55.3	1.3
100°-110°	175.8	4.3
110°-120°	300.9	7.3
120°-130°	395.7	9.6
130°-140°	444.2	10.8
140°-150°	435.6	10.6
150°-160°	365.4	8.9
160°-170°	242.3	5.9
170°-180°	84.7	2.1
0°-30°	554.9	13.5
0°-40°	861.7	21.0
0°-60°	1365.1	33.3
0°-90°	1604.9	39.1
90°-120°	532.1	13.0
90°-150°	1807.5	44.0
90°-180°	2500.0	60.9
0°-180°	4104.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	779	779	779	779	779	
5°	779	776	766	773	771	74
15°	741	733	709	696	689	209
25°	673	650	604	575	564	309
35°	580	544	482	437	422	363
45°	474	426	353	302	286	366
55°	360	305	229	187	173	322
65°	243	186	123	99	97	241
75°	130	80	56	52	51	137
85°	30	16	13	13	13	35
90°	1	10	26	25	26	4
95°	39	47	48	48	47	44
105°	162	164	166	167	167	171
115°	302	306	305	304	302	299
125°	439	446	444	441	440	392
135°	568	576	578	577	575	439
145°	690	695	699	700	697	431
155°	789	791	793	797	795	363
165°	858	857	857	862	859	242
175°	893	890	889	894	890	85
180°	894	894	894	894	894	

TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	779.1	779.1	779.1	779.1	779.1
2.5°	782.6	779.1	771.3	778.4	777.0
5°	779.1	775.6	766.4	772.8	770.6
7.5°	772.8	768.5	758.7	761.5	757.9
10°	764.3	759.3	745.3	743.1	739.0
12.5°	753.8	747.3	728.3	724.2	716.3
15°	741.0	733.2	709.3	695.9	688.9
17.5°	726.2	714.9	685.3	669.8	658.6
20°	709.3	695.1	660.0	642.3	626.8
22.5°	691.0	674.8	633.9	609.9	599.4
25°	672.7	650.1	603.5	574.7	564.0
27.5°	650.8	626.8	575.3	542.2	525.9
30°	627.5	600.7	544.3	508.4	489.3
32.5°	604.9	572.5	514.7	472.4	454.8
35°	579.6	543.7	481.6	437.2	421.6
37.5°	554.9	516.0	450.5	401.9	384.3
40°	528.8	486.5	418.1	368.1	349.7
42.5°	502.0	456.9	385.7	333.5	315.9
45°	473.8	426.5	352.6	302.5	285.5
47.5°	447.0	397.0	320.8	270.7	255.2
50°	417.5	367.4	289.8	241.1	226.4
52.5°	388.4	335.5	260.1	213.7	200.3
55°	360.2	305.3	229.1	186.9	173.4
57.5°	331.4	274.9	201.7	162.2	150.9
60°	301.8	245.3	172.8	136.9	125.5
62.5°	272.9	216.5	148.1	114.2	108.6
65°	243.3	186.2	122.7	98.8	96.6
67.5°	215.1	157.9	98.8	86.7	84.6
70°	185.4	130.4	81.7	74.7	71.9
72.5°	157.2	105.0	68.3	62.8	61.4
75°	129.7	80.3	56.4	51.5	50.8
77.5°	102.3	57.1	44.4	41.6	40.2
80°	76.8	40.9	33.8	31.0	31.0
82.5°	53.5	27.5	23.3	21.9	21.9
85°	30.3	15.5	13.4	13.4	13.4
87.5°	11.3	5.7	5.7	4.9	4.9
90°	0.8	9.7	26.4	24.8	25.6
92.5°	16.7	22.6	23.5	24.2	24.2
95°	39.4	46.9	48.3	48.3	46.9
97.5°	65.5	72.5	75.5	75.5	75.5
100°	95.7	101.9	104.1	104.1	103.3
102.5°	127.5	132.1	135.1	135.9	135.1
105°	162.3	164.5	166.1	167.4	167.4
107.5°	196.8	200.0	200.0	200.6	196.8
110°	230.3	234.6	234.6	234.6	232.4

TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	266.4	271.0	270.1	268.0	266.4
115°	302.0	306.2	304.9	304.2	302.0
117.5°	337.2	343.2	339.4	337.2	335.1
120°	372.9	378.8	372.9	372.9	370.4
122.5°	405.2	412.7	409.0	406.8	405.2
125°	439.2	445.9	443.7	441.3	440.5
127.5°	472.3	480.7	477.8	474.5	472.3
130°	503.3	513.0	511.7	510.1	507.1
132.5°	538.1	545.6	546.2	542.4	540.3
135°	568.1	576.4	578.1	577.2	575.0
137.5°	601.4	608.2	609.5	609.1	605.8
140°	630.8	637.6	641.4	641.4	638.4
142.5°	661.1	667.8	670.0	670.8	667.8
145°	689.7	695.0	699.4	700.1	697.2
147.5°	715.3	722.0	725.2	726.6	723.6
150°	741.7	746.3	749.2	751.7	749.2
152.5°	765.2	769.7	773.5	776.5	773.5
155°	788.6	790.7	793.1	796.9	794.6
157.5°	808.8	810.4	811.8	817.2	813.4
160°	826.9	828.5	829.3	833.9	830.7
162.5°	843.6	843.6	844.4	849.5	845.7
165°	857.9	857.1	857.1	862.4	858.7
167.5°	870.8	868.4	868.4	873.7	870.0
170°	880.5	878.4	877.6	883.0	878.4
172.5°	887.2	885.1	884.3	889.7	885.1
175°	892.7	890.5	888.9	894.3	889.7
177.5°	895.6	893.4	891.8	896.5	891.8
180°	894.3	894.3	894.3	894.3	894.3

TEST NUMBER: P902144

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US830-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	8.22	8.97	9.27	10.02	11.44	4.18	4.93	5.23	5.98	7.40
	3H	9.87	10.54	10.93	11.60	13.04	5.34	6.01	6.40	7.07	8.51
	4H	10.46	11.09	11.53	12.15	13.60	5.78	6.41	6.85	7.47	8.92
	6H	10.86	11.44	11.94	12.51	13.96	6.07	6.66	7.16	7.72	9.18
	8H	10.97	11.53	12.06	12.61	14.06	6.15	6.71	7.24	7.79	9.24
	12H	11.02	11.55	12.11	12.62	14.10	6.18	6.71	7.27	7.79	9.26
4H	2H	8.22	8.86	9.30	9.92	11.37	4.76	5.39	5.84	6.45	7.90
	3H	10.02	10.55	11.10	11.64	13.09	6.07	6.60	7.16	7.69	9.15
	4H	10.69	11.17	11.78	12.25	13.73	6.60	7.08	7.69	8.16	9.65
	6H	11.18	11.59	12.28	12.70	14.17	6.99	7.41	8.09	8.51	9.99
	8H	11.34	11.73	12.44	12.82	14.31	7.11	7.50	8.21	8.59	10.08
	12H	11.42	11.77	12.53	12.88	14.37	7.16	7.51	8.27	8.62	10.11
8H	4H	10.65	11.03	11.74	12.13	13.62	6.86	7.25	7.96	8.34	9.83
	6H	11.18	11.50	12.30	12.64	14.13	7.35	7.67	8.47	8.80	10.29
	8H	11.38	11.66	12.51	12.78	14.29	7.52	7.80	8.65	8.92	10.43
	12H	11.50	11.75	12.63	12.86	14.41	7.62	7.87	8.75	8.98	10.53
12H	4H	10.59	10.94	11.71	12.05	13.55	6.86	7.21	7.97	8.32	9.81
	6H	11.16	11.44	12.28	12.56	14.06	7.39	7.67	8.52	8.79	10.30
	8H	11.36	11.60	12.49	12.72	14.26	7.58	7.83	8.71	8.94	10.49