

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P923969

Luminaire Tested: DFN2DIP-4P2F0-020D030US950-RLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P923969
REPORT IS A COMBINATION OF REPORTS P900538 AND P897455
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-4P2F0-020D030US950-RLLONL
Description: 2 foot, 90deg - 4way Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4455.2 lumens
Efficiency: N/A
Efficacy: 111.4 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.07' x L: 2.07' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 40
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9967
Total Harmonic Distortion (THDi): 0.063
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	104	104	104	104		94	94	94	94		76	76	76		59	59	59		44	44	44
1	95	91	87	84		86	83	80	77		67	65	63		52	51	50		39	38	38
2	87	80	74	69		78	73	68	63		59	56	53		46	44	42		35	33	32
3	79	70	63	58		72	64	58	53		52	48	45		41	38	36		31	29	28
4	73	63	55	49		66	57	51	46		47	42	38		37	34	31		28	26	24
5	67	56	48	42		60	51	44	39		42	37	33		33	30	27		25	23	21
6	62	50	42	37		56	46	39	34		38	33	29		30	27	24		23	21	19
7	57	45	38	32		52	41	35	30		34	29	26		28	24	21		21	19	17
8	53	41	34	29		48	38	31	27		31	26	23		25	22	19		20	17	15
9	49	37	30	25		45	34	28	24		29	24	20		23	20	17		18	16	14
10	46	34	27	23		42	32	25	21		26	22	18		22	18	15		17	14	13

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1975	1975	1975
5°	1974	1938	1952
10°	1950	1895	1886
15°	1919	1828	1785
20°	1880	1737	1661
25°	1840	1636	1543
30°	1787	1532	1393
35°	1735	1422	1262
40°	1681	1308	1112
45°	1620	1183	976
50°	1556	1057	844
55°	1489	923	717
60°	1412	783	587
65°	1322	642	525
70°	1213	510	471
75°	1077	440	421
80°	881	356	356
85°	567	218	250

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1620 cd/sqm

TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.9	1.7
10°-20°	202.9	4.6
20°-30°	284.8	6.4
30°-40°	310.5	7.0
40°-50°	285.4	6.4
50°-60°	224.1	5.0
60°-70°	145.9	3.3
70°-80°	75.1	1.7
80°-90°	20.9	0.5
90°-100°	31.9	0.7
100°-110°	118.7	2.7
110°-120°	314.9	7.1
120°-130°	522.3	11.7
130°-140°	554.8	12.5
140°-150°	515.6	11.6
150°-160°	414.5	9.3
160°-170°	267.1	6.0
170°-180°	91.9	2.1
0°-30°	561.6	12.6
0°-40°	872.1	19.6
0°-60°	1381.7	31.0
0°-90°	1623.5	36.4
90°-120°	465.5	10.4
90°-150°	2058.1	46.2
90°-180°	2832.0	63.6
0°-180°	4455.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	789	789	789	789	789	
5°	789	785	776	782	780	75
15°	750	742	718	704	697	211
25°	681	658	611	582	571	313
35°	587	550	488	442	427	367
45°	480	432	357	306	289	370
55°	365	309	232	189	176	326
65°	246	188	124	100	98	244
75°	131	81	57	52	51	139
85°	31	16	14	14	14	35
90°	1	8	14	18	19	4
95°	45	22	27	31	30	54
105°	212	233	43	50	53	227
115°	402	414	431	108	57	396
125°	568	577	591	596	598	507
135°	703	714	721	728	726	543
145°	816	815	827	832	828	510
155°	898	892	900	904	899	414
165°	946	942	944	949	944	267
175°	968	963	964	969	962	92
180°	966	966	966	966	966	

TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	788.6	788.6	788.6	788.6	788.6
2.5°	792.1	788.6	780.7	787.9	786.5
5°	788.6	785.0	775.7	782.2	780.0
7.5°	782.2	777.9	767.9	770.7	767.1
10°	773.6	768.5	754.3	752.1	747.9
12.5°	762.9	756.4	737.2	733.0	725.0
15°	750.0	742.1	717.9	704.3	697.3
17.5°	735.1	723.6	693.7	677.9	666.6
20°	717.9	703.6	668.0	650.2	634.4
22.5°	699.4	683.0	641.6	617.3	606.6
25°	680.9	658.0	610.8	581.7	570.9
27.5°	658.7	634.4	582.3	548.7	532.3
30°	635.2	608.0	550.9	514.6	495.2
32.5°	612.3	579.5	521.0	478.1	460.3
35°	586.6	550.3	487.5	442.5	426.7
37.5°	561.6	522.3	456.0	406.8	388.9
40°	535.2	492.5	423.2	372.5	353.9
42.5°	508.1	462.5	390.4	337.5	319.8
45°	479.6	431.7	356.9	306.1	289.0
47.5°	452.5	401.8	324.7	274.0	258.3
50°	422.5	371.9	293.4	244.0	229.2
52.5°	393.1	339.6	263.3	216.3	202.7
55°	364.6	309.0	231.9	189.2	175.5
57.5°	335.4	278.3	204.2	164.2	152.7
60°	305.5	248.3	174.9	138.5	127.1
62.5°	276.2	219.1	149.9	115.6	109.9
65°	246.2	188.4	124.2	100.0	97.8
67.5°	217.7	159.8	100.0	87.8	85.7
70°	187.7	132.0	82.7	75.7	72.8
72.5°	159.1	106.3	69.2	63.5	62.1
75°	131.3	81.3	57.0	52.1	51.4
77.5°	103.5	57.8	44.9	42.1	40.6
80°	77.8	41.4	34.2	31.4	31.4
82.5°	54.2	27.9	23.6	22.1	22.1
85°	30.6	15.6	13.5	13.5	13.5
87.5°	11.4	5.7	5.7	5.0	5.0
90°	0.7	8.4	13.9	17.6	18.8
92.5°	17.6	14.7	16.8	18.2	18.8
95°	45.4	22.3	27.2	30.8	30.1
97.5°	81.8	24.5	35.6	37.8	38.4
100°	123.7	28.0	39.9	45.4	46.8
102.5°	169.8	168.5	41.2	48.8	51.0
105°	212.5	233.4	42.6	50.3	53.1
107.5°	262.1	279.5	44.1	51.7	54.6
110°	309.7	324.3	122.3	52.5	55.2

TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	354.4	366.9	355.1	53.8	55.9
115°	401.8	413.7	431.2	107.6	57.3
117.5°	443.1	457.1	469.0	369.0	185.9
120°	489.2	499.7	512.3	520.7	426.3
122.5°	528.3	539.6	553.6	557.7	558.5
125°	568.2	577.3	590.6	595.5	597.6
127.5°	604.5	614.3	624.9	631.8	632.5
130°	638.8	650.1	657.7	665.3	664.7
132.5°	673.7	682.9	690.5	696.8	696.1
135°	703.1	714.4	720.6	727.6	726.2
137.5°	733.8	742.2	749.3	756.2	754.1
140°	763.9	769.5	777.1	783.4	780.0
142.5°	789.1	794.0	803.1	808.6	805.2
145°	815.7	814.9	826.8	831.7	828.2
147.5°	838.7	836.6	848.5	851.9	849.2
150°	861.1	856.2	867.4	871.5	868.0
152.5°	879.9	874.3	884.8	889.0	884.2
155°	898.1	891.9	900.2	904.4	898.9
157.5°	912.8	907.3	913.6	918.4	912.8
160°	925.4	921.2	925.4	929.6	924.6
162.5°	936.5	932.3	935.9	940.7	934.4
165°	946.3	942.2	944.3	949.1	944.3
167.5°	954.0	949.8	951.9	956.9	950.6
170°	960.3	956.1	957.5	962.4	956.1
172.5°	964.5	960.3	961.7	966.6	960.3
175°	967.9	963.1	964.5	969.4	962.4
177.5°	969.4	964.5	965.3	970.1	963.8
180°	965.9	965.9	965.9	965.9	965.9

TEST NUMBER: P923969

CATALOG NUMBER: DFN2DIP-4P2F0-020D030US950-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	7.96	8.69	9.03	9.76	11.22	3.92	4.65	4.99	5.72	7.18
	3H	9.61	10.26	10.69	11.34	12.81	5.08	5.74	6.17	6.82	8.29
	4H	10.20	10.82	11.29	11.89	13.37	5.52	6.13	6.61	7.21	8.69
	6H	10.59	11.16	11.69	12.25	13.74	5.81	6.38	6.91	7.46	8.95
	8H	10.71	11.25	11.81	12.35	13.83	5.89	6.43	6.99	7.53	9.01
	12H	10.76	11.27	11.87	12.36	13.87	5.92	6.43	7.03	7.53	9.03
4H	2H	7.96	8.58	9.06	9.66	11.14	4.49	5.11	5.59	6.19	7.67
	3H	9.75	10.27	10.86	11.38	12.87	5.81	6.33	6.92	7.43	8.92
	4H	10.43	10.90	11.53	11.99	13.51	6.34	6.81	7.45	7.91	9.42
	6H	10.91	11.32	12.03	12.44	13.94	6.73	7.13	7.84	8.25	9.76
	8H	11.07	11.45	12.19	12.56	14.08	6.84	7.22	7.96	8.33	9.85
	12H	11.15	11.49	12.28	12.62	14.14	6.89	7.23	8.02	8.36	9.88
8H	4H	10.38	10.76	11.50	11.87	13.39	6.60	6.97	7.71	8.08	9.61
	6H	10.92	11.23	12.06	12.38	13.90	7.08	7.39	8.22	8.55	10.06
	8H	11.12	11.39	12.26	12.52	14.06	7.26	7.53	8.40	8.66	10.20
	12H	11.24	11.48	12.38	12.61	14.18	7.35	7.59	8.50	8.72	10.30
12H	4H	10.33	10.67	11.46	11.79	13.32	6.59	6.93	7.73	8.06	9.58
	6H	10.89	11.16	12.03	12.30	13.84	7.12	7.40	8.27	8.53	10.07
	8H	11.09	11.33	12.24	12.46	14.03	7.31	7.55	8.46	8.68	10.26