

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P918778

Luminaire Tested: DFN2DIP-4P4F0-080D070US935-FLLFLL

Issue Date: 11/21/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P918778  
REPORT IS A COMBINATION OF REPORTS P899137 AND P895967  
Test Lab: INNOVATION CENTER  
Issue Date: 11/21/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: DFN2DIP-4P4F0-080D070US935-FLLFLL  
Description: 4 foot, 90deg - 4way Define Geo, with Direct Frosted Lens, Indirect Frosted Lens  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 12153.0 lumens  
Efficiency: N/A  
Efficacy: 82.7 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29  
Luminous Opening: Rectangular w/ Sides (W: 4.07' x L: 4.07' x H: 0.1')  
CIE Type: General Diffuse

Input Watts (W): 146.9  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: 0.9971  
Total Harmonic Distortion (THDi): 0.049  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFLL

### Luminous Intensity Polar Plot



TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFLL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20 |    |    |    | 20 |    |    |    | 20 |
| RC  | 80  |     |     |     | 70  |     |     |     | 50 |    |    |    | 30 |    |    |    | 10 |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |     |     |     |     |     |     |     |     |    |    |    |    |    |    |    |    |    |
| 0   | 109 | 109 | 109 | 109 | 101 | 101 | 101 | 101 | 87 | 87 | 87 | 74 | 74 | 74 | 62 | 62 | 62 |
| 1   | 99  | 95  | 91  | 87  | 92  | 88  | 85  | 82  | 76 | 74 | 71 | 65 | 63 | 61 | 55 | 53 | 52 |
| 2   | 90  | 83  | 77  | 71  | 84  | 77  | 72  | 67  | 67 | 63 | 59 | 57 | 54 | 51 | 48 | 46 | 44 |
| 3   | 82  | 73  | 65  | 59  | 76  | 68  | 61  | 56  | 59 | 54 | 50 | 50 | 47 | 43 | 43 | 40 | 37 |
| 4   | 75  | 64  | 56  | 50  | 70  | 60  | 53  | 48  | 52 | 47 | 42 | 45 | 41 | 37 | 38 | 35 | 32 |
| 5   | 69  | 57  | 49  | 43  | 64  | 54  | 46  | 41  | 47 | 41 | 37 | 40 | 36 | 32 | 34 | 31 | 28 |
| 6   | 64  | 52  | 43  | 38  | 59  | 48  | 41  | 36  | 42 | 36 | 32 | 37 | 32 | 28 | 31 | 28 | 25 |
| 7   | 59  | 47  | 39  | 33  | 55  | 44  | 37  | 31  | 38 | 32 | 28 | 33 | 29 | 25 | 28 | 25 | 22 |
| 8   | 55  | 42  | 35  | 29  | 51  | 40  | 33  | 28  | 35 | 29 | 25 | 30 | 26 | 22 | 26 | 23 | 20 |
| 9   | 51  | 39  | 31  | 26  | 47  | 36  | 30  | 25  | 32 | 26 | 23 | 28 | 23 | 20 | 24 | 21 | 18 |
| 10  | 48  | 36  | 28  | 23  | 44  | 34  | 27  | 22  | 30 | 24 | 20 | 26 | 21 | 18 | 22 | 19 | 16 |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°   | 45°  | 90°  |
|-----|------|------|------|
| 0°  | 1739 | 1739 | 1739 |
| 5°  | 1742 | 1715 | 1727 |
| 10° | 1728 | 1693 | 1704 |
| 15° | 1702 | 1665 | 1668 |
| 20° | 1668 | 1627 | 1631 |
| 25° | 1634 | 1581 | 1589 |
| 30° | 1591 | 1539 | 1534 |
| 35° | 1551 | 1489 | 1477 |
| 40° | 1501 | 1438 | 1422 |
| 45° | 1452 | 1387 | 1366 |
| 50° | 1397 | 1334 | 1301 |
| 55° | 1341 | 1272 | 1242 |
| 60° | 1276 | 1199 | 1174 |
| 65° | 1207 | 1123 | 1094 |
| 70° | 1118 | 1031 | 1008 |
| 75° | 994  | 920  | 929  |
| 80° | 846  | 780  | 777  |
| 85° | 614  | 537  | 524  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1452 cd/sqm

TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFLL

**ZONAL LUMENS:**

| Zone      | Lumens  | % Fixture |
|-----------|---------|-----------|
| 0°-10°    | 252.3   | 2.1       |
| 10°-20°   | 709.8   | 5.8       |
| 20°-30°   | 1043.1  | 8.6       |
| 30°-40°   | 1211.4  | 10.0      |
| 40°-50°   | 1209.9  | 10.0      |
| 50°-60°   | 1055.0  | 8.7       |
| 60°-70°   | 779.9   | 6.4       |
| 70°-80°   | 441.2   | 3.6       |
| 80°-90°   | 121.9   | 1.0       |
| 90°-100°  | 117.9   | 1.0       |
| 100°-110° | 374.8   | 3.1       |
| 110°-120° | 641.3   | 5.3       |
| 120°-130° | 843.5   | 6.9       |
| 130°-140° | 946.7   | 7.8       |
| 140°-150° | 928.4   | 7.6       |
| 150°-160° | 778.8   | 6.4       |
| 160°-170° | 516.5   | 4.2       |
| 170°-180° | 180.5   | 1.5       |
| 0°-30°    | 2005.1  | 16.5      |
| 0°-40°    | 3216.5  | 26.5      |
| 0°-60°    | 5481.5  | 45.1      |
| 0°-90°    | 6824.5  | 56.2      |
| 90°-120°  | 1134.1  | 9.3       |
| 90°-150°  | 3852.7  | 31.7      |
| 90°-180°  | 5328.0  | 43.8      |
| 0°-180°   | 12153.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | 22.5° | 45°  | 67.5° | 90°  | Flux |
|------|------|-------|------|-------|------|------|
| 0°   | 2680 | 2680  | 2680 | 2680  | 2680 |      |
| 5°   | 2680 | 2670  | 2642 | 2662  | 2657 | 254  |
| 15°  | 2551 | 2536  | 2502 | 2513  | 2500 | 719  |
| 25°  | 2309 | 2289  | 2245 | 2250  | 2245 | 1063 |
| 35°  | 1992 | 1966  | 1925 | 1910  | 1897 | 1244 |
| 45°  | 1621 | 1603  | 1564 | 1536  | 1526 | 1251 |
| 55°  | 1227 | 1211  | 1180 | 1150  | 1137 | 1097 |
| 65°  | 827  | 812   | 786  | 763   | 750  | 818  |
| 75°  | 433  | 428   | 415  | 400   | 405  | 462  |
| 85°  | 106  | 103   | 101  | 93    | 90   | 118  |
| 90°  | 2    | 21    | 56   | 53    | 55   | 12   |
| 95°  | 84   | 100   | 103  | 103   | 100  | 93   |
| 105° | 346  | 350   | 354  | 357   | 357  | 365  |
| 115° | 644  | 653   | 650  | 648   | 644  | 637  |
| 125° | 936  | 950   | 946  | 941   | 939  | 837  |
| 135° | 1211 | 1229  | 1232 | 1230  | 1226 | 936  |
| 145° | 1470 | 1481  | 1491 | 1492  | 1486 | 918  |
| 155° | 1681 | 1685  | 1691 | 1699  | 1694 | 774  |
| 165° | 1828 | 1827  | 1827 | 1838  | 1830 | 516  |
| 175° | 1903 | 1898  | 1895 | 1906  | 1896 | 181  |
| 180° | 1906 | 1906  | 1906 | 1906  | 1906 |      |

TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFL

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 0°     | 2680.1 | 2680.1 | 2680.1 | 2680.1 | 2680.1 |
| 2.5°   | 2695.7 | 2682.9 | 2654.5 | 2680.1 | 2675.2 |
| 5°     | 2680.1 | 2670.0 | 2641.6 | 2662.1 | 2657.2 |
| 7.5°   | 2662.1 | 2646.8 | 2618.4 | 2639.1 | 2634.0 |
| 10°    | 2634.0 | 2615.9 | 2585.0 | 2605.5 | 2597.9 |
| 12.5°  | 2595.1 | 2579.8 | 2548.9 | 2561.7 | 2556.6 |
| 15°    | 2551.4 | 2536.1 | 2502.4 | 2512.8 | 2500.0 |
| 17.5°  | 2497.2 | 2481.9 | 2448.2 | 2461.2 | 2448.2 |
| 20°    | 2437.9 | 2422.6 | 2386.5 | 2394.2 | 2384.0 |
| 22.5°  | 2378.9 | 2355.6 | 2321.9 | 2321.9 | 2316.8 |
| 25°    | 2309.1 | 2288.6 | 2244.9 | 2249.8 | 2244.9 |
| 27.5°  | 2231.7 | 2213.7 | 2180.3 | 2172.6 | 2159.8 |
| 30°    | 2154.6 | 2133.8 | 2095.3 | 2087.7 | 2077.2 |
| 32.5°  | 2072.1 | 2056.8 | 2015.4 | 1999.8 | 1989.5 |
| 35°    | 1992.2 | 1966.5 | 1925.2 | 1909.6 | 1896.8 |
| 37.5°  | 1901.9 | 1878.7 | 1837.5 | 1819.4 | 1806.5 |
| 40°    | 1809.3 | 1788.5 | 1747.2 | 1724.2 | 1713.8 |
| 42.5°  | 1719.1 | 1698.2 | 1657.2 | 1631.2 | 1616.0 |
| 45°    | 1621.2 | 1603.1 | 1564.3 | 1536.1 | 1525.8 |
| 47.5°  | 1525.8 | 1507.7 | 1466.4 | 1438.0 | 1422.6 |
| 50°    | 1425.1 | 1412.3 | 1376.1 | 1340.1 | 1327.2 |
| 52.5°  | 1327.2 | 1309.1 | 1275.8 | 1247.4 | 1229.3 |
| 55°    | 1226.8 | 1211.3 | 1180.4 | 1149.5 | 1136.6 |
| 57.5°  | 1126.3 | 1113.4 | 1079.8 | 1048.9 | 1038.4 |
| 60°    | 1025.6 | 1015.5 | 979.4  | 951.0  | 943.3  |
| 62.5°  | 927.7  | 909.7  | 884.0  | 858.3  | 847.9  |
| 65°    | 827.4  | 811.8  | 786.1  | 762.8  | 750.0  |
| 67.5°  | 724.3  | 711.2  | 688.2  | 670.2  | 659.8  |
| 70°    | 628.9  | 618.5  | 595.3  | 577.2  | 567.1  |
| 72.5°  | 531.0  | 520.6  | 507.7  | 489.7  | 482.1  |
| 75°    | 432.8  | 427.9  | 414.8  | 399.5  | 404.7  |
| 77.5°  | 345.3  | 334.9  | 329.8  | 322.1  | 314.4  |
| 80°    | 257.9  | 255.1  | 249.9  | 242.3  | 237.0  |
| 82.5°  | 175.3  | 175.3  | 172.8  | 162.4  | 162.4  |
| 85°    | 105.6  | 103.1  | 100.7  | 92.7   | 90.2   |
| 87.5°  | 46.5   | 41.3   | 36.1   | 28.4   | 25.7   |
| 90°    | 1.7    | 20.7   | 56.3   | 52.9   | 54.6   |
| 92.5°  | 35.6   | 48.3   | 50.0   | 51.7   | 51.7   |
| 95°    | 83.9   | 100.0  | 102.9  | 102.9  | 100.0  |
| 97.5°  | 139.7  | 154.5  | 160.9  | 160.9  | 160.9  |
| 100°   | 204.0  | 217.2  | 221.8  | 221.8  | 220.1  |
| 102.5° | 271.8  | 281.5  | 287.9  | 289.6  | 287.9  |
| 105°   | 345.9  | 350.5  | 354.0  | 356.9  | 356.9  |
| 107.5° | 419.5  | 426.4  | 426.4  | 427.6  | 419.5  |
| 110°   | 490.8  | 500.0  | 500.0  | 500.0  | 495.3  |



TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFL

**CANDELA DISTRIBUTION (continued):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 112.5° | 567.7  | 577.6  | 575.8  | 571.2  | 567.7  |
| 115°   | 643.6  | 652.8  | 650.0  | 648.2  | 643.6  |
| 117.5° | 718.8  | 731.5  | 723.5  | 718.8  | 714.3  |
| 120°   | 794.7  | 807.4  | 794.7  | 794.7  | 789.5  |
| 122.5° | 863.7  | 879.8  | 871.8  | 867.1  | 863.7  |
| 125°   | 936.1  | 950.5  | 945.9  | 940.7  | 939.0  |
| 127.5° | 1006.8 | 1024.6 | 1018.3 | 1011.4 | 1006.8 |
| 130°   | 1072.9 | 1093.6 | 1090.7 | 1087.3 | 1080.9 |
| 132.5° | 1147.0 | 1163.1 | 1164.2 | 1156.2 | 1151.6 |
| 135°   | 1210.8 | 1228.6 | 1232.1 | 1230.3 | 1225.7 |
| 137.5° | 1282.0 | 1296.4 | 1299.2 | 1298.1 | 1291.2 |
| 140°   | 1344.7 | 1359.1 | 1367.1 | 1367.1 | 1360.8 |
| 142.5° | 1409.0 | 1423.4 | 1428.0 | 1429.7 | 1423.4 |
| 145°   | 1470.0 | 1481.4 | 1490.6 | 1492.4 | 1486.1 |
| 147.5° | 1524.6 | 1538.9 | 1545.8 | 1548.7 | 1542.4 |
| 150°   | 1580.9 | 1590.6 | 1597.0 | 1602.1 | 1597.0 |
| 152.5° | 1630.8 | 1640.6 | 1648.6 | 1655.0 | 1648.6 |
| 155°   | 1680.8 | 1685.4 | 1690.7 | 1698.7 | 1693.5 |
| 157.5° | 1724.0 | 1727.4 | 1730.3 | 1741.8 | 1733.7 |
| 160°   | 1762.5 | 1765.9 | 1767.6 | 1777.4 | 1770.5 |
| 162.5° | 1798.1 | 1798.1 | 1799.8 | 1810.7 | 1802.7 |
| 165°   | 1828.5 | 1826.8 | 1826.8 | 1838.3 | 1830.2 |
| 167.5° | 1856.1 | 1851.0 | 1851.0 | 1862.4 | 1854.4 |
| 170°   | 1876.8 | 1872.2 | 1870.5 | 1882.0 | 1872.2 |
| 172.5° | 1891.2 | 1886.5 | 1884.8 | 1896.3 | 1886.5 |
| 175°   | 1902.6 | 1898.1 | 1894.6 | 1906.1 | 1896.3 |
| 177.5° | 1909.0 | 1904.4 | 1900.9 | 1910.7 | 1900.9 |
| 180°   | 1906.1 | 1906.1 | 1906.1 | 1906.1 | 1906.1 |

TEST NUMBER: P918778

CATALOG NUMBER: DFN2DIP-4P4F0-080D070US935-FLLFLL

**CIE UGR TABLE:**

| Reflectances:   |      |                  |       |       |       |       |                |       |       |       |       |
|-----------------|------|------------------|-------|-------|-------|-------|----------------|-------|-------|-------|-------|
| Ceiling         |      | 0.7              | 0.7   | 0.5   | 0.5   | 0.3   | 0.7            | 0.7   | 0.5   | 0.5   | 0.3   |
| Wall            |      | 0.5              | 0.3   | 0.5   | 0.3   | 0.3   | 0.5            | 0.3   | 0.5   | 0.3   | 0.3   |
| Reference plane |      | 0.2              | 0.2   | 0.2   | 0.2   | 0.2   | 0.2            | 0.2   | 0.2   | 0.2   | 0.2   |
| Room dimensions |      | Viewed crosswise |       |       |       |       | Viewed endwise |       |       |       |       |
| X=2H            | Y=2H | 9.76             | 10.68 | 10.66 | 11.60 | 12.78 | 9.32           | 10.24 | 10.22 | 11.16 | 12.34 |
|                 | 3H   | 11.43            | 12.26 | 12.35 | 13.19 | 14.39 | 10.94          | 11.77 | 11.86 | 12.70 | 13.90 |
|                 | 4H   | 12.03            | 12.81 | 12.96 | 13.74 | 14.96 | 11.53          | 12.31 | 12.46 | 13.25 | 14.46 |
|                 | 6H   | 12.43            | 13.15 | 13.37 | 14.10 | 15.32 | 11.93          | 12.65 | 12.87 | 13.59 | 14.82 |
|                 | 8H   | 12.54            | 13.23 | 13.49 | 14.19 | 15.41 | 12.04          | 12.73 | 12.99 | 13.69 | 14.91 |
|                 | 12H  | 12.59            | 13.25 | 13.55 | 14.20 | 15.45 | 12.08          | 12.74 | 13.04 | 13.69 | 14.94 |
| 4H              | 2H   | 10.23            | 11.01 | 11.17 | 11.95 | 13.16 | 9.88           | 10.66 | 10.81 | 11.59 | 12.81 |
|                 | 3H   | 12.11            | 12.76 | 13.05 | 13.73 | 14.96 | 11.70          | 12.35 | 12.65 | 13.32 | 14.55 |
|                 | 4H   | 12.83            | 13.42 | 13.78 | 14.39 | 15.64 | 12.41          | 13.00 | 13.36 | 13.96 | 15.22 |
|                 | 6H   | 13.35            | 13.87 | 14.32 | 14.85 | 16.10 | 12.92          | 13.43 | 13.89 | 14.42 | 15.67 |
|                 | 8H   | 13.51            | 13.99 | 14.48 | 14.97 | 16.23 | 13.07          | 13.55 | 14.04 | 14.53 | 15.79 |
|                 | 12H  | 13.59            | 14.02 | 14.57 | 15.01 | 16.29 | 13.14          | 13.57 | 14.13 | 14.56 | 15.84 |
| 8H              | 4H   | 13.03            | 13.51 | 14.00 | 14.49 | 15.76 | 12.66          | 13.13 | 13.62 | 14.11 | 15.38 |
|                 | 6H   | 13.67            | 14.07 | 14.67 | 15.09 | 16.35 | 13.29          | 13.69 | 14.28 | 14.71 | 15.97 |
|                 | 8H   | 13.90            | 14.25 | 14.90 | 15.26 | 16.54 | 13.50          | 13.85 | 14.51 | 14.86 | 16.15 |
|                 | 12H  | 14.04            | 14.34 | 15.04 | 15.35 | 16.68 | 13.62          | 13.93 | 14.63 | 14.93 | 16.26 |
| 12H             | 4H   | 13.02            | 13.45 | 14.01 | 14.45 | 15.72 | 12.65          | 13.09 | 13.64 | 14.08 | 15.35 |
|                 | 6H   | 13.70            | 14.05 | 14.71 | 15.06 | 16.35 | 13.33          | 13.68 | 14.33 | 14.69 | 15.97 |
|                 | 8H   | 13.95            | 14.26 | 14.96 | 15.26 | 16.59 | 13.57          | 13.88 | 14.58 | 14.88 | 16.21 |