

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P905148

Luminaire Tested: DFN2DIP-HX2F0-020D020US835-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P905148
REPORT IS A COMBINATION OF REPORTS P899152 AND P896039
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX2F0-020D020US835-RLLFLL
Description: 2 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3470.0 lumens
Efficiency: N/A
Efficacy: 113.8 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 1.99' x L: 2.3' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 30.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9968
Total Harmonic Distortion (THDi): 0.064
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83	68	68	68	55	55	55
1	98	94	90	87	90	87	84	81	73	71	69	61	59	58	50	49	48
2	90	83	77	72	82	76	71	67	65	61	58	54	51	49	44	42	41
3	82	73	66	60	75	68	61	57	58	53	49	48	45	42	40	37	35
4	75	65	57	51	69	60	54	48	51	46	42	43	40	36	36	33	31
5	69	58	50	44	64	54	47	42	46	41	37	39	35	32	32	29	27
6	64	52	44	39	59	49	42	37	42	36	32	35	31	28	30	26	24
7	59	47	40	34	55	44	37	32	38	33	29	32	28	25	27	24	22
8	55	43	36	30	51	40	33	29	35	29	26	30	26	23	25	22	20
9	51	39	32	27	47	37	30	26	32	27	23	27	23	20	23	20	18
10	48	36	29	24	44	34	28	23	30	24	21	25	21	19	22	18	16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1948	1948	1948
5°	1948	1912	1925
10°	1925	1870	1859
15°	1896	1803	1759
20°	1857	1714	1637
25°	1818	1615	1520
30°	1767	1513	1372
35°	1716	1405	1243
40°	1665	1292	1095
45°	1605	1169	961
50°	1543	1045	831
55°	1478	912	705
60°	1403	775	577
65°	1316	635	516
70°	1210	505	462
75°	1078	436	413
80°	887	354	347
85°	579	218	244

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1605 cd/sqm

TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLFL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	77.5	2.2
10°-20°	212.7	6.1
20°-30°	298.6	8.6
30°-40°	325.5	9.4
40°-50°	299.1	8.6
50°-60°	234.9	6.8
60°-70°	152.9	4.4
70°-80°	78.7	2.3
80°-90°	21.9	0.6
90°-100°	39.1	1.1
100°-110°	124.4	3.6
110°-120°	212.8	6.1
120°-130°	279.9	8.1
130°-140°	314.2	9.1
140°-150°	308.1	8.9
150°-160°	258.4	7.4
160°-170°	171.4	4.9
170°-180°	59.9	1.7
0°-30°	588.7	17.0
0°-40°	914.2	26.3
0°-60°	1448.3	41.7
0°-90°	1701.8	49.0
90°-120°	376.3	10.8
90°-150°	1278.5	36.8
90°-180°	1768.0	51.0
0°-180°	3470.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	827	827	827	827	827	
5°	827	823	813	820	818	78
15°	786	778	752	738	731	222
25°	714	690	640	610	598	328
35°	615	577	511	464	447	385
45°	503	452	374	321	303	388
55°	382	324	243	198	184	342
65°	258	198	130	105	102	256
75°	138	85	60	55	54	146
85°	32	16	14	14	14	37
90°	1	7	19	18	18	3
95°	28	33	34	34	33	31
105°	115	116	118	118	118	121
115°	214	217	216	215	214	211
125°	311	315	314	312	312	278
135°	402	408	409	408	407	311
145°	488	492	495	495	493	305
155°	558	559	561	564	562	257
165°	607	606	606	610	607	171
175°	631	630	629	632	629	60
180°	632	632	632	632	632	

TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLFL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	826.6	826.6	826.6	826.6	826.6
2.5°	830.3	826.6	818.3	825.9	824.4
5°	826.6	822.9	813.1	819.9	817.6
7.5°	819.9	815.4	804.9	807.9	804.1
10°	810.9	805.6	790.7	788.4	784.0
12.5°	799.7	792.9	772.7	768.3	760.0
15°	786.2	777.9	752.5	738.3	730.9
17.5°	770.5	758.5	727.1	710.6	698.7
20°	752.5	737.5	700.2	681.5	665.0
22.5°	733.1	715.9	672.5	647.1	635.9
25°	713.7	689.7	640.3	609.7	598.4
27.5°	690.5	665.0	610.4	575.2	558.0
30°	665.8	637.3	577.5	539.4	519.1
32.5°	641.8	607.4	546.1	501.2	482.5
35°	614.9	576.8	511.0	463.8	447.3
37.5°	588.7	547.5	478.0	426.4	407.7
40°	561.0	516.2	443.6	390.5	371.0
42.5°	532.6	484.8	409.2	353.8	335.2
45°	502.7	452.5	374.1	320.9	302.9
47.5°	474.3	421.2	340.4	287.2	270.8
50°	442.9	389.8	307.5	255.8	240.2
52.5°	412.1	356.0	276.0	226.7	212.5
55°	382.2	323.9	243.1	198.3	184.0
57.5°	351.6	291.7	214.0	172.1	160.1
60°	320.2	260.3	183.3	145.2	133.2
62.5°	289.5	229.7	157.1	121.2	115.2
65°	258.1	197.5	130.2	104.8	102.5
67.5°	228.2	167.5	104.8	92.0	89.8
70°	196.7	138.4	86.7	79.3	76.3
72.5°	166.8	111.4	72.5	66.6	65.1
75°	137.6	85.2	59.8	54.6	53.9
77.5°	108.5	60.6	47.1	44.1	42.6
80°	81.5	43.4	35.9	32.9	32.9
82.5°	56.8	29.2	24.7	23.2	23.2
85°	32.1	16.4	14.2	14.2	14.2
87.5°	12.0	6.0	6.0	5.2	5.2
90°	0.6	6.9	18.7	17.5	18.1
92.5°	11.8	16.0	16.6	17.2	17.2
95°	27.8	33.2	34.1	34.1	33.2
97.5°	46.3	51.3	53.4	53.4	53.4
100°	67.7	72.1	73.6	73.6	73.0
102.5°	90.2	93.4	95.5	96.1	95.5
105°	114.8	116.3	117.5	118.4	118.4
107.5°	139.2	141.5	141.5	141.9	139.2
110°	162.9	165.9	165.9	165.9	164.4

TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLFL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	188.4	191.6	191.1	189.5	188.4
115°	213.6	216.6	215.7	215.1	213.6
117.5°	238.6	242.8	240.1	238.6	237.0
120°	263.7	267.9	263.7	263.7	262.0
122.5°	286.6	291.9	289.3	287.8	286.6
125°	310.6	315.4	313.9	312.2	311.6
127.5°	334.1	340.0	337.9	335.6	334.1
130°	356.0	362.9	361.9	360.8	358.7
132.5°	380.6	386.0	386.3	383.7	382.1
135°	401.8	407.7	408.8	408.3	406.7
137.5°	425.4	430.2	431.2	430.8	428.5
140°	446.2	451.0	453.7	453.7	451.6
142.5°	467.6	472.3	473.9	474.4	472.3
145°	487.8	491.6	494.7	495.2	493.1
147.5°	505.9	510.7	513.0	513.9	511.8
150°	524.6	527.8	529.9	531.6	529.9
152.5°	541.2	544.4	547.1	549.2	547.1
155°	557.8	559.3	561.0	563.7	562.0
157.5°	572.1	573.2	574.2	578.0	575.3
160°	584.9	586.0	586.6	589.8	587.5
162.5°	596.7	596.7	597.2	600.9	598.2
165°	606.8	606.2	606.2	610.0	607.4
167.5°	615.9	614.2	614.2	618.0	615.4
170°	622.8	621.3	620.7	624.5	621.3
172.5°	627.6	626.0	625.5	629.3	626.0
175°	631.4	629.9	628.7	632.5	629.3
177.5°	633.5	632.0	630.8	634.0	630.8
180°	632.5	632.5	632.5	632.5	632.5

TEST NUMBER: P905148

CATALOG NUMBER: DFN2DIP-HX2F0-020D020US835-RLFL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	9.23	10.06	10.21	11.04	12.32	5.22	6.04	6.19	7.02	8.31
	3H	10.89	11.62	11.87	12.61	13.92	6.39	7.12	7.37	8.12	9.43
	4H	11.48	12.17	12.47	13.17	14.48	6.83	7.52	7.82	8.52	9.84
	6H	11.88	12.52	12.88	13.52	14.85	7.13	7.77	8.14	8.77	10.10
	8H	11.99	12.60	13.01	13.62	14.94	7.22	7.82	8.23	8.84	10.17
	12H	12.04	12.62	13.06	13.63	14.98	7.25	7.83	8.27	8.84	10.19
4H	2H	9.25	9.94	10.25	10.94	12.25	5.80	6.49	6.80	7.49	8.81
	3H	11.05	11.62	12.06	12.65	13.98	7.13	7.71	8.14	8.73	10.06
	4H	11.72	12.25	12.74	13.26	14.62	7.66	8.19	8.68	9.20	10.56
	6H	12.21	12.66	13.24	13.70	15.05	8.06	8.51	9.09	9.55	10.91
	8H	12.37	12.79	13.40	13.83	15.19	8.18	8.60	9.21	9.64	11.00
	12H	12.45	12.83	13.50	13.88	15.25	8.24	8.62	9.28	9.66	11.04
8H	4H	11.68	12.11	12.71	13.14	14.50	7.93	8.35	8.96	9.38	10.75
	6H	12.22	12.57	13.27	13.64	15.01	8.42	8.77	9.47	9.84	11.21
	8H	12.42	12.73	13.48	13.79	15.17	8.60	8.90	9.66	9.96	11.35
	12H	12.54	12.81	13.61	13.87	15.29	8.70	8.97	9.77	10.03	11.45
12H	4H	11.63	12.01	12.68	13.06	14.43	7.93	8.31	8.97	9.35	10.73
	6H	12.19	12.50	13.26	13.56	14.94	8.46	8.77	9.52	9.83	11.21
	8H	12.40	12.67	13.46	13.72	15.15	8.66	8.93	9.72	9.98	11.41