

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P924328

Luminaire Tested: DFN2DIP-HX2F0-060D030US950-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P924328
REPORT IS A COMBINATION OF REPORTS P899170 AND P896039
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX2F0-060D030US950-RLLFLL
Description: 2 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7398.2 lumens
Efficiency: N/A
Efficacy: 91.1 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 1.99' x L: 2.3' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 81.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9971
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92		81	81	81		71
1	102	98	94	91	96	92	89	86	82	79	77		72	70	69		63
2	93	86	80	75	88	81	76	72	72	68	65		64	61	58		57
3	86	76	69	63	80	72	66	61	65	59	55		57	53	50		51
4	79	68	60	54	74	65	58	52	58	52	48		52	47	44		46
5	73	61	53	47	68	58	51	45	52	46	42		47	42	38		42
6	67	55	47	41	63	52	45	40	47	41	37		42	38	34		38
7	62	50	42	37	59	48	40	35	43	37	33		39	34	30		35
8	58	46	38	33	55	44	37	32	40	34	29		36	31	27		32
9	54	42	35	29	51	40	33	29	36	31	27		33	28	25		30
10	51	39	31	27	48	37	30	26	34	28	24		31	26	23		28

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5574	5574	5574
5°	5574	5472	5510
10°	5510	5352	5321
15°	5425	5162	5034
20°	5316	4906	4686
25°	5204	4621	4351
30°	5057	4331	3928
35°	4912	4020	3557
40°	4765	3699	3134
45°	4594	3345	2751
50°	4417	2989	2377
55°	4231	2611	2019
60°	4015	2217	1652
65°	3767	1818	1476
70°	3465	1446	1321
75°	3085	1249	1183
80°	2539	1013	996
85°	1661	624	697

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 4594 cd/sqm

TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLFL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	221.7	3.0
10°-20°	608.7	8.2
20°-30°	854.5	11.6
30°-40°	931.5	12.6
40°-50°	856.2	11.6
50°-60°	672.4	9.1
60°-70°	437.7	5.9
70°-80°	225.3	3.0
80°-90°	60.1	0.8
90°-100°	56.0	0.8
100°-110°	178.0	2.4
110°-120°	304.6	4.1
120°-130°	400.5	5.4
130°-140°	449.6	6.1
140°-150°	440.9	6.0
150°-160°	369.8	5.0
160°-170°	245.3	3.3
170°-180°	85.7	1.2
0°-30°	1684.9	22.8
0°-40°	2616.4	35.4
0°-60°	4144.9	56.0
0°-90°	4868.0	65.8
90°-120°	538.5	7.3
90°-150°	1829.5	24.7
90°-180°	2530.0	34.2
0°-180°	7398.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2366	2366	2366	2366	2366	
5°	2366	2355	2327	2346	2340	224
15°	2250	2226	2154	2113	2092	634
25°	2042	1974	1833	1745	1713	939
35°	1760	1651	1462	1327	1280	1102
45°	1439	1295	1071	918	867	1111
55°	1094	927	696	567	527	978
65°	739	565	372	300	293	732
75°	394	244	171	156	154	417
85°	92	47	41	41	41	106
90°	1	10	27	25	26	7
95°	40	48	49	49	48	44
105°	164	166	168	169	169	173
115°	306	310	309	308	306	302
125°	445	451	449	447	446	397
135°	575	583	585	584	582	444
145°	698	704	708	709	706	436
155°	798	800	803	807	804	367
165°	868	868	868	873	869	245
175°	904	901	900	905	900	86
180°	905	905	905	905	905	

TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2365.7	2365.7	2365.7	2365.7	2365.7
2.5°	2376.4	2365.7	2342.1	2363.6	2359.3
5°	2365.7	2355.0	2327.1	2346.5	2340.1
7.5°	2346.5	2333.7	2303.7	2312.1	2301.4
10°	2320.7	2305.7	2263.1	2256.5	2243.7
12.5°	2288.7	2269.4	2211.5	2198.8	2175.1
15°	2250.1	2226.4	2153.8	2113.1	2091.7
17.5°	2205.2	2170.8	2080.9	2033.8	1999.6
20°	2153.8	2110.8	2003.9	1950.5	1903.2
22.5°	2098.1	2048.8	1924.6	1851.9	1819.9
25°	2042.5	1973.9	1832.6	1745.0	1712.7
27.5°	1976.2	1903.2	1747.0	1646.3	1597.1
30°	1905.5	1824.0	1652.7	1543.7	1485.8
32.5°	1836.9	1738.4	1563.0	1434.4	1380.8
35°	1759.9	1650.7	1462.4	1327.4	1280.2
37.5°	1685.0	1567.0	1368.1	1220.3	1166.8
40°	1605.7	1477.4	1269.5	1117.5	1061.9
42.5°	1524.4	1387.4	1171.1	1012.6	959.2
45°	1438.7	1295.2	1070.6	918.3	867.0
47.5°	1357.4	1205.5	974.2	822.1	775.0
50°	1267.5	1115.5	880.0	732.1	687.4
52.5°	1179.5	1019.0	790.0	648.7	608.1
55°	1094.0	927.0	695.8	567.4	526.7
57.5°	1006.3	834.9	612.4	492.5	458.1
60°	916.3	745.1	524.5	415.5	381.1
62.5°	828.6	657.4	449.5	346.9	329.8
65°	738.7	565.1	372.5	299.8	293.3
67.5°	653.0	479.5	299.8	263.3	256.9
70°	563.1	396.1	248.2	227.0	218.3
72.5°	477.5	318.9	207.6	190.6	186.2
75°	393.9	243.9	171.2	156.3	154.3
77.5°	310.5	173.3	134.9	126.3	122.0
80°	233.3	124.2	102.7	94.3	94.3
82.5°	162.7	83.6	70.6	66.3	66.3
85°	92.0	47.0	40.6	40.6	40.6
87.5°	34.3	17.1	17.1	15.0	15.0
90°	0.9	9.8	26.7	25.1	25.9
92.5°	16.9	22.9	23.8	24.5	24.5
95°	39.9	47.5	48.8	48.8	47.5
97.5°	66.3	73.4	76.4	76.4	76.4
100°	96.8	103.1	105.3	105.3	104.6
102.5°	129.1	133.8	136.7	137.6	136.7
105°	164.3	166.5	168.1	169.4	169.4
107.5°	199.2	202.4	202.4	203.0	199.2
110°	233.1	237.5	237.5	237.5	235.3

TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	269.6	274.3	273.4	271.2	269.6
115°	305.7	310.0	308.6	307.9	305.7
117.5°	341.3	347.4	343.5	341.3	339.1
120°	377.4	383.4	377.4	377.4	374.9
122.5°	410.1	417.8	413.9	411.7	410.1
125°	444.6	451.3	449.1	446.7	445.9
127.5°	478.0	486.5	483.6	480.2	478.0
130°	509.4	519.3	517.9	516.3	513.3
132.5°	544.6	552.3	552.8	549.0	546.8
135°	575.0	583.4	585.1	584.2	582.0
137.5°	608.7	615.6	617.0	616.5	613.1
140°	638.5	645.4	649.2	649.2	646.1
142.5°	669.1	675.9	678.1	679.0	675.9
145°	698.0	703.5	707.9	708.6	705.7
147.5°	724.0	730.8	734.0	735.4	732.4
150°	750.7	755.4	758.3	760.8	758.3
152.5°	774.5	779.0	782.9	785.9	782.9
155°	798.2	800.3	802.8	806.6	804.2
157.5°	818.6	820.2	821.7	827.1	823.3
160°	836.9	838.6	839.4	844.0	840.8
162.5°	853.8	853.8	854.7	859.8	856.0
165°	868.3	867.5	867.5	872.9	869.1
167.5°	881.4	878.9	878.9	884.4	880.5
170°	891.2	889.0	888.3	893.7	889.0
172.5°	898.0	895.9	895.0	900.5	895.9
175°	903.5	901.3	899.7	905.2	900.5
177.5°	906.5	904.3	902.7	907.3	902.7
180°	905.2	905.2	905.2	905.2	905.2

TEST NUMBER: P924328

CATALOG NUMBER: DFN2DIP-HX2F0-060D030US950-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.34	15.32	15.16	16.15	17.18	10.32	11.30	11.14	12.13	13.16
	3H	16.00	16.88	16.83	17.72	18.78	11.51	12.38	12.34	13.22	14.28
	4H	16.60	17.43	17.45	18.28	19.35	11.95	12.78	12.80	13.63	14.70
	6H	17.01	17.77	17.87	18.63	19.71	12.27	13.03	13.12	13.88	14.96
	8H	17.13	17.85	18.00	18.73	19.81	12.35	13.08	13.22	13.95	15.03
	12H	17.19	17.87	18.06	18.74	19.85	12.39	13.08	13.26	13.95	15.06
4H	2H	14.37	15.20	15.22	16.05	17.12	10.92	11.75	11.77	12.60	13.67
	3H	16.19	16.87	17.05	17.75	18.84	12.27	12.95	13.13	13.83	14.92
	4H	16.86	17.49	17.74	18.37	19.48	12.80	13.43	13.68	14.31	15.42
	6H	17.36	17.90	18.25	18.80	19.92	13.21	13.75	14.10	14.66	15.77
	8H	17.53	18.03	18.42	18.93	20.05	13.34	13.84	14.23	14.74	15.86
	12H	17.62	18.07	18.53	18.98	20.12	13.40	13.85	14.31	14.77	15.90
8H	4H	16.84	17.34	17.73	18.24	19.37	13.08	13.58	13.97	14.48	15.61
	6H	17.38	17.80	18.30	18.74	19.86	13.58	14.00	14.50	14.94	16.06
	8H	17.58	17.95	18.51	18.88	20.03	13.76	14.13	14.69	15.06	16.20
	12H	17.71	18.03	18.64	18.96	20.16	13.87	14.19	14.80	15.12	16.31
12H	4H	16.80	17.25	17.71	18.17	19.30	13.09	13.54	14.00	14.46	15.59
	6H	17.36	17.72	18.29	18.66	19.80	13.62	13.99	14.55	14.93	16.07
	8H	17.57	17.89	18.50	18.81	20.01	13.83	14.15	14.76	15.07	16.27