

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P908017

Luminaire Tested: DFN2DIP-HX3F0-040D070US840-RLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P908017
REPORT IS A COMBINATION OF REPORTS P900780 AND P897645
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX3F0-040D070US840-RLLONL
Description: 3 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 10431.9 lumens
Efficiency: N/A
Efficacy: 118.7 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.84' x L: 3.28' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 87.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9968
Total Harmonic Distortion (THDi): 0.064
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	103	103	103	103	93	93	93	93	74	74	74		56	56	56		40
1	94	90	87	83	85	81	78	76	65	63	61		50	49	48		36
2	86	79	73	68	77	72	67	62	57	54	51		44	42	40		32
3	79	70	63	57	71	63	57	53	51	47	43		39	37	34		29
4	72	62	54	49	65	56	50	45	45	41	37		35	32	30		26
5	66	55	47	42	59	50	43	38	41	36	32		32	28	26		24
6	61	49	42	36	55	45	38	33	37	32	28		29	25	23		21
7	56	45	37	32	51	41	34	29	33	28	25		26	23	20		20
8	52	41	33	28	47	37	31	26	30	25	22		24	21	18		18
9	49	37	30	25	44	34	27	23	28	23	20		22	19	16		17
10	45	34	27	22	41	31	25	21	26	21	18		20	17	15		16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1934	1934	1934
5°	1936	1902	1914
10°	1916	1863	1851
15°	1889	1800	1754
20°	1853	1714	1635
25°	1816	1618	1520
30°	1767	1519	1374
35°	1720	1413	1247
40°	1671	1304	1101
45°	1614	1183	968
50°	1555	1060	839
55°	1494	930	715
60°	1423	793	587
65°	1341	655	527
70°	1242	526	476
75°	1117	461	431
80°	936	382	370
85°	639	249	272

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1614 cd/sqm

TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.5	1.5
10°-20°	429.5	4.1
20°-30°	603.0	5.8
30°-40°	657.4	6.3
40°-50°	604.2	5.8
50°-60°	474.5	4.5
60°-70°	308.9	3.0
70°-80°	159.0	1.5
80°-90°	44.8	0.4
90°-100°	78.7	0.8
100°-110°	293.3	2.8
110°-120°	777.8	7.5
120°-130°	1290.0	12.4
130°-140°	1370.3	13.1
140°-150°	1273.5	12.2
150°-160°	1023.9	9.8
160°-170°	659.7	6.3
170°-180°	227.1	2.2
0°-30°	1189.0	11.4
0°-40°	1846.4	17.7
0°-60°	2925.1	28.0
0°-90°	3437.7	33.0
90°-120°	1149.7	11.0
90°-150°	5083.5	48.7
90°-180°	6994.0	67.0
0°-180°	10431.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1670	1670	1670	1670	1670	
5°	1670	1662	1642	1656	1651	158
15°	1588	1571	1520	1491	1476	447
25°	1441	1393	1293	1231	1209	663
35°	1242	1165	1032	937	903	777
45°	1015	914	756	648	612	784
55°	772	654	491	400	372	690
65°	521	399	263	212	207	517
75°	278	172	121	110	109	294
85°	65	33	29	29	29	75
90°	2	21	34	43	47	10
95°	112	55	67	76	74	133
105°	525	577	105	124	131	561
115°	993	1022	1065	266	142	977
125°	1403	1426	1459	1471	1476	1252
135°	1737	1764	1780	1797	1794	1342
145°	2015	2013	2042	2054	2046	1260
155°	2218	2203	2224	2234	2220	1022
165°	2337	2327	2332	2344	2332	660
175°	2391	2379	2382	2394	2377	228
180°	2386	2386	2386	2386	2386	

TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1669.5	1669.5	1669.5	1669.5	1669.5
2.5°	1677.1	1669.5	1652.8	1668.1	1665.0
5°	1669.5	1661.9	1642.2	1655.9	1651.4
7.5°	1655.9	1646.9	1625.8	1631.6	1624.2
10°	1637.8	1627.2	1597.0	1592.4	1583.5
12.5°	1615.2	1601.5	1560.6	1551.7	1535.0
15°	1587.9	1571.2	1519.9	1491.3	1476.2
17.5°	1556.2	1532.0	1468.4	1435.3	1411.1
20°	1519.9	1489.7	1414.1	1376.4	1343.1
22.5°	1480.7	1445.9	1358.2	1306.9	1284.3
25°	1441.4	1393.0	1293.2	1231.4	1208.6
27.5°	1394.6	1343.1	1232.8	1161.9	1127.0
30°	1344.7	1287.2	1166.3	1089.3	1048.5
32.5°	1296.4	1226.8	1103.0	1012.3	974.4
35°	1242.0	1164.9	1032.0	936.8	903.4
37.5°	1189.1	1105.9	965.4	861.1	823.4
40°	1133.2	1042.6	896.0	788.7	749.4
42.5°	1075.7	979.1	826.5	714.6	676.9
45°	1015.3	914.0	755.5	648.1	611.9
47.5°	958.0	850.7	687.5	580.2	546.9
50°	894.4	787.2	621.0	516.6	485.0
52.5°	832.4	719.1	557.5	457.8	429.1
55°	772.0	654.2	491.0	400.4	371.7
57.5°	710.1	589.3	432.1	347.5	323.4
60°	646.6	525.7	370.1	293.2	269.0
62.5°	584.8	463.9	317.2	244.8	232.8
65°	521.3	398.8	262.9	211.6	206.9
67.5°	460.9	338.4	211.6	185.8	181.3
70°	397.4	279.5	175.2	160.2	154.0
72.5°	337.0	225.1	146.5	134.5	131.5
75°	277.9	172.2	120.9	110.3	108.9
77.5°	219.1	122.3	95.2	89.2	86.0
80°	164.6	87.7	72.4	66.6	66.6
82.5°	114.8	59.0	49.9	46.8	46.8
85°	64.9	33.2	28.7	28.7	28.7
87.5°	24.2	12.0	12.0	10.6	10.6
90°	1.6	20.7	34.4	43.2	46.6
92.5°	43.2	36.3	41.4	44.9	46.6
95°	112.1	55.1	67.3	76.0	74.2
97.5°	201.9	60.5	88.0	93.3	94.9
100°	305.7	69.1	98.4	112.1	115.6
102.5°	419.4	416.2	101.9	120.8	126.0
105°	524.8	576.6	105.3	124.2	131.2
107.5°	647.3	690.4	108.9	127.7	134.7
110°	764.9	800.9	302.2	129.6	136.3



TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	875.4	906.3	877.0	132.8	138.1
115°	992.6	1021.9	1065.1	265.9	141.7
117.5°	1094.5	1128.9	1158.4	911.4	459.2
120°	1208.4	1234.3	1265.5	1286.2	1053.1
122.5°	1304.9	1332.6	1367.4	1377.6	1379.4
125°	1403.4	1425.9	1458.8	1470.9	1475.9
127.5°	1493.2	1517.3	1543.4	1560.6	1562.3
130°	1577.8	1605.5	1624.4	1643.5	1641.8
132.5°	1664.2	1686.7	1705.6	1721.1	1719.5
135°	1736.7	1764.3	1779.8	1797.2	1793.7
137.5°	1812.5	1833.3	1850.7	1867.9	1862.8
140°	1886.7	1900.7	1919.6	1935.1	1926.5
142.5°	1949.0	1961.2	1983.5	1997.2	1988.6
145°	2014.7	2012.9	2042.2	2054.3	2045.7
147.5°	2071.4	2066.4	2095.7	2104.3	2097.5
150°	2126.8	2114.8	2142.4	2152.6	2144.0
152.5°	2173.3	2159.6	2185.5	2195.9	2183.8
155°	2218.3	2202.8	2223.5	2233.8	2220.1
157.5°	2254.5	2240.8	2256.3	2268.5	2254.5
160°	2285.7	2275.2	2285.7	2295.9	2283.8
162.5°	2313.2	2302.9	2311.5	2323.6	2308.0
165°	2337.3	2327.1	2332.2	2344.3	2332.2
167.5°	2356.4	2345.9	2351.3	2363.4	2347.8
170°	2372.0	2361.6	2365.0	2377.1	2361.6
172.5°	2382.3	2372.0	2375.5	2387.5	2372.0
175°	2390.9	2378.7	2382.3	2394.3	2377.1
177.5°	2394.3	2382.3	2384.1	2396.2	2380.6
180°	2385.7	2385.7	2385.7	2385.7	2385.7

TEST NUMBER: P908017

CATALOG NUMBER: DFN2DIP-HX3F0-040D070US840-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	7.55	8.26	8.65	9.35	10.85	3.53	4.24	4.63	5.33	6.83
	3H	9.21	9.85	10.32	10.95	12.46	4.70	5.34	5.81	6.44	7.95
	4H	9.81	10.41	10.93	11.51	13.03	5.15	5.75	6.26	6.85	8.37
	6H	10.22	10.77	11.34	11.88	13.41	5.46	6.01	6.58	7.11	8.64
	8H	10.34	10.86	11.47	11.98	13.51	5.54	6.07	6.67	7.19	8.71
	12H	10.39	10.89	11.53	12.00	13.55	5.58	6.08	6.71	7.19	8.74
4H	2H	7.56	8.16	8.68	9.26	10.78	4.11	4.71	5.23	5.81	7.33
	3H	9.37	9.86	10.49	10.99	12.52	5.44	5.94	6.57	7.07	8.60
	4H	10.05	10.51	11.18	11.62	13.17	5.98	6.44	7.11	7.55	9.11
	6H	10.55	10.94	11.69	12.08	13.62	6.39	6.78	7.53	7.92	9.46
	8H	10.72	11.08	11.85	12.21	13.77	6.51	6.88	7.65	8.01	9.57
	12H	10.80	11.13	11.95	12.27	13.84	6.57	6.90	7.72	8.04	9.61
8H	4H	10.00	10.37	11.14	11.50	13.06	6.25	6.61	7.38	7.74	9.30
	6H	10.56	10.86	11.72	12.03	13.59	6.75	7.06	7.91	8.23	9.79
	8H	10.77	11.03	11.93	12.18	13.76	6.94	7.20	8.10	8.36	9.93
	12H	10.90	11.13	12.06	12.28	13.89	7.05	7.28	8.22	8.43	10.04
12H	4H	9.95	10.28	11.10	11.42	12.99	6.24	6.58	7.40	7.72	9.28
	6H	10.53	10.80	11.70	11.95	13.53	6.80	7.06	7.96	8.22	9.79
	8H	10.74	10.97	11.91	12.12	13.73	7.00	7.23	8.17	8.38	9.99