

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P921735

Luminaire Tested: DFN2DIP-HX3F0-080D030US940-FLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P921735
REPORT IS A COMBINATION OF REPORTS P900731 AND P897645
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX3F0-080D030US940-FLLONL
Description: 3 foot, Hexagon Define Geo, with Direct Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9710.8 lumens
Efficiency: N/A
Efficacy: 94.4 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 2.84' x L: 3.28' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 102.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9971
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	113	113	113	113	107	107	107	107	96	96	96		86	86	86		77
1	103	98	94	91	97	94	90	87	84	82	79		76	74	72		68
2	94	86	80	74	89	82	76	71	74	69	66		67	63	60		60
3	86	76	68	62	81	72	65	60	65	60	55		59	55	51		53
4	78	67	59	53	74	64	57	51	58	52	47		53	48	44		48
5	72	60	51	45	68	57	50	44	52	46	41		47	42	38		43
6	67	54	45	39	63	52	44	38	47	41	36		43	37	33		39
7	62	49	41	35	58	47	39	34	43	36	32		39	34	30		36
8	57	44	36	31	54	43	35	30	39	33	28		36	30	27		33
9	53	41	33	28	51	39	32	27	36	30	25		33	28	24		30
10	50	38	30	25	48	36	29	24	33	27	23		31	25	22		28

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3215	3215	3215
5°	3219	3168	3190
10°	3191	3123	3145
15°	3143	3070	3076
20°	3078	2996	3005
25°	3014	2908	2924
30°	2933	2827	2820
35°	2856	2731	2711
40°	2763	2633	2607
45°	2669	2536	2500
50°	2566	2433	2377
55°	2459	2315	2263
60°	2337	2175	2133
65°	2204	2029	1979
70°	2035	1851	1813
75°	1801	1638	1658
80°	1519	1367	1365
85°	1077	904	886

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 2669 cd/sqm

TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	261.3	2.7
10°-20°	735.1	7.6
20°-30°	1080.3	11.1
30°-40°	1254.7	12.9
40°-50°	1253.1	12.9
50°-60°	1092.7	11.3
60°-70°	807.7	8.3
70°-80°	457.0	4.7
80°-90°	122.2	1.3
90°-100°	29.8	0.3
100°-110°	111.0	1.1
110°-120°	294.3	3.0
120°-130°	488.2	5.0
130°-140°	518.5	5.3
140°-150°	481.9	5.0
150°-160°	387.5	4.0
160°-170°	249.7	2.6
170°-180°	85.9	0.9
0°-30°	2076.6	21.4
0°-40°	3331.3	34.3
0°-60°	5677.0	58.5
0°-90°	7064.0	72.7
90°-120°	435.1	4.5
90°-150°	1923.7	19.8
90°-180°	2647.0	27.3
0°-180°	9710.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2776	2776	2776	2776	2776	
5°	2776	2765	2736	2757	2752	263
15°	2642	2626	2592	2602	2589	744
25°	2392	2370	2325	2330	2325	1100
35°	2063	2037	1994	1978	1964	1288
45°	1679	1660	1620	1591	1580	1296
55°	1271	1254	1222	1190	1177	1136
65°	857	841	814	790	777	847
75°	448	443	430	414	419	479
85°	109	107	104	96	94	122
90°	1	8	13	16	18	9
95°	42	21	25	29	28	50
105°	199	218	40	47	50	212
115°	376	387	403	101	54	370
125°	531	540	552	557	559	474
135°	657	668	674	680	679	508
145°	762	762	773	777	774	477
155°	840	834	841	845	840	387
165°	884	881	883	887	883	250
175°	905	900	902	906	900	86
180°	903	903	903	903	903	

TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2775.7	2775.7	2775.7	2775.7	2775.7
2.5°	2791.9	2778.6	2749.1	2775.7	2770.6
5°	2775.7	2765.3	2735.9	2757.1	2752.0
7.5°	2757.1	2741.2	2711.8	2733.3	2727.9
10°	2727.9	2709.2	2677.2	2698.4	2690.6
12.5°	2687.7	2671.8	2639.8	2653.1	2647.8
15°	2642.4	2626.5	2591.7	2602.5	2589.2
17.5°	2586.3	2570.4	2535.6	2549.0	2535.6
20°	2524.9	2509.0	2471.6	2479.6	2469.1
22.5°	2463.7	2439.6	2404.8	2404.8	2399.4
25°	2391.5	2370.3	2325.0	2330.0	2325.0
27.5°	2311.3	2292.7	2258.1	2250.1	2236.9
30°	2231.5	2209.9	2170.1	2162.1	2151.3
32.5°	2146.0	2130.1	2087.3	2071.2	2060.5
35°	2063.2	2036.7	1993.9	1977.7	1964.4
37.5°	1969.8	1945.7	1903.0	1884.3	1871.0
40°	1873.8	1852.3	1809.5	1785.7	1774.9
42.5°	1780.4	1758.8	1716.4	1689.4	1673.7
45°	1679.0	1660.3	1620.1	1590.9	1580.2
47.5°	1580.2	1561.5	1518.7	1489.2	1473.4
50°	1476.0	1462.7	1425.2	1387.9	1374.6
52.5°	1374.6	1355.8	1321.3	1291.9	1273.2
55°	1270.6	1254.5	1222.5	1190.5	1177.1
57.5°	1166.4	1153.2	1118.3	1086.3	1075.5
60°	1062.2	1051.8	1014.3	984.9	977.0
62.5°	960.8	942.2	915.5	888.9	878.2
65°	856.9	840.8	814.1	790.1	776.8
67.5°	750.1	736.6	712.7	694.1	683.3
70°	651.3	640.5	616.5	597.8	587.3
72.5°	549.9	539.2	525.8	507.2	499.3
75°	448.3	443.2	429.6	413.8	419.1
77.5°	357.7	346.9	341.5	333.6	325.7
80°	267.1	264.2	258.9	250.9	245.5
82.5°	181.6	181.6	179.0	168.2	168.2
85°	109.3	106.7	104.2	96.0	93.5
87.5°	48.2	42.8	37.4	29.4	26.7
90°	0.6	7.8	13.0	16.4	17.6
92.5°	16.4	13.7	15.7	17.0	17.6
95°	42.4	20.9	25.4	28.8	28.1
97.5°	76.4	22.9	33.3	35.3	35.9
100°	115.7	26.1	37.3	42.4	43.8
102.5°	158.7	157.5	38.5	45.7	47.7
105°	198.6	218.2	39.9	47.0	49.7
107.5°	245.0	261.3	41.2	48.3	51.0
110°	289.4	303.1	114.3	49.0	51.6

TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	331.3	343.0	331.9	50.3	52.3
115°	375.6	386.7	403.1	100.6	53.6
117.5°	414.2	427.2	438.4	344.9	173.8
120°	457.3	467.1	478.8	486.7	398.5
122.5°	493.8	504.4	517.5	521.3	522.0
125°	531.1	539.6	552.1	556.6	558.6
127.5°	565.1	574.2	584.1	590.6	591.2
130°	597.1	607.6	614.7	621.9	621.3
132.5°	629.7	638.3	645.4	651.3	650.7
135°	657.2	667.7	673.5	680.1	678.8
137.5°	685.9	693.8	700.3	706.9	704.9
140°	714.0	719.3	726.4	732.3	729.1
142.5°	737.6	742.2	750.6	755.8	752.6
145°	762.4	761.7	772.8	777.4	774.1
147.5°	783.9	781.9	793.1	796.3	793.7
150°	804.9	800.3	810.7	814.6	811.4
152.5°	822.4	817.3	827.1	831.0	826.4
155°	839.5	833.7	841.4	845.3	840.2
157.5°	853.2	848.0	853.9	858.4	853.2
160°	865.0	861.0	865.0	868.9	864.2
162.5°	875.4	871.5	874.8	879.3	873.4
165°	884.5	880.7	882.6	887.2	882.6
167.5°	891.7	887.8	889.7	894.4	888.5
170°	897.6	893.7	895.0	899.6	893.7
172.5°	901.5	897.6	898.9	903.5	897.6
175°	904.7	900.2	901.5	906.1	899.6
177.5°	906.1	901.5	902.2	906.8	900.9
180°	902.9	902.9	902.9	902.9	902.9

TEST NUMBER: P921735

CATALOG NUMBER: DFN2DIP-HX3F0-080D030US940-FLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.16	14.27	13.90	15.03	15.93	12.73	13.85	13.47	14.60	15.51
	3H	14.83	15.83	15.58	16.60	17.53	14.37	15.36	15.11	16.13	17.06
	4H	15.43	16.37	16.19	17.14	18.09	14.96	15.90	15.72	16.68	17.62
	6H	15.83	16.70	16.61	17.49	18.45	15.36	16.23	16.14	17.02	17.98
	8H	15.94	16.77	16.73	17.58	18.54	15.47	16.30	16.26	17.11	18.07
	12H	16.00	16.79	16.79	17.58	18.57	15.52	16.31	16.32	17.11	18.10
4H	2H	13.65	14.59	14.42	15.37	16.32	13.31	14.25	14.08	15.03	15.97
	3H	15.53	16.32	16.31	17.13	18.09	15.14	15.93	15.92	16.74	17.70
	4H	16.25	16.97	17.05	17.77	18.77	15.85	16.56	16.64	17.37	18.37
	6H	16.77	17.39	17.58	18.23	19.22	16.37	16.99	17.18	17.82	18.82
	8H	16.92	17.50	17.74	18.33	19.34	16.52	17.10	17.33	17.92	18.94
	12H	17.00	17.53	17.84	18.38	19.39	16.59	17.11	17.43	17.96	18.98
8H	4H	16.46	17.04	17.28	17.87	18.88	16.11	16.68	16.92	17.51	18.53
	6H	17.10	17.58	17.94	18.45	19.46	16.74	17.22	17.58	18.09	19.10
	8H	17.31	17.74	18.17	18.61	19.64	16.95	17.38	17.81	18.24	19.27
	12H	17.45	17.83	18.31	18.69	19.77	17.07	17.45	17.93	18.31	19.39
12H	4H	16.46	16.98	17.30	17.83	18.85	16.11	16.63	16.95	17.48	18.50
	6H	17.13	17.55	17.98	18.42	19.45	16.78	17.21	17.63	18.07	19.10
	8H	17.37	17.75	18.23	18.61	19.69	17.02	17.40	17.88	18.26	19.34