

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P927554

Luminaire Tested: DFN2DIP-HX4F0-040D120US840-RLLONL

Issue Date: 12/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P927554
REPORT IS A COMBINATION OF REPORTS P900964 AND P896187
Test Lab: INNOVATION CENTER
Issue Date: 12/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX4F0-040D120US840-RLLONL
Description: 4 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 15429.8 lumens
Efficiency: N/A
Efficacy: 119.4 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 3.54' x L: 4.09' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 129.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9977
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	101	101	101	101	89	89	89	89	68	68	68	49	49	49	31	31	31
1	92	88	84	81	81	78	75	72	60	58	56	43	42	41	27	27	26
2	84	77	71	66	74	68	64	60	52	49	47	38	36	34	24	23	22
3	76	68	61	55	68	60	55	50	46	43	39	34	31	29	22	20	19
4	70	60	52	47	62	53	47	42	41	37	34	30	27	25	20	18	17
5	64	53	46	40	57	48	41	36	37	32	29	27	24	22	18	16	15
6	59	48	40	35	52	43	36	31	33	29	25	24	21	19	16	14	13
7	54	43	35	30	48	38	32	27	30	25	22	22	19	17	15	13	12
8	50	39	32	27	45	35	29	24	27	23	20	20	17	15	14	12	10
9	47	35	28	23	42	32	26	21	25	20	17	19	16	13	12	11	9
10	44	32	25	21	39	29	23	19	23	19	16	17	14	12	12	10	9

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1241	1241	1241
5°	1243	1222	1229
10°	1231	1198	1190
15°	1214	1158	1128
20°	1192	1104	1052
25°	1169	1043	979
30°	1138	980	886
35°	1108	913	804
40°	1078	843	711
45°	1042	766	626
50°	1005	688	543
55°	967	604	463
60°	922	517	381
65°	871	428	343
70°	810	346	311
75°	732	305	283
80°	619	256	245
85°	433	172	185

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 90°

Luminance: 2101 cd/sqm

TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.5	1.0
10°-20°	429.5	2.8
20°-30°	603.0	3.9
30°-40°	657.3	4.3
40°-50°	604.2	3.9
50°-60°	474.5	3.1
60°-70°	308.9	2.0
70°-80°	159.0	1.0
80°-90°	47.8	0.3
90°-100°	134.8	0.9
100°-110°	502.7	3.3
110°-120°	1333.2	8.6
120°-130°	2211.3	14.3
130°-140°	2348.9	15.2
140°-150°	2183.0	14.1
150°-160°	1755.1	11.4
160°-170°	1130.9	7.3
170°-180°	389.2	2.5
0°-30°	1189.0	7.7
0°-40°	1846.3	12.0
0°-60°	2924.9	19.0
0°-90°	3440.5	22.3
90°-120°	1970.8	12.8
90°-150°	8714.0	56.5
90°-180°	11989.0	77.7
0°-180°	15429.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1669	1669	1669	1669	1669	
5°	1669	1662	1642	1656	1651	158
15°	1588	1571	1520	1491	1476	447
25°	1441	1393	1293	1231	1208	663
35°	1242	1165	1032	937	903	777
45°	1015	914	755	648	612	784
55°	772	654	491	400	372	690
65°	521	399	263	212	207	517
75°	278	172	121	110	109	294
85°	65	33	29	29	29	75
90°	3	35	59	74	80	14
95°	192	94	115	130	127	228
105°	900	988	181	213	225	961
115°	1701	1752	1826	456	243	1675
125°	2406	2444	2501	2521	2530	2146
135°	2977	3024	3051	3081	3075	2300
145°	3454	3450	3501	3521	3506	2160
155°	3802	3776	3812	3829	3806	1752
165°	4007	3989	3998	4019	3998	1132
175°	4098	4078	4084	4104	4075	390
180°	4090	4090	4090	4090	4090	

TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1669.4	1669.4	1669.4	1669.4	1669.4
2.5°	1677.0	1669.4	1652.7	1668.0	1664.9
5°	1669.4	1661.8	1642.1	1655.8	1651.3
7.5°	1655.8	1646.8	1625.7	1631.5	1624.1
10°	1637.7	1627.1	1596.9	1592.3	1583.4
12.5°	1615.1	1601.4	1560.5	1551.6	1534.9
15°	1587.8	1571.1	1519.8	1491.2	1476.1
17.5°	1556.1	1531.9	1468.4	1435.2	1411.0
20°	1519.8	1489.6	1414.0	1376.4	1343.0
22.5°	1480.6	1445.8	1358.1	1306.8	1284.3
25°	1441.3	1392.9	1293.1	1231.4	1208.5
27.5°	1394.5	1343.0	1232.8	1161.8	1126.9
30°	1344.6	1287.1	1166.2	1089.3	1048.5
32.5°	1296.3	1226.7	1102.9	1012.2	974.4
35°	1242.0	1164.8	1031.9	936.7	903.4
37.5°	1189.0	1105.8	965.4	861.1	823.4
40°	1133.1	1042.5	895.9	788.7	749.4
42.5°	1075.6	979.0	826.4	714.5	676.9
45°	1015.3	914.0	755.4	648.1	611.8
47.5°	957.9	850.7	687.5	580.1	546.9
50°	894.4	787.1	620.9	516.6	485.0
52.5°	832.4	719.1	557.5	457.7	429.1
55°	772.0	654.1	491.0	400.4	371.7
57.5°	710.1	589.2	432.1	347.5	323.3
60°	646.6	525.7	370.1	293.1	269.0
62.5°	584.8	463.9	317.2	244.8	232.8
65°	521.3	398.8	262.9	211.6	206.9
67.5°	460.9	338.4	211.6	185.8	181.3
70°	397.4	279.5	175.2	160.2	154.0
72.5°	337.0	225.1	146.5	134.5	131.5
75°	277.9	172.2	120.9	110.3	108.9
77.5°	219.1	122.3	95.2	89.2	86.0
80°	164.6	87.7	72.4	66.5	66.5
82.5°	114.8	59.0	49.9	46.8	46.8
85°	64.9	33.2	28.7	28.7	28.7
87.5°	24.2	12.0	12.0	10.6	10.6
90°	2.8	35.4	59.1	74.1	79.8
92.5°	74.1	62.2	71.0	76.9	79.8
95°	192.2	94.5	115.2	130.4	127.2
97.5°	346.2	103.7	150.8	159.9	162.7
100°	523.9	118.4	168.6	192.2	198.2
102.5°	719.0	713.3	174.6	207.0	216.1
105°	899.5	988.5	180.7	213.0	224.9
107.5°	1109.7	1183.5	186.6	218.9	230.8
110°	1311.0	1372.9	517.9	222.1	233.7

TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	1500.5	1553.5	1503.3	227.7	236.8
115°	1701.4	1751.7	1825.8	455.7	242.9
117.5°	1876.1	1935.2	1985.8	1562.3	787.1
120°	2071.5	2115.7	2169.2	2204.7	1805.1
122.5°	2237.0	2284.5	2343.8	2361.4	2364.5
125°	2405.6	2444.3	2500.6	2521.3	2530.1
127.5°	2559.5	2601.0	2645.7	2675.2	2678.0
130°	2704.6	2752.1	2784.4	2817.1	2814.3
132.5°	2852.6	2891.3	2923.6	2950.3	2947.5
135°	2977.0	3024.5	3050.8	3080.7	3074.7
137.5°	3107.1	3142.5	3172.4	3201.9	3193.1
140°	3234.3	3258.1	3290.4	3317.2	3302.4
142.5°	3341.0	3361.8	3400.1	3423.6	3408.9
145°	3453.5	3450.4	3500.6	3521.4	3506.5
147.5°	3550.9	3542.1	3592.4	3607.1	3595.5
150°	3645.7	3625.0	3672.4	3690.0	3675.3
152.5°	3725.5	3701.9	3746.3	3764.1	3743.4
155°	3802.4	3776.0	3811.6	3829.2	3805.6
157.5°	3864.6	3841.1	3867.8	3888.5	3864.6
160°	3918.0	3900.2	3918.0	3935.6	3914.9
162.5°	3965.2	3947.6	3962.4	3983.1	3956.4
165°	4006.6	3989.0	3997.8	4018.6	3997.8
167.5°	4039.3	4021.3	4030.5	4051.2	4024.6
170°	4066.0	4048.1	4054.0	4074.7	4048.1
172.5°	4083.5	4066.0	4072.0	4092.7	4066.0
175°	4098.3	4077.6	4083.5	4104.3	4074.7
177.5°	4104.3	4083.5	4086.8	4107.5	4080.8
180°	4089.6	4089.6	4089.6	4089.6	4089.6

TEST NUMBER: P927554

CATALOG NUMBER: DFN2DIP-HX4F0-040D120US840-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	4.47	5.12	5.64	6.27	7.89	0.45	1.09	1.61	2.24	3.86
	3H	6.14	6.72	7.31	7.87	9.51	1.62	2.20	2.80	3.36	4.99
	4H	6.74	7.29	7.92	8.44	10.08	2.07	2.61	3.25	3.77	5.41
	6H	7.15	7.66	8.34	8.82	10.47	2.38	2.88	3.57	4.04	5.69
	8H	7.27	7.75	8.46	8.93	10.57	2.47	2.94	3.66	4.12	5.76
	12H	7.33	7.78	8.52	8.95	10.62	2.50	2.96	3.70	4.13	5.79
4H	2H	4.47	5.02	5.66	6.18	7.81	1.02	1.57	2.21	2.73	4.36
	3H	6.28	6.74	7.48	7.92	9.57	2.35	2.81	3.55	3.99	5.65
	4H	6.97	7.39	8.16	8.56	10.23	2.90	3.32	4.09	4.49	6.16
	6H	7.47	7.83	8.67	9.03	10.69	3.31	3.67	4.51	4.86	6.52
	8H	7.65	7.98	8.84	9.17	10.84	3.43	3.77	4.63	4.95	6.63
	12H	7.73	8.04	8.95	9.23	10.91	3.49	3.80	4.71	4.99	6.67
8H	4H	6.92	7.26	8.12	8.44	10.12	3.16	3.50	4.36	4.68	6.36
	6H	7.48	7.76	8.70	8.99	10.66	3.68	3.95	4.89	5.18	6.85
	8H	7.70	7.94	8.92	9.14	10.84	3.87	4.11	5.09	5.31	7.01
	12H	7.83	8.04	9.06	9.24	10.97	3.98	4.19	5.21	5.39	7.12
12H	4H	6.87	7.17	8.08	8.37	10.05	3.16	3.47	4.37	4.66	6.34
	6H	7.46	7.70	8.68	8.90	10.59	3.73	3.97	4.95	5.17	6.86
	8H	7.67	7.88	8.90	9.08	10.81	3.93	4.14	5.16	5.34	7.07