

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P927598

Luminaire Tested: DFN2DIP-HX4F0-060D050US840-RLLONL

Issue Date: 12/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P927598
REPORT IS A COMBINATION OF REPORTS P900842 AND P896187
Test Lab: INNOVATION CENTER
Issue Date: 12/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX4F0-060D050US840-RLLONL
Description: 4 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 10148.5 lumens
Efficiency: N/A
Efficacy: 110.6 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 3.54' x L: 4.09' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 91.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.099
Total Harmonic Distortion (THDi): 0.979
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	107	107	107	107	99	99	99	99	84	84	84	70	70	70	57	57	57
1	98	94	91	87	91	87	84	81	74	72	70	62	61	59	51	50	49
2	90	83	77	72	83	77	72	67	66	62	59	55	52	50	45	44	42
3	82	73	66	61	76	68	62	57	58	54	50	49	46	43	41	38	36
4	76	65	58	52	70	61	54	49	52	47	43	44	40	37	37	34	32
5	70	58	50	45	64	54	47	42	47	41	37	40	36	33	33	30	28
6	64	53	45	39	59	49	42	37	42	37	33	36	32	29	30	27	25
7	60	48	40	34	55	45	38	33	39	33	29	33	29	26	28	25	22
8	55	43	36	31	51	41	34	29	35	30	26	30	26	23	26	23	20
9	52	40	32	27	48	37	31	26	32	27	23	28	24	21	24	21	18
10	48	36	29	25	45	34	28	24	30	25	21	26	22	19	22	19	17

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1862	1862	1862
5°	1865	1833	1844
10°	1847	1797	1784
15°	1821	1738	1692
20°	1788	1656	1578
25°	1754	1564	1468
30°	1708	1470	1329
35°	1663	1369	1206
40°	1617	1265	1066
45°	1563	1149	939
50°	1508	1032	814
55°	1450	906	695
60°	1384	776	572
65°	1307	642	515
70°	1214	518	466
75°	1098	457	424
80°	928	384	368
85°	649	257	277

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1563 cd/sqm

TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	234.7	2.3
10°-20°	644.3	6.3
20°-30°	904.5	8.9
30°-40°	986.0	9.7
40°-50°	906.2	8.9
50°-60°	711.7	7.0
60°-70°	463.3	4.6
70°-80°	238.5	2.3
80°-90°	63.9	0.6
90°-100°	56.2	0.6
100°-110°	209.5	2.1
110°-120°	555.5	5.5
120°-130°	921.4	9.1
130°-140°	978.7	9.6
140°-150°	909.6	9.0
150°-160°	731.3	7.2
160°-170°	471.2	4.6
170°-180°	162.2	1.6
0°-30°	1783.5	17.6
0°-40°	2769.5	27.3
0°-60°	4387.4	43.2
0°-90°	5153.0	50.8
90°-120°	821.2	8.1
90°-150°	3630.8	35.8
90°-180°	4996.0	49.2
0°-180°	10148.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2504	2504	2504	2504	2504	
5°	2504	2493	2463	2484	2477	237
15°	2382	2357	2280	2237	2214	671
25°	2162	2089	1940	1847	1813	994
35°	1863	1747	1548	1405	1355	1166
45°	1523	1371	1133	972	918	1176
55°	1158	981	736	601	558	1035
65°	782	598	394	317	310	775
75°	417	258	181	165	163	441
85°	97	50	43	43	43	112
90°	1	15	25	31	33	10
95°	80	39	48	54	53	95
105°	375	412	75	89	94	401
115°	709	730	761	190	101	698
125°	1002	1018	1042	1050	1054	894
135°	1240	1260	1271	1284	1281	958
145°	1439	1438	1459	1467	1461	900
155°	1584	1573	1588	1596	1586	730
165°	1669	1662	1666	1674	1666	472
175°	1708	1699	1702	1710	1698	163
180°	1704	1704	1704	1704	1704	

TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2504.1	2504.1	2504.1	2504.1	2504.1
2.5°	2515.4	2504.1	2479.1	2501.9	2497.3
5°	2504.1	2492.8	2463.2	2483.7	2476.9
7.5°	2483.7	2470.2	2438.5	2447.4	2436.0
10°	2456.4	2440.6	2395.4	2388.5	2374.9
12.5°	2422.6	2402.1	2340.8	2327.4	2302.3
15°	2381.7	2356.7	2279.7	2236.7	2214.1
17.5°	2334.2	2297.8	2202.6	2152.8	2116.5
20°	2279.7	2234.3	2121.1	2064.5	2014.6
22.5°	2220.9	2168.6	2037.2	1960.2	1926.3
25°	2162.0	2089.4	1939.8	1847.0	1812.9
27.5°	2091.8	2014.6	1849.1	1742.6	1690.5
30°	2017.0	1930.6	1749.4	1634.0	1572.7
32.5°	1944.4	1840.1	1654.5	1518.3	1461.6
35°	1862.9	1747.3	1547.9	1405.0	1355.1
37.5°	1783.5	1658.7	1448.2	1291.6	1235.1
40°	1699.6	1563.8	1343.7	1182.9	1124.0
42.5°	1613.6	1468.6	1239.6	1071.8	1015.4
45°	1522.9	1370.9	1133.2	972.0	917.7
47.5°	1436.8	1276.0	1031.2	870.1	820.4
50°	1341.6	1180.8	931.4	774.9	727.6
52.5°	1248.5	1078.6	836.2	686.7	643.6
55°	1157.9	981.2	736.4	600.6	557.5
57.5°	1065.1	883.8	648.2	521.3	484.9
60°	969.9	788.7	555.2	439.8	403.4
62.5°	877.1	695.9	475.8	367.2	349.1
65°	781.9	598.2	394.3	317.4	310.4
67.5°	691.2	507.5	317.4	278.7	271.9
70°	596.0	419.3	262.7	240.2	231.0
72.5°	505.4	337.6	219.7	201.8	197.1
75°	416.9	258.2	181.3	165.4	163.3
77.5°	328.7	183.5	142.8	133.7	129.2
80°	246.9	131.5	108.7	99.8	99.8
82.5°	172.2	88.5	74.7	70.2	70.2
85°	97.3	49.8	43.0	43.0	43.0
87.5°	36.4	18.1	18.1	15.9	15.9
90°	1.2	14.7	24.6	30.9	33.2
92.5°	30.9	26.0	29.6	32.1	33.2
95°	80.1	39.4	48.1	54.3	53.0
97.5°	144.2	43.2	62.8	66.6	67.8
100°	218.3	49.4	70.3	80.1	82.6
102.5°	299.6	297.2	72.8	86.2	90.1
105°	374.8	411.9	75.2	88.8	93.7
107.5°	462.4	493.1	77.8	91.2	96.2
110°	546.3	572.1	215.8	92.5	97.3

TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	625.2	647.3	626.4	94.9	98.7
115°	709.0	729.9	760.8	189.9	101.2
117.5°	781.7	806.3	827.4	650.9	328.0
120°	863.1	881.6	903.8	918.6	752.1
122.5°	932.0	951.8	976.6	983.9	985.3
125°	1002.3	1018.5	1041.9	1050.5	1054.2
127.5°	1066.4	1083.7	1102.4	1114.6	1115.8
130°	1126.9	1146.7	1160.2	1173.8	1172.7
132.5°	1188.6	1204.7	1218.1	1229.3	1228.1
135°	1240.4	1260.2	1271.1	1283.7	1281.1
137.5°	1294.6	1309.4	1321.8	1334.1	1330.5
140°	1347.6	1357.6	1371.0	1382.1	1376.1
142.5°	1392.1	1400.8	1416.7	1426.5	1420.4
145°	1439.0	1437.7	1458.6	1467.2	1461.1
147.5°	1479.6	1475.8	1496.8	1503.0	1498.1
150°	1519.0	1510.5	1530.1	1537.5	1531.4
152.5°	1552.3	1542.5	1560.9	1568.4	1559.7
155°	1584.4	1573.4	1588.1	1595.5	1585.7
157.5°	1610.2	1600.4	1611.5	1620.2	1610.2
160°	1632.5	1625.1	1632.5	1639.8	1631.2
162.5°	1652.1	1644.9	1650.9	1659.6	1648.5
165°	1669.4	1662.1	1665.8	1674.3	1665.8
167.5°	1683.0	1675.6	1679.4	1688.0	1676.9
170°	1694.1	1686.7	1689.2	1697.8	1686.7
172.5°	1701.5	1694.1	1696.7	1705.2	1694.1
175°	1707.7	1699.0	1701.5	1710.1	1697.8
177.5°	1710.1	1701.5	1702.8	1711.4	1700.3
180°	1703.9	1703.9	1703.9	1703.9	1703.9

TEST NUMBER: P927598

CATALOG NUMBER: DFN2DIP-HX4F0-060D050US840-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	9.38	10.22	10.34	11.18	12.45	5.35	6.19	6.31	7.16	8.42
	3H	11.06	11.81	12.03	12.78	14.07	6.54	7.29	7.51	8.27	9.56
	4H	11.67	12.38	12.65	13.36	14.65	7.00	7.70	7.98	8.68	9.98
	6H	12.09	12.74	13.08	13.73	15.03	7.32	7.97	8.31	8.96	10.26
	8H	12.22	12.84	13.22	13.84	15.14	7.41	8.03	8.41	9.03	10.34
	12H	12.28	12.87	13.28	13.87	15.19	7.46	8.04	8.46	9.04	10.37
4H	2H	9.40	10.11	10.39	11.09	12.38	5.95	6.66	6.94	7.64	8.93
	3H	11.23	11.82	12.23	12.83	14.14	7.30	7.89	8.30	8.90	10.21
	4H	11.92	12.46	12.93	13.46	14.80	7.85	8.39	8.86	9.39	10.72
	6H	12.44	12.90	13.46	13.93	15.26	8.27	8.74	9.29	9.76	11.09
	8H	12.62	13.05	13.63	14.07	15.41	8.40	8.84	9.42	9.85	11.20
	12H	12.71	13.10	13.75	14.14	15.48	8.47	8.86	9.51	9.89	11.24
8H	4H	11.89	12.32	12.91	13.34	14.69	8.13	8.56	9.15	9.58	10.93
	6H	12.46	12.82	13.50	13.88	15.22	8.66	9.01	9.70	10.07	11.41
	8H	12.68	12.99	13.73	14.04	15.40	8.85	9.16	9.90	10.21	11.57
	12H	12.82	13.09	13.87	14.13	15.54	8.97	9.24	10.02	10.29	11.69
12H	4H	11.84	12.23	12.88	13.27	14.62	8.14	8.53	9.17	9.56	10.91
	6H	12.44	12.75	13.49	13.80	15.16	8.70	9.02	9.75	10.07	11.42
	8H	12.66	12.93	13.71	13.97	15.38	8.92	9.19	9.97	10.23	11.64