

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P927702

Luminaire Tested: DFN2DIP-HX4F0-090D040US840-RLLONL

Issue Date: 12/12/2024

Test Information

Test Method: LM-79-2019
Report Number: P927702
REPORT IS A COMBINATION OF REPORTS P900830 AND P896187
Test Lab: INNOVATION CENTER
Issue Date: 12/12/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX4F0-090D040US840-RLLONL
Description: 4 foot, Hexagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 11723.8 lumens
Efficiency: N/A
Efficacy: 98.7 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 3.54' x L: 4.09' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 118.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9821
Total Harmonic Distortion (THDi): 0.08
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92	81	81	81	71	71	71
1	102	98	94	91	96	92	89	86	82	79	77	72	71	69	64	62	61
2	93	86	80	75	88	81	76	72	73	68	65	64	61	59	57	54	52
3	86	76	69	63	80	72	66	61	65	60	55	57	54	50	51	48	45
4	79	68	60	54	74	65	58	52	58	52	48	52	47	44	46	42	40
5	73	61	53	47	68	58	51	45	52	46	42	47	42	38	42	38	35
6	67	55	47	41	63	52	45	40	47	41	37	43	38	34	38	34	31
7	62	50	42	37	59	48	40	35	43	37	33	39	34	30	35	31	28
8	58	46	38	33	55	44	37	32	40	34	29	36	31	27	32	28	25
9	54	42	35	29	51	40	33	29	37	31	27	33	28	25	30	26	23
10	51	39	32	27	48	37	30	26	34	28	24	31	26	23	28	24	21

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2793	2793	2793
5°	2798	2749	2766
10°	2770	2695	2676
15°	2732	2606	2537
20°	2682	2484	2367
25°	2631	2346	2202
30°	2562	2206	1993
35°	2494	2054	1809
40°	2425	1897	1599
45°	2345	1723	1408
50°	2262	1548	1221
55°	2176	1360	1042
60°	2076	1163	858
65°	1961	964	772
70°	1821	777	699
75°	1646	686	636
80°	1393	576	553
85°	973	386	416

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2345 cd/sqm

TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	352.0	3.0
10°-20°	966.4	8.2
20°-30°	1356.8	11.6
30°-40°	1479.0	12.6
40°-50°	1359.4	11.6
50°-60°	1067.6	9.1
60°-70°	694.9	5.9
70°-80°	357.7	3.1
80°-90°	93.7	0.8
90°-100°	44.9	0.4
100°-110°	167.6	1.4
110°-120°	444.4	3.8
120°-130°	737.1	6.3
130°-140°	783.0	6.7
140°-150°	727.7	6.2
150°-160°	585.0	5.0
160°-170°	377.0	3.2
170°-180°	129.8	1.1
0°-30°	2675.2	22.8
0°-40°	4154.2	35.4
0°-60°	6581.1	56.1
0°-90°	7727.4	65.9
90°-120°	656.9	5.6
90°-150°	2904.6	24.8
90°-180°	3996.0	34.1
0°-180°	11723.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3756	3756	3756	3756	3756	
5°	3756	3739	3695	3726	3715	356
15°	3573	3535	3420	3355	3321	1007
25°	3243	3134	2910	2770	2719	1491
35°	2794	2621	2322	2108	2033	1749
45°	2284	2056	1700	1458	1377	1764
55°	1737	1472	1105	901	836	1552
65°	1173	897	591	476	466	1163
75°	625	387	272	248	245	661
85°	146	75	64	64	64	168
90°	1	12	20	25	27	11
95°	64	32	38	43	42	76
105°	300	330	60	71	75	320
115°	567	584	609	152	81	558
125°	802	815	834	840	843	715
135°	992	1008	1017	1027	1025	767
145°	1151	1150	1167	1174	1169	720
155°	1268	1259	1270	1276	1268	584
165°	1336	1330	1333	1340	1333	377
175°	1366	1359	1361	1368	1358	130
180°	1363	1363	1363	1363	1363	

TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3756.2	3756.2	3756.2	3756.2	3756.2
2.5°	3773.1	3756.2	3718.6	3752.9	3746.1
5°	3756.2	3739.2	3694.9	3725.5	3715.4
7.5°	3725.5	3705.3	3657.7	3671.0	3654.1
10°	3684.8	3660.9	3593.2	3582.7	3562.5
12.5°	3633.9	3603.3	3511.3	3491.1	3453.5
15°	3572.6	3535.1	3419.7	3355.1	3321.2
17.5°	3501.2	3446.8	3303.9	3229.2	3174.8
20°	3419.7	3351.5	3181.6	3096.9	3021.8
22.5°	3331.3	3253.1	3055.8	2940.3	2889.5
25°	3243.0	3134.0	2909.7	2770.5	2719.3
27.5°	3137.7	3021.8	2773.7	2614.0	2535.7
30°	3025.5	2896.0	2624.1	2451.0	2359.0
32.5°	2916.5	2760.0	2481.6	2277.5	2192.4
35°	2794.3	2620.8	2321.8	2107.7	2032.6
37.5°	2675.3	2488.1	2172.2	1937.4	1852.7
40°	2549.4	2345.7	2015.7	1774.4	1686.1
42.5°	2420.3	2202.9	1859.4	1607.8	1523.0
45°	2284.4	2056.5	1699.7	1458.1	1376.6
47.5°	2155.2	1914.0	1546.8	1305.2	1230.5
50°	2012.4	1771.1	1397.2	1162.4	1091.3
52.5°	1872.9	1617.9	1254.4	1030.0	965.5
55°	1736.9	1471.8	1104.6	900.9	836.3
57.5°	1597.7	1325.8	972.3	781.9	727.5
60°	1454.8	1182.9	832.8	659.6	605.2
62.5°	1315.7	1043.7	713.7	550.7	523.7
65°	1172.8	897.3	591.4	476.0	465.6
67.5°	1036.9	761.3	476.0	418.0	407.9
70°	894.1	629.0	394.2	360.3	346.6
72.5°	758.1	506.3	329.6	302.5	295.8
75°	625.4	387.4	271.9	248.1	244.9
77.5°	493.0	275.2	214.2	200.5	193.7
80°	370.4	197.3	163.0	149.7	149.7
82.5°	258.2	132.7	112.2	105.3	105.3
85°	146.0	74.6	64.5	64.5	64.5
87.5°	54.4	27.1	27.1	23.8	23.8
90°	0.9	11.8	19.7	24.7	26.6
92.5°	24.7	20.7	23.6	25.6	26.6
95°	64.0	31.5	38.4	43.4	42.4
97.5°	115.4	34.5	50.3	53.3	54.2
100°	174.6	39.5	56.2	64.0	66.0
102.5°	239.6	237.8	58.2	69.0	72.0
105°	299.8	329.5	60.2	71.0	74.9
107.5°	369.9	394.5	62.2	73.0	76.9
110°	437.0	457.6	172.7	74.0	77.9

TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	500.2	517.8	501.1	75.9	79.0
115°	567.1	583.9	608.6	151.9	81.0
117.5°	625.4	645.1	661.9	520.8	262.3
120°	690.5	705.2	723.0	734.9	601.7
122.5°	745.6	761.5	781.3	787.1	788.1
125°	801.9	814.8	833.5	840.5	843.4
127.5°	853.2	867.0	881.9	891.8	892.7
130°	901.5	917.4	928.1	939.0	938.1
132.5°	950.8	963.8	974.6	983.4	982.5
135°	992.3	1008.2	1017.0	1026.9	1024.9
137.5°	1035.7	1047.5	1057.5	1067.3	1064.3
140°	1078.1	1086.0	1096.8	1105.7	1100.8
142.5°	1113.7	1120.6	1133.4	1141.2	1136.3
145°	1151.2	1150.2	1166.8	1173.8	1168.8
147.5°	1183.6	1180.7	1197.4	1202.4	1198.5
150°	1215.2	1208.3	1224.2	1230.0	1225.1
152.5°	1241.9	1234.0	1248.7	1254.7	1247.8
155°	1267.5	1258.7	1270.5	1276.4	1268.5
157.5°	1288.2	1280.3	1289.3	1296.2	1288.2
160°	1306.0	1300.0	1306.0	1311.8	1305.0
162.5°	1321.7	1315.9	1320.8	1327.7	1318.8
165°	1335.6	1329.7	1332.6	1339.5	1332.6
167.5°	1346.5	1340.4	1343.5	1350.4	1341.5
170°	1355.4	1349.4	1351.3	1358.3	1349.4
172.5°	1361.2	1355.4	1357.4	1364.2	1355.4
175°	1366.1	1359.2	1361.2	1368.1	1358.3
177.5°	1368.1	1361.2	1362.2	1369.2	1360.3
180°	1363.2	1363.2	1363.2	1363.2	1363.2

TEST NUMBER: P927702

CATALOG NUMBER: DFN2DIP-HX4F0-090D040US840-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.09	13.07	12.90	13.90	14.93	8.06	9.04	8.87	9.87	10.90
	3H	13.78	14.65	14.60	15.49	16.55	9.26	10.14	10.09	10.98	12.04
	4H	14.39	15.22	15.24	16.07	17.13	9.72	10.55	10.57	11.40	12.46
	6H	14.82	15.58	15.68	16.44	17.52	10.05	10.81	10.91	11.67	12.75
	8H	14.95	15.68	15.82	16.55	17.63	10.15	10.87	11.01	11.74	12.82
	12H	15.02	15.71	15.89	16.58	17.68	10.20	10.88	11.07	11.75	12.86
4H	2H	12.12	12.95	12.97	13.80	14.87	8.67	9.50	9.52	10.35	11.42
	3H	13.97	14.65	14.83	15.54	16.62	10.04	10.73	10.90	11.61	12.69
	4H	14.67	15.29	15.54	16.17	17.28	10.59	11.22	11.47	12.10	13.21
	6H	15.19	15.73	16.08	16.63	17.74	11.02	11.56	11.91	12.46	13.58
	8H	15.37	15.87	16.26	16.77	17.89	11.16	11.66	12.05	12.56	13.68
	12H	15.47	15.92	16.38	16.84	17.97	11.23	11.68	12.14	12.60	13.73
8H	4H	14.65	15.15	15.54	16.05	17.17	10.89	11.39	11.78	12.29	13.41
	6H	15.22	15.63	16.14	16.57	17.70	11.41	11.83	12.33	12.77	13.89
	8H	15.44	15.80	16.36	16.74	17.88	11.61	11.97	12.53	12.91	14.05
	12H	15.58	15.91	16.51	16.83	18.02	11.73	12.06	12.66	12.98	14.17
12H	4H	14.60	15.06	15.51	15.97	17.10	10.90	11.35	11.81	12.27	13.40
	6H	15.19	15.56	16.12	16.49	17.64	11.46	11.83	12.39	12.76	13.90
	8H	15.42	15.75	16.35	16.67	17.86	11.68	12.00	12.61	12.93	14.12