

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P913694

Luminaire Tested: DFN2DIP-HX4F0-090D070US927-FLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P913694
REPORT IS A COMBINATION OF REPORTS P899363 AND P896188
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-HX4F0-090D070US927-FLLFLL
Description: 4 foot, Hexagon Define Geo, with Direct Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 11965.9 lumens
Efficiency: N/A
Efficacy: 93.3 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.54' x L: 4.09' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 128.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9821
Total Harmonic Distortion (THDi): 0.08
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	109	109	109	109		102	102	102	102		88	88	88		76	76	76		64	64	64
1	100	95	91	88		93	89	86	83		78	75	73		67	65	63		57	56	54
2	91	83	77	72		85	78	73	68		68	64	60		59	56	53		50	48	46
3	83	73	66	60		77	69	62	57		60	55	51		52	48	45		44	42	39
4	76	65	57	51		71	61	54	48		53	48	43		46	42	38		40	36	34
5	70	58	50	44		65	54	47	41		48	42	37		42	37	33		36	32	29
6	64	52	44	38		60	49	41	36		43	37	33		38	33	29		33	29	26
7	59	47	39	33		55	44	37	32		39	33	29		34	29	26		30	26	23
8	55	43	35	29		51	40	33	28		36	30	26		31	27	23		27	23	21
9	51	39	31	26		48	37	30	25		33	27	23		29	24	21		25	21	19
10	48	36	29	24		45	34	27	23		30	25	21		27	22	19		23	20	17

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2063	2063	2063
5°	2066	2034	2048
10°	2050	2007	2020
15°	2020	1974	1977
20°	1979	1928	1933
25°	1939	1874	1882
30°	1888	1823	1816
35°	1840	1763	1748
40°	1781	1702	1682
45°	1722	1641	1615
50°	1658	1578	1537
55°	1591	1504	1466
60°	1515	1416	1384
65°	1432	1326	1288
70°	1326	1215	1184
75°	1180	1083	1089
80°	1004	914	906
85°	728	623	602

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1722 cd/sqm

TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	261.1	2.2
10°-20°	734.7	6.1
20°-30°	1079.6	9.0
30°-40°	1253.9	10.5
40°-50°	1252.4	10.5
50°-60°	1092.1	9.1
60°-70°	807.3	6.7
70°-80°	456.7	3.8
80°-90°	125.5	1.0
90°-100°	108.5	0.9
100°-110°	344.8	2.9
110°-120°	590.1	4.9
120°-130°	776.1	6.5
130°-140°	871.1	7.3
140°-150°	854.2	7.1
150°-160°	716.6	6.0
160°-170°	475.2	4.0
170°-180°	166.1	1.4
0°-30°	2075.4	17.3
0°-40°	3329.4	27.8
0°-60°	5673.8	47.4
0°-90°	7063.3	59.0
90°-120°	1043.4	8.7
90°-150°	3544.8	29.6
90°-180°	4903.0	41.0
0°-180°	11965.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2774	2774	2774	2774	2774	
5°	2774	2764	2734	2756	2750	263
15°	2641	2625	2590	2601	2588	744
25°	2390	2369	2324	2329	2324	1100
35°	2062	2036	1993	1977	1963	1288
45°	1678	1659	1619	1590	1579	1295
55°	1270	1254	1222	1190	1176	1135
65°	856	840	814	790	776	847
75°	448	443	429	414	419	478
85°	109	107	104	96	93	122
90°	2	19	52	49	50	12
95°	77	92	95	95	92	86
105°	318	322	326	328	328	336
115°	592	601	598	596	592	586
125°	861	874	870	866	864	770
135°	1114	1130	1134	1132	1128	861
145°	1352	1363	1372	1373	1367	845
155°	1546	1551	1556	1563	1558	712
165°	1682	1681	1681	1691	1684	475
175°	1751	1746	1743	1754	1745	166
180°	1754	1754	1754	1754	1754	

TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2774.1	2774.1	2774.1	2774.1	2774.1
2.5°	2790.3	2777.0	2747.6	2774.1	2769.1
5°	2774.1	2763.7	2734.3	2755.5	2750.4
7.5°	2755.5	2739.7	2710.2	2731.8	2726.4
10°	2726.4	2707.7	2675.7	2696.9	2689.0
12.5°	2686.1	2670.3	2638.4	2651.6	2646.3
15°	2640.9	2625.1	2590.2	2601.0	2587.7
17.5°	2584.8	2569.0	2534.2	2547.5	2534.2
20°	2523.4	2507.6	2470.2	2478.1	2467.6
22.5°	2462.3	2438.3	2403.4	2403.4	2398.0
25°	2390.1	2368.9	2323.6	2328.7	2323.6
27.5°	2310.0	2291.3	2256.8	2248.9	2235.6
30°	2230.2	2208.7	2168.8	2160.8	2150.1
32.5°	2144.8	2128.9	2086.1	2070.0	2059.3
35°	2062.1	2035.5	1992.7	1976.7	1963.3
37.5°	1968.7	1944.6	1901.9	1883.3	1869.9
40°	1872.7	1851.2	1808.5	1784.7	1774.0
42.5°	1779.3	1757.8	1715.4	1688.5	1672.7
45°	1678.0	1659.4	1619.1	1590.0	1579.3
47.5°	1579.3	1560.6	1517.8	1488.4	1472.6
50°	1475.1	1461.8	1424.4	1387.1	1373.8
52.5°	1373.8	1355.1	1320.6	1291.2	1272.5
55°	1269.9	1253.8	1221.8	1189.9	1176.5
57.5°	1165.8	1152.5	1117.7	1085.7	1074.9
60°	1061.6	1051.1	1013.8	984.4	976.4
62.5°	960.3	941.6	915.0	888.4	877.7
65°	856.4	840.3	813.6	789.6	776.3
67.5°	749.7	736.2	712.3	693.7	682.9
70°	650.9	640.2	616.2	597.5	587.0
72.5°	549.6	538.8	525.5	506.9	499.0
75°	448.1	442.9	429.4	413.5	418.9
77.5°	357.4	346.7	341.4	333.4	325.5
80°	266.9	264.0	258.6	250.7	245.4
82.5°	181.4	181.4	178.9	168.1	168.1
85°	109.2	106.7	104.2	95.9	93.4
87.5°	48.1	42.7	37.4	29.5	26.6
90°	1.6	19.0	51.8	48.6	50.2
92.5°	32.8	44.4	46.0	47.6	47.6
95°	77.2	92.0	94.7	94.7	92.0
97.5°	128.5	142.2	148.1	148.1	148.1
100°	187.7	199.9	204.1	204.1	202.5
102.5°	250.1	259.0	264.9	266.5	264.9
105°	318.3	322.5	325.7	328.4	328.4
107.5°	386.0	392.3	392.3	393.4	386.0
110°	451.5	460.0	460.0	460.0	455.7

TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	522.4	531.4	529.8	525.5	522.4
115°	592.2	600.6	598.0	596.4	592.2
117.5°	661.4	673.0	665.7	661.4	657.2
120°	731.2	742.8	731.2	731.2	726.4
122.5°	794.6	809.5	802.1	797.8	794.6
125°	861.3	874.5	870.3	865.5	864.0
127.5°	926.3	942.7	936.9	930.6	926.3
130°	987.1	1006.1	1003.5	1000.4	994.5
132.5°	1055.3	1070.2	1071.2	1063.8	1059.5
135°	1114.0	1130.4	1133.6	1131.9	1127.7
137.5°	1179.6	1192.8	1195.4	1194.4	1188.0
140°	1237.2	1250.5	1257.8	1257.8	1252.0
142.5°	1296.4	1309.6	1313.8	1315.4	1309.6
145°	1352.5	1363.0	1371.5	1373.1	1367.3
147.5°	1402.7	1415.9	1422.3	1424.9	1419.1
150°	1454.5	1463.5	1469.3	1474.1	1469.3
152.5°	1500.5	1509.5	1516.9	1522.7	1516.9
155°	1546.5	1550.7	1555.5	1562.9	1558.1
157.5°	1586.2	1589.4	1592.0	1602.6	1595.1
160°	1621.6	1624.8	1626.3	1635.3	1629.0
162.5°	1654.4	1654.4	1656.0	1666.0	1658.6
165°	1682.4	1680.8	1680.8	1691.4	1683.9
167.5°	1707.8	1703.0	1703.0	1713.6	1706.2
170°	1726.8	1722.6	1721.0	1731.5	1722.6
172.5°	1740.0	1735.7	1734.2	1744.8	1735.7
175°	1750.6	1746.4	1743.2	1753.7	1744.8
177.5°	1756.4	1752.1	1749.0	1758.0	1749.0
180°	1753.7	1753.7	1753.7	1753.7	1753.7

TEST NUMBER: P913694

CATALOG NUMBER: DFN2DIP-HX4F0-090D070US927-FLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	10.58	11.53	11.46	12.43	13.56	10.15	11.10	11.02	11.99	13.13
	3H	12.25	13.10	13.14	14.01	15.17	11.78	12.63	12.66	13.53	14.70
	4H	12.84	13.65	13.74	14.56	15.73	12.37	13.17	13.27	14.08	15.26
	6H	13.25	13.99	14.16	14.91	16.09	12.77	13.51	13.69	14.43	15.62
	8H	13.35	14.06	14.28	15.00	16.18	12.88	13.59	13.80	14.52	15.71
	12H	13.41	14.08	14.33	15.01	16.22	12.92	13.60	13.85	14.53	15.74
4H	2H	11.05	11.86	11.96	12.77	13.94	10.71	11.51	11.62	12.43	13.60
	3H	12.93	13.60	13.85	14.54	15.73	12.54	13.21	13.46	14.15	15.34
	4H	13.65	14.26	14.58	15.20	16.41	13.24	13.86	14.17	14.79	16.01
	6H	14.17	14.70	15.11	15.66	16.87	13.76	14.29	14.70	15.25	16.46
	8H	14.32	14.82	15.27	15.77	17.00	13.91	14.40	14.85	15.36	16.59
	12H	14.40	14.85	15.36	15.82	17.05	13.98	14.42	14.94	15.40	16.63
8H	4H	13.85	14.35	14.80	15.30	16.53	13.49	13.99	14.44	14.94	16.17
	6H	14.49	14.90	15.46	15.90	17.12	14.13	14.53	15.10	15.53	16.76
	8H	14.71	15.07	15.69	16.06	17.30	14.34	14.70	15.32	15.69	16.93
	12H	14.85	15.17	15.83	16.15	17.44	14.46	14.78	15.45	15.76	17.05
12H	4H	13.84	14.29	14.81	15.26	16.49	13.49	13.94	14.46	14.91	16.14
	6H	14.52	14.88	15.50	15.87	17.11	14.17	14.53	15.15	15.52	16.76
	8H	14.77	15.09	15.75	16.07	17.36	14.41	14.73	15.39	15.71	17.00