

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P908368

Luminaire Tested: DFN2DIP-PN2F0-050D030US840-FLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P908368
REPORT IS A COMBINATION OF REPORTS P899477 AND P896349
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-PN2F0-050D030US840-FLLFLL
Description: 2 foot, Pentagon Define Geo, with Direct Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7680.0 lumens
Efficiency: N/A
Efficacy: 109.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 2.17' x L: 2.29' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 69.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9821
Total Harmonic Distortion (THDi): 0.08
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92		80	80	80		70
1	101	97	93	89	95	91	88	84	81	78	75		71	69	67		62
2	92	85	78	73	86	80	74	69	71	66	63		62	59	56		55
3	84	74	67	61	79	70	63	58	62	57	53		55	51	47		48
4	77	66	58	52	72	62	55	49	55	50	45		49	44	41		43
5	71	59	50	44	66	56	48	42	50	44	39		44	39	35		39
6	65	53	45	39	61	50	43	37	45	39	34		40	35	31		35
7	60	48	40	34	57	45	38	33	41	35	30		36	31	28		32
8	56	44	36	30	53	41	34	29	37	31	27		33	28	25		30
9	52	40	32	27	49	38	31	26	34	28	24		31	26	22		27
10	49	37	29	24	46	35	28	23	32	26	22		28	24	20		25

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4255	4255	4255
5°	4255	4187	4218
10°	4214	4122	4155
15°	4145	4044	4059
20°	4055	3941	3962
25°	3964	3820	3850
30°	3853	3706	3710
35°	3747	3573	3562
40°	3617	3438	3420
45°	3488	3303	3275
50°	3346	3160	3108
55°	3196	2996	2952
60°	3027	2802	2775
65°	2842	2599	2565
70°	2606	2353	2338
75°	2283	2058	2119
80°	1889	1680	1719
85°	1282	1062	1077

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3488 cd/sqm

TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	184.9	2.4
10°-20°	520.3	6.8
20°-30°	764.6	10.0
30°-40°	888.1	11.6
40°-50°	887.0	11.5
50°-60°	773.4	10.1
60°-70°	571.7	7.4
70°-80°	323.5	4.2
80°-90°	88.1	1.1
90°-100°	59.3	0.8
100°-110°	188.4	2.5
110°-120°	322.4	4.2
120°-130°	424.0	5.5
130°-140°	475.9	6.2
140°-150°	466.7	6.1
150°-160°	391.5	5.1
160°-170°	259.6	3.4
170°-180°	90.7	1.2
0°-30°	1469.8	19.1
0°-40°	2357.9	30.7
0°-60°	4018.3	52.3
0°-90°	5001.6	65.1
90°-120°	570.1	7.4
90°-150°	1936.6	25.2
90°-180°	2678.0	34.9
0°-180°	7680.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1965	1965	1965	1965	1965	
5°	1965	1957	1936	1952	1948	187
15°	1870	1859	1834	1842	1833	527
25°	1693	1678	1646	1649	1646	779
35°	1460	1442	1411	1400	1390	912
45°	1188	1175	1147	1126	1118	917
55°	899	888	865	843	833	804
65°	606	595	576	559	550	600
75°	317	314	304	293	297	339
85°	77	76	74	68	66	86
90°	1	10	28	27	28	7
95°	42	50	52	52	50	47
105°	174	176	178	179	179	184
115°	324	328	327	326	324	320
125°	471	478	475	473	472	420
135°	609	618	619	618	616	470
145°	739	745	749	750	747	462
155°	845	847	850	854	851	389
165°	919	918	918	924	920	259
175°	956	954	952	958	953	91
180°	958	958	958	958	958	

TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1964.7	1964.7	1964.7	1964.7	1964.7
2.5°	1976.1	1966.7	1945.9	1964.7	1961.2
5°	1964.7	1957.3	1936.4	1951.5	1947.9
7.5°	1951.5	1940.3	1919.5	1934.7	1930.9
10°	1930.9	1917.6	1895.0	1910.0	1904.4
12.5°	1902.4	1891.2	1868.6	1877.9	1874.1
15°	1870.3	1859.1	1834.4	1842.1	1832.6
17.5°	1830.6	1819.4	1794.7	1804.1	1794.7
20°	1787.2	1775.9	1749.5	1755.0	1747.7
22.5°	1743.8	1726.8	1702.1	1702.1	1698.3
25°	1692.7	1677.7	1645.6	1649.2	1645.6
27.5°	1636.0	1622.8	1598.3	1592.7	1583.3
30°	1579.4	1564.3	1536.0	1530.4	1522.8
32.5°	1518.9	1507.7	1477.4	1466.0	1458.4
35°	1460.4	1441.6	1411.3	1399.9	1390.5
37.5°	1394.2	1377.3	1347.0	1333.7	1324.3
40°	1326.4	1311.1	1280.8	1263.9	1256.4
42.5°	1260.2	1245.0	1214.9	1195.8	1184.6
45°	1188.4	1175.2	1146.7	1126.1	1118.4
47.5°	1118.4	1105.2	1075.0	1054.1	1042.9
50°	1044.7	1035.3	1008.9	982.4	972.9
52.5°	972.9	959.7	935.2	914.4	901.2
55°	899.4	888.0	865.3	842.6	833.2
57.5°	825.6	816.2	791.5	768.9	761.2
60°	751.8	744.5	718.0	697.1	691.6
62.5°	680.1	666.9	648.0	629.1	621.6
65°	606.5	595.1	576.2	559.3	549.8
67.5°	531.0	521.4	504.5	491.3	483.6
70°	461.0	453.4	436.4	423.1	415.8
72.5°	389.3	381.6	372.2	359.0	353.4
75°	317.3	313.7	304.1	292.9	296.7
77.5°	253.2	245.5	241.8	236.1	230.6
80°	189.0	187.0	183.2	177.6	173.8
82.5°	128.5	128.5	126.6	119.1	119.1
85°	77.4	75.5	73.7	68.0	66.1
87.5°	34.0	30.3	26.5	20.8	18.9
90°	0.9	10.4	28.3	26.6	27.5
92.5°	17.9	24.2	25.1	26.0	26.0
95°	42.2	50.3	51.7	51.7	50.3
97.5°	70.2	77.7	80.9	80.9	80.9
100°	102.5	109.2	111.5	111.5	110.7
102.5°	136.6	141.6	144.7	145.6	144.7
105°	173.9	176.2	177.9	179.4	179.4
107.5°	210.9	214.3	214.3	214.9	210.9
110°	246.7	251.4	251.4	251.4	249.0



TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	285.4	290.3	289.4	287.1	285.4
115°	323.6	328.1	326.7	325.9	323.6
117.5°	361.3	367.7	363.7	361.3	359.0
120°	399.5	405.9	399.5	399.5	396.9
122.5°	434.1	442.2	438.2	435.9	434.1
125°	470.6	477.8	475.4	472.8	472.0
127.5°	506.0	515.0	511.9	508.4	506.0
130°	539.3	549.7	548.3	546.5	543.3
132.5°	576.5	584.6	585.2	581.2	578.9
135°	608.6	617.5	619.4	618.4	616.1
137.5°	644.4	651.7	653.1	652.6	649.0
140°	675.9	683.2	687.2	687.2	684.0
142.5°	708.3	715.5	717.8	718.7	715.5
145°	738.9	744.7	749.3	750.1	747.0
147.5°	766.4	773.6	777.0	778.5	775.3
150°	794.7	799.6	802.7	805.4	802.7
152.5°	819.8	824.7	828.7	831.9	828.7
155°	845.0	847.2	849.8	853.8	851.3
157.5°	866.6	868.3	869.8	875.6	871.5
160°	886.0	887.7	888.6	893.4	890.0
162.5°	903.8	903.8	904.7	910.2	906.2
165°	919.2	918.3	918.3	924.0	920.0
167.5°	933.0	930.4	930.4	936.1	932.1
170°	943.4	941.1	940.3	946.0	941.1
172.5°	950.6	948.4	947.5	953.2	948.4
175°	956.4	954.1	952.4	958.2	953.2
177.5°	959.6	957.3	955.5	960.5	955.5
180°	958.2	958.2	958.2	958.2	958.2

TEST NUMBER: P908368

CATALOG NUMBER: DFN2DIP-PN2F0-050D030US840-FLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.48	14.49	14.29	15.33	16.37	13.04	14.05	13.85	14.89	15.93
	3H	15.13	16.04	15.96	16.89	17.95	14.65	15.56	15.48	16.41	17.47
	4H	15.71	16.57	16.55	17.43	18.50	15.23	16.09	16.07	16.94	18.02
	6H	16.10	16.90	16.96	17.76	18.85	15.61	16.41	16.47	17.27	18.36
	8H	16.20	16.96	17.07	17.84	18.93	15.72	16.47	16.58	17.35	18.44
	12H	16.25	16.97	17.12	17.84	18.96	15.76	16.48	16.63	17.35	18.47
4H	2H	13.95	14.81	14.79	15.66	16.74	13.60	14.46	14.44	15.31	16.39
	3H	15.80	16.52	16.66	17.41	18.50	15.40	16.12	16.26	17.01	18.10
	4H	16.51	17.16	17.38	18.05	19.16	16.09	16.75	16.97	17.63	18.75
	6H	17.01	17.58	17.90	18.49	19.61	16.59	17.16	17.48	18.07	19.19
	8H	17.15	17.68	18.05	18.59	19.72	16.73	17.26	17.62	18.16	19.30
	12H	17.22	17.70	18.14	18.62	19.76	16.79	17.27	17.70	18.19	19.33
8H	4H	16.70	17.23	17.60	18.14	19.27	16.33	16.86	17.23	17.77	18.90
	6H	17.32	17.76	18.24	18.70	19.84	16.94	17.38	17.86	18.33	19.46
	8H	17.53	17.91	18.45	18.85	20.00	17.15	17.53	18.07	18.47	19.62
	12H	17.65	17.99	18.58	18.92	20.13	17.25	17.60	18.19	18.53	19.73
12H	4H	16.69	17.17	17.61	18.09	19.23	16.33	16.81	17.25	17.73	18.87
	6H	17.34	17.73	18.27	18.67	19.82	16.98	17.37	17.91	18.31	19.46
	8H	17.58	17.92	18.51	18.85	20.05	17.21	17.55	18.14	18.48	19.68