

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P913802

Luminaire Tested: DFN2DIP-PN2F0-040D020US927-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P913802
REPORT IS A COMBINATION OF REPORTS P899466 AND P896349
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-PN2F0-040D020US927-RLLFLL
Description: 2 foot, Pentagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4095.5 lumens
Efficiency: N/A
Efficacy: 74.2 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.17' x L: 2.29' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 55.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9613
Total Harmonic Distortion (THDi): 0.083
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92	81	81	81	71	71	71
1	102	98	94	91	96	92	89	86	82	79	77	72	70	69	63	62	61
2	93	86	80	75	88	81	76	72	72	68	65	64	61	58	57	54	52
3	86	76	69	63	80	72	66	61	65	59	55	57	53	50	51	48	45
4	79	68	60	54	74	65	58	52	58	52	48	52	47	44	46	42	40
5	73	61	53	47	68	58	51	45	52	46	42	47	42	38	42	38	35
6	67	55	47	41	63	52	45	40	47	41	37	42	38	34	38	34	31
7	62	50	42	37	59	48	40	35	43	37	33	39	34	30	35	31	28
8	58	46	38	33	55	44	37	32	40	34	29	36	31	27	32	28	25
9	54	42	35	29	51	40	33	29	36	31	27	33	28	25	30	26	23
10	51	39	31	27	48	37	30	26	34	28	24	31	26	23	28	24	21

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2836	2836	2836
5°	2836	2785	2805
10°	2804	2725	2710
15°	2761	2629	2565
20°	2705	2499	2388
25°	2648	2355	2218
30°	2573	2207	2004
35°	2500	2049	1815
40°	2424	1887	1600
45°	2337	1707	1406
50°	2247	1526	1215
55°	2152	1334	1033
60°	2042	1133	847
65°	1916	930	757
70°	1762	741	679
75°	1568	641	610
80°	1290	521	516
85°	843	324	366

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2337 cd/sqm

TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	122.7	3.0
10°-20°	336.9	8.2
20°-30°	473.1	11.6
30°-40°	515.7	12.6
40°-50°	473.9	11.6
50°-60°	372.2	9.1
60°-70°	242.3	5.9
70°-80°	124.7	3.0
80°-90°	33.3	0.8
90°-100°	31.0	0.8
100°-110°	98.5	2.4
110°-120°	168.6	4.1
120°-130°	221.7	5.4
130°-140°	248.9	6.1
140°-150°	244.1	6.0
150°-160°	204.7	5.0
160°-170°	135.8	3.3
170°-180°	47.5	1.2
0°-30°	932.7	22.8
0°-40°	1448.4	35.4
0°-60°	2294.6	56.0
0°-90°	2694.8	65.8
90°-120°	298.1	7.3
90°-150°	1012.8	24.7
90°-180°	1401.0	34.2
0°-180°	4095.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1310	1310	1310	1310	1310	
5°	1310	1304	1288	1299	1296	124
15°	1246	1233	1192	1170	1158	351
25°	1131	1093	1014	966	948	520
35°	974	914	810	735	709	610
45°	796	717	593	508	480	615
55°	606	513	385	314	292	541
65°	409	313	206	166	162	405
75°	218	135	95	86	85	231
85°	51	26	22	22	22	58
90°	0	6	15	14	14	4
95°	22	26	27	27	26	25
105°	91	92	93	94	94	96
115°	169	172	171	170	169	167
125°	246	250	249	247	247	220
135°	318	323	324	323	322	246
145°	386	389	392	392	391	241
155°	442	443	444	447	445	203
165°	481	480	480	483	481	136
175°	500	499	498	501	498	48
180°	501	501	501	501	501	

TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLFL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1309.6	1309.6	1309.6	1309.6	1309.6
2.5°	1315.6	1309.6	1296.6	1308.5	1306.1
5°	1309.6	1303.7	1288.2	1298.9	1295.5
7.5°	1298.9	1291.9	1275.3	1279.9	1274.1
10°	1284.8	1276.4	1252.8	1249.1	1242.1
12.5°	1267.0	1256.3	1224.2	1217.2	1204.1
15°	1245.6	1232.6	1192.3	1169.8	1158.0
17.5°	1220.8	1201.7	1151.9	1125.9	1106.9
20°	1192.3	1168.5	1109.3	1079.7	1053.6
22.5°	1161.5	1134.2	1065.4	1025.2	1007.5
25°	1130.7	1092.7	1014.5	966.0	948.1
27.5°	1094.0	1053.6	967.1	911.4	884.1
30°	1054.9	1009.7	914.9	854.5	822.5
32.5°	1016.9	962.3	865.2	794.1	764.4
35°	974.3	913.8	809.5	734.8	708.7
37.5°	932.8	867.5	757.3	675.5	645.9
40°	888.9	817.8	702.8	618.7	587.9
42.5°	843.8	768.0	648.3	560.5	531.0
45°	796.5	717.0	592.6	508.4	480.0
47.5°	751.5	667.3	539.3	455.1	429.0
50°	701.6	617.5	487.1	405.3	380.5
52.5°	653.0	564.1	437.4	359.1	336.6
55°	605.6	513.2	385.2	314.1	291.6
57.5°	557.1	462.2	339.0	272.6	253.7
60°	507.2	412.4	290.3	230.0	211.0
62.5°	458.8	363.9	248.8	192.0	182.6
65°	408.9	312.8	206.2	166.0	162.3
67.5°	361.6	265.5	166.0	145.8	142.2
70°	311.7	219.3	137.4	125.6	120.8
72.5°	264.4	176.6	114.9	105.5	103.1
75°	218.0	135.1	94.8	86.5	85.4
77.5°	171.9	95.9	74.7	69.9	67.5
80°	129.1	68.8	56.8	52.2	52.2
82.5°	90.1	46.3	39.1	36.7	36.7
85°	50.9	26.1	22.5	22.5	22.5
87.5°	19.0	9.4	9.4	8.3	8.3
90°	0.5	5.5	14.8	13.9	14.3
92.5°	9.3	12.7	13.2	13.6	13.6
95°	22.0	26.3	27.0	27.0	26.3
97.5°	36.7	40.6	42.3	42.3	42.3
100°	53.6	57.1	58.3	58.3	57.8
102.5°	71.5	74.0	75.7	76.1	75.7
105°	90.9	92.1	93.1	93.8	93.8
107.5°	110.3	112.1	112.1	112.4	110.3
110°	129.0	131.4	131.4	131.4	130.2



TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	149.2	151.8	151.4	150.1	149.2
115°	169.2	171.6	170.9	170.4	169.2
117.5°	189.0	192.3	190.2	189.0	187.7
120°	208.9	212.2	208.9	208.9	207.6
122.5°	227.0	231.2	229.2	228.0	227.0
125°	246.1	249.9	248.7	247.3	246.8
127.5°	264.7	269.3	267.7	265.9	264.7
130°	282.0	287.5	286.7	285.8	284.2
132.5°	301.5	305.8	306.0	304.0	302.7
135°	318.3	323.0	323.8	323.4	322.2
137.5°	337.0	340.8	341.6	341.3	339.4
140°	353.5	357.3	359.4	359.4	357.7
142.5°	370.4	374.1	375.4	375.8	374.1
145°	386.4	389.4	391.9	392.3	390.6
147.5°	400.8	404.6	406.4	407.1	405.4
150°	415.6	418.1	419.8	421.1	419.8
152.5°	428.7	431.3	433.4	435.1	433.4
155°	441.9	443.1	444.4	446.6	445.2
157.5°	453.2	454.1	454.9	457.9	455.7
160°	463.3	464.2	464.7	467.2	465.4
162.5°	472.7	472.7	473.1	476.0	473.9
165°	480.7	480.2	480.2	483.2	481.2
167.5°	487.9	486.6	486.6	489.6	487.5
170°	493.4	492.2	491.7	494.7	492.2
172.5°	497.2	495.9	495.5	498.5	495.9
175°	500.2	499.0	498.0	501.1	498.5
177.5°	501.8	500.7	499.7	502.2	499.7
180°	501.1	501.1	501.1	501.1	501.1

TEST NUMBER: P913802

CATALOG NUMBER: DFN2DIP-PN2F0-040D020US927-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.01	12.99	12.83	13.82	14.85	7.98	8.96	8.80	9.79	10.82
	3H	13.68	14.56	14.51	15.40	16.46	9.16	10.04	9.99	10.88	11.94
	4H	14.28	15.11	15.13	15.96	17.03	9.61	10.43	10.46	11.28	12.35
	6H	14.70	15.46	15.55	16.31	17.39	9.92	10.68	10.78	11.54	12.62
	8H	14.82	15.54	15.68	16.42	17.50	10.01	10.73	10.88	11.61	12.69
	12H	14.88	15.56	15.75	16.43	17.54	10.05	10.74	10.92	11.61	12.71
4H	2H	12.04	12.87	12.89	13.72	14.79	8.58	9.41	9.43	10.26	11.33
	3H	13.86	14.55	14.73	15.43	16.52	9.93	10.61	10.79	11.50	12.58
	4H	14.55	15.17	15.42	16.05	17.16	10.47	11.09	11.34	11.97	13.08
	6H	15.05	15.59	15.94	16.49	17.61	10.87	11.41	11.76	12.32	13.43
	8H	15.22	15.72	16.11	16.62	17.74	11.00	11.50	11.89	12.40	13.52
	12H	15.31	15.76	16.22	16.68	17.81	11.06	11.51	11.97	12.43	13.56
8H	4H	14.52	15.02	15.41	15.92	17.05	10.74	11.25	11.64	12.15	13.27
	6H	15.07	15.48	15.99	16.42	17.55	11.25	11.66	12.16	12.60	13.73
	8H	15.27	15.64	16.20	16.57	17.72	11.42	11.79	12.35	12.72	13.87
	12H	15.40	15.73	16.33	16.65	17.85	11.54	11.86	12.47	12.78	13.98
12H	4H	14.48	14.93	15.39	15.85	16.98	10.75	11.20	11.66	12.12	13.25
	6H	15.04	15.41	15.97	16.34	17.49	11.29	11.66	12.22	12.59	13.73
	8H	15.26	15.58	16.19	16.50	17.70	11.49	11.81	12.42	12.74	13.94