

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P924674

Luminaire Tested: DFN2DIP-PN2F0-020D020US950-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P924674
REPORT IS A COMBINATION OF REPORTS P899462 AND P896349
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-PN2F0-020D020US950-RLLFLL
Description: 2 foot, Pentagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3310.4 lumens
Efficiency: N/A
Efficacy: 102.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.17' x L: 2.29' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 32.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.099
Total Harmonic Distortion (THDi): 0.979
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83	68	68	68	55	55	55
1	98	94	90	87	90	87	84	81	73	71	69	61	59	58	50	49	48
2	90	83	77	72	82	76	71	67	65	61	58	54	51	49	44	42	41
3	82	73	66	60	75	68	61	57	58	53	49	48	45	42	40	37	35
4	75	65	57	51	69	60	54	48	51	46	42	43	40	36	36	33	31
5	69	58	50	44	64	54	47	42	46	41	37	39	35	32	32	29	27
6	64	52	44	39	59	49	42	37	42	36	32	35	31	28	30	26	24
7	59	47	40	34	55	44	37	32	38	33	29	32	28	25	27	24	22
8	55	43	36	30	51	40	33	29	35	29	26	30	26	23	25	22	20
9	51	39	32	27	47	37	30	26	32	27	23	27	23	20	23	20	18
10	48	36	29	24	44	34	28	23	30	24	21	25	21	19	22	18	16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1708	1708	1708
5°	1708	1677	1689
10°	1688	1641	1632
15°	1662	1583	1545
20°	1629	1505	1438
25°	1595	1418	1336
30°	1549	1329	1206
35°	1505	1234	1093
40°	1460	1136	963
45°	1407	1028	846
50°	1353	919	732
55°	1296	803	622
60°	1230	683	510
65°	1154	560	456
70°	1061	446	409
75°	945	386	367
80°	777	314	311
85°	507	194	220

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1407 cd/sqm

TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLFL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.9	2.2
10°-20°	202.9	6.1
20°-30°	284.8	8.6
30°-40°	310.5	9.4
40°-50°	285.4	8.6
50°-60°	224.1	6.8
60°-70°	145.9	4.4
70°-80°	75.1	2.3
80°-90°	20.9	0.6
90°-100°	37.3	1.1
100°-110°	118.7	3.6
110°-120°	203.0	6.1
120°-130°	267.0	8.1
130°-140°	299.7	9.1
140°-150°	293.9	8.9
150°-160°	246.5	7.4
160°-170°	163.5	4.9
170°-180°	57.1	1.7
0°-30°	561.6	17.0
0°-40°	872.1	26.3
0°-60°	1381.7	41.7
0°-90°	1623.5	49.0
90°-120°	359.0	10.8
90°-150°	1219.7	36.8
90°-180°	1687.0	51.0
0°-180°	3310.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	789	789	789	789	789	
5°	789	785	776	782	780	75
15°	750	742	718	704	697	211
25°	681	658	611	582	571	313
35°	587	550	488	442	427	367
45°	480	432	357	306	289	370
55°	365	309	232	189	176	326
65°	246	188	124	100	98	244
75°	131	81	57	52	51	139
85°	31	16	14	14	14	35
90°	1	7	18	17	17	3
95°	26	32	32	32	32	30
105°	110	111	112	113	113	116
115°	204	207	206	205	204	202
125°	296	301	300	298	297	265
135°	383	389	390	390	388	296
145°	465	469	472	472	470	291
155°	532	534	535	538	536	245
165°	579	578	578	582	580	163
175°	602	601	600	603	600	57
180°	603	603	603	603	603	

TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLFL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	788.6	788.6	788.6	788.6	788.6
2.5°	792.1	788.6	780.7	787.9	786.5
5°	788.6	785.0	775.7	782.2	780.0
7.5°	782.2	777.9	767.9	770.7	767.1
10°	773.6	768.5	754.3	752.1	747.9
12.5°	762.9	756.4	737.2	733.0	725.0
15°	750.0	742.1	717.9	704.3	697.3
17.5°	735.1	723.6	693.7	677.9	666.6
20°	717.9	703.6	668.0	650.2	634.4
22.5°	699.4	683.0	641.6	617.3	606.6
25°	680.9	658.0	610.8	581.7	570.9
27.5°	658.7	634.4	582.3	548.7	532.3
30°	635.2	608.0	550.9	514.6	495.2
32.5°	612.3	579.5	521.0	478.1	460.3
35°	586.6	550.3	487.5	442.5	426.7
37.5°	561.6	522.3	456.0	406.8	388.9
40°	535.2	492.5	423.2	372.5	353.9
42.5°	508.1	462.5	390.4	337.5	319.8
45°	479.6	431.7	356.9	306.1	289.0
47.5°	452.5	401.8	324.7	274.0	258.3
50°	422.5	371.9	293.4	244.0	229.2
52.5°	393.1	339.6	263.3	216.3	202.7
55°	364.6	309.0	231.9	189.2	175.5
57.5°	335.4	278.3	204.2	164.2	152.7
60°	305.5	248.3	174.9	138.5	127.1
62.5°	276.2	219.1	149.9	115.6	109.9
65°	246.2	188.4	124.2	100.0	97.8
67.5°	217.7	159.8	100.0	87.8	85.7
70°	187.7	132.0	82.7	75.7	72.8
72.5°	159.1	106.3	69.2	63.5	62.1
75°	131.3	81.3	57.0	52.1	51.4
77.5°	103.5	57.8	44.9	42.1	40.6
80°	77.8	41.4	34.2	31.4	31.4
82.5°	54.2	27.9	23.6	22.1	22.1
85°	30.6	15.6	13.5	13.5	13.5
87.5°	11.4	5.7	5.7	5.0	5.0
90°	0.6	6.6	17.8	16.7	17.3
92.5°	11.3	15.3	15.8	16.4	16.4
95°	26.5	31.7	32.5	32.5	31.7
97.5°	44.2	48.9	50.9	50.9	50.9
100°	64.6	68.8	70.2	70.2	69.6
102.5°	86.1	89.1	91.1	91.7	91.1
105°	109.5	111.0	112.1	113.0	113.0
107.5°	132.8	135.0	135.0	135.4	132.8
110°	155.4	158.3	158.3	158.3	156.8

TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	179.7	182.8	182.3	180.8	179.7
115°	203.8	206.6	205.8	205.2	203.8
117.5°	227.6	231.6	229.1	227.6	226.1
120°	251.6	255.6	251.6	251.6	249.9
122.5°	273.4	278.5	276.0	274.6	273.4
125°	296.3	300.9	299.5	297.8	297.3
127.5°	318.7	324.4	322.4	320.2	318.7
130°	339.6	346.2	345.3	344.2	342.2
132.5°	363.1	368.2	368.5	366.0	364.5
135°	383.3	388.9	390.0	389.5	388.0
137.5°	405.8	410.4	411.4	411.0	408.8
140°	425.7	430.3	432.8	432.8	430.8
142.5°	446.1	450.6	452.1	452.6	450.6
145°	465.4	469.0	471.9	472.4	470.4
147.5°	482.6	487.2	489.4	490.3	488.3
150°	500.5	503.5	505.5	507.1	505.5
152.5°	516.3	519.4	521.9	523.9	521.9
155°	532.1	533.6	535.2	537.8	536.1
157.5°	545.8	546.8	547.8	551.4	548.8
160°	558.0	559.0	559.6	562.7	560.5
162.5°	569.3	569.3	569.7	573.3	570.7
165°	578.9	578.3	578.3	581.9	579.5
167.5°	587.6	585.9	585.9	589.6	587.1
170°	594.2	592.7	592.1	595.8	592.7
172.5°	598.7	597.2	596.7	600.4	597.2
175°	602.4	600.9	599.8	603.4	600.4
177.5°	604.4	602.9	601.8	604.8	601.8
180°	603.4	603.4	603.4	603.4	603.4

TEST NUMBER: P924674

CATALOG NUMBER: DFN2DIP-PN2F0-020D020US950-RLFL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	8.80	9.62	9.77	10.60	11.89	4.77	5.59	5.74	6.57	7.86
	3H	10.45	11.19	11.44	12.18	13.49	5.94	6.68	6.92	7.67	8.98
	4H	11.05	11.74	12.05	12.74	14.06	6.38	7.07	7.37	8.07	9.39
	6H	11.45	12.09	12.46	13.09	14.42	6.68	7.32	7.69	8.32	9.65
	8H	11.57	12.18	12.58	13.19	14.52	6.76	7.37	7.78	8.39	9.72
	12H	11.62	12.20	12.64	13.21	14.56	6.80	7.38	7.82	8.39	9.74
4H	2H	8.81	9.51	9.81	10.50	11.82	5.35	6.05	6.35	7.04	8.36
	3H	10.62	11.19	11.63	12.22	13.55	6.68	7.26	7.69	8.28	9.61
	4H	11.29	11.82	12.31	12.84	14.19	7.21	7.74	8.23	8.76	10.11
	6H	11.79	12.24	12.82	13.28	14.63	7.61	8.07	8.64	9.11	10.46
	8H	11.95	12.37	12.98	13.41	14.77	7.73	8.16	8.76	9.19	10.55
	12H	12.03	12.42	13.08	13.46	14.83	7.79	8.17	8.84	9.22	10.59
8H	4H	11.25	11.68	12.29	12.71	14.08	7.48	7.90	8.51	8.94	10.30
	6H	11.80	12.15	12.85	13.22	14.59	7.97	8.32	9.03	9.40	10.76
	8H	12.00	12.31	13.06	13.37	14.75	8.15	8.46	9.21	9.52	10.90
	12H	12.12	12.40	13.19	13.45	14.87	8.26	8.53	9.32	9.58	11.01
12H	4H	11.21	11.59	12.25	12.63	14.01	7.48	7.86	8.53	8.91	10.28
	6H	11.77	12.08	12.83	13.14	14.52	8.02	8.33	9.08	9.39	10.77
	8H	11.98	12.25	13.04	13.30	14.73	8.21	8.48	9.28	9.54	10.96