

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P905684

Luminaire Tested: DFN2DIP-PN3F0-030D050US835-FLLFLL

Issue Date: 11/21/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P905684  
REPORT IS A COMBINATION OF REPORTS P899539 AND P896399  
Test Lab: INNOVATION CENTER  
Issue Date: 11/21/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: DFN2DIP-PN3F0-030D050US835-FLLFLL  
Description: 3 foot, Pentagon Define Geo, with Direct Frosted Lens, Indirect Frosted Lens  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 7395.0 lumens  
Efficiency: N/A  
Efficacy: 120.0 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29  
Luminous Opening: Rectangular w/ Sides (W: 2.96' x L: 3.11' x H: 0.1')  
CIE Type: General Diffuse

Input Watts (W): 61.6  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: 0.099  
Total Harmonic Distortion (THDi): 0.979  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFLL

### Luminous Intensity Polar Plot



TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |    |
|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| RF  | 20  |     |     |     | 20 |    |    |    | 20 |    |    |    | 20 |    |    |    | 20 |
| RC  | 80  |     |     |     | 70 |    |    |    | 50 |    |    |    | 30 |    |    |    | 10 |
| RW  | 70  | 50  | 30  | 10  | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 0   | 105 | 105 | 105 | 105 | 95 | 95 | 95 | 95 | 78 | 78 | 78 | 62 | 62 | 62 | 47 | 47 | 47 |
| 1   | 96  | 91  | 87  | 84  | 87 | 83 | 80 | 77 | 68 | 66 | 64 | 54 | 53 | 51 | 42 | 41 | 40 |
| 2   | 87  | 80  | 74  | 69  | 79 | 73 | 68 | 63 | 60 | 56 | 53 | 48 | 45 | 43 | 37 | 35 | 33 |
| 3   | 79  | 70  | 63  | 57  | 72 | 64 | 58 | 53 | 53 | 48 | 44 | 42 | 39 | 36 | 32 | 30 | 28 |
| 4   | 73  | 62  | 54  | 48  | 66 | 57 | 50 | 45 | 47 | 42 | 38 | 38 | 34 | 31 | 29 | 27 | 25 |
| 5   | 67  | 55  | 47  | 41  | 60 | 51 | 44 | 38 | 42 | 37 | 33 | 34 | 30 | 27 | 26 | 23 | 21 |
| 6   | 61  | 49  | 41  | 36  | 56 | 45 | 38 | 33 | 38 | 32 | 28 | 30 | 27 | 24 | 24 | 21 | 19 |
| 7   | 57  | 45  | 37  | 31  | 51 | 41 | 34 | 29 | 34 | 29 | 25 | 28 | 24 | 21 | 22 | 19 | 17 |
| 8   | 52  | 40  | 33  | 28  | 48 | 37 | 30 | 26 | 31 | 26 | 22 | 25 | 21 | 18 | 20 | 17 | 15 |
| 9   | 49  | 37  | 29  | 24  | 44 | 34 | 27 | 23 | 28 | 23 | 20 | 23 | 19 | 17 | 18 | 16 | 14 |
| 10  | 46  | 34  | 27  | 22  | 41 | 31 | 25 | 20 | 26 | 21 | 18 | 21 | 18 | 15 | 17 | 14 | 12 |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°   | 45°  | 90°  |
|-----|------|------|------|
| 0°  | 1365 | 1365 | 1365 |
| 5°  | 1366 | 1345 | 1354 |
| 10° | 1354 | 1326 | 1335 |
| 15° | 1333 | 1303 | 1306 |
| 20° | 1306 | 1271 | 1276 |
| 25° | 1278 | 1234 | 1242 |
| 30° | 1244 | 1200 | 1198 |
| 35° | 1211 | 1159 | 1152 |
| 40° | 1171 | 1118 | 1108 |
| 45° | 1131 | 1076 | 1063 |
| 50° | 1087 | 1033 | 1011 |
| 55° | 1041 | 982  | 963  |
| 60° | 989  | 923  | 908  |
| 65° | 933  | 861  | 843  |
| 70° | 860  | 786  | 772  |
| 75° | 760  | 695  | 707  |
| 80° | 639  | 579  | 584  |
| 85° | 451  | 383  | 380  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 90°

Vertical Angle: 90°

Luminance: 1567 cd/sqm

TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFLL

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 109.9  | 1.5       |
| 10°-20°   | 309.1  | 4.2       |
| 20°-30°   | 454.3  | 6.1       |
| 30°-40°   | 527.6  | 7.1       |
| 40°-50°   | 527.0  | 7.1       |
| 50°-60°   | 459.5  | 6.2       |
| 60°-70°   | 339.7  | 4.6       |
| 70°-80°   | 192.2  | 2.6       |
| 80°-90°   | 55.2   | 0.7       |
| 90°-100°  | 97.8   | 1.3       |
| 100°-110° | 310.9  | 4.2       |
| 110°-120° | 532.1  | 7.2       |
| 120°-130° | 699.7  | 9.5       |
| 130°-140° | 785.4  | 10.6      |
| 140°-150° | 770.2  | 10.4      |
| 150°-160° | 646.1  | 8.7       |
| 160°-170° | 428.5  | 5.8       |
| 170°-180° | 149.8  | 2.0       |
| 0°-30°    | 873.3  | 11.8      |
| 0°-40°    | 1400.9 | 18.9      |
| 0°-60°    | 2387.4 | 32.3      |
| 0°-90°    | 2974.5 | 40.2      |
| 90°-120°  | 940.8  | 12.7      |
| 90°-150°  | 3196.2 | 43.2      |
| 90°-180°  | 4421.0 | 59.8      |
| 0°-180°   | 7395.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | 22.5° | 45°  | 67.5° | 90°  | Flux |
|------|------|-------|------|-------|------|------|
| 0°   | 1167 | 1167  | 1167 | 1167  | 1167 |      |
| 5°   | 1167 | 1163  | 1150 | 1160  | 1157 | 111  |
| 15°  | 1111 | 1105  | 1090 | 1094  | 1089 | 313  |
| 25°  | 1006 | 997   | 978  | 980   | 978  | 463  |
| 35°  | 868  | 856   | 838  | 832   | 826  | 542  |
| 45°  | 706  | 698   | 681  | 669   | 664  | 545  |
| 55°  | 534  | 528   | 514  | 501   | 495  | 478  |
| 65°  | 360  | 354   | 342  | 332   | 327  | 356  |
| 75°  | 188  | 186   | 181  | 174   | 176  | 201  |
| 85°  | 46   | 45    | 44   | 40    | 39   | 51   |
| 90°  | 1    | 17    | 47   | 44    | 45   | 7    |
| 95°  | 70   | 83    | 85   | 85    | 83   | 77   |
| 105° | 287  | 291   | 294  | 296   | 296  | 303  |
| 115° | 534  | 542   | 539  | 538   | 534  | 528  |
| 125° | 777  | 788   | 785  | 780   | 779  | 694  |
| 135° | 1004 | 1019  | 1022 | 1021  | 1017 | 776  |
| 145° | 1220 | 1229  | 1237 | 1238  | 1233 | 762  |
| 155° | 1394 | 1398  | 1402 | 1409  | 1405 | 642  |
| 165° | 1517 | 1516  | 1516 | 1525  | 1518 | 428  |
| 175° | 1578 | 1575  | 1572 | 1581  | 1573 | 150  |
| 180° | 1581 | 1581  | 1581 | 1581  | 1581 |      |

TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFLL

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 0°     | 1167.3 | 1167.3 | 1167.3 | 1167.3 | 1167.3 |
| 2.5°   | 1174.1 | 1168.5 | 1156.1 | 1167.3 | 1165.2 |
| 5°     | 1167.3 | 1162.9 | 1150.5 | 1159.5 | 1157.3 |
| 7.5°   | 1159.5 | 1152.8 | 1140.4 | 1149.5 | 1147.2 |
| 10°    | 1147.2 | 1139.3 | 1125.9 | 1134.8 | 1131.5 |
| 12.5°  | 1130.3 | 1123.6 | 1110.2 | 1115.7 | 1113.5 |
| 15°    | 1111.2 | 1104.6 | 1089.9 | 1094.4 | 1088.8 |
| 17.5°  | 1087.6 | 1081.0 | 1066.3 | 1071.9 | 1066.3 |
| 20°    | 1061.8 | 1055.1 | 1039.4 | 1042.7 | 1038.3 |
| 22.5°  | 1036.1 | 1026.0 | 1011.3 | 1011.3 | 1009.0 |
| 25°    | 1005.7 | 996.8  | 977.7  | 979.9  | 977.7  |
| 27.5°  | 972.0  | 964.1  | 949.6  | 946.3  | 940.7  |
| 30°    | 938.4  | 929.4  | 912.6  | 909.2  | 904.7  |
| 32.5°  | 902.5  | 895.8  | 877.8  | 871.0  | 866.5  |
| 35°    | 867.7  | 856.5  | 838.5  | 831.7  | 826.1  |
| 37.5°  | 828.4  | 818.3  | 800.3  | 792.4  | 786.8  |
| 40°    | 788.0  | 779.0  | 761.0  | 751.0  | 746.5  |
| 42.5°  | 748.7  | 739.7  | 721.8  | 710.5  | 703.8  |
| 45°    | 706.1  | 698.2  | 681.3  | 669.0  | 664.5  |
| 47.5°  | 664.5  | 656.7  | 638.7  | 626.3  | 619.6  |
| 50°    | 620.7  | 615.1  | 599.4  | 583.7  | 578.1  |
| 52.5°  | 578.1  | 570.2  | 555.7  | 543.3  | 535.4  |
| 55°    | 534.4  | 527.6  | 514.1  | 500.7  | 495.1  |
| 57.5°  | 490.5  | 484.9  | 470.3  | 456.8  | 452.3  |
| 60°    | 446.7  | 442.3  | 426.6  | 414.2  | 410.9  |
| 62.5°  | 404.1  | 396.2  | 385.0  | 373.8  | 369.3  |
| 65°    | 360.4  | 353.6  | 342.4  | 332.3  | 326.7  |
| 67.5°  | 315.5  | 309.8  | 299.7  | 291.9  | 287.4  |
| 70°    | 273.9  | 269.4  | 259.3  | 251.4  | 247.0  |
| 72.5°  | 231.3  | 226.7  | 221.1  | 213.3  | 210.0  |
| 75°    | 188.5  | 186.4  | 180.7  | 174.0  | 176.3  |
| 77.5°  | 150.4  | 145.9  | 143.6  | 140.3  | 137.0  |
| 80°    | 112.3  | 111.1  | 108.8  | 105.5  | 103.3  |
| 82.5°  | 76.3   | 76.3   | 75.3   | 70.7   | 70.7   |
| 85°    | 46.0   | 44.9   | 43.8   | 40.4   | 39.3   |
| 87.5°  | 20.2   | 18.0   | 15.7   | 12.4   | 11.2   |
| 90°    | 1.4    | 17.2   | 46.7   | 43.9   | 45.3   |
| 92.5°  | 29.6   | 40.0   | 41.5   | 42.9   | 42.9   |
| 95°    | 69.6   | 83.0   | 85.3   | 85.3   | 83.0   |
| 97.5°  | 115.8  | 128.2  | 133.5  | 133.5  | 133.5  |
| 100°   | 169.2  | 180.2  | 184.0  | 184.0  | 182.6  |
| 102.5° | 225.5  | 233.6  | 238.8  | 240.3  | 238.8  |
| 105°   | 287.0  | 290.8  | 293.7  | 296.0  | 296.0  |
| 107.5° | 348.0  | 353.7  | 353.7  | 354.7  | 348.0  |
| 110°   | 407.1  | 414.8  | 414.8  | 414.8  | 410.9  |

TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFLL

**CANDELA DISTRIBUTION (continued):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 112.5° | 471.0  | 479.1  | 477.7  | 473.9  | 471.0  |
| 115°   | 533.9  | 541.6  | 539.2  | 537.8  | 533.9  |
| 117.5° | 596.4  | 606.9  | 600.2  | 596.4  | 592.6  |
| 120°   | 659.3  | 669.8  | 659.3  | 659.3  | 655.0  |
| 122.5° | 716.5  | 729.9  | 723.2  | 719.4  | 716.5  |
| 125°   | 776.6  | 788.5  | 784.7  | 780.4  | 779.0  |
| 127.5° | 835.2  | 850.0  | 844.8  | 839.0  | 835.2  |
| 130°   | 890.1  | 907.2  | 904.8  | 902.0  | 896.7  |
| 132.5° | 951.6  | 964.9  | 965.9  | 959.2  | 955.4  |
| 135°   | 1004.5 | 1019.2 | 1022.1 | 1020.7 | 1016.9 |
| 137.5° | 1063.6 | 1075.5 | 1077.9 | 1076.9 | 1071.2 |
| 140°   | 1115.5 | 1127.5 | 1134.1 | 1134.1 | 1128.9 |
| 142.5° | 1168.9 | 1180.9 | 1184.7 | 1186.1 | 1180.9 |
| 145°   | 1219.5 | 1229.0 | 1236.6 | 1238.1 | 1232.8 |
| 147.5° | 1264.8 | 1276.7 | 1282.4 | 1284.8 | 1279.5 |
| 150°   | 1311.5 | 1319.6 | 1324.8 | 1329.1 | 1324.8 |
| 152.5° | 1353.0 | 1361.1 | 1367.7 | 1373.0 | 1367.7 |
| 155°   | 1394.4 | 1398.2 | 1402.5 | 1409.2 | 1404.9 |
| 157.5° | 1430.2 | 1433.0 | 1435.4 | 1445.0 | 1438.3 |
| 160°   | 1462.1 | 1465.0 | 1466.4 | 1474.5 | 1468.8 |
| 162.5° | 1491.7 | 1491.7 | 1493.1 | 1502.2 | 1495.5 |
| 165°   | 1517.0 | 1515.5 | 1515.5 | 1525.1 | 1518.4 |
| 167.5° | 1539.8 | 1535.5 | 1535.5 | 1545.1 | 1538.4 |
| 170°   | 1557.0 | 1553.2 | 1551.8 | 1561.3 | 1553.2 |
| 172.5° | 1568.9 | 1565.1 | 1563.7 | 1573.2 | 1565.1 |
| 175°   | 1578.5 | 1574.6 | 1571.8 | 1581.3 | 1573.2 |
| 177.5° | 1583.7 | 1579.9 | 1577.0 | 1585.1 | 1577.0 |
| 180°   | 1581.3 | 1581.3 | 1581.3 | 1581.3 | 1581.3 |

TEST NUMBER: P905684

CATALOG NUMBER: DFN2DIP-PN3F0-030D050US835-FLLFLL

**CIE UGR TABLE:**

| Reflectances:   |      |                  |       |       |       |       |                |       |       |       |       |
|-----------------|------|------------------|-------|-------|-------|-------|----------------|-------|-------|-------|-------|
| Ceiling         |      | 0.7              | 0.7   | 0.5   | 0.5   | 0.3   | 0.7            | 0.7   | 0.5   | 0.5   | 0.3   |
| Wall            |      | 0.5              | 0.3   | 0.5   | 0.3   | 0.3   | 0.5            | 0.3   | 0.5   | 0.3   | 0.3   |
| Reference plane |      | 0.2              | 0.2   | 0.2   | 0.2   | 0.2   | 0.2            | 0.2   | 0.2   | 0.2   | 0.2   |
| Room dimensions |      | Viewed crosswise |       |       |       |       | Viewed endwise |       |       |       |       |
| X=2H            | Y=2H | 7.33             | 8.11  | 8.37  | 9.16  | 10.56 | 6.89           | 7.67  | 7.93  | 8.72  | 10.12 |
|                 | 3H   | 8.98             | 9.68  | 10.03 | 10.73 | 12.16 | 8.50           | 9.20  | 9.55  | 10.25 | 11.67 |
|                 | 4H   | 9.56             | 10.22 | 10.62 | 11.28 | 12.71 | 9.08           | 9.74  | 10.14 | 10.79 | 12.22 |
|                 | 6H   | 9.95             | 10.56 | 11.02 | 11.62 | 13.06 | 9.46           | 10.07 | 10.53 | 11.13 | 12.57 |
|                 | 8H   | 10.05            | 10.63 | 11.13 | 11.71 | 13.14 | 9.56           | 10.14 | 10.64 | 11.22 | 12.66 |
|                 | 12H  | 10.10            | 10.65 | 11.17 | 11.72 | 13.18 | 9.60           | 10.15 | 10.68 | 11.22 | 12.68 |
| 4H              | 2H   | 7.78             | 8.44  | 8.85  | 9.50  | 10.93 | 7.43           | 8.09  | 8.50  | 9.15  | 10.58 |
|                 | 3H   | 9.63             | 10.19 | 10.71 | 11.27 | 12.71 | 9.23           | 9.78  | 10.30 | 10.87 | 12.31 |
|                 | 4H   | 10.34            | 10.85 | 11.42 | 11.92 | 13.38 | 9.92           | 10.43 | 11.00 | 11.50 | 12.97 |
|                 | 6H   | 10.84            | 11.28 | 11.93 | 12.37 | 13.83 | 10.42          | 10.86 | 11.51 | 11.95 | 13.41 |
|                 | 8H   | 10.99            | 11.40 | 12.08 | 12.48 | 13.96 | 10.56          | 10.97 | 11.65 | 12.06 | 13.53 |
|                 | 12H  | 11.05            | 11.42 | 12.16 | 12.52 | 14.00 | 10.62          | 10.99 | 11.72 | 12.09 | 13.57 |
| 8H              | 4H   | 10.52            | 10.93 | 11.61 | 12.02 | 13.49 | 10.15          | 10.56 | 11.24 | 11.65 | 13.12 |
|                 | 6H   | 11.15            | 11.48 | 12.25 | 12.61 | 14.08 | 10.77          | 11.11 | 11.88 | 12.24 | 13.71 |
|                 | 8H   | 11.36            | 11.66 | 12.48 | 12.77 | 14.26 | 10.98          | 11.27 | 12.09 | 12.38 | 13.88 |
|                 | 12H  | 11.48            | 11.74 | 12.60 | 12.85 | 14.38 | 11.08          | 11.34 | 12.20 | 12.45 | 13.98 |
| 12H             | 4H   | 10.51            | 10.87 | 11.61 | 11.98 | 13.46 | 10.14          | 10.51 | 11.25 | 11.61 | 13.09 |
|                 | 6H   | 11.17            | 11.47 | 12.29 | 12.58 | 14.07 | 10.81          | 11.10 | 11.93 | 12.22 | 13.71 |
|                 | 8H   | 11.41            | 11.66 | 12.53 | 12.77 | 14.30 | 11.03          | 11.29 | 12.15 | 12.40 | 13.93 |