

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P903402

Luminaire Tested: DFN2DIP-PN4F0-110D050US830-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P903402
REPORT IS A COMBINATION OF REPORTS P899642 AND P896497
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-PN4F0-110D050US830-RLLFLL
Description: 4 foot, Pentagon Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 12983.5 lumens
Efficiency: N/A
Efficacy: 85.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 3.74' x L: 3.94' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 151.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.996
Total Harmonic Distortion (THDi): 0.064
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	111	111	111	111	105	105	105	105	93	93	93		82	82	82		73
1	102	98	94	91	97	93	90	87	83	80	78		74	72	70		65
2	94	87	81	76	88	82	77	72	73	69	66		66	62	60		58
3	86	77	70	64	81	73	66	61	65	60	56		59	55	51		52
4	79	68	61	55	74	65	58	53	59	53	49		53	48	45		47
5	73	61	53	47	69	58	51	46	53	47	42		48	43	39		43
6	68	56	47	42	64	53	46	40	48	42	37		43	38	35		39
7	63	50	42	37	59	48	41	36	44	38	33		40	35	31		36
8	58	46	38	33	55	44	37	32	40	34	30		37	32	28		33
9	55	42	35	30	52	40	34	29	37	31	27		34	29	25		31
10	51	39	32	27	48	37	31	26	34	29	25		31	27	23		29

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3128	3128	3128
5°	3133	3079	3099
10°	3102	3019	2998
15°	3059	2919	2843
20°	3003	2782	2652
25°	2945	2628	2468
30°	2867	2471	2234
35°	2791	2301	2028
40°	2714	2125	1793
45°	2624	1931	1579
50°	2531	1734	1370
55°	2433	1524	1170
60°	2321	1304	963
65°	2192	1080	868
70°	2035	872	786
75°	1838	769	717
80°	1552	647	624
85°	1081	434	472

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 2624 cd/sqm

TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLFL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	401.6	3.1
10°-20°	1102.5	8.5
20°-30°	1547.8	11.9
30°-40°	1687.2	13.0
40°-50°	1550.8	11.9
50°-60°	1217.9	9.4
60°-70°	792.7	6.1
70°-80°	408.1	3.1
80°-90°	108.4	0.8
90°-100°	92.2	0.7
100°-110°	293.0	2.3
110°-120°	501.5	3.9
120°-130°	659.5	5.1
130°-140°	740.3	5.7
140°-150°	725.9	5.6
150°-160°	609.0	4.7
160°-170°	403.9	3.1
170°-180°	141.2	1.1
0°-30°	3051.9	23.5
0°-40°	4739.1	36.5
0°-60°	7507.8	57.8
0°-90°	8817.0	67.9
90°-120°	886.7	6.8
90°-150°	3012.5	23.2
90°-180°	4167.0	32.1
0°-180°	12983.5	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	4285	4285	4285	4285	4285	
5°	4285	4266	4215	4250	4239	406
15°	4076	4033	3901	3828	3789	1148
25°	3700	3575	3319	3161	3102	1701
35°	3188	2990	2649	2404	2319	1995
45°	2606	2346	1939	1663	1570	2013
55°	1981	1679	1260	1028	954	1771
65°	1338	1024	675	543	531	1326
75°	713	442	310	283	279	755
85°	167	85	74	74	74	191
90°	1	16	44	41	43	13
95°	66	78	80	80	78	73
105°	270	274	277	279	279	285
115°	503	510	508	507	503	498
125°	732	743	740	736	734	654
135°	947	961	963	962	958	732
145°	1149	1158	1166	1167	1162	718
155°	1314	1318	1322	1328	1324	605
165°	1430	1428	1428	1438	1431	403
175°	1488	1484	1482	1490	1483	141
180°	1490	1490	1490	1490	1490	

TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLFL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	4285.1	4285.1	4285.1	4285.1	4285.1
2.5°	4304.4	4285.1	4242.3	4281.4	4273.6
5°	4285.1	4265.8	4215.1	4250.1	4238.6
7.5°	4250.1	4227.0	4172.7	4188.0	4168.6
10°	4203.6	4176.4	4099.1	4087.1	4064.1
12.5°	4145.6	4110.6	4005.7	3982.6	3939.8
15°	4075.6	4032.9	3901.2	3827.6	3788.8
17.5°	3994.2	3932.1	3769.1	3683.9	3621.8
20°	3901.2	3823.4	3629.6	3532.9	3447.3
22.5°	3800.4	3711.1	3486.1	3354.4	3296.4
25°	3699.6	3575.3	3319.4	3160.6	3102.2
27.5°	3579.5	3447.3	3164.3	2982.0	2892.8
30°	3451.5	3303.8	2993.6	2796.1	2691.1
32.5°	3327.3	3148.7	2831.0	2598.2	2501.1
35°	3187.8	2989.8	2648.8	2404.4	2318.8
37.5°	3052.0	2838.5	2478.0	2210.2	2113.6
40°	2908.4	2676.0	2299.5	2024.2	1923.4
42.5°	2761.1	2513.0	2121.4	1834.2	1737.5
45°	2606.0	2346.0	1939.1	1663.4	1570.5
47.5°	2458.7	2183.5	1764.6	1488.9	1403.8
50°	2295.8	2020.5	1593.9	1326.1	1245.0
52.5°	2136.6	1845.7	1431.0	1175.1	1101.4
55°	1981.4	1679.0	1260.2	1027.7	954.1
57.5°	1822.7	1512.4	1109.2	892.0	829.8
60°	1659.7	1349.5	950.0	752.5	690.4
62.5°	1500.9	1190.7	814.3	628.3	597.4
65°	1337.9	1023.6	674.8	543.1	531.1
67.5°	1182.9	868.6	543.1	476.8	465.3
70°	1019.9	717.6	449.7	411.0	395.4
72.5°	864.8	577.7	376.1	345.2	337.3
75°	713.4	441.9	310.2	283.0	279.4
77.5°	562.4	314.0	244.4	228.8	220.9
80°	422.5	225.1	186.0	170.8	170.8
82.5°	294.5	151.4	128.0	120.2	120.2
85°	166.6	85.2	73.6	73.6	73.6
87.5°	62.1	30.8	30.8	27.1	27.1
90°	1.3	16.2	44.0	41.4	42.7
92.5°	27.9	37.7	39.1	40.4	40.4
95°	65.6	78.2	80.4	80.4	78.2
97.5°	109.1	120.8	125.8	125.8	125.8
100°	159.5	169.8	173.4	173.4	172.1
102.5°	212.5	220.2	225.1	226.5	225.1
105°	270.5	274.1	276.8	279.0	279.0
107.5°	328.0	333.4	333.4	334.3	328.0
110°	383.7	391.0	391.0	391.0	387.3

TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	443.9	451.6	450.3	446.7	443.9
115°	503.2	510.5	508.2	506.9	503.2
117.5°	562.1	572.0	565.7	562.1	558.6
120°	621.4	631.3	621.4	621.4	617.4
122.5°	675.3	688.0	681.6	678.1	675.3
125°	732.0	743.2	739.6	735.6	734.2
127.5°	787.2	801.2	796.3	790.8	787.2
130°	839.0	855.1	852.8	850.2	845.2
132.5°	896.9	909.5	910.4	904.1	900.5
135°	946.8	960.6	963.4	962.1	958.5
137.5°	1002.5	1013.7	1016.0	1015.0	1009.7
140°	1051.4	1062.7	1068.9	1068.9	1064.0
142.5°	1101.7	1113.0	1116.6	1117.9	1113.0
145°	1149.4	1158.4	1165.5	1167.0	1162.0
147.5°	1192.1	1203.3	1208.7	1211.0	1206.0
150°	1236.1	1243.8	1248.7	1252.7	1248.7
152.5°	1275.3	1282.9	1289.1	1294.1	1289.1
155°	1314.3	1317.9	1321.9	1328.2	1324.2
157.5°	1348.0	1350.7	1352.9	1362.0	1355.7
160°	1378.1	1380.8	1382.1	1389.8	1384.4
162.5°	1406.0	1406.0	1407.3	1415.9	1409.6
165°	1429.8	1428.4	1428.4	1437.5	1431.2
167.5°	1451.3	1447.3	1447.3	1456.3	1450.0
170°	1467.5	1464.0	1462.6	1471.6	1464.0
172.5°	1478.8	1475.2	1473.9	1482.8	1475.2
175°	1487.8	1484.1	1481.5	1490.4	1482.8
177.5°	1492.7	1489.1	1486.4	1494.0	1486.4
180°	1490.4	1490.4	1490.4	1490.4	1490.4

TEST NUMBER: P903402

CATALOG NUMBER: DFN2DIP-PN4F0-110D050US830-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.64	13.65	13.44	14.46	15.45	8.61	9.61	9.40	10.42	11.41
	3H	14.34	15.23	15.14	16.05	17.08	9.81	10.71	10.62	11.53	12.55
	4H	14.96	15.80	15.78	16.63	17.66	10.27	11.11	11.09	11.94	12.98
	6H	15.39	16.17	16.23	17.00	18.05	10.60	11.38	11.44	12.22	13.26
	8H	15.52	16.26	16.37	17.12	18.16	10.70	11.44	11.54	12.29	13.34
	12H	15.59	16.29	16.44	17.14	18.22	10.75	11.45	11.60	12.30	13.37
4H	2H	12.68	13.53	13.51	14.36	15.39	9.23	10.07	10.06	10.90	11.93
	3H	14.53	15.23	15.37	16.09	17.14	10.59	11.29	11.43	12.16	13.21
	4H	15.23	15.87	16.09	16.73	17.81	11.15	11.79	12.00	12.65	13.72
	6H	15.76	16.31	16.63	17.19	18.27	11.58	12.13	12.45	13.01	14.09
	8H	15.94	16.45	16.81	17.33	18.43	11.71	12.22	12.58	13.10	14.20
	12H	16.04	16.51	16.94	17.40	18.50	11.78	12.25	12.68	13.15	14.24
8H	4H	15.21	15.73	16.08	16.60	17.70	11.44	11.96	12.32	12.84	13.93
	6H	15.79	16.21	16.69	17.13	18.23	11.97	12.39	12.87	13.31	14.41
	8H	16.01	16.38	16.92	17.30	18.41	12.16	12.54	13.07	13.45	14.56
	12H	16.16	16.49	17.07	17.39	18.56	12.29	12.62	13.20	13.53	14.69
12H	4H	15.17	15.63	16.06	16.53	17.63	11.46	11.92	12.35	12.82	13.92
	6H	15.76	16.14	16.67	17.06	18.17	12.02	12.40	12.93	13.31	14.42
	8H	15.99	16.33	16.91	17.23	18.40	12.24	12.57	13.15	13.48	14.64

END OF REPORT