

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P914248

Luminaire Tested: DFN2DIP-PN4F0-090D070US927-FLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P914248
REPORT IS A COMBINATION OF REPORTS P899673 AND P896497
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-PN4F0-090D070US927-FLLFLL
Description: 4 foot, Pentagon Define Geo, with Direct Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 11965.9 lumens
Efficiency: N/A
Efficacy: 84.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.74' x L: 3.94' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 140.9
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9963
Total Harmonic Distortion (THDi): 0.065
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	109	109	109	109		102	102	102	102		88	88	88		76	76	76		64	64	64
1	100	95	91	88		93	89	86	83		78	75	73		67	65	63		57	56	54
2	91	83	77	72		85	78	73	68		68	64	60		59	56	53		50	48	46
3	83	73	66	60		77	69	62	57		60	55	51		52	48	45		44	42	39
4	76	65	57	51		71	61	54	48		53	48	43		46	42	38		40	36	34
5	70	58	50	44		65	54	47	41		48	42	37		42	37	33		36	32	29
6	64	52	44	38		60	49	41	36		43	37	33		38	33	29		33	29	26
7	59	47	39	33		55	44	37	32		39	33	29		34	29	26		30	26	23
8	55	43	35	29		51	40	33	28		36	30	26		31	27	23		27	23	21
9	51	39	31	26		48	37	30	25		33	27	23		29	24	21		25	21	19
10	48	36	29	24		45	34	27	23		30	25	21		27	22	19		23	20	17

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2025	2025	2025
5°	2028	1997	2011
10°	2012	1970	1984
15°	1982	1938	1942
20°	1942	1893	1898
25°	1903	1840	1848
30°	1853	1790	1785
35°	1805	1731	1717
40°	1747	1672	1653
45°	1689	1612	1588
50°	1626	1550	1512
55°	1560	1477	1442
60°	1485	1391	1362
65°	1403	1302	1268
70°	1299	1194	1167
75°	1154	1065	1074
80°	981	899	896
85°	709	614	599

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1689 cd/sqm

TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	261.1	2.2
10°-20°	734.7	6.1
20°-30°	1079.6	9.0
30°-40°	1253.9	10.5
40°-50°	1252.4	10.5
50°-60°	1092.1	9.1
60°-70°	807.3	6.7
70°-80°	456.7	3.8
80°-90°	125.5	1.0
90°-100°	108.5	0.9
100°-110°	344.8	2.9
110°-120°	590.1	4.9
120°-130°	776.1	6.5
130°-140°	871.1	7.3
140°-150°	854.2	7.1
150°-160°	716.6	6.0
160°-170°	475.2	4.0
170°-180°	166.1	1.4
0°-30°	2075.4	17.3
0°-40°	3329.4	27.8
0°-60°	5673.8	47.4
0°-90°	7063.3	59.0
90°-120°	1043.4	8.7
90°-150°	3544.8	29.6
90°-180°	4903.0	41.0
0°-180°	11965.9	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2774	2774	2774	2774	2774	
5°	2774	2764	2734	2756	2750	263
15°	2641	2625	2590	2601	2588	744
25°	2390	2369	2324	2329	2324	1100
35°	2062	2036	1993	1977	1963	1288
45°	1678	1659	1619	1590	1579	1295
55°	1270	1254	1222	1190	1176	1135
65°	856	840	814	790	776	847
75°	448	443	429	414	419	478
85°	109	107	104	96	93	122
90°	2	19	52	49	50	12
95°	77	92	95	95	92	86
105°	318	322	326	328	328	336
115°	592	601	598	596	592	586
125°	861	874	870	866	864	770
135°	1114	1130	1134	1132	1128	861
145°	1352	1363	1372	1373	1367	845
155°	1546	1551	1556	1563	1558	712
165°	1682	1681	1681	1691	1684	475
175°	1751	1746	1743	1754	1745	166
180°	1754	1754	1754	1754	1754	

TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2774.1	2774.1	2774.1	2774.1	2774.1
2.5°	2790.3	2777.0	2747.6	2774.1	2769.1
5°	2774.1	2763.7	2734.3	2755.5	2750.4
7.5°	2755.5	2739.7	2710.2	2731.8	2726.4
10°	2726.4	2707.7	2675.7	2696.9	2689.0
12.5°	2686.1	2670.3	2638.4	2651.6	2646.3
15°	2640.9	2625.1	2590.2	2601.0	2587.7
17.5°	2584.8	2569.0	2534.2	2547.5	2534.2
20°	2523.4	2507.6	2470.2	2478.1	2467.6
22.5°	2462.3	2438.3	2403.4	2403.4	2398.0
25°	2390.1	2368.9	2323.6	2328.7	2323.6
27.5°	2310.0	2291.3	2256.8	2248.9	2235.6
30°	2230.2	2208.7	2168.8	2160.8	2150.1
32.5°	2144.8	2128.9	2086.1	2070.0	2059.3
35°	2062.1	2035.5	1992.7	1976.7	1963.3
37.5°	1968.7	1944.6	1901.9	1883.3	1869.9
40°	1872.7	1851.2	1808.5	1784.7	1774.0
42.5°	1779.3	1757.8	1715.4	1688.5	1672.7
45°	1678.0	1659.4	1619.1	1590.0	1579.3
47.5°	1579.3	1560.6	1517.8	1488.4	1472.6
50°	1475.1	1461.8	1424.4	1387.1	1373.8
52.5°	1373.8	1355.1	1320.6	1291.2	1272.5
55°	1269.9	1253.8	1221.8	1189.9	1176.5
57.5°	1165.8	1152.5	1117.7	1085.7	1074.9
60°	1061.6	1051.1	1013.8	984.4	976.4
62.5°	960.3	941.6	915.0	888.4	877.7
65°	856.4	840.3	813.6	789.6	776.3
67.5°	749.7	736.2	712.3	693.7	682.9
70°	650.9	640.2	616.2	597.5	587.0
72.5°	549.6	538.8	525.5	506.9	499.0
75°	448.1	442.9	429.4	413.5	418.9
77.5°	357.4	346.7	341.4	333.4	325.5
80°	266.9	264.0	258.6	250.7	245.4
82.5°	181.4	181.4	178.9	168.1	168.1
85°	109.2	106.7	104.2	95.9	93.4
87.5°	48.1	42.7	37.4	29.5	26.6
90°	1.6	19.0	51.8	48.6	50.2
92.5°	32.8	44.4	46.0	47.6	47.6
95°	77.2	92.0	94.7	94.7	92.0
97.5°	128.5	142.2	148.1	148.1	148.1
100°	187.7	199.9	204.1	204.1	202.5
102.5°	250.1	259.0	264.9	266.5	264.9
105°	318.3	322.5	325.7	328.4	328.4
107.5°	386.0	392.3	392.3	393.4	386.0
110°	451.5	460.0	460.0	460.0	455.7

TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	522.4	531.4	529.8	525.5	522.4
115°	592.2	600.6	598.0	596.4	592.2
117.5°	661.4	673.0	665.7	661.4	657.2
120°	731.2	742.8	731.2	731.2	726.4
122.5°	794.6	809.5	802.1	797.8	794.6
125°	861.3	874.5	870.3	865.5	864.0
127.5°	926.3	942.7	936.9	930.6	926.3
130°	987.1	1006.1	1003.5	1000.4	994.5
132.5°	1055.3	1070.2	1071.2	1063.8	1059.5
135°	1114.0	1130.4	1133.6	1131.9	1127.7
137.5°	1179.6	1192.8	1195.4	1194.4	1188.0
140°	1237.2	1250.5	1257.8	1257.8	1252.0
142.5°	1296.4	1309.6	1313.8	1315.4	1309.6
145°	1352.5	1363.0	1371.5	1373.1	1367.3
147.5°	1402.7	1415.9	1422.3	1424.9	1419.1
150°	1454.5	1463.5	1469.3	1474.1	1469.3
152.5°	1500.5	1509.5	1516.9	1522.7	1516.9
155°	1546.5	1550.7	1555.5	1562.9	1558.1
157.5°	1586.2	1589.4	1592.0	1602.6	1595.1
160°	1621.6	1624.8	1626.3	1635.3	1629.0
162.5°	1654.4	1654.4	1656.0	1666.0	1658.6
165°	1682.4	1680.8	1680.8	1691.4	1683.9
167.5°	1707.8	1703.0	1703.0	1713.6	1706.2
170°	1726.8	1722.6	1721.0	1731.5	1722.6
172.5°	1740.0	1735.7	1734.2	1744.8	1735.7
175°	1750.6	1746.4	1743.2	1753.7	1744.8
177.5°	1756.4	1752.1	1749.0	1758.0	1749.0
180°	1753.7	1753.7	1753.7	1753.7	1753.7

TEST NUMBER: P914248

CATALOG NUMBER: DFN2DIP-PN4F0-090D070US927-FLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	10.52	11.47	11.40	12.37	13.50	10.08	11.03	10.96	11.93	13.06
	3H	12.19	13.04	13.08	13.95	15.11	11.71	12.56	12.60	13.47	14.63
	4H	12.79	13.59	13.69	14.50	15.67	12.30	13.10	13.20	14.02	15.19
	6H	13.19	13.94	14.11	14.85	16.04	12.70	13.44	13.62	14.36	15.55
	8H	13.30	14.01	14.22	14.94	16.13	12.81	13.52	13.73	14.45	15.64
	12H	13.35	14.03	14.28	14.96	16.17	12.85	13.53	13.78	14.46	15.67
4H	2H	11.00	11.80	11.90	12.71	13.88	10.64	11.45	11.55	12.36	13.53
	3H	12.87	13.54	13.79	14.49	15.67	12.47	13.14	13.39	14.08	15.27
	4H	13.59	14.21	14.52	15.14	16.36	13.17	13.79	14.10	14.73	15.94
	6H	14.12	14.64	15.06	15.61	16.82	13.69	14.22	14.63	15.18	16.39
	8H	14.27	14.76	15.21	15.72	16.95	13.84	14.33	14.79	15.29	16.52
	12H	14.35	14.79	15.31	15.77	17.00	13.91	14.35	14.87	15.33	16.56
8H	4H	13.80	14.29	14.74	15.25	16.47	13.43	13.92	14.37	14.88	16.10
	6H	14.43	14.84	15.41	15.84	17.07	14.06	14.47	15.03	15.47	16.69
	8H	14.66	15.02	15.64	16.01	17.25	14.27	14.64	15.25	15.62	16.86
	12H	14.80	15.11	15.78	16.09	17.38	14.39	14.71	15.38	15.69	16.98
12H	4H	13.79	14.23	14.75	15.21	16.44	13.42	13.87	14.39	14.84	16.07
	6H	14.47	14.83	15.45	15.81	17.06	14.10	14.46	15.08	15.45	16.69
	8H	14.71	15.03	15.70	16.01	17.30	14.34	14.66	15.33	15.64	16.93

END OF REPORT