

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P925418

Luminaire Tested: DFN2DIP-SQ2F0-080D040US950-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P925418
REPORT IS A COMBINATION OF REPORTS P899794 AND P896659
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-SQ2F0-080D040US950-RLLFLL
Description: 2 foot, Square Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9864.4 lumens
Efficiency: N/A
Efficacy: 91.0 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.21' x L: 2.21' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 108.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9957
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	111	111	111	111		104	104	104	104		92	92	92		81	81	81		71	71	71
1	102	98	94	91		96	92	89	86		82	79	77		72	70	69		63	62	61
2	93	86	80	75		88	81	76	72		72	68	65		64	61	58		57	54	52
3	86	76	69	63		80	72	66	61		65	59	55		57	53	50		51	48	45
4	79	68	60	54		74	65	58	52		58	52	48		52	47	44		46	42	40
5	73	61	53	47		68	58	51	45		52	46	42		47	42	38		42	38	35
6	67	55	47	41		63	52	45	40		47	41	37		42	38	34		38	34	31
7	62	50	42	37		59	48	40	35		43	37	33		39	34	30		35	31	28
8	58	46	38	33		55	44	37	32		40	34	29		36	31	27		32	28	25
9	54	42	35	29		51	40	33	29		36	31	27		33	28	25		30	26	23
10	51	39	31	27		48	37	30	26		34	28	24		31	26	23		28	24	21

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	6936	6936	6936
5°	6935	6811	6860
10°	6854	6662	6627
15°	6748	6427	6273
20°	6611	6110	5842
25°	6471	5757	5426
30°	6287	5396	4902
35°	6106	5010	4441
40°	5921	4611	3915
45°	5707	4172	3440
50°	5485	3730	2975
55°	5253	3259	2529
60°	4983	2769	2073
65°	4672	2273	1854
70°	4294	1810	1665
75°	3818	1567	1495
80°	3135	1272	1266
85°	2041	790	902

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5707 cd/sqm

TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLFL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	295.6	3.0
10°-20°	811.5	8.2
20°-30°	1139.4	11.6
30°-40°	1242.0	12.6
40°-50°	1141.5	11.6
50°-60°	896.5	9.1
60°-70°	583.5	5.9
70°-80°	300.4	3.0
80°-90°	80.1	0.8
90°-100°	74.7	0.8
100°-110°	237.3	2.4
110°-120°	406.1	4.1
120°-130°	534.0	5.4
130°-140°	599.4	6.1
140°-150°	587.8	6.0
150°-160°	493.1	5.0
160°-170°	327.0	3.3
170°-180°	114.3	1.2
0°-30°	2246.6	22.8
0°-40°	3488.6	35.4
0°-60°	5526.6	56.0
0°-90°	6490.6	65.8
90°-120°	718.0	7.3
90°-150°	2439.3	24.7
90°-180°	3374.0	34.2
0°-180°	9864.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3154	3154	3154	3154	3154	
5°	3154	3140	3103	3128	3120	299
15°	3000	2969	2872	2818	2789	845
25°	2723	2632	2444	2327	2284	1252
35°	2347	2201	1950	1770	1707	1469
45°	1918	1727	1427	1224	1156	1481
55°	1459	1236	928	756	702	1303
65°	985	754	497	400	391	976
75°	525	325	228	208	206	555
85°	123	63	54	54	54	141
90°	1	13	36	34	34	10
95°	53	63	65	65	63	59
105°	219	222	224	226	226	231
115°	408	413	412	410	408	403
125°	593	602	599	596	594	530
135°	767	778	780	779	776	593
145°	931	938	944	945	941	582
155°	1064	1067	1070	1076	1072	490
165°	1158	1157	1157	1164	1159	327
175°	1205	1202	1200	1207	1201	114
180°	1207	1207	1207	1207	1207	

TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLFL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3154.3	3154.3	3154.3	3154.3	3154.3
2.5°	3168.5	3154.3	3122.8	3151.5	3145.8
5°	3154.3	3140.1	3102.8	3128.5	3120.1
7.5°	3128.5	3111.6	3071.6	3082.9	3068.5
10°	3094.3	3074.4	3017.4	3008.6	2991.6
12.5°	3051.7	3025.9	2948.6	2931.6	2900.2
15°	3000.1	2968.7	2871.7	2817.5	2789.0
17.5°	2940.1	2894.4	2774.5	2711.8	2666.0
20°	2871.7	2814.5	2671.9	2600.7	2537.6
22.5°	2797.5	2731.8	2566.2	2469.2	2426.5
25°	2723.3	2631.9	2443.5	2326.6	2283.6
27.5°	2634.9	2537.6	2329.3	2195.2	2129.4
30°	2540.7	2431.9	2203.6	2058.3	1981.0
32.5°	2449.2	2317.8	2084.0	1912.6	1841.1
35°	2346.6	2200.9	1949.8	1770.0	1706.9
37.5°	2246.6	2089.5	1824.1	1627.0	1555.8
40°	2141.0	1969.8	1692.7	1490.1	1415.8
42.5°	2032.5	1849.9	1561.5	1350.2	1278.9
45°	1918.3	1726.9	1427.4	1224.5	1156.1
47.5°	1809.9	1607.3	1299.0	1096.1	1033.4
50°	1689.9	1487.4	1173.3	976.1	916.4
52.5°	1572.8	1358.6	1053.3	865.0	810.8
55°	1458.6	1236.0	927.7	756.5	702.3
57.5°	1341.7	1113.3	816.5	656.6	610.8
60°	1221.7	993.4	699.3	553.9	508.2
62.5°	1104.8	876.4	599.4	462.5	439.8
65°	984.9	753.5	496.7	399.8	390.9
67.5°	870.7	639.4	399.8	351.0	342.6
70°	750.8	528.2	331.0	302.5	291.1
72.5°	636.6	425.2	276.9	254.1	248.3
75°	525.2	325.3	228.4	208.4	205.7
77.5°	414.0	231.1	179.9	168.4	162.7
80°	311.0	165.7	136.9	125.6	125.6
82.5°	216.8	111.4	94.2	88.4	88.4
85°	122.7	62.7	54.2	54.2	54.2
87.5°	45.7	22.7	22.7	20.0	20.0
90°	1.0	13.1	35.7	33.5	34.5
92.5°	22.5	30.5	31.7	32.7	32.7
95°	53.1	63.3	65.2	65.2	63.3
97.5°	88.4	97.9	101.9	101.9	101.9
100°	129.2	137.6	140.4	140.4	139.4
102.5°	172.1	178.3	182.3	183.4	182.3
105°	219.0	221.9	224.1	225.9	225.9
107.5°	265.6	270.0	270.0	270.6	265.6
110°	310.7	316.5	316.5	316.5	313.7

TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	359.5	365.7	364.5	361.7	359.5
115°	407.5	413.4	411.5	410.4	407.5
117.5°	455.2	463.2	458.1	455.2	452.3
120°	503.2	511.2	503.2	503.2	499.9
122.5°	546.8	557.0	552.0	549.0	546.8
125°	592.7	601.8	598.9	595.6	594.5
127.5°	637.5	648.7	644.7	640.3	637.5
130°	679.2	692.4	690.6	688.4	684.4
132.5°	726.2	736.4	737.2	732.0	729.1
135°	766.6	777.9	780.1	778.9	776.1
137.5°	811.8	820.8	822.6	821.9	817.6
140°	851.3	860.5	865.6	865.6	861.6
142.5°	892.2	901.2	904.1	905.3	901.2
145°	930.7	938.0	943.8	944.9	940.9
147.5°	965.3	974.3	978.7	980.5	976.5
150°	1000.9	1007.1	1011.1	1014.4	1011.1
152.5°	1032.6	1038.7	1043.9	1047.9	1043.9
155°	1064.2	1067.1	1070.4	1075.5	1072.2
157.5°	1091.6	1093.7	1095.5	1102.8	1097.7
160°	1115.9	1118.1	1119.1	1125.3	1121.0
162.5°	1138.4	1138.4	1139.6	1146.4	1141.4
165°	1157.8	1156.6	1156.6	1163.9	1158.8
167.5°	1175.2	1171.9	1171.9	1179.2	1174.1
170°	1188.3	1185.3	1184.3	1191.5	1185.3
172.5°	1197.4	1194.5	1193.4	1200.7	1194.5
175°	1204.7	1201.8	1199.6	1206.8	1200.7
177.5°	1208.7	1205.8	1203.6	1209.8	1203.6
180°	1206.8	1206.8	1206.8	1206.8	1206.8

TEST NUMBER: P925418

CATALOG NUMBER: DFN2DIP-SQ2F0-080D040US950-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.12	16.10	15.94	16.93	17.96	11.08	12.06	11.90	12.89	13.92
	3H	16.79	17.67	17.62	18.51	19.57	12.26	13.14	13.09	13.98	15.04
	4H	17.39	18.22	18.24	19.07	20.14	12.71	13.53	13.55	14.38	15.45
	6H	17.81	18.57	18.66	19.42	20.51	13.02	13.78	13.88	14.64	15.72
	8H	17.93	18.65	18.79	19.53	20.61	13.11	13.83	13.97	14.70	15.79
	12H	17.99	18.68	18.86	19.54	20.65	13.15	13.83	14.02	14.70	15.81
4H	2H	15.15	15.98	16.00	16.83	17.90	11.68	12.51	12.54	13.36	14.43
	3H	16.97	17.66	17.83	18.54	19.62	13.03	13.71	13.89	14.60	15.68
	4H	17.66	18.28	18.53	19.16	20.27	13.57	14.19	14.44	15.07	16.18
	6H	18.16	18.70	19.05	19.60	20.72	13.97	14.51	14.86	15.41	16.53
	8H	18.33	18.83	19.22	19.73	20.85	14.09	14.60	14.99	15.49	16.62
	12H	18.42	18.87	19.33	19.79	20.92	14.16	14.61	15.07	15.52	16.66
8H	4H	17.63	18.13	18.52	19.03	20.16	13.84	14.35	14.74	15.24	16.37
	6H	18.18	18.59	19.10	19.53	20.66	14.34	14.76	15.26	15.70	16.82
	8H	18.38	18.75	19.31	19.68	20.83	14.52	14.89	15.45	15.82	16.96
	12H	18.51	18.84	19.45	19.76	20.96	14.63	14.95	15.56	15.88	17.08
12H	4H	17.59	18.04	18.50	18.96	20.09	13.85	14.30	14.76	15.22	16.35
	6H	18.15	18.52	19.08	19.45	20.60	14.39	14.76	15.32	15.69	16.83
	8H	18.37	18.69	19.30	19.61	20.81	14.59	14.91	15.52	15.84	17.03

END OF REPORT