

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P911837

Luminaire Tested: DFN2DIP-SQ3F0-050D050US850-FLLONL

Issue Date: 11/21/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P911837  
REPORT IS A COMBINATION OF REPORTS P901401 AND P898289  
Test Lab: INNOVATION CENTER  
Issue Date: 11/21/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: DFN2DIP-SQ3F0-050D050US850-FLLONL  
Description: 3 foot, Square Define Geo, with Direct Frosted Lens, Indirect Open No Lens  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 10979.1 lumens  
Efficiency: N/A  
Efficacy: 138.8 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29  
Luminous Opening: Rectangular w/ Sides (W: 3.06' x L: 3.06' x H: 0.1')  
CIE Type: General Diffuse

Input Watts (W): 79.1  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: 0.9789  
Total Harmonic Distortion (THDi): 0.074  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLLONL

### Luminous Intensity Polar Plot



TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLLONL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |    |
|-----|-----|-----|-----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| RF  | 20  |     |     |     | 20 |    |    |    | 20 |    |    |    | 20 |    |    |    | 20 |
| RC  | 80  |     |     |     | 70 |    |    |    | 50 |    |    |    | 30 |    |    |    | 10 |
| RW  | 70  | 50  | 30  | 10  | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |     |     |     |     |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 0   | 107 | 107 | 107 | 107 | 99 | 99 | 99 | 99 | 83 | 83 | 83 | 69 | 69 | 69 | 56 | 56 | 56 |
| 1   | 98  | 93  | 90  | 86  | 90 | 86 | 83 | 80 | 73 | 71 | 68 | 61 | 59 | 58 | 50 | 48 | 47 |
| 2   | 89  | 82  | 75  | 70  | 82 | 76 | 70 | 66 | 64 | 60 | 57 | 53 | 51 | 48 | 44 | 42 | 40 |
| 3   | 81  | 72  | 64  | 59  | 75 | 66 | 60 | 55 | 56 | 52 | 48 | 47 | 44 | 41 | 39 | 36 | 34 |
| 4   | 74  | 64  | 56  | 50  | 68 | 59 | 52 | 47 | 50 | 45 | 41 | 42 | 38 | 35 | 35 | 32 | 29 |
| 5   | 68  | 57  | 48  | 42  | 63 | 53 | 45 | 40 | 45 | 39 | 35 | 38 | 34 | 30 | 31 | 28 | 26 |
| 6   | 63  | 51  | 43  | 37  | 58 | 47 | 40 | 35 | 40 | 35 | 31 | 34 | 30 | 27 | 28 | 25 | 23 |
| 7   | 58  | 46  | 38  | 32  | 53 | 43 | 36 | 30 | 37 | 31 | 27 | 31 | 27 | 23 | 26 | 23 | 20 |
| 8   | 54  | 42  | 34  | 29  | 50 | 39 | 32 | 27 | 33 | 28 | 24 | 28 | 24 | 21 | 24 | 20 | 18 |
| 9   | 50  | 38  | 30  | 25  | 46 | 35 | 29 | 24 | 31 | 25 | 21 | 26 | 22 | 19 | 22 | 19 | 16 |
| 10  | 47  | 35  | 28  | 23  | 43 | 33 | 26 | 22 | 28 | 23 | 19 | 24 | 20 | 17 | 20 | 17 | 15 |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0°   | 45°  | 90°  |
|-----|------|------|------|
| 0°  | 2472 | 2472 | 2472 |
| 5°  | 2475 | 2436 | 2453 |
| 10° | 2453 | 2402 | 2419 |
| 15° | 2415 | 2360 | 2367 |
| 20° | 2365 | 2304 | 2313 |
| 25° | 2315 | 2237 | 2250 |
| 30° | 2252 | 2174 | 2172 |
| 35° | 2193 | 2100 | 2088 |
| 40° | 2121 | 2025 | 2009 |
| 45° | 2048 | 1951 | 1927 |
| 50° | 1969 | 1872 | 1833 |
| 55° | 1885 | 1781 | 1746 |
| 60° | 1791 | 1673 | 1647 |
| 65° | 1688 | 1561 | 1530 |
| 70° | 1557 | 1425 | 1404 |
| 75° | 1375 | 1261 | 1286 |
| 80° | 1156 | 1052 | 1063 |
| 85° | 813  | 697  | 695  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2048 cd/sqm

TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLLONL

**ZONAL LUMENS:**

| Zone      | Lumens  | % Fixture |
|-----------|---------|-----------|
| 0°-10°    | 203.1   | 1.8       |
| 10°-20°   | 571.4   | 5.2       |
| 20°-30°   | 839.7   | 7.6       |
| 30°-40°   | 975.2   | 8.9       |
| 40°-50°   | 974.0   | 8.9       |
| 50°-60°   | 849.3   | 7.7       |
| 60°-70°   | 627.9   | 5.7       |
| 70°-80°   | 355.2   | 3.2       |
| 80°-90°   | 97.1    | 0.9       |
| 90°-100°  | 61.7    | 0.6       |
| 100°-110° | 230.0   | 2.1       |
| 110°-120° | 610.1   | 5.6       |
| 120°-130° | 1011.9  | 9.2       |
| 130°-140° | 1074.8  | 9.8       |
| 140°-150° | 999.0   | 9.1       |
| 150°-160° | 803.1   | 7.3       |
| 160°-170° | 517.5   | 4.7       |
| 170°-180° | 178.1   | 1.6       |
| 0°-30°    | 1614.1  | 14.7      |
| 0°-40°    | 2589.4  | 23.6      |
| 0°-60°    | 4412.7  | 40.2      |
| 0°-90°    | 5492.9  | 50.0      |
| 90°-120°  | 901.9   | 8.2       |
| 90°-150°  | 3987.5  | 36.3      |
| 90°-180°  | 5486.0  | 50.0      |
| 0°-180°   | 10979.1 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | 22.5° | 45°  | 67.5° | 90°  | Flux |
|------|------|-------|------|-------|------|------|
| 0°   | 2158 | 2158  | 2158 | 2158  | 2158 |      |
| 5°   | 2158 | 2150  | 2126 | 2143  | 2139 | 205  |
| 15°  | 2054 | 2042  | 2014 | 2023  | 2012 | 578  |
| 25°  | 1859 | 1842  | 1807 | 1811  | 1807 | 855  |
| 35°  | 1604 | 1583  | 1550 | 1537  | 1527 | 1001 |
| 45°  | 1305 | 1290  | 1259 | 1237  | 1228 | 1007 |
| 55°  | 988  | 975   | 950  | 925   | 915  | 883  |
| 65°  | 666  | 654   | 633  | 614   | 604  | 659  |
| 75°  | 348  | 344   | 334  | 322   | 326  | 372  |
| 85°  | 85   | 83    | 81   | 75    | 73   | 95   |
| 90°  | 1    | 16    | 27   | 34    | 36   | 10   |
| 95°  | 88   | 43    | 53   | 60    | 58   | 104  |
| 105° | 412  | 452   | 83   | 98    | 103  | 440  |
| 115° | 779  | 802   | 836  | 209   | 111  | 767  |
| 125° | 1101 | 1118  | 1144 | 1154  | 1158 | 982  |
| 135° | 1362 | 1384  | 1396 | 1410  | 1407 | 1052 |
| 145° | 1580 | 1579  | 1602 | 1611  | 1605 | 988  |
| 155° | 1740 | 1728  | 1744 | 1752  | 1742 | 802  |
| 165° | 1833 | 1825  | 1829 | 1839  | 1829 | 518  |
| 175° | 1875 | 1866  | 1869 | 1878  | 1865 | 178  |
| 180° | 1871 | 1871  | 1871 | 1871  | 1871 |      |

TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLLONL

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 0°     | 2157.6 | 2157.6 | 2157.6 | 2157.6 | 2157.6 |
| 2.5°   | 2170.1 | 2159.8 | 2136.9 | 2157.6 | 2153.7 |
| 5°     | 2157.6 | 2149.5 | 2126.5 | 2143.0 | 2139.2 |
| 7.5°   | 2143.0 | 2130.7 | 2107.9 | 2124.6 | 2120.4 |
| 10°    | 2120.4 | 2105.9 | 2081.0 | 2097.5 | 2091.4 |
| 12.5°  | 2089.1 | 2076.8 | 2052.0 | 2062.3 | 2058.1 |
| 15°    | 2053.9 | 2041.6 | 2014.5 | 2022.9 | 2012.5 |
| 17.5°  | 2010.3 | 1998.0 | 1970.9 | 1981.2 | 1970.9 |
| 20°    | 1962.6 | 1950.3 | 1921.2 | 1927.3 | 1919.2 |
| 22.5°  | 1915.0 | 1896.3 | 1869.2 | 1869.2 | 1865.0 |
| 25°    | 1858.9 | 1842.4 | 1807.1 | 1811.1 | 1807.1 |
| 27.5°  | 1796.6 | 1782.1 | 1755.2 | 1749.0 | 1738.7 |
| 30°    | 1734.5 | 1717.8 | 1686.8 | 1680.6 | 1672.3 |
| 32.5°  | 1668.0 | 1655.7 | 1622.5 | 1609.9 | 1601.6 |
| 35°    | 1603.7 | 1583.1 | 1549.8 | 1537.3 | 1527.0 |
| 37.5°  | 1531.1 | 1512.5 | 1479.2 | 1464.7 | 1454.3 |
| 40°    | 1456.6 | 1439.8 | 1406.5 | 1388.0 | 1379.7 |
| 42.5°  | 1383.9 | 1367.2 | 1334.1 | 1313.2 | 1300.9 |
| 45°    | 1305.1 | 1290.5 | 1259.3 | 1236.6 | 1228.2 |
| 47.5°  | 1228.2 | 1213.7 | 1180.5 | 1157.6 | 1145.3 |
| 50°    | 1147.3 | 1136.9 | 1107.9 | 1078.8 | 1068.4 |
| 52.5°  | 1068.4 | 1053.9 | 1027.0 | 1004.2 | 989.7  |
| 55°    | 987.7  | 975.1  | 950.2  | 925.3  | 915.0  |
| 57.5°  | 906.6  | 896.3  | 869.2  | 844.4  | 836.0  |
| 60°    | 825.7  | 817.6  | 788.5  | 765.5  | 759.4  |
| 62.5°  | 746.9  | 732.4  | 711.6  | 690.9  | 682.6  |
| 65°    | 666.1  | 653.5  | 632.8  | 614.2  | 603.7  |
| 67.5°  | 583.1  | 572.6  | 554.1  | 539.5  | 531.1  |
| 70°    | 506.3  | 497.9  | 479.2  | 464.7  | 456.6  |
| 72.5°  | 427.5  | 419.1  | 408.8  | 394.2  | 388.0  |
| 75°    | 348.4  | 344.5  | 333.9  | 321.6  | 325.8  |
| 77.5°  | 278.0  | 269.6  | 265.5  | 259.3  | 253.2  |
| 80°    | 207.6  | 205.4  | 201.2  | 195.1  | 190.9  |
| 82.5°  | 141.1  | 141.1  | 139.1  | 130.8  | 130.8  |
| 85°    | 84.9   | 83.0   | 81.0   | 74.6   | 72.6   |
| 87.5°  | 37.4   | 33.3   | 29.1   | 22.8   | 20.7   |
| 90°    | 1.3    | 16.2   | 27.1   | 33.9   | 36.5   |
| 92.5°  | 33.9   | 28.5   | 32.5   | 35.3   | 36.5   |
| 95°    | 87.9   | 43.3   | 52.8   | 59.7   | 58.2   |
| 97.5°  | 158.4  | 47.5   | 69.0   | 73.2   | 74.4   |
| 100°   | 239.8  | 54.2   | 77.2   | 87.9   | 90.7   |
| 102.5° | 329.0  | 326.4  | 80.0   | 94.7   | 98.9   |
| 105°   | 411.7  | 452.4  | 82.6   | 97.5   | 102.9  |
| 107.5° | 507.8  | 541.5  | 85.4   | 100.1  | 105.7  |
| 110°   | 600.0  | 628.2  | 237.0  | 101.6  | 106.9  |

TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLLONL

**CANDELA DISTRIBUTION (continued):**

|        | 0°     | 22.5°  | 45°    | 67.5°  | 90°    |
|--------|--------|--------|--------|--------|--------|
| 112.5° | 686.6  | 710.9  | 687.9  | 104.2  | 108.3  |
| 115°   | 778.6  | 801.6  | 835.5  | 208.6  | 111.1  |
| 117.5° | 858.5  | 885.5  | 908.7  | 714.9  | 360.2  |
| 120°   | 947.9  | 968.2  | 992.6  | 1008.9 | 826.0  |
| 122.5° | 1023.6 | 1045.3 | 1072.5 | 1080.6 | 1082.1 |
| 125°   | 1100.8 | 1118.5 | 1144.3 | 1153.7 | 1157.8 |
| 127.5° | 1171.2 | 1190.2 | 1210.7 | 1224.1 | 1225.4 |
| 130°   | 1237.6 | 1259.4 | 1274.1 | 1289.1 | 1287.9 |
| 132.5° | 1305.4 | 1323.0 | 1337.8 | 1350.1 | 1348.8 |
| 135°   | 1362.3 | 1384.0 | 1396.0 | 1409.8 | 1407.0 |
| 137.5° | 1421.7 | 1438.0 | 1451.7 | 1465.2 | 1461.2 |
| 140°   | 1480.0 | 1490.9 | 1505.7 | 1517.9 | 1511.2 |
| 142.5° | 1528.9 | 1538.4 | 1555.9 | 1566.7 | 1559.9 |
| 145°   | 1580.3 | 1578.9 | 1601.8 | 1611.4 | 1604.6 |
| 147.5° | 1624.9 | 1620.8 | 1643.9 | 1650.6 | 1645.3 |
| 150°   | 1668.3 | 1658.8 | 1680.5 | 1688.6 | 1681.8 |
| 152.5° | 1704.8 | 1694.0 | 1714.3 | 1722.5 | 1713.0 |
| 155°   | 1740.0 | 1727.9 | 1744.1 | 1752.2 | 1741.5 |
| 157.5° | 1768.4 | 1757.7 | 1769.9 | 1779.4 | 1768.4 |
| 160°   | 1792.9 | 1784.7 | 1792.9 | 1800.9 | 1791.5 |
| 162.5° | 1814.4 | 1806.5 | 1813.1 | 1822.6 | 1810.4 |
| 165°   | 1833.4 | 1825.4 | 1829.4 | 1838.8 | 1829.4 |
| 167.5° | 1848.4 | 1840.2 | 1844.4 | 1853.8 | 1841.6 |
| 170°   | 1860.6 | 1852.4 | 1855.1 | 1864.6 | 1852.4 |
| 172.5° | 1868.7 | 1860.6 | 1863.3 | 1872.8 | 1860.6 |
| 175°   | 1875.4 | 1865.9 | 1868.7 | 1878.1 | 1864.6 |
| 177.5° | 1878.1 | 1868.7 | 1870.1 | 1879.5 | 1867.3 |
| 180°   | 1871.3 | 1871.3 | 1871.3 | 1871.3 | 1871.3 |

TEST NUMBER: P911837

CATALOG NUMBER: DFN2DIP-SQ3F0-050D050US850-FLONL

**CIE UGR TABLE:**

| Reflectances:   |      |                  |       |       |       |       |                |       |       |       |       |
|-----------------|------|------------------|-------|-------|-------|-------|----------------|-------|-------|-------|-------|
| Ceiling         |      | 0.7              | 0.7   | 0.5   | 0.5   | 0.3   | 0.7            | 0.7   | 0.5   | 0.5   | 0.3   |
| Wall            |      | 0.5              | 0.3   | 0.5   | 0.3   | 0.3   | 0.5            | 0.3   | 0.5   | 0.3   | 0.3   |
| Reference plane |      | 0.2              | 0.2   | 0.2   | 0.2   | 0.2   | 0.2            | 0.2   | 0.2   | 0.2   | 0.2   |
| Room dimensions |      | Viewed crosswise |       |       |       |       | Viewed endwise |       |       |       |       |
| X=2H            | Y=2H | 10.39            | 11.25 | 11.34 | 12.22 | 13.49 | 9.94           | 10.80 | 10.90 | 11.78 | 13.05 |
|                 | 3H   | 12.04            | 12.81 | 13.01 | 13.80 | 15.09 | 11.55          | 12.32 | 12.52 | 13.31 | 14.60 |
|                 | 4H   | 12.63            | 13.36 | 13.61 | 14.34 | 15.64 | 12.13          | 12.86 | 13.11 | 13.85 | 15.15 |
|                 | 6H   | 13.02            | 13.70 | 14.02 | 14.69 | 16.00 | 12.52          | 13.20 | 13.52 | 14.19 | 15.50 |
|                 | 8H   | 13.13            | 13.77 | 14.12 | 14.77 | 16.09 | 12.62          | 13.27 | 13.62 | 14.27 | 15.58 |
|                 | 12H  | 13.17            | 13.78 | 14.18 | 14.78 | 16.12 | 12.66          | 13.27 | 13.67 | 14.27 | 15.61 |
| 4H              | 2H   | 10.84            | 11.57 | 11.83 | 12.56 | 13.86 | 10.49          | 11.22 | 11.48 | 12.20 | 13.51 |
|                 | 3H   | 12.70            | 13.31 | 13.70 | 14.33 | 15.64 | 12.30          | 12.91 | 13.29 | 13.92 | 15.24 |
|                 | 4H   | 13.41            | 13.97 | 14.42 | 14.98 | 16.32 | 12.99          | 13.55 | 14.00 | 14.56 | 15.89 |
|                 | 6H   | 13.92            | 14.41 | 14.94 | 15.44 | 16.77 | 13.49          | 13.97 | 14.51 | 15.00 | 16.34 |
|                 | 8H   | 14.07            | 14.52 | 15.09 | 15.54 | 16.90 | 13.64          | 14.08 | 14.65 | 15.11 | 16.46 |
|                 | 12H  | 14.14            | 14.55 | 15.18 | 15.59 | 16.94 | 13.69          | 14.10 | 14.73 | 15.14 | 16.50 |
| 8H              | 4H   | 13.61            | 14.06 | 14.62 | 15.08 | 16.43 | 13.23          | 13.68 | 14.25 | 14.70 | 16.05 |
|                 | 6H   | 14.23            | 14.60 | 15.27 | 15.67 | 17.02 | 13.85          | 14.22 | 14.89 | 15.28 | 16.63 |
|                 | 8H   | 14.45            | 14.78 | 15.50 | 15.83 | 17.19 | 14.06          | 14.38 | 15.11 | 15.43 | 16.80 |
|                 | 12H  | 14.58            | 14.86 | 15.63 | 15.91 | 17.32 | 14.17          | 14.45 | 15.22 | 15.50 | 16.91 |
| 12H             | 4H   | 13.59            | 14.00 | 14.63 | 15.04 | 16.39 | 13.22          | 13.63 | 14.26 | 14.67 | 16.02 |
|                 | 6H   | 14.26            | 14.59 | 15.31 | 15.64 | 17.01 | 13.89          | 14.21 | 14.94 | 15.27 | 16.63 |
|                 | 8H   | 14.50            | 14.79 | 15.55 | 15.83 | 17.24 | 14.12          | 14.41 | 15.17 | 15.45 | 16.86 |

END OF REPORT