

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P914733

Luminaire Tested: DFN2DIP-SQ3F0-090D110US927-FLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P914733
REPORT IS A COMBINATION OF REPORTS P901517 AND P898289
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-SQ3F0-090D110US927-FLLONL
Description: 3 foot, Square Define Geo, with Direct Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 15685.1 lumens
Efficiency: N/A
Efficacy: 90.3 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.06' x L: 3.06' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 173.7
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.996
Total Harmonic Distortion (THDi): 0.064
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	106	106	106	106	97	97	97	97	81	81	81		65	65	65		52
1	97	92	89	85	88	85	82	79	71	68	66		58	56	54		46
2	88	81	75	69	80	74	69	64	62	58	55		51	48	45		40
3	80	71	64	58	73	65	59	54	55	50	46		45	41	38		36
4	73	63	55	49	67	58	51	46	48	43	39		40	36	33		32
5	67	56	48	42	61	52	44	39	43	38	34		36	32	29		29
6	62	50	42	36	57	46	39	34	39	34	29		32	28	25		26
7	57	45	37	32	52	42	35	30	35	30	26		29	25	22		24
8	53	41	33	28	49	38	31	26	32	27	23		27	23	20		22
9	50	37	30	25	45	35	28	23	30	24	21		25	21	18		20
10	46	34	27	22	42	32	25	21	27	22	18		23	19	16		19

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3179	3179	3179
5°	3182	3132	3154
10°	3154	3088	3111
15°	3106	3035	3043
20°	3041	2962	2974
25°	2976	2876	2894
30°	2896	2795	2792
35°	2820	2700	2685
40°	2726	2604	2583
45°	2633	2508	2478
50°	2531	2407	2357
55°	2424	2290	2246
60°	2303	2151	2118
65°	2170	2007	1967
70°	2001	1832	1805
75°	1768	1622	1653
80°	1486	1352	1366
85°	1046	897	894

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2633 cd/sqm

TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	261.1	1.7
10°-20°	734.7	4.7
20°-30°	1079.6	6.9
30°-40°	1253.9	8.0
40°-50°	1252.4	8.0
50°-60°	1092.1	7.0
60°-70°	807.3	5.1
70°-80°	456.7	2.9
80°-90°	125.7	0.8
90°-100°	97.0	0.6
100°-110°	361.5	2.3
110°-120°	958.7	6.1
120°-130°	1590.2	10.1
130°-140°	1689.1	10.8
140°-150°	1569.9	10.0
150°-160°	1262.1	8.0
160°-170°	813.3	5.2
170°-180°	279.9	1.8
0°-30°	2075.4	13.2
0°-40°	3329.4	21.2
0°-60°	5673.8	36.2
0°-90°	7063.5	45.0
90°-120°	1417.2	9.0
90°-150°	6266.3	40.0
90°-180°	8622.0	55.0
0°-180°	15685.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2774	2774	2774	2774	2774	
5°	2774	2764	2734	2756	2750	263
15°	2641	2625	2590	2601	2588	744
25°	2390	2369	2324	2329	2324	1100
35°	2062	2036	1993	1977	1963	1288
45°	1678	1659	1619	1590	1579	1295
55°	1270	1254	1222	1190	1176	1135
65°	856	840	814	790	776	847
75°	448	443	429	414	419	478
85°	109	107	104	96	93	122
90°	2	26	42	53	57	14
95°	138	68	83	94	92	164
105°	647	711	130	153	162	691
115°	1224	1260	1313	328	175	1205
125°	1730	1758	1798	1813	1819	1543
135°	2141	2175	2194	2215	2211	1654
145°	2484	2481	2517	2532	2522	1553
155°	2734	2715	2741	2754	2737	1260
165°	2881	2869	2875	2890	2875	814
175°	2947	2932	2936	2952	2930	280
180°	2941	2941	2941	2941	2941	

TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2774.1	2774.1	2774.1	2774.1	2774.1
2.5°	2790.3	2777.0	2747.6	2774.1	2769.1
5°	2774.1	2763.7	2734.3	2755.5	2750.4
7.5°	2755.5	2739.7	2710.2	2731.8	2726.4
10°	2726.4	2707.7	2675.7	2696.9	2689.0
12.5°	2686.1	2670.3	2638.4	2651.6	2646.3
15°	2640.9	2625.1	2590.2	2601.0	2587.7
17.5°	2584.8	2569.0	2534.2	2547.5	2534.2
20°	2523.4	2507.6	2470.2	2478.1	2467.6
22.5°	2462.3	2438.3	2403.4	2403.4	2398.0
25°	2390.1	2368.9	2323.6	2328.7	2323.6
27.5°	2310.0	2291.3	2256.8	2248.9	2235.6
30°	2230.2	2208.7	2168.8	2160.8	2150.1
32.5°	2144.8	2128.9	2086.1	2070.0	2059.3
35°	2062.1	2035.5	1992.7	1976.7	1963.3
37.5°	1968.7	1944.6	1901.9	1883.3	1869.9
40°	1872.7	1851.2	1808.5	1784.7	1774.0
42.5°	1779.3	1757.8	1715.4	1688.5	1672.7
45°	1678.0	1659.4	1619.1	1590.0	1579.3
47.5°	1579.3	1560.6	1517.8	1488.4	1472.6
50°	1475.1	1461.8	1424.4	1387.1	1373.8
52.5°	1373.8	1355.1	1320.6	1291.2	1272.5
55°	1269.9	1253.8	1221.8	1189.9	1176.5
57.5°	1165.8	1152.5	1117.7	1085.7	1074.9
60°	1061.6	1051.1	1013.8	984.4	976.4
62.5°	960.3	941.6	915.0	888.4	877.7
65°	856.4	840.3	813.6	789.6	776.3
67.5°	749.7	736.2	712.3	693.7	682.9
70°	650.9	640.2	616.2	597.5	587.0
72.5°	549.6	538.8	525.5	506.9	499.0
75°	448.1	442.9	429.4	413.5	418.9
77.5°	357.4	346.7	341.4	333.4	325.5
80°	266.9	264.0	258.6	250.7	245.4
82.5°	181.4	181.4	178.9	168.1	168.1
85°	109.2	106.7	104.2	95.9	93.4
87.5°	48.1	42.7	37.4	29.5	26.6
90°	2.1	25.5	42.5	53.3	57.4
92.5°	53.3	44.8	51.0	55.4	57.4
95°	138.2	68.0	82.9	93.7	91.5
97.5°	248.9	74.5	108.4	114.9	117.0
100°	376.8	85.2	121.3	138.2	142.5
102.5°	517.0	512.9	125.6	148.9	155.4
105°	646.9	710.8	129.9	153.1	161.8
107.5°	798.0	851.0	134.2	157.4	166.0
110°	942.8	987.3	372.5	159.7	168.0

TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	1079.0	1117.1	1081.0	163.7	170.3
115°	1223.5	1259.6	1313.0	327.7	174.6
117.5°	1349.2	1391.6	1428.0	1123.5	566.0
120°	1489.6	1521.5	1559.9	1585.4	1298.1
122.5°	1608.7	1642.7	1685.4	1698.1	1700.4
125°	1730.0	1757.8	1798.2	1813.1	1819.4
127.5°	1840.6	1870.4	1902.5	1923.7	1925.8
130°	1945.0	1979.1	2002.3	2025.8	2023.9
132.5°	2051.4	2079.2	2102.4	2121.6	2119.6
135°	2140.9	2174.9	2193.9	2215.4	2211.1
137.5°	2234.3	2259.9	2281.3	2302.6	2296.2
140°	2325.8	2343.0	2366.2	2385.4	2374.8
142.5°	2402.6	2417.5	2445.1	2462.0	2451.4
145°	2483.5	2481.2	2517.3	2532.3	2521.7
147.5°	2553.5	2547.2	2583.3	2593.9	2585.6
150°	2621.7	2606.8	2640.9	2653.6	2643.0
152.5°	2679.1	2662.1	2694.0	2706.9	2692.0
155°	2734.5	2715.4	2740.9	2753.6	2736.7
157.5°	2779.1	2762.2	2781.4	2796.3	2779.1
160°	2817.6	2804.6	2817.6	2830.1	2815.3
162.5°	2851.4	2838.8	2849.4	2864.3	2845.1
165°	2881.2	2868.6	2874.9	2889.8	2874.9
167.5°	2904.7	2891.9	2898.4	2913.3	2894.2
170°	2923.9	2911.0	2915.3	2930.3	2911.0
172.5°	2936.5	2923.9	2928.2	2943.1	2923.9
175°	2947.2	2932.3	2936.5	2951.5	2930.3
177.5°	2951.5	2936.5	2938.8	2953.7	2934.6
180°	2940.9	2940.9	2940.9	2940.9	2940.9

TEST NUMBER: P914733

CATALOG NUMBER: DFN2DIP-SQ3F0-090D110US927-FLLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	10.78	11.60	11.78	12.61	13.95	10.33	11.15	11.33	12.16	13.50
	3H	12.43	13.16	13.44	14.18	15.54	11.94	12.67	12.95	13.69	15.05
	4H	13.01	13.71	14.04	14.73	16.10	12.52	13.21	13.54	14.24	15.61
	6H	13.41	14.05	14.44	15.07	16.46	12.91	13.55	13.94	14.57	15.96
	8H	13.51	14.12	14.55	15.16	16.54	13.01	13.62	14.05	14.66	16.04
	12H	13.55	14.13	14.60	15.17	16.57	13.05	13.62	14.09	14.66	16.06
4H	2H	11.23	11.93	12.26	12.95	14.32	10.88	11.57	11.90	12.59	13.96
	3H	13.09	13.67	14.12	14.72	16.10	12.68	13.26	13.72	14.31	15.69
	4H	13.80	14.33	14.84	15.37	16.77	13.37	13.90	14.42	14.94	16.35
	6H	14.30	14.76	15.36	15.83	17.23	13.87	14.33	14.93	15.39	16.79
	8H	14.45	14.88	15.50	15.93	17.35	14.01	14.44	15.07	15.50	16.91
	12H	14.52	14.90	15.59	15.98	17.40	14.07	14.46	15.14	15.53	16.95
8H	4H	13.98	14.41	15.04	15.47	16.88	13.61	14.03	14.66	15.09	16.51
	6H	14.61	14.96	15.69	16.06	17.47	14.22	14.58	15.30	15.68	17.09
	8H	14.82	15.13	15.91	16.22	17.65	14.43	14.74	15.52	15.83	17.26
	12H	14.95	15.22	16.04	16.30	17.77	14.54	14.81	15.63	15.89	17.36
12H	4H	13.97	14.35	15.04	15.43	16.85	13.60	13.98	14.67	15.06	16.48
	6H	14.64	14.95	15.72	16.03	17.46	14.26	14.57	15.35	15.66	17.09
	8H	14.87	15.14	15.96	16.22	17.70	14.49	14.76	15.58	15.84	17.31

END OF REPORT