

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P904028

Luminaire Tested: DFN2DIP-SQ4F0-080D110US830-FLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P904028
REPORT IS A COMBINATION OF REPORTS P900153 AND P896915
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-SQ4F0-080D110US830-FLLFLL
Description: 4 foot, Square Define Geo, with Direct Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 16640.6 lumens
Efficiency: N/A
Efficacy: 107.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.92' x L: 3.92' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 154.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9954
Total Harmonic Distortion (THDi): 0.076
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	106	106	106	106	97	97	97	97	81	81	81	65	65	65	51	51	51			45
1	97	92	88	85	88	85	81	78	71	68	66	57	56	54	45	44	43			38
2	88	81	75	69	80	74	69	64	62	58	55	50	48	45	40	38	37			32
3	80	71	64	58	73	65	59	54	55	50	46	45	41	38	35	33	31			27
4	73	63	55	49	67	58	51	46	48	43	39	40	36	33	32	29	27			23
5	67	56	48	42	61	51	44	39	43	38	34	36	32	28	29	26	23			20
6	62	50	42	36	57	46	39	34	39	33	29	32	28	25	26	23	21			18
7	57	45	37	32	52	42	35	30	35	30	26	29	25	22	24	21	18			16
8	53	41	33	28	49	38	31	26	32	27	23	27	23	20	22	19	16			14
9	49	37	30	25	45	35	28	23	29	24	21	25	21	18	20	17	15			13
10	46	34	27	22	42	32	25	21	27	22	18	23	19	16	19	16	13			11

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2059	2059	2059
5°	2062	2030	2044
10°	2045	2003	2017
15°	2015	1971	1975
20°	1974	1925	1931
25°	1934	1871	1880
30°	1883	1821	1816
35°	1835	1761	1747
40°	1776	1700	1682
45°	1717	1640	1616
50°	1653	1577	1539
55°	1585	1503	1469
60°	1509	1416	1388
65°	1426	1326	1292
70°	1320	1216	1190
75°	1173	1085	1097
80°	996	918	916
85°	720	628	616

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 90°

Luminance: 2581 cd/sqm

TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	276.1	1.7
10°-20°	777.0	4.7
20°-30°	1141.8	6.9
30°-40°	1326.2	8.0
40°-50°	1324.5	8.0
50°-60°	1155.0	6.9
60°-70°	853.8	5.1
70°-80°	483.0	2.9
80°-90°	136.8	0.8
90°-100°	202.9	1.2
100°-110°	644.7	3.9
110°-120°	1103.3	6.6
120°-130°	1451.0	8.7
130°-140°	1628.6	9.8
140°-150°	1597.1	9.6
150°-160°	1339.7	8.1
160°-170°	888.5	5.3
170°-180°	310.5	1.9
0°-30°	2195.0	13.2
0°-40°	3521.1	21.2
0°-60°	6000.6	36.1
0°-90°	7474.2	44.9
90°-120°	1950.9	11.7
90°-150°	6627.6	39.8
90°-180°	9166.0	55.1
0°-180°	16640.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2934	2934	2934	2934	2934	
5°	2934	2923	2892	2914	2909	279
15°	2793	2776	2739	2751	2737	787
25°	2528	2505	2458	2463	2458	1163
35°	2181	2153	2108	2090	2076	1362
45°	1775	1755	1712	1682	1670	1370
55°	1343	1326	1292	1258	1244	1201
65°	906	889	860	835	821	896
75°	474	468	454	437	443	506
85°	116	113	110	102	99	129
90°	3	36	97	91	94	16
95°	144	172	177	177	172	161
105°	595	603	609	614	614	628
115°	1107	1123	1118	1115	1107	1095
125°	1610	1635	1627	1618	1615	1439
135°	2083	2114	2119	2116	2109	1610
145°	2529	2548	2564	2567	2556	1580
155°	2892	2899	2908	2922	2913	1331
165°	3146	3142	3142	3162	3148	887
175°	3273	3265	3259	3279	3262	311
180°	3279	3279	3279	3279	3279	

TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2933.9	2933.9	2933.9	2933.9	2933.9
2.5°	2951.0	2937.0	2905.9	2933.9	2928.6
5°	2933.9	2922.9	2891.8	2914.2	2908.9
7.5°	2914.2	2897.5	2866.4	2889.1	2883.4
10°	2883.4	2863.6	2829.8	2852.2	2843.9
12.5°	2840.9	2824.1	2790.3	2804.3	2798.7
15°	2793.0	2776.3	2739.4	2750.8	2736.8
17.5°	2733.7	2717.0	2680.1	2694.3	2680.1
20°	2668.8	2652.0	2612.5	2620.9	2609.8
22.5°	2604.2	2578.7	2541.8	2541.8	2536.2
25°	2527.8	2505.4	2457.5	2462.9	2457.5
27.5°	2443.1	2423.4	2386.8	2378.4	2364.4
30°	2358.7	2335.9	2293.8	2285.4	2274.0
32.5°	2268.3	2251.5	2206.3	2189.2	2177.9
35°	2180.9	2152.8	2107.5	2090.5	2076.4
37.5°	2082.1	2056.6	2011.5	1991.7	1977.6
40°	1980.7	1957.8	1912.7	1887.5	1876.1
42.5°	1881.9	1859.1	1814.2	1785.7	1769.1
45°	1774.7	1754.9	1712.4	1681.6	1670.3
47.5°	1670.3	1650.5	1605.2	1574.1	1557.4
50°	1560.1	1546.1	1506.5	1467.0	1452.9
52.5°	1452.9	1433.1	1396.7	1365.6	1345.8
55°	1343.0	1326.0	1292.2	1258.4	1244.3
57.5°	1232.9	1218.9	1182.0	1148.2	1136.8
60°	1122.8	1111.7	1072.1	1041.0	1032.6
62.5°	1015.6	995.9	967.7	939.6	928.2
65°	905.8	888.7	860.5	835.1	821.0
67.5°	792.9	778.5	753.4	733.7	722.3
70°	688.4	677.0	651.7	631.9	620.8
72.5°	581.3	570.0	555.8	536.1	527.7
75°	473.8	468.4	454.1	437.3	443.0
77.5°	378.1	366.6	361.0	352.6	344.2
80°	282.3	279.3	273.6	265.2	259.5
82.5°	191.9	191.9	189.2	177.8	177.8
85°	115.6	112.8	110.2	101.5	98.8
87.5°	50.9	45.2	39.5	31.1	28.2
90°	2.9	35.6	96.9	91.0	93.9
92.5°	61.3	83.0	86.0	89.0	89.0
95°	144.3	172.0	176.9	176.9	172.0
97.5°	240.3	265.9	276.8	276.8	276.8
100°	350.9	373.6	381.5	381.5	378.6
102.5°	467.6	484.4	495.3	498.2	495.3
105°	595.1	603.0	609.0	613.9	613.9
107.5°	721.6	733.5	733.5	735.5	721.6
110°	844.2	860.1	860.1	860.1	852.2

TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	976.7	993.4	990.5	982.6	976.7
115°	1107.2	1122.9	1118.0	1115.1	1107.2
117.5°	1236.7	1258.4	1244.5	1236.7	1228.8
120°	1367.2	1388.9	1367.2	1367.2	1358.3
122.5°	1485.8	1513.4	1499.6	1491.7	1485.8
125°	1610.3	1635.0	1627.1	1618.3	1615.2
127.5°	1731.9	1762.6	1751.7	1739.8	1731.9
130°	1845.6	1881.2	1876.2	1870.3	1859.4
132.5°	1973.1	2000.8	2002.8	1989.0	1981.0
135°	2082.8	2113.5	2119.4	2116.5	2108.6
137.5°	2205.5	2230.1	2235.1	2233.1	2221.3
140°	2313.2	2337.9	2351.7	2351.7	2340.9
142.5°	2423.9	2448.6	2456.5	2459.5	2448.6
145°	2528.7	2548.4	2564.3	2567.2	2556.4
147.5°	2622.6	2647.3	2659.2	2664.1	2653.3
150°	2719.5	2736.3	2747.1	2756.1	2747.1
152.5°	2805.5	2822.3	2836.1	2847.0	2836.1
155°	2891.5	2899.4	2908.3	2922.2	2913.2
157.5°	2965.6	2971.6	2976.5	2996.2	2982.4
160°	3031.9	3037.8	3040.7	3057.6	3045.7
162.5°	3093.1	3093.1	3096.2	3114.9	3101.1
165°	3145.5	3142.5	3142.5	3162.3	3148.5
167.5°	3193.0	3184.1	3184.1	3203.9	3190.0
170°	3228.6	3220.7	3217.7	3237.4	3220.7
172.5°	3253.3	3245.4	3242.4	3262.2	3245.4
175°	3273.1	3265.2	3259.2	3279.0	3262.2
177.5°	3283.9	3276.0	3270.1	3286.9	3270.1
180°	3279.0	3279.0	3279.0	3279.0	3279.0

TEST NUMBER: P904028

CATALOG NUMBER: DFN2DIP-SQ4F0-080D110US830-FLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	9.30	10.12	10.30	11.13	12.47	8.86	9.68	9.86	10.69	12.03
	3H	10.96	11.70	11.97	12.72	14.08	10.47	11.21	11.48	12.23	13.59
	4H	11.55	12.25	12.57	13.27	14.64	11.06	11.75	12.08	12.77	14.15
	6H	11.95	12.59	12.99	13.62	15.00	11.45	12.09	12.49	13.12	14.50
	8H	12.06	12.67	13.10	13.71	15.09	11.56	12.17	12.60	13.21	14.59
	12H	12.11	12.69	13.15	13.72	15.13	11.60	12.18	12.64	13.21	14.62
4H	2H	9.76	10.45	10.79	11.48	12.85	9.40	10.10	10.43	11.12	12.49
	3H	11.63	12.20	12.66	13.26	14.64	11.22	11.80	12.25	12.85	14.23
	4H	12.34	12.87	13.39	13.91	15.32	11.92	12.45	12.96	13.49	14.90
	6H	12.86	13.31	13.91	14.38	15.78	12.43	12.88	13.48	13.95	15.35
	8H	13.01	13.44	14.06	14.49	15.91	12.57	13.00	13.63	14.06	15.47
	12H	13.08	13.47	14.16	14.54	15.96	12.63	13.02	13.71	14.09	15.51
8H	4H	12.53	12.96	13.59	14.02	15.44	12.16	12.58	13.21	13.64	15.06
	6H	13.17	13.52	14.25	14.62	16.04	12.78	13.14	13.86	14.24	15.65
	8H	13.39	13.70	14.48	14.79	16.22	13.00	13.31	14.08	14.39	15.83
	12H	13.52	13.80	14.61	14.88	16.35	13.11	13.39	14.20	14.46	15.94
12H	4H	12.52	12.90	13.59	13.98	15.40	12.15	12.54	13.22	13.61	15.03
	6H	13.20	13.51	14.28	14.59	16.03	12.83	13.14	13.91	14.22	15.65
	8H	13.44	13.71	14.53	14.79	16.27	13.06	13.33	14.15	14.41	15.89