

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P909798

Luminaire Tested: DFN2DIP-TR2F0-060D020US840-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P909798
REPORT IS A COMBINATION OF REPORTS P900230 AND P897145
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-TR2F0-060D020US840-RLLFLL
Description: 2 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6937.8 lumens
Efficiency: N/A
Efficacy: 92.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.04' x L: 2.36' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 74.7
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9971
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2F0-060D020US840-RLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2F0-060D020US840-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	113	113	113	113	107	107	107	107	97	97	97		87	87	87		78
1	104	100	96	93	99	95	92	89	86	84	81		78	76	74		70
2	95	88	82	77	90	84	79	74	76	72	68		69	66	63		63
3	87	78	71	65	83	75	68	63	68	63	58		62	58	54		56
4	80	70	62	56	76	67	60	54	61	55	51		56	51	47		51
5	74	63	54	48	70	60	53	47	55	49	44		51	45	42		46
6	69	57	48	43	65	54	47	41	50	44	39		46	41	37		42
7	64	51	43	38	61	49	42	37	46	39	35		42	37	33		39
8	59	47	39	34	57	45	38	33	42	36	31		39	34	30		36
9	56	43	36	31	53	42	35	30	39	33	28		36	31	27		33
10	52	40	33	28	50	39	32	27	36	30	26		33	28	25		31

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5586	5586	5586
5°	5586	5484	5522
10°	5523	5365	5333
15°	5438	5175	5047
20°	5329	4919	4698
25°	5218	4635	4362
30°	5071	4344	3939
35°	4927	4033	3568
40°	4779	3712	3144
45°	4609	3358	2760
50°	4432	3001	2386
55°	4246	2622	2026
60°	4031	2228	1659
65°	3783	1828	1483
70°	3482	1456	1329
75°	3103	1259	1190
80°	2557	1022	1003
85°	1679	633	706

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4609 cd/sqm

TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2F0-060D020US840-RLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	234.7	3.4
10°-20°	644.3	9.3
20°-30°	904.6	13.0
30°-40°	986.1	14.2
40°-50°	906.3	13.1
50°-60°	711.7	10.3
60°-70°	463.3	6.7
70°-80°	238.5	3.4
80°-90°	62.7	0.9
90°-100°	39.5	0.6
100°-110°	125.6	1.8
110°-120°	214.9	3.1
120°-130°	282.7	4.1
130°-140°	317.3	4.6
140°-150°	311.1	4.5
150°-160°	261.0	3.8
160°-170°	173.1	2.5
170°-180°	60.5	0.9
0°-30°	1783.6	25.7
0°-40°	2769.6	39.9
0°-60°	4387.7	63.2
0°-90°	5152.1	74.3
90°-120°	380.0	5.5
90°-150°	1291.1	18.6
90°-180°	1786.0	25.7
0°-180°	6937.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2504	2504	2504	2504	2504	
5°	2504	2493	2463	2484	2477	237
15°	2382	2357	2280	2237	2214	671
25°	2162	2090	1940	1847	1813	994
35°	1863	1747	1548	1405	1355	1166
45°	1523	1371	1133	972	918	1176
55°	1158	981	736	601	558	1035
65°	782	598	394	317	310	775
75°	417	258	181	165	163	441
85°	97	50	43	43	43	112
90°	1	7	19	18	18	7
95°	28	34	34	34	34	31
105°	116	117	119	120	120	122
115°	216	219	218	217	216	213
125°	314	318	317	315	315	280
135°	406	412	413	412	411	314
145°	493	496	500	500	498	308
155°	563	565	566	569	568	259
165°	613	612	612	616	613	173
175°	638	636	635	639	636	61
180°	639	639	639	639	639	

TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2FO-060D020US840-RLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2504.3	2504.3	2504.3	2504.3	2504.3
2.5°	2515.6	2504.3	2479.2	2502.0	2497.5
5°	2504.3	2493.0	2463.4	2483.9	2477.1
7.5°	2483.9	2470.3	2438.6	2447.5	2436.2
10°	2456.6	2440.7	2395.6	2388.6	2375.1
12.5°	2422.8	2402.3	2341.0	2327.5	2302.5
15°	2381.9	2356.8	2279.9	2236.9	2214.2
17.5°	2334.3	2297.9	2202.7	2152.9	2116.7
20°	2279.9	2234.4	2121.2	2064.7	2014.7
22.5°	2221.0	2168.8	2037.3	1960.4	1926.4
25°	2162.1	2089.5	1940.0	1847.1	1813.0
27.5°	2091.9	2014.7	1849.3	1742.7	1690.6
30°	2017.1	1930.8	1749.5	1634.1	1572.8
32.5°	1944.5	1840.2	1654.6	1518.4	1461.7
35°	1863.0	1747.4	1548.0	1405.1	1355.1
37.5°	1783.6	1658.8	1448.2	1291.7	1235.2
40°	1699.7	1563.9	1343.8	1183.0	1124.1
42.5°	1613.7	1468.6	1239.7	1071.9	1015.4
45°	1523.0	1371.0	1133.3	972.1	917.8
47.5°	1436.9	1276.1	1031.3	870.2	820.4
50°	1341.7	1180.8	931.5	775.0	727.6
52.5°	1248.6	1078.6	836.3	686.7	643.7
55°	1158.0	981.3	736.5	600.7	557.5
57.5°	1065.2	883.8	648.2	521.3	484.9
60°	970.0	788.7	555.2	439.8	403.4
62.5°	877.2	695.9	475.8	367.2	349.1
65°	781.9	598.2	394.4	317.4	310.4
67.5°	691.3	507.6	317.4	278.7	272.0
70°	596.0	419.3	262.8	240.2	231.1
72.5°	505.4	337.6	219.7	201.8	197.1
75°	417.0	258.2	181.3	165.4	163.3
77.5°	328.7	183.5	142.8	133.7	129.2
80°	246.9	131.5	108.7	99.8	99.8
82.5°	172.2	88.5	74.7	70.2	70.2
85°	97.4	49.8	43.0	43.0	43.0
87.5°	36.4	18.1	18.1	15.9	15.9
90°	0.6	7.0	18.9	17.7	18.3
92.5°	11.9	16.2	16.8	17.4	17.4
95°	28.1	33.5	34.4	34.4	33.5
97.5°	46.8	51.8	53.9	53.9	53.9
100°	68.4	72.8	74.3	74.3	73.7
102.5°	91.1	94.3	96.4	97.0	96.4
105°	115.9	117.4	118.7	119.6	119.6
107.5°	140.6	142.9	142.9	143.3	140.6
110°	164.5	167.5	167.5	167.5	166.0

TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2F0-060D020US840-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	190.3	193.5	193.0	191.4	190.3
115°	215.7	218.7	217.8	217.2	215.7
117.5°	241.0	245.2	242.5	241.0	239.3
120°	266.3	270.5	266.3	266.3	264.6
122.5°	289.4	294.8	292.2	290.6	289.4
125°	313.7	318.5	317.0	315.3	314.7
127.5°	337.4	343.4	341.2	338.9	337.4
130°	359.5	366.5	365.5	364.4	362.2
132.5°	384.4	389.8	390.1	387.5	385.9
135°	405.8	411.7	412.8	412.3	410.7
137.5°	429.6	434.4	435.5	435.1	432.7
140°	450.6	455.4	458.2	458.2	456.1
142.5°	472.2	477.0	478.6	479.1	477.0
145°	492.6	496.4	499.6	500.1	498.0
147.5°	510.9	515.7	518.1	519.0	516.8
150°	529.8	533.0	535.1	536.8	535.1
152.5°	546.5	549.8	552.5	554.6	552.5
155°	563.3	564.8	566.5	569.3	567.5
157.5°	577.7	578.9	579.9	583.7	581.0
160°	590.7	591.8	592.4	595.6	593.3
162.5°	602.6	602.6	603.1	606.8	604.1
165°	612.8	612.2	612.2	616.0	613.4
167.5°	622.0	620.3	620.3	624.1	621.5
170°	628.9	627.4	626.8	630.7	627.4
172.5°	633.8	632.2	631.7	635.5	632.2
175°	637.6	636.1	634.9	638.7	635.5
177.5°	639.7	638.2	637.0	640.3	637.0
180°	638.7	638.7	638.7	638.7	638.7

TEST NUMBER: P909798

CATALOG NUMBER: DFN2DIP-TR2F0-060D020US840-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.01	16.09	15.74	16.83	17.71	11.00	12.07	11.72	12.81	13.69
	3H	16.69	17.65	17.42	18.40	19.31	12.19	13.15	12.93	13.90	14.81
	4H	17.29	18.20	18.05	18.96	19.88	12.64	13.55	13.40	14.31	15.23
	6H	17.71	18.54	18.47	19.31	20.25	12.96	13.80	13.73	14.56	15.50
	8H	17.83	18.62	18.61	19.41	20.35	13.05	13.84	13.83	14.63	15.57
	12H	17.89	18.65	18.67	19.43	20.39	13.09	13.85	13.88	14.63	15.60
4H	2H	15.06	15.97	15.82	16.73	17.65	11.61	12.52	12.37	13.28	14.20
	3H	16.88	17.64	17.65	18.43	19.37	12.96	13.72	13.73	14.51	15.45
	4H	17.57	18.25	18.35	19.04	20.01	13.51	14.19	14.29	14.98	15.95
	6H	18.07	18.66	18.88	19.48	20.46	13.92	14.51	14.73	15.33	16.31
	8H	18.24	18.79	19.05	19.61	20.59	14.05	14.60	14.85	15.41	16.40
	12H	18.33	18.83	19.16	19.66	20.66	14.11	14.61	14.94	15.45	16.44
8H	4H	17.55	18.10	18.36	18.91	19.90	13.79	14.34	14.60	15.16	16.14
	6H	18.10	18.55	18.93	19.41	20.40	14.30	14.75	15.13	15.61	16.60
	8H	18.30	18.70	19.15	19.56	20.57	14.48	14.88	15.32	15.74	16.74
	12H	18.43	18.79	19.28	19.63	20.70	14.59	14.95	15.44	15.79	16.86
12H	4H	17.51	18.01	18.34	18.84	19.84	13.80	14.30	14.63	15.13	16.13
	6H	18.07	18.48	18.92	19.33	20.34	14.34	14.75	15.19	15.60	16.61
	8H	18.29	18.64	19.14	19.49	20.55	14.55	14.90	15.40	15.75	16.81