

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P915754

Luminaire Tested: DFN2DIP-TR4F0-120D070US927-FLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P915754
REPORT IS A COMBINATION OF REPORTS P900439 AND P897293
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-TR4F0-120D070US927-FLLFLL
Description: 4 foot, Triangle Define Geo, with Direct Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 14318.7 lumens
Efficiency: N/A
Efficacy: 80.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.43' x L: 3.96' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 177.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9821
Total Harmonic Distortion (THDi): 0.08
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

Luminous Intensity Polar Plot



TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	111	111	111	111	104	104	104	104	92	92	92		81	81	81		71
1	101	97	93	89	95	91	88	85	81	78	76		71	69	67		62
2	92	85	78	73	87	80	74	70	71	67	63		63	59	56		55
3	84	74	67	61	79	70	64	58	63	57	53		55	51	48		49
4	77	66	58	52	72	62	55	49	56	50	45		49	45	41		44
5	71	59	51	44	66	56	48	43	50	44	39		44	39	36		39
6	65	53	45	39	61	50	43	37	45	39	34		40	35	31		36
7	61	48	40	34	57	45	38	33	41	35	30		37	32	28		33
8	56	44	36	30	53	41	34	29	37	31	27		34	28	25		30
9	52	40	32	27	49	38	31	26	34	28	24		31	26	22		28
10	49	37	29	24	46	35	28	24	32	26	22		29	24	20		26

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2939	2939	2939
5°	2943	2898	2917
10°	2919	2859	2877
15°	2877	2811	2816
20°	2819	2746	2752
25°	2761	2668	2679
30°	2689	2595	2586
35°	2620	2509	2488
40°	2536	2422	2394
45°	2452	2336	2299
50°	2360	2244	2188
55°	2263	2139	2086
60°	2155	2013	1969
65°	2036	1884	1831
70°	1885	1726	1683
75°	1676	1536	1546
80°	1424	1295	1284
85°	1030	879	851

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 2452 cd/sqm

TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	348.1	2.4
10°-20°	979.5	6.8
20°-30°	1439.5	10.1
30°-40°	1671.9	11.7
40°-50°	1669.9	11.7
50°-60°	1456.0	10.2
60°-70°	1076.3	7.5
70°-80°	609.0	4.3
80°-90°	165.7	1.2
90°-100°	108.5	0.8
100°-110°	344.8	2.4
110°-120°	590.1	4.1
120°-130°	776.1	5.4
130°-140°	871.1	6.1
140°-150°	854.2	6.0
150°-160°	716.6	5.0
160°-170°	475.2	3.3
170°-180°	166.1	1.2
0°-30°	2767.2	19.3
0°-40°	4439.1	31.0
0°-60°	7565.0	52.8
0°-90°	9416.1	65.8
90°-120°	1043.4	7.3
90°-150°	3544.8	24.8
90°-180°	4903.0	34.2
0°-180°	14318.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3699	3699	3699	3699	3699	
5°	3699	3685	3646	3674	3667	351
15°	3521	3500	3454	3468	3450	992
25°	3187	3158	3098	3105	3098	1466
35°	2749	2714	2657	2636	2618	1717
45°	2237	2212	2159	2120	2106	1727
55°	1693	1672	1629	1586	1569	1514
65°	1142	1120	1085	1053	1035	1129
75°	597	591	572	551	558	638
85°	146	142	139	128	124	162
90°	2	19	52	49	50	14
95°	77	92	95	95	92	86
105°	318	322	326	328	328	336
115°	592	601	598	596	592	586
125°	861	874	870	866	864	770
135°	1114	1130	1134	1132	1128	861
145°	1352	1363	1372	1373	1367	845
155°	1546	1551	1556	1563	1558	712
165°	1682	1681	1681	1691	1684	475
175°	1751	1746	1743	1754	1745	166
180°	1754	1754	1754	1754	1754	

TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3698.9	3698.9	3698.9	3698.9	3698.9
2.5°	3720.4	3702.7	3663.4	3698.9	3692.1
5°	3698.9	3684.9	3645.7	3674.0	3667.2
7.5°	3674.0	3652.8	3613.6	3642.3	3635.2
10°	3635.2	3610.2	3567.6	3595.9	3585.3
12.5°	3581.5	3560.4	3517.8	3535.5	3528.3
15°	3521.2	3500.0	3453.6	3467.9	3450.2
17.5°	3446.5	3425.3	3378.9	3396.6	3378.9
20°	3364.6	3343.4	3293.7	3304.2	3290.2
22.5°	3283.0	3251.0	3204.5	3204.5	3197.4
25°	3186.8	3158.5	3098.1	3105.0	3098.1
27.5°	3080.0	3055.1	3009.1	2998.5	2980.8
30°	2973.6	2944.9	2891.7	2881.2	2866.8
32.5°	2859.6	2838.5	2781.5	2760.0	2745.7
35°	2749.4	2714.0	2657.0	2635.5	2617.8
37.5°	2624.9	2592.9	2535.9	2511.0	2493.2
40°	2497.0	2468.4	2411.3	2379.6	2365.3
42.5°	2372.5	2343.8	2287.2	2251.4	2230.2
45°	2237.4	2212.5	2158.9	2120.0	2105.7
47.5°	2105.7	2080.7	2023.8	1984.6	1963.4
50°	1966.8	1949.1	1899.3	1849.4	1831.7
52.5°	1831.7	1806.8	1760.8	1721.5	1696.6
55°	1693.2	1671.7	1629.0	1586.4	1568.7
57.5°	1554.3	1536.6	1490.2	1447.6	1433.2
60°	1415.5	1401.5	1351.7	1312.5	1301.9
62.5°	1280.4	1255.4	1220.0	1184.5	1170.2
65°	1141.9	1120.4	1084.9	1052.8	1035.1
67.5°	999.7	981.5	949.8	925.0	910.6
70°	867.9	853.6	821.5	796.6	782.7
72.5°	732.8	718.5	700.8	675.9	665.3
75°	597.4	590.6	572.4	551.4	558.5
77.5°	476.6	462.2	455.1	444.5	434.0
80°	355.8	352.0	344.9	334.4	327.2
82.5°	241.9	241.9	238.5	224.2	224.2
85°	145.7	142.3	138.9	127.9	124.5
87.5°	64.2	57.0	49.8	39.2	35.5
90°	1.6	19.0	51.8	48.6	50.2
92.5°	32.8	44.4	46.0	47.6	47.6
95°	77.2	92.0	94.7	94.7	92.0
97.5°	128.5	142.2	148.1	148.1	148.1
100°	187.7	199.9	204.1	204.1	202.5
102.5°	250.1	259.0	264.9	266.5	264.9
105°	318.3	322.5	325.7	328.4	328.4
107.5°	386.0	392.3	392.3	393.4	386.0
110°	451.5	460.0	460.0	460.0	455.7

TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	522.4	531.4	529.8	525.5	522.4
115°	592.2	600.6	598.0	596.4	592.2
117.5°	661.4	673.0	665.7	661.4	657.2
120°	731.2	742.8	731.2	731.2	726.4
122.5°	794.6	809.5	802.1	797.8	794.6
125°	861.3	874.5	870.3	865.5	864.0
127.5°	926.3	942.7	936.9	930.6	926.3
130°	987.1	1006.1	1003.5	1000.4	994.5
132.5°	1055.3	1070.2	1071.2	1063.8	1059.5
135°	1114.0	1130.4	1133.6	1131.9	1127.7
137.5°	1179.6	1192.8	1195.4	1194.4	1188.0
140°	1237.2	1250.5	1257.8	1257.8	1252.0
142.5°	1296.4	1309.6	1313.8	1315.4	1309.6
145°	1352.5	1363.0	1371.5	1373.1	1367.3
147.5°	1402.7	1415.9	1422.3	1424.9	1419.1
150°	1454.5	1463.5	1469.3	1474.1	1469.3
152.5°	1500.5	1509.5	1516.9	1522.7	1516.9
155°	1546.5	1550.7	1555.5	1562.9	1558.1
157.5°	1586.2	1589.4	1592.0	1602.6	1595.1
160°	1621.6	1624.8	1626.3	1635.3	1629.0
162.5°	1654.4	1654.4	1656.0	1666.0	1658.6
165°	1682.4	1680.8	1680.8	1691.4	1683.9
167.5°	1707.8	1703.0	1703.0	1713.6	1706.2
170°	1726.8	1722.6	1721.0	1731.5	1722.6
172.5°	1740.0	1735.7	1734.2	1744.8	1735.7
175°	1750.6	1746.4	1743.2	1753.7	1744.8
177.5°	1756.4	1752.1	1749.0	1758.0	1749.0
180°	1753.7	1753.7	1753.7	1753.7	1753.7

TEST NUMBER: P915754

CATALOG NUMBER: DFN2DIP-TR4F0-120D070US927-FLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.35	13.37	13.16	14.21	15.23	11.92	12.94	12.73	13.77	14.80
	3H	14.02	14.94	14.84	15.78	16.84	13.55	14.47	14.37	15.31	16.37
	4H	14.62	15.49	15.46	16.33	17.40	14.15	15.01	14.98	15.86	16.93
	6H	15.03	15.83	15.88	16.68	17.76	14.55	15.35	15.40	16.21	17.29
	8H	15.13	15.90	15.99	16.77	17.85	14.66	15.42	15.52	16.30	17.38
	12H	15.19	15.92	16.05	16.78	17.89	14.71	15.44	15.57	16.30	17.41
4H	2H	12.83	13.70	13.68	14.55	15.61	12.49	13.36	13.33	14.20	15.27
	3H	14.71	15.44	15.57	16.32	17.40	14.32	15.04	15.17	15.93	17.01
	4H	15.43	16.09	16.30	16.97	18.08	15.03	15.69	15.90	16.57	17.68
	6H	15.96	16.53	16.84	17.43	18.54	15.55	16.12	16.43	17.02	18.13
	8H	16.11	16.64	17.00	17.54	18.67	15.70	16.23	16.59	17.13	18.26
	12H	16.19	16.67	17.10	17.59	18.72	15.77	16.25	16.68	17.17	18.30
8H	4H	15.64	16.18	16.53	17.07	18.20	15.28	15.82	16.17	16.71	17.84
	6H	16.28	16.72	17.19	17.66	18.79	15.92	16.36	16.83	17.30	18.42
	8H	16.50	16.89	17.43	17.83	18.97	16.13	16.53	17.06	17.46	18.60
	12H	16.64	16.99	17.57	17.91	19.10	16.26	16.60	17.18	17.53	18.72
12H	4H	15.64	16.12	16.54	17.03	18.16	15.28	15.77	16.19	16.68	17.81
	6H	16.31	16.70	17.24	17.64	18.78	15.96	16.35	16.88	17.29	18.43
	8H	16.56	16.91	17.49	17.83	19.02	16.21	16.55	17.13	17.47	18.67