

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P923751

Luminaire Tested: DFN2DIP-TR4F0-070D050US940-FLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P923751
REPORT IS A COMBINATION OF REPORTS P901913 AND P898849
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-TR4F0-070D050US940-FLLONL
Description: 4 foot, Triangle Define Geo, with Direct Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 10593.6 lumens
Efficiency: N/A
Efficacy: 102.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.16 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 3.43' x L: 3.96' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 103.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.9977
Total Harmonic Distortion (THDi): 0.049
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	109	109	109	109		102	102	102	102		88	88	88		75	75	75		64	64	64
1	100	95	91	88		93	89	86	82		77	75	72		66	65	63		56	55	54
2	91	83	77	72		84	78	72	68		68	64	60		58	55	53		50	47	45
3	83	73	66	60		77	69	62	57		60	55	50		52	48	44		44	41	39
4	76	65	57	51		70	61	54	48		53	47	43		46	42	38		39	36	33
5	70	58	50	43		65	54	47	41		48	42	37		41	37	33		35	32	29
6	64	52	44	38		60	49	41	36		43	37	32		37	33	29		32	29	26
7	59	47	39	33		55	44	37	32		39	33	29		34	29	26		29	26	23
8	55	43	35	29		51	40	33	28		36	30	26		31	26	23		27	23	20
9	51	39	31	26		48	37	30	25		33	27	23		29	24	21		25	21	18
10	48	36	29	24		45	34	27	23		30	25	21		27	22	19		23	19	17

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1930	1930	1930
5°	1933	1903	1915
10°	1917	1877	1889
15°	1889	1846	1849
20°	1851	1803	1807
25°	1813	1752	1759
30°	1765	1704	1698
35°	1720	1648	1634
40°	1665	1591	1572
45°	1610	1534	1509
50°	1549	1474	1436
55°	1486	1404	1370
60°	1415	1322	1293
65°	1337	1237	1202
70°	1238	1133	1105
75°	1100	1009	1015
80°	935	850	843
85°	677	577	559

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1610 cd/sqm

TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	228.6	2.2
10°-20°	643.2	6.1
20°-30°	945.2	8.9
30°-40°	1097.8	10.4
40°-50°	1096.5	10.4
50°-60°	956.1	9.0
60°-70°	706.8	6.7
70°-80°	399.9	3.8
80°-90°	108.2	1.0
90°-100°	49.6	0.5
100°-110°	185.0	1.7
110°-120°	490.6	4.6
120°-130°	813.6	7.7
130°-140°	864.3	8.2
140°-150°	803.2	7.6
150°-160°	645.8	6.1
160°-170°	416.1	3.9
170°-180°	143.2	1.4
0°-30°	1817.0	17.2
0°-40°	2914.9	27.5
0°-60°	4967.4	46.9
0°-90°	6182.2	58.4
90°-120°	725.2	6.8
90°-150°	3206.2	30.3
90°-180°	4411.0	41.6
0°-180°	10593.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2429	2429	2429	2429	2429	
5°	2429	2420	2394	2412	2408	231
15°	2312	2298	2268	2277	2266	651
25°	2093	2074	2034	2039	2034	963
35°	1805	1782	1745	1730	1719	1127
45°	1469	1453	1418	1392	1383	1134
55°	1112	1098	1070	1042	1030	994
65°	750	736	712	691	680	741
75°	392	388	376	362	367	419
85°	96	94	91	84	82	107
90°	1	13	22	27	29	10
95°	71	35	42	48	47	84
105°	331	364	66	78	83	354
115°	626	644	672	168	89	616
125°	885	899	920	928	931	789
135°	1095	1113	1122	1134	1131	846
145°	1271	1270	1288	1296	1290	795
155°	1399	1389	1402	1409	1400	645
165°	1474	1468	1471	1478	1471	416
175°	1508	1500	1502	1510	1499	144
180°	1505	1505	1505	1505	1505	

TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2428.8	2428.8	2428.8	2428.8	2428.8
2.5°	2442.9	2431.2	2405.5	2428.8	2424.3
5°	2428.8	2419.7	2393.9	2412.4	2408.0
7.5°	2412.4	2398.5	2372.8	2391.7	2386.9
10°	2386.9	2370.5	2342.5	2361.2	2354.2
12.5°	2351.7	2337.9	2309.9	2321.5	2316.8
15°	2312.1	2298.2	2267.7	2277.2	2265.5
17.5°	2263.0	2249.2	2218.7	2230.3	2218.7
20°	2209.2	2195.4	2162.7	2169.6	2160.4
22.5°	2155.7	2134.7	2104.2	2104.2	2099.4
25°	2092.6	2073.9	2034.3	2038.8	2034.3
27.5°	2022.4	2006.1	1975.9	1968.9	1957.2
30°	1952.6	1933.7	1898.8	1891.9	1882.4
32.5°	1877.7	1863.9	1826.4	1812.3	1802.9
35°	1805.4	1782.1	1744.6	1730.5	1718.9
37.5°	1723.6	1702.5	1665.1	1648.8	1637.1
40°	1639.6	1620.8	1583.3	1562.5	1553.1
42.5°	1557.8	1539.0	1501.8	1478.3	1464.4
45°	1469.1	1452.8	1417.6	1392.0	1382.6
47.5°	1382.6	1366.3	1328.8	1303.1	1289.2
50°	1291.5	1279.8	1247.1	1214.4	1202.7
52.5°	1202.7	1186.4	1156.2	1130.4	1114.0
55°	1111.8	1097.7	1069.7	1041.7	1030.0
57.5°	1020.7	1009.0	978.5	950.5	941.1
60°	929.4	920.2	887.6	861.8	854.9
62.5°	840.7	824.4	801.1	777.8	768.4
65°	749.8	735.7	712.4	691.3	679.7
67.5°	656.4	644.5	623.7	607.3	597.9
70°	569.9	560.5	539.4	523.1	513.9
72.5°	481.2	471.8	460.1	443.8	436.8
75°	392.3	387.8	375.9	362.0	366.8
77.5°	313.0	303.5	298.8	291.9	285.0
80°	233.6	231.2	226.5	219.5	214.8
82.5°	158.8	158.8	156.6	147.2	147.2
85°	95.7	93.5	91.2	84.0	81.8
87.5°	42.1	37.5	32.7	25.8	23.3
90°	1.1	13.0	21.8	27.3	29.3
92.5°	27.3	22.9	26.1	28.4	29.3
95°	70.7	34.8	42.4	48.0	46.8
97.5°	127.3	38.2	55.5	58.9	59.8
100°	192.8	43.6	62.1	70.7	72.9
102.5°	264.6	262.4	64.3	76.2	79.5
105°	331.0	363.7	66.4	78.4	82.8
107.5°	408.3	435.4	68.7	80.5	85.0
110°	482.4	505.2	190.6	81.7	86.0

TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	552.1	571.6	553.1	83.8	87.1
115°	626.1	644.5	671.8	167.7	89.3
117.5°	690.3	712.0	730.7	574.8	289.6
120°	762.1	778.5	798.1	811.2	664.1
122.5°	823.0	840.5	862.4	868.9	870.0
125°	885.1	899.4	920.1	927.6	930.9
127.5°	941.7	957.0	973.5	984.3	985.3
130°	995.1	1012.6	1024.5	1036.5	1035.5
132.5°	1049.6	1063.8	1075.7	1085.6	1084.5
135°	1095.4	1112.9	1122.5	1133.5	1131.3
137.5°	1143.2	1156.3	1167.2	1178.1	1174.9
140°	1190.0	1198.8	1210.7	1220.5	1215.1
142.5°	1229.3	1237.0	1251.1	1259.7	1254.3
145°	1270.7	1269.5	1288.0	1295.7	1290.2
147.5°	1306.5	1303.2	1321.8	1327.2	1322.9
150°	1341.4	1333.8	1351.2	1357.7	1352.3
152.5°	1370.7	1362.1	1378.4	1385.0	1377.3
155°	1399.1	1389.4	1402.4	1408.9	1400.3
157.5°	1421.9	1413.3	1423.1	1430.7	1421.9
160°	1441.6	1435.0	1441.6	1448.0	1440.5
162.5°	1458.9	1452.5	1457.9	1465.5	1455.7
165°	1474.2	1467.8	1471.0	1478.5	1471.0
167.5°	1486.2	1479.6	1483.0	1490.6	1480.8
170°	1496.0	1489.4	1491.7	1499.2	1489.4
172.5°	1502.5	1496.0	1498.3	1505.8	1496.0
175°	1508.0	1500.3	1502.5	1510.1	1499.2
177.5°	1510.1	1502.5	1503.7	1511.3	1501.5
180°	1504.7	1504.7	1504.7	1504.7	1504.7

TEST NUMBER: P923751

CATALOG NUMBER: DFN2DIP-TR4F0-070D050US940-FLLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	10.29	11.23	11.17	12.13	13.28	9.86	10.80	10.74	11.70	12.85
	3H	11.95	12.80	12.85	13.71	14.88	11.48	12.33	12.38	13.24	14.41
	4H	12.55	13.34	13.45	14.26	15.44	12.07	12.87	12.98	13.79	14.97
	6H	12.95	13.69	13.87	14.61	15.80	12.47	13.21	13.40	14.13	15.33
	8H	13.06	13.76	13.98	14.70	15.89	12.58	13.28	13.51	14.22	15.42
	12H	13.11	13.78	14.04	14.71	15.93	12.63	13.29	13.56	14.23	15.45
4H	2H	10.76	11.56	11.67	12.48	13.66	10.42	11.21	11.33	12.13	13.31
	3H	12.63	13.30	13.56	14.25	15.44	12.24	12.91	13.17	13.86	15.05
	4H	13.35	13.96	14.29	14.90	16.12	12.94	13.55	13.88	14.50	15.72
	6H	13.87	14.40	14.82	15.36	16.58	13.46	13.99	14.41	14.95	16.17
	8H	14.02	14.51	14.97	15.47	16.71	13.61	14.10	14.56	15.06	16.30
	12H	14.10	14.54	15.07	15.52	16.76	13.68	14.12	14.65	15.10	16.34
8H	4H	13.55	14.04	14.50	15.01	16.24	13.19	13.68	14.14	14.65	15.88
	6H	14.19	14.59	15.17	15.60	16.83	13.83	14.23	14.80	15.23	16.47
	8H	14.41	14.77	15.40	15.76	17.01	14.04	14.40	15.03	15.39	16.64
	12H	14.54	14.86	15.53	15.85	17.15	14.16	14.48	15.15	15.46	16.76
12H	4H	13.54	13.99	14.51	14.96	16.21	13.19	13.63	14.16	14.61	15.85
	6H	14.22	14.58	15.21	15.57	16.82	13.87	14.23	14.85	15.22	16.47
	8H	14.46	14.78	15.45	15.77	17.07	14.11	14.42	15.10	15.41	16.71

END OF REPORT