

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P926552

Luminaire Tested: DFN2DIP-TR4F0-090D050US950-RLLFLL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P926552
REPORT IS A COMBINATION OF REPORTS P900398 AND P897293
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-TR4F0-090D050US950-RLLFLL
Description: 4 foot, Triangle Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Frosted Lens
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11519.6 lumens
Efficiency: N/A
Efficacy: 91.9 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 3.43' x L: 3.96' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 125.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.099
Total Harmonic Distortion (THDi): 0.979
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P926552
CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

Luminous Intensity Polar Plot





TEST NUMBER: P926552

CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	110	110	110	110	104	104	104	104	91	91	91	79	79	79	68	68	68	63	63	63	63
1	101	97	93	90	95	91	88	85	81	78	76	71	69	67	61	60	59	55	55	55	55
2	93	86	80	75	87	81	75	71	71	67	64	63	60	57	55	53	51	47	47	47	47
3	85	76	69	63	80	72	65	60	64	59	54	56	52	49	49	46	44	40	40	40	40
4	78	68	60	54	73	64	57	52	57	51	47	50	46	43	44	41	38	35	35	35	35
5	72	61	53	47	68	57	50	45	51	45	41	46	41	37	40	37	34	31	31	31	31
6	67	55	47	41	62	52	45	39	47	41	36	41	37	33	37	33	30	27	27	27	27
7	62	50	42	36	58	47	40	35	42	37	32	38	33	30	34	30	27	25	25	25	25
8	58	45	38	32	54	43	36	31	39	33	29	35	30	27	31	27	24	22	22	22	22
9	54	42	34	29	51	40	33	28	36	30	26	32	28	24	29	25	22	20	20	20	20
10	50	38	31	26	47	37	30	25	33	28	24	30	25	22	27	23	20	18	18	18	18

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2819	2819	2819
5°	2824	2774	2792
10°	2796	2720	2701
15°	2757	2630	2561
20°	2706	2506	2388
25°	2654	2367	2222
30°	2584	2225	2010
35°	2516	2071	1825
40°	2446	1913	1612
45°	2365	1737	1420
50°	2281	1560	1231
55°	2194	1370	1051
60°	2092	1172	865
65°	1976	970	778
70°	1835	782	704
75°	1657	689	640
80°	1400	578	555
85°	975	386	417

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2365 cd/sqm



TEST NUMBER: P926552

CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	332.6	2.9
10°-20°	913.0	7.9
20°-30°	1281.8	11.1
30°-40°	1397.3	12.1
40°-50°	1284.2	11.1
50°-60°	1008.6	8.8
60°-70°	656.5	5.7
70°-80°	337.9	2.9
80°-90°	90.6	0.8
90°-100°	93.4	0.8
100°-110°	296.6	2.6
110°-120°	507.6	4.4
120°-130°	667.5	5.8
130°-140°	749.3	6.5
140°-150°	734.8	6.4
150°-160°	616.4	5.4
160°-170°	408.8	3.5
170°-180°	142.9	1.2
0°-30°	2527.4	21.9
0°-40°	3924.6	34.1
0°-60°	6217.4	54.0
0°-90°	7302.4	63.4
90°-120°	897.5	7.8
90°-150°	3049.2	26.5
90°-180°	4217.0	36.6
0°-180°	11519.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3549	3549	3549	3549	3549	
5°	3549	3533	3491	3520	3510	336
15°	3375	3340	3231	3170	3138	951
25°	3064	2961	2749	2617	2569	1409
35°	2640	2476	2194	1991	1920	1652
45°	2158	1943	1606	1378	1300	1667
55°	1641	1390	1044	851	790	1466
65°	1108	848	559	450	440	1099
75°	591	366	257	234	231	625
85°	138	70	61	61	61	158
90°	1	16	45	42	43	11
95°	66	79	81	81	79	74
105°	274	277	280	282	282	289
115°	509	517	514	513	509	504
125°	741	752	749	744	743	662
135°	958	972	975	974	970	741
145°	1163	1172	1180	1181	1176	727
155°	1330	1334	1338	1344	1340	612
165°	1447	1446	1446	1455	1449	408
175°	1506	1502	1500	1509	1501	143
180°	1509	1509	1509	1509	1509	



TEST NUMBER: P926552

CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3548.6	3548.6	3548.6	3548.6	3548.6
2.5°	3564.6	3548.6	3513.1	3545.5	3539.1
5°	3548.6	3532.6	3490.7	3519.6	3510.1
7.5°	3519.6	3500.5	3455.6	3468.2	3452.1
10°	3481.1	3458.6	3394.6	3384.7	3365.6
12.5°	3433.1	3404.2	3317.2	3298.2	3262.7
15°	3375.2	3339.8	3230.7	3169.7	3137.7
17.5°	3307.7	3256.3	3121.3	3050.8	2999.4
20°	3230.7	3166.3	3005.8	2925.7	2854.8
22.5°	3147.2	3073.3	2886.9	2777.9	2729.9
25°	3063.8	2960.8	2749.0	2617.4	2569.0
27.5°	2964.3	2854.8	2620.4	2469.5	2395.6
30°	2858.3	2736.0	2479.1	2315.5	2228.6
32.5°	2755.3	2607.5	2344.5	2151.7	2071.2
35°	2639.9	2476.0	2193.5	1991.2	1920.3
37.5°	2527.4	2350.7	2052.1	1830.3	1750.3
40°	2408.6	2216.0	1904.3	1676.4	1592.9
42.5°	2286.5	2081.2	1756.7	1519.0	1438.8
45°	2158.1	1942.8	1605.8	1377.5	1300.5
47.5°	2036.1	1808.2	1461.3	1233.0	1162.5
50°	1901.2	1673.2	1320.0	1098.1	1031.0
52.5°	1769.4	1528.5	1185.1	973.1	912.1
55°	1640.9	1390.5	1043.6	851.2	790.1
57.5°	1509.4	1252.5	918.6	738.7	687.3
60°	1374.4	1117.5	786.8	623.2	571.7
62.5°	1243.0	986.1	674.3	520.3	494.7
65°	1108.0	847.7	558.8	449.7	439.9
67.5°	979.6	719.2	449.7	394.9	385.3
70°	844.7	594.2	372.4	340.4	327.4
72.5°	716.2	478.3	311.4	285.8	279.4
75°	590.8	366.0	256.9	234.4	231.3
77.5°	465.7	260.0	202.3	189.5	183.0
80°	349.9	186.4	154.0	141.4	141.4
82.5°	243.9	125.4	106.0	99.5	99.5
85°	137.9	70.5	61.0	61.0	61.0
87.5°	51.4	25.6	25.6	22.5	22.5
90°	1.3	16.4	44.6	41.9	43.2
92.5°	28.2	38.2	39.6	40.9	40.9
95°	66.4	79.2	81.4	81.4	79.2
97.5°	110.5	122.3	127.4	127.4	127.4
100°	161.4	171.9	175.5	175.5	174.2
102.5°	215.1	222.9	227.8	229.2	227.8
105°	273.8	277.4	280.2	282.4	282.4
107.5°	332.0	337.4	337.4	338.4	332.0
110°	388.4	395.7	395.7	395.7	392.0



TEST NUMBER: P926552

CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	449.3	457.1	455.7	452.1	449.3
115°	509.3	516.7	514.4	513.1	509.3
117.5°	569.0	579.0	572.6	569.0	565.3
120°	629.0	639.0	629.0	629.0	624.9
122.5°	683.5	696.3	689.9	686.3	683.5
125°	740.9	752.2	748.6	744.5	743.2
127.5°	796.8	810.9	805.9	800.4	796.8
130°	849.2	865.5	863.2	860.5	855.5
132.5°	907.8	920.5	921.5	915.1	911.5
135°	958.3	972.3	975.1	973.7	970.1
137.5°	1014.7	1026.0	1028.3	1027.4	1021.9
140°	1064.2	1075.6	1081.9	1081.9	1077.0
142.5°	1115.1	1126.6	1130.2	1131.5	1126.6
145°	1163.4	1172.5	1179.7	1181.1	1176.1
147.5°	1206.6	1218.0	1223.4	1225.7	1220.6
150°	1251.2	1258.9	1263.9	1268.0	1263.9
152.5°	1290.8	1298.5	1304.8	1309.8	1304.8
155°	1330.3	1333.9	1338.0	1344.4	1340.3
157.5°	1364.4	1367.1	1369.4	1378.5	1372.1
160°	1394.8	1397.6	1398.9	1406.7	1401.2
162.5°	1423.1	1423.1	1424.4	1433.1	1426.7
165°	1447.2	1445.8	1445.8	1454.9	1448.6
167.5°	1469.0	1464.9	1464.9	1474.0	1467.6
170°	1485.4	1481.8	1480.4	1489.5	1481.8
172.5°	1496.7	1493.1	1491.8	1500.8	1493.1
175°	1505.9	1502.2	1499.5	1508.6	1500.8
177.5°	1510.8	1507.2	1504.5	1512.2	1504.5
180°	1508.6	1508.6	1508.6	1508.6	1508.6



TEST NUMBER: P926552
 CATALOG NUMBER: DFN2DIP-TR4F0-090D050US950-RLLFLL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.91	12.86	12.75	13.72	14.79	7.88	8.84	8.72	9.69	10.76
	3H	13.59	14.45	14.45	15.31	16.41	9.08	9.93	9.93	10.80	11.90
	4H	14.21	15.01	15.08	15.89	16.99	9.54	10.34	10.41	11.21	12.32
	6H	14.64	15.38	15.52	16.26	17.38	9.87	10.61	10.75	11.49	12.61
	8H	14.77	15.47	15.66	16.37	17.49	9.96	10.66	10.85	11.56	12.68
	12H	14.83	15.50	15.73	16.39	17.54	10.01	10.68	10.90	11.57	12.72
4H	2H	11.94	12.75	12.82	13.62	14.73	8.49	9.30	9.37	10.17	11.28
	3H	13.78	14.45	14.67	15.36	16.48	9.85	10.52	10.74	11.43	12.55
	4H	14.48	15.09	15.38	15.99	17.14	10.41	11.02	11.30	11.92	13.07
	6H	15.00	15.52	15.91	16.45	17.60	10.83	11.36	11.75	12.28	13.44
	8H	15.18	15.67	16.09	16.59	17.75	10.97	11.46	11.88	12.38	13.54
	12H	15.28	15.72	16.21	16.66	17.83	11.04	11.48	11.97	12.42	13.59
8H	4H	14.46	14.94	15.37	15.86	17.03	10.70	11.19	11.61	12.11	13.27
	6H	15.03	15.43	15.97	16.39	17.55	11.22	11.62	12.16	12.59	13.75
	8H	15.24	15.60	16.19	16.55	17.73	11.41	11.77	12.36	12.72	13.90
	12H	15.39	15.70	16.34	16.65	17.88	11.54	11.85	12.49	12.80	14.03
12H	4H	14.41	14.85	15.35	15.79	16.96	10.71	11.15	11.64	12.09	13.25
	6H	15.00	15.36	15.95	16.31	17.49	11.27	11.63	12.22	12.58	13.76
	8H	15.23	15.54	16.18	16.49	17.72	11.49	11.80	12.44	12.75	13.98