

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P902165

Luminaire Tested: DFN2DIP-4P2F0-040D020US830-RLLONL

Issue Date: 11/21/2024

Test Information

Test Method: LM-79-2019
Report Number: P902165
REPORT IS A COMBINATION OF REPORTS P900536 AND P897455
Test Lab: INNOVATION CENTER
Issue Date: 11/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: DFN2DIP-4P2F0-040D020US830-RLLONL
Description: 2 foot, 90deg - 4way Define Geo, with Direct 1in Regressed Frosted Lens, Indirect Open No Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5070.8 lumens
Efficiency: N/A
Efficacy: 90.4 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 0.99 / 1.16
Luminous Opening: Rectangular w/ Sides (W: 2.07' x L: 2.07' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 56.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: 0.983
Total Harmonic Distortion (THDi): 0.073
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLLONL

Luminous Intensity Polar Plot



TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLONL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	110	110	110	110	103	103	103	103	91	91	91	79	79	79	68	68	68
1	101	97	93	90	95	91	88	85	80	78	76	71	69	67	61	60	59
2	93	86	80	75	87	81	75	71	71	67	64	63	60	57	55	52	51
3	85	76	69	63	80	72	65	60	63	58	54	56	52	49	49	46	44
4	78	68	60	54	73	64	57	52	57	51	47	50	46	43	44	41	38
5	72	61	53	47	67	57	50	45	51	45	41	46	41	37	40	37	34
6	67	55	47	41	62	52	45	39	46	41	36	41	37	33	37	33	30
7	62	50	42	36	58	47	40	35	42	36	32	38	33	30	34	30	27
8	58	45	38	32	54	43	36	31	39	33	29	35	30	27	31	27	24
9	54	42	34	29	51	40	33	28	36	30	26	32	27	24	29	25	22
10	50	38	31	26	47	37	30	25	33	28	24	30	25	22	27	23	20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3902	3902	3902
5°	3900	3830	3858
10°	3854	3745	3726
15°	3793	3611	3526
20°	3715	3432	3283
25°	3635	3232	3048
30°	3531	3028	2753
35°	3428	2810	2493
40°	3323	2585	2198
45°	3201	2337	1929
50°	3075	2088	1668
55°	2943	1823	1417
60°	2789	1547	1161
65°	2612	1268	1037
70°	2398	1008	929
75°	2127	870	833
80°	1739	703	703
85°	1122	433	496

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3201 cd/sqm

TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLLONL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	146.0	2.9
10°-20°	400.9	7.9
20°-30°	562.8	11.1
30°-40°	613.5	12.1
40°-50°	563.9	11.1
50°-60°	442.9	8.7
60°-70°	288.3	5.7
70°-80°	148.4	2.9
80°-90°	39.0	0.8
90°-100°	21.0	0.4
100°-110°	78.2	1.5
110°-120°	207.4	4.1
120°-130°	344.0	6.8
130°-140°	365.4	7.2
140°-150°	339.6	6.7
150°-160°	273.0	5.4
160°-170°	175.9	3.5
170°-180°	60.6	1.2
0°-30°	1109.8	21.9
0°-40°	1723.3	34.0
0°-60°	2730.1	53.8
0°-90°	3205.7	63.2
90°-120°	306.6	6.0
90°-150°	1355.6	26.7
90°-180°	1865.0	36.8
0°-180°	5070.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1558	1558	1558	1558	1558	
5°	1558	1551	1533	1546	1541	148
15°	1482	1466	1419	1392	1378	418
25°	1345	1300	1207	1149	1128	619
35°	1159	1087	963	874	843	726
45°	948	853	705	605	571	732
55°	721	611	458	374	347	644
65°	486	372	245	198	193	482
75°	259	161	113	103	102	274
85°	61	31	27	27	27	70
90°	0	6	9	12	12	5
95°	30	15	18	20	20	35
105°	140	154	28	33	35	150
115°	265	272	284	71	38	261
125°	374	380	389	392	394	334
135°	463	470	475	479	478	358
145°	537	537	545	548	546	336
155°	592	587	593	596	592	273
165°	623	621	622	625	622	176
175°	638	634	635	638	634	61
180°	636	636	636	636	636	

TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLLONL

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1558.2	1558.2	1558.2	1558.2	1558.2
2.5°	1565.3	1558.2	1542.7	1556.9	1554.0
5°	1558.2	1551.1	1532.8	1545.5	1541.3
7.5°	1545.5	1537.1	1517.4	1522.9	1515.9
10°	1528.6	1518.7	1490.5	1486.2	1477.9
12.5°	1507.5	1494.8	1456.6	1448.2	1432.7
15°	1482.1	1466.5	1418.6	1391.9	1377.8
17.5°	1452.5	1429.8	1370.6	1339.6	1317.0
20°	1418.6	1390.3	1319.8	1284.7	1253.6
22.5°	1382.0	1349.5	1267.6	1219.7	1198.7
25°	1345.3	1300.1	1207.0	1149.3	1128.0
27.5°	1301.7	1253.6	1150.7	1084.4	1051.9
30°	1255.1	1201.4	1088.5	1016.7	978.6
32.5°	1209.9	1145.0	1029.4	944.8	909.5
35°	1159.2	1087.2	963.2	874.3	843.2
37.5°	1109.8	1032.2	901.1	803.7	768.5
40°	1057.6	973.1	836.2	736.1	699.5
42.5°	1004.0	913.8	771.4	666.9	631.8
45°	947.6	853.1	705.1	604.9	571.1
47.5°	894.1	794.0	641.7	541.5	510.5
50°	834.8	734.7	579.6	482.2	452.7
52.5°	776.9	671.2	520.4	427.3	400.5
55°	720.6	610.6	458.3	373.7	346.9
57.5°	662.8	550.0	403.3	324.3	301.8
60°	603.5	490.7	345.4	273.6	251.1
62.5°	545.8	433.0	296.1	228.5	217.3
65°	486.5	372.2	245.3	197.5	193.1
67.5°	430.2	315.8	197.5	173.4	169.2
70°	370.9	260.9	163.5	149.5	143.7
72.5°	314.5	210.1	136.8	125.5	122.7
75°	259.4	160.7	112.8	102.9	101.6
77.5°	204.5	114.1	88.9	83.2	80.3
80°	153.6	81.8	67.6	62.1	62.1
82.5°	107.2	55.0	46.6	43.6	43.6
85°	60.6	31.0	26.8	26.8	26.8
87.5°	22.6	11.2	11.2	9.9	9.9
90°	0.5	5.6	9.1	11.5	12.4
92.5°	11.5	9.7	11.0	12.0	12.4
95°	29.9	14.7	17.9	20.3	19.8
97.5°	53.8	16.1	23.5	24.9	25.4
100°	81.5	18.4	26.2	29.9	30.8
102.5°	111.9	110.9	27.1	32.2	33.6
105°	140.0	153.7	28.1	33.1	35.0
107.5°	172.7	184.1	29.0	34.0	35.9
110°	204.0	213.6	80.6	34.6	36.4

TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLLONL

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	233.4	241.7	233.8	35.4	36.9
115°	264.7	272.5	284.1	70.9	37.8
117.5°	291.8	301.0	308.9	243.1	122.4
120°	322.3	329.1	337.4	343.0	280.8
122.5°	348.0	355.3	364.6	367.3	367.9
125°	374.3	380.2	389.0	392.2	393.6
127.5°	398.2	404.6	411.6	416.1	416.6
130°	420.8	428.1	433.2	438.3	437.8
132.5°	443.7	449.8	454.8	458.9	458.5
135°	463.2	470.5	474.6	479.3	478.3
137.5°	483.3	488.9	493.5	498.1	496.7
140°	503.1	506.9	511.9	516.0	513.8
142.5°	519.7	523.0	529.0	532.6	530.3
145°	537.2	536.8	544.6	547.8	545.5
147.5°	552.4	551.0	558.8	561.1	559.3
150°	567.1	563.9	571.3	574.0	571.7
152.5°	579.6	575.9	582.8	585.6	582.3
155°	591.5	587.4	593.0	595.7	592.0
157.5°	601.2	597.6	601.7	604.9	601.2
160°	609.5	606.7	609.5	612.3	609.1
162.5°	616.8	614.1	616.4	619.6	615.5
165°	623.3	620.6	621.9	625.2	621.9
167.5°	628.4	625.6	627.0	630.3	626.0
170°	632.5	629.7	630.7	633.9	629.7
172.5°	635.3	632.5	633.5	636.7	632.5
175°	637.5	634.3	635.3	638.5	633.9
177.5°	638.5	635.3	635.7	638.9	634.8
180°	636.2	636.2	636.2	636.2	636.2

TEST NUMBER: P902165

CATALOG NUMBER: DFN2DIP-4P2F0-040D020US830-RLONL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.90	13.85	13.74	14.71	15.78	8.85	9.81	9.70	10.66	11.74
	3H	14.56	15.41	15.41	16.28	17.38	10.03	10.88	10.89	11.75	12.85
	4H	15.16	15.96	16.03	16.84	17.95	10.47	11.28	11.34	12.15	13.26
	6H	15.57	16.31	16.45	17.19	18.31	10.78	11.52	11.66	12.40	13.53
	8H	15.69	16.39	16.58	17.29	18.41	10.87	11.57	11.76	12.47	13.59
	12H	15.74	16.41	16.64	17.31	18.45	10.90	11.57	11.80	12.47	13.61
4H	2H	12.92	13.73	13.80	14.60	15.71	9.45	10.26	10.33	11.13	12.24
	3H	14.74	15.40	15.62	16.31	17.44	10.79	11.46	11.68	12.36	13.49
	4H	15.42	16.02	16.31	16.93	18.08	11.32	11.93	12.22	12.83	13.99
	6H	15.91	16.44	16.83	17.36	18.52	11.73	12.25	12.64	13.18	14.33
	8H	16.08	16.57	17.00	17.49	18.66	11.85	12.33	12.76	13.26	14.42
	12H	16.17	16.61	17.10	17.55	18.72	11.91	12.34	12.84	13.28	14.46
8H	4H	15.39	15.87	16.30	16.80	17.96	11.60	12.09	12.52	13.01	14.18
	6H	15.93	16.33	16.87	17.30	18.46	12.09	12.50	13.04	13.46	14.63
	8H	16.13	16.49	17.09	17.45	18.63	12.27	12.63	13.22	13.58	14.76
	12H	16.26	16.58	17.22	17.52	18.76	12.38	12.69	13.33	13.64	14.87
12H	4H	15.34	15.78	16.28	16.72	17.89	11.61	12.05	12.54	12.99	14.16
	6H	15.91	16.26	16.86	17.22	18.40	12.14	12.49	13.09	13.45	14.63
	8H	16.12	16.43	17.07	17.38	18.61	12.34	12.65	13.29	13.60	14.83