

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331766-930

Luminaire Tested: **S122RDIW-S290D435U930-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P331766-930
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-8,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S122RDIW-S290D435U930-4F0-1E-UDD-A1
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 290 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 435 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2146.8 lumens
Efficiency: N/A
Efficacy: 93.3 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 1.16 / 1.02
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 23
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	105	105	105	105	96	96	96	96	79	79	79	64	64	64	50	50	50	43
1	97	93	89	86	88	85	82	79	71	68	66	57	56	54	45	44	43	37
2	89	82	76	71	81	75	70	66	63	59	56	51	49	47	40	39	37	33
3	81	73	66	60	74	67	61	56	56	52	48	46	43	40	36	34	33	28
4	75	65	57	52	68	60	53	48	50	45	42	41	38	35	33	31	29	25
5	69	58	50	45	63	54	47	42	45	40	36	37	34	31	30	28	26	22
6	64	52	45	39	58	48	42	37	41	36	32	34	30	28	28	25	23	20
7	59	48	40	35	54	44	37	33	37	32	29	31	28	25	26	23	21	18
8	55	43	36	31	50	40	34	29	34	29	26	29	25	22	24	21	19	17
9	51	40	33	28	47	37	31	26	32	27	23	27	23	20	22	19	17	15
10	48	37	30	25	44	34	28	24	29	24	21	25	21	18	21	18	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	8606	8606	8606	8606
5°	9611	8660	7679	8660
10°	10663	8599	6655	8599
15°	11188	8473	5244	8473
20°	9699	8285	4538	8285
25°	6360	8031	4051	8031
30°	4282	7720	3667	7720
35°	3467	7330	3307	7330
40°	3084	6905	3060	6905
45°	2790	6405	2731	6405
50°	2539	5913	2532	5913
55°	2387	5362	2356	5362
60°	1999	4863	1973	4863
65°	1685	4413	1910	4413
70°	1553	3942	1803	3942
75°	1454	3431	1666	3431
80°	1339	2827	1478	2827
85°	1241	2242	1297	2242



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.5	2.4
10°-20°	140.8	6.6
20°-30°	181.4	8.5
30°-40°	172.4	8.0
40°-50°	147.7	6.9
50°-60°	112.5	5.2
60°-70°	71.1	3.3
70°-80°	35.5	1.7
80°-90°	11.0	0.5
90°-100°	27.7	1.3
100°-110°	86.1	4.0
110°-120°	147.2	6.9
120°-130°	193.6	9.0
130°-140°	217.3	10.1
140°-150°	213.1	9.9
150°-160°	178.7	8.3
160°-170°	118.6	5.5
170°-180°	41.4	1.9
0°-30°	372.7	17.4
0°-40°	545.1	25.4
0°-60°	805.3	37.5
0°-90°	922.9	43.0
90°-120°	261.1	12.2
90°-150°	885.2	41.2
90°-180°	1224.0	57.0
0°-180°	2146.8	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	533	533	533	533	533	
5°	593	534	474	534	593	59
15°	669	507	314	507	669	181
25°	357	451	227	451	357	169
35°	176	372	168	372	176	113
45°	122	280	120	280	122	95
55°	85	190	84	190	85	74
65°	44	116	50	116	44	45
75°	23	55	27	55	23	25
85°	7	12	7	12	7	7
90°	13	0	13	0	13	6
95°	23	19	23	19	23	26
105°	82	79	82	79	82	86
115°	148	148	148	148	148	146
125°	216	215	216	215	216	192
135°	281	278	281	278	281	217
145°	341	338	341	338	341	213
155°	389	386	389	386	389	179
165°	420	420	420	420	420	119
175°	436	437	436	437	436	41
180°	438	438	438	438	438	



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	554.6	555.1	555.5	554.5	554.5	553.6	551.6	550.2	546.0	545.4	545.4
5°	593.0	592.6	593.4	590.9	587.7	586.9	583.3	578.7	573.9	568.6	567.4
7.5°	631.1	630.6	629.1	628.7	626.1	620.5	614.9	608.9	600.9	593.0	589.1
10°	650.4	656.6	652.8	646.4	647.6	639.0	634.3	626.3	619.6	608.0	605.4
12.5°	669.4	671.8	670.6	666.9	665.3	659.3	653.0	646.0	633.7	623.3	614.2
15°	669.3	672.8	673.8	672.6	673.5	673.2	669.8	664.1	653.4	641.9	631.9
17.5°	619.9	622.3	628.4	632.5	637.7	648.7	654.1	656.2	654.6	648.0	641.0
20°	564.5	560.4	577.5	586.1	593.5	612.0	628.0	634.1	643.9	643.8	641.9
22.5°	485.9	486.9	503.0	513.4	535.0	553.6	571.7	594.7	613.7	626.2	633.6
25°	357.0	364.1	380.2	394.3	418.3	452.8	484.1	520.4	554.6	581.7	607.5
27.5°	268.2	268.7	281.4	294.5	308.8	337.0	376.4	419.7	468.6	508.9	555.2
30°	229.7	228.5	233.9	241.9	254.1	276.0	305.6	348.1	396.9	457.6	511.7
32.5°	202.4	202.4	206.5	212.4	222.5	237.3	257.6	292.2	338.2	397.9	461.3
35°	175.9	175.8	178.7	183.0	187.2	196.7	210.6	228.7	260.4	316.1	380.9
37.5°	156.9	157.8	159.2	161.9	166.6	171.9	180.2	192.4	214.9	247.9	302.4
40°	146.3	146.7	148.7	150.9	153.7	157.8	164.6	174.5	190.9	217.2	257.1
42.5°	136.6	136.9	138.4	140.4	142.6	146.7	152.4	160.9	174.2	194.7	227.6
45°	122.2	122.2	123.5	124.4	126.9	130.5	135.2	142.3	151.5	166.6	188.5
47.5°	108.8	108.8	109.7	111.3	112.8	115.7	120.3	126.0	132.7	144.5	163.1
50°	101.1	101.3	101.8	103.1	104.1	106.6	110.2	115.2	122.2	131.3	146.8
52.5°	94.9	94.8	95.5	96.0	96.7	98.5	101.2	105.6	111.9	119.8	132.6
55°	84.8	84.1	85.2	86.1	86.7	87.4	88.9	91.6	97.0	103.7	113.3
57.5°	72.2	71.9	72.7	73.5	75.3	77.3	78.6	80.3	83.1	87.9	97.4
60°	61.9	61.9	63.5	64.1	66.1	68.7	71.3	72.8	75.6	78.7	85.8
62.5°	52.7	52.8	53.6	54.1	55.3	58.5	62.1	65.4	68.0	71.0	75.7
65°	44.1	44.4	44.4	44.8	45.6	46.3	47.8	50.4	55.0	59.3	62.8
67.5°	37.4	37.5	37.7	38.0	38.2	39.0	39.6	40.8	41.8	45.8	50.2
70°	32.9	33.5	33.3	33.7	33.9	34.2	35.0	35.5	37.3	38.2	40.8
72.5°	28.8	29.2	29.2	29.4	29.9	30.0	30.6	31.1	32.2	32.9	34.4
75°	23.3	23.2	23.3	23.7	23.9	24.1	24.1	24.8	25.4	26.1	27.1
77.5°	18.0	18.2	18.2	18.2	18.3	18.6	18.5	18.8	19.4	19.8	20.2
80°	14.4	14.6	14.4	14.6	14.8	15.0	14.8	15.0	15.6	15.9	15.9
82.5°	11.2	11.3	11.3	11.3	11.4	11.4	11.7	11.7	12.1	12.1	12.2
85°	6.7	6.5	6.5	6.5	6.7	6.8	6.7	6.7	6.8	6.8	6.8
87.5°	4.9	5.0	5.0	5.0	5.0	5.0	5.0	5.2	5.1	5.2	4.7
90°	12.6	12.5	12.4	12.3	12.2	12.3	12.5	12.6	12.8	13.0	11.1
92.5°	12.0	12.0	11.9	11.9	11.9	11.9	11.8	11.8	11.7	11.7	11.3
95°	22.9	23.1	23.2	23.4	23.6	23.6	23.6	23.6	23.6	23.6	23.5
97.5°	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.5
100°	50.6	50.7	50.8	50.9	51.0	51.0	51.0	51.0	51.0	51.0	50.7
102.5°	63.0	63.1	63.2	63.3	63.3	63.3	63.3	63.2	63.2	63.1	62.8
105°	82.0	82.0	82.0	82.0	82.0	81.9	81.8	81.6	81.4	81.3	81.1
107.5°	99.9	100.3	100.6	101.0	101.4	101.6	101.5	101.4	101.3	101.3	101.3
110°	113.7	114.0	114.2	114.5	114.7	114.9	114.9	114.9	114.9	114.9	114.9



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	127.1	127.3	127.4	127.6	127.8	128.0	128.2	128.4	128.6	128.7	128.8
115°	147.7	148.0	148.2	148.5	148.7	148.9	149.0	149.0	149.1	149.2	149.4
117.5°	167.5	167.7	168.0	168.2	168.4	168.7	168.8	169.1	169.3	169.5	169.9
120°	181.4	181.6	181.9	182.1	182.4	182.5	182.5	182.5	182.5	182.5	183.1
122.5°	194.9	195.1	195.3	195.5	195.7	195.8	196.1	196.2	196.5	196.7	197.1
125°	215.7	215.8	215.9	216.0	216.1	216.2	216.5	216.7	217.0	217.2	217.4
127.5°	234.6	234.9	235.1	235.4	235.7	235.9	236.3	236.5	236.8	237.2	237.4
130°	248.3	248.6	248.9	249.2	249.6	249.8	250.0	250.1	250.3	250.5	250.6
132.5°	261.2	261.5	261.7	262.0	262.3	262.6	262.9	263.3	263.7	264.0	264.0
135°	281.4	281.7	281.9	282.2	282.4	282.6	282.7	282.7	282.8	282.9	282.7
137.5°	299.8	300.1	300.4	300.8	301.1	301.3	301.3	301.4	301.5	301.6	301.3
140°	312.5	312.8	313.2	313.5	313.8	314.0	314.0	314.0	314.0	314.0	313.6
142.5°	324.0	324.3	324.7	325.0	325.3	325.5	325.4	325.3	325.3	325.2	324.9
145°	341.3	341.6	341.9	342.3	342.6	342.8	342.7	342.6	342.5	342.4	341.9
147.5°	356.8	357.0	357.3	357.7	358.0	358.1	357.9	357.7	357.5	357.3	357.0
150°	366.8	367.0	367.3	367.5	367.8	367.8	367.5	367.3	367.0	366.8	366.5
152.5°	376.3	376.6	376.8	377.2	377.5	377.5	377.2	376.8	376.6	376.3	375.9
155°	389.0	389.2	389.5	389.7	390.0	389.9	389.5	389.1	388.7	388.2	388.0
157.5°	399.9	400.3	400.6	401.0	401.5	401.4	400.8	400.2	399.7	399.2	399.0
160°	406.7	407.0	407.3	407.6	408.0	407.9	407.4	406.9	406.4	405.9	405.9
162.5°	412.6	412.9	413.4	413.8	414.2	414.1	413.5	412.9	412.4	411.9	411.8
165°	420.4	420.8	421.2	421.6	422.0	421.9	421.3	420.8	420.2	419.6	419.6
167.5°	426.7	427.1	427.5	428.0	428.4	428.4	427.8	427.2	426.6	426.1	426.1
170°	430.0	430.5	431.0	431.5	431.9	431.9	431.3	430.7	430.2	429.6	429.7
172.5°	432.6	433.1	433.6	434.1	434.6	434.6	434.0	433.4	432.8	432.3	432.4
175°	435.5	436.0	436.5	437.0	437.5	437.4	436.8	436.3	435.7	435.1	435.3
177.5°	436.8	437.2	437.7	438.0	438.4	438.4	438.0	437.7	437.2	436.8	436.9
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	545.8	544.5	543.5	540.9	539.5	536.5	536.1	536.0	532.1	528.4	527.3
5°	564.5	561.5	557.1	551.9	546.5	541.0	537.3	534.3	526.8	519.8	515.8
7.5°	583.3	577.0	569.3	559.5	551.3	542.2	535.3	529.2	518.7	508.6	501.8
10°	597.5	587.1	576.9	563.4	552.8	542.4	532.8	524.5	512.7	499.3	489.8
12.5°	606.2	594.8	580.7	567.5	553.8	540.6	527.7	517.1	503.1	489.3	478.2
15°	618.0	605.8	588.7	569.8	552.3	535.0	520.2	506.9	488.8	472.2	458.5
17.5°	627.7	610.8	592.6	570.7	550.3	528.5	509.4	492.4	472.1	452.2	436.1
20°	630.8	614.1	593.0	571.1	547.1	521.3	500.8	482.2	460.6	438.9	420.4
22.5°	628.8	615.9	592.4	566.2	541.6	514.7	491.5	469.9	445.9	423.8	402.4
25°	615.8	611.3	589.1	560.6	532.5	501.2	474.3	450.8	423.4	399.7	376.3
27.5°	585.3	594.9	581.1	550.7	519.4	485.9	455.7	428.9	400.5	373.8	350.6
30°	556.0	578.0	572.1	543.9	508.9	476.0	442.1	414.1	383.8	356.3	333.4
32.5°	515.8	552.2	558.0	534.4	498.2	462.0	426.5	398.7	367.0	338.1	315.7
35°	451.8	506.3	531.3	516.3	480.0	440.9	404.3	371.9	340.0	311.5	289.3
37.5°	375.6	449.8	491.5	492.5	459.2	418.6	378.6	346.4	313.8	285.8	261.8
40°	326.1	406.5	460.8	472.8	444.7	400.8	360.4	327.6	295.8	268.3	240.8
42.5°	281.7	361.7	428.4	449.4	427.1	383.4	342.9	308.7	277.7	251.8	223.6
45°	227.8	297.8	371.3	408.7	396.3	356.0	313.2	280.5	251.5	229.1	202.0
47.5°	192.2	241.5	312.7	363.2	363.1	326.2	284.1	252.9	225.9	204.9	183.0
50°	171.9	214.8	275.0	332.4	337.2	306.3	266.3	235.4	210.2	188.2	170.6
52.5°	153.6	189.1	243.1	298.2	311.9	285.1	246.3	217.8	193.3	173.0	158.0
55°	129.8	157.3	198.4	249.8	270.6	251.7	217.2	190.5	170.7	153.7	140.7
57.5°	109.8	130.4	163.4	204.8	228.9	217.1	188.7	167.0	150.0	134.6	124.4
60°	97.3	114.1	142.0	176.7	203.3	195.0	170.7	150.6	136.2	122.8	113.2
62.5°	85.4	99.9	123.8	152.0	176.3	172.9	153.1	136.2	123.5	111.4	103.2
65°	68.7	79.2	98.0	120.0	139.7	141.3	127.0	115.5	104.3	94.7	87.4
67.5°	54.7	61.6	74.8	93.4	108.0	113.3	104.6	95.8	86.8	79.4	73.1
70°	46.1	51.7	61.3	76.3	89.8	95.4	90.3	83.5	75.7	69.6	64.2
72.5°	37.3	42.8	49.9	60.9	72.5	78.5	76.7	71.8	65.6	60.4	55.4
75°	28.1	29.8	34.7	42.1	51.1	56.3	57.6	55.0	50.0	46.1	43.1
77.5°	20.8	21.9	24.1	28.0	33.9	38.6	40.4	40.1	36.7	34.5	31.6
80°	16.6	17.2	18.3	20.0	24.5	29.1	30.4	30.4	28.0	27.1	24.3
82.5°	12.6	13.0	13.8	14.7	16.7	20.8	22.3	22.5	21.0	19.8	17.6
85°	7.3	7.0	7.4	8.0	8.3	9.5	11.7	12.1	11.7	10.2	9.6
87.5°	4.4	4.2	3.8	3.3	3.3	3.3	3.8	4.4	4.0	3.8	3.6
90°	9.3	7.5	5.7	4.3	3.3	2.4	1.4	0.4	1.4	2.4	3.3
92.5°	10.9	10.4	10.0	9.5	8.7	8.0	7.3	6.6	7.3	8.0	8.7
95°	23.3	23.2	23.0	22.5	21.7	20.9	20.1	19.2	20.1	20.9	21.7
97.5°	39.1	38.8	38.5	38.0	37.3	36.5	35.8	35.1	35.8	36.5	37.3
100°	50.5	50.2	50.0	49.6	48.9	48.2	47.5	46.9	47.5	48.2	48.9
102.5°	62.5	62.1	61.9	61.4	60.9	60.3	59.8	59.4	59.8	60.3	60.9
105°	81.0	80.8	80.6	80.4	80.1	79.9	79.7	79.4	79.7	79.9	80.1
107.5°	101.3	101.3	101.3	101.1	100.8	100.4	100.0	99.6	100.0	100.4	100.8
110°	114.9	114.9	114.9	114.6	114.1	113.7	113.2	112.7	113.2	113.7	114.1



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	128.9	129.0	129.1	128.8	128.3	127.8	127.3	126.9	127.3	127.8	128.3
115°	149.5	149.7	149.9	149.7	149.2	148.7	148.2	147.7	148.2	148.7	149.2
117.5°	170.4	170.9	171.3	171.2	170.6	169.9	169.3	168.6	169.3	169.9	170.6
120°	183.8	184.4	185.1	185.1	184.4	183.8	183.1	182.5	183.1	183.8	184.4
122.5°	197.5	198.0	198.5	198.4	197.5	196.7	196.0	195.2	196.0	196.7	197.5
125°	217.7	217.9	218.2	217.9	217.2	216.5	215.7	215.0	215.7	216.5	217.2
127.5°	237.7	238.1	238.3	238.0	237.1	236.1	235.2	234.2	235.2	236.1	237.1
130°	250.8	250.9	251.1	250.6	249.6	248.5	247.4	246.4	247.4	248.5	249.6
132.5°	264.0	263.9	263.9	263.4	262.6	261.7	260.8	260.0	260.8	261.7	262.6
135°	282.6	282.4	282.3	281.8	280.9	280.0	279.1	278.2	279.1	280.0	280.9
137.5°	301.2	300.9	300.7	300.2	299.5	298.7	298.0	297.3	298.0	298.7	299.5
140°	313.2	312.7	312.3	311.8	311.0	310.3	309.6	308.8	309.6	310.3	311.0
142.5°	324.7	324.3	324.1	323.6	322.9	322.1	321.4	320.7	321.4	322.1	322.9
145°	341.4	341.0	340.5	339.9	339.3	338.8	338.2	337.6	338.2	338.8	339.3
147.5°	356.7	356.4	356.0	355.6	354.8	354.2	353.4	352.8	353.4	354.2	354.8
150°	366.2	365.8	365.5	365.1	364.6	364.1	363.6	363.1	363.6	364.1	364.6
152.5°	375.4	375.0	374.7	374.2	373.7	373.2	372.8	372.3	372.8	373.2	373.7
155°	387.8	387.5	387.3	387.0	386.8	386.5	386.2	386.0	386.2	386.5	386.8
157.5°	398.8	398.7	398.5	398.4	398.3	398.1	397.9	397.8	397.9	398.1	398.3
160°	405.8	405.7	405.6	405.5	405.4	405.2	405.0	404.9	405.0	405.2	405.4
162.5°	411.7	411.6	411.6	411.5	411.4	411.4	411.4	411.3	411.4	411.4	411.4
165°	419.6	419.6	419.6	419.6	419.7	419.8	419.9	420.0	419.9	419.8	419.7
167.5°	426.1	426.1	426.1	426.2	426.5	426.7	427.0	427.2	427.0	426.7	426.5
170°	429.7	429.8	429.9	430.1	430.3	430.6	430.8	431.0	430.8	430.6	430.3
172.5°	432.4	432.5	432.6	432.8	433.0	433.3	433.5	433.7	433.5	433.3	433.0
175°	435.5	435.6	435.8	436.0	436.3	436.5	436.8	437.0	436.8	436.5	436.3
177.5°	437.1	437.2	437.3	437.5	437.7	437.9	438.1	438.3	438.1	437.9	437.7
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	525.5	524.4	522.4	519.5	517.7	514.6	512.6	513.7	514.0	513.7	513.5
5°	511.4	507.4	502.1	496.8	492.0	486.9	483.9	482.7	480.0	478.6	477.8
7.5°	494.2	487.5	480.0	470.9	463.3	455.2	451.1	449.1	443.8	440.9	438.4
10°	481.5	470.9	463.3	451.5	444.3	433.7	426.5	426.7	419.5	415.4	412.5
12.5°	467.4	455.8	443.2	432.5	422.5	414.0	405.3	401.8	394.1	390.2	382.2
15°	444.1	430.6	417.3	402.8	392.6	379.4	366.9	351.5	339.1	328.3	325.4
17.5°	418.7	401.9	388.5	371.5	354.1	332.0	317.4	308.4	301.0	295.3	291.1
20°	401.1	384.1	369.8	344.3	320.7	305.7	295.1	288.1	280.4	274.3	270.9
22.5°	382.8	365.0	345.5	317.0	298.6	286.7	277.1	269.2	263.9	259.2	256.1
25°	356.7	337.2	305.2	285.6	270.8	258.1	251.5	246.7	241.2	234.6	231.7
27.5°	329.1	298.2	275.2	260.6	246.5	238.3	232.3	225.1	220.1	217.2	214.1
30°	308.5	277.6	259.7	243.7	233.7	224.6	217.6	213.5	208.7	203.7	201.7
32.5°	285.6	260.9	243.6	230.4	220.2	212.5	206.9	200.3	196.9	193.8	189.6
35°	257.1	238.3	222.6	211.9	202.2	195.9	189.5	185.6	179.3	176.7	175.0
37.5°	232.9	216.7	205.0	193.6	186.0	179.0	175.0	168.8	166.2	162.5	159.0
40°	219.2	203.3	192.1	182.8	174.2	169.1	164.1	159.1	155.0	153.4	149.1
42.5°	205.4	192.4	181.1	171.0	165.3	159.7	153.4	149.8	145.5	142.8	140.2
45°	186.1	174.6	165.0	156.7	150.3	144.6	140.6	134.4	132.1	126.7	124.4
47.5°	169.3	158.6	149.4	141.5	135.3	131.6	125.6	120.8	117.0	113.7	110.8
50°	157.3	148.3	139.4	132.4	126.9	121.5	115.4	113.0	107.0	105.3	103.7
52.5°	146.3	137.8	129.7	122.8	117.2	112.0	106.6	103.5	99.5	97.8	96.6
55°	130.9	122.8	115.0	108.9	103.4	98.0	94.7	90.7	88.9	87.6	86.1
57.5°	115.5	108.2	102.2	96.0	90.4	86.2	82.3	80.0	78.1	76.4	74.6
60°	105.7	98.7	93.4	87.6	81.9	78.4	75.4	72.6	70.4	67.8	67.0
62.5°	95.4	89.2	84.3	78.7	73.7	70.5	67.7	65.1	62.4	58.6	57.6
65°	81.1	76.3	71.1	66.4	62.0	58.9	54.8	51.9	50.7	50.4	50.2
67.5°	68.2	63.7	59.2	54.5	50.5	47.5	45.4	45.0	44.2	44.0	43.5
70°	59.6	55.4	51.0	46.5	42.6	42.1	41.3	40.5	39.6	39.3	38.9
72.5°	51.9	47.5	43.0	39.5	37.8	37.2	36.4	35.6	35.1	34.7	34.5
75°	39.8	35.7	32.8	31.5	30.6	30.0	28.9	28.4	28.0	27.4	27.2
77.5°	28.7	26.3	25.0	24.2	23.2	22.7	22.0	21.4	21.0	21.0	20.6
80°	21.9	20.7	19.8	18.7	18.3	17.6	17.4	16.9	17.0	16.5	16.5
82.5°	17.0	15.6	14.8	14.3	13.9	13.3	13.1	12.9	12.9	12.5	12.5
85°	8.7	8.3	8.0	7.6	7.6	7.0	7.3	7.0	7.0	6.7	6.5
87.5°	3.7	3.8	3.8	4.2	4.6	4.8	4.8	4.6	4.6	4.6	4.4
90°	4.3	5.7	7.5	9.3	11.1	13.0	12.8	12.6	12.5	12.3	12.2
92.5°	9.5	10.0	10.4	10.9	11.3	11.7	11.7	11.8	11.8	11.9	11.9
95°	22.5	23.0	23.2	23.3	23.5	23.6	23.6	23.6	23.6	23.6	23.6
97.5°	38.0	38.5	38.8	39.1	39.5	39.7	39.7	39.7	39.7	39.7	39.7
100°	49.6	50.0	50.2	50.5	50.7	51.0	51.0	51.0	51.0	51.0	51.0
102.5°	61.4	61.9	62.1	62.5	62.8	63.1	63.2	63.2	63.3	63.3	63.3
105°	80.4	80.6	80.8	81.0	81.1	81.3	81.4	81.6	81.8	81.9	82.0
107.5°	101.1	101.3	101.3	101.3	101.3	101.3	101.3	101.4	101.5	101.6	101.4
110°	114.6	114.9	114.9	114.9	114.9	114.9	114.9	114.9	114.9	114.9	114.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	128.8	129.1	129.0	128.9	128.8	128.7	128.6	128.4	128.2	128.0	127.8
115°	149.7	149.9	149.7	149.5	149.4	149.2	149.1	149.0	149.0	148.9	148.7
117.5°	171.2	171.3	170.9	170.4	169.9	169.5	169.3	169.1	168.8	168.7	168.4
120°	185.1	185.1	184.4	183.8	183.1	182.5	182.5	182.5	182.5	182.5	182.4
122.5°	198.4	198.5	198.0	197.5	197.1	196.7	196.5	196.2	196.1	195.8	195.7
125°	217.9	218.2	217.9	217.7	217.4	217.2	217.0	216.7	216.5	216.2	216.1
127.5°	238.0	238.3	238.1	237.7	237.4	237.2	236.8	236.5	236.3	235.9	235.7
130°	250.6	251.1	250.9	250.8	250.6	250.5	250.3	250.1	250.0	249.8	249.6
132.5°	263.4	263.9	263.9	264.0	264.0	264.0	263.7	263.3	262.9	262.6	262.3
135°	281.8	282.3	282.4	282.6	282.7	282.9	282.8	282.7	282.7	282.6	282.4
137.5°	300.2	300.7	300.9	301.2	301.3	301.6	301.5	301.4	301.3	301.3	301.1
140°	311.8	312.3	312.7	313.2	313.6	314.0	314.0	314.0	314.0	314.0	313.8
142.5°	323.6	324.1	324.3	324.7	324.9	325.2	325.3	325.3	325.4	325.5	325.3
145°	339.9	340.5	341.0	341.4	341.9	342.4	342.5	342.6	342.7	342.8	342.6
147.5°	355.6	356.0	356.4	356.7	357.0	357.3	357.5	357.7	357.9	358.1	358.0
150°	365.1	365.5	365.8	366.2	366.5	366.8	367.0	367.3	367.5	367.8	367.8
152.5°	374.2	374.7	375.0	375.4	375.9	376.3	376.6	376.8	377.2	377.5	377.5
155°	387.0	387.3	387.5	387.8	388.0	388.2	388.7	389.1	389.5	389.9	390.0
157.5°	398.4	398.5	398.7	398.8	399.0	399.2	399.7	400.2	400.8	401.4	401.5
160°	405.5	405.6	405.7	405.8	405.9	405.9	406.4	406.9	407.4	407.9	408.0
162.5°	411.5	411.6	411.6	411.7	411.8	411.9	412.4	412.9	413.5	414.1	414.2
165°	419.6	419.6	419.6	419.6	419.6	419.6	420.2	420.8	421.3	421.9	422.0
167.5°	426.2	426.1	426.1	426.1	426.1	426.1	426.6	427.2	427.8	428.4	428.4
170°	430.1	429.9	429.8	429.7	429.7	429.6	430.2	430.7	431.3	431.9	431.9
172.5°	432.8	432.6	432.5	432.4	432.4	432.3	432.8	433.4	434.0	434.6	434.6
175°	436.0	435.8	435.6	435.5	435.3	435.1	435.7	436.3	436.8	437.4	437.5
177.5°	437.5	437.3	437.2	437.1	436.9	436.8	437.2	437.7	438.0	438.4	438.4
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	511.8	512.1	511.7	511.9	511.7	512.1	511.8	513.5	513.7	514.0	513.7
5°	476.9	474.7	474.3	473.8	474.3	474.7	476.9	477.8	478.6	480.0	482.7
7.5°	435.2	434.9	433.9	432.6	433.9	434.9	435.2	438.4	440.9	443.8	449.1
10°	408.4	407.4	407.2	405.9	407.2	407.4	408.4	412.5	415.4	419.5	426.7
12.5°	376.9	371.0	370.4	367.1	370.4	371.0	376.9	382.2	390.2	394.1	401.8
15°	321.0	319.8	316.1	313.7	316.1	319.8	321.0	325.4	328.3	339.1	351.5
17.5°	288.9	285.3	284.1	283.6	284.1	285.3	288.9	291.1	295.3	301.0	308.4
20°	268.3	265.1	264.5	264.1	264.5	265.1	268.3	270.9	274.3	280.4	288.1
22.5°	254.1	250.6	249.2	248.1	249.2	250.6	254.1	256.1	259.2	263.9	269.2
25°	229.8	228.5	227.8	227.4	227.8	228.5	229.8	231.7	234.6	241.2	246.7
27.5°	210.8	208.0	207.4	206.4	207.4	208.0	210.8	214.1	217.2	220.1	225.1
30°	200.0	199.1	197.8	196.7	197.8	199.1	200.0	201.7	203.7	208.7	213.5
32.5°	187.3	186.5	185.3	184.8	185.3	186.5	187.3	189.6	193.8	196.9	200.3
35°	173.2	170.6	169.4	167.8	169.4	170.6	173.2	175.0	176.7	179.3	185.6
37.5°	158.2	156.9	155.3	155.9	155.3	156.9	158.2	159.0	162.5	166.2	168.8
40°	146.7	145.8	145.4	145.2	145.4	145.8	146.7	149.1	153.4	155.0	159.1
42.5°	137.5	134.9	134.0	134.0	134.0	134.9	137.5	140.2	142.8	145.5	149.8
45°	123.5	121.2	119.4	119.6	119.4	121.2	123.5	124.4	126.7	132.1	134.4
47.5°	109.3	109.2	108.1	108.4	108.1	109.2	109.3	110.8	113.7	117.0	120.8
50°	102.4	101.3	100.5	100.8	100.5	101.3	102.4	103.7	105.3	107.0	113.0
52.5°	95.9	94.9	94.3	95.1	94.3	94.9	95.9	96.6	97.8	99.5	103.5
55°	85.2	84.1	83.9	83.7	83.9	84.1	85.2	86.1	87.6	88.9	90.7
57.5°	73.2	72.5	71.3	70.9	71.3	72.5	73.2	74.6	76.4	78.1	80.0
60°	64.7	63.2	61.3	61.1	61.3	63.2	64.7	67.0	67.8	70.4	72.6
62.5°	56.7	56.5	56.1	56.1	56.1	56.5	56.7	57.6	58.6	62.4	65.1
65°	49.8	49.7	49.8	50.0	49.8	49.7	49.8	50.2	50.4	50.7	51.9
67.5°	43.4	43.0	42.7	42.9	42.7	43.0	43.4	43.5	44.0	44.2	45.0
70°	38.5	38.3	38.2	38.2	38.2	38.3	38.5	38.9	39.3	39.6	40.5
72.5°	33.8	33.8	33.6	33.4	33.6	33.8	33.8	34.5	34.7	35.1	35.6
75°	27.1	26.7	26.7	26.7	26.7	26.7	27.1	27.2	27.4	28.0	28.4
77.5°	20.6	20.4	20.2	20.1	20.2	20.4	20.6	20.6	21.0	21.0	21.4
80°	16.3	16.1	15.9	15.9	15.9	16.1	16.3	16.5	16.5	17.0	16.9
82.5°	12.5	12.2	12.2	12.1	12.2	12.2	12.5	12.5	12.5	12.9	12.9
85°	6.7	6.8	6.7	7.0	6.7	6.8	6.7	6.5	6.7	7.0	7.0
87.5°	4.4	4.2	4.4	4.3	4.4	4.2	4.4	4.4	4.6	4.6	4.6
90°	12.3	12.4	12.5	12.6	12.5	12.4	12.3	12.2	12.3	12.5	12.6
92.5°	11.9	11.9	12.0	12.0	12.0	11.9	11.9	11.9	11.9	11.8	11.8
95°	23.4	23.2	23.1	22.9	23.1	23.2	23.4	23.6	23.6	23.6	23.6
97.5°	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7
100°	50.9	50.8	50.7	50.6	50.7	50.8	50.9	51.0	51.0	51.0	51.0
102.5°	63.3	63.2	63.1	63.0	63.1	63.2	63.3	63.3	63.3	63.3	63.2
105°	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	81.9	81.8	81.6
107.5°	101.0	100.6	100.3	99.9	100.3	100.6	101.0	101.4	101.6	101.5	101.4
110°	114.5	114.2	114.0	113.7	114.0	114.2	114.5	114.7	114.9	114.9	114.9



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	127.6	127.4	127.3	127.1	127.3	127.4	127.6	127.8	128.0	128.2	128.4
115°	148.5	148.2	148.0	147.7	148.0	148.2	148.5	148.7	148.9	149.0	149.0
117.5°	168.2	168.0	167.7	167.5	167.7	168.0	168.2	168.4	168.7	168.8	169.1
120°	182.1	181.9	181.6	181.4	181.6	181.9	182.1	182.4	182.5	182.5	182.5
122.5°	195.5	195.3	195.1	194.9	195.1	195.3	195.5	195.7	195.8	196.1	196.2
125°	216.0	215.9	215.8	215.7	215.8	215.9	216.0	216.1	216.2	216.5	216.7
127.5°	235.4	235.1	234.9	234.6	234.9	235.1	235.4	235.7	235.9	236.3	236.5
130°	249.2	248.9	248.6	248.3	248.6	248.9	249.2	249.6	249.8	250.0	250.1
132.5°	262.0	261.7	261.5	261.2	261.5	261.7	262.0	262.3	262.6	262.9	263.3
135°	282.2	281.9	281.7	281.4	281.7	281.9	282.2	282.4	282.6	282.7	282.7
137.5°	300.8	300.4	300.1	299.8	300.1	300.4	300.8	301.1	301.3	301.3	301.4
140°	313.5	313.2	312.8	312.5	312.8	313.2	313.5	313.8	314.0	314.0	314.0
142.5°	325.0	324.7	324.3	324.0	324.3	324.7	325.0	325.3	325.5	325.4	325.3
145°	342.3	341.9	341.6	341.3	341.6	341.9	342.3	342.6	342.8	342.7	342.6
147.5°	357.7	357.3	357.0	356.8	357.0	357.3	357.7	358.0	358.1	357.9	357.7
150°	367.5	367.3	367.0	366.8	367.0	367.3	367.5	367.8	367.8	367.5	367.3
152.5°	377.2	376.8	376.6	376.3	376.6	376.8	377.2	377.5	377.5	377.2	376.8
155°	389.7	389.5	389.2	389.0	389.2	389.5	389.7	390.0	389.9	389.5	389.1
157.5°	401.0	400.6	400.3	399.9	400.3	400.6	401.0	401.5	401.4	400.8	400.2
160°	407.6	407.3	407.0	406.7	407.0	407.3	407.6	408.0	407.9	407.4	406.9
162.5°	413.8	413.4	412.9	412.6	412.9	413.4	413.8	414.2	414.1	413.5	412.9
165°	421.6	421.2	420.8	420.4	420.8	421.2	421.6	422.0	421.9	421.3	420.8
167.5°	428.0	427.5	427.1	426.7	427.1	427.5	428.0	428.4	428.4	427.8	427.2
170°	431.5	431.0	430.5	430.0	430.5	431.0	431.5	431.9	431.9	431.3	430.7
172.5°	434.1	433.6	433.1	432.6	433.1	433.6	434.1	434.6	434.6	434.0	433.4
175°	437.0	436.5	436.0	435.5	436.0	436.5	437.0	437.5	437.4	436.8	436.3
177.5°	438.0	437.7	437.2	436.8	437.2	437.7	438.0	438.4	438.4	438.0	437.7
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	512.6	514.6	517.7	519.5	522.4	524.4	525.5	527.3	528.4	532.1	536.0
5°	483.9	486.9	492.0	496.8	502.1	507.4	511.4	515.8	519.8	526.8	534.3
7.5°	451.1	455.2	463.3	470.9	480.0	487.5	494.2	501.8	508.6	518.7	529.2
10°	426.5	433.7	444.3	451.5	463.3	470.9	481.5	489.8	499.3	512.7	524.5
12.5°	405.3	414.0	422.5	432.5	443.2	455.8	467.4	478.2	489.3	503.1	517.1
15°	366.9	379.4	392.6	402.8	417.3	430.6	444.1	458.5	472.2	488.8	506.9
17.5°	317.4	332.0	354.1	371.5	388.5	401.9	418.7	436.1	452.2	472.1	492.4
20°	295.1	305.7	320.7	344.3	369.8	384.1	401.1	420.4	438.9	460.6	482.2
22.5°	277.1	286.7	298.6	317.0	345.5	365.0	382.8	402.4	423.8	445.9	469.9
25°	251.5	258.1	270.8	285.6	305.2	337.2	356.7	376.3	399.7	423.4	450.8
27.5°	232.3	238.3	246.5	260.6	275.2	298.2	329.1	350.6	373.8	400.5	428.9
30°	217.6	224.6	233.7	243.7	259.7	277.6	308.5	333.4	356.3	383.8	414.1
32.5°	206.9	212.5	220.2	230.4	243.6	260.9	285.6	315.7	338.1	367.0	398.7
35°	189.5	195.9	202.2	211.9	222.6	238.3	257.1	289.3	311.5	340.0	371.9
37.5°	175.0	179.0	186.0	193.6	205.0	216.7	232.9	261.8	285.8	313.8	346.4
40°	164.1	169.1	174.2	182.8	192.1	203.3	219.2	240.8	268.3	295.8	327.6
42.5°	153.4	159.7	165.3	171.0	181.1	192.4	205.4	223.6	251.8	277.7	308.7
45°	140.6	144.6	150.3	156.7	165.0	174.6	186.1	202.0	229.1	251.5	280.5
47.5°	125.6	131.6	135.3	141.5	149.4	158.6	169.3	183.0	204.9	225.9	252.9
50°	115.4	121.5	126.9	132.4	139.4	148.3	157.3	170.6	188.2	210.2	235.4
52.5°	106.6	112.0	117.2	122.8	129.7	137.8	146.3	158.0	173.0	193.3	217.8
55°	94.7	98.0	103.4	108.9	115.0	122.8	130.9	140.7	153.7	170.7	190.5
57.5°	82.3	86.2	90.4	96.0	102.2	108.2	115.5	124.4	134.6	150.0	167.0
60°	75.4	78.4	81.9	87.6	93.4	98.7	105.7	113.2	122.8	136.2	150.6
62.5°	67.7	70.5	73.7	78.7	84.3	89.2	95.4	103.2	111.4	123.5	136.2
65°	54.8	58.9	62.0	66.4	71.1	76.3	81.1	87.4	94.7	104.3	115.5
67.5°	45.4	47.5	50.5	54.5	59.2	63.7	68.2	73.1	79.4	86.8	95.8
70°	41.3	42.1	42.6	46.5	51.0	55.4	59.6	64.2	69.6	75.7	83.5
72.5°	36.4	37.2	37.8	39.5	43.0	47.5	51.9	55.4	60.4	65.6	71.8
75°	28.9	30.0	30.6	31.5	32.8	35.7	39.8	43.1	46.1	50.0	55.0
77.5°	22.0	22.7	23.2	24.2	25.0	26.3	28.7	31.6	34.5	36.7	40.1
80°	17.4	17.6	18.3	18.7	19.8	20.7	21.9	24.3	27.1	28.0	30.4
82.5°	13.1	13.3	13.9	14.3	14.8	15.6	17.0	17.6	19.8	21.0	22.5
85°	7.3	7.0	7.6	7.6	8.0	8.3	8.7	9.6	10.2	11.7	12.1
87.5°	4.8	4.8	4.6	4.2	3.8	3.8	3.7	3.6	3.8	4.0	4.4
90°	12.8	13.0	11.1	9.3	7.5	5.7	4.3	3.3	2.4	1.4	0.4
92.5°	11.7	11.7	11.3	10.9	10.4	10.0	9.5	8.7	8.0	7.3	6.6
95°	23.6	23.6	23.5	23.3	23.2	23.0	22.5	21.7	20.9	20.1	19.2
97.5°	39.7	39.7	39.5	39.1	38.8	38.5	38.0	37.3	36.5	35.8	35.1
100°	51.0	51.0	50.7	50.5	50.2	50.0	49.6	48.9	48.2	47.5	46.9
102.5°	63.2	63.1	62.8	62.5	62.1	61.9	61.4	60.9	60.3	59.8	59.4
105°	81.4	81.3	81.1	81.0	80.8	80.6	80.4	80.1	79.9	79.7	79.4
107.5°	101.3	101.3	101.3	101.3	101.3	101.3	101.1	100.8	100.4	100.0	99.6
110°	114.9	114.9	114.9	114.9	114.9	114.9	114.6	114.1	113.7	113.2	112.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	128.6	128.7	128.8	128.9	129.0	129.1	128.8	128.3	127.8	127.3	126.9
115°	149.1	149.2	149.4	149.5	149.7	149.9	149.7	149.2	148.7	148.2	147.7
117.5°	169.3	169.5	169.9	170.4	170.9	171.3	171.2	170.6	169.9	169.3	168.6
120°	182.5	182.5	183.1	183.8	184.4	185.1	185.1	184.4	183.8	183.1	182.5
122.5°	196.5	196.7	197.1	197.5	198.0	198.5	198.4	197.5	196.7	196.0	195.2
125°	217.0	217.2	217.4	217.7	217.9	218.2	217.9	217.2	216.5	215.7	215.0
127.5°	236.8	237.2	237.4	237.7	238.1	238.3	238.0	237.1	236.1	235.2	234.2
130°	250.3	250.5	250.6	250.8	250.9	251.1	250.6	249.6	248.5	247.4	246.4
132.5°	263.7	264.0	264.0	264.0	263.9	263.9	263.4	262.6	261.7	260.8	260.0
135°	282.8	282.9	282.7	282.6	282.4	282.3	281.8	280.9	280.0	279.1	278.2
137.5°	301.5	301.6	301.3	301.2	300.9	300.7	300.2	299.5	298.7	298.0	297.3
140°	314.0	314.0	313.6	313.2	312.7	312.3	311.8	311.0	310.3	309.6	308.8
142.5°	325.3	325.2	324.9	324.7	324.3	324.1	323.6	322.9	322.1	321.4	320.7
145°	342.5	342.4	341.9	341.4	341.0	340.5	339.9	339.3	338.8	338.2	337.6
147.5°	357.5	357.3	357.0	356.7	356.4	356.0	355.6	354.8	354.2	353.4	352.8
150°	367.0	366.8	366.5	366.2	365.8	365.5	365.1	364.6	364.1	363.6	363.1
152.5°	376.6	376.3	375.9	375.4	375.0	374.7	374.2	373.7	373.2	372.8	372.3
155°	388.7	388.2	388.0	387.8	387.5	387.3	387.0	386.8	386.5	386.2	386.0
157.5°	399.7	399.2	399.0	398.8	398.7	398.5	398.4	398.3	398.1	397.9	397.8
160°	406.4	405.9	405.9	405.8	405.7	405.6	405.5	405.4	405.2	405.0	404.9
162.5°	412.4	411.9	411.8	411.7	411.6	411.6	411.5	411.4	411.4	411.4	411.3
165°	420.2	419.6	419.6	419.6	419.6	419.6	419.6	419.7	419.8	419.9	420.0
167.5°	426.6	426.1	426.1	426.1	426.1	426.1	426.2	426.5	426.7	427.0	427.2
170°	430.2	429.6	429.7	429.7	429.8	429.9	430.1	430.3	430.6	430.8	431.0
172.5°	432.8	432.3	432.4	432.4	432.5	432.6	432.8	433.0	433.3	433.5	433.7
175°	435.7	435.1	435.3	435.5	435.6	435.8	436.0	436.3	436.5	436.8	437.0
177.5°	437.2	436.8	436.9	437.1	437.2	437.3	437.5	437.7	437.9	438.1	438.3
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	536.1	536.5	539.5	540.9	543.5	544.5	545.8	545.4	545.4	546.0	550.2
5°	537.3	541.0	546.5	551.9	557.1	561.5	564.5	567.4	568.6	573.9	578.7
7.5°	535.3	542.2	551.3	559.5	569.3	577.0	583.3	589.1	593.0	600.9	608.9
10°	532.8	542.4	552.8	563.4	576.9	587.1	597.5	605.4	608.0	619.6	626.3
12.5°	527.7	540.6	553.8	567.5	580.7	594.8	606.2	614.2	623.3	633.7	646.0
15°	520.2	535.0	552.3	569.8	588.7	605.8	618.0	631.9	641.9	653.4	664.1
17.5°	509.4	528.5	550.3	570.7	592.6	610.8	627.7	641.0	648.0	654.6	656.2
20°	500.8	521.3	547.1	571.1	593.0	614.1	630.8	641.9	643.8	643.9	634.1
22.5°	491.5	514.7	541.6	566.2	592.4	615.9	628.8	633.6	626.2	613.7	594.7
25°	474.3	501.2	532.5	560.6	589.1	611.3	615.8	607.5	581.7	554.6	520.4
27.5°	455.7	485.9	519.4	550.7	581.1	594.9	585.3	555.2	508.9	468.6	419.7
30°	442.1	476.0	508.9	543.9	572.1	578.0	556.0	511.7	457.6	396.9	348.1
32.5°	426.5	462.0	498.2	534.4	558.0	552.2	515.8	461.3	397.9	338.2	292.2
35°	404.3	440.9	480.0	516.3	531.3	506.3	451.8	380.9	316.1	260.4	228.7
37.5°	378.6	418.6	459.2	492.5	491.5	449.8	375.6	302.4	247.9	214.9	192.4
40°	360.4	400.8	444.7	472.8	460.8	406.5	326.1	257.1	217.2	190.9	174.5
42.5°	342.9	383.4	427.1	449.4	428.4	361.7	281.7	227.6	194.7	174.2	160.9
45°	313.2	356.0	396.3	408.7	371.3	297.8	227.8	188.5	166.6	151.5	142.3
47.5°	284.1	326.2	363.1	363.2	312.7	241.5	192.2	163.1	144.5	132.7	126.0
50°	266.3	306.3	337.2	332.4	275.0	214.8	171.9	146.8	131.3	122.2	115.2
52.5°	246.3	285.1	311.9	298.2	243.1	189.1	153.6	132.6	119.8	111.9	105.6
55°	217.2	251.7	270.6	249.8	198.4	157.3	129.8	113.3	103.7	97.0	91.6
57.5°	188.7	217.1	228.9	204.8	163.4	130.4	109.8	97.4	87.9	83.1	80.3
60°	170.7	195.0	203.3	176.7	142.0	114.1	97.3	85.8	78.7	75.6	72.8
62.5°	153.1	172.9	176.3	152.0	123.8	99.9	85.4	75.7	71.0	68.0	65.4
65°	127.0	141.3	139.7	120.0	98.0	79.2	68.7	62.8	59.3	55.0	50.4
67.5°	104.6	113.3	108.0	93.4	74.8	61.6	54.7	50.2	45.8	41.8	40.8
70°	90.3	95.4	89.8	76.3	61.3	51.7	46.1	40.8	38.2	37.3	35.5
72.5°	76.7	78.5	72.5	60.9	49.9	42.8	37.3	34.4	32.9	32.2	31.1
75°	57.6	56.3	51.1	42.1	34.7	29.8	28.1	27.1	26.1	25.4	24.8
77.5°	40.4	38.6	33.9	28.0	24.1	21.9	20.8	20.2	19.8	19.4	18.8
80°	30.4	29.1	24.5	20.0	18.3	17.2	16.6	15.9	15.9	15.6	15.0
82.5°	22.3	20.8	16.7	14.7	13.8	13.0	12.6	12.2	12.1	12.1	11.7
85°	11.7	9.5	8.3	8.0	7.4	7.0	7.3	6.8	6.8	6.8	6.7
87.5°	3.8	3.3	3.3	3.3	3.8	4.2	4.4	4.7	5.2	5.1	5.2
90°	1.4	2.4	3.3	4.3	5.7	7.5	9.3	11.1	13.0	12.8	12.6
92.5°	7.3	8.0	8.7	9.5	10.0	10.4	10.9	11.3	11.7	11.7	11.8
95°	20.1	20.9	21.7	22.5	23.0	23.2	23.3	23.5	23.6	23.6	23.6
97.5°	35.8	36.5	37.3	38.0	38.5	38.8	39.1	39.5	39.7	39.7	39.7
100°	47.5	48.2	48.9	49.6	50.0	50.2	50.5	50.7	51.0	51.0	51.0
102.5°	59.8	60.3	60.9	61.4	61.9	62.1	62.5	62.8	63.1	63.2	63.2
105°	79.7	79.9	80.1	80.4	80.6	80.8	81.0	81.1	81.3	81.4	81.6
107.5°	100.0	100.4	100.8	101.1	101.3	101.3	101.3	101.3	101.3	101.3	101.4
110°	113.2	113.7	114.1	114.6	114.9	114.9	114.9	114.9	114.9	114.9	114.9



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	127.3	127.8	128.3	128.8	129.1	129.0	128.9	128.8	128.7	128.6	128.4
115°	148.2	148.7	149.2	149.7	149.9	149.7	149.5	149.4	149.2	149.1	149.0
117.5°	169.3	169.9	170.6	171.2	171.3	170.9	170.4	169.9	169.5	169.3	169.1
120°	183.1	183.8	184.4	185.1	185.1	184.4	183.8	183.1	182.5	182.5	182.5
122.5°	196.0	196.7	197.5	198.4	198.5	198.0	197.5	197.1	196.7	196.5	196.2
125°	215.7	216.5	217.2	217.9	218.2	217.9	217.7	217.4	217.2	217.0	216.7
127.5°	235.2	236.1	237.1	238.0	238.3	238.1	237.7	237.4	237.2	236.8	236.5
130°	247.4	248.5	249.6	250.6	251.1	250.9	250.8	250.6	250.5	250.3	250.1
132.5°	260.8	261.7	262.6	263.4	263.9	263.9	264.0	264.0	264.0	263.7	263.3
135°	279.1	280.0	280.9	281.8	282.3	282.4	282.6	282.7	282.9	282.8	282.7
137.5°	298.0	298.7	299.5	300.2	300.7	300.9	301.2	301.3	301.6	301.5	301.4
140°	309.6	310.3	311.0	311.8	312.3	312.7	313.2	313.6	314.0	314.0	314.0
142.5°	321.4	322.1	322.9	323.6	324.1	324.3	324.7	324.9	325.2	325.3	325.3
145°	338.2	338.8	339.3	339.9	340.5	341.0	341.4	341.9	342.4	342.5	342.6
147.5°	353.4	354.2	354.8	355.6	356.0	356.4	356.7	357.0	357.3	357.5	357.7
150°	363.6	364.1	364.6	365.1	365.5	365.8	366.2	366.5	366.8	367.0	367.3
152.5°	372.8	373.2	373.7	374.2	374.7	375.0	375.4	375.9	376.3	376.6	376.8
155°	386.2	386.5	386.8	387.0	387.3	387.5	387.8	388.0	388.2	388.7	389.1
157.5°	397.9	398.1	398.3	398.4	398.5	398.7	398.8	399.0	399.2	399.7	400.2
160°	405.0	405.2	405.4	405.5	405.6	405.7	405.8	405.9	405.9	406.4	406.9
162.5°	411.4	411.4	411.4	411.5	411.6	411.6	411.7	411.8	411.9	412.4	412.9
165°	419.9	419.8	419.7	419.6	419.6	419.6	419.6	419.6	419.6	420.2	420.8
167.5°	427.0	426.7	426.5	426.2	426.1	426.1	426.1	426.1	426.1	426.6	427.2
170°	430.8	430.6	430.3	430.1	429.9	429.8	429.7	429.7	429.6	430.2	430.7
172.5°	433.5	433.3	433.0	432.8	432.6	432.5	432.4	432.4	432.3	432.8	433.4
175°	436.8	436.5	436.3	436.0	435.8	435.6	435.5	435.3	435.1	435.7	436.3
177.5°	438.1	437.9	437.7	437.5	437.3	437.2	437.1	436.9	436.8	437.2	437.7
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7	437.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	533.0	533.0	533.0	533.0	533.0	533.0	533.0
2.5°	551.6	553.6	554.5	554.5	555.5	555.1	554.6
5°	583.3	586.9	587.7	590.9	593.4	592.6	593.0
7.5°	614.9	620.5	626.1	628.7	629.1	630.6	631.1
10°	634.3	639.0	647.6	646.4	652.8	656.6	650.4
12.5°	653.0	659.3	665.3	666.9	670.6	671.8	669.4
15°	669.8	673.2	673.5	672.6	673.8	672.8	669.3
17.5°	654.1	648.7	637.7	632.5	628.4	622.3	619.9
20°	628.0	612.0	593.5	586.1	577.5	560.4	564.5
22.5°	571.7	553.6	535.0	513.4	503.0	486.9	485.9
25°	484.1	452.8	418.3	394.3	380.2	364.1	357.0
27.5°	376.4	337.0	308.8	294.5	281.4	268.7	268.2
30°	305.6	276.0	254.1	241.9	233.9	228.5	229.7
32.5°	257.6	237.3	222.5	212.4	206.5	202.4	202.4
35°	210.6	196.7	187.2	183.0	178.7	175.8	175.9
37.5°	180.2	171.9	166.6	161.9	159.2	157.8	156.9
40°	164.6	157.8	153.7	150.9	148.7	146.7	146.3
42.5°	152.4	146.7	142.6	140.4	138.4	136.9	136.6
45°	135.2	130.5	126.9	124.4	123.5	122.2	122.2
47.5°	120.3	115.7	112.8	111.3	109.7	108.8	108.8
50°	110.2	106.6	104.1	103.1	101.8	101.3	101.1
52.5°	101.2	98.5	96.7	96.0	95.5	94.8	94.9
55°	88.9	87.4	86.7	86.1	85.2	84.1	84.8
57.5°	78.6	77.3	75.3	73.5	72.7	71.9	72.2
60°	71.3	68.7	66.1	64.1	63.5	61.9	61.9
62.5°	62.1	58.5	55.3	54.1	53.6	52.8	52.7
65°	47.8	46.3	45.6	44.8	44.4	44.4	44.1
67.5°	39.6	39.0	38.2	38.0	37.7	37.5	37.4
70°	35.0	34.2	33.9	33.7	33.3	33.5	32.9
72.5°	30.6	30.0	29.9	29.4	29.2	29.2	28.8
75°	24.1	24.1	23.9	23.7	23.3	23.2	23.3
77.5°	18.5	18.6	18.3	18.2	18.2	18.2	18.0
80°	14.8	15.0	14.8	14.6	14.4	14.6	14.4
82.5°	11.7	11.4	11.4	11.3	11.3	11.3	11.2
85°	6.7	6.8	6.7	6.5	6.5	6.5	6.7
87.5°	5.0	5.0	5.0	5.0	5.0	5.0	4.9
90°	12.5	12.3	12.2	12.3	12.4	12.5	12.6
92.5°	11.8	11.9	11.9	11.9	11.9	12.0	12.0
95°	23.6	23.6	23.6	23.4	23.2	23.1	22.9
97.5°	39.7	39.7	39.7	39.7	39.7	39.7	39.7
100°	51.0	51.0	51.0	50.9	50.8	50.7	50.6
102.5°	63.3	63.3	63.3	63.3	63.2	63.1	63.0
105°	81.8	81.9	82.0	82.0	82.0	82.0	82.0
107.5°	101.5	101.6	101.4	101.0	100.6	100.3	99.9
110°	114.9	114.9	114.7	114.5	114.2	114.0	113.7



TEST NUMBER: P331766-930

CATALOG NUMBER: S122RDIW-S290D435U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	128.2	128.0	127.8	127.6	127.4	127.3	127.1
115°	149.0	148.9	148.7	148.5	148.2	148.0	147.7
117.5°	168.8	168.7	168.4	168.2	168.0	167.7	167.5
120°	182.5	182.5	182.4	182.1	181.9	181.6	181.4
122.5°	196.1	195.8	195.7	195.5	195.3	195.1	194.9
125°	216.5	216.2	216.1	216.0	215.9	215.8	215.7
127.5°	236.3	235.9	235.7	235.4	235.1	234.9	234.6
130°	250.0	249.8	249.6	249.2	248.9	248.6	248.3
132.5°	262.9	262.6	262.3	262.0	261.7	261.5	261.2
135°	282.7	282.6	282.4	282.2	281.9	281.7	281.4
137.5°	301.3	301.3	301.1	300.8	300.4	300.1	299.8
140°	314.0	314.0	313.8	313.5	313.2	312.8	312.5
142.5°	325.4	325.5	325.3	325.0	324.7	324.3	324.0
145°	342.7	342.8	342.6	342.3	341.9	341.6	341.3
147.5°	357.9	358.1	358.0	357.7	357.3	357.0	356.8
150°	367.5	367.8	367.8	367.5	367.3	367.0	366.8
152.5°	377.2	377.5	377.5	377.2	376.8	376.6	376.3
155°	389.5	389.9	390.0	389.7	389.5	389.2	389.0
157.5°	400.8	401.4	401.5	401.0	400.6	400.3	399.9
160°	407.4	407.9	408.0	407.6	407.3	407.0	406.7
162.5°	413.5	414.1	414.2	413.8	413.4	412.9	412.6
165°	421.3	421.9	422.0	421.6	421.2	420.8	420.4
167.5°	427.8	428.4	428.4	428.0	427.5	427.1	426.7
170°	431.3	431.9	431.9	431.5	431.0	430.5	430.0
172.5°	434.0	434.6	434.6	434.1	433.6	433.1	432.6
175°	436.8	437.4	437.5	437.0	436.5	436.0	435.5
177.5°	438.0	438.4	438.4	438.0	437.7	437.2	436.8
180°	437.7	437.7	437.7	437.7	437.7	437.7	437.7

(END OF REPORT)