

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331579

Luminaire Tested: **S122DIW-S865D1440U835-4F0-1E-UDD-A**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P331579  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-2,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S122DIW-S865D1440U835-4F0-1E-UDD-A  
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 865 LUMENS PER FOOT, ASYMMETRIC DIFFUSER  
UPLIGHT 1440 LUMENS PER FOOT, NO LENS  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 9574.0 lumens  
Efficiency: N/A  
Efficacy: 125.0 lumens/watt  
Spacing Criteria (0/90/45): 1.08 / 1.16 / 1.23  
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')  
CIE Type: Semi-Indirect  
  
Input Watts (W): 76.6  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

### Luminous Intensity Polar Plot





TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20																		
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	105	105	105	105	95	95	95	95	78	78	78	62	62	62	47	47	47	40																												
1	96	92	88	85	87	84	81	78	69	66	64	55	53	52	42	41	40	34																												
2	88	81	75	70	80	74	69	64	61	57	54	48	46	44	37	36	34	29																												
3	80	71	64	59	73	65	59	54	54	49	46	43	40	38	33	31	30	25																												
4	73	63	56	50	67	58	51	46	48	43	39	39	35	33	30	28	26	22																												
5	68	56	49	43	61	52	45	40	43	38	34	35	31	28	27	25	23	19																												
6	62	51	43	37	57	47	40	35	39	34	30	32	28	25	25	22	20	17																												
7	58	46	38	33	52	42	35	31	35	30	26	29	25	22	23	20	18	15																												
8	53	42	34	29	49	38	32	27	32	27	24	26	23	20	21	18	16	14																												
9	50	38	31	26	45	35	29	24	30	25	21	24	21	18	19	17	15	13																												
10	47	35	28	23	42	32	26	22	27	22	19	23	19	16	18	15	14	12																												

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	27876	27876	27876	27876
5°	31253	28058	24864	28058
10°	35813	27829	21518	27829
15°	39619	27318	19010	27318
20°	39015	26770	17330	26770
25°	35179	26042	16265	26042
30°	29071	24878	15489	24878
35°	21187	23660	14937	23660
40°	16923	22223	14629	22223
45°	14787	20559	14212	20559
50°	13901	18952	13933	18952
55°	12814	17315	13560	17315
60°	11741	15578	12984	15578
65°	10697	14017	12420	14017
70°	9711	12500	11589	12500
75°	8609	10805	10268	10805
80°	7401	8945	8266	8945
85°	6632	6632	4909	6632



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	164.4	1.7
10°-20°	478.0	5.0
20°-30°	693.8	7.2
30°-40°	732.1	7.6
40°-50°	648.2	6.8
50°-60°	517.3	5.4
60°-70°	351.6	3.7
70°-80°	180.3	1.9
80°-90°	48.3	0.5
90°-100°	65.6	0.7
100°-110°	240.4	2.5
110°-120°	642.7	6.7
120°-130°	1060.9	11.1
130°-140°	1128.3	11.8
140°-150°	1048.7	11.0
150°-160°	843.1	8.8
160°-170°	543.3	5.7
170°-180°	187.0	2.0
0°-30°	1336.2	14.0
0°-40°	2068.3	21.6
0°-60°	3233.8	33.8
0°-90°	3813.9	39.8
90°-120°	948.7	9.9
90°-150°	4186.6	43.7
90°-180°	5760.0	60.2
0°-180°	9574.0	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1726	1726	1726	1726	1726	
5°	1928	1731	1534	1731	1928	193
15°	2370	1634	1137	1634	2370	654
25°	1975	1462	913	1462	1975	893
35°	1075	1200	758	1200	1075	699
45°	648	900	622	900	648	509
55°	455	615	482	615	455	408
65°	280	367	325	367	280	278
75°	138	173	165	173	138	147
85°	36	36	26	36	36	40
90°	38	1	38	1	38	19
95°	61	92	61	92	61	57
105°	108	432	108	432	108	112
115°	117	818	117	818	117	292
125°	1216	1156	1216	1156	1216	1052
135°	1478	1431	1478	1431	1478	1139
145°	1685	1660	1685	1660	1685	1054
155°	1829	1828	1829	1828	1829	844
165°	1921	1926	1921	1926	1921	542
175°	1958	1970	1958	1970	1958	187
180°	1966	1966	1966	1966	1966	



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1806.2	1806.7	1807.8	1799.3	1798.2	1798.2	1790.8	1784.4	1777.0	1766.9	1768.0
5°	1928.3	1935.6	1938.2	1930.3	1918.3	1917.0	1905.7	1887.1	1869.9	1855.9	1846.0
7.5°	2074.0	2076.9	2070.4	2059.9	2051.0	2035.1	2014.1	1993.6	1964.8	1938.4	1918.7
10°	2184.4	2188.4	2177.1	2161.8	2149.2	2130.6	2100.1	2068.9	2031.1	1994.6	1965.4
12.5°	2268.3	2278.1	2263.6	2261.6	2240.0	2214.5	2178.2	2162.4	2109.2	2058.3	2027.0
15°	2370.2	2369.5	2370.9	2358.2	2342.3	2338.3	2299.9	2258.1	2183.1	2153.2	2101.5
17.5°	2340.7	2350.8	2355.5	2355.3	2354.9	2352.4	2340.1	2313.7	2276.1	2227.7	2167.9
20°	2270.7	2283.9	2285.9	2301.2	2309.8	2321.1	2325.7	2318.4	2295.2	2254.7	2203.0
22.5°	2162.4	2166.1	2172.3	2196.1	2214.8	2243.1	2257.8	2282.3	2273.4	2253.7	2210.4
25°	1974.7	1968.1	1991.3	2003.2	2046.4	2091.5	2124.0	2159.8	2191.7	2210.9	2198.3
27.5°	1749.4	1739.4	1774.2	1805.9	1840.9	1889.8	1940.5	2000.3	2050.1	2112.3	2133.7
30°	1559.3	1565.3	1598.5	1632.3	1685.4	1754.4	1811.5	1877.2	1948.2	2017.8	2066.3
32.5°	1354.4	1377.4	1398.4	1450.2	1497.0	1573.9	1657.5	1739.7	1828.2	1907.4	1982.4
35°	1074.9	1101.5	1130.7	1168.5	1234.2	1310.5	1392.1	1502.9	1623.7	1731.9	1820.8
37.5°	904.8	900.6	917.3	944.6	997.8	1059.4	1153.4	1262.9	1405.0	1532.1	1657.5
40°	802.9	800.2	812.2	837.4	877.9	923.0	1005.3	1101.5	1233.5	1388.8	1538.1
42.5°	732.8	734.4	741.0	758.8	786.6	823.7	885.3	967.2	1088.1	1234.3	1394.8
45°	647.6	652.3	659.6	668.2	684.1	714.6	749.1	807.5	903.1	1025.2	1183.1
47.5°	586.3	586.4	593.9	601.4	610.9	628.1	656.2	692.9	760.3	859.7	995.5
50°	553.4	548.8	554.1	560.0	570.0	581.9	600.5	635.0	680.1	760.4	873.9
52.5°	513.1	513.2	518.0	520.2	529.1	541.1	558.0	581.9	622.8	685.6	778.9
55°	455.2	458.5	461.2	465.1	473.1	481.7	495.0	510.9	542.8	589.9	658.9
57.5°	400.8	401.8	404.5	412.1	417.1	425.1	437.7	452.1	472.8	507.7	559.6
60°	363.6	363.6	368.9	372.2	378.9	386.8	396.8	410.7	429.3	457.8	499.7
62.5°	329.7	329.1	331.2	336.7	341.7	349.2	359.1	370.9	388.4	413.8	448.2
65°	280.0	278.7	282.7	284.0	289.3	296.6	304.6	317.2	331.1	349.7	380.2
67.5°	232.2	233.8	236.0	238.5	241.4	249.1	254.4	263.3	275.1	290.5	311.2
70°	205.7	205.7	205.7	207.7	211.7	215.7	221.0	228.3	239.5	252.8	271.4
72.5°	176.0	178.1	180.2	179.0	184.1	186.5	192.8	196.9	207.7	216.2	232.6
75°	138.0	138.0	138.0	141.3	143.3	145.3	149.3	153.3	158.6	169.2	177.8
77.5°	103.0	102.7	103.4	104.2	106.3	108.7	109.9	113.5	118.4	123.3	130.6
80°	79.6	81.0	81.6	82.9	82.9	84.3	84.9	89.6	92.9	96.2	100.9
82.5°	61.6	61.8	62.0	62.2	62.8	63.6	65.3	66.8	67.9	70.7	74.3
85°	35.8	35.2	35.2	36.5	35.8	35.8	37.2	38.5	38.5	39.1	41.1
87.5°	21.5	21.4	21.8	21.1	21.0	21.3	21.0	20.1	20.3	20.6	20.6
90°	38.4	37.8	37.1	36.5	35.9	34.8	33.2	31.6	30.0	28.4	25.9
92.5°	38.4	38.0	37.6	37.3	36.9	36.3	35.5	34.6	33.8	33.0	31.7
95°	61.2	61.5	61.8	62.1	62.4	61.8	60.2	58.6	57.0	55.5	53.3
97.5°	81.6	81.3	80.9	80.5	80.1	79.3	78.0	76.8	75.5	74.2	69.1
100°	95.3	94.7	94.0	93.4	92.8	91.2	88.7	86.1	83.6	81.1	75.7
102.5°	102.1	101.2	100.3	99.5	98.6	96.5	93.2	89.9	86.6	83.3	128.3
105°	108.1	106.8	105.6	104.3	103.0	100.7	97.2	93.7	90.2	86.8	173.0
107.5°	111.2	110.0	108.7	107.4	106.2	107.3	110.8	114.4	117.9	121.5	224.9
110°	112.4	111.1	109.8	108.6	107.3	122.5	154.1	185.7	217.3	248.9	340.2



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	113.5	112.5	111.5	110.5	109.4	166.6	281.9	397.2	512.5	627.8	650.3
115°	116.6	139.4	162.1	184.9	207.6	292.2	438.5	584.9	731.2	877.5	869.6
117.5°	476.2	550.9	625.7	700.5	775.3	830.4	865.8	901.2	936.6	972.0	966.5
120°	867.6	910.2	952.9	995.6	1038.2	1057.7	1053.9	1050.1	1046.3	1042.5	1036.8
122.5°	1082.6	1090.9	1099.2	1107.4	1115.7	1118.7	1116.5	1114.2	1111.9	1109.6	1103.4
125°	1216.0	1215.1	1214.1	1213.2	1212.2	1210.6	1208.4	1206.2	1204.0	1201.8	1195.8
127.5°	1300.2	1300.0	1299.8	1299.6	1299.5	1297.7	1294.5	1291.3	1288.1	1284.9	1280.4
130°	1352.5	1352.9	1353.2	1353.5	1353.8	1352.2	1348.8	1345.3	1341.8	1338.3	1334.8
132.5°	1403.7	1404.1	1404.4	1404.7	1405.0	1403.7	1400.7	1397.7	1394.8	1391.8	1388.3
135°	1477.7	1478.3	1479.0	1479.6	1480.2	1479.0	1475.8	1472.6	1469.5	1466.3	1463.5
137.5°	1545.1	1546.2	1547.3	1548.3	1549.4	1548.4	1545.3	1542.2	1539.1	1536.0	1532.8
140°	1587.2	1588.8	1590.4	1592.0	1593.5	1592.9	1590.1	1587.2	1584.4	1581.5	1578.1
142.5°	1628.2	1629.8	1631.3	1632.9	1634.5	1634.0	1631.4	1628.8	1626.2	1623.6	1619.6
145°	1685.4	1686.9	1688.5	1690.1	1691.7	1691.4	1689.1	1686.9	1684.7	1682.5	1677.1
147.5°	1735.7	1737.0	1738.4	1739.7	1741.0	1740.9	1739.2	1737.6	1735.9	1734.3	1729.0
150°	1766.4	1768.0	1769.6	1771.2	1772.7	1772.6	1770.7	1768.8	1766.9	1765.0	1759.9
152.5°	1792.6	1794.7	1796.8	1798.8	1800.9	1801.0	1799.1	1797.2	1795.3	1793.4	1788.6
155°	1829.0	1831.5	1834.1	1836.6	1839.1	1839.4	1837.5	1835.6	1833.7	1831.8	1828.1
157.5°	1862.3	1864.7	1867.2	1869.7	1872.1	1872.3	1870.1	1868.0	1865.9	1863.7	1861.0
160°	1881.6	1883.8	1886.0	1888.3	1890.5	1890.6	1888.7	1886.8	1884.9	1883.0	1881.1
162.5°	1897.6	1900.3	1903.0	1905.7	1908.4	1908.7	1906.6	1904.4	1902.3	1900.1	1898.5
165°	1921.4	1923.7	1925.9	1928.1	1930.3	1930.3	1928.1	1925.9	1923.7	1921.4	1920.5
167.5°	1936.5	1939.4	1942.2	1945.1	1947.9	1948.2	1946.0	1943.8	1941.6	1939.4	1938.5
170°	1945.6	1948.5	1951.3	1954.2	1957.0	1957.3	1955.1	1952.9	1950.7	1948.5	1947.8
172.5°	1952.4	1955.3	1958.1	1961.0	1963.8	1964.1	1961.9	1959.7	1957.5	1955.3	1954.7
175°	1958.4	1961.6	1964.7	1967.9	1971.1	1971.5	1969.3	1967.1	1964.9	1962.7	1962.1
177.5°	1962.1	1964.4	1966.7	1968.9	1971.2	1971.5	1969.7	1967.9	1966.2	1964.4	1964.1
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1771.7	1767.4	1764.8	1755.2	1746.7	1738.2	1735.6	1736.6	1725.0	1713.8	1709.0
5°	1840.7	1827.4	1814.8	1796.9	1775.7	1752.4	1740.5	1731.2	1708.0	1682.8	1668.2
7.5°	1902.5	1883.5	1859.3	1825.6	1794.6	1758.1	1734.9	1714.3	1680.4	1644.8	1623.0
10°	1940.2	1914.3	1883.1	1842.0	1804.2	1759.7	1728.5	1697.4	1657.5	1615.1	1588.5
12.5°	1972.6	1937.7	1907.0	1854.2	1809.5	1753.9	1716.9	1672.9	1631.0	1580.6	1554.6
15°	2049.7	1985.3	1926.9	1867.2	1812.1	1734.5	1693.4	1634.3	1579.2	1516.9	1487.0
17.5°	2109.3	2037.0	1945.0	1869.1	1804.8	1718.9	1658.5	1587.7	1522.6	1451.3	1410.7
20°	2143.3	2060.3	1961.4	1871.2	1794.2	1696.0	1630.3	1558.0	1481.7	1401.4	1357.6
22.5°	2163.4	2076.2	1978.4	1863.2	1773.0	1677.4	1594.8	1515.5	1438.2	1351.5	1305.6
25°	2169.8	2090.2	1986.7	1856.6	1746.5	1638.3	1538.8	1461.8	1368.2	1287.3	1220.3
27.5°	2138.2	2081.1	1981.6	1844.1	1715.8	1589.3	1478.4	1391.2	1292.5	1204.6	1137.2
30°	2099.5	2066.3	1969.4	1831.4	1691.4	1555.4	1433.3	1334.4	1236.2	1147.3	1078.3
32.5°	2039.5	2032.3	1947.1	1813.3	1665.4	1512.4	1386.0	1286.1	1177.3	1089.9	1024.1
35°	1921.6	1953.5	1899.7	1773.0	1616.4	1451.2	1314.5	1200.4	1087.6	1003.9	942.2
37.5°	1763.7	1842.8	1828.7	1713.9	1550.3	1384.6	1233.7	1114.4	1006.9	922.5	861.9
40°	1654.9	1755.7	1770.3	1668.8	1503.6	1333.1	1173.2	1054.4	949.5	872.6	811.5
42.5°	1538.1	1655.9	1696.0	1614.7	1452.6	1278.9	1119.0	996.0	892.2	817.4	763.2
45°	1342.4	1498.3	1570.6	1524.2	1367.6	1189.7	1025.2	900.4	806.2	735.9	694.1
47.5°	1159.3	1329.7	1427.0	1410.6	1272.9	1096.8	934.1	814.4	722.7	666.6	629.2
50°	1029.8	1205.0	1322.4	1327.8	1205.0	1030.5	867.3	754.5	670.2	617.8	587.2
52.5°	917.3	1084.5	1212.6	1240.7	1129.1	961.5	807.3	695.0	620.8	572.6	545.3
55°	770.4	911.7	1053.7	1105.5	1015.9	856.6	714.0	615.1	545.4	512.3	488.4
57.5°	640.5	758.3	889.4	946.6	891.4	755.1	621.3	535.5	478.9	449.9	431.6
60°	572.0	664.9	781.7	850.0	802.2	680.8	564.0	482.4	436.0	410.1	392.8
62.5°	508.3	590.6	689.3	751.8	725.8	611.3	506.7	434.6	394.5	370.3	357.8
65°	419.4	484.4	560.7	618.4	601.2	514.2	428.7	366.9	335.1	315.8	305.9
67.5°	345.3	392.3	445.2	495.8	481.9	420.3	351.5	303.5	279.8	263.2	257.2
70°	298.6	334.4	381.5	422.0	410.7	360.3	305.9	264.8	244.2	230.3	224.3
72.5°	254.0	283.5	319.4	352.5	344.9	303.0	257.6	226.5	210.7	197.9	193.0
75°	191.8	214.3	236.2	258.1	256.1	223.6	197.1	173.2	160.6	150.6	148.6
77.5°	141.6	154.2	169.1	182.1	178.5	159.9	139.1	125.4	116.1	109.5	108.4
80°	108.2	115.5	126.1	135.4	130.7	122.8	106.2	96.2	89.6	82.9	80.3
82.5°	78.4	85.7	92.1	97.1	93.6	86.1	75.9	69.1	65.2	60.6	59.6
85°	41.1	45.1	47.8	49.1	47.8	43.1	38.5	35.8	32.5	30.5	29.9
87.5°	20.6	20.1	19.6	20.1	17.8	17.1	14.3	12.0	12.1	12.3	11.9
90°	23.4	20.9	18.3	15.3	11.9	8.4	4.9	1.4	4.9	8.4	11.9
92.5°	30.5	29.2	27.9	27.5	27.8	28.1	28.4	28.7	28.4	28.1	27.8
95°	51.0	48.8	46.6	50.7	61.2	71.6	82.0	92.4	82.0	71.6	61.2
97.5°	64.0	58.9	53.8	65.9	95.3	124.7	154.1	183.5	154.1	124.7	95.3
100°	70.3	64.9	59.6	78.5	121.8	165.1	208.4	251.7	208.4	165.1	121.8
102.5°	173.2	218.2	263.1	290.2	299.3	308.5	317.7	326.8	317.7	308.5	299.3
105°	259.3	345.6	431.9	470.3	460.8	451.3	441.8	432.4	441.8	451.3	460.8
107.5°	328.4	431.9	535.4	583.3	575.6	568.0	560.3	552.7	560.3	568.0	575.6
110°	431.6	522.9	614.2	656.6	650.0	643.3	636.7	630.1	636.7	643.3	650.0





TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	672.9	695.5	718.0	726.4	720.5	714.6	708.7	702.9	708.7	714.6	720.5
115°	861.7	853.8	845.9	839.3	833.9	828.5	823.2	817.8	823.2	828.5	833.9
117.5°	961.1	955.6	950.2	944.5	938.5	932.5	926.5	920.5	926.5	932.5	938.5
120°	1031.1	1025.4	1019.7	1014.5	1009.8	1005.0	1000.3	995.6	1000.3	1005.0	1009.8
122.5°	1097.2	1091.0	1084.9	1079.3	1074.3	1069.3	1064.3	1059.3	1064.3	1069.3	1074.3
125°	1189.8	1183.8	1177.8	1172.7	1168.6	1164.5	1160.4	1156.3	1160.4	1164.5	1168.6
127.5°	1275.9	1271.4	1266.9	1262.4	1257.8	1253.3	1248.7	1244.2	1248.7	1253.3	1257.8
130°	1331.4	1327.9	1324.4	1320.2	1315.1	1310.0	1305.0	1299.9	1305.0	1310.0	1315.1
132.5°	1384.8	1381.4	1377.9	1374.0	1369.7	1365.4	1361.1	1356.8	1361.1	1365.4	1369.7
135°	1460.6	1457.8	1454.9	1451.0	1445.9	1440.9	1435.8	1430.8	1435.8	1440.9	1445.9
137.5°	1529.6	1526.3	1523.1	1519.7	1516.2	1512.7	1509.1	1505.6	1509.1	1512.7	1516.2
140°	1574.6	1571.1	1567.6	1564.6	1562.1	1559.6	1557.0	1554.5	1557.0	1559.6	1562.1
142.5°	1615.7	1611.7	1607.7	1604.6	1602.3	1600.0	1597.7	1595.5	1597.7	1600.0	1602.3
145°	1671.8	1666.4	1661.0	1658.5	1658.8	1659.1	1659.4	1659.8	1659.4	1659.1	1658.8
147.5°	1723.7	1718.3	1713.0	1711.0	1712.2	1713.4	1714.6	1715.8	1714.6	1713.4	1712.2
150°	1754.9	1749.8	1744.8	1743.3	1745.6	1747.8	1750.0	1752.2	1750.0	1747.8	1745.6
152.5°	1783.8	1779.0	1774.2	1773.1	1775.5	1778.0	1780.5	1782.9	1780.5	1778.0	1775.5
155°	1824.3	1820.5	1816.7	1816.2	1819.0	1821.9	1824.7	1827.6	1824.7	1821.9	1819.0
157.5°	1858.4	1855.7	1853.1	1853.0	1855.4	1857.8	1860.2	1862.6	1860.2	1857.8	1855.4
160°	1879.3	1877.4	1875.5	1875.5	1877.4	1879.3	1881.1	1883.0	1881.1	1879.3	1877.4
162.5°	1896.8	1895.2	1893.5	1893.7	1895.6	1897.5	1899.4	1901.2	1899.4	1897.5	1895.6
165°	1919.5	1918.6	1917.7	1918.1	1920.0	1921.9	1923.8	1925.7	1923.8	1921.9	1920.0
167.5°	1937.6	1936.7	1935.8	1936.3	1938.2	1940.1	1942.0	1943.9	1942.0	1940.1	1938.2
170°	1947.2	1946.6	1945.9	1946.6	1948.5	1950.4	1952.3	1954.2	1952.3	1950.4	1948.5
172.5°	1954.0	1953.4	1952.8	1953.4	1955.3	1957.2	1959.1	1961.0	1959.1	1957.2	1955.3
175°	1961.4	1960.8	1960.2	1961.0	1963.2	1965.4	1967.6	1969.8	1967.6	1965.4	1963.2
177.5°	1963.9	1963.6	1963.4	1964.1	1965.9	1967.7	1969.5	1971.2	1969.5	1967.7	1965.9
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1703.7	1700.5	1689.4	1683.6	1674.0	1665.0	1659.1	1661.8	1663.9	1662.8	1661.3
5°	1654.9	1642.3	1623.0	1606.4	1594.5	1572.6	1563.3	1558.7	1554.7	1550.0	1545.4
7.5°	1596.8	1576.9	1549.2	1525.6	1503.3	1476.1	1460.6	1451.3	1441.8	1431.3	1422.0
10°	1555.4	1527.5	1498.3	1465.1	1438.6	1414.0	1392.1	1377.5	1364.3	1351.6	1342.4
12.5°	1511.8	1479.7	1443.6	1398.2	1369.0	1333.9	1330.5	1304.8	1284.1	1276.3	1265.4
15°	1442.6	1397.4	1351.6	1297.9	1274.7	1242.8	1222.9	1203.0	1185.1	1172.5	1169.2
17.5°	1363.9	1305.5	1259.9	1221.3	1183.2	1150.6	1132.3	1116.4	1101.6	1084.8	1082.5
20°	1303.9	1253.4	1203.7	1169.8	1130.7	1097.5	1074.9	1059.0	1046.4	1036.5	1027.8
22.5°	1247.1	1191.9	1146.3	1109.3	1070.7	1043.9	1026.1	1010.7	1000.2	989.2	981.1
25°	1155.9	1112.8	1063.0	1021.2	989.3	972.1	957.5	944.2	937.6	930.3	921.0
27.5°	1076.1	1028.2	981.7	949.3	921.3	906.0	895.7	886.6	880.4	876.1	870.8
30°	1019.9	971.4	934.9	903.1	879.9	864.6	858.0	852.7	845.4	842.7	840.1
32.5°	965.7	922.1	890.9	863.3	841.1	831.2	825.1	820.3	814.6	811.9	806.6
35°	889.2	852.7	822.1	806.9	789.0	780.3	775.7	769.1	763.7	761.1	760.4
37.5°	817.1	785.4	765.3	745.7	738.1	732.8	726.5	721.9	720.3	719.9	719.3
40°	770.4	744.5	726.6	710.7	707.3	699.4	694.1	690.1	690.1	690.8	690.1
42.5°	727.9	704.7	688.9	675.1	671.2	666.5	661.2	660.9	662.0	664.2	662.0
45°	663.5	647.0	635.7	629.0	621.7	617.1	616.4	618.4	619.1	619.8	621.7
47.5°	604.4	593.3	583.1	575.8	572.6	571.8	571.0	574.5	577.7	578.9	581.9
50°	569.3	556.7	548.1	543.4	540.8	539.5	540.8	544.8	547.4	550.7	552.7
52.5°	530.0	521.1	515.2	511.6	510.5	511.3	511.6	516.1	520.4	521.5	522.5
55°	475.8	469.1	467.8	461.8	464.5	463.8	467.1	469.8	473.8	477.8	478.4
57.5°	421.6	416.3	412.7	413.3	414.1	417.0	419.8	424.4	428.7	432.9	433.3
60°	385.5	382.9	380.9	380.9	382.2	386.2	389.5	394.1	396.8	399.5	401.4
62.5°	352.6	350.0	348.0	349.0	352.5	354.9	358.7	361.2	363.9	366.5	367.5
65°	300.6	299.3	301.3	302.6	303.2	306.6	311.2	313.2	315.8	317.2	321.8
67.5°	252.7	252.9	252.7	254.5	258.4	259.2	263.6	268.2	268.7	271.3	274.3
70°	220.3	221.6	223.0	224.3	227.6	228.9	232.2	234.2	236.9	238.9	240.9
72.5°	190.6	190.8	192.2	191.9	194.7	197.6	200.4	202.4	205.0	207.6	209.5
75°	146.6	146.6	148.0	148.6	152.0	155.3	154.6	155.9	158.6	161.2	162.6
77.5°	107.1	105.6	107.1	107.8	108.8	111.6	112.1	114.0	117.0	116.1	117.6
80°	81.6	79.6	81.6	82.3	82.3	85.6	85.6	86.9	88.9	86.9	88.9
82.5°	58.3	57.3	58.8	58.9	60.0	60.1	61.2	61.4	63.4	62.5	63.4
85°	29.2	28.5	29.2	28.5	29.2	29.9	29.9	29.2	29.2	30.5	28.5
87.5°	12.1	12.2	12.1	12.6	12.6	12.6	12.4	12.7	13.0	12.3	12.5
90°	15.3	18.3	20.9	23.4	25.9	28.4	30.0	31.6	33.2	34.8	35.9
92.5°	27.5	27.9	29.2	30.5	31.7	33.0	33.8	34.6	35.5	36.3	36.9
95°	50.7	46.6	48.8	51.0	53.3	55.5	57.0	58.6	60.2	61.8	62.4
97.5°	65.9	53.8	58.9	64.0	69.1	74.2	75.5	76.8	78.0	79.3	80.1
100°	78.5	59.6	64.9	70.3	75.7	81.1	83.6	86.1	88.7	91.2	92.8
102.5°	290.2	263.1	218.2	173.2	128.3	83.3	86.6	89.9	93.2	96.5	98.6
105°	470.3	431.9	345.6	259.3	173.0	86.8	90.2	93.7	97.2	100.7	103.0
107.5°	583.3	535.4	431.9	328.4	224.9	121.5	117.9	114.4	110.8	107.3	106.2
110°	656.6	614.2	522.9	431.6	340.2	248.9	217.3	185.7	154.1	122.5	107.3



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	726.4	718.0	695.5	672.9	650.3	627.8	512.5	397.2	281.9	166.6	109.4
115°	839.3	845.9	853.8	861.7	869.6	877.5	731.2	584.9	438.5	292.2	207.6
117.5°	944.5	950.2	955.6	961.1	966.5	972.0	936.6	901.2	865.8	830.4	775.3
120°	1014.5	1019.7	1025.4	1031.1	1036.8	1042.5	1046.3	1050.1	1053.9	1057.7	1038.2
122.5°	1079.3	1084.9	1091.0	1097.2	1103.4	1109.6	1111.9	1114.2	1116.5	1118.7	1115.7
125°	1172.7	1177.8	1183.8	1189.8	1195.8	1201.8	1204.0	1206.2	1208.4	1210.6	1212.2
127.5°	1262.4	1266.9	1271.4	1275.9	1280.4	1284.9	1288.1	1291.3	1294.5	1297.7	1299.5
130°	1320.2	1324.4	1327.9	1331.4	1334.8	1338.3	1341.8	1345.3	1348.8	1352.2	1353.8
132.5°	1374.0	1377.9	1381.4	1384.8	1388.3	1391.8	1394.8	1397.7	1400.7	1403.7	1405.0
135°	1451.0	1454.9	1457.8	1460.6	1463.5	1466.3	1469.5	1472.6	1475.8	1479.0	1480.2
137.5°	1519.7	1523.1	1526.3	1529.6	1532.8	1536.0	1539.1	1542.2	1545.3	1548.4	1549.4
140°	1564.6	1567.6	1571.1	1574.6	1578.1	1581.5	1584.4	1587.2	1590.1	1592.9	1593.5
142.5°	1604.6	1607.7	1611.7	1615.7	1619.6	1623.6	1626.2	1628.8	1631.4	1634.0	1634.5
145°	1658.5	1661.0	1666.4	1671.8	1677.1	1682.5	1684.7	1686.9	1689.1	1691.4	1691.7
147.5°	1711.0	1713.0	1718.3	1723.7	1729.0	1734.3	1735.9	1737.6	1739.2	1740.9	1741.0
150°	1743.3	1744.8	1749.8	1754.9	1759.9	1765.0	1766.9	1768.8	1770.7	1772.6	1772.7
152.5°	1773.1	1774.2	1779.0	1783.8	1788.6	1793.4	1795.3	1797.2	1799.1	1801.0	1800.9
155°	1816.2	1816.7	1820.5	1824.3	1828.1	1831.8	1833.7	1835.6	1837.5	1839.4	1839.1
157.5°	1853.0	1853.1	1855.7	1858.4	1861.0	1863.7	1865.9	1868.0	1870.1	1872.3	1872.1
160°	1875.5	1875.5	1877.4	1879.3	1881.1	1883.0	1884.9	1886.8	1888.7	1890.6	1890.5
162.5°	1893.7	1893.5	1895.2	1896.8	1898.5	1900.1	1902.3	1904.4	1906.6	1908.7	1908.4
165°	1918.1	1917.7	1918.6	1919.5	1920.5	1921.4	1923.7	1925.9	1928.1	1930.3	1930.3
167.5°	1936.3	1935.8	1936.7	1937.6	1938.5	1939.4	1941.6	1943.8	1946.0	1948.2	1947.9
170°	1946.6	1945.9	1946.6	1947.2	1947.8	1948.5	1950.7	1952.9	1955.1	1957.3	1957.0
172.5°	1953.4	1952.8	1953.4	1954.0	1954.7	1955.3	1957.5	1959.7	1961.9	1964.1	1963.8
175°	1961.0	1960.2	1960.8	1961.4	1962.1	1962.7	1964.9	1967.1	1969.3	1971.5	1971.1
177.5°	1964.1	1963.4	1963.6	1963.9	1964.1	1964.4	1966.2	1967.9	1969.7	1971.5	1971.2
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1655.9	1654.9	1654.9	1650.1	1654.9	1654.9	1655.9	1661.3	1662.8	1663.9	1661.8
5°	1536.1	1534.1	1530.8	1534.1	1530.8	1534.1	1536.1	1545.4	1550.0	1554.7	1558.7
7.5°	1417.6	1409.6	1408.4	1400.6	1408.4	1409.6	1417.6	1422.0	1431.3	1441.8	1451.3
10°	1331.1	1325.8	1325.1	1312.5	1325.1	1325.8	1331.1	1342.4	1351.6	1364.3	1377.5
12.5°	1265.3	1252.5	1255.0	1247.7	1255.0	1252.5	1265.3	1265.4	1276.3	1284.1	1304.8
15°	1151.3	1151.3	1148.6	1137.3	1148.6	1151.3	1151.3	1169.2	1172.5	1185.1	1203.0
17.5°	1069.4	1068.0	1061.7	1064.9	1061.7	1068.0	1069.4	1082.5	1084.8	1101.6	1116.4
20°	1020.5	1016.6	1008.6	1008.6	1008.6	1016.6	1020.5	1027.8	1036.5	1046.4	1059.0
22.5°	974.4	974.1	965.6	968.2	965.6	974.1	974.4	981.1	989.2	1000.2	1010.7
25°	920.3	915.0	911.1	913.0	911.1	915.0	920.3	921.0	930.3	937.6	944.2
27.5°	869.1	866.2	865.9	860.5	865.9	866.2	869.1	870.8	876.1	880.4	886.6
30°	839.4	832.8	834.1	830.8	834.1	832.8	839.4	840.1	842.7	845.4	852.7
32.5°	805.4	803.0	801.7	798.9	801.7	803.0	805.4	806.6	811.9	814.6	820.3
35°	759.1	759.8	756.4	757.8	756.4	759.8	759.1	760.4	761.1	763.7	769.1
37.5°	718.6	720.7	719.2	719.6	719.2	720.7	718.6	719.3	719.9	720.3	721.9
40°	692.1	692.1	692.1	694.1	692.1	692.1	692.1	690.1	690.8	690.1	690.1
42.5°	666.6	665.5	664.5	664.3	664.5	665.5	666.6	662.0	664.2	662.0	660.9
45°	623.1	625.1	625.7	622.4	625.7	625.1	623.1	621.7	619.8	619.1	618.4
47.5°	583.7	583.9	583.7	586.6	583.7	583.9	583.7	581.9	578.9	577.7	574.5
50°	556.1	554.7	556.1	554.7	556.1	554.7	556.1	552.7	550.7	547.4	544.8
52.5°	526.9	527.1	526.3	526.1	526.3	527.1	526.9	522.5	521.5	520.4	516.1
55°	481.1	482.4	481.7	481.7	481.7	482.4	481.1	478.4	477.8	473.8	469.8
57.5°	433.7	434.9	435.8	432.9	435.8	434.9	433.7	433.3	432.9	428.7	424.4
60°	400.8	404.1	403.4	402.1	403.4	404.1	400.8	401.4	399.5	396.8	394.1
62.5°	370.5	371.7	371.6	371.3	371.6	371.7	370.5	367.5	366.5	363.9	361.2
65°	323.8	325.1	323.1	325.1	323.1	325.1	323.8	321.8	317.2	315.8	313.2
67.5°	273.5	273.9	275.4	276.3	275.4	273.9	273.5	274.3	271.3	268.7	268.2
70°	242.2	241.5	243.5	245.5	243.5	241.5	242.2	240.9	238.9	236.9	234.2
72.5°	209.3	210.7	210.1	211.5	210.1	210.7	209.3	209.5	207.6	205.0	202.4
75°	161.2	163.2	162.6	164.6	162.6	163.2	161.2	162.6	161.2	158.6	155.9
77.5°	116.5	116.8	116.5	117.6	116.5	116.8	116.5	117.6	116.1	117.0	114.0
80°	88.9	87.6	86.3	88.9	86.3	87.6	88.9	88.9	86.9	88.9	86.9
82.5°	61.8	62.6	61.3	61.3	61.3	62.6	61.8	63.4	62.5	63.4	61.4
85°	28.5	27.9	26.5	26.5	26.5	27.9	28.5	28.5	30.5	29.2	29.2
87.5°	12.6	12.2	12.3	11.9	12.3	12.2	12.6	12.5	12.3	13.0	12.7
90°	36.5	37.1	37.8	38.4	37.8	37.1	36.5	35.9	34.8	33.2	31.6
92.5°	37.3	37.6	38.0	38.4	38.0	37.6	37.3	36.9	36.3	35.5	34.6
95°	62.1	61.8	61.5	61.2	61.5	61.8	62.1	62.4	61.8	60.2	58.6
97.5°	80.5	80.9	81.3	81.6	81.3	80.9	80.5	80.1	79.3	78.0	76.8
100°	93.4	94.0	94.7	95.3	94.7	94.0	93.4	92.8	91.2	88.7	86.1
102.5°	99.5	100.3	101.2	102.1	101.2	100.3	99.5	98.6	96.5	93.2	89.9
105°	104.3	105.6	106.8	108.1	106.8	105.6	104.3	103.0	100.7	97.2	93.7
107.5°	107.4	108.7	110.0	111.2	110.0	108.7	107.4	106.2	107.3	110.8	114.4
110°	108.6	109.8	111.1	112.4	111.1	109.8	108.6	107.3	122.5	154.1	185.7



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	110.5	111.5	112.5	113.5	112.5	111.5	110.5	109.4	166.6	281.9	397.2
115°	184.9	162.1	139.4	116.6	139.4	162.1	184.9	207.6	292.2	438.5	584.9
117.5°	700.5	625.7	550.9	476.2	550.9	625.7	700.5	775.3	830.4	865.8	901.2
120°	995.6	952.9	910.2	867.6	910.2	952.9	995.6	1038.2	1057.7	1053.9	1050.1
122.5°	1107.4	1099.2	1090.9	1082.6	1090.9	1099.2	1107.4	1115.7	1118.7	1116.5	1114.2
125°	1213.2	1214.1	1215.1	1216.0	1215.1	1214.1	1213.2	1212.2	1210.6	1208.4	1206.2
127.5°	1299.6	1299.8	1300.0	1300.2	1300.0	1299.8	1299.6	1299.5	1297.7	1294.5	1291.3
130°	1353.5	1353.2	1352.9	1352.5	1352.9	1353.2	1353.5	1353.8	1352.2	1348.8	1345.3
132.5°	1404.7	1404.4	1404.1	1403.7	1404.1	1404.4	1404.7	1405.0	1403.7	1400.7	1397.7
135°	1479.6	1479.0	1478.3	1477.7	1478.3	1479.0	1479.6	1480.2	1479.0	1475.8	1472.6
137.5°	1548.3	1547.3	1546.2	1545.1	1546.2	1547.3	1548.3	1549.4	1548.4	1545.3	1542.2
140°	1592.0	1590.4	1588.8	1587.2	1588.8	1590.4	1592.0	1593.5	1592.9	1590.1	1587.2
142.5°	1632.9	1631.3	1629.8	1628.2	1629.8	1631.3	1632.9	1634.5	1634.0	1631.4	1628.8
145°	1690.1	1688.5	1686.9	1685.4	1686.9	1688.5	1690.1	1691.7	1691.4	1689.1	1686.9
147.5°	1739.7	1738.4	1737.0	1735.7	1737.0	1738.4	1739.7	1741.0	1740.9	1739.2	1737.6
150°	1771.2	1769.6	1768.0	1766.4	1768.0	1769.6	1771.2	1772.7	1772.6	1770.7	1768.8
152.5°	1798.8	1796.8	1794.7	1792.6	1794.7	1796.8	1798.8	1800.9	1801.0	1799.1	1797.2
155°	1836.6	1834.1	1831.5	1829.0	1831.5	1834.1	1836.6	1839.1	1839.4	1837.5	1835.6
157.5°	1869.7	1867.2	1864.7	1862.3	1864.7	1867.2	1869.7	1872.1	1872.3	1870.1	1868.0
160°	1888.3	1886.0	1883.8	1881.6	1883.8	1886.0	1888.3	1890.5	1890.6	1888.7	1886.8
162.5°	1905.7	1903.0	1900.3	1897.6	1900.3	1903.0	1905.7	1908.4	1908.7	1906.6	1904.4
165°	1928.1	1925.9	1923.7	1921.4	1923.7	1925.9	1928.1	1930.3	1930.3	1928.1	1925.9
167.5°	1945.1	1942.2	1939.4	1936.5	1939.4	1942.2	1945.1	1947.9	1948.2	1946.0	1943.8
170°	1954.2	1951.3	1948.5	1945.6	1948.5	1951.3	1954.2	1957.0	1957.3	1955.1	1952.9
172.5°	1961.0	1958.1	1955.3	1952.4	1955.3	1958.1	1961.0	1963.8	1964.1	1961.9	1959.7
175°	1967.9	1964.7	1961.6	1958.4	1961.6	1964.7	1967.9	1971.1	1971.5	1969.3	1967.1
177.5°	1968.9	1966.7	1964.4	1962.1	1964.4	1966.7	1968.9	1971.2	1971.5	1969.7	1967.9
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1659.1	1665.0	1674.0	1683.6	1689.4	1700.5	1703.7	1709.0	1713.8	1725.0	1736.6
5°	1563.3	1572.6	1594.5	1606.4	1623.0	1642.3	1654.9	1668.2	1682.8	1708.0	1731.2
7.5°	1460.6	1476.1	1503.3	1525.6	1549.2	1576.9	1596.8	1623.0	1644.8	1680.4	1714.3
10°	1392.1	1414.0	1438.6	1465.1	1498.3	1527.5	1555.4	1588.5	1615.1	1657.5	1697.4
12.5°	1330.5	1333.9	1369.0	1398.2	1443.6	1479.7	1511.8	1554.6	1580.6	1631.0	1672.9
15°	1222.9	1242.8	1274.7	1297.9	1351.6	1397.4	1442.6	1487.0	1516.9	1579.2	1634.3
17.5°	1132.3	1150.6	1183.2	1221.3	1259.9	1305.5	1363.9	1410.7	1451.3	1522.6	1587.7
20°	1074.9	1097.5	1130.7	1169.8	1203.7	1253.4	1303.9	1357.6	1401.4	1481.7	1558.0
22.5°	1026.1	1043.9	1070.7	1109.3	1146.3	1191.9	1247.1	1305.6	1351.5	1438.2	1515.5
25°	957.5	972.1	989.3	1021.2	1063.0	1112.8	1155.9	1220.3	1287.3	1368.2	1461.8
27.5°	895.7	906.0	921.3	949.3	981.7	1028.2	1076.1	1137.2	1204.6	1292.5	1391.2
30°	858.0	864.6	879.9	903.1	934.9	971.4	1019.9	1078.3	1147.3	1236.2	1334.4
32.5°	825.1	831.2	841.1	863.3	890.9	922.1	965.7	1024.1	1089.9	1177.3	1286.1
35°	775.7	780.3	789.0	806.9	822.1	852.7	889.2	942.2	1003.9	1087.6	1200.4
37.5°	726.5	732.8	738.1	745.7	765.3	785.4	817.1	861.9	922.5	1006.9	1114.4
40°	694.1	699.4	707.3	710.7	726.6	744.5	770.4	811.5	872.6	949.5	1054.4
42.5°	661.2	666.5	671.2	675.1	688.9	704.7	727.9	763.2	817.4	892.2	996.0
45°	616.4	617.1	621.7	629.0	635.7	647.0	663.5	694.1	735.9	806.2	900.4
47.5°	571.0	571.8	572.6	575.8	583.1	593.3	604.4	629.2	666.6	722.7	814.4
50°	540.8	539.5	540.8	543.4	548.1	556.7	569.3	587.2	617.8	670.2	754.5
52.5°	511.6	511.3	510.5	511.6	515.2	521.1	530.0	545.3	572.6	620.8	695.0
55°	467.1	463.8	464.5	461.8	467.8	469.1	475.8	488.4	512.3	545.4	615.1
57.5°	419.8	417.0	414.1	413.3	412.7	416.3	421.6	431.6	449.9	478.9	535.5
60°	389.5	386.2	382.2	380.9	380.9	382.9	385.5	392.8	410.1	436.0	482.4
62.5°	358.7	354.9	352.5	349.0	348.0	350.0	352.6	357.8	370.3	394.5	434.6
65°	311.2	306.6	303.2	302.6	301.3	299.3	300.6	305.9	315.8	335.1	366.9
67.5°	263.6	259.2	258.4	254.5	252.7	252.9	252.7	257.2	263.2	279.8	303.5
70°	232.2	228.9	227.6	224.3	223.0	221.6	220.3	224.3	230.3	244.2	264.8
72.5°	200.4	197.6	194.7	191.9	192.2	190.8	190.6	193.0	197.9	210.7	226.5
75°	154.6	155.3	152.0	148.6	148.0	146.6	146.6	148.6	150.6	160.6	173.2
77.5°	112.1	111.6	108.8	107.8	107.1	105.6	107.1	108.4	109.5	116.1	125.4
80°	85.6	85.6	82.3	82.3	81.6	79.6	81.6	80.3	82.9	89.6	96.2
82.5°	61.2	60.1	60.0	58.9	58.8	57.3	58.3	59.6	60.6	65.2	69.1
85°	29.9	29.9	29.2	28.5	29.2	28.5	29.2	29.9	30.5	32.5	35.8
87.5°	12.4	12.6	12.6	12.6	12.1	12.2	12.1	11.9	12.3	12.1	12.0
90°	30.0	28.4	25.9	23.4	20.9	18.3	15.3	11.9	8.4	4.9	1.4
92.5°	33.8	33.0	31.7	30.5	29.2	27.9	27.5	27.8	28.1	28.4	28.7
95°	57.0	55.5	53.3	51.0	48.8	46.6	50.7	61.2	71.6	82.0	92.4
97.5°	75.5	74.2	69.1	64.0	58.9	53.8	65.9	95.3	124.7	154.1	183.5
100°	83.6	81.1	75.7	70.3	64.9	59.6	78.5	121.8	165.1	208.4	251.7
102.5°	86.6	83.3	128.3	173.2	218.2	263.1	290.2	299.3	308.5	317.7	326.8
105°	90.2	86.8	173.0	259.3	345.6	431.9	470.3	460.8	451.3	441.8	432.4
107.5°	117.9	121.5	224.9	328.4	431.9	535.4	583.3	575.6	568.0	560.3	552.7
110°	217.3	248.9	340.2	431.6	522.9	614.2	656.6	650.0	643.3	636.7	630.1



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	512.5	627.8	650.3	672.9	695.5	718.0	726.4	720.5	714.6	708.7	702.9
115°	731.2	877.5	869.6	861.7	853.8	845.9	839.3	833.9	828.5	823.2	817.8
117.5°	936.6	972.0	966.5	961.1	955.6	950.2	944.5	938.5	932.5	926.5	920.5
120°	1046.3	1042.5	1036.8	1031.1	1025.4	1019.7	1014.5	1009.8	1005.0	1000.3	995.6
122.5°	1111.9	1109.6	1103.4	1097.2	1091.0	1084.9	1079.3	1074.3	1069.3	1064.3	1059.3
125°	1204.0	1201.8	1195.8	1189.8	1183.8	1177.8	1172.7	1168.6	1164.5	1160.4	1156.3
127.5°	1288.1	1284.9	1280.4	1275.9	1271.4	1266.9	1262.4	1257.8	1253.3	1248.7	1244.2
130°	1341.8	1338.3	1334.8	1331.4	1327.9	1324.4	1320.2	1315.1	1310.0	1305.0	1299.9
132.5°	1394.8	1391.8	1388.3	1384.8	1381.4	1377.9	1374.0	1369.7	1365.4	1361.1	1356.8
135°	1469.5	1466.3	1463.5	1460.6	1457.8	1454.9	1451.0	1445.9	1440.9	1435.8	1430.8
137.5°	1539.1	1536.0	1532.8	1529.6	1526.3	1523.1	1519.7	1516.2	1512.7	1509.1	1505.6
140°	1584.4	1581.5	1578.1	1574.6	1571.1	1567.6	1564.6	1562.1	1559.6	1557.0	1554.5
142.5°	1626.2	1623.6	1619.6	1615.7	1611.7	1607.7	1604.6	1602.3	1600.0	1597.7	1595.5
145°	1684.7	1682.5	1677.1	1671.8	1666.4	1661.0	1658.5	1658.8	1659.1	1659.4	1659.8
147.5°	1735.9	1734.3	1729.0	1723.7	1718.3	1713.0	1711.0	1712.2	1713.4	1714.6	1715.8
150°	1766.9	1765.0	1759.9	1754.9	1749.8	1744.8	1743.3	1745.6	1747.8	1750.0	1752.2
152.5°	1795.3	1793.4	1788.6	1783.8	1779.0	1774.2	1773.1	1775.5	1778.0	1780.5	1782.9
155°	1833.7	1831.8	1828.1	1824.3	1820.5	1816.7	1816.2	1819.0	1821.9	1824.7	1827.6
157.5°	1865.9	1863.7	1861.0	1858.4	1855.7	1853.1	1853.0	1855.4	1857.8	1860.2	1862.6
160°	1884.9	1883.0	1881.1	1879.3	1877.4	1875.5	1875.5	1877.4	1879.3	1881.1	1883.0
162.5°	1902.3	1900.1	1898.5	1896.8	1895.2	1893.5	1893.7	1895.6	1897.5	1899.4	1901.2
165°	1923.7	1921.4	1920.5	1919.5	1918.6	1917.7	1918.1	1920.0	1921.9	1923.8	1925.7
167.5°	1941.6	1939.4	1938.5	1937.6	1936.7	1935.8	1936.3	1938.2	1940.1	1942.0	1943.9
170°	1950.7	1948.5	1947.8	1947.2	1946.6	1945.9	1946.6	1948.5	1950.4	1952.3	1954.2
172.5°	1957.5	1955.3	1954.7	1954.0	1953.4	1952.8	1953.4	1955.3	1957.2	1959.1	1961.0
175°	1964.9	1962.7	1962.1	1961.4	1960.8	1960.2	1961.0	1963.2	1965.4	1967.6	1969.8
177.5°	1966.2	1964.4	1964.1	1963.9	1963.6	1963.4	1964.1	1965.9	1967.7	1969.5	1971.2
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1735.6	1738.2	1746.7	1755.2	1764.8	1767.4	1771.7	1768.0	1766.9	1777.0	1784.4
5°	1740.5	1752.4	1775.7	1796.9	1814.8	1827.4	1840.7	1846.0	1855.9	1869.9	1887.1
7.5°	1734.9	1758.1	1794.6	1825.6	1859.3	1883.5	1902.5	1918.7	1938.4	1964.8	1993.6
10°	1728.5	1759.7	1804.2	1842.0	1883.1	1914.3	1940.2	1965.4	1994.6	2031.1	2068.9
12.5°	1716.9	1753.9	1809.5	1854.2	1907.0	1937.7	1972.6	2027.0	2058.3	2109.2	2162.4
15°	1693.4	1734.5	1812.1	1867.2	1926.9	1985.3	2049.7	2101.5	2153.2	2183.1	2258.1
17.5°	1658.5	1718.9	1804.8	1869.1	1945.0	2037.0	2109.3	2167.9	2227.7	2276.1	2313.7
20°	1630.3	1696.0	1794.2	1871.2	1961.4	2060.3	2143.3	2203.0	2254.7	2295.2	2318.4
22.5°	1594.8	1677.4	1773.0	1863.2	1978.4	2076.2	2163.4	2210.4	2253.7	2273.4	2282.3
25°	1538.8	1638.3	1746.5	1856.6	1986.7	2090.2	2169.8	2198.3	2210.9	2191.7	2159.8
27.5°	1478.4	1589.3	1715.8	1844.1	1981.6	2081.1	2138.2	2133.7	2112.3	2050.1	2000.3
30°	1433.3	1555.4	1691.4	1831.4	1969.4	2066.3	2099.5	2066.3	2017.8	1948.2	1877.2
32.5°	1386.0	1512.4	1665.4	1813.3	1947.1	2032.3	2039.5	1982.4	1907.4	1828.2	1739.7
35°	1314.5	1451.2	1616.4	1773.0	1899.7	1953.5	1921.6	1820.8	1731.9	1623.7	1502.9
37.5°	1233.7	1384.6	1550.3	1713.9	1828.7	1842.8	1763.7	1657.5	1532.1	1405.0	1262.9
40°	1173.2	1333.1	1503.6	1668.8	1770.3	1755.7	1654.9	1538.1	1388.8	1233.5	1101.5
42.5°	1119.0	1278.9	1452.6	1614.7	1696.0	1655.9	1538.1	1394.8	1234.3	1088.1	967.2
45°	1025.2	1189.7	1367.6	1524.2	1570.6	1498.3	1342.4	1183.1	1025.2	903.1	807.5
47.5°	934.1	1096.8	1272.9	1410.6	1427.0	1329.7	1159.3	995.5	859.7	760.3	692.9
50°	867.3	1030.5	1205.0	1327.8	1322.4	1205.0	1029.8	873.9	760.4	680.1	635.0
52.5°	807.3	961.5	1129.1	1240.7	1212.6	1084.5	917.3	778.9	685.6	622.8	581.9
55°	714.0	856.6	1015.9	1105.5	1053.7	911.7	770.4	658.9	589.9	542.8	510.9
57.5°	621.3	755.1	891.4	946.6	889.4	758.3	640.5	559.6	507.7	472.8	452.1
60°	564.0	680.8	802.2	850.0	781.7	664.9	572.0	499.7	457.8	429.3	410.7
62.5°	506.7	611.3	725.8	751.8	689.3	590.6	508.3	448.2	413.8	388.4	370.9
65°	428.7	514.2	601.2	618.4	560.7	484.4	419.4	380.2	349.7	331.1	317.2
67.5°	351.5	420.3	481.9	495.8	445.2	392.3	345.3	311.2	290.5	275.1	263.3
70°	305.9	360.3	410.7	422.0	381.5	334.4	298.6	271.4	252.8	239.5	228.3
72.5°	257.6	303.0	344.9	352.5	319.4	283.5	254.0	232.6	216.2	207.7	196.9
75°	197.1	223.6	256.1	258.1	236.2	214.3	191.8	177.8	169.2	158.6	153.3
77.5°	139.1	159.9	178.5	182.1	169.1	154.2	141.6	130.6	123.3	118.4	113.5
80°	106.2	122.8	130.7	135.4	126.1	115.5	108.2	100.9	96.2	92.9	89.6
82.5°	75.9	86.1	93.6	97.1	92.1	85.7	78.4	74.3	70.7	67.9	66.8
85°	38.5	43.1	47.8	49.1	47.8	45.1	41.1	41.1	39.1	38.5	38.5
87.5°	14.3	17.1	17.8	20.1	19.6	20.1	20.6	20.6	20.6	20.3	20.1
90°	4.9	8.4	11.9	15.3	18.3	20.9	23.4	25.9	28.4	30.0	31.6
92.5°	28.4	28.1	27.8	27.5	27.9	29.2	30.5	31.7	33.0	33.8	34.6
95°	82.0	71.6	61.2	50.7	46.6	48.8	51.0	53.3	55.5	57.0	58.6
97.5°	154.1	124.7	95.3	65.9	53.8	58.9	64.0	69.1	74.2	75.5	76.8
100°	208.4	165.1	121.8	78.5	59.6	64.9	70.3	75.7	81.1	83.6	86.1
102.5°	317.7	308.5	299.3	290.2	263.1	218.2	173.2	128.3	83.3	86.6	89.9
105°	441.8	451.3	460.8	470.3	431.9	345.6	259.3	173.0	86.8	90.2	93.7
107.5°	560.3	568.0	575.6	583.3	535.4	431.9	328.4	224.9	121.5	117.9	114.4
110°	636.7	643.3	650.0	656.6	614.2	522.9	431.6	340.2	248.9	217.3	185.7





TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	708.7	714.6	720.5	726.4	718.0	695.5	672.9	650.3	627.8	512.5	397.2
115°	823.2	828.5	833.9	839.3	845.9	853.8	861.7	869.6	877.5	731.2	584.9
117.5°	926.5	932.5	938.5	944.5	950.2	955.6	961.1	966.5	972.0	936.6	901.2
120°	1000.3	1005.0	1009.8	1014.5	1019.7	1025.4	1031.1	1036.8	1042.5	1046.3	1050.1
122.5°	1064.3	1069.3	1074.3	1079.3	1084.9	1091.0	1097.2	1103.4	1109.6	1111.9	1114.2
125°	1160.4	1164.5	1168.6	1172.7	1177.8	1183.8	1189.8	1195.8	1201.8	1204.0	1206.2
127.5°	1248.7	1253.3	1257.8	1262.4	1266.9	1271.4	1275.9	1280.4	1284.9	1288.1	1291.3
130°	1305.0	1310.0	1315.1	1320.2	1324.4	1327.9	1331.4	1334.8	1338.3	1341.8	1345.3
132.5°	1361.1	1365.4	1369.7	1374.0	1377.9	1381.4	1384.8	1388.3	1391.8	1394.8	1397.7
135°	1435.8	1440.9	1445.9	1451.0	1454.9	1457.8	1460.6	1463.5	1466.3	1469.5	1472.6
137.5°	1509.1	1512.7	1516.2	1519.7	1523.1	1526.3	1529.6	1532.8	1536.0	1539.1	1542.2
140°	1557.0	1559.6	1562.1	1564.6	1567.6	1571.1	1574.6	1578.1	1581.5	1584.4	1587.2
142.5°	1597.7	1600.0	1602.3	1604.6	1607.7	1611.7	1615.7	1619.6	1623.6	1626.2	1628.8
145°	1659.4	1659.1	1658.8	1658.5	1661.0	1666.4	1671.8	1677.1	1682.5	1684.7	1686.9
147.5°	1714.6	1713.4	1712.2	1711.0	1713.0	1718.3	1723.7	1729.0	1734.3	1735.9	1737.6
150°	1750.0	1747.8	1745.6	1743.3	1744.8	1749.8	1754.9	1759.9	1765.0	1766.9	1768.8
152.5°	1780.5	1778.0	1775.5	1773.1	1774.2	1779.0	1783.8	1788.6	1793.4	1795.3	1797.2
155°	1824.7	1821.9	1819.0	1816.2	1816.7	1820.5	1824.3	1828.1	1831.8	1833.7	1835.6
157.5°	1860.2	1857.8	1855.4	1853.0	1853.1	1855.7	1858.4	1861.0	1863.7	1865.9	1868.0
160°	1881.1	1879.3	1877.4	1875.5	1875.5	1877.4	1879.3	1881.1	1883.0	1884.9	1886.8
162.5°	1899.4	1897.5	1895.6	1893.7	1893.5	1895.2	1896.8	1898.5	1900.1	1902.3	1904.4
165°	1923.8	1921.9	1920.0	1918.1	1917.7	1918.6	1919.5	1920.5	1921.4	1923.7	1925.9
167.5°	1942.0	1940.1	1938.2	1936.3	1935.8	1936.7	1937.6	1938.5	1939.4	1941.6	1943.8
170°	1952.3	1950.4	1948.5	1946.6	1945.9	1946.6	1947.2	1947.8	1948.5	1950.7	1952.9
172.5°	1959.1	1957.2	1955.3	1953.4	1952.8	1953.4	1954.0	1954.7	1955.3	1957.5	1959.7
175°	1967.6	1965.4	1963.2	1961.0	1960.2	1960.8	1961.4	1962.1	1962.7	1964.9	1967.1
177.5°	1969.5	1967.7	1965.9	1964.1	1963.4	1963.6	1963.9	1964.1	1964.4	1966.2	1967.9
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1790.8	1798.2	1798.2	1799.3	1807.8	1806.7	1806.2
5°	1905.7	1917.0	1918.3	1930.3	1938.2	1935.6	1928.3
7.5°	2014.1	2035.1	2051.0	2059.9	2070.4	2076.9	2074.0
10°	2100.1	2130.6	2149.2	2161.8	2177.1	2188.4	2184.4
12.5°	2178.2	2214.5	2240.0	2261.6	2263.6	2278.1	2268.3
15°	2299.9	2338.3	2342.3	2358.2	2370.9	2369.5	2370.2
17.5°	2340.1	2352.4	2354.9	2355.3	2355.5	2350.8	2340.7
20°	2325.7	2321.1	2309.8	2301.2	2285.9	2283.9	2270.7
22.5°	2257.8	2243.1	2214.8	2196.1	2172.3	2166.1	2162.4
25°	2124.0	2091.5	2046.4	2003.2	1991.3	1968.1	1974.7
27.5°	1940.5	1889.8	1840.9	1805.9	1774.2	1739.4	1749.4
30°	1811.5	1754.4	1685.4	1632.3	1598.5	1565.3	1559.3
32.5°	1657.5	1573.9	1497.0	1450.2	1398.4	1377.4	1354.4
35°	1392.1	1310.5	1234.2	1168.5	1130.7	1101.5	1074.9
37.5°	1153.4	1059.4	997.8	944.6	917.3	900.6	904.8
40°	1005.3	923.0	877.9	837.4	812.2	800.2	802.9
42.5°	885.3	823.7	786.6	758.8	741.0	734.4	732.8
45°	749.1	714.6	684.1	668.2	659.6	652.3	647.6
47.5°	656.2	628.1	610.9	601.4	593.9	586.4	586.3
50°	600.5	581.9	570.0	560.0	554.1	548.8	553.4
52.5°	558.0	541.1	529.1	520.2	518.0	513.2	513.1
55°	495.0	481.7	473.1	465.1	461.2	458.5	455.2
57.5°	437.7	425.1	417.1	412.1	404.5	401.8	400.8
60°	396.8	386.8	378.9	372.2	368.9	363.6	363.6
62.5°	359.1	349.2	341.7	336.7	331.2	329.1	329.7
65°	304.6	296.6	289.3	284.0	282.7	278.7	280.0
67.5°	254.4	249.1	241.4	238.5	236.0	233.8	232.2
70°	221.0	215.7	211.7	207.7	205.7	205.7	205.7
72.5°	192.8	186.5	184.1	179.0	180.2	178.1	176.0
75°	149.3	145.3	143.3	141.3	138.0	138.0	138.0
77.5°	109.9	108.7	106.3	104.2	103.4	102.7	103.0
80°	84.9	84.3	82.9	82.9	81.6	81.0	79.6
82.5°	65.3	63.6	62.8	62.2	62.0	61.8	61.6
85°	37.2	35.8	35.8	36.5	35.2	35.2	35.8
87.5°	21.0	21.3	21.0	21.1	21.8	21.4	21.5
90°	33.2	34.8	35.9	36.5	37.1	37.8	38.4
92.5°	35.5	36.3	36.9	37.3	37.6	38.0	38.4
95°	60.2	61.8	62.4	62.1	61.8	61.5	61.2
97.5°	78.0	79.3	80.1	80.5	80.9	81.3	81.6
100°	88.7	91.2	92.8	93.4	94.0	94.7	95.3
102.5°	93.2	96.5	98.6	99.5	100.3	101.2	102.1
105°	97.2	100.7	103.0	104.3	105.6	106.8	108.1
107.5°	110.8	107.3	106.2	107.4	108.7	110.0	111.2
110°	154.1	122.5	107.3	108.6	109.8	111.1	112.4



TEST NUMBER: P331579

CATALOG NUMBER: S122DIW-S865D1440U835-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	281.9	166.6	109.4	110.5	111.5	112.5	113.5
115°	438.5	292.2	207.6	184.9	162.1	139.4	116.6
117.5°	865.8	830.4	775.3	700.5	625.7	550.9	476.2
120°	1053.9	1057.7	1038.2	995.6	952.9	910.2	867.6
122.5°	1116.5	1118.7	1115.7	1107.4	1099.2	1090.9	1082.6
125°	1208.4	1210.6	1212.2	1213.2	1214.1	1215.1	1216.0
127.5°	1294.5	1297.7	1299.5	1299.6	1299.8	1300.0	1300.2
130°	1348.8	1352.2	1353.8	1353.5	1353.2	1352.9	1352.5
132.5°	1400.7	1403.7	1405.0	1404.7	1404.4	1404.1	1403.7
135°	1475.8	1479.0	1480.2	1479.6	1479.0	1478.3	1477.7
137.5°	1545.3	1548.4	1549.4	1548.3	1547.3	1546.2	1545.1
140°	1590.1	1592.9	1593.5	1592.0	1590.4	1588.8	1587.2
142.5°	1631.4	1634.0	1634.5	1632.9	1631.3	1629.8	1628.2
145°	1689.1	1691.4	1691.7	1690.1	1688.5	1686.9	1685.4
147.5°	1739.2	1740.9	1741.0	1739.7	1738.4	1737.0	1735.7
150°	1770.7	1772.6	1772.7	1771.2	1769.6	1768.0	1766.4
152.5°	1799.1	1801.0	1800.9	1798.8	1796.8	1794.7	1792.6
155°	1837.5	1839.4	1839.1	1836.6	1834.1	1831.5	1829.0
157.5°	1870.1	1872.3	1872.1	1869.7	1867.2	1864.7	1862.3
160°	1888.7	1890.6	1890.5	1888.3	1886.0	1883.8	1881.6
162.5°	1906.6	1908.7	1908.4	1905.7	1903.0	1900.3	1897.6
165°	1928.1	1930.3	1930.3	1928.1	1925.9	1923.7	1921.4
167.5°	1946.0	1948.2	1947.9	1945.1	1942.2	1939.4	1936.5
170°	1955.1	1957.3	1957.0	1954.2	1951.3	1948.5	1945.6
172.5°	1961.9	1964.1	1963.8	1961.0	1958.1	1955.3	1952.4
175°	1969.3	1971.5	1971.1	1967.9	1964.7	1961.6	1958.4
177.5°	1969.7	1971.5	1971.2	1968.9	1966.7	1964.4	1962.1
180°	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5	1965.5

(END OF REPORT)