

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: NEO-RAY

Report Number: P331567

Luminaire Tested: **S122DIW-S865D970U835-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P331567
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-2,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S122DIW-S865D970U835-4F0-1E-UDD-A
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 865 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 970 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7682.3 lumens
Efficiency: N/A
Efficacy: 125.5 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.16 / 1.23
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 61.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	107	107	107	107	99	99	99	99	83	83	83	69	69	69	56	56	56	50
1	98	94	90	87	90	87	84	81	74	71	69	61	60	58	50	49	48	43
2	90	83	77	72	83	77	71	67	65	61	58	54	52	49	45	43	41	37
3	82	73	66	60	76	68	62	57	58	53	49	49	45	42	40	38	36	32
4	75	65	57	52	69	60	54	48	52	47	43	44	40	37	36	33	31	27
5	69	58	50	44	64	54	47	42	46	41	37	39	35	32	33	30	27	24
6	64	52	44	39	59	49	42	37	42	37	33	36	32	28	30	27	24	22
7	59	47	40	34	55	44	37	32	38	33	29	33	28	25	27	24	22	19
8	55	43	36	30	51	40	34	29	35	30	26	30	26	23	25	22	20	17
9	51	40	32	27	48	37	30	26	32	27	23	28	24	21	23	20	18	16
10	48	36	29	25	45	34	28	23	30	25	21	26	22	19	22	19	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	27876	27876	27876	27876
5°	31253	28058	24864	28058
10°	35813	27829	21518	27829
15°	39619	27318	19010	27318
20°	39015	26770	17330	26770
25°	35179	26042	16265	26042
30°	29071	24878	15489	24878
35°	21187	23660	14937	23660
40°	16923	22223	14629	22223
45°	14787	20559	14212	20559
50°	13901	18952	13933	18952
55°	12814	17315	13560	17315
60°	11741	15578	12984	15578
65°	10697	14017	12420	14017
70°	9711	12500	11589	12500
75°	8609	10805	10268	10805
80°	7401	8945	8266	8945
85°	6632	6632	4909	6632



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	164.4	2.1
10°-20°	478.0	6.2
20°-30°	693.8	9.0
30°-40°	732.1	9.5
40°-50°	648.2	8.4
50°-60°	517.3	6.7
60°-70°	351.6	4.6
70°-80°	180.3	2.3
80°-90°	46.7	0.6
90°-100°	44.1	0.6
100°-110°	161.5	2.1
110°-120°	431.8	5.6
120°-130°	712.8	9.3
130°-140°	758.0	9.9
140°-150°	704.6	9.2
150°-160°	566.5	7.4
160°-170°	365.0	4.8
170°-180°	125.6	1.6
0°-30°	1336.2	17.4
0°-40°	2068.3	26.9
0°-60°	3233.8	42.1
0°-90°	3812.4	49.6
90°-120°	637.4	8.3
90°-150°	2812.8	36.6
90°-180°	3870.0	50.4
0°-180°	7682.3	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1726	1726	1726	1726	1726	
5°	1928	1731	1534	1731	1928	193
15°	2370	1634	1137	1634	2370	654
25°	1975	1462	913	1462	1975	893
35°	1075	1200	758	1200	1075	699
45°	648	900	622	900	648	509
55°	455	615	482	615	455	408
65°	280	367	325	367	280	278
75°	138	173	165	173	138	147
85°	36	36	26	36	36	40
90°	26	1	26	1	26	13
95°	41	62	41	62	41	38
105°	73	290	73	290	73	76
115°	78	549	78	549	78	196
125°	817	777	817	777	817	707
135°	993	961	993	961	993	765
145°	1132	1115	1132	1115	1132	708
155°	1229	1228	1229	1228	1229	567
165°	1291	1294	1291	1294	1291	364
175°	1316	1323	1316	1323	1316	125
180°	1320	1320	1320	1320	1320	



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1806.2	1806.7	1807.8	1799.3	1798.2	1798.2	1790.8	1784.4	1777.0	1766.9	1768.0
5°	1928.3	1935.6	1938.2	1930.3	1918.3	1917.0	1905.7	1887.1	1869.9	1855.9	1846.0
7.5°	2074.0	2076.9	2070.4	2059.9	2051.0	2035.1	2014.1	1993.6	1964.8	1938.4	1918.7
10°	2184.4	2188.4	2177.1	2161.8	2149.2	2130.6	2100.1	2068.9	2031.1	1994.6	1965.4
12.5°	2268.3	2278.1	2263.6	2261.6	2240.0	2214.5	2178.2	2162.4	2109.2	2058.3	2027.0
15°	2370.2	2369.5	2370.9	2358.2	2342.3	2338.3	2299.9	2258.1	2183.1	2153.2	2101.5
17.5°	2340.7	2350.8	2355.5	2355.3	2354.9	2352.4	2340.1	2313.7	2276.1	2227.7	2167.9
20°	2270.7	2283.9	2285.9	2301.2	2309.8	2321.1	2325.7	2318.4	2295.2	2254.7	2203.0
22.5°	2162.4	2166.1	2172.3	2196.1	2214.8	2243.1	2257.8	2282.3	2273.4	2253.7	2210.4
25°	1974.7	1968.1	1991.3	2003.2	2046.4	2091.5	2124.0	2159.8	2191.7	2210.9	2198.3
27.5°	1749.4	1739.4	1774.2	1805.9	1840.9	1889.8	1940.5	2000.3	2050.1	2112.3	2133.7
30°	1559.3	1565.3	1598.5	1632.3	1685.4	1754.4	1811.5	1877.2	1948.2	2017.8	2066.3
32.5°	1354.4	1377.4	1398.4	1450.2	1497.0	1573.9	1657.5	1739.7	1828.2	1907.4	1982.4
35°	1074.9	1101.5	1130.7	1168.5	1234.2	1310.5	1392.1	1502.9	1623.7	1731.9	1820.8
37.5°	904.8	900.6	917.3	944.6	997.8	1059.4	1153.4	1262.9	1405.0	1532.1	1657.5
40°	802.9	800.2	812.2	837.4	877.9	923.0	1005.3	1101.5	1233.5	1388.8	1538.1
42.5°	732.8	734.4	741.0	758.8	786.6	823.7	885.3	967.2	1088.1	1234.3	1394.8
45°	647.6	652.3	659.6	668.2	684.1	714.6	749.1	807.5	903.1	1025.2	1183.1
47.5°	586.3	586.4	593.9	601.4	610.9	628.1	656.2	692.9	760.3	859.7	995.5
50°	553.4	548.8	554.1	560.0	570.0	581.9	600.5	635.0	680.1	760.4	873.9
52.5°	513.1	513.2	518.0	520.2	529.1	541.1	558.0	581.9	622.8	685.6	778.9
55°	455.2	458.5	461.2	465.1	473.1	481.7	495.0	510.9	542.8	589.9	658.9
57.5°	400.8	401.8	404.5	412.1	417.1	425.1	437.7	452.1	472.8	507.7	559.6
60°	363.6	363.6	368.9	372.2	378.9	386.8	396.8	410.7	429.3	457.8	499.7
62.5°	329.7	329.1	331.2	336.7	341.7	349.2	359.1	370.9	388.4	413.8	448.2
65°	280.0	278.7	282.7	284.0	289.3	296.6	304.6	317.2	331.1	349.7	380.2
67.5°	232.2	233.8	236.0	238.5	241.4	249.1	254.4	263.3	275.1	290.5	311.2
70°	205.7	205.7	205.7	207.7	211.7	215.7	221.0	228.3	239.5	252.8	271.4
72.5°	176.0	178.1	180.2	179.0	184.1	186.5	192.8	196.9	207.7	216.2	232.6
75°	138.0	138.0	138.0	141.3	143.3	145.3	149.3	153.3	158.6	169.2	177.8
77.5°	103.0	102.7	103.4	104.2	106.3	108.7	109.9	113.5	118.4	123.3	130.6
80°	79.6	81.0	81.6	82.9	82.9	84.3	84.9	89.6	92.9	96.2	100.9
82.5°	61.6	61.8	62.0	62.2	62.8	63.6	65.3	66.8	67.9	70.7	74.3
85°	35.8	35.2	35.2	36.5	35.8	35.8	37.2	38.5	38.5	39.1	41.1
87.5°	19.0	18.9	19.3	18.7	18.6	19.0	18.8	18.0	18.4	18.7	18.9
90°	25.8	25.4	24.9	24.5	24.1	23.4	22.3	21.2	20.2	19.1	17.4
92.5°	25.8	25.5	25.3	25.0	24.8	24.4	23.8	23.3	22.7	22.2	21.3
95°	41.1	41.3	41.5	41.7	41.9	41.5	40.5	39.4	38.3	37.3	35.8
97.5°	54.8	54.6	54.3	54.1	53.8	53.3	52.4	51.6	50.7	49.9	46.4
100°	64.0	63.6	63.2	62.7	62.3	61.3	59.6	57.9	56.2	54.5	50.9
102.5°	68.6	68.0	67.4	66.8	66.2	64.8	62.6	60.4	58.2	56.0	86.2
105°	72.6	71.8	70.9	70.1	69.2	67.6	65.3	63.0	60.6	58.3	116.3
107.5°	74.7	73.9	73.0	72.2	71.3	72.1	74.5	76.8	79.2	81.6	151.1
110°	75.5	74.6	73.8	72.9	72.1	82.3	103.5	124.7	146.0	167.2	228.6



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	76.3	75.6	74.9	74.2	73.5	111.9	189.4	266.8	344.3	421.8	436.9
115°	78.4	93.6	108.9	124.2	139.5	196.3	294.6	392.9	491.2	589.6	584.3
117.5°	319.9	370.2	420.4	470.6	520.9	557.9	581.7	605.4	629.2	653.0	649.4
120°	582.9	611.5	640.2	668.9	697.5	710.6	708.0	705.5	703.0	700.4	696.6
122.5°	727.4	732.9	738.5	744.0	749.6	751.6	750.1	748.6	747.0	745.5	741.3
125°	817.0	816.3	815.7	815.1	814.4	813.4	811.9	810.4	808.9	807.4	803.4
127.5°	873.5	873.4	873.3	873.2	873.0	871.9	869.7	867.6	865.4	863.2	860.2
130°	908.7	908.9	909.1	909.3	909.6	908.5	906.2	903.8	901.5	899.2	896.8
132.5°	943.1	943.3	943.5	943.7	944.0	943.1	941.1	939.1	937.1	935.1	932.7
135°	992.8	993.2	993.6	994.1	994.5	993.6	991.5	989.4	987.3	985.2	983.2
137.5°	1038.1	1038.8	1039.5	1040.3	1041.0	1040.3	1038.2	1036.1	1034.1	1032.0	1029.8
140°	1066.4	1067.4	1068.5	1069.6	1070.6	1070.2	1068.3	1066.4	1064.5	1062.6	1060.2
142.5°	1093.9	1095.0	1096.0	1097.1	1098.1	1097.8	1096.1	1094.3	1092.6	1090.8	1088.2
145°	1132.3	1133.4	1134.4	1135.5	1136.6	1136.3	1134.9	1133.4	1131.9	1130.4	1126.8
147.5°	1166.1	1167.0	1167.9	1168.8	1169.7	1169.6	1168.5	1167.4	1166.3	1165.2	1161.6
150°	1186.8	1187.8	1188.9	1190.0	1191.0	1190.9	1189.6	1188.4	1187.1	1185.8	1182.4
152.5°	1204.4	1205.8	1207.2	1208.6	1210.0	1210.0	1208.7	1207.5	1206.2	1204.9	1201.7
155°	1228.8	1230.5	1232.2	1233.9	1235.6	1235.8	1234.5	1233.3	1232.0	1230.7	1228.2
157.5°	1251.2	1252.8	1254.5	1256.1	1257.8	1257.9	1256.5	1255.0	1253.6	1252.1	1250.3
160°	1264.2	1265.7	1267.1	1268.6	1270.1	1270.2	1268.9	1267.7	1266.4	1265.1	1263.9
162.5°	1274.9	1276.7	1278.5	1280.3	1282.2	1282.4	1280.9	1279.5	1278.0	1276.6	1275.5
165°	1290.9	1292.4	1293.9	1295.4	1296.9	1296.9	1295.4	1293.9	1292.4	1290.9	1290.3
167.5°	1301.1	1303.0	1304.9	1306.8	1308.7	1308.9	1307.4	1305.9	1304.4	1303.0	1302.4
170°	1307.2	1309.1	1311.0	1312.9	1314.8	1315.0	1313.5	1312.1	1310.6	1309.1	1308.7
172.5°	1311.8	1313.7	1315.6	1317.5	1319.4	1319.6	1318.1	1316.6	1315.2	1313.7	1313.2
175°	1315.8	1317.9	1320.0	1322.1	1324.3	1324.6	1323.1	1321.6	1320.1	1318.6	1318.2
177.5°	1318.3	1319.8	1321.3	1322.8	1324.4	1324.5	1323.3	1322.2	1321.0	1319.8	1319.6
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1771.7	1767.4	1764.8	1755.2	1746.7	1738.2	1735.6	1736.6	1725.0	1713.8	1709.0
5°	1840.7	1827.4	1814.8	1796.9	1775.7	1752.4	1740.5	1731.2	1708.0	1682.8	1668.2
7.5°	1902.5	1883.5	1859.3	1825.6	1794.6	1758.1	1734.9	1714.3	1680.4	1644.8	1623.0
10°	1940.2	1914.3	1883.1	1842.0	1804.2	1759.7	1728.5	1697.4	1657.5	1615.1	1588.5
12.5°	1972.6	1937.7	1907.0	1854.2	1809.5	1753.9	1716.9	1672.9	1631.0	1580.6	1554.6
15°	2049.7	1985.3	1926.9	1867.2	1812.1	1734.5	1693.4	1634.3	1579.2	1516.9	1487.0
17.5°	2109.3	2037.0	1945.0	1869.1	1804.8	1718.9	1658.5	1587.7	1522.6	1451.3	1410.7
20°	2143.3	2060.3	1961.4	1871.2	1794.2	1696.0	1630.3	1558.0	1481.7	1401.4	1357.6
22.5°	2163.4	2076.2	1978.4	1863.2	1773.0	1677.4	1594.8	1515.5	1438.2	1351.5	1305.6
25°	2169.8	2090.2	1986.7	1856.6	1746.5	1638.3	1538.8	1461.8	1368.2	1287.3	1220.3
27.5°	2138.2	2081.1	1981.6	1844.1	1715.8	1589.3	1478.4	1391.2	1292.5	1204.6	1137.2
30°	2099.5	2066.3	1969.4	1831.4	1691.4	1555.4	1433.3	1334.4	1236.2	1147.3	1078.3
32.5°	2039.5	2032.3	1947.1	1813.3	1665.4	1512.4	1386.0	1286.1	1177.3	1089.9	1024.1
35°	1921.6	1953.5	1899.7	1773.0	1616.4	1451.2	1314.5	1200.4	1087.6	1003.9	942.2
37.5°	1763.7	1842.8	1828.7	1713.9	1550.3	1384.6	1233.7	1114.4	1006.9	922.5	861.9
40°	1654.9	1755.7	1770.3	1668.8	1503.6	1333.1	1173.2	1054.4	949.5	872.6	811.5
42.5°	1538.1	1655.9	1696.0	1614.7	1452.6	1278.9	1119.0	996.0	892.2	817.4	763.2
45°	1342.4	1498.3	1570.6	1524.2	1367.6	1189.7	1025.2	900.4	806.2	735.9	694.1
47.5°	1159.3	1329.7	1427.0	1410.6	1272.9	1096.8	934.1	814.4	722.7	666.6	629.2
50°	1029.8	1205.0	1322.4	1327.8	1205.0	1030.5	867.3	754.5	670.2	617.8	587.2
52.5°	917.3	1084.5	1212.6	1240.7	1129.1	961.5	807.3	695.0	620.8	572.6	545.3
55°	770.4	911.7	1053.7	1105.5	1015.9	856.6	714.0	615.1	545.4	512.3	488.4
57.5°	640.5	758.3	889.4	946.6	891.4	755.1	621.3	535.5	478.9	449.9	431.6
60°	572.0	664.9	781.7	850.0	802.2	680.8	564.0	482.4	436.0	410.1	392.8
62.5°	508.3	590.6	689.3	751.8	725.8	611.3	506.7	434.6	394.5	370.3	357.8
65°	419.4	484.4	560.7	618.4	601.2	514.2	428.7	366.9	335.1	315.8	305.9
67.5°	345.3	392.3	445.2	495.8	481.9	420.3	351.5	303.5	279.8	263.2	257.2
70°	298.6	334.4	381.5	422.0	410.7	360.3	305.9	264.8	244.2	230.3	224.3
72.5°	254.0	283.5	319.4	352.5	344.9	303.0	257.6	226.5	210.7	197.9	193.0
75°	191.8	214.3	236.2	258.1	256.1	223.6	197.1	173.2	160.6	150.6	148.6
77.5°	141.6	154.2	169.1	182.1	178.5	159.9	139.1	125.4	116.1	109.5	108.4
80°	108.2	115.5	126.1	135.4	130.7	122.8	106.2	96.2	89.6	82.9	80.3
82.5°	78.4	85.7	92.1	97.1	93.6	86.1	75.9	69.1	65.2	60.6	59.6
85°	41.1	45.1	47.8	49.1	47.8	43.1	38.5	35.8	32.5	30.5	29.9
87.5°	19.1	18.7	18.4	19.0	17.0	16.5	13.9	11.9	11.8	11.7	11.1
90°	15.7	14.0	12.3	10.3	8.0	5.6	3.3	1.0	3.3	5.6	8.0
92.5°	20.5	19.6	18.8	18.5	18.7	18.9	19.1	19.3	19.1	18.9	18.7
95°	34.3	32.8	31.3	34.1	41.1	48.1	55.1	62.1	55.1	48.1	41.1
97.5°	43.0	39.6	36.1	44.3	64.0	83.8	103.5	123.3	103.5	83.8	64.0
100°	47.2	43.6	40.0	52.8	81.9	110.9	140.0	169.1	140.0	110.9	81.9
102.5°	116.4	146.6	176.8	194.9	201.1	207.3	213.4	219.6	213.4	207.3	201.1
105°	174.2	232.2	290.2	316.0	309.6	303.2	296.9	290.5	296.9	303.2	309.6
107.5°	220.6	290.2	359.7	391.9	386.7	381.6	376.5	371.3	376.5	381.6	386.7
110°	290.0	351.3	412.7	441.1	436.7	432.2	427.8	423.3	427.8	432.2	436.7



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	452.1	467.3	482.4	488.0	484.1	480.1	476.2	472.2	476.2	480.1	484.1
115°	578.9	573.6	568.3	563.9	560.3	556.7	553.0	549.4	553.0	556.7	560.3
117.5°	645.7	642.1	638.4	634.6	630.5	626.5	622.5	618.4	622.5	626.5	630.5
120°	692.8	688.9	685.1	681.6	678.4	675.2	672.1	668.9	672.1	675.2	678.4
122.5°	737.2	733.0	728.9	725.1	721.7	718.4	715.0	711.7	715.0	718.4	721.7
125°	799.4	795.3	791.3	787.9	785.1	782.4	779.6	776.8	779.6	782.4	785.1
127.5°	857.2	854.2	851.2	848.1	845.1	842.0	839.0	835.9	839.0	842.0	845.1
130°	894.5	892.1	889.8	886.9	883.5	880.2	876.8	873.4	876.8	880.2	883.5
132.5°	930.4	928.1	925.7	923.1	920.2	917.4	914.5	911.6	914.5	917.4	920.2
135°	981.3	979.4	977.5	974.9	971.5	968.1	964.7	961.3	964.7	968.1	971.5
137.5°	1027.6	1025.5	1023.3	1021.0	1018.7	1016.3	1013.9	1011.5	1013.9	1016.3	1018.7
140°	1057.9	1055.5	1053.2	1051.2	1049.5	1047.8	1046.1	1044.4	1046.1	1047.8	1049.5
142.5°	1085.5	1082.8	1080.1	1078.0	1076.5	1075.0	1073.4	1071.9	1073.4	1075.0	1076.5
145°	1123.2	1119.6	1116.0	1114.3	1114.5	1114.7	1114.9	1115.1	1114.9	1114.7	1114.5
147.5°	1158.0	1154.5	1150.9	1149.5	1150.3	1151.1	1151.9	1152.8	1151.9	1151.1	1150.3
150°	1179.0	1175.6	1172.2	1171.3	1172.8	1174.2	1175.7	1177.2	1175.7	1174.2	1172.8
152.5°	1198.5	1195.2	1192.0	1191.2	1192.9	1194.5	1196.2	1197.9	1196.2	1194.5	1192.9
155°	1225.6	1223.1	1220.5	1220.2	1222.1	1224.0	1225.9	1227.9	1225.9	1224.0	1222.1
157.5°	1248.6	1246.8	1245.0	1244.9	1246.5	1248.1	1249.8	1251.4	1249.8	1248.1	1246.5
160°	1262.6	1261.3	1260.0	1260.0	1261.3	1262.6	1263.9	1265.1	1263.9	1262.6	1261.3
162.5°	1274.4	1273.3	1272.2	1272.3	1273.5	1274.8	1276.1	1277.4	1276.1	1274.8	1273.5
165°	1289.6	1289.0	1288.4	1288.7	1290.0	1291.2	1292.5	1293.8	1292.5	1291.2	1290.0
167.5°	1301.8	1301.2	1300.6	1300.9	1302.2	1303.5	1304.7	1306.0	1304.7	1303.5	1302.2
170°	1308.2	1307.8	1307.4	1307.8	1309.1	1310.4	1311.6	1312.9	1311.6	1310.4	1309.1
172.5°	1312.8	1312.4	1312.0	1312.4	1313.7	1314.9	1316.2	1317.5	1316.2	1314.9	1313.7
175°	1317.8	1317.4	1316.9	1317.5	1319.0	1320.4	1321.9	1323.4	1321.9	1320.4	1319.0
177.5°	1319.4	1319.3	1319.1	1319.6	1320.8	1322.0	1323.2	1324.4	1323.2	1322.0	1320.8
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1703.7	1700.5	1689.4	1683.6	1674.0	1665.0	1659.1	1661.8	1663.9	1662.8	1661.3
5°	1654.9	1642.3	1623.0	1606.4	1594.5	1572.6	1563.3	1558.7	1554.7	1550.0	1545.4
7.5°	1596.8	1576.9	1549.2	1525.6	1503.3	1476.1	1460.6	1451.3	1441.8	1431.3	1422.0
10°	1555.4	1527.5	1498.3	1465.1	1438.6	1414.0	1392.1	1377.5	1364.3	1351.6	1342.4
12.5°	1511.8	1479.7	1443.6	1398.2	1369.0	1333.9	1330.5	1304.8	1284.1	1276.3	1265.4
15°	1442.6	1397.4	1351.6	1297.9	1274.7	1242.8	1222.9	1203.0	1185.1	1172.5	1169.2
17.5°	1363.9	1305.5	1259.9	1221.3	1183.2	1150.6	1132.3	1116.4	1101.6	1084.8	1082.5
20°	1303.9	1253.4	1203.7	1169.8	1130.7	1097.5	1074.9	1059.0	1046.4	1036.5	1027.8
22.5°	1247.1	1191.9	1146.3	1109.3	1070.7	1043.9	1026.1	1010.7	1000.2	989.2	981.1
25°	1155.9	1112.8	1063.0	1021.2	989.3	972.1	957.5	944.2	937.6	930.3	921.0
27.5°	1076.1	1028.2	981.7	949.3	921.3	906.0	895.7	886.6	880.4	876.1	870.8
30°	1019.9	971.4	934.9	903.1	879.9	864.6	858.0	852.7	845.4	842.7	840.1
32.5°	965.7	922.1	890.9	863.3	841.1	831.2	825.1	820.3	814.6	811.9	806.6
35°	889.2	852.7	822.1	806.9	789.0	780.3	775.7	769.1	763.7	761.1	760.4
37.5°	817.1	785.4	765.3	745.7	738.1	732.8	726.5	721.9	720.3	719.9	719.3
40°	770.4	744.5	726.6	710.7	707.3	699.4	694.1	690.1	690.1	690.8	690.1
42.5°	727.9	704.7	688.9	675.1	671.2	666.5	661.2	660.9	662.0	664.2	662.0
45°	663.5	647.0	635.7	629.0	621.7	617.1	616.4	618.4	619.1	619.8	621.7
47.5°	604.4	593.3	583.1	575.8	572.6	571.8	571.0	574.5	577.7	578.9	581.9
50°	569.3	556.7	548.1	543.4	540.8	539.5	540.8	544.8	547.4	550.7	552.7
52.5°	530.0	521.1	515.2	511.6	510.5	511.3	511.6	516.1	520.4	521.5	522.5
55°	475.8	469.1	467.8	461.8	464.5	463.8	467.1	469.8	473.8	477.8	478.4
57.5°	421.6	416.3	412.7	413.3	414.1	417.0	419.8	424.4	428.7	432.9	433.3
60°	385.5	382.9	380.9	380.9	382.2	386.2	389.5	394.1	396.8	399.5	401.4
62.5°	352.6	350.0	348.0	349.0	352.5	354.9	358.7	361.2	363.9	366.5	367.5
65°	300.6	299.3	301.3	302.6	303.2	306.6	311.2	313.2	315.8	317.2	321.8
67.5°	252.7	252.9	252.7	254.5	258.4	259.2	263.6	268.2	268.7	271.3	274.3
70°	220.3	221.6	223.0	224.3	227.6	228.9	232.2	234.2	236.9	238.9	240.9
72.5°	190.6	190.8	192.2	191.9	194.7	197.6	200.4	202.4	205.0	207.6	209.5
75°	146.6	146.6	148.0	148.6	152.0	155.3	154.6	155.9	158.6	161.2	162.6
77.5°	107.1	105.6	107.1	107.8	108.8	111.6	112.1	114.0	117.0	116.1	117.6
80°	81.6	79.6	81.6	82.3	82.3	85.6	85.6	86.9	88.9	86.9	88.9
82.5°	58.3	57.3	58.8	58.9	60.0	60.1	61.2	61.4	63.4	62.5	63.4
85°	29.2	28.5	29.2	28.5	29.2	29.9	29.9	29.2	29.2	30.5	28.5
87.5°	11.1	11.0	10.8	11.1	10.9	10.7	10.4	10.6	10.8	10.0	10.1
90°	10.3	12.3	14.0	15.7	17.4	19.1	20.2	21.2	22.3	23.4	24.1
92.5°	18.5	18.8	19.6	20.5	21.3	22.2	22.7	23.3	23.8	24.4	24.8
95°	34.1	31.3	32.8	34.3	35.8	37.3	38.3	39.4	40.5	41.5	41.9
97.5°	44.3	36.1	39.6	43.0	46.4	49.9	50.7	51.6	52.4	53.3	53.8
100°	52.8	40.0	43.6	47.2	50.9	54.5	56.2	57.9	59.6	61.3	62.3
102.5°	194.9	176.8	146.6	116.4	86.2	56.0	58.2	60.4	62.6	64.8	66.2
105°	316.0	290.2	232.2	174.2	116.3	58.3	60.6	63.0	65.3	67.6	69.2
107.5°	391.9	359.7	290.2	220.6	151.1	81.6	79.2	76.8	74.5	72.1	71.3
110°	441.1	412.7	351.3	290.0	228.6	167.2	146.0	124.7	103.5	82.3	72.1



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	488.0	482.4	467.3	452.1	436.9	421.8	344.3	266.8	189.4	111.9	73.5
115°	563.9	568.3	573.6	578.9	584.3	589.6	491.2	392.9	294.6	196.3	139.5
117.5°	634.6	638.4	642.1	645.7	649.4	653.0	629.2	605.4	581.7	557.9	520.9
120°	681.6	685.1	688.9	692.8	696.6	700.4	703.0	705.5	708.0	710.6	697.5
122.5°	725.1	728.9	733.0	737.2	741.3	745.5	747.0	748.6	750.1	751.6	749.6
125°	787.9	791.3	795.3	799.4	803.4	807.4	808.9	810.4	811.9	813.4	814.4
127.5°	848.1	851.2	854.2	857.2	860.2	863.2	865.4	867.6	869.7	871.9	873.0
130°	886.9	889.8	892.1	894.5	896.8	899.2	901.5	903.8	906.2	908.5	909.6
132.5°	923.1	925.7	928.1	930.4	932.7	935.1	937.1	939.1	941.1	943.1	944.0
135°	974.9	977.5	979.4	981.3	983.2	985.2	987.3	989.4	991.5	993.6	994.5
137.5°	1021.0	1023.3	1025.5	1027.6	1029.8	1032.0	1034.1	1036.1	1038.2	1040.3	1041.0
140°	1051.2	1053.2	1055.5	1057.9	1060.2	1062.6	1064.5	1066.4	1068.3	1070.2	1070.6
142.5°	1078.0	1080.1	1082.8	1085.5	1088.2	1090.8	1092.6	1094.3	1096.1	1097.8	1098.1
145°	1114.3	1116.0	1119.6	1123.2	1126.8	1130.4	1131.9	1133.4	1134.9	1136.3	1136.6
147.5°	1149.5	1150.9	1154.5	1158.0	1161.6	1165.2	1166.3	1167.4	1168.5	1169.6	1169.7
150°	1171.3	1172.2	1175.6	1179.0	1182.4	1185.8	1187.1	1188.4	1189.6	1190.9	1191.0
152.5°	1191.2	1192.0	1195.2	1198.5	1201.7	1204.9	1206.2	1207.5	1208.7	1210.0	1210.0
155°	1220.2	1220.5	1223.1	1225.6	1228.2	1230.7	1232.0	1233.3	1234.5	1235.8	1235.6
157.5°	1244.9	1245.0	1246.8	1248.6	1250.3	1252.1	1253.6	1255.0	1256.5	1257.9	1257.8
160°	1260.0	1260.0	1261.3	1262.6	1263.9	1265.1	1266.4	1267.7	1268.9	1270.2	1270.1
162.5°	1272.3	1272.2	1273.3	1274.4	1275.5	1276.6	1278.0	1279.5	1280.9	1282.4	1282.2
165°	1288.7	1288.4	1289.0	1289.6	1290.3	1290.9	1292.4	1293.9	1295.4	1296.9	1296.9
167.5°	1300.9	1300.6	1301.2	1301.8	1302.4	1303.0	1304.4	1305.9	1307.4	1308.9	1308.7
170°	1307.8	1307.4	1307.8	1308.2	1308.7	1309.1	1310.6	1312.1	1313.5	1315.0	1314.8
172.5°	1312.4	1312.0	1312.4	1312.8	1313.2	1313.7	1315.2	1316.6	1318.1	1319.6	1319.4
175°	1317.5	1316.9	1317.4	1317.8	1318.2	1318.6	1320.1	1321.6	1323.1	1324.6	1324.3
177.5°	1319.6	1319.1	1319.3	1319.4	1319.6	1319.8	1321.0	1322.2	1323.3	1324.5	1324.4
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1655.9	1654.9	1654.9	1650.1	1654.9	1654.9	1655.9	1661.3	1662.8	1663.9	1661.8
5°	1536.1	1534.1	1530.8	1534.1	1530.8	1534.1	1536.1	1545.4	1550.0	1554.7	1558.7
7.5°	1417.6	1409.6	1408.4	1400.6	1408.4	1409.6	1417.6	1422.0	1431.3	1441.8	1451.3
10°	1331.1	1325.8	1325.1	1312.5	1325.1	1325.8	1331.1	1342.4	1351.6	1364.3	1377.5
12.5°	1265.3	1252.5	1255.0	1247.7	1255.0	1252.5	1265.3	1265.4	1276.3	1284.1	1304.8
15°	1151.3	1151.3	1148.6	1137.3	1148.6	1151.3	1151.3	1169.2	1172.5	1185.1	1203.0
17.5°	1069.4	1068.0	1061.7	1064.9	1061.7	1068.0	1069.4	1082.5	1084.8	1101.6	1116.4
20°	1020.5	1016.6	1008.6	1008.6	1008.6	1016.6	1020.5	1027.8	1036.5	1046.4	1059.0
22.5°	974.4	974.1	965.6	968.2	965.6	974.1	974.4	981.1	989.2	1000.2	1010.7
25°	920.3	915.0	911.1	913.0	911.1	915.0	920.3	921.0	930.3	937.6	944.2
27.5°	869.1	866.2	865.9	860.5	865.9	866.2	869.1	870.8	876.1	880.4	886.6
30°	839.4	832.8	834.1	830.8	834.1	832.8	839.4	840.1	842.7	845.4	852.7
32.5°	805.4	803.0	801.7	798.9	801.7	803.0	805.4	806.6	811.9	814.6	820.3
35°	759.1	759.8	756.4	757.8	756.4	759.8	759.1	760.4	761.1	763.7	769.1
37.5°	718.6	720.7	719.2	719.6	719.2	720.7	718.6	719.3	719.9	720.3	721.9
40°	692.1	692.1	692.1	694.1	692.1	692.1	692.1	690.1	690.8	690.1	690.1
42.5°	666.6	665.5	664.5	664.3	664.5	665.5	666.6	662.0	664.2	662.0	660.9
45°	623.1	625.1	625.7	622.4	625.7	625.1	623.1	621.7	619.8	619.1	618.4
47.5°	583.7	583.9	583.7	586.6	583.7	583.9	583.7	581.9	578.9	577.7	574.5
50°	556.1	554.7	556.1	554.7	556.1	554.7	556.1	552.7	550.7	547.4	544.8
52.5°	526.9	527.1	526.3	526.1	526.3	527.1	526.9	522.5	521.5	520.4	516.1
55°	481.1	482.4	481.7	481.7	481.7	482.4	481.1	478.4	477.8	473.8	469.8
57.5°	433.7	434.9	435.8	432.9	435.8	434.9	433.7	433.3	432.9	428.7	424.4
60°	400.8	404.1	403.4	402.1	403.4	404.1	400.8	401.4	399.5	396.8	394.1
62.5°	370.5	371.7	371.6	371.3	371.6	371.7	370.5	367.5	366.5	363.9	361.2
65°	323.8	325.1	323.1	325.1	323.1	325.1	323.8	321.8	317.2	315.8	313.2
67.5°	273.5	273.9	275.4	276.3	275.4	273.9	273.5	274.3	271.3	268.7	268.2
70°	242.2	241.5	243.5	245.5	243.5	241.5	242.2	240.9	238.9	236.9	234.2
72.5°	209.3	210.7	210.1	211.5	210.1	210.7	209.3	209.5	207.6	205.0	202.4
75°	161.2	163.2	162.6	164.6	162.6	163.2	161.2	162.6	161.2	158.6	155.9
77.5°	116.5	116.8	116.5	117.6	116.5	116.8	116.5	117.6	116.1	117.0	114.0
80°	88.9	87.6	86.3	88.9	86.3	87.6	88.9	88.9	86.9	88.9	86.9
82.5°	61.8	62.6	61.3	61.3	61.3	62.6	61.8	63.4	62.5	63.4	61.4
85°	28.5	27.9	26.5	26.5	26.5	27.9	28.5	28.5	30.5	29.2	29.2
87.5°	10.2	9.8	9.9	9.4	9.9	9.8	10.2	10.1	10.0	10.8	10.6
90°	24.5	24.9	25.4	25.8	25.4	24.9	24.5	24.1	23.4	22.3	21.2
92.5°	25.0	25.3	25.5	25.8	25.5	25.3	25.0	24.8	24.4	23.8	23.3
95°	41.7	41.5	41.3	41.1	41.3	41.5	41.7	41.9	41.5	40.5	39.4
97.5°	54.1	54.3	54.6	54.8	54.6	54.3	54.1	53.8	53.3	52.4	51.6
100°	62.7	63.2	63.6	64.0	63.6	63.2	62.7	62.3	61.3	59.6	57.9
102.5°	66.8	67.4	68.0	68.6	68.0	67.4	66.8	66.2	64.8	62.6	60.4
105°	70.1	70.9	71.8	72.6	71.8	70.9	70.1	69.2	67.6	65.3	63.0
107.5°	72.2	73.0	73.9	74.7	73.9	73.0	72.2	71.3	72.1	74.5	76.8
110°	72.9	73.8	74.6	75.5	74.6	73.8	72.9	72.1	82.3	103.5	124.7



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	74.2	74.9	75.6	76.3	75.6	74.9	74.2	73.5	111.9	189.4	266.8
115°	124.2	108.9	93.6	78.4	93.6	108.9	124.2	139.5	196.3	294.6	392.9
117.5°	470.6	420.4	370.2	319.9	370.2	420.4	470.6	520.9	557.9	581.7	605.4
120°	668.9	640.2	611.5	582.9	611.5	640.2	668.9	697.5	710.6	708.0	705.5
122.5°	744.0	738.5	732.9	727.4	732.9	738.5	744.0	749.6	751.6	750.1	748.6
125°	815.1	815.7	816.3	817.0	816.3	815.7	815.1	814.4	813.4	811.9	810.4
127.5°	873.2	873.3	873.4	873.5	873.4	873.3	873.2	873.0	871.9	869.7	867.6
130°	909.3	909.1	908.9	908.7	908.9	909.1	909.3	909.6	908.5	906.2	903.8
132.5°	943.7	943.5	943.3	943.1	943.3	943.5	943.7	944.0	943.1	941.1	939.1
135°	994.1	993.6	993.2	992.8	993.2	993.6	994.1	994.5	993.6	991.5	989.4
137.5°	1040.3	1039.5	1038.8	1038.1	1038.8	1039.5	1040.3	1041.0	1040.3	1038.2	1036.1
140°	1069.6	1068.5	1067.4	1066.4	1067.4	1068.5	1069.6	1070.6	1070.2	1068.3	1066.4
142.5°	1097.1	1096.0	1095.0	1093.9	1095.0	1096.0	1097.1	1098.1	1097.8	1096.1	1094.3
145°	1135.5	1134.4	1133.4	1132.3	1133.4	1134.4	1135.5	1136.6	1136.3	1134.9	1133.4
147.5°	1168.8	1167.9	1167.0	1166.1	1167.0	1167.9	1168.8	1169.7	1169.6	1168.5	1167.4
150°	1190.0	1188.9	1187.8	1186.8	1187.8	1188.9	1190.0	1191.0	1190.9	1189.6	1188.4
152.5°	1208.6	1207.2	1205.8	1204.4	1205.8	1207.2	1208.6	1210.0	1210.0	1208.7	1207.5
155°	1233.9	1232.2	1230.5	1228.8	1230.5	1232.2	1233.9	1235.6	1235.8	1234.5	1233.3
157.5°	1256.1	1254.5	1252.8	1251.2	1252.8	1254.5	1256.1	1257.8	1257.9	1256.5	1255.0
160°	1268.6	1267.1	1265.7	1264.2	1265.7	1267.1	1268.6	1270.1	1270.2	1268.9	1267.7
162.5°	1280.3	1278.5	1276.7	1274.9	1276.7	1278.5	1280.3	1282.2	1282.4	1280.9	1279.5
165°	1295.4	1293.9	1292.4	1290.9	1292.4	1293.9	1295.4	1296.9	1296.9	1295.4	1293.9
167.5°	1306.8	1304.9	1303.0	1301.1	1303.0	1304.9	1306.8	1308.7	1308.9	1307.4	1305.9
170°	1312.9	1311.0	1309.1	1307.2	1309.1	1311.0	1312.9	1314.8	1315.0	1313.5	1312.1
172.5°	1317.5	1315.6	1313.7	1311.8	1313.7	1315.6	1317.5	1319.4	1319.6	1318.1	1316.6
175°	1322.1	1320.0	1317.9	1315.8	1317.9	1320.0	1322.1	1324.3	1324.6	1323.1	1321.6
177.5°	1322.8	1321.3	1319.8	1318.3	1319.8	1321.3	1322.8	1324.4	1324.5	1323.3	1322.2
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1659.1	1665.0	1674.0	1683.6	1689.4	1700.5	1703.7	1709.0	1713.8	1725.0	1736.6
5°	1563.3	1572.6	1594.5	1606.4	1623.0	1642.3	1654.9	1668.2	1682.8	1708.0	1731.2
7.5°	1460.6	1476.1	1503.3	1525.6	1549.2	1576.9	1596.8	1623.0	1644.8	1680.4	1714.3
10°	1392.1	1414.0	1438.6	1465.1	1498.3	1527.5	1555.4	1588.5	1615.1	1657.5	1697.4
12.5°	1330.5	1333.9	1369.0	1398.2	1443.6	1479.7	1511.8	1554.6	1580.6	1631.0	1672.9
15°	1222.9	1242.8	1274.7	1297.9	1351.6	1397.4	1442.6	1487.0	1516.9	1579.2	1634.3
17.5°	1132.3	1150.6	1183.2	1221.3	1259.9	1305.5	1363.9	1410.7	1451.3	1522.6	1587.7
20°	1074.9	1097.5	1130.7	1169.8	1203.7	1253.4	1303.9	1357.6	1401.4	1481.7	1558.0
22.5°	1026.1	1043.9	1070.7	1109.3	1146.3	1191.9	1247.1	1305.6	1351.5	1438.2	1515.5
25°	957.5	972.1	989.3	1021.2	1063.0	1112.8	1155.9	1220.3	1287.3	1368.2	1461.8
27.5°	895.7	906.0	921.3	949.3	981.7	1028.2	1076.1	1137.2	1204.6	1292.5	1391.2
30°	858.0	864.6	879.9	903.1	934.9	971.4	1019.9	1078.3	1147.3	1236.2	1334.4
32.5°	825.1	831.2	841.1	863.3	890.9	922.1	965.7	1024.1	1089.9	1177.3	1286.1
35°	775.7	780.3	789.0	806.9	822.1	852.7	889.2	942.2	1003.9	1087.6	1200.4
37.5°	726.5	732.8	738.1	745.7	765.3	785.4	817.1	861.9	922.5	1006.9	1114.4
40°	694.1	699.4	707.3	710.7	726.6	744.5	770.4	811.5	872.6	949.5	1054.4
42.5°	661.2	666.5	671.2	675.1	688.9	704.7	727.9	763.2	817.4	892.2	996.0
45°	616.4	617.1	621.7	629.0	635.7	647.0	663.5	694.1	735.9	806.2	900.4
47.5°	571.0	571.8	572.6	575.8	583.1	593.3	604.4	629.2	666.6	722.7	814.4
50°	540.8	539.5	540.8	543.4	548.1	556.7	569.3	587.2	617.8	670.2	754.5
52.5°	511.6	511.3	510.5	511.6	515.2	521.1	530.0	545.3	572.6	620.8	695.0
55°	467.1	463.8	464.5	461.8	467.8	469.1	475.8	488.4	512.3	545.4	615.1
57.5°	419.8	417.0	414.1	413.3	412.7	416.3	421.6	431.6	449.9	478.9	535.5
60°	389.5	386.2	382.2	380.9	380.9	382.9	385.5	392.8	410.1	436.0	482.4
62.5°	358.7	354.9	352.5	349.0	348.0	350.0	352.6	357.8	370.3	394.5	434.6
65°	311.2	306.6	303.2	302.6	301.3	299.3	300.6	305.9	315.8	335.1	366.9
67.5°	263.6	259.2	258.4	254.5	252.7	252.9	252.7	257.2	263.2	279.8	303.5
70°	232.2	228.9	227.6	224.3	223.0	221.6	220.3	224.3	230.3	244.2	264.8
72.5°	200.4	197.6	194.7	191.9	192.2	190.8	190.6	193.0	197.9	210.7	226.5
75°	154.6	155.3	152.0	148.6	148.0	146.6	146.6	148.6	150.6	160.6	173.2
77.5°	112.1	111.6	108.8	107.8	107.1	105.6	107.1	108.4	109.5	116.1	125.4
80°	85.6	85.6	82.3	82.3	81.6	79.6	81.6	80.3	82.9	89.6	96.2
82.5°	61.2	60.1	60.0	58.9	58.8	57.3	58.3	59.6	60.6	65.2	69.1
85°	29.9	29.9	29.2	28.5	29.2	28.5	29.2	29.9	30.5	32.5	35.8
87.5°	10.4	10.7	10.9	11.1	10.8	11.0	11.1	11.1	11.7	11.8	11.9
90°	20.2	19.1	17.4	15.7	14.0	12.3	10.3	8.0	5.6	3.3	1.0
92.5°	22.7	22.2	21.3	20.5	19.6	18.8	18.5	18.7	18.9	19.1	19.3
95°	38.3	37.3	35.8	34.3	32.8	31.3	34.1	41.1	48.1	55.1	62.1
97.5°	50.7	49.9	46.4	43.0	39.6	36.1	44.3	64.0	83.8	103.5	123.3
100°	56.2	54.5	50.9	47.2	43.6	40.0	52.8	81.9	110.9	140.0	169.1
102.5°	58.2	56.0	86.2	116.4	146.6	176.8	194.9	201.1	207.3	213.4	219.6
105°	60.6	58.3	116.3	174.2	232.2	290.2	316.0	309.6	303.2	296.9	290.5
107.5°	79.2	81.6	151.1	220.6	290.2	359.7	391.9	386.7	381.6	376.5	371.3
110°	146.0	167.2	228.6	290.0	351.3	412.7	441.1	436.7	432.2	427.8	423.3



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	344.3	421.8	436.9	452.1	467.3	482.4	488.0	484.1	480.1	476.2	472.2
115°	491.2	589.6	584.3	578.9	573.6	568.3	563.9	560.3	556.7	553.0	549.4
117.5°	629.2	653.0	649.4	645.7	642.1	638.4	634.6	630.5	626.5	622.5	618.4
120°	703.0	700.4	696.6	692.8	688.9	685.1	681.6	678.4	675.2	672.1	668.9
122.5°	747.0	745.5	741.3	737.2	733.0	728.9	725.1	721.7	718.4	715.0	711.7
125°	808.9	807.4	803.4	799.4	795.3	791.3	787.9	785.1	782.4	779.6	776.8
127.5°	865.4	863.2	860.2	857.2	854.2	851.2	848.1	845.1	842.0	839.0	835.9
130°	901.5	899.2	896.8	894.5	892.1	889.8	886.9	883.5	880.2	876.8	873.4
132.5°	937.1	935.1	932.7	930.4	928.1	925.7	923.1	920.2	917.4	914.5	911.6
135°	987.3	985.2	983.2	981.3	979.4	977.5	974.9	971.5	968.1	964.7	961.3
137.5°	1034.1	1032.0	1029.8	1027.6	1025.5	1023.3	1021.0	1018.7	1016.3	1013.9	1011.5
140°	1064.5	1062.6	1060.2	1057.9	1055.5	1053.2	1051.2	1049.5	1047.8	1046.1	1044.4
142.5°	1092.6	1090.8	1088.2	1085.5	1082.8	1080.1	1078.0	1076.5	1075.0	1073.4	1071.9
145°	1131.9	1130.4	1126.8	1123.2	1119.6	1116.0	1114.3	1114.5	1114.7	1114.9	1115.1
147.5°	1166.3	1165.2	1161.6	1158.0	1154.5	1150.9	1149.5	1150.3	1151.1	1151.9	1152.8
150°	1187.1	1185.8	1182.4	1179.0	1175.6	1172.2	1171.3	1172.8	1174.2	1175.7	1177.2
152.5°	1206.2	1204.9	1201.7	1198.5	1195.2	1192.0	1191.2	1192.9	1194.5	1196.2	1197.9
155°	1232.0	1230.7	1228.2	1225.6	1223.1	1220.5	1220.2	1222.1	1224.0	1225.9	1227.9
157.5°	1253.6	1252.1	1250.3	1248.6	1246.8	1245.0	1244.9	1246.5	1248.1	1249.8	1251.4
160°	1266.4	1265.1	1263.9	1262.6	1261.3	1260.0	1260.0	1261.3	1262.6	1263.9	1265.1
162.5°	1278.0	1276.6	1275.5	1274.4	1273.3	1272.2	1272.3	1273.5	1274.8	1276.1	1277.4
165°	1292.4	1290.9	1290.3	1289.6	1289.0	1288.4	1288.7	1290.0	1291.2	1292.5	1293.8
167.5°	1304.4	1303.0	1302.4	1301.8	1301.2	1300.6	1300.9	1302.2	1303.5	1304.7	1306.0
170°	1310.6	1309.1	1308.7	1308.2	1307.8	1307.4	1307.8	1309.1	1310.4	1311.6	1312.9
172.5°	1315.2	1313.7	1313.2	1312.8	1312.4	1312.0	1312.4	1313.7	1314.9	1316.2	1317.5
175°	1320.1	1318.6	1318.2	1317.8	1317.4	1316.9	1317.5	1319.0	1320.4	1321.9	1323.4
177.5°	1321.0	1319.8	1319.6	1319.4	1319.3	1319.1	1319.6	1320.8	1322.0	1323.2	1324.4
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1735.6	1738.2	1746.7	1755.2	1764.8	1767.4	1771.7	1768.0	1766.9	1777.0	1784.4
5°	1740.5	1752.4	1775.7	1796.9	1814.8	1827.4	1840.7	1846.0	1855.9	1869.9	1887.1
7.5°	1734.9	1758.1	1794.6	1825.6	1859.3	1883.5	1902.5	1918.7	1938.4	1964.8	1993.6
10°	1728.5	1759.7	1804.2	1842.0	1883.1	1914.3	1940.2	1965.4	1994.6	2031.1	2068.9
12.5°	1716.9	1753.9	1809.5	1854.2	1907.0	1937.7	1972.6	2027.0	2058.3	2109.2	2162.4
15°	1693.4	1734.5	1812.1	1867.2	1926.9	1985.3	2049.7	2101.5	2153.2	2183.1	2258.1
17.5°	1658.5	1718.9	1804.8	1869.1	1945.0	2037.0	2109.3	2167.9	2227.7	2276.1	2313.7
20°	1630.3	1696.0	1794.2	1871.2	1961.4	2060.3	2143.3	2203.0	2254.7	2295.2	2318.4
22.5°	1594.8	1677.4	1773.0	1863.2	1978.4	2076.2	2163.4	2210.4	2253.7	2273.4	2282.3
25°	1538.8	1638.3	1746.5	1856.6	1986.7	2090.2	2169.8	2198.3	2210.9	2191.7	2159.8
27.5°	1478.4	1589.3	1715.8	1844.1	1981.6	2081.1	2138.2	2133.7	2112.3	2050.1	2000.3
30°	1433.3	1555.4	1691.4	1831.4	1969.4	2066.3	2099.5	2066.3	2017.8	1948.2	1877.2
32.5°	1386.0	1512.4	1665.4	1813.3	1947.1	2032.3	2039.5	1982.4	1907.4	1828.2	1739.7
35°	1314.5	1451.2	1616.4	1773.0	1899.7	1953.5	1921.6	1820.8	1731.9	1623.7	1502.9
37.5°	1233.7	1384.6	1550.3	1713.9	1828.7	1842.8	1763.7	1657.5	1532.1	1405.0	1262.9
40°	1173.2	1333.1	1503.6	1668.8	1770.3	1755.7	1654.9	1538.1	1388.8	1233.5	1101.5
42.5°	1119.0	1278.9	1452.6	1614.7	1696.0	1655.9	1538.1	1394.8	1234.3	1088.1	967.2
45°	1025.2	1189.7	1367.6	1524.2	1570.6	1498.3	1342.4	1183.1	1025.2	903.1	807.5
47.5°	934.1	1096.8	1272.9	1410.6	1427.0	1329.7	1159.3	995.5	859.7	760.3	692.9
50°	867.3	1030.5	1205.0	1327.8	1322.4	1205.0	1029.8	873.9	760.4	680.1	635.0
52.5°	807.3	961.5	1129.1	1240.7	1212.6	1084.5	917.3	778.9	685.6	622.8	581.9
55°	714.0	856.6	1015.9	1105.5	1053.7	911.7	770.4	658.9	589.9	542.8	510.9
57.5°	621.3	755.1	891.4	946.6	889.4	758.3	640.5	559.6	507.7	472.8	452.1
60°	564.0	680.8	802.2	850.0	781.7	664.9	572.0	499.7	457.8	429.3	410.7
62.5°	506.7	611.3	725.8	751.8	689.3	590.6	508.3	448.2	413.8	388.4	370.9
65°	428.7	514.2	601.2	618.4	560.7	484.4	419.4	380.2	349.7	331.1	317.2
67.5°	351.5	420.3	481.9	495.8	445.2	392.3	345.3	311.2	290.5	275.1	263.3
70°	305.9	360.3	410.7	422.0	381.5	334.4	298.6	271.4	252.8	239.5	228.3
72.5°	257.6	303.0	344.9	352.5	319.4	283.5	254.0	232.6	216.2	207.7	196.9
75°	197.1	223.6	256.1	258.1	236.2	214.3	191.8	177.8	169.2	158.6	153.3
77.5°	139.1	159.9	178.5	182.1	169.1	154.2	141.6	130.6	123.3	118.4	113.5
80°	106.2	122.8	130.7	135.4	126.1	115.5	108.2	100.9	96.2	92.9	89.6
82.5°	75.9	86.1	93.6	97.1	92.1	85.7	78.4	74.3	70.7	67.9	66.8
85°	38.5	43.1	47.8	49.1	47.8	45.1	41.1	41.1	39.1	38.5	38.5
87.5°	13.9	16.5	17.0	19.0	18.4	18.7	19.1	18.9	18.7	18.4	18.0
90°	3.3	5.6	8.0	10.3	12.3	14.0	15.7	17.4	19.1	20.2	21.2
92.5°	19.1	18.9	18.7	18.5	18.8	19.6	20.5	21.3	22.2	22.7	23.3
95°	55.1	48.1	41.1	34.1	31.3	32.8	34.3	35.8	37.3	38.3	39.4
97.5°	103.5	83.8	64.0	44.3	36.1	39.6	43.0	46.4	49.9	50.7	51.6
100°	140.0	110.9	81.9	52.8	40.0	43.6	47.2	50.9	54.5	56.2	57.9
102.5°	213.4	207.3	201.1	194.9	176.8	146.6	116.4	86.2	56.0	58.2	60.4
105°	296.9	303.2	309.6	316.0	290.2	232.2	174.2	116.3	58.3	60.6	63.0
107.5°	376.5	381.6	386.7	391.9	359.7	290.2	220.6	151.1	81.6	79.2	76.8
110°	427.8	432.2	436.7	441.1	412.7	351.3	290.0	228.6	167.2	146.0	124.7



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	476.2	480.1	484.1	488.0	482.4	467.3	452.1	436.9	421.8	344.3	266.8
115°	553.0	556.7	560.3	563.9	568.3	573.6	578.9	584.3	589.6	491.2	392.9
117.5°	622.5	626.5	630.5	634.6	638.4	642.1	645.7	649.4	653.0	629.2	605.4
120°	672.1	675.2	678.4	681.6	685.1	688.9	692.8	696.6	700.4	703.0	705.5
122.5°	715.0	718.4	721.7	725.1	728.9	733.0	737.2	741.3	745.5	747.0	748.6
125°	779.6	782.4	785.1	787.9	791.3	795.3	799.4	803.4	807.4	808.9	810.4
127.5°	839.0	842.0	845.1	848.1	851.2	854.2	857.2	860.2	863.2	865.4	867.6
130°	876.8	880.2	883.5	886.9	889.8	892.1	894.5	896.8	899.2	901.5	903.8
132.5°	914.5	917.4	920.2	923.1	925.7	928.1	930.4	932.7	935.1	937.1	939.1
135°	964.7	968.1	971.5	974.9	977.5	979.4	981.3	983.2	985.2	987.3	989.4
137.5°	1013.9	1016.3	1018.7	1021.0	1023.3	1025.5	1027.6	1029.8	1032.0	1034.1	1036.1
140°	1046.1	1047.8	1049.5	1051.2	1053.2	1055.5	1057.9	1060.2	1062.6	1064.5	1066.4
142.5°	1073.4	1075.0	1076.5	1078.0	1080.1	1082.8	1085.5	1088.2	1090.8	1092.6	1094.3
145°	1114.9	1114.7	1114.5	1114.3	1116.0	1119.6	1123.2	1126.8	1130.4	1131.9	1133.4
147.5°	1151.9	1151.1	1150.3	1149.5	1150.9	1154.5	1158.0	1161.6	1165.2	1166.3	1167.4
150°	1175.7	1174.2	1172.8	1171.3	1172.2	1175.6	1179.0	1182.4	1185.8	1187.1	1188.4
152.5°	1196.2	1194.5	1192.9	1191.2	1192.0	1195.2	1198.5	1201.7	1204.9	1206.2	1207.5
155°	1225.9	1224.0	1222.1	1220.2	1220.5	1223.1	1225.6	1228.2	1230.7	1232.0	1233.3
157.5°	1249.8	1248.1	1246.5	1244.9	1245.0	1246.8	1248.6	1250.3	1252.1	1253.6	1255.0
160°	1263.9	1262.6	1261.3	1260.0	1260.0	1261.3	1262.6	1263.9	1265.1	1266.4	1267.7
162.5°	1276.1	1274.8	1273.5	1272.3	1272.2	1273.3	1274.4	1275.5	1276.6	1278.0	1279.5
165°	1292.5	1291.2	1290.0	1288.7	1288.4	1289.0	1289.6	1290.3	1290.9	1292.4	1293.9
167.5°	1304.7	1303.5	1302.2	1300.9	1300.6	1301.2	1301.8	1302.4	1303.0	1304.4	1305.9
170°	1311.6	1310.4	1309.1	1307.8	1307.4	1307.8	1308.2	1308.7	1309.1	1310.6	1312.1
172.5°	1316.2	1314.9	1313.7	1312.4	1312.0	1312.4	1312.8	1313.2	1313.7	1315.2	1316.6
175°	1321.9	1320.4	1319.0	1317.5	1316.9	1317.4	1317.8	1318.2	1318.6	1320.1	1321.6
177.5°	1323.2	1322.0	1320.8	1319.6	1319.1	1319.3	1319.4	1319.6	1319.8	1321.0	1322.2
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5	1726.5
2.5°	1790.8	1798.2	1798.2	1799.3	1807.8	1806.7	1806.2
5°	1905.7	1917.0	1918.3	1930.3	1938.2	1935.6	1928.3
7.5°	2014.1	2035.1	2051.0	2059.9	2070.4	2076.9	2074.0
10°	2100.1	2130.6	2149.2	2161.8	2177.1	2188.4	2184.4
12.5°	2178.2	2214.5	2240.0	2261.6	2263.6	2278.1	2268.3
15°	2299.9	2338.3	2342.3	2358.2	2370.9	2369.5	2370.2
17.5°	2340.1	2352.4	2354.9	2355.3	2355.5	2350.8	2340.7
20°	2325.7	2321.1	2309.8	2301.2	2285.9	2283.9	2270.7
22.5°	2257.8	2243.1	2214.8	2196.1	2172.3	2166.1	2162.4
25°	2124.0	2091.5	2046.4	2003.2	1991.3	1968.1	1974.7
27.5°	1940.5	1889.8	1840.9	1805.9	1774.2	1739.4	1749.4
30°	1811.5	1754.4	1685.4	1632.3	1598.5	1565.3	1559.3
32.5°	1657.5	1573.9	1497.0	1450.2	1398.4	1377.4	1354.4
35°	1392.1	1310.5	1234.2	1168.5	1130.7	1101.5	1074.9
37.5°	1153.4	1059.4	997.8	944.6	917.3	900.6	904.8
40°	1005.3	923.0	877.9	837.4	812.2	800.2	802.9
42.5°	885.3	823.7	786.6	758.8	741.0	734.4	732.8
45°	749.1	714.6	684.1	668.2	659.6	652.3	647.6
47.5°	656.2	628.1	610.9	601.4	593.9	586.4	586.3
50°	600.5	581.9	570.0	560.0	554.1	548.8	553.4
52.5°	558.0	541.1	529.1	520.2	518.0	513.2	513.1
55°	495.0	481.7	473.1	465.1	461.2	458.5	455.2
57.5°	437.7	425.1	417.1	412.1	404.5	401.8	400.8
60°	396.8	386.8	378.9	372.2	368.9	363.6	363.6
62.5°	359.1	349.2	341.7	336.7	331.2	329.1	329.7
65°	304.6	296.6	289.3	284.0	282.7	278.7	280.0
67.5°	254.4	249.1	241.4	238.5	236.0	233.8	232.2
70°	221.0	215.7	211.7	207.7	205.7	205.7	205.7
72.5°	192.8	186.5	184.1	179.0	180.2	178.1	176.0
75°	149.3	145.3	143.3	141.3	138.0	138.0	138.0
77.5°	109.9	108.7	106.3	104.2	103.4	102.7	103.0
80°	84.9	84.3	82.9	82.9	81.6	81.0	79.6
82.5°	65.3	63.6	62.8	62.2	62.0	61.8	61.6
85°	37.2	35.8	35.8	36.5	35.2	35.2	35.8
87.5°	18.8	19.0	18.6	18.7	19.3	18.9	19.0
90°	22.3	23.4	24.1	24.5	24.9	25.4	25.8
92.5°	23.8	24.4	24.8	25.0	25.3	25.5	25.8
95°	40.5	41.5	41.9	41.7	41.5	41.3	41.1
97.5°	52.4	53.3	53.8	54.1	54.3	54.6	54.8
100°	59.6	61.3	62.3	62.7	63.2	63.6	64.0
102.5°	62.6	64.8	66.2	66.8	67.4	68.0	68.6
105°	65.3	67.6	69.2	70.1	70.9	71.8	72.6
107.5°	74.5	72.1	71.3	72.2	73.0	73.9	74.7
110°	103.5	82.3	72.1	72.9	73.8	74.6	75.5



TEST NUMBER: P331567

CATALOG NUMBER: S122DIW-S865D970U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	189.4	111.9	73.5	74.2	74.9	75.6	76.3
115°	294.6	196.3	139.5	124.2	108.9	93.6	78.4
117.5°	581.7	557.9	520.9	470.6	420.4	370.2	319.9
120°	708.0	710.6	697.5	668.9	640.2	611.5	582.9
122.5°	750.1	751.6	749.6	744.0	738.5	732.9	727.4
125°	811.9	813.4	814.4	815.1	815.7	816.3	817.0
127.5°	869.7	871.9	873.0	873.2	873.3	873.4	873.5
130°	906.2	908.5	909.6	909.3	909.1	908.9	908.7
132.5°	941.1	943.1	944.0	943.7	943.5	943.3	943.1
135°	991.5	993.6	994.5	994.1	993.6	993.2	992.8
137.5°	1038.2	1040.3	1041.0	1040.3	1039.5	1038.8	1038.1
140°	1068.3	1070.2	1070.6	1069.6	1068.5	1067.4	1066.4
142.5°	1096.1	1097.8	1098.1	1097.1	1096.0	1095.0	1093.9
145°	1134.9	1136.3	1136.6	1135.5	1134.4	1133.4	1132.3
147.5°	1168.5	1169.6	1169.7	1168.8	1167.9	1167.0	1166.1
150°	1189.6	1190.9	1191.0	1190.0	1188.9	1187.8	1186.8
152.5°	1208.7	1210.0	1210.0	1208.6	1207.2	1205.8	1204.4
155°	1234.5	1235.8	1235.6	1233.9	1232.2	1230.5	1228.8
157.5°	1256.5	1257.9	1257.8	1256.1	1254.5	1252.8	1251.2
160°	1268.9	1270.2	1270.1	1268.6	1267.1	1265.7	1264.2
162.5°	1280.9	1282.4	1282.2	1280.3	1278.5	1276.7	1274.9
165°	1295.4	1296.9	1296.9	1295.4	1293.9	1292.4	1290.9
167.5°	1307.4	1308.9	1308.7	1306.8	1304.9	1303.0	1301.1
170°	1313.5	1315.0	1314.8	1312.9	1311.0	1309.1	1307.2
172.5°	1318.1	1319.6	1319.4	1317.5	1315.6	1313.7	1311.8
175°	1323.1	1324.6	1324.3	1322.1	1320.0	1317.9	1315.8
177.5°	1323.3	1324.5	1324.4	1322.8	1321.3	1319.8	1318.3
180°	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5	1320.5

(END OF REPORT)