

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331822-935

Luminaire Tested: **S122RDIW-S675D1440U935-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P331822-935  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-8,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S122RDIW-S675D1440U935-4F0-1E-UDD-A1  
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 675 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING  
UPLIGHT 1440 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6493.0 lumens  
Efficiency: N/A  
Efficacy: 95.3 lumens/watt  
Spacing Criteria (0/90/45): 0.86 / 1.16 / 1.02  
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')  
CIE Type: Semi-Indirect


Input Watts (W): 68.1  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

### Luminous Intensity Polar Plot





TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	103	103	103	103	93	93	93	93	74	74	74	57	57	57	41	41	41	34
1	95	91	87	84	85	82	79	76	66	64	62	51	50	48	37	36	36	29
2	87	80	74	69	78	72	67	63	58	55	52	45	43	41	33	32	31	26
3	79	71	64	58	71	64	58	54	52	48	44	41	38	36	30	28	27	22
4	73	63	55	50	66	57	51	46	46	42	38	36	33	31	27	25	24	20
5	67	56	49	43	60	51	45	40	42	37	33	33	30	27	25	23	21	18
6	62	51	43	37	56	46	40	35	38	33	29	30	27	24	23	21	19	16
7	57	46	38	33	52	42	35	31	34	30	26	27	24	21	21	19	17	14
8	53	42	34	29	48	38	32	27	31	27	23	25	22	19	19	17	15	13
9	50	38	31	26	45	35	29	24	29	24	21	23	20	17	18	16	14	12
10	46	35	28	24	42	32	26	22	27	22	19	22	18	16	17	15	13	11

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	20423	20423	20423	20423
5°	22809	20551	18220	20551
10°	25306	20407	15795	20407
15°	26551	20107	12445	20107
20°	23017	19663	10768	19663
25°	15096	19057	9615	19057
30°	10161	18321	8701	18321
35°	8229	17394	7849	17394
40°	7318	16387	7263	16387
45°	6624	15203	6485	15203
50°	6028	14031	6006	14031
55°	5666	12732	5590	12732
60°	4740	11538	4682	11538
65°	3996	10476	4531	10476
70°	3696	9356	4277	9356
75°	3456	8141	3949	8141
80°	3189	6704	3515	6704
85°	2927	5298	3094	5298



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	119.9	1.8
10°-20°	334.1	5.1
20°-30°	430.5	6.6
30°-40°	409.1	6.3
40°-50°	350.5	5.4
50°-60°	266.9	4.1
60°-70°	168.7	2.6
70°-80°	84.3	1.3
80°-90°	28.1	0.4
90°-100°	97.5	1.5
100°-110°	302.7	4.7
110°-120°	517.4	8.0
120°-130°	680.4	10.5
130°-140°	763.7	11.8
140°-150°	748.8	11.5
150°-160°	628.1	9.7
160°-170°	416.6	6.4
170°-180°	145.6	2.2
0°-30°	884.5	13.6
0°-40°	1293.7	19.9
0°-60°	1911.1	29.4
0°-90°	2192.1	33.8
90°-120°	917.6	14.1
90°-150°	3110.6	47.9
90°-180°	4301.0	66.2
0°-180°	6493.0	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1265	1265	1265	1265	1265	
5°	1407	1268	1124	1268	1407	139
15°	1588	1203	744	1203	1588	428
25°	847	1070	540	1070	847	402
35°	418	882	398	882	418	267
45°	290	666	284	666	290	224
55°	201	452	199	452	201	177
65°	105	274	119	274	105	106
75°	55	130	63	130	55	59
85°	16	29	17	29	16	18
90°	44	1	44	1	44	20
95°	80	68	80	68	80	90
105°	288	279	288	279	288	303
115°	519	519	519	519	519	513
125°	758	755	758	755	758	676
135°	989	977	989	977	989	761
145°	1199	1186	1199	1186	1199	749
155°	1367	1356	1367	1356	1367	629
165°	1477	1476	1477	1476	1477	417
175°	1530	1536	1530	1536	1530	145
180°	1538	1538	1538	1538	1538	



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1316.2	1317.2	1318.4	1315.9	1315.9	1313.7	1309.2	1305.7	1295.8	1294.4	1294.4
5°	1407.3	1406.4	1408.2	1402.5	1394.6	1392.8	1384.4	1373.5	1362.0	1349.3	1346.6
7.5°	1497.8	1496.5	1493.0	1492.0	1485.9	1472.7	1459.2	1444.9	1425.9	1407.4	1398.1
10°	1543.5	1558.1	1549.2	1533.9	1537.0	1516.3	1505.3	1486.4	1470.6	1442.9	1436.8
12.5°	1588.5	1594.2	1591.5	1582.7	1578.7	1564.4	1549.6	1533.2	1504.0	1479.1	1457.5
15°	1588.4	1596.7	1598.9	1596.3	1598.4	1597.6	1589.7	1576.1	1550.6	1523.3	1499.6
17.5°	1471.1	1476.9	1491.3	1501.1	1513.4	1539.4	1552.2	1557.2	1553.4	1537.9	1521.2
20°	1339.6	1329.9	1370.4	1391.0	1408.6	1452.5	1490.3	1504.9	1528.1	1527.7	1523.3
22.5°	1153.2	1155.5	1193.9	1218.4	1269.7	1313.6	1356.8	1411.4	1456.4	1486.2	1503.7
25°	847.4	864.1	902.3	935.7	992.8	1074.6	1148.8	1235.0	1316.3	1380.4	1441.6
27.5°	636.4	637.7	668.0	698.8	732.7	799.7	893.2	996.1	1112.0	1207.6	1317.7
30°	545.0	542.3	555.1	574.0	603.0	654.9	725.1	826.3	941.8	1086.0	1214.4
32.5°	480.3	480.4	490.1	504.0	528.1	563.1	611.2	693.4	802.6	944.3	1094.8
35°	417.5	417.1	424.1	434.2	444.4	466.7	499.7	542.8	617.9	750.2	904.0
37.5°	372.6	374.4	377.9	384.2	395.4	407.9	427.7	456.6	510.1	588.3	717.6
40°	347.2	348.1	352.9	358.2	364.8	374.4	390.7	414.0	453.1	515.6	610.0
42.5°	324.0	324.9	328.3	333.2	338.4	348.1	361.5	381.7	413.4	462.1	540.0
45°	290.1	290.1	293.2	295.3	301.1	309.9	320.8	337.5	359.6	395.5	447.4
47.5°	258.2	258.3	260.4	264.2	267.8	274.6	285.4	299.0	315.0	342.9	387.2
50°	240.0	240.4	241.7	244.8	247.0	253.1	261.5	273.4	290.1	311.6	348.5
52.5°	225.2	224.9	226.6	227.9	229.5	233.8	240.0	250.6	265.4	284.2	314.8
55°	201.3	199.5	202.2	204.4	205.7	207.4	210.9	217.6	230.3	246.2	269.0
57.5°	171.4	170.7	172.5	174.6	178.7	183.5	186.4	190.6	197.3	208.6	231.3
60°	146.8	146.8	150.8	152.1	156.9	163.1	169.2	172.7	179.3	186.8	203.5
62.5°	125.0	125.4	127.2	128.5	131.2	138.8	147.4	155.2	161.4	168.5	179.6
65°	104.6	105.5	105.5	106.3	108.1	109.9	113.4	119.5	130.5	140.6	149.0
67.5°	88.8	89.0	89.3	90.1	90.7	92.6	93.9	96.7	99.3	108.8	119.2
70°	78.3	79.6	79.1	80.0	80.4	81.3	83.1	84.4	88.3	90.6	96.7
72.5°	68.4	69.3	69.2	69.8	70.9	71.1	72.5	73.9	76.4	78.3	81.5
75°	55.4	54.9	55.4	56.2	56.7	57.2	57.2	58.9	60.2	62.0	64.1
77.5°	42.7	43.1	43.0	43.1	43.2	44.0	43.9	44.8	46.1	46.9	48.0
80°	34.3	34.7	34.3	34.7	35.1	35.6	35.1	35.6	36.9	37.8	37.8
82.5°	26.5	26.6	26.9	26.9	27.0	27.1	27.8	27.9	28.8	28.7	29.0
85°	15.8	15.4	15.4	15.4	15.8	16.3	15.8	15.8	16.3	16.3	16.3
87.5°	14.5	14.7	14.7	14.6	14.6	14.6	14.7	15.2	15.0	15.4	13.8
90°	44.2	43.8	43.6	43.3	43.0	43.1	43.7	44.3	44.9	45.5	39.1
92.5°	42.0	42.0	41.9	41.8	41.8	41.8	41.6	41.5	41.4	41.2	39.8
95°	80.5	81.0	81.6	82.2	82.7	83.1	83.1	83.1	83.1	83.1	82.5
97.5°	139.4	139.5	139.5	139.6	139.7	139.7	139.7	139.7	139.7	139.7	138.5
100°	177.8	178.1	178.4	178.7	179.0	179.1	179.1	179.1	179.1	179.1	178.2
102.5°	221.4	221.7	222.1	222.3	222.6	222.7	222.4	222.1	222.0	221.7	220.6
105°	288.2	288.2	288.2	288.2	288.2	287.8	287.3	286.7	286.1	285.6	285.0
107.5°	350.9	352.3	353.6	355.0	356.3	356.8	356.6	356.4	356.1	355.9	355.9
110°	399.8	400.6	401.5	402.3	403.2	403.7	403.7	403.7	403.7	403.7	403.7



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	446.5	447.1	447.8	448.4	449.0	449.7	450.4	451.1	451.8	452.5	452.7
115°	519.2	520.0	520.9	521.8	522.6	523.2	523.5	523.8	524.1	524.4	525.0
117.5°	588.5	589.4	590.2	591.1	591.9	592.8	593.5	594.2	594.9	595.6	597.1
120°	637.3	638.2	639.0	639.9	640.8	641.2	641.2	641.2	641.2	641.2	643.5
122.5°	685.1	685.7	686.4	687.0	687.6	688.3	689.0	689.7	690.3	691.0	692.7
125°	758.0	758.4	758.6	758.9	759.2	759.7	760.6	761.5	762.3	763.2	764.1
127.5°	824.5	825.4	826.3	827.2	828.2	829.1	830.2	831.2	832.2	833.4	834.4
130°	872.3	873.4	874.6	875.7	876.8	877.7	878.3	878.9	879.5	880.0	880.6
132.5°	917.9	918.9	919.8	920.8	921.6	922.7	924.0	925.3	926.5	927.8	927.7
135°	989.1	990.0	990.8	991.7	992.6	993.2	993.4	993.7	994.0	994.3	993.7
137.5°	1053.4	1054.6	1055.8	1057.0	1058.1	1058.8	1059.0	1059.2	1059.5	1059.7	1058.9
140°	1098.1	1099.2	1100.4	1101.6	1102.8	1103.3	1103.3	1103.3	1103.3	1103.3	1101.9
142.5°	1138.6	1139.8	1140.9	1142.1	1143.2	1143.7	1143.5	1143.2	1143.0	1142.8	1141.8
145°	1199.4	1200.5	1201.7	1202.8	1203.9	1204.4	1204.1	1203.9	1203.5	1203.2	1201.5
147.5°	1253.6	1254.7	1255.8	1256.9	1258.0	1258.3	1257.6	1257.0	1256.4	1255.7	1254.6
150°	1288.9	1289.8	1290.6	1291.5	1292.4	1292.4	1291.5	1290.6	1289.8	1288.9	1287.8
152.5°	1322.2	1323.3	1324.3	1325.4	1326.5	1326.5	1325.4	1324.3	1323.3	1322.2	1320.8
155°	1366.8	1367.7	1368.6	1369.4	1370.3	1369.9	1368.6	1367.1	1365.6	1364.2	1363.3
157.5°	1405.2	1406.6	1408.0	1409.4	1410.7	1410.5	1408.5	1406.5	1404.5	1402.7	1402.1
160°	1429.1	1430.3	1431.4	1432.5	1433.7	1433.4	1431.7	1429.9	1428.2	1426.5	1426.2
162.5°	1449.8	1451.3	1452.7	1454.1	1455.4	1455.1	1453.2	1451.2	1449.2	1447.3	1447.0
165°	1477.1	1478.6	1480.1	1481.4	1482.9	1482.6	1480.6	1478.6	1476.5	1474.5	1474.5
167.5°	1499.4	1501.0	1502.4	1504.0	1505.5	1505.2	1503.2	1501.2	1499.2	1497.1	1497.2
170°	1510.9	1512.6	1514.3	1516.0	1517.8	1517.7	1515.6	1513.6	1511.6	1509.6	1509.8
172.5°	1520.3	1522.0	1523.7	1525.4	1527.2	1527.0	1525.0	1522.9	1521.0	1518.9	1519.2
175°	1530.3	1532.1	1533.8	1535.5	1537.3	1537.1	1535.1	1533.1	1531.1	1529.0	1529.7
177.5°	1535.0	1536.4	1537.8	1539.2	1540.6	1540.6	1539.2	1537.8	1536.4	1535.0	1535.5
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1295.1	1292.3	1289.9	1283.5	1280.4	1273.3	1272.3	1272.0	1262.7	1254.0	1251.5
5°	1339.6	1332.6	1322.0	1309.7	1296.9	1283.8	1275.0	1268.0	1250.3	1233.6	1224.0
7.5°	1384.4	1369.3	1351.1	1327.8	1308.4	1286.6	1270.4	1255.9	1231.0	1207.0	1190.9
10°	1417.8	1393.2	1369.1	1337.0	1311.9	1287.3	1264.5	1244.7	1216.5	1184.9	1162.4
12.5°	1438.6	1411.5	1378.2	1346.8	1314.4	1283.1	1252.5	1227.1	1194.0	1161.3	1134.7
15°	1466.6	1437.6	1397.1	1352.4	1310.6	1269.7	1234.6	1202.9	1159.9	1120.8	1088.2
17.5°	1489.5	1449.7	1406.2	1354.4	1306.1	1254.0	1208.8	1168.4	1120.4	1073.2	1034.9
20°	1496.9	1457.4	1407.3	1355.4	1298.3	1237.2	1188.4	1144.4	1093.0	1041.6	997.6
22.5°	1492.4	1461.6	1405.8	1343.8	1285.3	1221.3	1166.2	1115.3	1058.3	1005.7	954.8
25°	1461.4	1450.8	1398.1	1330.3	1263.6	1189.3	1125.6	1069.7	1004.7	948.5	893.0
27.5°	1389.0	1411.8	1379.1	1307.0	1232.7	1153.1	1081.4	1017.9	950.4	887.1	831.9
30°	1319.4	1371.7	1357.6	1290.8	1207.7	1129.5	1049.1	982.7	910.7	845.6	791.1
32.5°	1224.1	1310.5	1324.2	1268.3	1182.4	1096.5	1012.2	946.2	870.9	802.4	749.2
35°	1072.4	1201.6	1260.9	1225.3	1139.2	1046.5	959.4	882.5	806.9	739.3	686.5
37.5°	891.4	1067.4	1166.2	1168.8	1089.7	993.2	898.5	822.2	744.8	678.3	621.3
40°	774.0	964.7	1093.5	1122.1	1055.2	951.1	855.2	777.5	701.9	636.8	571.4
42.5°	668.5	858.5	1016.8	1066.5	1013.4	909.9	813.8	732.5	659.0	597.4	530.5
45°	540.6	706.7	881.2	970.0	940.6	844.7	743.2	665.8	596.8	543.6	479.5
47.5°	456.0	573.1	741.9	862.0	861.5	774.0	674.2	600.1	536.1	486.3	434.3
50°	407.9	509.8	652.6	788.9	800.3	726.9	632.0	558.6	498.9	446.5	404.8
52.5°	364.6	448.7	577.0	707.7	740.2	676.7	584.5	516.8	458.7	410.7	374.9
55°	308.1	373.2	470.7	592.9	642.1	597.3	515.6	452.3	405.2	364.8	334.0
57.5°	260.6	309.4	387.7	486.1	543.4	515.2	447.7	396.3	356.1	319.5	295.2
60°	230.7	270.7	337.1	419.3	482.6	462.8	405.2	357.3	323.0	291.4	268.5
62.5°	202.6	236.9	293.9	360.6	418.6	410.4	363.3	323.2	293.2	264.3	245.0
65°	163.1	188.1	232.5	284.8	331.4	335.4	301.5	274.2	247.5	224.5	207.4
67.5°	129.8	146.2	177.5	221.5	256.4	268.9	248.2	227.4	206.1	188.5	173.6
70°	109.4	122.6	145.5	181.1	213.2	226.4	214.5	198.2	179.8	165.2	152.5
72.5°	88.7	101.5	118.4	144.5	172.0	186.2	182.1	170.5	155.5	143.4	131.4
75°	66.8	70.8	82.2	99.8	121.3	133.6	136.7	130.5	118.6	109.4	102.4
77.5°	49.4	51.7	57.3	66.5	80.5	91.5	96.0	95.3	87.1	81.7	75.2
80°	39.5	40.9	43.5	47.4	58.0	69.0	72.1	72.1	66.4	64.1	57.6
82.5°	30.0	31.0	32.6	34.8	39.7	49.3	52.8	53.5	49.9	46.9	41.8
85°	17.1	16.7	17.6	18.9	19.8	22.4	27.7	28.6	27.7	24.2	22.8
87.5°	12.5	11.6	10.3	9.0	8.7	8.4	9.4	10.4	9.7	9.4	9.4
90°	32.7	26.4	20.1	15.2	11.7	8.2	4.7	1.3	4.7	8.2	11.7
92.5°	38.3	36.8	35.3	33.2	30.7	28.2	25.7	23.1	25.7	28.2	30.7
95°	81.9	81.4	80.8	79.0	76.1	73.3	70.3	67.5	70.3	73.3	76.1
97.5°	137.5	136.4	135.3	133.5	131.0	128.4	125.9	123.3	125.9	128.4	131.0
100°	177.4	176.5	175.6	174.1	171.8	169.4	167.1	164.9	167.1	169.4	171.8
102.5°	219.5	218.4	217.3	215.9	214.0	212.2	210.3	208.4	210.3	212.2	214.0
105°	284.4	283.9	283.3	282.5	281.6	280.8	279.9	279.1	279.9	280.8	281.6
107.5°	355.9	355.9	355.9	355.2	354.0	352.8	351.5	350.2	351.5	352.8	354.0
110°	403.7	403.7	403.7	402.8	401.1	399.3	397.6	395.9	397.6	399.3	401.1





TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	453.0	453.1	453.4	452.6	450.9	449.2	447.5	445.7	447.5	449.2	450.9
115°	525.6	526.2	526.7	526.2	524.4	522.6	520.9	519.2	520.9	522.6	524.4
117.5°	598.7	600.4	602.0	601.7	599.3	597.0	594.7	592.5	594.7	597.0	599.3
120°	645.8	648.2	650.5	650.5	648.2	645.8	643.5	641.2	643.5	645.8	648.2
122.5°	694.3	695.9	697.5	697.0	694.1	691.4	688.6	685.9	688.6	691.4	694.1
125°	765.0	765.9	766.7	765.9	763.2	760.6	758.0	755.4	758.0	760.6	763.2
127.5°	835.4	836.5	837.5	836.4	833.1	829.7	826.5	823.2	826.5	829.7	833.1
130°	881.2	881.8	882.4	880.8	877.0	873.3	869.5	865.7	869.5	873.3	877.0
132.5°	927.6	927.5	927.4	925.7	922.7	919.6	916.6	913.5	916.6	919.6	922.7
135°	993.2	992.6	992.0	990.1	986.9	983.8	980.6	977.4	980.6	983.8	986.9
137.5°	1058.2	1057.5	1056.7	1055.0	1052.4	1049.8	1047.2	1044.7	1047.2	1049.8	1052.4
140°	1100.4	1099.0	1097.5	1095.5	1093.0	1090.4	1087.7	1085.1	1087.7	1090.4	1093.0
142.5°	1140.8	1139.8	1138.8	1137.0	1134.5	1131.9	1129.3	1126.7	1129.3	1131.9	1134.5
145°	1199.8	1198.1	1196.4	1194.5	1192.4	1190.4	1188.4	1186.4	1188.4	1190.4	1192.4
147.5°	1253.4	1252.2	1251.1	1249.3	1246.9	1244.4	1242.0	1239.6	1242.0	1244.4	1246.9
150°	1286.6	1285.5	1284.3	1282.9	1281.2	1279.4	1277.6	1275.9	1277.6	1279.4	1281.2
152.5°	1319.4	1318.0	1316.6	1315.1	1313.3	1311.6	1309.8	1308.1	1309.8	1311.6	1313.3
155°	1362.4	1361.6	1360.7	1359.9	1359.0	1358.1	1357.3	1356.4	1357.3	1358.1	1359.0
157.5°	1401.6	1401.1	1400.6	1400.0	1399.5	1398.9	1398.3	1397.7	1398.3	1398.9	1399.5
160°	1425.9	1425.6	1425.4	1425.0	1424.4	1423.7	1423.2	1422.6	1423.2	1423.7	1424.4
162.5°	1446.7	1446.4	1446.1	1446.0	1445.8	1445.7	1445.6	1445.4	1445.6	1445.7	1445.8
165°	1474.5	1474.5	1474.5	1474.7	1475.0	1475.2	1475.6	1475.8	1475.6	1475.2	1475.0
167.5°	1497.3	1497.3	1497.4	1497.8	1498.7	1499.5	1500.4	1501.2	1500.4	1499.5	1498.7
170°	1510.2	1510.5	1510.7	1511.3	1512.2	1513.0	1513.9	1514.8	1513.9	1513.0	1512.2
172.5°	1519.5	1519.8	1520.1	1520.7	1521.6	1522.4	1523.3	1524.1	1523.3	1522.4	1521.6
175°	1530.2	1530.8	1531.4	1532.1	1532.9	1533.8	1534.6	1535.5	1534.6	1533.8	1532.9
177.5°	1535.9	1536.4	1536.9	1537.5	1538.2	1538.9	1539.6	1540.2	1539.6	1538.9	1538.2
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1247.0	1244.5	1239.9	1232.9	1228.6	1221.2	1216.3	1219.2	1219.9	1219.2	1218.5
5°	1213.5	1204.2	1191.5	1179.1	1167.8	1155.5	1148.4	1145.3	1139.2	1135.7	1133.9
7.5°	1172.9	1157.0	1139.0	1117.6	1099.3	1080.3	1070.6	1065.7	1053.1	1046.3	1040.3
10°	1142.7	1117.7	1099.7	1071.5	1054.4	1029.3	1012.2	1012.6	995.5	985.8	978.8
12.5°	1109.3	1081.8	1051.8	1026.5	1002.6	982.6	961.9	953.6	935.3	926.0	907.1
15°	1054.0	1021.8	990.2	955.9	931.8	900.5	870.6	834.1	804.7	779.2	772.2
17.5°	993.4	953.7	922.0	881.8	840.3	787.8	753.2	732.0	714.3	700.9	690.8
20°	951.9	911.5	877.7	817.0	761.2	725.7	700.2	683.9	665.4	650.9	643.0
22.5°	908.4	866.2	820.0	752.3	708.9	680.3	657.5	638.9	626.4	615.0	607.9
25°	846.4	800.3	724.3	677.7	642.6	612.7	596.8	585.4	572.2	556.8	549.8
27.5°	781.1	707.7	653.1	618.5	584.9	565.4	551.2	534.2	522.4	515.5	508.2
30°	732.2	658.8	616.2	578.4	554.7	533.1	516.4	506.8	495.3	483.5	478.6
32.5°	677.7	619.1	578.2	546.7	522.6	504.3	491.1	475.4	467.2	459.9	449.8
35°	610.0	565.7	528.3	502.8	479.9	465.0	449.6	440.4	425.4	419.3	415.3
37.5°	552.7	514.2	486.4	459.4	441.3	424.8	415.4	400.7	394.3	385.7	377.4
40°	520.4	482.6	455.7	433.8	413.5	401.2	389.4	377.5	367.8	363.9	353.8
42.5°	487.3	456.6	429.7	405.6	392.1	379.1	364.1	355.4	345.3	339.0	332.7
45°	441.7	414.5	391.6	371.8	356.9	343.3	333.6	319.1	313.4	300.6	295.3
47.5°	401.7	376.3	354.5	335.7	321.1	312.2	298.1	286.7	277.6	269.8	263.0
50°	373.2	352.1	331.0	314.3	301.1	288.3	273.8	268.1	254.0	250.0	246.2
52.5°	347.2	327.1	307.7	291.4	278.2	265.8	253.0	245.6	236.1	232.1	229.3
55°	310.7	291.4	272.9	258.4	245.2	232.5	224.5	215.3	210.9	207.8	204.4
57.5°	274.1	256.8	242.6	227.9	214.6	204.6	195.4	189.9	185.3	181.2	177.0
60°	251.0	234.3	221.5	207.8	194.2	185.9	178.9	172.3	167.0	160.8	159.1
62.5°	226.4	211.7	200.1	186.8	175.0	167.3	160.6	154.4	148.0	139.1	136.6
65°	192.5	181.1	168.8	157.8	147.2	139.7	130.1	123.0	120.5	119.5	119.1
67.5°	162.0	151.1	140.5	129.3	119.7	112.8	107.9	106.8	105.0	104.4	103.2
70°	141.5	131.4	120.9	110.3	101.1	99.8	98.0	96.3	94.0	93.2	92.3
72.5°	123.2	112.8	102.2	93.8	89.8	88.2	86.4	84.6	83.2	82.3	81.7
75°	94.5	84.8	77.8	74.7	72.5	71.2	68.5	67.2	66.4	65.0	64.6
77.5°	68.0	62.6	59.3	57.4	55.1	53.7	52.2	50.9	49.9	49.7	49.0
80°	51.8	49.2	47.0	44.4	43.5	41.8	41.3	40.0	40.5	39.1	39.1
82.5°	40.3	36.9	35.0	33.8	33.0	31.6	31.1	30.5	30.6	29.6	29.6
85°	20.7	19.8	18.9	18.0	18.0	16.7	17.1	16.7	16.7	15.8	15.4
87.5°	9.7	10.3	10.9	12.1	13.4	14.4	14.2	13.8	13.7	13.5	13.2
90°	15.2	20.1	26.4	32.7	39.1	45.5	44.9	44.3	43.7	43.1	43.0
92.5°	33.2	35.3	36.8	38.3	39.8	41.2	41.4	41.5	41.6	41.8	41.8
95°	79.0	80.8	81.4	81.9	82.5	83.1	83.1	83.1	83.1	83.1	82.7
97.5°	133.5	135.3	136.4	137.5	138.5	139.7	139.7	139.7	139.7	139.7	139.7
100°	174.1	175.6	176.5	177.4	178.2	179.1	179.1	179.1	179.1	179.1	179.0
102.5°	215.9	217.3	218.4	219.5	220.6	221.7	222.0	222.1	222.4	222.7	222.6
105°	282.5	283.3	283.9	284.4	285.0	285.6	286.1	286.7	287.3	287.8	288.2
107.5°	355.2	355.9	355.9	355.9	355.9	355.9	356.1	356.4	356.6	356.8	356.3
110°	402.8	403.7	403.7	403.7	403.7	403.7	403.7	403.7	403.7	403.7	403.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	452.6	453.4	453.1	453.0	452.7	452.5	451.8	451.1	450.4	449.7	449.0
115°	526.2	526.7	526.2	525.6	525.0	524.4	524.1	523.8	523.5	523.2	522.6
117.5°	601.7	602.0	600.4	598.7	597.1	595.6	594.9	594.2	593.5	592.8	591.9
120°	650.5	650.5	648.2	645.8	643.5	641.2	641.2	641.2	641.2	641.2	640.8
122.5°	697.0	697.5	695.9	694.3	692.7	691.0	690.3	689.7	689.0	688.3	687.6
125°	765.9	766.7	765.9	765.0	764.1	763.2	762.3	761.5	760.6	759.7	759.2
127.5°	836.4	837.5	836.5	835.4	834.4	833.4	832.2	831.2	830.2	829.1	828.2
130°	880.8	882.4	881.8	881.2	880.6	880.0	879.5	878.9	878.3	877.7	876.8
132.5°	925.7	927.4	927.5	927.6	927.7	927.8	926.5	925.3	924.0	922.7	921.6
135°	990.1	992.0	992.6	993.2	993.7	994.3	994.0	993.7	993.4	993.2	992.6
137.5°	1055.0	1056.7	1057.5	1058.2	1058.9	1059.7	1059.5	1059.2	1059.0	1058.8	1058.1
140°	1095.5	1097.5	1099.0	1100.4	1101.9	1103.3	1103.3	1103.3	1103.3	1103.3	1102.8
142.5°	1137.0	1138.8	1139.8	1140.8	1141.8	1142.8	1143.0	1143.2	1143.5	1143.7	1143.2
145°	1194.5	1196.4	1198.1	1199.8	1201.5	1203.2	1203.5	1203.9	1204.1	1204.4	1203.9
147.5°	1249.3	1251.1	1252.2	1253.4	1254.6	1255.7	1256.4	1257.0	1257.6	1258.3	1258.0
150°	1282.9	1284.3	1285.5	1286.6	1287.8	1288.9	1289.8	1290.6	1291.5	1292.4	1292.4
152.5°	1315.1	1316.6	1318.0	1319.4	1320.8	1322.2	1323.3	1324.3	1325.4	1326.5	1326.5
155°	1359.9	1360.7	1361.6	1362.4	1363.3	1364.2	1365.6	1367.1	1368.6	1369.9	1370.3
157.5°	1400.0	1400.6	1401.1	1401.6	1402.1	1402.7	1404.5	1406.5	1408.5	1410.5	1410.7
160°	1425.0	1425.4	1425.6	1425.9	1426.2	1426.5	1428.2	1429.9	1431.7	1433.4	1433.7
162.5°	1446.0	1446.1	1446.4	1446.7	1447.0	1447.3	1449.2	1451.2	1453.2	1455.1	1455.4
165°	1474.7	1474.5	1474.5	1474.5	1474.5	1474.5	1476.5	1478.6	1480.6	1482.6	1482.9
167.5°	1497.8	1497.4	1497.3	1497.3	1497.2	1497.1	1499.2	1501.2	1503.2	1505.2	1505.5
170°	1511.3	1510.7	1510.5	1510.2	1509.8	1509.6	1511.6	1513.6	1515.6	1517.7	1517.8
172.5°	1520.7	1520.1	1519.8	1519.5	1519.2	1518.9	1521.0	1522.9	1525.0	1527.0	1527.2
175°	1532.1	1531.4	1530.8	1530.2	1529.7	1529.0	1531.1	1533.1	1535.1	1537.1	1537.3
177.5°	1537.5	1536.9	1536.4	1535.9	1535.5	1535.0	1536.4	1537.8	1539.2	1540.6	1540.6
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1214.6	1215.3	1214.3	1215.0	1214.3	1215.3	1214.6	1218.5	1219.2	1219.9	1219.2
5°	1131.7	1126.4	1125.6	1124.2	1125.6	1126.4	1131.7	1133.9	1135.7	1139.2	1145.3
7.5°	1032.8	1031.9	1029.8	1026.7	1029.8	1031.9	1032.8	1040.3	1046.3	1053.1	1065.7
10°	969.1	966.9	966.5	963.4	966.5	966.9	969.1	978.8	985.8	995.5	1012.6
12.5°	894.6	880.4	878.9	871.2	878.9	880.4	894.6	907.1	926.0	935.3	953.6
15°	761.6	759.1	750.2	744.5	750.2	759.1	761.6	772.2	779.2	804.7	834.1
17.5°	685.7	677.1	674.3	673.1	674.3	677.1	685.7	690.8	700.9	714.3	732.0
20°	636.8	629.0	627.6	626.7	627.6	629.0	636.8	643.0	650.9	665.4	683.9
22.5°	603.0	594.8	591.4	588.8	591.4	594.8	603.0	607.9	615.0	626.4	638.9
25°	545.4	542.3	540.6	539.7	540.6	542.3	545.4	549.8	556.8	572.2	585.4
27.5°	500.3	493.5	492.2	490.0	492.2	493.5	500.3	508.2	515.5	522.4	534.2
30°	474.7	472.4	469.4	466.7	469.4	472.4	474.7	478.6	483.5	495.3	506.8
32.5°	444.4	442.6	439.9	438.6	439.9	442.6	444.4	449.8	459.9	467.2	475.4
35°	411.0	404.8	402.2	398.2	402.2	404.8	411.0	415.3	419.3	425.4	440.4
37.5°	375.5	372.3	368.6	369.9	368.6	372.3	375.5	377.4	385.7	394.3	400.7
40°	348.1	345.9	345.0	344.6	345.0	345.9	348.1	353.8	363.9	367.8	377.5
42.5°	326.3	320.2	318.0	317.9	318.0	320.2	326.3	332.7	339.0	345.3	355.4
45°	293.2	287.4	283.4	284.0	283.4	287.4	293.2	295.3	300.6	313.4	319.1
47.5°	259.2	259.1	256.6	257.4	256.6	259.1	259.2	263.0	269.8	277.6	286.7
50°	243.1	240.4	238.7	239.1	238.7	240.4	243.1	246.2	250.0	254.0	268.1
52.5°	227.6	225.3	223.9	225.8	223.9	225.3	227.6	229.3	232.1	236.1	245.6
55°	202.2	199.5	199.1	198.6	199.1	199.5	202.2	204.4	207.8	210.9	215.3
57.5°	173.7	172.0	169.4	168.2	169.4	172.0	173.7	177.0	181.2	185.3	189.9
60°	153.3	149.9	145.5	145.0	145.5	149.9	153.3	159.1	160.8	167.0	172.3
62.5°	134.7	134.1	133.2	133.1	133.2	134.1	134.7	136.6	139.1	148.0	154.4
65°	118.2	117.8	118.2	118.6	118.2	117.8	118.2	119.1	119.5	120.5	123.0
67.5°	103.1	102.2	101.4	101.8	101.4	102.2	103.1	103.2	104.4	105.0	106.8
70°	91.4	91.0	90.6	90.6	90.6	91.0	91.4	92.3	93.2	94.0	96.3
72.5°	80.2	80.1	79.6	79.3	79.6	80.1	80.2	81.7	82.3	83.2	84.6
75°	64.1	63.3	63.3	63.3	63.3	63.3	64.1	64.6	65.0	66.4	67.2
77.5°	48.9	48.5	48.0	47.6	48.0	48.5	48.9	49.0	49.7	49.9	50.9
80°	38.7	38.2	37.8	37.8	37.8	38.2	38.7	39.1	39.1	40.5	40.0
82.5°	29.5	29.1	29.0	28.7	29.0	29.1	29.5	29.6	29.6	30.6	30.5
85°	15.8	16.3	15.8	16.7	15.8	16.3	15.8	15.4	15.8	16.7	16.7
87.5°	13.3	12.9	13.3	13.1	13.3	12.9	13.3	13.2	13.5	13.7	13.8
90°	43.3	43.6	43.8	44.2	43.8	43.6	43.3	43.0	43.1	43.7	44.3
92.5°	41.8	41.9	42.0	42.0	42.0	41.9	41.8	41.8	41.8	41.6	41.5
95°	82.2	81.6	81.0	80.5	81.0	81.6	82.2	82.7	83.1	83.1	83.1
97.5°	139.6	139.5	139.5	139.4	139.5	139.5	139.6	139.7	139.7	139.7	139.7
100°	178.7	178.4	178.1	177.8	178.1	178.4	178.7	179.0	179.1	179.1	179.1
102.5°	222.3	222.1	221.7	221.4	221.7	222.1	222.3	222.6	222.7	222.4	222.1
105°	288.2	288.2	288.2	288.2	288.2	288.2	288.2	288.2	287.8	287.3	286.7
107.5°	355.0	353.6	352.3	350.9	352.3	353.6	355.0	356.3	356.8	356.6	356.4
110°	402.3	401.5	400.6	399.8	400.6	401.5	402.3	403.2	403.7	403.7	403.7



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	448.4	447.8	447.1	446.5	447.1	447.8	448.4	449.0	449.7	450.4	451.1
115°	521.8	520.9	520.0	519.2	520.0	520.9	521.8	522.6	523.2	523.5	523.8
117.5°	591.1	590.2	589.4	588.5	589.4	590.2	591.1	591.9	592.8	593.5	594.2
120°	639.9	639.0	638.2	637.3	638.2	639.0	639.9	640.8	641.2	641.2	641.2
122.5°	687.0	686.4	685.7	685.1	685.7	686.4	687.0	687.6	688.3	689.0	689.7
125°	758.9	758.6	758.4	758.0	758.4	758.6	758.9	759.2	759.7	760.6	761.5
127.5°	827.2	826.3	825.4	824.5	825.4	826.3	827.2	828.2	829.1	830.2	831.2
130°	875.7	874.6	873.4	872.3	873.4	874.6	875.7	876.8	877.7	878.3	878.9
132.5°	920.8	919.8	918.9	917.9	918.9	919.8	920.8	921.6	922.7	924.0	925.3
135°	991.7	990.8	990.0	989.1	990.0	990.8	991.7	992.6	993.2	993.4	993.7
137.5°	1057.0	1055.8	1054.6	1053.4	1054.6	1055.8	1057.0	1058.1	1058.8	1059.0	1059.2
140°	1101.6	1100.4	1099.2	1098.1	1099.2	1100.4	1101.6	1102.8	1103.3	1103.3	1103.3
142.5°	1142.1	1140.9	1139.8	1138.6	1139.8	1140.9	1142.1	1143.2	1143.7	1143.5	1143.2
145°	1202.8	1201.7	1200.5	1199.4	1200.5	1201.7	1202.8	1203.9	1204.4	1204.1	1203.9
147.5°	1256.9	1255.8	1254.7	1253.6	1254.7	1255.8	1256.9	1258.0	1258.3	1257.6	1257.0
150°	1291.5	1290.6	1289.8	1288.9	1289.8	1290.6	1291.5	1292.4	1292.4	1291.5	1290.6
152.5°	1325.4	1324.3	1323.3	1322.2	1323.3	1324.3	1325.4	1326.5	1326.5	1325.4	1324.3
155°	1369.4	1368.6	1367.7	1366.8	1367.7	1368.6	1369.4	1370.3	1369.9	1368.6	1367.1
157.5°	1409.4	1408.0	1406.6	1405.2	1406.6	1408.0	1409.4	1410.7	1410.5	1408.5	1406.5
160°	1432.5	1431.4	1430.3	1429.1	1430.3	1431.4	1432.5	1433.7	1433.4	1431.7	1429.9
162.5°	1454.1	1452.7	1451.3	1449.8	1451.3	1452.7	1454.1	1455.4	1455.1	1453.2	1451.2
165°	1481.4	1480.1	1478.6	1477.1	1478.6	1480.1	1481.4	1482.9	1482.6	1480.6	1478.6
167.5°	1504.0	1502.4	1501.0	1499.4	1501.0	1502.4	1504.0	1505.5	1505.2	1503.2	1501.2
170°	1516.0	1514.3	1512.6	1510.9	1512.6	1514.3	1516.0	1517.8	1517.7	1515.6	1513.6
172.5°	1525.4	1523.7	1522.0	1520.3	1522.0	1523.7	1525.4	1527.2	1527.0	1525.0	1522.9
175°	1535.5	1533.8	1532.1	1530.3	1532.1	1533.8	1535.5	1537.3	1537.1	1535.1	1533.1
177.5°	1539.2	1537.8	1536.4	1535.0	1536.4	1537.8	1539.2	1540.6	1540.6	1539.2	1537.8
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1216.3	1221.2	1228.6	1232.9	1239.9	1244.5	1247.0	1251.5	1254.0	1262.7	1272.0
5°	1148.4	1155.5	1167.8	1179.1	1191.5	1204.2	1213.5	1224.0	1233.6	1250.3	1268.0
7.5°	1070.6	1080.3	1099.3	1117.6	1139.0	1157.0	1172.9	1190.9	1207.0	1231.0	1255.9
10°	1012.2	1029.3	1054.4	1071.5	1099.7	1117.7	1142.7	1162.4	1184.9	1216.5	1244.7
12.5°	961.9	982.6	1002.6	1026.5	1051.8	1081.8	1109.3	1134.7	1161.3	1194.0	1227.1
15°	870.6	900.5	931.8	955.9	990.2	1021.8	1054.0	1088.2	1120.8	1159.9	1202.9
17.5°	753.2	787.8	840.3	881.8	922.0	953.7	993.4	1034.9	1073.2	1120.4	1168.4
20°	700.2	725.7	761.2	817.0	877.7	911.5	951.9	997.6	1041.6	1093.0	1144.4
22.5°	657.5	680.3	708.9	752.3	820.0	866.2	908.4	954.8	1005.7	1058.3	1115.3
25°	596.8	612.7	642.6	677.7	724.3	800.3	846.4	893.0	948.5	1004.7	1069.7
27.5°	551.2	565.4	584.9	618.5	653.1	707.7	781.1	831.9	887.1	950.4	1017.9
30°	516.4	533.1	554.7	578.4	616.2	658.8	732.2	791.1	845.6	910.7	982.7
32.5°	491.1	504.3	522.6	546.7	578.2	619.1	677.7	749.2	802.4	870.9	946.2
35°	449.6	465.0	479.9	502.8	528.3	565.7	610.0	686.5	739.3	806.9	882.5
37.5°	415.4	424.8	441.3	459.4	486.4	514.2	552.7	621.3	678.3	744.8	822.2
40°	389.4	401.2	413.5	433.8	455.7	482.6	520.4	571.4	636.8	701.9	777.5
42.5°	364.1	379.1	392.1	405.6	429.7	456.6	487.3	530.5	597.4	659.0	732.5
45°	333.6	343.3	356.9	371.8	391.6	414.5	441.7	479.5	543.6	596.8	665.8
47.5°	298.1	312.2	321.1	335.7	354.5	376.3	401.7	434.3	486.3	536.1	600.1
50°	273.8	288.3	301.1	314.3	331.0	352.1	373.2	404.8	446.5	498.9	558.6
52.5°	253.0	265.8	278.2	291.4	307.7	327.1	347.2	374.9	410.7	458.7	516.8
55°	224.5	232.5	245.2	258.4	272.9	291.4	310.7	334.0	364.8	405.2	452.3
57.5°	195.4	204.6	214.6	227.9	242.6	256.8	274.1	295.2	319.5	356.1	396.3
60°	178.9	185.9	194.2	207.8	221.5	234.3	251.0	268.5	291.4	323.0	357.3
62.5°	160.6	167.3	175.0	186.8	200.1	211.7	226.4	245.0	264.3	293.2	323.2
65°	130.1	139.7	147.2	157.8	168.8	181.1	192.5	207.4	224.5	247.5	274.2
67.5°	107.9	112.8	119.7	129.3	140.5	151.1	162.0	173.6	188.5	206.1	227.4
70°	98.0	99.8	101.1	110.3	120.9	131.4	141.5	152.5	165.2	179.8	198.2
72.5°	86.4	88.2	89.8	93.8	102.2	112.8	123.2	131.4	143.4	155.5	170.5
75°	68.5	71.2	72.5	74.7	77.8	84.8	94.5	102.4	109.4	118.6	130.5
77.5°	52.2	53.7	55.1	57.4	59.3	62.6	68.0	75.2	81.7	87.1	95.3
80°	41.3	41.8	43.5	44.4	47.0	49.2	51.8	57.6	64.1	66.4	72.1
82.5°	31.1	31.6	33.0	33.8	35.0	36.9	40.3	41.8	46.9	49.9	53.5
85°	17.1	16.7	18.0	18.0	18.9	19.8	20.7	22.8	24.2	27.7	28.6
87.5°	14.2	14.4	13.4	12.1	10.9	10.3	9.7	9.4	9.4	9.7	10.4
90°	44.9	45.5	39.1	32.7	26.4	20.1	15.2	11.7	8.2	4.7	1.3
92.5°	41.4	41.2	39.8	38.3	36.8	35.3	33.2	30.7	28.2	25.7	23.1
95°	83.1	83.1	82.5	81.9	81.4	80.8	79.0	76.1	73.3	70.3	67.5
97.5°	139.7	139.7	138.5	137.5	136.4	135.3	133.5	131.0	128.4	125.9	123.3
100°	179.1	179.1	178.2	177.4	176.5	175.6	174.1	171.8	169.4	167.1	164.9
102.5°	222.0	221.7	220.6	219.5	218.4	217.3	215.9	214.0	212.2	210.3	208.4
105°	286.1	285.6	285.0	284.4	283.9	283.3	282.5	281.6	280.8	279.9	279.1
107.5°	356.1	355.9	355.9	355.9	355.9	355.9	355.2	354.0	352.8	351.5	350.2
110°	403.7	403.7	403.7	403.7	403.7	403.7	402.8	401.1	399.3	397.6	395.9



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	451.8	452.5	452.7	453.0	453.1	453.4	452.6	450.9	449.2	447.5	445.7
115°	524.1	524.4	525.0	525.6	526.2	526.7	526.2	524.4	522.6	520.9	519.2
117.5°	594.9	595.6	597.1	598.7	600.4	602.0	601.7	599.3	597.0	594.7	592.5
120°	641.2	641.2	643.5	645.8	648.2	650.5	650.5	648.2	645.8	643.5	641.2
122.5°	690.3	691.0	692.7	694.3	695.9	697.5	697.0	694.1	691.4	688.6	685.9
125°	762.3	763.2	764.1	765.0	765.9	766.7	765.9	763.2	760.6	758.0	755.4
127.5°	832.2	833.4	834.4	835.4	836.5	837.5	836.4	833.1	829.7	826.5	823.2
130°	879.5	880.0	880.6	881.2	881.8	882.4	880.8	877.0	873.3	869.5	865.7
132.5°	926.5	927.8	927.7	927.6	927.5	927.4	925.7	922.7	919.6	916.6	913.5
135°	994.0	994.3	993.7	993.2	992.6	992.0	990.1	986.9	983.8	980.6	977.4
137.5°	1059.5	1059.7	1058.9	1058.2	1057.5	1056.7	1055.0	1052.4	1049.8	1047.2	1044.7
140°	1103.3	1103.3	1101.9	1100.4	1099.0	1097.5	1095.5	1093.0	1090.4	1087.7	1085.1
142.5°	1143.0	1142.8	1141.8	1140.8	1139.8	1138.8	1137.0	1134.5	1131.9	1129.3	1126.7
145°	1203.5	1203.2	1201.5	1199.8	1198.1	1196.4	1194.5	1192.4	1190.4	1188.4	1186.4
147.5°	1256.4	1255.7	1254.6	1253.4	1252.2	1251.1	1249.3	1246.9	1244.4	1242.0	1239.6
150°	1289.8	1288.9	1287.8	1286.6	1285.5	1284.3	1282.9	1281.2	1279.4	1277.6	1275.9
152.5°	1323.3	1322.2	1320.8	1319.4	1318.0	1316.6	1315.1	1313.3	1311.6	1309.8	1308.1
155°	1365.6	1364.2	1363.3	1362.4	1361.6	1360.7	1359.9	1359.0	1358.1	1357.3	1356.4
157.5°	1404.5	1402.7	1402.1	1401.6	1401.1	1400.6	1400.0	1399.5	1398.9	1398.3	1397.7
160°	1428.2	1426.5	1426.2	1425.9	1425.6	1425.4	1425.0	1424.4	1423.7	1423.2	1422.6
162.5°	1449.2	1447.3	1447.0	1446.7	1446.4	1446.1	1446.0	1445.8	1445.7	1445.6	1445.4
165°	1476.5	1474.5	1474.5	1474.5	1474.5	1474.5	1474.7	1475.0	1475.2	1475.6	1475.8
167.5°	1499.2	1497.1	1497.2	1497.3	1497.3	1497.4	1497.8	1498.7	1499.5	1500.4	1501.2
170°	1511.6	1509.6	1509.8	1510.2	1510.5	1510.7	1511.3	1512.2	1513.0	1513.9	1514.8
172.5°	1521.0	1518.9	1519.2	1519.5	1519.8	1520.1	1520.7	1521.6	1522.4	1523.3	1524.1
175°	1531.1	1529.0	1529.7	1530.2	1530.8	1531.4	1532.1	1532.9	1533.8	1534.6	1535.5
177.5°	1536.4	1535.0	1535.5	1535.9	1536.4	1536.9	1537.5	1538.2	1538.9	1539.6	1540.2
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1272.3	1273.3	1280.4	1283.5	1289.9	1292.3	1295.1	1294.4	1294.4	1295.8	1305.7
5°	1275.0	1283.8	1296.9	1309.7	1322.0	1332.6	1339.6	1346.6	1349.3	1362.0	1373.5
7.5°	1270.4	1286.6	1308.4	1327.8	1351.1	1369.3	1384.4	1398.1	1407.4	1425.9	1444.9
10°	1264.5	1287.3	1311.9	1337.0	1369.1	1393.2	1417.8	1436.8	1442.9	1470.6	1486.4
12.5°	1252.5	1283.1	1314.4	1346.8	1378.2	1411.5	1438.6	1457.5	1479.1	1504.0	1533.2
15°	1234.6	1269.7	1310.6	1352.4	1397.1	1437.6	1466.6	1499.6	1523.3	1550.6	1576.1
17.5°	1208.8	1254.0	1306.1	1354.4	1406.2	1449.7	1489.5	1521.2	1537.9	1553.4	1557.2
20°	1188.4	1237.2	1298.3	1355.4	1407.3	1457.4	1496.9	1523.3	1527.7	1528.1	1504.9
22.5°	1166.2	1221.3	1285.3	1343.8	1405.8	1461.6	1492.4	1503.7	1486.2	1456.4	1411.4
25°	1125.6	1189.3	1263.6	1330.3	1398.1	1450.8	1461.4	1441.6	1380.4	1316.3	1235.0
27.5°	1081.4	1153.1	1232.7	1307.0	1379.1	1411.8	1389.0	1317.7	1207.6	1112.0	996.1
30°	1049.1	1129.5	1207.7	1290.8	1357.6	1371.7	1319.4	1214.4	1086.0	941.8	826.3
32.5°	1012.2	1096.5	1182.4	1268.3	1324.2	1310.5	1224.1	1094.8	944.3	802.6	693.4
35°	959.4	1046.5	1139.2	1225.3	1260.9	1201.6	1072.4	904.0	750.2	617.9	542.8
37.5°	898.5	993.2	1089.7	1168.8	1166.2	1067.4	891.4	717.6	588.3	510.1	456.6
40°	855.2	951.1	1055.2	1122.1	1093.5	964.7	774.0	610.0	515.6	453.1	414.0
42.5°	813.8	909.9	1013.4	1066.5	1016.8	858.5	668.5	540.0	462.1	413.4	381.7
45°	743.2	844.7	940.6	970.0	881.2	706.7	540.6	447.4	395.5	359.6	337.5
47.5°	674.2	774.0	861.5	862.0	741.9	573.1	456.0	387.2	342.9	315.0	299.0
50°	632.0	726.9	800.3	788.9	652.6	509.8	407.9	348.5	311.6	290.1	273.4
52.5°	584.5	676.7	740.2	707.7	577.0	448.7	364.6	314.8	284.2	265.4	250.6
55°	515.6	597.3	642.1	592.9	470.7	373.2	308.1	269.0	246.2	230.3	217.6
57.5°	447.7	515.2	543.4	486.1	387.7	309.4	260.6	231.3	208.6	197.3	190.6
60°	405.2	462.8	482.6	419.3	337.1	270.7	230.7	203.5	186.8	179.3	172.7
62.5°	363.3	410.4	418.6	360.6	293.9	236.9	202.6	179.6	168.5	161.4	155.2
65°	301.5	335.4	331.4	284.8	232.5	188.1	163.1	149.0	140.6	130.5	119.5
67.5°	248.2	268.9	256.4	221.5	177.5	146.2	129.8	119.2	108.8	99.3	96.7
70°	214.5	226.4	213.2	181.1	145.5	122.6	109.4	96.7	90.6	88.3	84.4
72.5°	182.1	186.2	172.0	144.5	118.4	101.5	88.7	81.5	78.3	76.4	73.9
75°	136.7	133.6	121.3	99.8	82.2	70.8	66.8	64.1	62.0	60.2	58.9
77.5°	96.0	91.5	80.5	66.5	57.3	51.7	49.4	48.0	46.9	46.1	44.8
80°	72.1	69.0	58.0	47.4	43.5	40.9	39.5	37.8	37.8	36.9	35.6
82.5°	52.8	49.3	39.7	34.8	32.6	31.0	30.0	29.0	28.7	28.8	27.9
85°	27.7	22.4	19.8	18.9	17.6	16.7	17.1	16.3	16.3	16.3	15.8
87.5°	9.4	8.4	8.7	9.0	10.3	11.6	12.5	13.8	15.4	15.0	15.2
90°	4.7	8.2	11.7	15.2	20.1	26.4	32.7	39.1	45.5	44.9	44.3
92.5°	25.7	28.2	30.7	33.2	35.3	36.8	38.3	39.8	41.2	41.4	41.5
95°	70.3	73.3	76.1	79.0	80.8	81.4	81.9	82.5	83.1	83.1	83.1
97.5°	125.9	128.4	131.0	133.5	135.3	136.4	137.5	138.5	139.7	139.7	139.7
100°	167.1	169.4	171.8	174.1	175.6	176.5	177.4	178.2	179.1	179.1	179.1
102.5°	210.3	212.2	214.0	215.9	217.3	218.4	219.5	220.6	221.7	222.0	222.1
105°	279.9	280.8	281.6	282.5	283.3	283.9	284.4	285.0	285.6	286.1	286.7
107.5°	351.5	352.8	354.0	355.2	355.9	355.9	355.9	355.9	355.9	356.1	356.4
110°	397.6	399.3	401.1	402.8	403.7	403.7	403.7	403.7	403.7	403.7	403.7





TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	447.5	449.2	450.9	452.6	453.4	453.1	453.0	452.7	452.5	451.8	451.1
115°	520.9	522.6	524.4	526.2	526.7	526.2	525.6	525.0	524.4	524.1	523.8
117.5°	594.7	597.0	599.3	601.7	602.0	600.4	598.7	597.1	595.6	594.9	594.2
120°	643.5	645.8	648.2	650.5	650.5	648.2	645.8	643.5	641.2	641.2	641.2
122.5°	688.6	691.4	694.1	697.0	697.5	695.9	694.3	692.7	691.0	690.3	689.7
125°	758.0	760.6	763.2	765.9	766.7	765.9	765.0	764.1	763.2	762.3	761.5
127.5°	826.5	829.7	833.1	836.4	837.5	836.5	835.4	834.4	833.4	832.2	831.2
130°	869.5	873.3	877.0	880.8	882.4	881.8	881.2	880.6	880.0	879.5	878.9
132.5°	916.6	919.6	922.7	925.7	927.4	927.5	927.6	927.7	927.8	926.5	925.3
135°	980.6	983.8	986.9	990.1	992.0	992.6	993.2	993.7	994.3	994.0	993.7
137.5°	1047.2	1049.8	1052.4	1055.0	1056.7	1057.5	1058.2	1058.9	1059.7	1059.5	1059.2
140°	1087.7	1090.4	1093.0	1095.5	1097.5	1099.0	1100.4	1101.9	1103.3	1103.3	1103.3
142.5°	1129.3	1131.9	1134.5	1137.0	1138.8	1139.8	1140.8	1141.8	1142.8	1143.0	1143.2
145°	1188.4	1190.4	1192.4	1194.5	1196.4	1198.1	1199.8	1201.5	1203.2	1203.5	1203.9
147.5°	1242.0	1244.4	1246.9	1249.3	1251.1	1252.2	1253.4	1254.6	1255.7	1256.4	1257.0
150°	1277.6	1279.4	1281.2	1282.9	1284.3	1285.5	1286.6	1287.8	1288.9	1289.8	1290.6
152.5°	1309.8	1311.6	1313.3	1315.1	1316.6	1318.0	1319.4	1320.8	1322.2	1323.3	1324.3
155°	1357.3	1358.1	1359.0	1359.9	1360.7	1361.6	1362.4	1363.3	1364.2	1365.6	1367.1
157.5°	1398.3	1398.9	1399.5	1400.0	1400.6	1401.1	1401.6	1402.1	1402.7	1404.5	1406.5
160°	1423.2	1423.7	1424.4	1425.0	1425.4	1425.6	1425.9	1426.2	1426.5	1428.2	1429.9
162.5°	1445.6	1445.7	1445.8	1446.0	1446.1	1446.4	1446.7	1447.0	1447.3	1449.2	1451.2
165°	1475.6	1475.2	1475.0	1474.7	1474.5	1474.5	1474.5	1474.5	1474.5	1476.5	1478.6
167.5°	1500.4	1499.5	1498.7	1497.8	1497.4	1497.3	1497.3	1497.2	1497.1	1499.2	1501.2
170°	1513.9	1513.0	1512.2	1511.3	1510.7	1510.5	1510.2	1509.8	1509.6	1511.6	1513.6
172.5°	1523.3	1522.4	1521.6	1520.7	1520.1	1519.8	1519.5	1519.2	1518.9	1521.0	1522.9
175°	1534.6	1533.8	1532.9	1532.1	1531.4	1530.8	1530.2	1529.7	1529.0	1531.1	1533.1
177.5°	1539.6	1538.9	1538.2	1537.5	1536.9	1536.4	1535.9	1535.5	1535.0	1536.4	1537.8
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9	1264.9
2.5°	1309.2	1313.7	1315.9	1315.9	1318.4	1317.2	1316.2
5°	1384.4	1392.8	1394.6	1402.5	1408.2	1406.4	1407.3
7.5°	1459.2	1472.7	1485.9	1492.0	1493.0	1496.5	1497.8
10°	1505.3	1516.3	1537.0	1533.9	1549.2	1558.1	1543.5
12.5°	1549.6	1564.4	1578.7	1582.7	1591.5	1594.2	1588.5
15°	1589.7	1597.6	1598.4	1596.3	1598.9	1596.7	1588.4
17.5°	1552.2	1539.4	1513.4	1501.1	1491.3	1476.9	1471.1
20°	1490.3	1452.5	1408.6	1391.0	1370.4	1329.9	1339.6
22.5°	1356.8	1313.6	1269.7	1218.4	1193.9	1155.5	1153.2
25°	1148.8	1074.6	992.8	935.7	902.3	864.1	847.4
27.5°	893.2	799.7	732.7	698.8	668.0	637.7	636.4
30°	725.1	654.9	603.0	574.0	555.1	542.3	545.0
32.5°	611.2	563.1	528.1	504.0	490.1	480.4	480.3
35°	499.7	466.7	444.4	434.2	424.1	417.1	417.5
37.5°	427.7	407.9	395.4	384.2	377.9	374.4	372.6
40°	390.7	374.4	364.8	358.2	352.9	348.1	347.2
42.5°	361.5	348.1	338.4	333.2	328.3	324.9	324.0
45°	320.8	309.9	301.1	295.3	293.2	290.1	290.1
47.5°	285.4	274.6	267.8	264.2	260.4	258.3	258.2
50°	261.5	253.1	247.0	244.8	241.7	240.4	240.0
52.5°	240.0	233.8	229.5	227.9	226.6	224.9	225.2
55°	210.9	207.4	205.7	204.4	202.2	199.5	201.3
57.5°	186.4	183.5	178.7	174.6	172.5	170.7	171.4
60°	169.2	163.1	156.9	152.1	150.8	146.8	146.8
62.5°	147.4	138.8	131.2	128.5	127.2	125.4	125.0
65°	113.4	109.9	108.1	106.3	105.5	105.5	104.6
67.5°	93.9	92.6	90.7	90.1	89.3	89.0	88.8
70°	83.1	81.3	80.4	80.0	79.1	79.6	78.3
72.5°	72.5	71.1	70.9	69.8	69.2	69.3	68.4
75°	57.2	57.2	56.7	56.2	55.4	54.9	55.4
77.5°	43.9	44.0	43.2	43.1	43.0	43.1	42.7
80°	35.1	35.6	35.1	34.7	34.3	34.7	34.3
82.5°	27.8	27.1	27.0	26.9	26.9	26.6	26.5
85°	15.8	16.3	15.8	15.4	15.4	15.4	15.8
87.5°	14.7	14.6	14.6	14.6	14.7	14.7	14.5
90°	43.7	43.1	43.0	43.3	43.6	43.8	44.2
92.5°	41.6	41.8	41.8	41.8	41.9	42.0	42.0
95°	83.1	83.1	82.7	82.2	81.6	81.0	80.5
97.5°	139.7	139.7	139.7	139.6	139.5	139.5	139.4
100°	179.1	179.1	179.0	178.7	178.4	178.1	177.8
102.5°	222.4	222.7	222.6	222.3	222.1	221.7	221.4
105°	287.3	287.8	288.2	288.2	288.2	288.2	288.2
107.5°	356.6	356.8	356.3	355.0	353.6	352.3	350.9
110°	403.7	403.7	403.2	402.3	401.5	400.6	399.8



TEST NUMBER: P331822-935

CATALOG NUMBER: S122RDIW-S675D1440U935-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	450.4	449.7	449.0	448.4	447.8	447.1	446.5
115°	523.5	523.2	522.6	521.8	520.9	520.0	519.2
117.5°	593.5	592.8	591.9	591.1	590.2	589.4	588.5
120°	641.2	641.2	640.8	639.9	639.0	638.2	637.3
122.5°	689.0	688.3	687.6	687.0	686.4	685.7	685.1
125°	760.6	759.7	759.2	758.9	758.6	758.4	758.0
127.5°	830.2	829.1	828.2	827.2	826.3	825.4	824.5
130°	878.3	877.7	876.8	875.7	874.6	873.4	872.3
132.5°	924.0	922.7	921.6	920.8	919.8	918.9	917.9
135°	993.4	993.2	992.6	991.7	990.8	990.0	989.1
137.5°	1059.0	1058.8	1058.1	1057.0	1055.8	1054.6	1053.4
140°	1103.3	1103.3	1102.8	1101.6	1100.4	1099.2	1098.1
142.5°	1143.5	1143.7	1143.2	1142.1	1140.9	1139.8	1138.6
145°	1204.1	1204.4	1203.9	1202.8	1201.7	1200.5	1199.4
147.5°	1257.6	1258.3	1258.0	1256.9	1255.8	1254.7	1253.6
150°	1291.5	1292.4	1292.4	1291.5	1290.6	1289.8	1288.9
152.5°	1325.4	1326.5	1326.5	1325.4	1324.3	1323.3	1322.2
155°	1368.6	1369.9	1370.3	1369.4	1368.6	1367.7	1366.8
157.5°	1408.5	1410.5	1410.7	1409.4	1408.0	1406.6	1405.2
160°	1431.7	1433.4	1433.7	1432.5	1431.4	1430.3	1429.1
162.5°	1453.2	1455.1	1455.4	1454.1	1452.7	1451.3	1449.8
165°	1480.6	1482.6	1482.9	1481.4	1480.1	1478.6	1477.1
167.5°	1503.2	1505.2	1505.5	1504.0	1502.4	1501.0	1499.4
170°	1515.6	1517.7	1517.8	1516.0	1514.3	1512.6	1510.9
172.5°	1525.0	1527.0	1527.2	1525.4	1523.7	1522.0	1520.3
175°	1535.1	1537.1	1537.3	1535.5	1533.8	1532.1	1530.3
177.5°	1539.2	1540.6	1540.6	1539.2	1537.8	1536.4	1535.0
180°	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2	1538.2

(END OF REPORT)