

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331586-940

Luminaire Tested: **S122DIW-S1005D435U940-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P331586-940  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-8,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S122DIW-S1005D435U940-4F0-1E-UDD-A1  
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 1005 LUMENS PER FOOT, ASYMMETRIC DIFFUSER  
UPLIGHT 435 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5263.4 lumens  
Efficiency: N/A  
Efficacy: 100.4 lumens/watt  
Spacing Criteria (0/90/45): 1.08 / 1.16 / 1.23  
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')  
CIE Type: Semi-Direct


Input Watts (W): 52.4  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

### Luminous Intensity Polar Plot





TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	113	113	113	113	107	107	107	107	97	97	97	87	87	87	79	79	79	75
1	104	100	96	93	99	95	92	89	86	84	81	78	76	74	71	69	68	64
2	95	88	82	77	90	84	79	74	76	72	69	70	66	63	63	61	58	55
3	87	78	71	65	83	75	68	63	68	63	59	62	58	54	57	53	50	47
4	80	70	62	56	76	67	60	54	61	55	51	56	51	47	51	47	44	41
5	74	63	55	49	70	60	53	47	55	49	44	51	46	42	46	42	39	36
6	69	57	49	43	65	54	47	42	50	44	39	46	41	37	42	38	35	32
7	64	52	44	38	61	50	42	37	46	40	35	42	37	33	39	35	31	29
8	60	47	39	34	57	45	38	33	42	36	31	39	34	30	36	32	28	26
9	56	43	36	31	53	42	35	30	39	33	29	36	31	27	33	29	26	24
10	52	40	33	28	50	39	32	27	36	30	26	33	28	25	31	27	24	22

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	28709	28709	28709	28709
5°	32185	28896	25606	28896
10°	36882	28658	22161	28658
15°	40802	28134	19579	28134
20°	40180	27569	17849	27569
25°	36230	26820	16751	26820
30°	29940	25620	15951	25620
35°	21821	24366	15382	24366
40°	17428	22885	15066	22885
45°	15230	21174	14636	21174
50°	14315	19515	14350	19515
55°	13196	17833	13965	17833
60°	12093	16043	13372	16043
65°	11018	14437	12791	14437
70°	10003	12873	11939	12873
75°	8865	11123	10574	11123
80°	7624	9214	8517	9214
85°	6836	6836	5076	6836



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	169.3	3.2
10°-20°	492.3	9.4
20°-30°	714.5	13.6
30°-40°	754.0	14.3
40°-50°	667.6	12.7
50°-60°	532.7	10.1
60°-70°	362.1	6.9
70°-80°	185.6	3.5
80°-90°	46.7	0.9
90°-100°	30.3	0.6
100°-110°	94.2	1.8
110°-120°	161.0	3.1
120°-130°	211.8	4.0
130°-140°	237.7	4.5
140°-150°	233.1	4.4
150°-160°	195.5	3.7
160°-170°	129.7	2.5
170°-180°	45.3	0.9
0°-30°	1376.1	26.1
0°-40°	2130.1	40.5
0°-60°	3330.4	63.3
0°-90°	3924.8	74.6
90°-120°	285.6	5.4
90°-150°	968.1	18.4
90°-180°	1339.0	25.4
0°-180°	5263.4	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1778	1778	1778	1778	1778	
5°	1986	1783	1580	1783	1986	198
15°	2441	1683	1171	1683	2441	674
25°	2034	1506	940	1506	2034	919
35°	1107	1236	780	1236	1107	720
45°	667	927	641	927	667	524
55°	469	634	496	634	469	420
65°	288	378	335	378	288	287
75°	142	178	170	178	142	152
85°	37	37	27	37	37	41
90°	14	0	14	0	14	8
95°	25	21	25	21	25	28
105°	90	87	90	87	90	94
115°	162	162	162	162	162	160
125°	236	235	236	235	236	210
135°	308	304	308	304	308	237
145°	373	369	373	369	373	233
155°	425	422	425	422	425	196
165°	460	459	460	459	460	130
175°	476	478	476	478	476	45
180°	479	479	479	479	479	



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1860.1	1860.6	1861.7	1853.0	1851.9	1851.9	1844.2	1837.7	1830.1	1819.6	1820.8
5°	1985.8	1993.3	1996.1	1987.9	1975.6	1974.2	1962.7	1943.5	1925.7	1911.4	1901.1
7.5°	2135.9	2138.9	2132.3	2121.5	2112.3	2095.9	2074.3	2053.1	2023.5	1996.3	1976.0
10°	2249.6	2253.7	2242.1	2226.4	2213.4	2194.3	2162.8	2130.7	2091.8	2054.2	2024.1
12.5°	2336.0	2346.1	2331.2	2329.1	2306.9	2280.6	2243.2	2227.0	2172.1	2119.8	2087.6
15°	2441.0	2440.3	2441.7	2428.7	2412.3	2408.2	2368.6	2325.5	2248.3	2217.5	2164.2
17.5°	2410.7	2421.0	2425.8	2425.6	2425.3	2422.7	2409.9	2382.7	2344.0	2294.2	2232.7
20°	2338.5	2352.2	2354.2	2369.9	2378.8	2390.4	2395.2	2387.6	2363.7	2322.1	2268.8
22.5°	2227.0	2230.8	2237.2	2261.6	2280.9	2310.1	2325.2	2350.5	2341.4	2320.9	2276.4
25°	2033.7	2026.9	2050.8	2063.1	2107.5	2153.9	2187.5	2224.4	2257.2	2277.0	2264.0
27.5°	1801.6	1791.4	1827.2	1859.8	1896.0	1946.2	1998.4	2060.0	2111.3	2175.4	2197.4
30°	1605.9	1612.0	1646.2	1681.1	1735.7	1806.8	1865.5	1933.2	2006.3	2078.1	2128.0
32.5°	1394.9	1418.5	1440.1	1493.5	1541.7	1621.0	1707.0	1791.6	1882.8	1964.4	2041.7
35°	1107.1	1134.3	1164.5	1203.4	1271.0	1349.6	1433.7	1547.8	1672.2	1783.6	1875.2
37.5°	931.8	927.5	944.7	972.9	1027.6	1091.1	1187.8	1300.6	1447.0	1577.9	1707.0
40°	826.9	824.1	836.4	862.4	904.1	950.6	1035.3	1134.3	1270.3	1430.3	1584.0
42.5°	754.7	756.3	763.2	781.5	810.0	848.3	911.8	996.0	1120.6	1271.2	1436.5
45°	667.0	671.7	679.3	688.1	704.5	736.0	771.5	831.7	930.1	1055.8	1218.4
47.5°	603.8	604.0	611.6	619.4	629.1	646.8	675.8	713.5	783.0	885.4	1025.2
50°	569.9	565.2	570.6	576.8	587.0	599.3	618.4	654.0	700.4	783.1	900.0
52.5°	528.3	528.5	533.4	535.7	544.9	557.2	574.7	599.3	641.4	706.1	802.1
55°	468.8	472.2	474.9	479.0	487.2	496.1	509.8	526.2	559.0	607.5	678.6
57.5°	412.8	413.8	416.6	424.4	429.5	437.7	450.8	465.7	487.0	522.9	576.3
60°	374.5	374.5	380.0	383.3	390.2	398.4	408.7	423.0	442.1	471.5	514.6
62.5°	339.5	338.9	341.2	346.7	352.0	359.6	369.8	382.0	400.0	426.1	461.5
65°	288.4	287.0	291.1	292.5	297.9	305.5	313.7	326.6	341.0	360.2	391.6
67.5°	239.2	240.9	243.0	245.6	248.6	256.5	262.0	271.2	283.3	299.2	320.5
70°	211.9	211.9	211.9	213.9	218.0	222.1	227.6	235.1	246.7	260.4	279.5
72.5°	181.2	183.4	185.6	184.4	189.6	192.0	198.6	202.9	213.9	222.7	239.6
75°	142.1	142.1	142.1	145.5	147.6	149.6	153.7	157.8	163.4	174.2	183.2
77.5°	106.0	105.8	106.5	107.3	109.5	111.9	113.2	116.8	121.9	127.0	134.5
80°	82.0	83.4	84.1	85.4	85.4	86.8	87.5	92.3	95.7	99.1	103.9
82.5°	63.4	63.7	63.8	64.1	64.6	65.5	67.2	68.8	70.0	72.9	76.5
85°	36.9	36.2	36.2	37.5	36.9	36.9	38.3	39.6	39.6	40.3	42.4
87.5°	16.9	16.9	17.5	16.9	16.9	17.5	17.5	16.9	17.6	18.1	18.3
90°	13.7	13.6	13.6	13.5	13.4	13.5	13.6	13.8	14.0	14.2	12.1
92.5°	13.1	13.1	13.0	13.0	13.0	13.0	12.9	12.9	12.8	12.8	12.4
95°	25.1	25.2	25.4	25.6	25.8	25.9	25.9	25.9	25.9	25.9	25.7
97.5°	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.2
100°	55.4	55.5	55.6	55.6	55.7	55.7	55.7	55.7	55.7	55.7	55.5
102.5°	68.9	69.0	69.1	69.2	69.3	69.3	69.2	69.1	69.1	69.0	68.7
105°	89.7	89.7	89.7	89.7	89.7	89.6	89.4	89.3	89.1	88.9	88.7
107.5°	109.2	109.7	110.0	110.5	110.9	111.1	111.0	110.9	110.8	110.8	110.8
110°	124.4	124.7	124.9	125.2	125.5	125.6	125.6	125.6	125.6	125.6	125.6



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	139.0	139.2	139.4	139.6	139.7	140.0	140.2	140.4	140.6	140.8	140.9
115°	161.6	161.8	162.1	162.4	162.6	162.8	162.9	163.0	163.1	163.2	163.4
117.5°	183.2	183.4	183.7	184.0	184.2	184.5	184.7	184.9	185.1	185.4	185.8
120°	198.4	198.7	198.9	199.2	199.5	199.6	199.6	199.6	199.6	199.6	200.3
122.5°	213.2	213.4	213.7	213.8	214.0	214.2	214.5	214.6	214.9	215.1	215.6
125°	235.9	236.0	236.1	236.2	236.3	236.5	236.7	237.0	237.3	237.6	237.8
127.5°	256.6	256.9	257.2	257.4	257.8	258.1	258.4	258.7	259.0	259.4	259.7
130°	271.5	271.9	272.2	272.6	273.0	273.2	273.4	273.6	273.8	273.9	274.1
132.5°	285.7	286.0	286.2	286.6	286.9	287.2	287.6	288.0	288.4	288.7	288.7
135°	307.8	308.1	308.4	308.6	308.9	309.1	309.2	309.2	309.3	309.4	309.2
137.5°	327.9	328.2	328.6	329.0	329.3	329.6	329.6	329.7	329.8	329.8	329.6
140°	341.8	342.1	342.5	342.9	343.2	343.4	343.4	343.4	343.4	343.4	343.0
142.5°	354.4	354.7	355.1	355.4	355.8	356.0	355.9	355.8	355.8	355.7	355.3
145°	373.3	373.6	374.0	374.3	374.7	374.9	374.8	374.7	374.6	374.5	374.0
147.5°	390.2	390.5	390.8	391.2	391.6	391.6	391.5	391.2	391.0	390.8	390.5
150°	401.2	401.4	401.7	402.0	402.3	402.3	402.0	401.7	401.4	401.2	400.8
152.5°	411.5	411.9	412.1	412.5	412.9	412.9	412.5	412.1	411.9	411.5	411.1
155°	425.4	425.7	426.0	426.2	426.5	426.4	426.0	425.5	425.1	424.6	424.4
157.5°	437.4	437.8	438.2	438.6	439.1	439.0	438.4	437.7	437.2	436.6	436.4
160°	444.8	445.1	445.5	445.9	446.2	446.1	445.6	445.1	444.5	444.0	443.9
162.5°	451.3	451.7	452.1	452.5	453.0	452.9	452.3	451.7	451.0	450.5	450.4
165°	459.8	460.2	460.7	461.1	461.5	461.5	460.8	460.2	459.6	459.0	459.0
167.5°	466.7	467.2	467.6	468.1	468.6	468.5	467.9	467.3	466.6	466.0	466.0
170°	470.3	470.8	471.4	471.9	472.4	472.3	471.7	471.1	470.5	469.8	469.9
172.5°	473.1	473.7	474.2	474.7	475.3	475.3	474.7	474.0	473.4	472.8	472.9
175°	476.4	476.9	477.4	478.0	478.5	478.4	477.8	477.2	476.5	475.9	476.1
177.5°	477.8	478.2	478.7	479.0	479.5	479.5	479.0	478.7	478.2	477.8	477.9
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1824.6	1820.2	1817.5	1807.7	1798.8	1790.1	1787.4	1788.5	1776.5	1765.0	1760.1
5°	1895.7	1882.0	1869.0	1850.6	1828.7	1804.7	1792.4	1782.9	1759.0	1733.0	1718.0
7.5°	1959.4	1939.8	1914.8	1880.1	1848.2	1810.6	1786.7	1765.5	1730.5	1693.9	1671.5
10°	1998.1	1971.5	1939.4	1897.0	1858.1	1812.3	1780.1	1748.0	1707.0	1663.3	1635.9
12.5°	2031.5	1995.6	1964.0	1909.6	1863.5	1806.2	1768.2	1722.9	1679.7	1627.7	1601.0
15°	2110.9	2044.6	1984.5	1923.0	1866.3	1786.3	1743.9	1683.1	1626.4	1562.2	1531.4
17.5°	2172.3	2097.7	2003.0	1924.9	1858.8	1770.2	1708.0	1635.1	1568.1	1494.7	1452.9
20°	2207.3	2121.8	2020.0	1927.1	1847.8	1746.7	1679.0	1604.5	1526.0	1443.2	1398.2
22.5°	2228.0	2138.2	2037.6	1918.9	1826.0	1727.5	1642.4	1560.8	1481.1	1391.9	1344.6
25°	2234.6	2152.6	2046.0	1912.1	1798.6	1687.2	1584.7	1505.5	1409.1	1325.7	1256.7
27.5°	2202.1	2143.3	2040.8	1899.2	1767.0	1636.8	1522.5	1432.7	1331.1	1240.5	1171.2
30°	2162.1	2128.0	2028.2	1886.1	1741.9	1601.8	1476.0	1374.2	1273.1	1181.5	1110.4
32.5°	2100.4	2093.0	2005.3	1867.5	1715.1	1557.6	1427.5	1324.5	1212.5	1122.5	1054.7
35°	1979.1	2011.8	1956.5	1826.0	1664.6	1494.5	1353.7	1236.2	1120.1	1033.9	970.4
37.5°	1816.4	1897.8	1883.4	1765.1	1596.6	1425.9	1270.5	1147.6	1037.0	950.0	887.7
40°	1704.3	1808.2	1823.2	1718.7	1548.5	1372.9	1208.2	1085.8	977.9	898.7	835.7
42.5°	1584.0	1705.4	1746.7	1662.9	1496.0	1317.1	1152.4	1025.7	918.8	841.8	786.0
45°	1382.4	1543.0	1617.6	1569.7	1408.5	1225.3	1055.8	927.3	830.3	757.9	714.8
47.5°	1194.0	1369.5	1469.6	1452.7	1311.0	1129.6	962.1	838.7	744.3	686.5	648.0
50°	1060.6	1241.0	1361.9	1367.4	1241.0	1061.2	893.1	776.9	690.2	636.2	604.8
52.5°	944.7	1116.9	1248.8	1277.7	1162.8	990.2	831.3	715.8	639.4	589.8	561.6
55°	793.4	939.0	1085.2	1138.4	1046.2	882.3	735.3	633.5	561.7	527.5	502.9
57.5°	659.6	781.0	916.0	974.9	918.0	777.7	639.9	551.4	493.3	463.3	444.4
60°	589.1	684.7	805.0	875.4	826.2	701.2	580.9	496.8	449.0	422.3	404.6
62.5°	523.4	608.2	709.9	774.3	747.4	629.5	521.8	447.6	406.4	381.3	368.5
65°	431.9	498.8	577.5	636.9	619.1	529.6	441.5	377.9	345.1	325.3	315.0
67.5°	355.6	404.0	458.5	510.6	496.2	432.8	362.0	312.5	288.1	271.0	264.8
70°	307.6	344.4	393.0	434.6	423.0	371.0	315.0	272.7	251.5	237.1	231.0
72.5°	261.6	291.9	329.0	363.0	355.2	312.0	265.3	233.3	217.0	203.8	198.8
75°	197.5	220.7	243.3	265.8	263.8	230.3	203.0	178.3	165.4	155.2	153.1
77.5°	145.8	158.8	174.2	187.5	183.8	164.7	143.2	129.1	119.6	112.7	111.6
80°	111.4	118.9	129.8	139.4	134.6	126.4	109.3	99.1	92.3	85.4	82.7
82.5°	80.8	88.3	94.9	100.0	96.4	88.7	78.2	71.2	67.1	62.4	61.3
85°	42.4	46.5	49.2	50.6	49.2	44.4	39.6	36.9	33.5	31.5	30.8
87.5°	18.5	18.0	17.7	18.5	16.6	16.4	14.0	12.1	11.8	11.4	10.6
90°	10.2	8.2	6.2	4.7	3.7	2.6	1.5	0.4	1.5	2.6	3.7
92.5°	11.9	11.4	11.0	10.3	9.5	8.7	8.0	7.2	8.0	8.7	9.5
95°	25.5	25.3	25.1	24.6	23.7	22.8	21.9	21.0	21.9	22.8	23.7
97.5°	42.8	42.4	42.1	41.6	40.8	39.9	39.1	38.3	39.1	39.9	40.8
100°	55.2	54.9	54.7	54.2	53.5	52.7	52.0	51.3	52.0	52.7	53.5
102.5°	68.3	67.9	67.7	67.1	66.6	66.0	65.5	64.9	65.5	66.0	66.6
105°	88.5	88.4	88.2	87.9	87.7	87.4	87.1	86.9	87.1	87.4	87.7
107.5°	110.8	110.8	110.8	110.6	110.2	109.8	109.4	109.0	109.4	109.8	110.2
110°	125.6	125.6	125.6	125.4	124.8	124.3	123.8	123.2	123.8	124.3	124.8





TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	141.0	141.1	141.2	140.9	140.4	139.8	139.3	138.8	139.3	139.8	140.4
115°	163.5	163.7	163.9	163.7	163.2	162.6	162.1	161.6	162.1	162.6	163.2
117.5°	186.4	186.9	187.3	187.3	186.5	185.8	185.1	184.4	185.1	185.8	186.5
120°	201.0	201.7	202.4	202.4	201.7	201.0	200.3	199.6	200.3	201.0	201.7
122.5°	216.1	216.6	217.1	217.0	216.1	215.2	214.4	213.5	214.4	215.2	216.1
125°	238.1	238.4	238.6	238.4	237.6	236.7	235.9	235.1	235.9	236.7	237.6
127.5°	260.0	260.4	260.6	260.3	259.3	258.2	257.3	256.2	257.3	258.2	259.3
130°	274.3	274.5	274.6	274.1	273.0	271.8	270.6	269.5	270.6	271.8	273.0
132.5°	288.7	288.6	288.6	288.1	287.2	286.2	285.3	284.4	285.3	286.2	287.2
135°	309.1	308.9	308.7	308.2	307.2	306.2	305.2	304.3	305.2	306.2	307.2
137.5°	329.4	329.1	328.9	328.3	327.5	326.7	325.9	325.1	325.9	326.7	327.5
140°	342.5	342.1	341.6	341.0	340.2	339.4	338.6	337.8	338.6	339.4	340.2
142.5°	355.1	354.7	354.5	353.9	353.1	352.3	351.5	350.7	351.5	352.3	353.1
145°	373.4	372.9	372.4	371.8	371.1	370.5	369.9	369.3	369.9	370.5	371.1
147.5°	390.1	389.8	389.4	388.9	388.1	387.4	386.6	385.8	386.6	387.4	388.1
150°	400.5	400.1	399.8	399.3	398.8	398.2	397.7	397.2	397.7	398.2	398.8
152.5°	410.6	410.2	409.8	409.3	408.8	408.2	407.7	407.2	407.7	408.2	408.8
155°	424.1	423.8	423.6	423.3	423.0	422.7	422.4	422.1	422.4	422.7	423.0
157.5°	436.2	436.0	435.9	435.8	435.6	435.4	435.2	435.1	435.2	435.4	435.6
160°	443.8	443.7	443.6	443.5	443.4	443.2	443.0	442.8	443.0	443.2	443.4
162.5°	450.3	450.2	450.1	450.0	450.0	450.0	450.0	449.9	450.0	450.0	450.0
165°	459.0	459.0	459.0	459.0	459.1	459.1	459.2	459.3	459.2	459.1	459.1
167.5°	466.0	466.0	466.0	466.2	466.5	466.7	467.0	467.3	467.0	466.7	466.5
170°	470.0	470.1	470.2	470.4	470.6	470.9	471.2	471.4	471.2	470.9	470.6
172.5°	473.0	473.1	473.1	473.3	473.6	473.9	474.1	474.4	474.1	473.9	473.6
175°	476.3	476.4	476.6	476.9	477.2	477.4	477.7	478.0	477.7	477.4	477.2
177.5°	478.0	478.2	478.3	478.5	478.8	478.9	479.2	479.4	479.2	478.9	478.8
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1754.6	1751.3	1739.8	1733.8	1724.0	1714.7	1708.7	1711.5	1713.6	1712.5	1710.8
5°	1704.3	1691.3	1671.5	1654.4	1642.1	1619.6	1610.0	1605.3	1601.2	1596.3	1591.5
7.5°	1644.4	1624.0	1595.5	1571.2	1548.2	1520.2	1504.2	1494.7	1484.8	1474.0	1464.5
10°	1601.8	1573.1	1543.0	1508.9	1481.6	1456.3	1433.7	1418.6	1405.0	1392.0	1382.4
12.5°	1557.0	1523.9	1486.7	1440.0	1409.9	1373.7	1370.3	1343.8	1322.4	1314.4	1303.1
15°	1485.6	1439.1	1392.0	1336.7	1312.8	1280.0	1259.5	1238.9	1220.5	1207.5	1204.1
17.5°	1404.6	1344.4	1297.5	1257.8	1218.6	1185.0	1166.1	1149.7	1134.5	1117.1	1114.8
20°	1342.8	1290.8	1239.7	1204.8	1164.5	1130.2	1107.1	1090.7	1077.6	1067.4	1058.5
22.5°	1284.3	1227.4	1180.5	1142.5	1102.7	1075.0	1056.8	1040.9	1030.1	1018.8	1010.4
25°	1190.4	1146.0	1094.8	1051.7	1018.9	1001.1	986.1	972.4	965.6	958.1	948.5
27.5°	1108.3	1058.9	1010.9	977.6	948.8	933.1	922.4	913.1	906.7	902.3	896.9
30°	1050.3	1000.4	962.9	930.1	906.2	890.5	883.6	878.2	870.6	867.9	865.1
32.5°	994.5	949.6	917.5	889.0	866.2	856.0	849.7	844.8	838.9	836.2	830.7
35°	915.7	878.2	846.7	831.0	812.5	803.6	798.9	792.0	786.6	783.8	783.1
37.5°	841.5	808.9	788.2	767.9	760.2	754.7	748.1	743.5	741.9	741.5	740.7
40°	793.4	766.7	748.3	731.9	728.4	720.2	714.8	710.7	710.7	711.4	710.7
42.5°	749.7	725.8	709.4	695.3	691.3	686.3	680.9	680.6	681.7	684.0	681.7
45°	683.4	666.3	654.7	647.8	640.3	635.5	634.8	636.9	637.6	638.3	640.3
47.5°	622.4	611.1	600.6	593.0	589.8	588.9	588.1	591.7	594.9	596.2	599.3
50°	586.3	573.4	564.5	559.6	557.0	555.5	557.0	561.1	563.7	567.2	569.3
52.5°	545.9	536.7	530.6	526.9	525.8	526.6	526.9	531.5	535.9	537.2	538.1
55°	490.0	483.1	481.8	475.6	478.3	477.7	481.1	483.8	487.9	492.0	492.7
57.5°	434.2	428.7	425.1	425.6	426.4	429.4	432.3	437.1	441.5	445.9	446.2
60°	397.1	394.3	392.3	392.3	393.6	397.7	401.1	405.9	408.7	411.3	413.4
62.5°	363.1	360.4	358.4	359.4	363.0	365.4	369.4	372.0	374.8	377.5	378.4
65°	309.6	308.2	310.2	311.7	312.3	315.8	320.5	322.5	325.3	326.6	331.4
67.5°	260.2	260.5	260.2	262.2	266.1	266.9	271.4	276.3	276.8	279.4	282.5
70°	226.9	228.3	229.6	231.0	234.4	235.8	239.2	241.2	244.0	246.0	248.1
72.5°	196.3	196.5	197.9	197.6	200.5	203.5	206.3	208.4	211.2	213.7	215.8
75°	151.1	151.1	152.4	153.1	156.5	159.9	159.3	160.6	163.4	166.0	167.5
77.5°	110.3	108.8	110.3	111.0	112.1	114.9	115.5	117.4	120.6	119.6	121.1
80°	84.1	82.0	84.1	84.7	84.7	88.2	88.2	89.5	91.6	89.5	91.6
82.5°	60.0	59.0	60.5	60.7	61.8	61.9	63.0	63.3	65.4	64.4	65.4
85°	30.1	29.4	30.1	29.4	30.1	30.8	30.8	30.1	30.1	31.5	29.4
87.5°	10.3	10.0	9.8	10.3	10.1	9.9	9.4	9.3	9.3	8.1	8.1
90°	4.7	6.2	8.2	10.2	12.1	14.2	14.0	13.8	13.6	13.5	13.4
92.5°	10.3	11.0	11.4	11.9	12.4	12.8	12.8	12.9	12.9	13.0	13.0
95°	24.6	25.1	25.3	25.5	25.7	25.9	25.9	25.9	25.9	25.9	25.8
97.5°	41.6	42.1	42.4	42.8	43.2	43.4	43.4	43.4	43.4	43.4	43.4
100°	54.2	54.7	54.9	55.2	55.5	55.7	55.7	55.7	55.7	55.7	55.7
102.5°	67.1	67.7	67.9	68.3	68.7	69.0	69.1	69.1	69.2	69.3	69.3
105°	87.9	88.2	88.4	88.5	88.7	88.9	89.1	89.3	89.4	89.6	89.7
107.5°	110.6	110.8	110.8	110.8	110.8	110.8	110.8	110.9	111.0	111.1	110.9
110°	125.4	125.6	125.6	125.6	125.6	125.6	125.6	125.6	125.6	125.6	125.5



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	140.9	141.2	141.1	141.0	140.9	140.8	140.6	140.4	140.2	140.0	139.7
115°	163.7	163.9	163.7	163.5	163.4	163.2	163.1	163.0	162.9	162.8	162.6
117.5°	187.3	187.3	186.9	186.4	185.8	185.4	185.1	184.9	184.7	184.5	184.2
120°	202.4	202.4	201.7	201.0	200.3	199.6	199.6	199.6	199.6	199.6	199.5
122.5°	217.0	217.1	216.6	216.1	215.6	215.1	214.9	214.6	214.5	214.2	214.0
125°	238.4	238.6	238.4	238.1	237.8	237.6	237.3	237.0	236.7	236.5	236.3
127.5°	260.3	260.6	260.4	260.0	259.7	259.4	259.0	258.7	258.4	258.1	257.8
130°	274.1	274.6	274.5	274.3	274.1	273.9	273.8	273.6	273.4	273.2	273.0
132.5°	288.1	288.6	288.6	288.7	288.7	288.7	288.4	288.0	287.6	287.2	286.9
135°	308.2	308.7	308.9	309.1	309.2	309.4	309.3	309.2	309.2	309.1	308.9
137.5°	328.3	328.9	329.1	329.4	329.6	329.8	329.8	329.7	329.6	329.6	329.3
140°	341.0	341.6	342.1	342.5	343.0	343.4	343.4	343.4	343.4	343.4	343.2
142.5°	353.9	354.5	354.7	355.1	355.3	355.7	355.8	355.8	355.9	356.0	355.8
145°	371.8	372.4	372.9	373.4	374.0	374.5	374.6	374.7	374.8	374.9	374.7
147.5°	388.9	389.4	389.8	390.1	390.5	390.8	391.0	391.2	391.5	391.6	391.6
150°	399.3	399.8	400.1	400.5	400.8	401.2	401.4	401.7	402.0	402.3	402.3
152.5°	409.3	409.8	410.2	410.6	411.1	411.5	411.9	412.1	412.5	412.9	412.9
155°	423.3	423.6	423.8	424.1	424.4	424.6	425.1	425.5	426.0	426.4	426.5
157.5°	435.8	435.9	436.0	436.2	436.4	436.6	437.2	437.7	438.4	439.0	439.1
160°	443.5	443.6	443.7	443.8	443.9	444.0	444.5	445.1	445.6	446.1	446.2
162.5°	450.0	450.1	450.2	450.3	450.4	450.5	451.0	451.7	452.3	452.9	453.0
165°	459.0	459.0	459.0	459.0	459.0	459.0	459.6	460.2	460.8	461.5	461.5
167.5°	466.2	466.0	466.0	466.0	466.0	466.0	466.6	467.3	467.9	468.5	468.6
170°	470.4	470.2	470.1	470.0	469.9	469.8	470.5	471.1	471.7	472.3	472.4
172.5°	473.3	473.1	473.1	473.0	472.9	472.8	473.4	474.0	474.7	475.3	475.3
175°	476.9	476.6	476.4	476.3	476.1	475.9	476.5	477.2	477.8	478.4	478.5
177.5°	478.5	478.3	478.2	478.0	477.9	477.8	478.2	478.7	479.0	479.5	479.5
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1705.4	1704.3	1704.3	1699.4	1704.3	1704.3	1705.4	1710.8	1712.5	1713.6	1711.5
5°	1582.0	1579.9	1576.5	1579.9	1576.5	1579.9	1582.0	1591.5	1596.3	1601.2	1605.3
7.5°	1459.9	1451.7	1450.5	1442.4	1450.5	1451.7	1459.9	1464.5	1474.0	1484.8	1494.7
10°	1370.8	1365.4	1364.7	1351.7	1364.7	1365.4	1370.8	1382.4	1392.0	1405.0	1418.6
12.5°	1303.1	1289.9	1292.5	1285.0	1292.5	1289.9	1303.1	1303.1	1314.4	1322.4	1343.8
15°	1185.6	1185.6	1182.9	1171.3	1182.9	1185.6	1185.6	1204.1	1207.5	1220.5	1238.9
17.5°	1101.4	1099.9	1093.4	1096.6	1093.4	1099.9	1101.4	1114.8	1117.1	1134.5	1149.7
20°	1051.0	1047.0	1038.8	1038.8	1038.8	1047.0	1051.0	1058.5	1067.4	1077.6	1090.7
22.5°	1003.4	1003.2	994.4	997.2	994.4	1003.2	1003.4	1010.4	1018.8	1030.1	1040.9
25°	947.8	942.4	938.3	940.3	938.3	942.4	947.8	948.5	958.1	965.6	972.4
27.5°	895.1	892.1	891.8	886.2	891.8	892.1	895.1	896.9	902.3	906.7	913.1
30°	864.4	857.6	859.0	855.6	859.0	857.6	864.4	865.1	867.9	870.6	878.2
32.5°	829.5	827.0	825.6	822.8	825.6	827.0	829.5	830.7	836.2	838.9	844.8
35°	781.8	782.5	779.0	780.4	779.0	782.5	781.8	783.1	783.8	786.6	792.0
37.5°	740.1	742.3	740.7	741.0	740.7	742.3	740.1	740.7	741.5	741.9	743.5
40°	712.7	712.7	712.7	714.8	712.7	712.7	712.7	710.7	711.4	710.7	710.7
42.5°	686.5	685.5	684.3	684.2	684.3	685.5	686.5	681.7	684.0	681.7	680.6
45°	641.7	643.7	644.4	641.0	644.4	643.7	641.7	640.3	638.3	637.6	636.9
47.5°	601.1	601.4	601.1	604.1	601.1	601.4	601.1	599.3	596.2	594.9	591.7
50°	572.7	571.3	572.7	571.3	572.7	571.3	572.7	569.3	567.2	563.7	561.1
52.5°	542.6	542.9	542.1	541.8	542.1	542.9	542.6	538.1	537.2	535.9	531.5
55°	495.4	496.8	496.1	496.1	496.1	496.8	495.4	492.7	492.0	487.9	483.8
57.5°	446.7	447.9	448.8	445.9	448.8	447.9	446.7	446.2	445.9	441.5	437.1
60°	412.8	416.2	415.4	414.1	415.4	416.2	412.8	413.4	411.3	408.7	405.9
62.5°	381.6	382.8	382.7	382.5	382.7	382.8	381.6	378.4	377.5	374.8	372.0
65°	333.5	334.8	332.8	334.8	332.8	334.8	333.5	331.4	326.6	325.3	322.5
67.5°	281.7	282.1	283.6	284.5	283.6	282.1	281.7	282.5	279.4	276.8	276.3
70°	249.4	248.8	250.8	252.9	250.8	248.8	249.4	248.1	246.0	244.0	241.2
72.5°	215.5	217.0	216.3	217.8	216.3	217.0	215.5	215.8	213.7	211.2	208.4
75°	166.0	168.1	167.5	169.5	167.5	168.1	166.0	167.5	166.0	163.4	160.6
77.5°	120.0	120.3	120.0	121.1	120.0	120.3	120.0	121.1	119.6	120.6	117.4
80°	91.6	90.2	88.8	91.6	88.8	90.2	91.6	91.6	89.5	91.6	89.5
82.5°	63.7	64.5	63.1	63.1	63.1	64.5	63.7	65.4	64.4	65.4	63.3
85°	29.4	28.7	27.4	27.4	27.4	28.7	29.4	29.4	31.5	30.1	30.1
87.5°	8.2	7.7	7.7	7.1	7.7	7.7	8.2	8.1	8.1	9.3	9.3
90°	13.5	13.6	13.6	13.7	13.6	13.6	13.5	13.4	13.5	13.6	13.8
92.5°	13.0	13.0	13.1	13.1	13.1	13.0	13.0	13.0	13.0	12.9	12.9
95°	25.6	25.4	25.2	25.1	25.2	25.4	25.6	25.8	25.9	25.9	25.9
97.5°	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
100°	55.6	55.6	55.5	55.4	55.5	55.6	55.6	55.7	55.7	55.7	55.7
102.5°	69.2	69.1	69.0	68.9	69.0	69.1	69.2	69.3	69.3	69.2	69.1
105°	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.6	89.4	89.3
107.5°	110.5	110.0	109.7	109.2	109.7	110.0	110.5	110.9	111.1	111.0	110.9
110°	125.2	124.9	124.7	124.4	124.7	124.9	125.2	125.5	125.6	125.6	125.6



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	139.6	139.4	139.2	139.0	139.2	139.4	139.6	139.7	140.0	140.2	140.4
115°	162.4	162.1	161.8	161.6	161.8	162.1	162.4	162.6	162.8	162.9	163.0
117.5°	184.0	183.7	183.4	183.2	183.4	183.7	184.0	184.2	184.5	184.7	184.9
120°	199.2	198.9	198.7	198.4	198.7	198.9	199.2	199.5	199.6	199.6	199.6
122.5°	213.8	213.7	213.4	213.2	213.4	213.7	213.8	214.0	214.2	214.5	214.6
125°	236.2	236.1	236.0	235.9	236.0	236.1	236.2	236.3	236.5	236.7	237.0
127.5°	257.4	257.2	256.9	256.6	256.9	257.2	257.4	257.8	258.1	258.4	258.7
130°	272.6	272.2	271.9	271.5	271.9	272.2	272.6	273.0	273.2	273.4	273.6
132.5°	286.6	286.2	286.0	285.7	286.0	286.2	286.6	286.9	287.2	287.6	288.0
135°	308.6	308.4	308.1	307.8	308.1	308.4	308.6	308.9	309.1	309.2	309.2
137.5°	329.0	328.6	328.2	327.9	328.2	328.6	329.0	329.3	329.6	329.6	329.7
140°	342.9	342.5	342.1	341.8	342.1	342.5	342.9	343.2	343.4	343.4	343.4
142.5°	355.4	355.1	354.7	354.4	354.7	355.1	355.4	355.8	356.0	355.9	355.8
145°	374.3	374.0	373.6	373.3	373.6	374.0	374.3	374.7	374.9	374.8	374.7
147.5°	391.2	390.8	390.5	390.2	390.5	390.8	391.2	391.6	391.6	391.5	391.2
150°	402.0	401.7	401.4	401.2	401.4	401.7	402.0	402.3	402.3	402.0	401.7
152.5°	412.5	412.1	411.9	411.5	411.9	412.1	412.5	412.9	412.9	412.5	412.1
155°	426.2	426.0	425.7	425.4	425.7	426.0	426.2	426.5	426.4	426.0	425.5
157.5°	438.6	438.2	437.8	437.4	437.8	438.2	438.6	439.1	439.0	438.4	437.7
160°	445.9	445.5	445.1	444.8	445.1	445.5	445.9	446.2	446.1	445.6	445.1
162.5°	452.5	452.1	451.7	451.3	451.7	452.1	452.5	453.0	452.9	452.3	451.7
165°	461.1	460.7	460.2	459.8	460.2	460.7	461.1	461.5	461.5	460.8	460.2
167.5°	468.1	467.6	467.2	466.7	467.2	467.6	468.1	468.6	468.5	467.9	467.3
170°	471.9	471.4	470.8	470.3	470.8	471.4	471.9	472.4	472.3	471.7	471.1
172.5°	474.7	474.2	473.7	473.1	473.7	474.2	474.7	475.3	475.3	474.7	474.0
175°	478.0	477.4	476.9	476.4	476.9	477.4	478.0	478.5	478.4	477.8	477.2
177.5°	479.0	478.7	478.2	477.8	478.2	478.7	479.0	479.5	479.5	479.0	478.7
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1708.7	1714.7	1724.0	1733.8	1739.8	1751.3	1754.6	1760.1	1765.0	1776.5	1788.5
5°	1610.0	1619.6	1642.1	1654.4	1671.5	1691.3	1704.3	1718.0	1733.0	1759.0	1782.9
7.5°	1504.2	1520.2	1548.2	1571.2	1595.5	1624.0	1644.4	1671.5	1693.9	1730.5	1765.5
10°	1433.7	1456.3	1481.6	1508.9	1543.0	1573.1	1601.8	1635.9	1663.3	1707.0	1748.0
12.5°	1370.3	1373.7	1409.9	1440.0	1486.7	1523.9	1557.0	1601.0	1627.7	1679.7	1722.9
15°	1259.5	1280.0	1312.8	1336.7	1392.0	1439.1	1485.6	1531.4	1562.2	1626.4	1683.1
17.5°	1166.1	1185.0	1218.6	1257.8	1297.5	1344.4	1404.6	1452.9	1494.7	1568.1	1635.1
20°	1107.1	1130.2	1164.5	1204.8	1239.7	1290.8	1342.8	1398.2	1443.2	1526.0	1604.5
22.5°	1056.8	1075.0	1102.7	1142.5	1180.5	1227.4	1284.3	1344.6	1391.9	1481.1	1560.8
25°	986.1	1001.1	1018.9	1051.7	1094.8	1146.0	1190.4	1256.7	1325.7	1409.1	1505.5
27.5°	922.4	933.1	948.8	977.6	1010.9	1058.9	1108.3	1171.2	1240.5	1331.1	1432.7
30°	883.6	890.5	906.2	930.1	962.9	1000.4	1050.3	1110.4	1181.5	1273.1	1374.2
32.5°	849.7	856.0	866.2	889.0	917.5	949.6	994.5	1054.7	1122.5	1212.5	1324.5
35°	798.9	803.6	812.5	831.0	846.7	878.2	915.7	970.4	1033.9	1120.1	1236.2
37.5°	748.1	754.7	760.2	767.9	788.2	808.9	841.5	887.7	950.0	1037.0	1147.6
40°	714.8	720.2	728.4	731.9	748.3	766.7	793.4	835.7	898.7	977.9	1085.8
42.5°	680.9	686.3	691.3	695.3	709.4	725.8	749.7	786.0	841.8	918.8	1025.7
45°	634.8	635.5	640.3	647.8	654.7	666.3	683.4	714.8	757.9	830.3	927.3
47.5°	588.1	588.9	589.8	593.0	600.6	611.1	622.4	648.0	686.5	744.3	838.7
50°	557.0	555.5	557.0	559.6	564.5	573.4	586.3	604.8	636.2	690.2	776.9
52.5°	526.9	526.6	525.8	526.9	530.6	536.7	545.9	561.6	589.8	639.4	715.8
55°	481.1	477.7	478.3	475.6	481.8	483.1	490.0	502.9	527.5	561.7	633.5
57.5°	432.3	429.4	426.4	425.6	425.1	428.7	434.2	444.4	463.3	493.3	551.4
60°	401.1	397.7	393.6	392.3	392.3	394.3	397.1	404.6	422.3	449.0	496.8
62.5°	369.4	365.4	363.0	359.4	358.4	360.4	363.1	368.5	381.3	406.4	447.6
65°	320.5	315.8	312.3	311.7	310.2	308.2	309.6	315.0	325.3	345.1	377.9
67.5°	271.4	266.9	266.1	262.2	260.2	260.5	260.2	264.8	271.0	288.1	312.5
70°	239.2	235.8	234.4	231.0	229.6	228.3	226.9	231.0	237.1	251.5	272.7
72.5°	206.3	203.5	200.5	197.6	197.9	196.5	196.3	198.8	203.8	217.0	233.3
75°	159.3	159.9	156.5	153.1	152.4	151.1	151.1	153.1	155.2	165.4	178.3
77.5°	115.5	114.9	112.1	111.0	110.3	108.8	110.3	111.6	112.7	119.6	129.1
80°	88.2	88.2	84.7	84.7	84.1	82.0	84.1	82.7	85.4	92.3	99.1
82.5°	63.0	61.9	61.8	60.7	60.5	59.0	60.0	61.3	62.4	67.1	71.2
85°	30.8	30.8	30.1	29.4	30.1	29.4	30.1	30.8	31.5	33.5	36.9
87.5°	9.4	9.9	10.1	10.3	9.8	10.0	10.3	10.6	11.4	11.8	12.1
90°	14.0	14.2	12.1	10.2	8.2	6.2	4.7	3.7	2.6	1.5	0.4
92.5°	12.8	12.8	12.4	11.9	11.4	11.0	10.3	9.5	8.7	8.0	7.2
95°	25.9	25.9	25.7	25.5	25.3	25.1	24.6	23.7	22.8	21.9	21.0
97.5°	43.4	43.4	43.2	42.8	42.4	42.1	41.6	40.8	39.9	39.1	38.3
100°	55.7	55.7	55.5	55.2	54.9	54.7	54.2	53.5	52.7	52.0	51.3
102.5°	69.1	69.0	68.7	68.3	67.9	67.7	67.1	66.6	66.0	65.5	64.9
105°	89.1	88.9	88.7	88.5	88.4	88.2	87.9	87.7	87.4	87.1	86.9
107.5°	110.8	110.8	110.8	110.8	110.8	110.8	110.6	110.2	109.8	109.4	109.0
110°	125.6	125.6	125.6	125.6	125.6	125.6	125.4	124.8	124.3	123.8	123.2



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	140.6	140.8	140.9	141.0	141.1	141.2	140.9	140.4	139.8	139.3	138.8
115°	163.1	163.2	163.4	163.5	163.7	163.9	163.7	163.2	162.6	162.1	161.6
117.5°	185.1	185.4	185.8	186.4	186.9	187.3	187.3	186.5	185.8	185.1	184.4
120°	199.6	199.6	200.3	201.0	201.7	202.4	202.4	201.7	201.0	200.3	199.6
122.5°	214.9	215.1	215.6	216.1	216.6	217.1	217.0	216.1	215.2	214.4	213.5
125°	237.3	237.6	237.8	238.1	238.4	238.6	238.4	237.6	236.7	235.9	235.1
127.5°	259.0	259.4	259.7	260.0	260.4	260.6	260.3	259.3	258.2	257.3	256.2
130°	273.8	273.9	274.1	274.3	274.5	274.6	274.1	273.0	271.8	270.6	269.5
132.5°	288.4	288.7	288.7	288.7	288.6	288.6	288.1	287.2	286.2	285.3	284.4
135°	309.3	309.4	309.2	309.1	308.9	308.7	308.2	307.2	306.2	305.2	304.3
137.5°	329.8	329.8	329.6	329.4	329.1	328.9	328.3	327.5	326.7	325.9	325.1
140°	343.4	343.4	343.0	342.5	342.1	341.6	341.0	340.2	339.4	338.6	337.8
142.5°	355.8	355.7	355.3	355.1	354.7	354.5	353.9	353.1	352.3	351.5	350.7
145°	374.6	374.5	374.0	373.4	372.9	372.4	371.8	371.1	370.5	369.9	369.3
147.5°	391.0	390.8	390.5	390.1	389.8	389.4	388.9	388.1	387.4	386.6	385.8
150°	401.4	401.2	400.8	400.5	400.1	399.8	399.3	398.8	398.2	397.7	397.2
152.5°	411.9	411.5	411.1	410.6	410.2	409.8	409.3	408.8	408.2	407.7	407.2
155°	425.1	424.6	424.4	424.1	423.8	423.6	423.3	423.0	422.7	422.4	422.1
157.5°	437.2	436.6	436.4	436.2	436.0	435.9	435.8	435.6	435.4	435.2	435.1
160°	444.5	444.0	443.9	443.8	443.7	443.6	443.5	443.4	443.2	443.0	442.8
162.5°	451.0	450.5	450.4	450.3	450.2	450.1	450.0	450.0	450.0	450.0	449.9
165°	459.6	459.0	459.0	459.0	459.0	459.0	459.0	459.1	459.1	459.2	459.3
167.5°	466.6	466.0	466.0	466.0	466.0	466.0	466.2	466.5	466.7	467.0	467.3
170°	470.5	469.8	469.9	470.0	470.1	470.2	470.4	470.6	470.9	471.2	471.4
172.5°	473.4	472.8	472.9	473.0	473.1	473.1	473.3	473.6	473.9	474.1	474.4
175°	476.5	475.9	476.1	476.3	476.4	476.6	476.9	477.2	477.4	477.7	478.0
177.5°	478.2	477.8	477.9	478.0	478.2	478.3	478.5	478.8	478.9	479.2	479.4
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1787.4	1790.1	1798.8	1807.7	1817.5	1820.2	1824.6	1820.8	1819.6	1830.1	1837.7
5°	1792.4	1804.7	1828.7	1850.6	1869.0	1882.0	1895.7	1901.1	1911.4	1925.7	1943.5
7.5°	1786.7	1810.6	1848.2	1880.1	1914.8	1939.8	1959.4	1976.0	1996.3	2023.5	2053.1
10°	1780.1	1812.3	1858.1	1897.0	1939.4	1971.5	1998.1	2024.1	2054.2	2091.8	2130.7
12.5°	1768.2	1806.2	1863.5	1909.6	1964.0	1995.6	2031.5	2087.6	2119.8	2172.1	2227.0
15°	1743.9	1786.3	1866.3	1923.0	1984.5	2044.6	2110.9	2164.2	2217.5	2248.3	2325.5
17.5°	1708.0	1770.2	1858.8	1924.9	2003.0	2097.7	2172.3	2232.7	2294.2	2344.0	2382.7
20°	1679.0	1746.7	1847.8	1927.1	2020.0	2121.8	2207.3	2268.8	2322.1	2363.7	2387.6
22.5°	1642.4	1727.5	1826.0	1918.9	2037.6	2138.2	2228.0	2276.4	2320.9	2341.4	2350.5
25°	1584.7	1687.2	1798.6	1912.1	2046.0	2152.6	2234.6	2264.0	2277.0	2257.2	2224.4
27.5°	1522.5	1636.8	1767.0	1899.2	2040.8	2143.3	2202.1	2197.4	2175.4	2111.3	2060.0
30°	1476.0	1601.8	1741.9	1886.1	2028.2	2128.0	2162.1	2128.0	2078.1	2006.3	1933.2
32.5°	1427.5	1557.6	1715.1	1867.5	2005.3	2093.0	2100.4	2041.7	1964.4	1882.8	1791.6
35°	1353.7	1494.5	1664.6	1826.0	1956.5	2011.8	1979.1	1875.2	1783.6	1672.2	1547.8
37.5°	1270.5	1425.9	1596.6	1765.1	1883.4	1897.8	1816.4	1707.0	1577.9	1447.0	1300.6
40°	1208.2	1372.9	1548.5	1718.7	1823.2	1808.2	1704.3	1584.0	1430.3	1270.3	1134.3
42.5°	1152.4	1317.1	1496.0	1662.9	1746.7	1705.4	1584.0	1436.5	1271.2	1120.6	996.0
45°	1055.8	1225.3	1408.5	1569.7	1617.6	1543.0	1382.4	1218.4	1055.8	930.1	831.7
47.5°	962.1	1129.6	1311.0	1452.7	1469.6	1369.5	1194.0	1025.2	885.4	783.0	713.5
50°	893.1	1061.2	1241.0	1367.4	1361.9	1241.0	1060.6	900.0	783.1	700.4	654.0
52.5°	831.3	990.2	1162.8	1277.7	1248.8	1116.9	944.7	802.1	706.1	641.4	599.3
55°	735.3	882.3	1046.2	1138.4	1085.2	939.0	793.4	678.6	607.5	559.0	526.2
57.5°	639.9	777.7	918.0	974.9	916.0	781.0	659.6	576.3	522.9	487.0	465.7
60°	580.9	701.2	826.2	875.4	805.0	684.7	589.1	514.6	471.5	442.1	423.0
62.5°	521.8	629.5	747.4	774.3	709.9	608.2	523.4	461.5	426.1	400.0	382.0
65°	441.5	529.6	619.1	636.9	577.5	498.8	431.9	391.6	360.2	341.0	326.6
67.5°	362.0	432.8	496.2	510.6	458.5	404.0	355.6	320.5	299.2	283.3	271.2
70°	315.0	371.0	423.0	434.6	393.0	344.4	307.6	279.5	260.4	246.7	235.1
72.5°	265.3	312.0	355.2	363.0	329.0	291.9	261.6	239.6	222.7	213.9	202.9
75°	203.0	230.3	263.8	265.8	243.3	220.7	197.5	183.2	174.2	163.4	157.8
77.5°	143.2	164.7	183.8	187.5	174.2	158.8	145.8	134.5	127.0	121.9	116.8
80°	109.3	126.4	134.6	139.4	129.8	118.9	111.4	103.9	99.1	95.7	92.3
82.5°	78.2	88.7	96.4	100.0	94.9	88.3	80.8	76.5	72.9	70.0	68.8
85°	39.6	44.4	49.2	50.6	49.2	46.5	42.4	42.4	40.3	39.6	39.6
87.5°	14.0	16.4	16.6	18.5	17.7	18.0	18.5	18.3	18.1	17.6	16.9
90°	1.5	2.6	3.7	4.7	6.2	8.2	10.2	12.1	14.2	14.0	13.8
92.5°	8.0	8.7	9.5	10.3	11.0	11.4	11.9	12.4	12.8	12.8	12.9
95°	21.9	22.8	23.7	24.6	25.1	25.3	25.5	25.7	25.9	25.9	25.9
97.5°	39.1	39.9	40.8	41.6	42.1	42.4	42.8	43.2	43.4	43.4	43.4
100°	52.0	52.7	53.5	54.2	54.7	54.9	55.2	55.5	55.7	55.7	55.7
102.5°	65.5	66.0	66.6	67.1	67.7	67.9	68.3	68.7	69.0	69.1	69.1
105°	87.1	87.4	87.7	87.9	88.2	88.4	88.5	88.7	88.9	89.1	89.3
107.5°	109.4	109.8	110.2	110.6	110.8	110.8	110.8	110.8	110.8	110.8	110.9
110°	123.8	124.3	124.8	125.4	125.6	125.6	125.6	125.6	125.6	125.6	125.6





TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	139.3	139.8	140.4	140.9	141.2	141.1	141.0	140.9	140.8	140.6	140.4
115°	162.1	162.6	163.2	163.7	163.9	163.7	163.5	163.4	163.2	163.1	163.0
117.5°	185.1	185.8	186.5	187.3	187.3	186.9	186.4	185.8	185.4	185.1	184.9
120°	200.3	201.0	201.7	202.4	202.4	201.7	201.0	200.3	199.6	199.6	199.6
122.5°	214.4	215.2	216.1	217.0	217.1	216.6	216.1	215.6	215.1	214.9	214.6
125°	235.9	236.7	237.6	238.4	238.6	238.4	238.1	237.8	237.6	237.3	237.0
127.5°	257.3	258.2	259.3	260.3	260.6	260.4	260.0	259.7	259.4	259.0	258.7
130°	270.6	271.8	273.0	274.1	274.6	274.5	274.3	274.1	273.9	273.8	273.6
132.5°	285.3	286.2	287.2	288.1	288.6	288.6	288.7	288.7	288.7	288.4	288.0
135°	305.2	306.2	307.2	308.2	308.7	308.9	309.1	309.2	309.4	309.3	309.2
137.5°	325.9	326.7	327.5	328.3	328.9	329.1	329.4	329.6	329.8	329.8	329.7
140°	338.6	339.4	340.2	341.0	341.6	342.1	342.5	343.0	343.4	343.4	343.4
142.5°	351.5	352.3	353.1	353.9	354.5	354.7	355.1	355.3	355.7	355.8	355.8
145°	369.9	370.5	371.1	371.8	372.4	372.9	373.4	374.0	374.5	374.6	374.7
147.5°	386.6	387.4	388.1	388.9	389.4	389.8	390.1	390.5	390.8	391.0	391.2
150°	397.7	398.2	398.8	399.3	399.8	400.1	400.5	400.8	401.2	401.4	401.7
152.5°	407.7	408.2	408.8	409.3	409.8	410.2	410.6	411.1	411.5	411.9	412.1
155°	422.4	422.7	423.0	423.3	423.6	423.8	424.1	424.4	424.6	425.1	425.5
157.5°	435.2	435.4	435.6	435.8	435.9	436.0	436.2	436.4	436.6	437.2	437.7
160°	443.0	443.2	443.4	443.5	443.6	443.7	443.8	443.9	444.0	444.5	445.1
162.5°	450.0	450.0	450.0	450.0	450.1	450.2	450.3	450.4	450.5	451.0	451.7
165°	459.2	459.1	459.1	459.0	459.0	459.0	459.0	459.0	459.0	459.6	460.2
167.5°	467.0	466.7	466.5	466.2	466.0	466.0	466.0	466.0	466.0	466.6	467.3
170°	471.2	470.9	470.6	470.4	470.2	470.1	470.0	469.9	469.8	470.5	471.1
172.5°	474.1	473.9	473.6	473.3	473.1	473.1	473.0	472.9	472.8	473.4	474.0
175°	477.7	477.4	477.2	476.9	476.6	476.4	476.3	476.1	475.9	476.5	477.2
177.5°	479.2	478.9	478.8	478.5	478.3	478.2	478.0	477.9	477.8	478.2	478.7
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8	478.8



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1	1778.1
2.5°	1844.2	1851.9	1851.9	1853.0	1861.7	1860.6	1860.1
5°	1962.7	1974.2	1975.6	1987.9	1996.1	1993.3	1985.8
7.5°	2074.3	2095.9	2112.3	2121.5	2132.3	2138.9	2135.9
10°	2162.8	2194.3	2213.4	2226.4	2242.1	2253.7	2249.6
12.5°	2243.2	2280.6	2306.9	2329.1	2331.2	2346.1	2336.0
15°	2368.6	2408.2	2412.3	2428.7	2441.7	2440.3	2441.0
17.5°	2409.9	2422.7	2425.3	2425.6	2425.8	2421.0	2410.7
20°	2395.2	2390.4	2378.8	2369.9	2354.2	2352.2	2338.5
22.5°	2325.2	2310.1	2280.9	2261.6	2237.2	2230.8	2227.0
25°	2187.5	2153.9	2107.5	2063.1	2050.8	2026.9	2033.7
27.5°	1998.4	1946.2	1896.0	1859.8	1827.2	1791.4	1801.6
30°	1865.5	1806.8	1735.7	1681.1	1646.2	1612.0	1605.9
32.5°	1707.0	1621.0	1541.7	1493.5	1440.1	1418.5	1394.9
35°	1433.7	1349.6	1271.0	1203.4	1164.5	1134.3	1107.1
37.5°	1187.8	1091.1	1027.6	972.9	944.7	927.5	931.8
40°	1035.3	950.6	904.1	862.4	836.4	824.1	826.9
42.5°	911.8	848.3	810.0	781.5	763.2	756.3	754.7
45°	771.5	736.0	704.5	688.1	679.3	671.7	667.0
47.5°	675.8	646.8	629.1	619.4	611.6	604.0	603.8
50°	618.4	599.3	587.0	576.8	570.6	565.2	569.9
52.5°	574.7	557.2	544.9	535.7	533.4	528.5	528.3
55°	509.8	496.1	487.2	479.0	474.9	472.2	468.8
57.5°	450.8	437.7	429.5	424.4	416.6	413.8	412.8
60°	408.7	398.4	390.2	383.3	380.0	374.5	374.5
62.5°	369.8	359.6	352.0	346.7	341.2	338.9	339.5
65°	313.7	305.5	297.9	292.5	291.1	287.0	288.4
67.5°	262.0	256.5	248.6	245.6	243.0	240.9	239.2
70°	227.6	222.1	218.0	213.9	211.9	211.9	211.9
72.5°	198.6	192.0	189.6	184.4	185.6	183.4	181.2
75°	153.7	149.6	147.6	145.5	142.1	142.1	142.1
77.5°	113.2	111.9	109.5	107.3	106.5	105.8	106.0
80°	87.5	86.8	85.4	85.4	84.1	83.4	82.0
82.5°	67.2	65.5	64.6	64.1	63.8	63.7	63.4
85°	38.3	36.9	36.9	37.5	36.2	36.2	36.9
87.5°	17.5	17.5	16.9	16.9	17.5	16.9	16.9
90°	13.6	13.5	13.4	13.5	13.6	13.6	13.7
92.5°	12.9	13.0	13.0	13.0	13.0	13.1	13.1
95°	25.9	25.9	25.8	25.6	25.4	25.2	25.1
97.5°	43.4	43.4	43.4	43.4	43.4	43.4	43.4
100°	55.7	55.7	55.7	55.6	55.6	55.5	55.4
102.5°	69.2	69.3	69.3	69.2	69.1	69.0	68.9
105°	89.4	89.6	89.7	89.7	89.7	89.7	89.7
107.5°	111.0	111.1	110.9	110.5	110.0	109.7	109.2
110°	125.6	125.6	125.5	125.2	124.9	124.7	124.4



TEST NUMBER: P331586-940

CATALOG NUMBER: S122DIW-S1005D435U940-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	140.2	140.0	139.7	139.6	139.4	139.2	139.0
115°	162.9	162.8	162.6	162.4	162.1	161.8	161.6
117.5°	184.7	184.5	184.2	184.0	183.7	183.4	183.2
120°	199.6	199.6	199.5	199.2	198.9	198.7	198.4
122.5°	214.5	214.2	214.0	213.8	213.7	213.4	213.2
125°	236.7	236.5	236.3	236.2	236.1	236.0	235.9
127.5°	258.4	258.1	257.8	257.4	257.2	256.9	256.6
130°	273.4	273.2	273.0	272.6	272.2	271.9	271.5
132.5°	287.6	287.2	286.9	286.6	286.2	286.0	285.7
135°	309.2	309.1	308.9	308.6	308.4	308.1	307.8
137.5°	329.6	329.6	329.3	329.0	328.6	328.2	327.9
140°	343.4	343.4	343.2	342.9	342.5	342.1	341.8
142.5°	355.9	356.0	355.8	355.4	355.1	354.7	354.4
145°	374.8	374.9	374.7	374.3	374.0	373.6	373.3
147.5°	391.5	391.6	391.6	391.2	390.8	390.5	390.2
150°	402.0	402.3	402.3	402.0	401.7	401.4	401.2
152.5°	412.5	412.9	412.9	412.5	412.1	411.9	411.5
155°	426.0	426.4	426.5	426.2	426.0	425.7	425.4
157.5°	438.4	439.0	439.1	438.6	438.2	437.8	437.4
160°	445.6	446.1	446.2	445.9	445.5	445.1	444.8
162.5°	452.3	452.9	453.0	452.5	452.1	451.7	451.3
165°	460.8	461.5	461.5	461.1	460.7	460.2	459.8
167.5°	467.9	468.5	468.6	468.1	467.6	467.2	466.7
170°	471.7	472.3	472.4	471.9	471.4	470.8	470.3
172.5°	474.7	475.3	475.3	474.7	474.2	473.7	473.1
175°	477.8	478.4	478.5	478.0	477.4	476.9	476.4
177.5°	479.0	479.5	479.5	479.0	478.7	478.2	477.8
180°	478.8	478.8	478.8	478.8	478.8	478.8	478.8

(END OF REPORT)